

FCC BT LE REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-
do, 16677, Rep. of Korea

Date of Issue:
December 04, 2018

Test Site/Location:
HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-
myeo,Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-1811-FC032-R1

FCC ID: A3LSMA920N


APPLICANT: SAMSUNG Electronics Co., Ltd.

Model: SM-A920N
EUT Type: Smart Phone
Peak Output Power: 2.172 dBm (1.649 mW)
Frequency Range: 2402 MHz -2480 MHz
Modulation type: GFSK
FCC Classification: Digital Transmission System(DTS)
FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by : Kwon Jeong
Engineer of Telecommunication testing center



Approved by : Jong Seok Lee
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1811-FC032	November 27, 2018	- First Approval Report
HCT-RF-1811-FC032-R1	December 04, 2018	- Revised the limit of conducted spurious emission

Table of Contents

1. EUT DESCRIPTION	4
2. TEST METHODOLOGY	5
EUT CONFIGURATION	5
EUT EXERCISE	5
GENERAL TEST PROCEDURES	5
DESCRIPTION OF TEST MODES	5
3. INSTRUMENT CALIBRATION.....	6
4. FACILITIES AND ACCREDITATIONS	6
FACILITIES	6
EQUIPMENT	6
5. ANTENNA REQUIREMENTS	6
6. MEASUREMENT UNCERTAINTY	7
7. DESCRIPTION OF TESTS	8
8. SUMMARY TEST OF RESULTS	23
9. TEST RESULT	24
9.1 DUTY CYCLE.....	24
9.2 6dB BANDWIDTH.....	28
9.3 OUTPUT POWER	33
9.4 POWER SPECTRAL DENSITY	41
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	46
9.6 RADIATED SPURIOUS EMISSIONS	63
9.7 RADIATED RESTRICTED BAND EDGES	70
9.8 POWERLINE CONDUCTED EMISSIONS	74
10. LIST OF TEST EQUIPMENT	78
11. ANNEX A_ TEST SETUP PHOTO	80

1. EUT DESCRIPTION

Model	SM-A920N	
EUT Type	Smart Phone	
Power Supply	DC 3.85 V	
Battery Information	Model: EB-BA920ABU Type: Li-ion battery	
Travel Adapter Information	Model: EP-TA20KWK Manufacture: SOLUM	
Frequency Range	2402 MHz - 2480 MHz	
Max. RF Output Power	Peak	250k Bit/s : 2.084 dBm (1.616 mW) 1M Bit/s : 2.151 dBm (1.641 mW) 2M Bit/s : 2.172 dBm (1.649 mW)
	Average	250k Bit/s : 1.93 dBm (1.560 mW) 1M Bit/s : 1.96 dBm (1.569 mW) 2M Bit/s : 2.17 dBm (1.648 mW)
Modulation Type	GFSK	
Bluetooth Version	5.0	
Number of Channels	40 Channels	
Antenna Specification	Antenna type: FPCB Peak Gain : -7.11 dBi	
Date(s) of Tests	November 06, 2018 ~ November 26, 2018	

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05 dated August 24, 2018 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013)

Conducted Antenna Terminal

See Section from 8.3.(KDB 558074 v05)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

* The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v05.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

7.2. 6dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.2 in KDB 558074 v05, Procedure 11.8.1 in ANSI 63.10-2013)


- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

This EUT TX condition is actual operating mode by BT LE mode test program.

The Spectrum Analyzer is set to

- Peak Power (Procedure 8.3.1.1 in KDB 558074 v05, Procedure 11.9.1.1 in ANSI 63.10-2013)
 - 1) RBW \geq DTS Bandwidth
 - 2) VBW \geq 3 x RBW
 - 3) SPAN \geq 3 x RBW
 - 4) Detector Mode = Peak
 - 5) Sweep = auto couple
 - 6) race Mode = max hold
 - 7) Allow trace to fully stabilize.
 - 8) Use peak marker function to determine the peak amplitude level

- Average Power (Procedure 8.3.2.2 in KDB 558074 v05, Procedure 11.9.2.2 in ANSI 63.10-2013)
 - 1) We use the spectrum analyzer's integrated band power measurement function.
 - 2) Measure the duty cycle
 - 3) Set span to at least 1.5 times the OBW
 - 4) RBW = 1-5 % of the OBW, not to exceed 1 MHz.
 - 5) VBW $\geq 3 \times$ RBW.
 - 6) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
 - 7) Sweep time = auto.
 - 8) Detector = RMS(i.e., power averaging)
 - 9) Do not use sweep triggering. Allow the sweep to "free run".
 - 10) Trace average at least 100 traces in power averaging(RMS) mode.
 - 11) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.
 - 12) Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05, Procedure 11.10.2 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Span = 1.5 times the DTS channel bandwidth.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = peak
- 7) Trace Mode = max hold
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 20 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 8.5 in KDB 558074 v05, Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points $\geq 2 \times$ Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	11.30
100	9.83
200	10.19
300	10.13
400	10.23
500	10.25
600	10.32
700	10.35
800	10.35
900	10.34
1000	10.39
2000	10.64
2400*	10.65
2500*	10.67
3000	10.68
4000	10.89
5000	11.07
6000	11.06
7000	11.35
8000	11.32
9000	11.48
10000	11.56
11000	11.56
12000	11.68
13000	11.83
14000	11.90
15000	11.98
16000	12.04
17000	12.02
18000	12.08
19000	12.07
20000	12.14
21000	12.17
22000	12.31
23000	12.60
24000	12.34
25000	12.53
26000	12.02

Note : 1. '*' is fundamental frequency range.
 2. Factor = Attenuator loss + Cable loss


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \cdot \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05, Procedure 11.12 in ANSI 63.10-2013)

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW \geq 3*RBW

(2) Measurement Type(Average):

- Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$
- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW \geq 3*RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

+ Duty Cycle Factor

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \cdot \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \cdot$ RBW

(2) Measurement Type(Average):

- Duty cycle < 98%, duty cycle variations are less than $\pm 2\%$
- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \cdot$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) + Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + external accessories(earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : X
 - Radiated Restricted Band Edge : Z
3. All packet length of operation were investigated and the test results are worst case in Highest packet length.
 - *Worst case :
 - LE 5.0(1M Bit/s) : 255 Byte
 - LE 5.0(2M Bit/s) : 255 Byte

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone+Earphone+Travel Adapter, Stand alone+Travel Adapter
 - Worstcase : Stand alone+Travel Adapter

Conducted test

The EUT was configured with packet length of highest power.

- * Packet length of highest power :
- LE 5.0(1M Bit/s) : 255 Byte
- LE 5.0(2M Bit/s) : 255 Byte

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6		PASS


9. TEST RESULT

9.1 DUTY CYCLE


Data rate (Bit/s)	Packet length (Byte)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
250k	37	3.1037	3.7516	0.8273	0.82
	255	17.0700	17.5200	0.9743	0.11
1M	37	0.3914	0.6245	0.6268	2.03
	255	2.1350	2.5000	0.8540	0.69
2M	37	0.2065	0.6245	0.3306	4.81
	255	1.0780	1.8737	0.5753	2.40

250k Bit/s Test Plots

37 Byte CH 39




255 Byte CH 39




1M Bit/s Test Plots

37 Byte CH 39




255 Byte CH 39




2M Bit/s Test Plots

37 Byte CH 39



255 Byte CH 39




9.2 6dB BANDWIDTH

Mode (Bit/s)	Channel	6 dB Bandwidth (kHz)	Limit (kHz)
1M	0	680.2	> 500
	19	682.4	
	39	683.9	
2M	0	1151.0	> 500
	19	1165.8	
	39	1153.8	

1M Bit/s Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)




6 dB Bandwidth plot (High-CH 39)



2M Bit/s Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)



6 dB Bandwidth plot (High-CH 39)



9.3 OUTPUT POWER

Peak Power

LE Mode		Data rate (Bit/s)	Packet length (Byte)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.				
2402	0	250k	37	1.925	30
			255	1.940	
		1M	37	1.960	
			255	1.961	
		2M	37	2.001	
			255	2.002	
2440	19	250k	37	1.026	
			255	1.022	
		1M	37	1.047	
			255	1.054	
		2M	37	1.067	
			255	1.089	
2480	39	250k	37	2.084	
			255	2.080	
		1M	37	2.150	
			255	2.151	
		2M	37	2.166	
			255	2.172	

Average Power

LE Mode		Data rate	Packet length	Measured Power(dBm)	Duty Cycle Factor (dB)	Result (dBm)	Limit (dBm)
Frequency[MHz]	Channel No.	(Bit/s)	(Byte)				
2402	0	250k	37	0.94	0.82	1.77	30
			255	1.75	0.11	1.86	
		1M	37	-0.24	2.03	1.79	
			255	1.21	0.69	1.89	
		2M	37	-3.08	4.81	1.73	
			255	-0.67	2.40	1.73	
2440	19	250k	37	-0.04	0.82	0.79	
			255	0.76	0.11	0.87	
		1M	37	-1.15	2.03	0.87	
			255	0.23	0.69	0.91	
		2M	37	-4.79	4.81	0.01	
			255	-2.26	2.40	0.14	
2480	39	250k	37	1.09	0.82	1.92	
			255	1.82	0.11	1.93	
		1M	37	-0.11	2.03	1.92	
			255	1.27	0.69	1.96	
		2M	37	-2.93	4.81	1.87	
			255	-0.23	2.40	2.17	

Note :

1. Spectrum reading values are not plot data.

The power results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss

3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

So, 10.7 dB is offset for 2.4 GHz Band.

■ 1M Bit/s(255 Byte) Test Plots

Peak Power


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)




Conducted Output Power (High-CH 39)




Average Power


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)



Conducted Output Power (High-CH 39)



Note:

Plot of worst case are only reported.


■ 2M Bit/s(255 Byte) Test Plots

Peak Power


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)




Conducted Output Power (High-CH 39)




Average Power


Conducted Output Power (Low-CH 0)



Conducted Output Power (Mid-CH 19)



Conducted Output Power (High-CH 39)



Note:

Plot of worst case are only reported.

9.4 POWER SPECTRAL DENSITY


Frequency (MHz)	Channel No.	Mode	Test Result	
			PSD (dBm)	Limit (dBm)
2402	0	1M Bit 255 Byte	-14.073	8.000
2440	19		-14.975	8.000
2480	39		-14.017	8.000
2402	0	2M Bit 255 Byte	-16.610	8.000
2440	19		-17.461	8.000
2480	39		-16.421	8.000

Note :


1. Spectrum reading values are not plot data.
 The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
 So, 10.7 dB is offset for 2.4 GHz Band.

■ 1M Bit/s Test Plots


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)




Power Spectral Density (High-CH 39)




2M Bit/s Test Plots


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)



Power Spectral Density (High-CH 39)



9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

■ 1M Bit/s Test Plots (BandEdge)

Low-CH 0




High-CH 39



■ 1M Bit/s Test Plots (Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (Low-CH 39)




1 GHz ~ 3 GHz

Conducted Spurious Emission (Low-CH 39)




3 GHz ~ 5 GHz

Conducted Spurious Emission (Low-CH 39)




5 GHz ~ 7 GHz

Conducted Spurious Emission (Low-CH 39)




7 GHz ~ 9 GHz

Conducted Spurious Emission (Low-CH 39)




9 GHz ~ 11 GHz

Conducted Spurious Emission (Low-CH 39)




11 GHz ~ 13 GHz

Conducted Spurious Emission (Low-CH 39)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Low-CH 39)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Low-CH 39)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Low-CH 39)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Low-CH 39)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Low-CH 39)



23 GHz ~ 25 GHz

Conducted Spurious Emission (Low-CH 39)



2M Bit/s Test Plots (BandEdge)

Low-CH 0




High-CH 39



■ 2M Bit/s Test Plots (Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (Low-CH 39)




1 GHz ~ 3 GHz

Conducted Spurious Emission (Low-CH 39)




3 GHz ~ 5 GHz

Conducted Spurious Emission (Low-CH 39)




5 GHz ~ 7 GHz

Conducted Spurious Emission (Low-CH 39)




7 GHz ~ 9 GHz

Conducted Spurious Emission (Low-CH 39)




9 GHz ~ 11 GHz

Conducted Spurious Emission (Low-CH 39)




11 GHz ~ 13 GHz

Conducted Spurious Emission (Low-CH 39)




13 GHz ~ 15 GHz

Conducted Spurious Emission (Low-CH 39)




15 GHz ~ 17 GHz

Conducted Spurious Emission (Low-CH 39)




17 GHz ~ 19 GHz

Conducted Spurious Emission (Low-CH 39)




19 GHz ~ 21 GHz

Conducted Spurious Emission (Low-CH 39)




21 GHz ~ 23 GHz

Conducted Spurious Emission (Low-CH 39)



23 GHz ~ 25 GHz

Conducted Spurious Emission (Low-CH 39)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \cdot \log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.
5. The test results for below 30 MHz is correlated to an open site.
The result on OATS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Mode : 1M Bit/s 255 Byte

Operation Mode: CH Low

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	48.37	0.00	0.62	V	48.99	73.98	24.99	PK
4804	36.55	0.69	0.62	V	37.855	53.98	16.13	AV
7206	44.67	0.00	10.05	V	54.72	73.98	19.26	PK
7206	33.86	0.69	10.05	V	44.595	53.98	9.39	AV
4804	48.72	0.00	0.62	H	49.34	73.98	24.64	PK
4804	36.71	0.69	0.62	H	38.015	53.98	15.97	AV
7206	45.43	0.00	10.05	H	55.48	73.98	18.50	PK
7206	33.92	0.69	10.05	H	44.655	53.98	9.33	AV

Operation Mode: CH Mid

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4880	47.83	0.00	1.61	V	49.44	73.98	24.54	PK
4880	36.48	0.69	1.61	V	38.775	53.98	15.21	AV
7320	45.69	0.00	10.02	V	55.71	73.98	18.27	PK
7320	33.68	0.69	10.02	V	44.385	53.98	9.59	AV
4880	48.61	0.00	1.61	H	50.22	73.98	23.76	PK
4880	36.59	0.69	1.61	H	38.885	53.98	15.10	AV
7320	46.56	0.00	10.02	H	56.58	73.98	17.40	PK
7320	33.82	0.69	10.02	H	44.525	53.98	9.45	AV

Operation Mode: CH High

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	49.06	0.00	1.69	V	50.75	73.98	23.23	PK
4960	37.27	0.69	1.69	V	39.65	53.98	14.34	AV
7440	45.34	0.00	11.43	V	56.77	73.98	17.21	PK
7440	33.40	0.69	11.43	V	45.515	53.98	8.46	AV
4960	49.77	0.00	1.69	H	51.46	73.98	22.52	PK
4960	37.44	0.69	1.69	H	39.815	53.98	14.17	AV
7440	45.46	0.00	11.43	H	56.89	73.98	17.09	PK
7440	33.48	0.69	11.43	H	45.595	53.98	8.39	AV

Mode : 2M Bit/s 255 Byte

Operation Mode: CH Low

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	48.62	0.00	0.62	V	49.24	73.98	24.74	PK
4804	36.61	2.40	0.62	V	39.631	53.98	14.35	AV
7206	45.22	0.00	10.05	V	55.27	73.98	18.71	PK
7206	33.58	2.40	10.05	V	46.031	53.98	7.95	AV
4804	48.78	0.00	0.62	H	49.4	73.98	24.58	PK
4804	36.68	2.40	0.62	H	39.701	53.98	14.28	AV
7206	45.90	0.00	10.05	H	55.95	73.98	18.03	PK
7206	33.64	2.40	10.05	H	46.091	53.98	7.89	AV

Operation Mode: CH Mid


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4880	48.76	0.00	0.19	V	48.95	73.98	25.03	PK
4880	36.40	2.40	0.19	V	38.991	53.98	14.99	AV
7320	45.09	0.00	8.85	V	53.94	73.98	20.04	PK
7320	33.51	2.40	8.85	V	44.761	53.98	9.22	AV
4880	49.41	0.00	0.19	H	49.6	73.98	24.38	PK
4880	36.47	2.40	0.19	H	39.061	53.98	14.92	AV
7320	46.06	0.00	8.85	H	54.91	73.98	19.07	PK
7320	33.63	2.40	8.85	H	44.881	53.98	9.10	AV

Operation Mode: CH High

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	49.46	0.00	1.69	V	51.15	73.98	22.83	PK
4960	37.38	2.40	1.69	V	41.47	53.98	12.51	AV
7440	45.42	0.00	11.43	V	56.85	73.98	17.13	PK
7440	33.40	2.40	11.43	V	47.231	53.98	6.75	AV
4960	49.90	0.00	1.69	H	51.59	73.98	22.39	PK
4960	37.40	2.40	1.69	H	41.491	53.98	12.49	AV
7440	45.60	0.00	11.43	H	57.03	73.98	16.95	PK
7440	33.47	2.40	11.43	H	47.301	53.98	6.68	AV


■ 1M Bit/s 255 Byte Test Plots (Worst case : X-H)

Radiated Spurious Emissions plot – Average Reading (Ch.39 3rd Harmonic)



Date: 12.NOV.2018 13:29:33

Radiated Spurious Emissions plot – Peak Reading (Ch.39 3rd Harmonic)




Date: 12.NOV.2018 13:29:54

Note:

Plot of worst case are only reported.


■ 2M Bit/s 255 Byte Test Plots (Worst case : X-H)

Radiated Spurious Emissions plot – Average Reading (Ch.39 3rd Harmonic)



Date: 12.NOV.2018 13:28:43

Radiated Spurious Emissions plot – Peak Reading (Ch.39 3rd Harmonic)



Date: 12.NOV.2018 13:27:57

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Mode : 1M Bit/s 255 Byte

Operating Frequency 2402 MHz
 Channel No. 0

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	14.34	0.00	33.30	H	47.64	73.98	26.34	PK
2390.0	3.65	0.69	33.30	H	37.64	53.98	16.34	AV
2390.0	14.65	0.00	33.30	V	47.95	73.98	26.03	PK
2390.0	3.79	0.69	33.30	V	37.78	53.98	16.20	AV

Operating Frequency 2480 MHz
 Channel No. 39

Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	14.90	0.00	33.41	H	48.31	73.98	25.67	PK
2483.5	3.95	0.69	33.41	H	38.05	53.98	15.93	AV
2483.5	15.42	0.00	33.41	V	48.83	73.98	25.15	PK
2483.5	3.98	0.69	33.41	V	38.08	53.98	15.90	AV

Mode : 2M Bit/s 255 Byte

Operating Frequency 2402 MHz
 Channel No. 0


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	14.68	0.00	33.30	H	47.98	73.98	26.00	PK
2390.0	3.66	2.40	33.30	H	39.36	53.98	14.62	AV
2390.0	15.59	0.00	33.30	V	48.89	73.98	25.09	PK
2390.0	3.70	2.40	33.30	V	39.40	53.98	14.58	AV

Operating Frequency 2480 MHz
 Channel No. 39


Frequency [MHz]	Reading [dBuV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	14.99	0.00	33.41	H	48.40	73.98	25.58	PK
2483.5	3.79	2.40	33.41	H	39.61	53.98	14.38	AV
2483.5	15.12	0.00	33.41	V	48.53	73.98	25.45	PK
2483.5	3.85	2.40	33.41	V	39.66	53.98	14.32	AV

Mode : 1M Bit/s 255 Byte Test Plots (Worst case : Z-V)

Radiated Restricted Band Edges plot – Average Reading (Ch.39)




Radiated Restricted Band Edges plot – Peak Reading (Ch.39)




Mode : 2M Bit/s 255 Byte Test Plots (Worst case : Z-V)

Radiated Restricted Band Edges plot – Average Reading (Ch.39)



Radiated Restricted Band Edges plot – Peak Reading (Ch.39)



Note:

Plot of worst case are only reported.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

EMI Auto Test(5)


1 / 2

HCT TEST Report

Common Information

EUT: SM-A920N
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE MODE

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	40.4	9.000	Off	N	9.7	25.5	65.9
0.156000	38.6	9.000	Off	N	9.7	27.0	65.7
0.160000	38.4	9.000	Off	N	9.7	27.1	65.5
0.174000	40.6	9.000	Off	N	9.7	24.2	64.8
0.182000	38.8	9.000	Off	N	9.7	25.5	64.4
0.192000	38.2	9.000	Off	N	9.7	25.8	63.9
1.136000	33.5	9.000	Off	N	9.8	22.5	56.0
1.142000	33.3	9.000	Off	N	9.8	22.7	56.0
1.162000	35.3	9.000	Off	N	9.8	20.7	56.0
1.168000	34.0	9.000	Off	N	9.8	22.0	56.0
1.178000	34.3	9.000	Off	N	9.8	21.7	56.0
1.194000	33.3	9.000	Off	N	9.8	22.7	56.0
8.918000	24.4	9.000	Off	N	10.2	35.6	60.0
9.000000	24.8	9.000	Off	N	10.2	35.2	60.0
9.230000	24.9	9.000	Off	N	10.2	35.1	60.0
9.534000	24.8	9.000	Off	N	10.2	35.2	60.0
13.782000	24.2	9.000	Off	N	10.4	35.8	60.0
13.880000	24.2	9.000	Off	N	10.4	35.8	60.0

2018-11-08

오후 7:23:33

EMI Auto Test(5)

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	25.2	9.000	Off	N	9.7	30.5	55.8
0.170000	24.9	9.000	Off	N	9.7	30.0	55.0
0.174000	25.6	9.000	Off	N	9.7	29.2	54.8
0.180000	24.8	9.000	Off	N	9.7	29.7	54.5
0.184000	24.0	9.000	Off	N	9.7	30.3	54.3
0.192000	23.1	9.000	Off	N	9.7	30.9	53.9
1.136000	26.7	9.000	Off	N	9.8	19.3	46.0
1.142000	26.1	9.000	Off	N	9.8	19.9	46.0
1.162000	27.0	9.000	Off	N	9.8	19.0	46.0
1.168000	26.3	9.000	Off	N	9.8	19.7	46.0
1.176000	26.4	9.000	Off	N	9.8	19.6	46.0
1.194000	26.3	9.000	Off	N	9.8	19.7	46.0
8.918000	18.6	9.000	Off	N	10.2	31.4	50.0
9.072000	18.8	9.000	Off	N	10.2	31.2	50.0
9.316000	18.8	9.000	Off	N	10.2	31.2	50.0
9.534000	18.6	9.000	Off	N	10.2	31.4	50.0
13.672000	18.4	9.000	Off	N	10.4	31.6	50.0
13.782000	18.0	9.000	Off	N	10.4	32.0	50.0

2018-11-08

오후 7:23:33

Conducted Emissions (Line 2)

EMI Auto Test(5)


1 / 2

HCT TEST Report

Common Information

EUT: SM-A920N
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: BT LE MODE

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	43.0	9.000	Off	L1	9.7	23.0	66.0
0.166000	41.5	9.000	Off	L1	9.7	23.6	65.2
0.172000	43.2	9.000	Off	L1	9.7	21.7	64.9
0.176000	42.8	9.000	Off	L1	9.7	21.9	64.7
0.180000	41.5	9.000	Off	L1	9.7	23.0	64.5
0.184000	40.6	9.000	Off	L1	9.7	23.7	64.3
1.144000	32.9	9.000	Off	L1	9.8	23.1	56.0
1.162000	33.3	9.000	Off	L1	9.8	22.7	56.0
1.166000	34.9	9.000	Off	L1	9.8	21.1	56.0
1.170000	32.7	9.000	Off	L1	9.8	23.3	56.0
1.182000	32.3	9.000	Off	L1	9.8	23.7	56.0
1.190000	34.1	9.000	Off	L1	9.8	21.9	56.0
8.880000	30.0	9.000	Off	L1	10.1	30.0	60.0
9.522000	30.5	9.000	Off	L1	10.2	29.5	60.0
9.578000	30.6	9.000	Off	L1	10.2	29.4	60.0
9.824000	30.6	9.000	Off	L1	10.2	29.4	60.0
9.950000	30.0	9.000	Off	L1	10.2	30.0	60.0
13.780000	28.7	9.000	Off	L1	10.2	31.3	60.0

2018-11-08

오후 7:35:15

EMI Auto Test(5)

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.2	9.000	Off	L1	9.7	27.8	56.0
0.154000	26.3	9.000	Off	L1	9.7	29.5	55.8
0.172000	28.7	9.000	Off	L1	9.7	26.2	54.9
0.176000	28.3	9.000	Off	L1	9.7	26.4	54.7
0.180000	27.1	9.000	Off	L1	9.7	27.4	54.5
0.184000	25.9	9.000	Off	L1	9.7	28.4	54.3
1.144000	26.0	9.000	Off	L1	9.8	20.0	46.0
1.148000	26.3	9.000	Off	L1	9.8	19.7	46.0
1.154000	25.9	9.000	Off	L1	9.8	20.1	46.0
1.162000	26.8	9.000	Off	L1	9.8	19.2	46.0
1.166000	26.7	9.000	Off	L1	9.8	19.3	46.0
1.170000	26.3	9.000	Off	L1	9.8	19.7	46.0
8.880000	22.1	9.000	Off	L1	10.1	27.9	50.0
8.982000	21.6	9.000	Off	L1	10.1	28.4	50.0
9.514000	22.3	9.000	Off	L1	10.2	27.7	50.0
9.578000	22.0	9.000	Off	L1	10.2	28.0	50.0
9.824000	21.8	9.000	Off	L1	10.2	28.2	50.0
13.780000	20.9	9.000	Off	L1	10.2	29.1	50.0

2018-11-08

오후 7:35:15

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/20/2017	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/27/2018	Annual	100033
ESPAAC	SU-642 / Temperature Chamber	03/30/2018	Annual	0093008124
Agilent	N9020A / Signal Analyzer	06/08/2018	Annual	MY52090906
Agilent	N1911A / Power Meter	04/16/2018	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/16/2018	Annual	MY52260025
Hewlett Packard	11667B / Power Splitter	06/07/2018	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/26/2018	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/10/2018	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/17/2018	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	04/19/2017	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/06/2017	Biennial	760
Schwarzbeck	VULB 9160 / TRILOG Antenna	08/09/2018	Biennial	9160-3368
Schwarzbeck	BBHA 9120D / Horn Antenna	05/02/2017	Biennial	9120D-937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	12/04/2017	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/03/2018	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/28/2018	Annual	101068-SZ
Agilent	N9020A / Signal Analyzer	06/08/2018	Annual	MY51110085
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/07/2018	Annual	8
Wainwright Instruments	WHKX7.0/18G-8SS / High Pass Filter	05/09/2018	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/29/2018	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2018	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/07/2018	Annual	1
Agilent	8493C-10 / Attenuator(10 dB)	07/17/2018	Annual	08285
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/10/2018	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/29/2018	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/27/2018	Annual	3000C000276

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1811-FC029-P
2	HCT-RF-1811-FC030-P
3	HCT-RF-1811-FC031-P
4	HCT-RF-1811-FC032-P
5	HCT-RF-1811-FC033-P
6	HCT-RF-1811-FC034-P
7	HCT-RF-1811-FC035-P