

**MEASUREMENT REPORT**
FCC Part 22 / IC RSS-132 LTE**Applicant Name:**

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

July 30 - Aug 05, 2013

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1307231354.A3L

FCC ID : **A3LSMC105****APPLICANT:** **SAMSUNG ELECTRONICS, CO. LTD.****FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

§2; §22

EUT Type:

Portable Handset

Model(s):

SM-C105

Test Device Serial No.:

identical prototype [S/N: 23July-2]

Mode	Tx Frequency (MHz)	Emission Designator	Modulation	ERP/EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE Band 5	824.7 - 848.3	1M11G7D	QPSK	0.098	19.93
LTE Band 5	824.7 - 848.3	1M10W7D	16QAM	0.072	18.59
LTE Band 5	825.5 - 847.5	2M71G7D	QPSK	0.074	18.71
LTE Band 5	825.5 - 847.5	2M70W7D	16QAM	0.068	18.31
LTE Band 5	826.5 - 846.5	4M50G7D	QPSK	0.091	19.61
LTE Band 5	826.5 - 846.5	4M50W7D	16QAM	0.068	18.31
LTE Band 5	829 - 844	9M01G7D	QPSK	0.096	19.81
LTE Band 5	829 - 844	8M99W7D	16QAM	0.074	18.71

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested. I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 1 of 44

TABLE OF CONTENTS

FCC PART 22 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.4 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TESTS	6
3.1 MEASUREMENT PROCEDURE	6
3.2 CELLULAR - BASE FREQUENCY BLOCKS.....	6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS.....	6
3.4 OCCUPIED BANDWIDTH	6
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	6
3.6 PEAK-AVERAGE RATIO	7
3.7 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.8 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS.....	12
6.1 SUMMARY.....	12
6.2 EFFECTIVE RADIATED POWER (ERP)	13
6.3 BAND 5 RADIATED SPURIOUS EMISSIONS	14
6.4 BAND 5 FREQUENCY STABILITY MEASUREMENTS.....	17
7.0 BAND 5 PLOTS OF EMISSIONS.....	19
8.0 CONCLUSION.....	44

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 2 of 44



MEASUREMENT REPORT

FCC Part 22




§2.1033 General Information

APPLICANT: Samsung Electronics, Co. Ltd.
APPLICANT ADDRESS: 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si, Gyeonggi-do 443-742, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22
BASE MODEL: SM-C105
FCC ID: A3LSMC105
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: 23July-2 ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: July 30 - Aug 05, 2013
TEST REPORT S/N: 0Y1307231354.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 3 of 44

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on January 10, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 4 of 44

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMC105**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 5, 802.11a/b/g/n WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.4 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 5 of 44


3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-C-2004) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168) were used in the measurement of the **Samsung Portable Handset** FCC ID: A3LSMC105.

3.2 Cellular - Base Frequency Blocks

§24.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§24.905



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 Occupied Bandwidth

§2.1049 RSS-Gen(4.6.1)

The implementation of this test is performed by the spectrum analyzer's occupied bandwidth function. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

3.5 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a)(b) RSS-132(4.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Cell band, or 1 MHz or greater for. However,

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 6 of 44

in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed for. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.6 Peak-Average Ratio

RSS-132(5.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For LTE signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 7 of 44

3.7 Radiated Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a) RSS-132(4.4) RSS-132(4.5.1)

Radiated spurious emissions are investigated indoors in a semi-anechoic chamber to determine the frequencies producing the worst case emissions. Final measurements for radiated power and radiated spurious emissions are performed on the 3 meter OATS per the guidelines of ANSI/TIA-603-C-2004. The measurement area is situated on an 18 meter x 20 meter galvanized 1/2" hardware cloth as the conducting ground plane. This material is sewn together in sections 4 feet wide and 60 feet long. A total of eighteen sections are required to cover the entire measurement area. Sections are laid across the width of the pad, overlapped 1" and sewn and soldered together at intervals of 3" (7.6 cm.) The terrain of the test site is reasonably flat and level. Power and cable to the test site are buried 18" deep into the ground outside the perimeter of the site. An all-weather non-metallic housing is situated on a 2 x 3 meter area adjacent to the measurement area to house the test equipment. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Emissions are also investigated with the receive antenna horizontally and vertically polarized. The level of the maximized emission is recorded with the spectrum analyzer using a peak detector with RBW = 1MHz, VBW = 3MHz for emissions greater than 1GHz. For emissions below 1GHz, the spectrum analyzer is set to RBW = 100kHz and VBW = 300kHz.

A half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 22.917(a).




Figure 3-1. Diagram of 3-meter Test Range

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 8 of 44

3.8 Frequency Stability / Temperature Variation

§2.1055 §22.863 §22.905 RSS-132(4.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification –The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency for Part 22.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 9 of 44

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	3/29/2013	Annual	3/29/2014	N/A
-	LTx2	Licensed Transmitter Cable Set	1/17/2013	Annual	1/17/2014	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	1937A03348
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	4/17/2013	Annual	4/17/2014	3008A00985
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/10/2012	Annual	10/10/2013	3613A00315
Agilent	N9038A	MXE EMI Receiver	12/8/2012	Annual	12/8/2013	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	1/11/2013	Annual	1/11/2014	MY52350166
Anritsu	MA2411B	Pulse Sensor	9/19/2012	Annual	9/19/2013	1027293
Anritsu	ML2495A	Power Meter	10/11/2012	Annual	10/11/2013	1039008
Espec	ESX-2CA	Environmental Chamber	4/16/2013	Annual	4/16/2014	17620
Mini-Circuits	VHF-3100+	High Pass Filter	9/21/2013	Annual	1/21/2014	31144
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	6/25/2012	Annual	9/25/2013	100976
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Sunol	DRH-118	Hom Antenna (1 - 18GHz)	6/19/2013	Biennial	6/19/2015	A050307
Sunol	DRH-118	Hom Antenna (1-18 GHz)	6/19/2013	Biennial	6/19/2015	A042511
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 10 of 44

5.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Amplitude/Angle Modulated

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Combination (Audio/Data)

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 11 of 44

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics, Co. Ltd.
 FCC ID: A3LSMC105
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
TRANSMITTER MODE (TX)						
2.1049	RSS-Gen (4.6.1)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section, 7.0
2.1051 22.917(a)	RSS-132(4.5.1)	Band Edge / Conducted Spurious Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Section, 7.0
	RSS-132(5.4)	Peak-Average Ratio	$< 13 \text{ dB}$		PASS	Section
2.1046	RSS-132(4.4)	Transmitter Conducted Output Power	N/A		PASS	See RF Exposure Report
22.913(a.2)	RSS-132(4.4) [SRSP-503(5.1.3)]	Effective Radiated Power (Band 5)	$< 7 \text{ Watts max. ERP}$	RADIATED	PASS	Section 6.2
2.1053 22.917(a)	RSS-132(4.5.1)	Undesirable Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section, 6.3
2.1055. 22.355	RSS-132(4.3)	Frequency Stability	$< 2.5 \text{ ppm (Part 22)}$		PASS	Section, 6.4

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 12 of 44

6.2 Effective Radiated Power (ERP)

§22.913(a.2) RSS-132(4.4)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Margin [dB]
824.70	1.4	QPSK	Standard	1 / 5	20.61	-0.83	V	19.78	0.095	-18.67
836.50	1.4	QPSK	Standard	1 / 5	20.73	-0.80	V	19.93	0.098	-18.52
848.30	1.4	QPSK	Standard	1 / 5	19.23	-0.77	V	18.46	0.070	-19.99
824.70	1.4	16-QAM	Standard	1 / 5	19.42	-0.83	V	18.59	0.072	-19.86
836.50	1.4	16-QAM	Standard	1 / 5	19.30	-0.80	V	18.50	0.071	-19.95
848.30	1.4	16-QAM	Standard	1 / 5	17.71	-0.77	V	16.94	0.049	-21.51
825.50	3	QPSK	Standard	1 / 14	19.32	-0.83	V	18.49	0.071	-19.96
836.50	3	QPSK	Standard	1 / 14	19.51	-0.80	V	18.71	0.074	-19.74
847.50	3	QPSK	Standard	1 / 14	18.90	-0.77	V	18.13	0.065	-20.32
825.50	3	16-QAM	Standard	1 / 14	18.21	-0.83	V	17.38	0.055	-21.07
836.50	3	16-QAM	Standard	1 / 14	19.11	-0.80	V	18.31	0.068	-20.14
847.50	3	16-QAM	Standard	1 / 14	17.91	-0.77	V	17.14	0.052	-21.31
826.50	5	QPSK	Standard	1 / 24	19.22	-0.83	V	18.39	0.069	-20.06
836.50	5	QPSK	Standard	1 / 24	20.41	-0.80	V	19.61	0.091	-18.84
846.50	5	QPSK	Standard	1 / 24	19.01	-0.77	V	18.24	0.067	-20.21
826.50	5	16-QAM	Standard	1 / 24	18.11	-0.83	V	17.28	0.053	-21.17
836.50	5	16-QAM	Standard	1 / 24	19.11	-0.80	V	18.31	0.068	-20.14
846.50	5	16-QAM	Standard	1 / 24	18.11	-0.77	V	17.34	0.054	-21.11
829.00	10	QPSK	Standard	1 / 49	19.61	-0.83	V	18.78	0.075	-19.67
836.50	10	QPSK	Standard	1 / 49	20.61	-0.80	V	19.81	0.096	-18.64
844.00	10	QPSK	Standard	1 / 49	18.90	-0.77	V	18.13	0.065	-20.32
829.00	10	16-QAM	Standard	1 / 49	18.71	-0.83	V	17.88	0.061	-20.57
836.50	10	16-QAM	Standard	1 / 49	19.51	-0.80	V	18.71	0.074	-19.74
844.00	10	16-QAM	Standard	1 / 49	18.12	-0.77	V	17.35	0.054	-21.10

Table 6-2. ERP Data (Band 5)

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with RB = 1 and Offset = MAX.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the V positioning. The data reported in the table above was measured in this test setup.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 13 of 44

6.3 Band 5 Radiated Spurious Emissions

§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz

MEASURED OUTPUT POWER: 19.78 dBm = 0.095 W

MODULATION SIGNAL: QPSK

BANDWIDTH: 1.4 MHz

DISTANCE: 3 meters

LIMIT: $43 + 10 \log_{10}(W) =$ 32.78 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-56.14	6.28	-49.86	V	69.64
2474.10	-50.65	6.57	-44.09	V	63.86
3298.80	-80.98	7.03	-73.95	V	93.72
4123.50	-79.29	7.75	-71.54	V	91.32
4948.20	-78.93	9.05	-69.88	V	89.66
5772.90	-75.21	9.15	-66.06	V	85.84

Table 6-3. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with RB = 1 and Offset = MAX.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the V positioning. The data reported in the table above was measured in this test setup.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 14 of 44

Band 5 Radiated Spurious Measurements (continued)

§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.50 MHz
 MEASURED OUTPUT POWER: 19.93 dBm = 0.098 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 32.93$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.00	-53.66	6.19	-47.47	V	67.39
2509.50	-50.87	6.58	-44.29	V	64.22
3346.00	-81.11	7.16	-73.95	V	93.88
4182.50	-79.66	7.99	-71.67	V	91.59
5019.00	-78.62	8.98	-69.64	V	89.57
5855.50	-74.96	9.17	-65.78	V	85.71

Table 6-4. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with RB = 1 and Offset = MAX.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the V positioning. The data reported in the table above was measured in this test setup.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 15 of 44

Band 5 Radiated Spurious Measurements (continued)

§2.1053 §22.917(a) RSS-132(4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.30 MHz
 MEASURED OUTPUT POWER: 18.46 dBm = 0.070 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 31.46$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1696.60	-56.04	6.09	-49.95	V	68.40
2544.90	-49.85	6.66	-43.19	V	61.65
3393.20	-81.24	7.28	-73.96	V	92.42
4241.50	-79.91	8.18	-71.73	V	90.19
5089.80	-78.23	8.89	-69.34	V	87.80
5938.10	-74.66	9.17	-65.49	V	83.94

Table 6-5. Radiated Spurious Data

NOTES:

1. This device was tested under all bandwidths, and RB configurations, and modulations. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with RB = 1 and Offset = MAX.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the V positioning. The data reported in the table above was measured in this test setup.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 16 of 44

6.4 Band 5 Frequency Stability Measurements

§2.1055 §22.355 RSS-132(4.3)

OPERATING FREQUENCY: 836,500,000 Hz

CHANNEL: 20525

REFERENCE VOLTAGE: 3.8 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,499,985	-15	-0.0000018
100 %		- 30	836,499,981	-19	-0.0000023
100 %		- 20	836,500,022	22	0.0000026
100 %		- 10	836,500,014	14	0.0000017
100 %		0	836,499,983	-17	-0.0000020
100 %		+ 10	836,499,988	-12	-0.0000014
100 %		+ 20	836,499,985	-15	-0.0000018
100 %		+ 30	836,499,988	-12	-0.0000014
100 %		+ 40	836,499,981	-19	-0.0000023
100 %		+ 50	836,499,978	-22	-0.0000026
115 %	4.37	+ 20	836,499,976	-24	-0.0000029
BATT. ENDPOINT	3.40	+ 20	836,499,974	-26	-0.0000031

Table 6-6. Frequency Stability Data (Band 5)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 17 of 44

Band 5 Frequency Stability Measurements (Cont'd)

§2.1055 §22.355 RSS-132(4.3)





Figure 6-1. Frequency Stability Graph (Band 5)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 18 of 44




Plot 7-2. Lower Extended Band Edge Plot (1.4MHz QPSK – RB Size 6)




Plot 7-3. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 20 of 44




Plot 7-4. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6)




Plot 7-5. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 21 of 44




Plot 7-6. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-7. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 22 of 44




Plot 7-8. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)



Plot 7-9. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 23 of 44



Plot 7-10. Conducted Spurious Plot (1.4MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-11. Upper Band Edge Plot (1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 24 of 44



Plot 7-12. Upper Extended Band Edge Plot (1.4MHz QPSK – RB Size 6)




Plot 7-13. Lower Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 25 of 44




Plot 7-14. Lower Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 7-15. Occupied Bandwidth Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 26 of 44




Plot 7-16. Occupied Bandwidth Plot (3.0MHz 16-QAM – RB Size 15)




Plot 7-17. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 27 of 44




Plot 7-18. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-19. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSCMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 28 of 44




Plot 7-20. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-21. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 29 of 44




Plot 7-22. Conducted Spurious Plot (3.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 7-23. Upper Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 30 of 44




Plot 7-24. Upper Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 7-25. Lower Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 31 of 44



Plot 7-26. Lower Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 7-27. Occupied Bandwidth Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 32 of 44




Plot 7-28. Occupied Bandwidth Plot (5.0MHz 16-QAM – RB Size 25)




Plot 7-29. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 33 of 44




Plot 7-30. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-31. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 34 of 44




Plot 7-32. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-33. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 35 of 44




Plot 7-34. Conducted Spurious Plot (5.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-35. Upper Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 36 of 44



Plot 7-36. Upper Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 7-37. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 37 of 44




Plot 7-38. Lower Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 7-39. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 38 of 44




Plot 7-40. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)




Plot 7-41. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 39 of 44




Plot 7-42. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)




Plot 7-43. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMC105	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 40 of 44




Plot 7-44. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)



Plot 7-45. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 41 of 44



Plot 7-46. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)



Plot 7-47. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMC105	 FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset	Page 42 of 44



Plot 7-48. Upper Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMC105	FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 43 of 44

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMC105** complies with all the requirements of Parts 2, 22 of the FCC rules for LTE operation only and RSS-132 of the Industry Canada rules.

FCC ID: A3LSMC105		FCC Pt. 22 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307231354.A3L	Test Dates: July 30 - Aug 05, 2013	EUT Type: Portable Handset		Page 44 of 44