

FCC ID:	A3LSMF700U
Date:	1/2/2020
Test Procedure:	KDB 680106 D01 v03

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.214	0.172	0.145	0.113	0.147	0.137	614.00
B (Right)	0.231	0.156	0.241	0.145	0.145	0.127	614.00
C (Top)	0.164	0.145	0.137	0.127	0.145	0.137	614.00
D (Left)	0.191	0.181	0.157	0.137	0.173	0.145	614.00
E (Front)	0.167	0.148	0.145	0.137	0.180	0.145	614.00
F (Back)	0.186	0.145	0.167	0.157	0.147	0.145	614.00

Table 1. E-field Measurement by distance/battery level (D2D - Open)

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
B (Right)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
C (Top)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
D (Left)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
E (Front)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
F (Back)	0.094	0.094	0.094	0.094	0.094	0.094	1.63

Table 2. H-field Measurement by distance/battery level (D2D - Open)

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.184	0.145	0.157	0.145	0.179	0.137	614.00
B (Right)	0.180	0.147	0.186	0.148	0.173	0.145	614.00
C (Top)	0.226	0.148	0.219	0.137	0.189	0.145	614.00
D (Left)	0.224	0.156	0.186	0.148	0.262	0.145	614.00
E (Front)	0.292	0.167	0.245	0.218	0.237	0.147	614.00
F (Back)	0.259	0.175	0.145	0.137	0.270	0.154	614.00

Table 3. E-field Measurement by distance/battery level (D2D - Closed)

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
B (Right)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
C (Top)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
D (Left)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
E (Front)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
F (Back)	0.094	0.094	0.094	0.094	0.094	0.094	1.63

Table 4. H-field Measurement by distance/battery level (D2D - Closed)

Note:

The right and left edge are determined with the EUT screen facing the user.

Description of Test Setup

- Testing was performed with a calibrated field probe.
- Measurement was performed on each side of the EUT as described per Table 4.
- Testing was performed at the distances and different battery level as indicated in the tables.
- Measurement procedure was performed per FCC Guidance.
- The EUT is capable of operating in folded closed and unfolded open configurations.

Test Equipment

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electric & Magnetic Field Probe	6/27/2019	Annual	6/27/2020	170WX60209