



MEASUREMENT REPORT

FCC PART 15.247 Bluetooth (Low Energy)

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea


Date of Testing:
04/12/2021 - 06/04/2021
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M2104130035-08.A3L

FCC ID:	A3LSMF711B
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Certification
Model: SM-F711B
EUT Type: Portable Handset
Max. RF Output Power: 3.714 mW (5.70dBm) Peak Conducted
Frequency Range: 2402 – 2480MHz
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (15.247)
ISED Specification: RSS-247 Issue 2
Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01 v05r02,
 KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President



FCC ID: A3LSMF711B	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 1 of 87

TABLE OF CONTENTS

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
1.1	Antenna Description	4
2.3	Test Configuration	5
2.4	Software and Firmware	5
2.5	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	AC Line Conducted Emissions	6
3.3	Radiated Emissions	7
3.4	Environmental Conditions	7
4.0	ANTENNA REQUIREMENTS	8
5.0	MEASUREMENT UNCERTAINTY	9
6.0	TEST EQUIPMENT CALIBRATION DATA	10
7.0	TEST RESULTS	11
7.1	Summary	11
7.2	6dB Bandwidth Measurement – Bluetooth (LE)	12
7.3	Output Power Measurement – Bluetooth (LE)	27
7.4	Power Spectral Density – Bluetooth (LE)	41
7.5	Conducted Emissions at the Band Edge	56
7.6	Conducted Spurious Emissions	65
7.7	Radiated Spurious Emission Measurements	73
7.8	Radiated Restricted Band Edge Measurements	80
7.9	Line-Conducted Test Data	81
8.0	CONCLUSION	87

FCC ID: A3LSMF711B	 <small>Proud to be part of  element</small>	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 2 of 87	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 3 of 87

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMF711B**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: 0129M, 0135M, 0189M, 0545M, 0059S, 0585S, 1600S

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (n5, n66), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

Ch.	Frequency (MHz)
0	2402
:	:
19	2440
:	:
39	2480

Table 2-1. Frequency / Channel Operations

1.1 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna Gain (dBi)
2.4	-6.1

Table 2-2. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 4 of 87

2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 Software and Firmware

The test was conducted with firmware version F711USQU0AUE1 installed on the EUT.

2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 5 of 87

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMF711B	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 6 of 87	

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 7 of 87	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 8 of 87	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMF711B	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 9 of 87

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	7/2/2020	Annual	7/2/2021	WL25-1
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	8/11/2021	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	7/17/2020	Annual	7/17/2021	MY49430494
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	7/9/2020	Biennial	7/9/2022	114451
Keysight Technologies	N9030A	PXA Signal Analyzer (3Hz-26.5GHz)	9/13/2019	Annual	10/16/2021	MY54490576
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	10/1/2019	Biennial	10/1/2021	310233
Sunol	DRH-118	Horn Antenna (1-18GHz)	10/3/2019	Biennial	10/3/2021	A050307

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 10 of 87

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMF711B
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	RSS-247 [5.4(4)]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

- All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Bluetooth LE Automation,” Version 3.6.
- For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Chamber Automation,” Version 1.3.1.

FCC ID: A3LSMF711B	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 11 of 87

7.2 6dB Bandwidth Measurement – Bluetooth (LE)

§15.247(a.2); RSS-247 [5.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 12 of 87

Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	0	LE	625.0	500	Pass
2440	125 kbps	19	LE	622.9	500	Pass
2480	125 kbps	39	LE	622.9	500	Pass
2402	500 kbps	0	LE	699.2	500	Pass
2440	500 kbps	19	LE	698.0	500	Pass
2480	500 kbps	39	LE	697.3	500	Pass
2402	1 Mbps	0	LE	664.5	500	Pass
2440	1 Mbps	19	LE	662.6	500	Pass
2480	1 Mbps	39	LE	664.1	500	Pass
2402	2 Mbps	0	LE	613.2	500	Pass
2440	2 Mbps	19	LE	607.8	500	Pass
2480	2 Mbps	39	LE	614.8	500	Pass

Table 7-2. Conducted Bandwidth Measurements - N

FCC ID: A3LSMF711B	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 13 of 87



Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 0) - N



Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 19) - N

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 14 of 87



Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39) - N




Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 15 of 87



Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 19) - N




Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 16 of 87




Plot 7-7. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N



Plot 7-8. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 17 of 87




Plot 7-9. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N




Plot 7-10. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 18 of 87



Plot 7-11. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 19) - N



Plot 7-12. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 19 of 87


Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	0	LE	620.3	500	Pass
2440	125 kbps	19	LE	623.0	500	Pass
2480	125 kbps	39	LE	619.3	500	Pass
2402	500 kbps	0	LE	661.3	500	Pass
2440	500 kbps	19	LE	661.5	500	Pass
2480	500 kbps	39	LE	660.3	500	Pass
2402	1 Mbps	0	LE	669.5	500	Pass
2440	1 Mbps	19	LE	670.5	500	Pass
2480	1 Mbps	39	LE	667.3	500	Pass
2402	2 Mbps	0	LE	1138.9	500	Pass
2440	2 Mbps	19	LE	1136.9	500	Pass
2480	2 Mbps	39	LE	1140.4	500	Pass

Table 7-3. Conducted Bandwidth Measurements - Q

FCC ID: A3LSMF711B	 Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 20 of 87




Plot 7-13. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 0) - Q



Plot 7-14. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 21 of 87



Plot 7-15. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39) – Q



Plot 7-16. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 0) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 22 of 87



Plot 7-17. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 19) - Q



Plot 7-18. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 23 of 87



Plot 7-19. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q



Plot 7-20. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 24 of 87




Plot 7-21. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) - Q



Plot 7-22. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 25 of 87



Plot 7-23. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 19) - Q



Plot 7-24. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 26 of 87

7.3 Output Power Measurement – Bluetooth (LE) §15.247(b.3); RSS-247 [5.4(4)]

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.1
KDB 558074 D01 v05r02 – Section 8.3.1.1

Test Settings

1. RBW = 3MHz
2. VBW = 50MHz
3. Span $\geq 3 \times$ RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 27 of 87


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power (N)		Peak Conducted Power (Q)	
				[dBm]	[mW]	[dBm]	[mW]
2402	125 kbps	0	LE	5.04	3.192	5.06	3.206
2440	125 kbps	19	LE	4.77	2.999	5.45	3.507
2480	125 kbps	39	LE	4.12	2.582	4.07	2.550
2402	500 kbps	0	LE	5.07	3.214	5.10	3.237
2440	500 kbps	19	LE	4.80	3.020	5.57	3.604
2480	500 kbps	39	LE	4.19	2.624	4.32	2.701
2402	1 Mbps	0	LE	5.09	3.228	5.11	3.246
2440	1 Mbps	19	LE	4.84	3.048	5.56	3.598
2480	1 Mbps	39	LE	4.18	2.618	4.33	2.712
2402	2 Mbps	0	LE	5.23	3.334	5.25	3.348
2440	2 Mbps	19	LE	4.98	3.148	5.70	3.714
2480	2 Mbps	39	LE	4.33	2.710	4.46	2.794

Table 7-4. Conducted Output Power Measurements (Bluetooth (LE))

FCC ID: A3LSMF711B	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 28 of 87




Plot 7-25. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 0) - N




Plot 7-26. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 29 of 87




Plot 7-27. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39) - N




Plot 7-28. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 30 of 87




Plot 7-29. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 19) - N




Plot 7-30. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 31 of 87




Plot 7-31. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N




Plot 7-32. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 32 of 87




Plot 7-33. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N




Plot 7-34. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 33 of 87




Plot 7-35. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 19) - N




Plot 7-36. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 34 of 87




Plot 7-37. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 0) - Q




Plot 7-38. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 35 of 87




Plot 7-39. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39) - Q




Plot 7-40. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 0) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 36 of 87




Plot 7-41. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 19) - Q




Plot 7-42. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 37 of 87




Plot 7-43. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q




Plot 7-44. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 38 of 87



Plot 7-47. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 19) - Q



Plot 7-48. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 40 of 87

7.4 Power Spectral Density – Bluetooth (LE)

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 41 of 87


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	0	LE	-1.18	8.0	-9.18
2440	125 kbps	19	LE	-1.21	8.0	-9.21
2480	125 kbps	39	LE	-2.24	8.0	-10.24
2402	500 kbps	0	LE	3.47	8.0	-4.53
2440	500 kbps	19	LE	3.44	8.0	-4.56
2480	500 kbps	39	LE	2.39	8.0	-5.61
2402	1 Mbps	0	LE	3.82	8.0	-4.18
2440	1 Mbps	19	LE	3.84	8.0	-4.16
2480	1 Mbps	39	LE	2.79	8.0	-5.21
2402	2 Mbps	0	LE	0.57	8.0	-7.43
2440	2 Mbps	19	LE	0.58	8.0	-7.42
2480	2 Mbps	39	LE	-0.55	8.0	-8.55

Table 7-5. Conducted Power Density Measurements - N

FCC ID: A3LSMF711B	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 42 of 87




Plot 7-49. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 0) - N




Plot 7-50. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 43 of 87




Plot 7-51. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39) - N




Plot 7-52. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 44 of 87




Plot 7-53. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 19) - N




Plot 7-54. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 45 of 87




Plot 7-55. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N




Plot 7-56. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 46 of 87




Plot 7-57. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N




Plot 7-58. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 47 of 87



Plot 7-59. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 19) - N




Plot 7-60. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 48 of 87


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	0	LE	-1.12	8.0	-9.12
2440	125 kbps	19	LE	-0.63	8.0	-8.63
2480	125 kbps	39	LE	-1.72	8.0	-9.72
2402	500 kbps	0	LE	-1.26	8.0	-9.26
2440	500 kbps	19	LE	-0.80	8.0	-8.80
2480	500 kbps	39	LE	-1.94	8.0	-9.94
2402	1 Mbps	0	LE	-9.82	8.0	-17.82
2440	1 Mbps	19	LE	-9.28	8.0	-17.28
2480	1 Mbps	39	LE	-10.50	8.0	-18.50
2402	2 Mbps	0	LE	-12.75	8.0	-20.75
2440	2 Mbps	19	LE	-12.57	8.0	-20.57
2480	2 Mbps	39	LE	-13.54	8.0	-21.54

Table 7-6. Conducted Power Density Measurements - Q

FCC ID: A3LSMF711B	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 49 of 87




Plot 7-61. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 0) - Q




Plot 7-62. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 50 of 87




Plot 7-63. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39) - Q




Plot 7-64. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 0) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 51 of 87




Plot 7-67. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q




Plot 7-68. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 53 of 87



Plot 7-71. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 19) - Q



Plot 7-72. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 55 of 87

7.5 Conducted Emissions at the Band Edge

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 56 of 87




Plot 7-73. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 0) - N




Plot 7-74. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 57 of 87




Plot 7-75. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 0) - N




Plot 7-76. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 58 of 87




Plot 7-77. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N




Plot 7-78. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 59 of 87




Plot 7-79. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0) - N




Plot 7-80. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 60 of 87




Plot 7-85. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q




Plot 7-86. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 63 of 87



Plot 7-87. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0) - Q



Plot 7-88. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 64 of 87

7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11.3 of ANSI C63.10-2013.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.5

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 65 of 87


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset	Page 66 of 87




Plot 7-89. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N




Plot 7-90. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 67 of 87




Plot 7-91. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19) - N




Plot 7-92. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 68 of 87




Plot 7-93. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N




Plot 7-94. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) - N

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 69 of 87




Plot 7-95. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q




Plot 7-96. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 70 of 87




Plot 7-97. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19) - Q




Plot 7-98. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 71 of 87



Plot 7-99. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) - Q



Plot 7-100. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39) - Q

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 72 of 87

7.7 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-7 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-7. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

KDB 558074 D01 v05r02 – Section 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3kHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 73 of 87

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-8 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-8. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMF711B	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 74 of 87

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-7.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Average measurements were recorded using a VBW of 3kHz, per Section 4.1.4.2.3 of ANSI C63.10-2013, since 1/T is equal to just under 3kHz. This method was used because the EUT could not be configured to operate with a duty cycle > 98%. Both average and peak measurements were made using a peak detector
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 75 of 87

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	H	174	124	-76.01	3.24	34.23	53.98	-19.75
4804.00	Peak	H	174	124	-65.23	3.24	45.01	73.98	-28.97
12010.00	Avg	H	-	-	-78.86	14.94	43.08	53.98	-10.90
12010.00	Peak	H	-	-	-68.11	14.94	53.83	73.98	-20.15

Table 7-9. Radiated Measurements @ 3 meters- N

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 19

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	H	129	114	-76.84	3.66	33.82	53.98	-20.16
4880.00	Peak	H	129	114	-64.85	3.66	45.81	73.98	-28.17
7320.00	Avg	H	-	-	-78.17	9.12	37.95	53.98	-16.03
7320.00	Peak	H	-	-	-67.27	9.12	48.85	73.98	-25.13
12200.00	Avg	H	-	-	-79.01	13.66	41.65	53.98	-12.33
12200.00	Peak	H	-	-	-68.45	13.66	52.21	73.98	-21.77

Table 7-10. Radiated Measurements @ 3 meters - N

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 76 of 87

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4960.00	Avg	H	-	-	-77.32	4.40	34.08	53.98	-19.90
4960.00	Peak	H	-	-	-66.06	4.40	45.34	73.98	-28.64
7440.00	Avg	H	-	-	-78.03	8.90	37.87	53.98	-16.11
7440.00	Peak	H	-	-	-66.96	8.90	48.94	73.98	-25.04
12400.00	Avg	H	-	-	-82.18	13.41	38.23	53.98	-15.75
12400.00	Peak	H	-	-	-68.54	13.41	51.87	73.98	-22.11

Table 7-11. Radiated Measurements @ 3 meters- N

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 77 of 87

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	V	-	-	-83.25	9.56	33.31	53.98	-20.67
4804.00	Peak	V	-	-	-69.13	9.56	47.43	73.98	-26.55
12010.00	Avg	V	-	-	-86.01	24.11	45.10	53.98	-8.88
12010.00	Peak	V	-	-	-72.83	24.11	58.28	73.98	-15.70

Table 7-12. Radiated Measurements @ 3 meters - Q

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 19

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	V	-	-	-83.63	9.45	32.82	53.98	-21.16
4880.00	Peak	V	-	-	-69.79	9.45	46.66	73.98	-27.32
7320.00	Avg	V	-	-	-85.38	15.78	37.40	53.98	-16.58
7320.00	Peak	V	-	-	-70.59	15.78	52.19	73.98	-21.79
12200.00	Avg	V	-	-	-84.32	23.75	46.43	53.98	-7.55
12200.00	Peak	V	-	-	-72.60	23.75	58.15	73.98	-15.83

Table 7-13. Radiated Measurements @ 3 meters- Q

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 78 of 87

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4960.00	Avg	V	-	-	-80.72	9.87	36.15	53.98	-17.83
4960.00	Peak	V	-	-	-69.90	9.87	46.97	73.98	-27.01
7440.00	Avg	V	-	-	-82.64	16.09	40.45	53.98	-13.53
7440.00	Peak	V	-	-	-71.66	16.09	51.43	73.98	-22.55
12400.00	Avg	V	-	-	-84.00	23.86	46.86	53.98	-7.12
12400.00	Peak	V	-	-	-72.27	23.86	58.59	73.98	-15.39

Table 7-14. Radiated Measurements @ 3 meters- Q

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 79 of 87

7.8 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


Bluetooth Mode:	LE
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	39




Plot 7-101. Radiated Restricted Upper Band Edge Measurement (Average) - N



Plot 7-102. Radiated Restricted Upper Band Edge Measurement (Peak) - N



Plot 7-103. Radiated Restricted Upper Band Edge Measurement (Average) - Q



Plot 7-104. Radiated Restricted Upper Band Edge Measurement (Peak) - Q

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 80 of 87

7.9 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-15. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 81 of 87

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-7. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMF711B	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 82 of 87




Plot 7-105. Line Conducted Plot with Bluetooth LE (L1) – N (OPEN)




Plot 7-106. Line Conducted Plot with Bluetooth LE (N) – N (OPEN)

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 83 of 87




Plot 7-107. Line Conducted Plot with Bluetooth LE (L1) - N (CLOSED)




Plot 7-108. Line Conducted Plot with Bluetooth LE (N) - N (CLOSED)

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 84 of 87




Plot 7-109. Line Conducted Plot with Bluetooth LE (L1) - Q (OPEN)




Plot 7-110. Line Conducted Plot with Bluetooth LE (N) - Q (OPEN)

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 85 of 87



Plot 7-111. Line Conducted Plot with Bluetooth LE (L1) - Q (CLOSED)



Plot 7-112. Line Conducted Plot with Bluetooth LE (N) - Q (CLOSED)

FCC ID: A3LSMF711B	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 86 of 87

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF711B** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: A3LSMF711B		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104130035-08.A3L	Test Dates: 04/12/2021 - 06/04/2021	EUT Type: Portable Handset		Page 87 of 87