


Plot 7-67. Conducted Spurious Plot SISO ANT2 (802.11b – Ch. 6)



Plot 7-68. Conducted Spurious Plot SISO ANT2 (802.11b – Ch. 6)

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 59 of 88

7.7 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-12 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3
KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 61 of 88

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-12.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 62 of 88

8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 63 of 88

7.7.1 SISO Antenna-2 Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-71. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 1) – OPEN




Plot 7-72. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 6) – OPEN




Plot 7-73. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 11) – OPEN


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 64 of 88



Plot 7-74. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 1) – CLOSED



Plot 7-75. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 6) – CLOSED




Plot 7-76. Radiated Spurious Plot above 1GHz SISO ANT2 (802.11b – Ch. 11) – CLOSED


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 65 of 88

SISO Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-77. Radiated Spurious Plot above 18GHz SISO ANT2- OPEN



Plot 7-78. Radiated Spurious Plot above 18GHz SISO ANT2- CLOSED

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 66 of 88

SISO Antenna-2 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	H	-	-	-79.65	6.80	34.15	53.98	-19.83
4824.00	Peak	H	-	-	-68.41	6.80	45.39	73.98	-28.59
12060.00	Avg	H	-	-	-81.59	18.06	43.47	53.98	-10.51
12060.00	Peak	H	-	-	-69.86	18.06	55.20	73.98	-18.78

Table 7-11. Radiated Measurements SISO ANT2 – OPEN

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2437MHz
 Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	H	-	-	-79.74	7.32	34.58	53.98	-19.40
4874.00	Peak	H	-	-	-68.91	7.32	45.41	73.98	-28.57
7311.00	Avg	H	-	-	-70.88	12.45	48.57	53.98	-5.40
7311.00	Peak	H	-	-	-64.29	12.45	55.16	73.98	-18.81
12185.00	Avg	H	-	-	-81.61	18.35	43.74	53.98	-10.24
12185.00	Peak	H	-	-	-70.24	18.35	55.11	73.98	-18.87

Table 7-12. Radiated Measurements SISO ANT2 - OPEN

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 67 of 88

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	H	-	-	-79.21	7.44	35.23	53.98	-18.75
4924.00	Peak	H	-	-	-68.48	7.44	45.96	73.98	-28.02
7386.00	Avg	H	125	313	-69.54	12.26	49.72	53.98	-4.26
7386.00	Peak	H	125	313	-58.73	12.26	60.53	73.98	-13.45
12310.00	Avg	H	-	-	-82.18	18.69	43.51	53.98	-10.47
12310.00	Peak	H	-	-	-70.90	18.69	54.79	73.98	-19.19

Table 7-13. Radiated Measurements SISO ANT2 - OPEN

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	V	-	-	-79.61	7.44	34.83	53.98	-19.15
4924.00	Peak	V	-	-	-68.25	7.44	46.19	73.98	-27.79
7386.00	Avg	V	-	-	-80.11	12.26	39.15	53.98	-14.83
7386.00	Peak	V	-	-	-69.12	12.26	50.14	73.98	-23.84
12310.00	Avg	V	-	-	-82.30	18.69	43.39	53.98	-10.59
12310.00	Peak	V	-	-	-71.31	18.69	54.38	73.98	-19.60

Table 7-14. Radiated Measurements SISO ANT2 with WCP


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 68 of 88

7.7.2 CDD Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-79. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 1) – OPEN




Plot 7-80. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 6) – OPEN




Plot 7-81. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 11) – OPEN


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 69 of 88



Plot 7-82. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 1) – CLOSED



Plot 7-83. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 6) – CLOSED




Plot 7-84. Radiated Spurious Plot above 1GHz CDD (802.11b – Ch. 11) – CLOSED


<p>FCC ID: A3LSMF711B1</p>		<p>MEASUREMENT REPORT (CERTIFICATION)</p>	 <p>Approved by: Technical Manager</p>
<p>Test Report S/N: 1M2108160097-07.A3L</p>	<p>Test Dates: 04/12/2021 – 06/26/2021</p>	<p>EUT Type: Portable Handset</p>	<p>Page 70 of 88</p>

CDD Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-85. Radiated Spurious Plot above 18GHz CDD – OPEN



Plot 7-86. Radiated Spurious Plot above 18GHz CDD – CLOSED

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 71 of 88

MIMO/CDD Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	H	154	41	-66.86	6.80	46.94	53.98	-7.04
4824.00	Peak	H	154	41	-62.55	6.80	51.25	73.98	-22.73
12060.00	Avg	H	-	-	-81.73	18.06	43.33	53.98	-10.65
12060.00	Peak	H	-	-	-70.80	18.06	54.26	73.98	-19.72

Table 7-15. Radiated Measurements CDD – OPEN

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2437MHz
 Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	H	152	33	-70.86	7.32	43.46	53.98	-10.52
4874.00	Peak	H	152	33	-65.09	7.32	49.23	73.98	-24.75
7311.00	Avg	H	-	-	-80.13	12.45	39.32	53.98	-14.65
7311.00	Peak	H	-	-	-69.37	12.45	50.08	73.98	-23.89
12185.00	Avg	H	-	-	-81.86	18.35	43.49	53.98	-10.49
12185.00	Peak	H	-	-	-70.97	18.35	54.38	73.98	-19.60

Table 7-16. Radiated Measurements CDD – OPEN

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 72 of 88

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	147	35	-68.85	7.44	45.59	53.98	-8.39
4924.00	Peak	H	147	35	-63.77	7.44	50.67	73.98	-23.31
7386.00	Avg	H	-	-	-80.20	12.26	39.06	53.98	-14.92
7386.00	Peak	H	-	-	-69.38	12.26	49.88	73.98	-24.10
12310.00	Avg	H	-	-	-82.21	18.69	43.48	53.98	-10.50
12310.00	Peak	H	-	-	-71.01	18.69	54.68	73.98	-19.30

Table 7-17. Radiated Measurements CDD – OPEN

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	V	300	44	-70.88	7.44	43.56	53.98	-10.42
4924.00	Peak	V	300	44	-64.80	7.44	49.64	73.98	-24.34
7386.00	Avg	V	101	349	-73.97	12.26	45.29	53.98	-8.69
7386.00	Peak	V	101	349	-65.43	12.26	53.83	73.98	-20.15
12310.00	Avg	V	-	-	-81.90	18.69	43.79	53.98	-10.19
12310.00	Peak	V	-	-	-70.80	18.69	54.89	73.98	-19.09


Table 7-18. Radiated Measurements CDD with WCP

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 73 of 88


7.7.3 SISO Antenna-2 Radiated Restricted Band Edge Measurements §15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Worst Case Orientation:	Open
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




Plot 7-87. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Average)




Plot 7-88. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Peak)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Worst Case Orientation:	Open
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11




Plot 7-89. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)




Plot 7-90. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 74 of 88

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Worst Case Orientation: Open
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12




Plot 7-91. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Average)




Plot 7-92. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Peak)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Worst Case Orientation: Open
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13



Plot 7-93. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)



Plot 7-94. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)


FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 75 of 88

7.7.5 MIMO Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11g
Worst Case Transfer Rate:	6 Mbps
Worst Case Orientation:	Open
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




Plot 7-95. Radiated Restricted Lower Band Edge Measurement MIMO (Average)




Plot 7-96. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)

Worst Case Mode:	802.11g
Worst Case Transfer Rate:	6 Mbps
Worst Case Orientation:	Open
Distance of Measurements:	3 Meters
Operating Frequency:	2462MHz
Channel:	11




Plot 7-97. Radiated Restricted Upper Band Edge Measurement MIMO (Average)




Plot 7-98. Radiated Restricted Upper Band Edge Measurement MIMO (Peak)

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 76 of 88

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Worst Case Orientation: Open
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12




Plot 7-99. Radiated Restricted Lower Band Edge Measurement MIMO (Average)




Plot 7-100. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MSC0
 Worst Case Orientation: Open
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13




Plot 7-101. Radiated Restricted Upper Band Edge Measurement MIMO (Average)




Plot 7-102. Radiated Restricted Upper Band Edge Measurement MIMO (Peak)

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset	Page 77 of 88	

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Worst Case Orientation: Open
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 1



Plot 7-103. Radiated Restricted Band Edge Measurement MIMO with WCP (Average)



Plot 7-104. Radiated Restricted Band Edge Measurement MIMO with WCP (Peak)

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset	Page 78 of 88

7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-29 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-19. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 79 of 88

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz


<p>FCC ID: A3LSMF711B1</p>		<p>MEASUREMENT REPORT (CERTIFICATION)</p>	<p>Approved by: Technical Manager</p>
<p>Test Report S/N: 1M2108160097-07.A3L</p>	<p>Test Dates: 04/12/2021 – 06/26/2021</p>	<p>EUT Type: Portable Handset</p>	<p>Page 80 of 88</p>

Test Notes


1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-29.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset	Page 81 of 88

MIMO Radiated Spurious Emissions Measurements (Below 1GHz)
§15.209; RSS-Gen [8.9]



Plot 7-105. Radiated Spurious Plot below 1GHz MIMO – OPEN



Plot 7-106. Radiated Spurious Plot below 1GHz MIMO – CLOSED

FCC ID: A3LSMF711B1	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 82 of 88

7.9 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-20. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 83 of 88

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
3. $Corr. (dB) = Cable\ loss (dB) + LISN\ insertion\ factor (dB)$
4. $QP/AV\ Level (dB\mu V) = QP/AV\ Analyzer/Receiver\ Level (dB\mu V) + Corr. (dB)$
5. $Margin (dB) = QP/AV\ Limit (dB\mu V) - QP/AV\ Level (dB\mu V)$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.
8. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset	Page 84 of 88




Plot 7-107. Line Conducted Plot with 802.11b (L1) – OPEN




Plot 7-108. Line Conducted Plot with 802.11b (N) – OPEN

FCC ID: A3LSMF711B1	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 85 of 88




Plot 7-109. Line Conducted Plot with 802.11b (L1) – CLOSED




Plot 7-110. Line Conducted Plot with 802.11b (N) – CLOSED

FCC ID: A3LSMF711B1	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 86 of 88



Plot 7-111. Line Conducted Plot with 802.11b (L1) with WCP




Plot 7-112. Line Conducted Plot with 802.11b with WCP

FCC ID: A3LSMF711B1	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset		Page 87 of 88

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF711B1** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: A3LSMF711B1		MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2108160097-07.A3L	Test Dates: 04/12/2021 – 06/26/2021	EUT Type: Portable Handset	Page 88 of 88