

APPENDIX G POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

G.1 Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

G.2 Distance Verification Procedure

The distance verification procedure was performed according to the following procedure:

1. A base station simulator was used to establish an RF connection and to monitor the power levels. The device being tested was placed below the relevant section of the phantom with the relevant side or edge of the device facing toward the phantom.
2. The device was moved toward and away from the phantom to determine the distance at which the mechanism triggers and the output power is reduced, per KDB Publication 616217 D04v01r02 and FCC Guidance. Each applicable test position was evaluated. The distances were confirmed to be the same or larger (more conservative) than the minimum distances provided by the manufacturer.
3. Steps 1 and 2 were repeated for low, mid, and high bands, as appropriate (see note below Table G-2 for more details).
4. Steps 1 through 3 were repeated for all distance-based power reduction mechanisms.

FCC ID: A3LSMF711JPN	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	Reviewed by: Quality Manager
Test Dates: 06/28/2021-07/31/2021	DUT Type: Portable Handset		APPENDIX G: Page 1 of 4

G.3 Main Antenna Verification Summary


**Table G-1
Power Measurement Verification for Main Antenna**

Mechanism(s)			Mode/Band	Conducted Power (dBm)			
1st	2nd	3rd		Un-triggered (Max)	Mechanism #1 (Reduced)	Mechanism #2 (Reduced)	
Hotspot On	[Redacted]	[Redacted]	UMTS 850	23.85	23.05		
Hotspot On			GPRS 850 3 Tx Slot	29.62	28.51		
Hotspot On			GPRS 1900 3 Tx Slot	25.93	21.10		
Grip			GPRS 1900 3 Tx Slot	25.81	22.90		
Hotspot On			Grip	GPRS 1900 3 Tx Slot	25.83	20.99	20.97
Grip			Hotspot On	GPRS 1900 3 Tx Slot	25.75	22.79	20.88
Hotspot On				LTE Band 5	23.89	23.06	
Hotspot On				LTE Band 4	23.32	18.28	
Grip				LTE Band 4	23.34	20.38	
Hotspot On			Grip	LTE Band 4	23.27	18.44	18.48
Grip			Hotspot On	LTE Band 4	23.35	19.47	18.56
Hotspot On				LTE Band 41	23.88	19.30	
Grip				LTE Band 41	23.89	21.52	
Hotspot On			Grip	LTE Band 41	23.90	19.45	19.46
Grip			Hotspot On	LTE Band 41	23.88	21.56	19.37

**Table G-2
Distance Measurement Verification for Main Antenna**

Mechanism(s)	Test Condition	Band	Distance Measurements (mm)		Minimum Distance per Manufacturer (mm)
			Moving Toward	Moving Away	
Grip	Phablet - Back Side	Mid	15	19	9
Grip	Phablet - Back Side	High	15	18	9
Grip	Phablet - Front Side	Mid	12	15	7
Grip	Phablet - Front Side	High	12	14	7
Grip	Phablet - Bottom Edge	Mid	14	17	12
Grip	Phablet - Bottom Edge	High	14	15	12

*Note: Mid band refers to: GSM1900, LTE B4; High band refers to: LTE B41

FCC ID: A3LSMF711JPN	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT	Reviewed by: Quality Manager
Test Dates: 06/28/2021-07/31/2021	DUT Type: Portable Handset		APPENDIX G: Page 2 of 4

G.4 WIFI Verification Summary

**Table G-3
Power Measurement Verification WIFI Antenna 1**


Mechanism(s)	Mode/Band	Conducted Power (dBm)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	17.51	11.64
Held-to-Ear	802.11g	16.08	11.23
Held-to-Ear	802.11n (2.4GHz)	16.01	11.05
Held-to-Ear	802.11a	15.30	8.98
Held-to-Ear	802.11n (5GHz, 20MHz BW)	14.80	8.29
Held-to-Ear	802.11ac (20MHz BW)	14.85	8.23
Held-to-Ear	802.11n (5GHz, 40MHz BW)	14.08	8.05
Held-to-Ear	802.11ac (40MHz BW)	14.15	8.25
Held-to-Ear	802.11ac (80MHz BW)	13.76	8.12

*Note: MIMO WIFI modes were not evaluated due to equipment limitations.

**Table G-4
Power Measurement Verification WIFI Antenna 2**

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	18.14	12.97
Held-to-Ear	802.11g	16.87	11.94
Held-to-Ear	802.11n (2.4GHz)	16.37	11.16
Held-to-Ear	802.11a	17.03	9.96
Held-to-Ear	802.11n (5GHz, 20MHz BW)	16.82	9.65
Held-to-Ear	802.11ac (20MHz BW)	16.87	9.72
Held-to-Ear	802.11n (5GHz, 40MHz BW)	15.96	9.51
Held-to-Ear	802.11ac (40MHz BW)	15.92	9.64
Held-to-Ear	802.11ac (80MHz BW)	15.26	9.41

*Note: MIMO WIFI modes were not evaluated due to equipment limitations.

FCC ID: A3LSMF711JPN	 SAR EVALUATION REPORT	Reviewed by: Quality Manager
Test Dates: 06/28/2021-07/31/2021	DUT Type: Portable Handset	APPENDIX G: Page 3 of 4

G.5 Bluetooth Verification Summary

**Table G-5
Power Measurement Verification Bluetooth**

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered (Max)	Mechanism #2 RCV Active (Reduced)
1st			
Held-to-Ear	Bluetooth Ant 1	15.07	9.18
Held-to-Ear	Bluetooth Ant 2	15.86	9.55

FCC ID: A3LSMF711JPN	 SAR EVALUATION REPORT	Reviewed by: Quality Manager
Test Dates: 06/28/2021-07/31/2021	DUT Type: Portable Handset	APPENDIX G: Page 4 of 4