



Plot 7-489. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 48)




Plot 7-490. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 319 of 413




Plot 7-491. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 46)




Plot 7-492. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 42)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 320 of 413




Plot 7-493. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 52)




Plot 7-494. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 321 of 413




Plot 7-495. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 64)




Plot 7-496. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 322 of 413




Plot 7-497. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 62)




Plot 7-498. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 323 of 413




Plot 7-499. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 100)




Plot 7-500. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 120)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 324 of 413




Plot 7-501. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 144)




Plot 7-502. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 102)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 325 of 413




Plot 7-503. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 118)




Plot 7-504. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 142)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 326 of 413




Plot 7-505. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 106)




Plot 7-506. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 122)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 327 of 413




Plot 7-507. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 138)




Plot 7-508. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 149)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 328 of 413




Plot 7-509. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 157)




Plot 7-510. Power Spectral Density Plot MIMO ANT1 (20 MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 165)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 329 of 413




Plot 7-511. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 151)



Plot 7-512. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 159)


FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 330 of 413




Plot 7-513. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 155)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 331 of 413

MIMO Antenna-2 Power Spectral Density Measurements (Full Tones) – Q




Plot 7-514. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 36)




Plot 7-515. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 40)

FCC ID: A3LSMF711U	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 332 of 413




Plot 7-516. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 48)




Plot 7-517. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 333 of 413




Plot 7-518. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 46)




Plot 7-519. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 42)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 334 of 413




Plot 7-520. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 52)




Plot 7-521. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 335 of 413




Plot 7-522. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 64)




Plot 7-523. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 336 of 413




Plot 7-524. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 62)




Plot 7-525. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 337 of 413




Plot 7-526. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 100)




Plot 7-527. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 120)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 338 of 413




Plot 7-528. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 144)




Plot 7-529. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 102)

FCC ID: A3LSMF711U	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 339 of 413




Plot 7-530. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 118)




Plot 7-531. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 142)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 340 of 413




Plot 7-532. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 106)




Plot 7-533. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 122)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 341 of 413




Plot 7-534. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 138)




Plot 7-535. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 149)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 342 of 413




Plot 7-536. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 157)




Plot 7-537. Power Spectral Density Plot MIMO ANT2 (20 MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 165)

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 343 of 413




Plot 7-538. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 151)



Plot 7-539. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 159)

FCC ID: A3LSMF711U	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 344 of 413



Plot 7-540. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 155)

FCC ID: A3LSMF711U	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 345 of 413

7.6 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 26 Tones, 52 Tones, 106 Tones, 242 Tones, 484 Tones and 996 Tones), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-94 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-94. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 346 of 413

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: A3LSMF711U	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 347 of 413

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-94.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-94. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all of the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.6 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: A3LSMF711U	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 348 of 413

7.6.1 MIMO Radiated Spurious Emission Measurements

26 Tones – N




Plot 7-541. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 26 Tones) – Open




Plot 7-542. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 349 of 413




Plot 7-543. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 26 Tones) – Open




Plot 7-544. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 26 Tones) – Open

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 350 of 413




Plot 7-545. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 26 Tones) – Closed




Plot 7-546. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 26 Tones) – Closed

FCC ID: A3LSMF711U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 351 of 413




Plot 7-547. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 26 Tones) – Closed




Plot 7-548. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 26 Tones) - Closed

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 352 of 413

MIMO Radiated Spurious Emissions Measurements (Above 18GHz) – N




Plot 7-549. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 26 Tones) - Open




Plot 7-550. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 26 Tones) - Open

FCC ID: A3LSMF711U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 353 of 413



Plot 7-551. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 26 Tones) - Closed



Plot 7-552. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 26 Tones) - Closed

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset	Page 354 of 413	

MIMO Radiated Spurious Emission Measurements (26 Tones) – N

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	H	122	158	-69.47	15.50	0.00	53.03	68.20	-15.17
* 15540.00	Average	H	-	-	-82.52	22.68	0.00	47.16	53.98	-6.82
* 15540.00	Peak	H	-	-	-71.59	22.68	0.00	58.09	73.98	-15.89
* 20720.00	Average	H	-	-	-66.76	4.48	-9.54	35.18	53.98	-18.80
* 20720.00	Peak	H	-	-	-56.70	4.48	-9.54	45.24	73.98	-28.74
25900.00	Peak	H	-	-	-55.99	6.92	-9.54	48.38	68.20	-19.82

Table 7-95. Radiated Measurements MIMO (26 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	H	232	238	-68.09	15.52	0.00	54.43	68.20	-13.77
* 15600.00	Average	H	-	-	-82.20	22.76	0.00	47.56	53.98	-6.42
* 15600.00	Peak	H	-	-	-71.31	22.76	0.00	58.45	73.98	-15.53
* 20800.00	Average	H	-	-	-66.60	4.88	-9.54	35.74	53.98	-18.24
* 20800.00	Peak	H	-	-	-55.99	4.88	-9.54	46.35	73.98	-27.63
26000.00	Peak	H	-	-	-56.06	7.10	-9.54	48.50	68.20	-19.70

Table 7-96. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 355 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10480.00	Peak	H	109	283	-66.30	15.44	0.00	56.14	68.20	-12.06
* 15720.00	Average	H	-	-	-82.85	22.76	0.00	46.91	53.98	-7.07
* 15720.00	Peak	H	-	-	-71.06	22.76	0.00	58.70	73.98	-15.28
* 20960.00	Average	H	-	-	-67.37	5.01	-9.54	35.09	53.98	-18.89
* 20960.00	Peak	H	-	-	-57.09	5.01	-9.54	45.38	73.98	-28.60
26200.00	Peak	H	-	-	-56.34	6.99	-9.54	48.11	68.20	-20.09

Table 7-97. Radiated Measurements MIMO (26 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10520.00	Peak	H	101	287	-63.23	15.76	0.00	59.53	68.20	-8.67
* 15780.00	Average	H	-	-	-82.10	22.90	0.00	47.80	53.98	-6.18
* 15780.00	Peak	H	-	-	-71.64	22.90	0.00	58.26	73.98	-15.72
* 21040.00	Average	H	-	-	-66.80	4.89	-9.54	35.55	53.98	-18.43
* 21040.00	Peak	H	-	-	-56.06	4.89	-9.54	46.28	73.98	-27.70
26300.00	Peak	H	-	-	-55.98	7.06	-9.54	48.54	68.20	-19.66

Table 7-98. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 356 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10560.00	Peak	H	104	280	-64.10	16.13	0.00	59.03	68.20	-9.17
* 15840.00	Average	H	-	-	-82.09	23.17	0.00	48.08	53.98	-5.90
* 15840.00	Peak	H	-	-	-71.19	23.17	0.00	58.98	73.98	-15.00
* 21120.00	Average	H	-	-	-66.91	5.08	-9.54	35.63	53.98	-18.35
* 21120.00	Peak	H	-	-	-56.65	5.08	-9.54	45.90	73.98	-28.08
26400.00	Peak	H	-	-	-56.42	7.43	-9.54	48.47	68.20	-19.73

Table 7-99. Radiated Measurements MIMO (26 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 10640.00	Average	H	100	287	-75.36	16.06	0.00	47.70	53.98	-6.28
* 10640.00	Peak	H	100	287	-62.97	16.06	0.00	60.09	73.98	-13.89
* 15960.00	Average	H	-	-	-82.55	23.29	0.00	47.74	53.98	-6.24
* 15960.00	Peak	H	-	-	-70.84	23.29	0.00	59.45	73.98	-14.53
* 21280.00	Average	H	-	-	-66.75	5.14	-9.54	35.85	53.98	-18.13
* 21280.00	Peak	H	-	-	-56.68	5.14	-9.54	45.92	73.98	-28.06
26600.00	Peak	H	-	-	-56.14	7.21	-9.54	48.53	68.20	-19.67

Table 7-100. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 357 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	131	13	-78.57	16.78	0.00	45.21	53.98	-8.77
* 11000.00	Peak	H	131	13	-66.57	24.50	0.00	64.93	73.98	-9.05
16500.00	Peak	H	-	-	-71.69	24.50	0.00	59.81	68.20	-8.39
22000.00	Peak	H	-	-	-56.91	5.16	-9.54	45.71	68.20	-22.49
27500.00	Peak	H	-	-	-56.27	7.69	-9.54	48.88	68.20	-19.32

Table 7-101. Radiated Measurements MIMO (26 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	H	289	45	-80.92	17.10	0.00	43.18	53.98	-10.80
* 11200.00	Peak	H	289	45	-70.19	24.47	0.00	61.28	73.98	-12.70
16800.00	Peak	H	-	-	-71.71	24.47	0.00	59.76	68.20	-8.44
* 22400.00	Average	H	-	-	-66.77	5.45	-9.54	36.13	53.98	-17.85
* 22400.00	Peak	H	-	-	-57.04	5.45	-9.54	45.86	73.98	-28.12
28000.00	Peak	H	-	-	-55.83	7.97	-9.54	49.60	68.20	-18.60

Table 7-102. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 358 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11440.00	Average	H	-	-	-82.28	17.95	0.00	42.67	53.98	-11.31
* 11440.00	Peak	H	-	-	-71.41	24.77	0.00	60.36	73.98	-13.62
17160.00	Peak	H	-	-	-72.15	24.77	0.00	59.62	68.20	-8.58
* 22880.00	Average	H	-	-	-66.54	5.43	-9.54	36.35	53.98	-17.63
* 22880.00	Peak	H	-	-	-56.63	5.43	-9.54	46.25	73.98	-27.73
28600.00	Peak	H	-	-	-57.06	8.29	-9.54	48.69	68.20	-19.51

Table 7-103. Radiated Measurements MIMO (26 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-82.27	17.83	0.00	42.56	53.98	-11.42
* 11490.00	Peak	H	-	-	-71.10	25.21	0.00	61.11	73.98	-12.87
17235.00	Peak	H	-	-	-72.61	25.21	0.00	59.60	68.20	-8.60
* 22980.00	Average	H	-	-	-66.57	5.29	-9.54	36.18	53.98	-17.80
* 22980.00	Peak	H	-	-	-55.67	5.29	-9.54	47.08	73.98	-26.90
28725.00	Peak	H	-	-	-56.27	8.24	-9.54	49.42	68.20	-18.78

Table 7-104. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 359 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11570.00	Average	H	-	-	-81.71	17.79	0.00	43.08	53.98	-10.90
* 11570.00	Peak	H	-	-	-70.99	17.79	0.00	53.80	73.98	-20.18
17355.00	Peak	H	-	-	-72.27	26.23	0.00	60.96	68.20	-7.24
23140.00	Peak	H	-	-	-56.56	5.34	-9.54	46.24	68.20	-21.96
28925.00	Peak	H	-	-	-56.05	8.48	-9.54	49.89	68.20	-18.31

Table 7-105. Radiated Measurements MIMO (26 Tones) – Open


Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-81.84	18.05	0.00	43.21	53.98	-10.77
* 11650.00	Peak	H	-	-	-70.61	18.05	0.00	54.44	73.98	-19.54
17475.00	Peak	H	-	-	-72.26	25.87	0.00	60.61	68.20	-7.59
23300.00	Peak	H	-	-	-56.05	5.29	-9.54	46.70	68.20	-21.50
29125.00	Peak	H	-	-	-56.12	8.49	-9.54	49.83	68.20	-18.37


Table 7-106. Radiated Measurements MIMO (26 Tones) – Open

FCC ID: A3LSMF711U	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 360 of 413

242 Tones – N




Plot 7-553. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 242 Tones) – Open




Plot 7-554. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 242 Tones) – Open

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 361 of 413




Plot 7-555. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 242 Tones) – Open




Plot 7-556. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 242 Tones) – Open

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 362 of 413




Plot 7-557. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 242 Tones) – Closed




Plot 7-558. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 242 Tones) – Closed

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 363 of 413




Plot 7-559. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 242 Tones) – Closed




Plot 7-560. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 242 Tones) – Closed

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 364 of 413

MIMO Radiated Spurious Emissions Measurements (Above 18GHz) – N




Plot 7-561. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 242 Tones) - Open




Plot 7-562. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 242 Tones) - Open

FCC ID: A3LSMF711U	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 365 of 413



Plot 7-563. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 242 Tones) - Closed



Plot 7-564. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 242 Tones) - Closed

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset	Page 366 of 413	

MIMO Radiated Spurious Emission Measurements (242 Tones) – N

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	H	379	42	-65.08	15.50	0.00	57.42	68.20	-10.78
* 15540.00	Average	H	-	-	-82.57	22.68	0.00	47.11	53.98	-6.87
* 15540.00	Peak	H	-	-	-71.68	22.68	0.00	58.00	73.98	-15.98
* 20720.00	Average	H	-	-	-67.33	4.48	-9.54	34.60	53.98	-19.38
* 20720.00	Peak	H	-	-	-57.41	4.48	-9.54	44.52	73.98	-29.46
25900.00	Peak	H	-	-	-55.70	6.92	-9.54	48.67	68.20	-19.53

Table 7-107. Radiated Measurements MIMO (242 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	H	367	36	-65.20	15.52	0.00	57.32	68.20	-10.88
* 15600.00	Average	H	-	-	-82.31	22.76	0.00	47.45	53.98	-6.53
* 15600.00	Peak	H	-	-	-71.24	22.76	0.00	58.52	73.98	-15.46
* 20800.00	Average	H	-	-	-66.51	4.88	-9.54	35.83	53.98	-18.14
* 20800.00	Peak	H	-	-	-55.58	4.88	-9.54	46.76	73.98	-27.22
26000.00	Peak	H	-	-	-56.04	7.10	-9.54	48.52	68.20	-19.68

Table 7-108. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 367 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10480.00	Peak	H	285	39	-65.07	15.44	0.00	57.37	68.20	-10.83
* 15720.00	Average	H	-	-	-82.79	22.76	0.00	46.97	53.98	-7.01
* 15720.00	Peak	H	-	-	-71.61	22.76	0.00	58.15	73.98	-15.83
* 20960.00	Average	H	-	-	-67.56	5.01	-9.54	34.91	53.98	-19.07
* 20960.00	Peak	H	-	-	-57.10	5.01	-9.54	45.36	73.98	-28.62
26200.00	Peak	H	-	-	-56.46	6.99	-9.54	47.99	68.20	-20.21

Table 7-109. Radiated Measurements MIMO (242 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10520.00	Peak	H	308	36	-64.49	15.76	0.00	58.27	68.20	-9.93
* 15780.00	Average	H	-	-	-82.35	22.90	0.00	47.55	53.98	-6.43
* 15780.00	Peak	H	-	-	-71.26	22.90	0.00	58.64	73.98	-15.34
* 21040.00	Average	H	-	-	-66.79	4.89	-9.54	35.55	53.98	-18.43
* 21040.00	Peak	H	-	-	-56.57	4.89	-9.54	45.77	73.98	-28.21
26300.00	Peak	H	-	-	-56.09	7.06	-9.54	48.43	68.20	-19.77

Table 7-110. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 368 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	H	383	39	-66.69	16.13	0.00	56.44	68.20	-11.76
* 15840.00	Average	H	-	-	-82.09	23.17	0.00	48.08	53.98	-5.90
* 15840.00	Peak	H	-	-	-70.92	23.17	0.00	59.25	73.98	-14.73
* 21120.00	Average	H	-	-	-67.32	5.08	-9.54	35.22	53.98	-18.76
* 21120.00	Peak	H	-	-	-56.83	5.08	-9.54	45.72	73.98	-28.26
26400.00	Peak	H	-	-	-55.97	7.43	-9.54	48.92	68.20	-19.28

Table 7-111. Radiated Measurements MIMO (242 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	109	41	-78.01	16.06	0.00	45.05	53.98	-8.93
* 10640.00	Peak	H	109	41	-66.81	16.06	0.00	56.25	73.98	-17.73
* 15960.00	Average	H	-	-	-82.57	23.29	0.00	47.72	53.98	-6.26
* 15960.00	Peak	H	-	-	-71.97	23.29	0.00	58.32	73.98	-15.66
* 21280.00	Average	H	-	-	-66.91	5.14	-9.54	35.69	53.98	-18.29
* 21280.00	Peak	H	-	-	-56.60	5.14	-9.54	46.00	73.98	-27.98
26600.00	Peak	H	-	-	-56.04	7.21	-9.54	48.63	68.20	-19.57

Table 7-112. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset	Page 369 of 413	

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11000.00	Average	H	-	-	-81.29	16.78	0.00	42.49	53.98	-11.49
* 11000.00	Peak	H	-	-	-70.08	24.50	0.00	61.42	73.98	-12.56
16500.00	Peak	H	-	-	-71.75	24.50	0.00	59.75	68.20	-8.45
22000.00	Peak	H	-	-	-55.79	5.16	-9.54	46.83	68.20	-21.37
27500.00	Peak	H	-	-	-56.42	7.69	-9.54	48.73	68.20	-19.47

Table 7-113. Radiated Measurements MIMO (242 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11200.00	Average	H	-	-	-81.45	17.10	0.00	42.65	53.98	-11.33
* 11200.00	Peak	H	-	-	-70.21	24.47	0.00	61.26	73.98	-12.72
16800.00	Peak	H	-	-	-72.24	24.47	0.00	59.23	68.20	-8.97
* 22400.00	Average	H	-	-	-66.45	5.45	-9.54	36.46	53.98	-17.52
* 22400.00	Peak	H	-	-	-56.39	5.45	-9.54	46.52	73.98	-27.46
28000.00	Peak	H	-	-	-56.83	7.97	-9.54	48.59	68.20	-19.61

Table 7-114. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 370 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11440.00	Average	H	-	-	-81.22	17.95	0.00	43.73	53.98	-10.25
* 11440.00	Peak	H	-	-	-71.55	24.77	0.00	60.22	73.98	-13.76
17160.00	Peak	H	-	-	-71.57	24.77	0.00	60.20	68.20	-8.00
* 22880.00	Average	H	-	-	-66.63	5.43	-9.54	36.26	53.98	-17.72
* 22880.00	Peak	H	-	-	-56.41	5.43	-9.54	46.47	73.98	-27.51
28600.00	Peak	H	-	-	-56.96	8.29	-9.54	48.78	68.20	-19.42

Table 7-115. Radiated Measurements MIMO (242 Tones) – Open

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-82.30	17.83	0.00	42.53	53.98	-11.45
* 11490.00	Peak	H	-	-	-71.09	25.21	0.00	61.12	73.98	-12.86
17235.00	Peak	H	-	-	-71.79	25.21	0.00	60.42	68.20	-7.78
* 22980.00	Average	H	-	-	-66.87	5.29	-9.54	35.88	53.98	-18.10
* 22980.00	Peak	H	-	-	-56.74	5.29	-9.54	46.01	73.98	-27.97
28725.00	Peak	H	-	-	-56.73	8.24	-9.54	48.97	68.20	-19.23

Table 7-116. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 371 of 413

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	H	-	-	-82.01	17.79	0.00	42.78	53.98	-11.20
* 11570.00	Peak	H	-	-	-70.92	17.79	0.00	53.87	73.98	-20.11
17355.00	Peak	H	-	-	-71.54	26.23	0.00	61.69	68.20	-6.51
23140.00	Peak	H	-	-	-56.15	5.34	-9.54	46.64	68.20	-21.56
28925.00	Peak	H	-	-	-56.88	8.48	-9.54	49.05	68.20	-19.15

Table 7-117. Radiated Measurements MIMO (242 Tones) – Open


Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-82.19	18.05	0.00	42.86	53.98	-11.12
* 11650.00	Peak	H	-	-	-71.23	18.05	0.00	53.82	73.98	-20.16
17475.00	Peak	H	-	-	-71.37	25.87	0.00	61.50	68.20	-6.70
23300.00	Peak	H	-	-	-56.01	5.29	-9.54	46.73	68.20	-21.47
29125.00	Peak	H	-	-	-56.72	8.49	-9.54	49.23	68.20	-18.97


Table 7-118. Radiated Measurements MIMO (242 Tones) – Open

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset	Page 372 of 413	

26 Tones – Q




Plot 7-565. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 26 Tones) – Open




Plot 7-566. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 26 Tones) – Open

FCC ID: A3LSMF711U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 373 of 413




Plot 7-567. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 26 Tones) – Open




Plot 7-568. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 26 Tones) – Open

FCC ID: A3LSMF711U	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 374 of 413




Plot 7-569. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 26 Tones) – Closed




Plot 7-570. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 26 Tones) – Closed

FCC ID: A3LSMF711U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset	Page 375 of 413	



Plot 7-571. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 26 Tones) – Closed



Plot 7-572. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 26 Tones) - Closed

FCC ID: A3LSMF711U	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104070032-15.A3L	Test Dates: 04/12/2021 – 06/04/2021	EUT Type: Portable Handset		Page 376 of 413