

## APPENDIX F: NR LOWER BANDWIDTH RF CONDUCTED POWERS

All conducted power measurements for 5G Sub6 WWAN technologies and bands in this section were performed by setting *Reserve\_power\_margin* (Qualcomm® Smart Transmit EFS entry) to 0 dB, so that the EUT transmits continuously at minimum (P<sub>limit</sub>, maximum tune up output power P<sub>max</sub>).

See the original filling for all NR lower bandwidth RF conducted powers for bands that were not evaluated for this permissive change.



### F.1 NR Lower Bandwidth RF Conducted Powers

#### F.1.1 NR Band n48

**Table F-1**

**NR Band n48 Measured  $P_{Limit}$  for DSI = 0/1 (Body-worn, or Phablet with grip sensor active) and/or DSI = 4 (Earjack Active) - 20 MHz Bandwidth**

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	18.78	18.05	18.82	18.41	0	0.0
	1	26	18.45	18.35	18.87	18.51		0.0
	1	49	18.42	18.55	18.85	18.71		0.0
	25	0	18.67	18.40	18.84	18.50	0-0.5	0.0
	25	13	18.59	18.56	18.97	18.61	0-0.5	0.0
	25	26	18.53	18.60	18.91	18.70		0.0
	50	0	18.59	18.54	18.93	18.61		0.0
DFT-s-OFDM QPSK	1	1	18.76	18.04	18.94	18.64	0	0.0
	1	26	18.56	18.24	19.01	18.62		0.0
	1	49	18.57	18.62	19.00	18.77		0.0
	25	0	18.65	18.19	18.89	18.54	0-1	0.0
	25	13	18.55	18.32	18.99	18.62	0	0.0
	25	26	18.52	18.41	18.97	18.67		0.0
	50	0	18.59	18.26	18.93	18.57		0-1
DFT-s-OFDM 16QAM	1	1	18.58	17.88	18.61	18.36	0-1	0.0
CP-OFDM QPSK	1	1	18.78	18.26	19.00	18.70	0-1.5	0.0



<b>FCC ID</b> A3LSMF711U1	 <small>Head to be part of Samsung</small>	<b>SAR EVALUATION REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Test Dates:</b> 12/14/21 – 12/21/21 & 02/07/22	<b>DUT Type:</b> Portable Handset			APPENDIX F: Page 1 of 4

**Table F-2**  
**NR Band n48 Measured  $P_{Limit}$  for DSI = 0/1 (Body-worn, or Phablet with grip sensor active) and/or DSI = 4 (Earjack Active) - 10 MHz Bandwidth**

NR Band n48 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]	
			637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)			
			Conducted Power [dBm]						
DFT-s-OFDM $\pi/2$ BPSK	1	1	18.80	18.35	18.90	18.64	0	0.0	
	1	12	18.57	18.44	18.91	18.81		0.0	
	1	22	18.57	18.50	18.83	18.92		0.0	
		12	0	18.69	18.40	18.90	18.75	0-0.5	0.0
		12	6	18.56	18.44	18.92	18.80	0	0.0
		12	12	18.54	18.45	18.84	18.86	0-0.5	0.0
		24	0	18.66	18.48	18.92	18.85		0.0
DFT-s-OFDM QPSK	1	1	18.73	18.51	19.05	18.80	0	0.0	
	1	12	18.69	18.56	19.01	18.93		0.0	
	1	22	18.65	18.62	18.95	18.91		0.0	
		12	0	18.71	18.49	18.96	18.80	0-1	0.0
		12	6	18.64	18.52	18.96	18.82	0	0.0
		12	12	18.59	18.48	18.90	18.92	0-1	0.0
		24	0	18.66	18.49	18.96	18.87		0.0
DFT-s-OFDM 16QAM	1	1	18.60	18.23	18.75	18.50	0-1	0.0	
CP-OFDM QPSK	1	1	18.74	18.60	19.15	18.84	0-1.5	0.0	

**Table F-3**  
**NR Band n48 Measured  $P_{Limit}$  for DSI = 2 (Head) - 20 MHz Bandwidth**

NR Band n48 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]	
			637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)			
			Conducted Power [dBm]						
DFT-s-OFDM $\pi/2$ BPSK	1	1	15.24	15.18	15.13	15.28	0	0.0	
	1	26	15.20	15.09	15.08	15.28		0.0	
	1	49	15.37	15.18	15.18	15.38		0.0	
		25	0	15.29	15.20	15.14	15.37	0-0.5	0.0
		25	13	15.39	15.22	15.18	15.35	0	0.0
		25	26	15.40	15.18	15.20	15.41	0-0.5	0.0
		50	0	15.38	15.18	15.16	15.37		0.0
DFT-s-OFDM QPSK	1	1	15.33	15.24	15.23	15.39	0	0.0	
	1	26	15.27	15.17	15.15	15.37		0.0	
	1	49	15.45	15.23	15.21	15.48		0.0	
		25	0	15.28	15.18	15.12	15.35	0-1	0.0
		25	13	15.39	15.19	15.14	15.36	0	0.0
		25	26	15.40	15.16	15.17	15.41	0-1	0.0
		50	0	15.35	15.18	15.14	15.37		0.0
DFT-s-OFDM 16QAM	1	1	15.29	15.21	15.08	15.36	0-1	0.0	
CP-OFDM QPSK	1	1	15.37	15.14	15.11	15.30	0-1.5	0.0	



FCC ID A3LSMF711U1	 <b>PCTEST</b> <small>Head to be part of Samsung</small>	<b>SAR EVALUATION REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Test Dates:</b> 12/14/21 – 12/21/21 & 02/07/22	<b>DUT Type:</b> Portable Handset			APPENDIX F: Page 2 of 4

**Table F-4**  
**NR Band n48 Measured  $P_{Limit}$  for DSI = 2 (Head) - 10 MHz Bandwidth**

NR Band n48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	15.30	15.04	15.10	15.28	0	0.0
	1	12	15.32	15.05	15.11	15.34		0.0
	1	22	15.28	15.08	15.08	15.32		0.0
	12	0	15.28	15.06	15.07	15.30	0-0.5	0.0
	12	6	15.33	15.04	15.10	15.36	0	0.0
	12	12	15.30	15.03	15.11	15.34	0-0.5	0.0
	24	0	15.30	15.01	15.05	15.36		0.0
DFT-s-OFDM QPSK	1	1	15.37	15.04	15.16	15.38	0	0.0
	1	12	15.38	15.08	15.13	15.40		0.0
	1	22	15.34	15.11	15.18	15.39		0.0
	12	0	15.31	15.03	15.07	15.31	0-1	0.0
	12	6	15.33	15.07	15.11	15.37	0	0.0
	12	12	15.32	15.05	15.14	15.35	0-1	0.0
	24	0	15.31	15.03	15.07	15.33		0.0
DFT-s-OFDM 16QAM	1	1	15.36	15.03	15.10	15.34	0-1	0.0
CP-OFDM QPSK	1	1	15.32	14.98	15.05	15.31	0-1.5	0.0



**Table F-5**  
**NR Band n48 Measured  $P_{Limit}$  for DSI = 3 (Hotspot) - 20 MHz Bandwidth**

NR Band n48 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.44	17.57	17.65	17.83	0	0.0
	1	26	17.37	17.59	17.42	17.84		0.0
	1	49	17.56	17.78	17.39	17.94		0.0
	25	0	17.47	17.55	17.54	17.83	0-0.5	0.0
	25	13	17.50	17.58	17.45	17.83	0	0.0
	25	26	17.53	17.70	17.37	17.85	0-0.5	0.0
	50	0	17.51	17.57	17.46	17.85		0.0
DFT-s-OFDM QPSK	1	1	17.56	17.55	17.70	17.84	0	0.0
	1	26	17.51	17.57	17.44	17.82		0.0
	1	49	17.68	17.78	17.39	17.88		0.0
	25	0	17.50	17.48	17.54	17.80	0-1	0.0
	25	13	17.51	17.52	17.45	17.86	0	0.0
	25	26	17.52	17.70	17.38	17.84	0-1	0.0
	50	0	17.54	17.55	17.48	17.86		0.0
DFT-s-OFDM 16QAM	1	1	17.61	17.55	17.74	17.91	0-1	0.0
CP-OFDM QPSK	1	1	17.38	17.29	17.46	17.84	0-1.5	0.0

FCC ID A3LSMF711U1	 <b>PCTEST</b> <small>Head to be part of @ Samsung</small>	<b>SAR EVALUATION REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Test Dates:</b> 12/14/21 – 12/21/21 & 02/07/22	<b>DUT Type:</b> Portable Handset			APPENDIX F: Page 3 of 4

**Table F-6**  
**NR Band n48 Measured  $P_{Limit}$  for DSI = 3 (Hotspot) - 10 MHz Bandwidth**

NR Band n48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM $\pi/2$ BPSK	1	1	17.40	17.49	17.37	17.67	0	0.0
	1	12	17.40	17.57	17.38	17.71		0.0
	1	22	17.42	17.57	17.38	17.72		0.0
	12	0	17.34	17.52	17.28	17.69	0-0.5	0.0
	12	6	17.37	17.54	17.31	17.68	0	0.0
	12	12	17.38	17.54	17.27	17.70	0-0.5	0.0
	24	0	17.40	17.55	17.28	17.69		0.0
DFT-s-OFDM QPSK	1	1	17.45	17.49	17.39	17.70	0	0.0
	1	12	17.44	17.61	17.38	17.72		0.0
	1	22	17.48	17.63	17.42	17.72		0.0
	12	0	17.35	17.54	17.33	17.67	0-1	0.0
	12	6	17.37	17.53	17.27	17.71	0	0.0
	12	12	17.36	17.55	17.24	17.76	0-1	0.0
	24	0	17.36	17.55	17.27	17.72		0.0
DFT-s-OFDM 16QAM	1	1	17.49	17.52	17.77	18.09	0-1	0.0
CP-OFDM QPSK	1	1	17.23	17.31	17.36	17.84	0-1.5	0.0

<b>FCC ID</b> A3LSMF711U1	 <b>PCTEST</b> <small>Proved to be part of Samsung</small>	<b>SAR EVALUATION REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Test Dates:</b> 12/14/21 – 12/21/21 & 02/07/22	<b>DUT Type:</b> Portable Handset			APPENDIX F: Page 4 of 4