

Element Suwon

13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954 South Korea Tel. 031.660.7319 / Fax 031.660.7318 http://www.element.com



PART 27 MEASUREMENT REPORT

Applicant Name:

Samsung Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, 16677, Korea **Date of Testing:**

6/17/2022 - 07/07/2022 **Test Report Issue Date:**

07/22/2022

Test Site/Location:

Element Lab. Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.: 1M2206140073-03.A3L

FCC ID: A3LSMF721JPN

Applicant Name: Samsung Electronics Co., Ltd.

Application Type:CertificationModel:SC-54CAdditional Model(s):SCG17

EUT Type: Portable Handset

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part: 27

Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168

D01 v03r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.





13

Prepared by

Reviewed by

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 1 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 1 of 85



TABLE OF CONTENTS

1.0	INTF	RODUCTION	4
	1.1	Scope	4
	1.2	Element Test Location	4
	1.3	Test Facility / Accreditations	4
2.0	PRC	DDUCT INFORMATION	5
	2.1	Equipment Description	5
	2.2	Device Capabilities	5
	2.3	Test Configuration	5
	2.4	Software and Firmware	5
	2.5	EMI Suppression Device(s)/Modifications	5
3.0	DES	SCRIPTION OF TESTS	6
	3.1	Evaluation Procedure	6
	3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEA	ASUREMENT UNCERTAINTY	7
5.0	TES	T EQUIPMENT CALIBRATION DATA	8
6.0	SAM	IPLE CALCULATIONS	9
7.0	TES	T RESULTS	10
	7.1	Summary	10
	7.2	Occupied Bandwidth	12
	7.3	Spurious and Harmonic Emissions at Antenna Terminal	25
	7.4	Band Edge Emissions at Antenna Terminal	38
	7.5	Peak-Average Ratio	60
	7.6	Radiated Power (ERP/EIRP)	67
	7.7	Radiated Spurious Emissions Measurements	70
	7.8	Frequency Stability / Temperature Variation	81
8.0	CON	NCLUSION	85

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 2 of 95	
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 2 of 85	



PART 27 MEASUREMENT REPORT

		Modulation		El	RP.	EII	RP	
Mode	Bandwidth		Tx Frequency Range [MHz]	Max. Power [W]	Max. Power [dBm]	Max. Power [W]	Max. Power [dBm]	Emission Designator
	10 MHz	QPSK	704.0 - 711.0	0.080	19.02	0.131	21.17	9M04G7D
	IU IVITZ	16QAM	704.0 - 711.0	0.067	18.26	0.110	20.41	9M03W7D
	5 MHz	QPSK	701.5 - 713.5	0.081	19.09	0.133	21.24	4M54G7D
LTE Band 12		16QAM	701.5 - 713.5	0.070	18.42	0.114	20.57	4M55W7D
LIE Dallu 12	3 MHz	QPSK	700.5 - 714.5	0.081	19.07	0.132	21.22	2M73G7D
		16QAM	700.5 - 714.5	0.067	18.27	0.110	20.42	2M73W7D
	1.4 MHz	QPSK	699.7 - 715.3	0.080	19.04	0.132	21.19	1M11G7D
		16QAM	699.7 - 715.3	0.064	18.04	0.104	20.19	1M11W7D
	10 MHz	QPSK	782.0	0.064	18.03	0.104	20.18	9M04G7D
LTE Dand 12	IU IVITZ	16QAM	782.0	0.054	17.32	0.089	19.47	9M05W7D
LTE Band 13	5 MHz	QPSK	779.5 - 784.5	0.063	17.96	0.103	20.11	4M57G7D
	O IVITZ	16QAM	779.5 - 784.5	0.054	17.29	0.088	19.44	4M56W7D

Overview Table (<1GHz Bands)

				EI	RP	
Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Max. Power [W]	Max. Power [dBm]	Emission Designator
	20 MHz	QPSK	1720.0 - 1745.0	0.126	21.01	18M1G7D
	20 1011 12	16QAM	1720.0 - 1745.0	0.119	20.76	18M0W7D
	15 MHz	QPSK	1717.5 - 1747.5	0.128	21.08	13M6G7D
		16QAM	1717.5 - 1747.5	0.121	20.84	13M5W7D
	10 MHz	QPSK	1715.0 - 1750.0	0.131	21.18	9M06G7D
LTE Band 4		16QAM	1715.0 - 1750.0	0.122	20.86	9M04W7D
LI E Ballu 4	5 MHz	QPSK	1712.5 - 1752.5	0.130	21.15	4M54G7D
		16QAM	1712.5 - 1752.5	0.119	20.76	4M53W7D
	3 MHz	QPSK	1711.5 - 1753.5	0.131	21.17	2M72G7D
	3 IVITZ	16QAM	1711.5 - 1753.5	0.119	20.77	2M71W7D
	1.4 MHz	QPSK	1710.7 - 1754.3	0.128	21.08	1M11G7D
	1.4 (VITIZ	16QAM	1710.7 - 1754.3	0.117	20.67	1M10W7D

Overview Table (>1GHz Bands)

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT	
Test Report S/N:	Test Dates:	EUT Type:	Page 3 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 3 01 65



1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element Suwon Laboratory located at 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954, South Korea. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea.

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.
 - Designation Number / CABID: KR0169
 - Test Firm Registration Number of FCC: 417945
 - Test Firm Registration Number of ISED: 26168

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 4 of 95	
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 4 of 85	



2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMF721JPN**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22 and RSS-132.

Test Device Serial No.: 1185M, 1186M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

This device supports two configurations: one is with screen open and one is with screen closed. Open, half opened and closed configurations are tested, and the worst case radiated emissions data is shown in this report.

2.4 Software and Firmware

Testing was performed on device(s) using software/firmware version SC54COMU0AVFF installed on the EUT.

2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT	
Test Report S/N:	Test Dates:	EUT Type:	Page 5 of 85
1M2206140073-03.A3L	06/17/2022 – 07/07/2022	Portable Handset	Fage 5 01 65



3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the "American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services" (ANSI C63.26-2015) were used in the measurement of the EUT.

Deviation from Measurement ProcedureNone

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI C63.26-2015. For emissions below 1GHz, a half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

 $P_{d [dBm]} = P_{g [dBm]} - cable loss_{[dB]} + antenna gain_{[dBd/dBi]};$ where P_{d} is the dipole equivalent power, P_{g} is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_{g [dBm]} - cable loss_{[dB]}$.

For radiated spurious emissions measurements, the field strength conversion method is used per the formulas in Section 5.2.7 of ANSI C63.26-2015. Field Strength (EIRP) is calculated using the following formulas:

 $E_{[dB\mu V/m]}$ = Measured amplitude level_[dBm] + 107 + Cable Loss_[dB] + Antenna Factor_[dB/m] And $EIRP_{[dBm]} = E_{[dB\mu V/m]} + 20logD - 104.8$; where D is the measurement distance in meters.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT		
Test Report S/N:	Test Dates:	EUT Type:	Dogo 6 of 95	
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 6 of 85	



4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (±dB)
Conducted Bench Top Measurements	1.60
Radiated Disturbance (<1GHz)	3.94
Radiated Disturbance (>1GHz)	4.75
Radiated Disturbance (>18GHz)	3.08

FCC ID: A3LSMF721JPN		PART 27 MEASUREMENT REPORT	
Test Report S/N:	Test Dates:	EUT Type:	Dogo 7 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 7 of 85



5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9030A	PXA Signal Analyzer	2022-07-04	Annual	2023-07-03	MY49432391
Anritsu	S820E	Cable and Antenna Analyzer	2022-07-06	Annual	2023-07-05	1839097
Anritsu	MA24106A	USB Power Sensor	2022-07-06	Annual	2023-07-05	1244512
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	2020-10-29	Biennial	2022-10-28	10160045
Com-Power	PAM-118A	Preamplifier	2022-07-06	Annual	2023-07-05	551042
Espec	SH-242	Environmental Chamber	2021-09-15	Annual	2022-09-14	93011064
Fairview Microwave	FM2CP1122-10	Coupler	2022-07-06	Annual	2023-07-05	1946
Keysight Technologies	N9030B	MXA Signal Analyzer	2022-05-10	Annual	2023-05-19	MY57142018
Mini Circuits	ZUDC10-83-S+	Coupler	2021-09-15	Annual	2022-09-14	2111
Mini-Circuits	BW-N10W5+	Attenuator	2022-05-09	Annual	2023-05-08	1607
Mini-Circuits	BW-N10W5+	Attenuator	2022-05-09	Annual	2023-05-08	1607
Rohde & Schwarz	TS-PR18	Preamplifier	2022-07-06	Annual	2023-07-05	102141
Rohde & Schwarz	SMBV100B	Signal Generator	2021-11-04	Annual	2022-11-03	101568
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2022-02-18	Annual	2023-02-17	131453
Rohde & Schwarz	ESW	EMI Test Receiver	2022-07-04	Annual	2023-07-03	101761
Rohde & Schwarz	FSW43	Signal & Spectrum Analyzer	2021-09-15	Annual	2022-09-14	101250
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2022-02-18	Annual	2023-02-17	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2022-03-28	Annual	2023-03-27	102151
Schwarzbeck	VULB9162	Broadband TRILOG Antenna	2021-07-13	Biennial	2023-07-12	9162-217
Schwarzbeck	UHA9105	Dipole Antenna	2020-07-09	Biennial	2022-07-08	91052522
Sunol	DRH-118	Horn Antenna	2021-07-14	Biennial	2023-07-13	A102416-1
Sunol	DRH-118	Horn Antenna	2021-01-12	Biennial	2023-01-11	A060215

Table 5-1. Test Equipment

Notes:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 8 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 6 01 65



6.0 SAMPLE CALCULATIONS

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz G = Phase Modulation 7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm – (-24.80) = 50.3 dBc.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 9 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 9 01 00



TEST RESULTS

7.1 **Summary**

Company Name: Samsung Electronics Co., Ltd.

FCC ID: A3LSMF721JPN

PCS Licensed Transmitter Held to Ear (PCE) FCC Classification:

Mode(s): <u>LTE</u>

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
	Occupied Bandwidth	2.1049(h)	N/A	PASS	Section 7.2
	Conducted Band Edge / Spurious Emissions (LTE Band 13)	2.1051, 27.53(c), 27.53(f)	Undesirable emissions must meet the limits detailed in sections 27.53(c) and 27.53(f)	PASS	Sections 7.3, 7.4
CONDUCTED	Conducted Band Edge / Spurious Emissions (LTE Band 12)	2.1051, 27.53(g)	≥ 43 + 10 log (P[Watts]) dB of attenuation below transmitter power	PASS	Sections 7.3, 7.4
CONDI	Conducted Band Edge / Spurious Emissions (LTE Band 4)	2.1051, 27.53(h)	≥ 43 + 10 log (P[Watts]) dB of attenuation below transmitter power	PASS	Sections 7.3, 7.4
	Peak-to-Average Ratio (LTE Band 4)	27.50(d)(5)	≤ 13 dB	PASS	Section 7.5
	Frequency Stability	2.1055, 27.54	Fundamental emissions stay within authorized frequency block	PASS	Section 7.8
	Effective Radiated Power (LTE Band 13)	27.50(b)(10)	≤ 3 Watts max. ERP	PASS	Section 7.6
	Effective Radiated Power (LTE Band 12)	27.50(c)(10)	≤ 3 Watts max. ERP	PASS	Section 7.6
RADIATED	Equivalent Isotropic Radiated Power (LTE Band 4)	27.50(d)(10)	≤ 1 Watt max. EIRP	PASS	Section 7.6
RADI	Radiated Spurious Emissions (LTE Band 13)	2.1053, 27.53(c), 27.53(f)	Undesirable emissions must meet the limits detailed in sections 27.53(c) and 27.53(f)	PASS	Section 7.7
	Radiated Spurious Emissions (LTE Band 12)	2.1053, 27.53(g)	≥ 43 + 10 log (P[Watts]) dB of attenuation below transmitter power	PASS	Section 7.7
	Radiated Spurious Emissions (LTE Band 4)	2.1053, 27.53(h)	≥ 43 + 10 log (P[Watts]) dB of attenuation below transmitter power	PASS	Section 7.7

Table 7-1. Summary of Test Results

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 10 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 10 01 65



Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is EMC Software Tool v1.0.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 11 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 11 01 05



7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 - Section 5.4.4

Test Settings

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2-7 were repeated after changing the RBW such that it would be within
 - 1-5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 12 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 12 01 05





Plot 7-1. Occupied Bandwidth Plot (LTE Band 12 - 10MHz QPSK - Full RB)



Plot 7-2. Occupied Bandwidth Plot (LTE Band 12 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 13 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 13 01 05





Plot 7-3. Occupied Bandwidth Plot (LTE Band 12 - 5MHz QPSK - Full RB)



Plot 7-4. Occupied Bandwidth Plot (LTE Band 12 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 14 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 14 01 05





Plot 7-5. Occupied Bandwidth Plot (LTE Band 12 - 3MHz QPSK - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 12 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 15 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 15 01 65





Plot 7-7. Occupied Bandwidth Plot (LTE Band 12 - 1.4MHz QPSK - Full RB)



Plot 7-8. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 16 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 10 01 05





Plot 7-9. Occupied Bandwidth Plot (LTE Band 13 - 10MHz QPSK - Full RB)



Plot 7-10. Occupied Bandwidth Plot (LTE Band 13 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 17 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 17 01 00





Plot 7-11. Occupied Bandwidth Plot (LTE Band 13 - 5MHz QPSK - Full RB)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 13 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 18 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 16 01 65






Plot 7-13. Occupied Bandwidth Plot (LTE Band 4 - 20MHz QPSK - Full RB)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 4 - 20MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 19 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 19 01 05





Plot 7-15. Occupied Bandwidth Plot (LTE Band 4 - 15MHz QPSK - Full RB)



Plot 7-16. Occupied Bandwidth Plot (LTE Band 4 - 15MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 20 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 20 01 05





Plot 7-17. Occupied Bandwidth Plot (LTE Band 4 - 10MHz QPSK - Full RB)



Plot 7-18. Occupied Bandwidth Plot (LTE Band 4 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 21 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 21 01 00





Plot 7-19. Occupied Bandwidth Plot (LTE Band 4 - 5MHz QPSK - Full RB)



Plot 7-20. Occupied Bandwidth Plot (LTE Band 4 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 22 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 22 01 00





Plot 7-21. Occupied Bandwidth Plot (LTE Band 4 - 3MHz QPSK - Full RB)




Plot 7-22. Occupied Bandwidth Plot (LTE Band 4 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 23 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	raye 23 01 00





Plot 7-23. Occupied Bandwidth Plot (LTE Band 4 - 1.4MHz QPSK - Full RB)



Plot 7-24. Occupied Bandwidth Plot (LTE Band 4 – 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 24 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	raye 24 01 00



7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is 43 + 10 $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

ANSI C63.26-2015 - Section 5.7.4

Test Settings

- 1. Start frequency was set to 30MHz and stop frequency was set to 18GHz (separated into at least two plots per channel)
- 2. RBW ≥ 100kHz
- 3. VBW \geq 3 x RBW
- 4. Detector = RMS
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Per Part 27 and RSS-139, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 25 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 25 01 65






Plot 7-25. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Low Channel)




Plot 7-26. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Low Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 26 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 20 01 00






Plot 7-27. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Low Channel)



Plot 7-28. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Mid Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 27 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 27 of 85






Plot 7-29. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Mid Channel)




Plot 7-30. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - Mid Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 28 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 20 01 00






Plot 7-31. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - High Channel)



Plot 7-32. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - High Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 29 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 29 01 00






Plot 7-33. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB - High Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 30 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 30 01 05






Plot 7-34. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - 1 RB)



Plot 7-35. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 31 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	






Plot 7-36. Conducted Spurious Plot (LTE Band 12 - 10MHz QPSK - 1 RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 22 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 32 of 85





Plot 7-37. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Low Channel)



Plot 7-38. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Low Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 22 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 33 of 85





Plot 7-39. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Low Channel)




Plot 7-40. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Mid Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 24 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 34 of 85





Plot 7-41. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Mid Channel)



Plot 7-42. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - Mid Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 25 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 35 of 85





Plot 7-43. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - High Channel)



Plot 7-44. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - High Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 26 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 36 of 85





Plot 7-45. Conducted Spurious Plot (LTE Band 4 - 20MHz QPSK - 1 RB - High Channel)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 27 of 05
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 37 of 85



7.4 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is 43 + 10 $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

ANSI C63.26-2015 - Section 5.7.3

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW ≥ 1% of the emission bandwidth
- 4. $VBW > 3 \times RBW$
- 5. Detector = RMS
- 6. Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 38 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 30 01 03



Test Notes

- 1. Per 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- 2. Per 27.53(g) for operations in the 663 698 MHz and 698 746MHz bands, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.
- 3. Per 27.53(c)(5) for operations in the 776-788 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.
- 4. For all plots showing emissions in the 763 775MHz and 793 805MHz band, the FCC limit per 27.53(c)(4) is $65 + 10 \log_{10}(P) = -35$ dBm in a 6.25kHz bandwidth.

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dags 20 of 05
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 39 of 85



LTE Band 12



Plot 7-46. Lower Band Edge Plot (LTE Band 12 - 10MHz QPSK - Full RB)



Plot 7-47. Upper Band Edge Plot (LTE Band 12 - 10MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 40 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 40 of 85





Plot 7-48. Lower Band Edge Plot (LTE Band 12 - 5MHz QPSK - Full RB)



Plot 7-49. Upper Band Edge Plot (LTE Band 12 - 5MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 41 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 41 of 85





Plot 7-50. Lower Band Edge Plot (LTE Band 12 - 3MHz QPSK - Full RB)



Plot 7-51. Upper Band Edge Plot (LTE Band 12 - 3MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 42 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Fage 42 01 00





Plot 7-52. Lower Band Edge Plot (LTE Band 12 - 1.4MHz QPSK - Full RB)



Plot 7-53. Upper Band Edge Plot (LTE Band 12 – 1.4MHz QPSK – Full RB)


FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 43 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	raye 43 01 00



LTE Band 13




Plot 7-54. Lower Band Edge Plot (LTE Band 13 - 10MHz QPSK - Full RB)




Plot 7-55. Lower Emission Mask Plot (LTE Band 13 – 10MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 44 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	raye 44 01 00






Plot 7-56. Upper Band Edge Plot (LTE Band 13 – 10MHz QPSK – Full RB)




Plot 7-57. Upper Emission Mask Plot (LTE Band 13 – 10MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 45 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 45 01 65





Plot 7-58. Lower Band Edge Plot (LTE Band 13 - 5MHz QPSK - Full RB)




Plot 7-59. Lower Emission Mask Plot (LTE Band 13 - 5MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 46 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	rage 40 01 00





Plot 7-60. Upper Band Edge Plot (LTE Band 13 - 5MHz QPSK - Full RB)



Plot 7-61. Upper Emission Mask Plot (LTE Band 13 – 5MHz QPSK – Full RB)


FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 47 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 47 of 85



LTE Band 4



Plot 7-62. Lower Band Edge Plot (LTE Band 4 - 20MHz QPSK - Full RB)




Plot 7-63. Lower Extended Band Edge Plot (LTE Band 4 – 20MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Page 48 of 85
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	raye 40 01 00





Plot 7-64. Upper Band Edge Plot (LTE Band 4 - 20MHz QPSK - Full RB)



Plot 7-65. Upper Extended Band Edge Plot (LTE Band 4 - 20MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 40 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 49 of 85





Plot 7-66. Lower Band Edge Plot (LTE Band 4 – 15MHz QPSK – Full RB)



Plot 7-67. Lower Extended Band Edge Plot (LTE Band 4 – 15MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo EO of 9E
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 50 of 85





Plot 7-68. Upper Band Edge Plot (LTE Band 4 - 15MHz QPSK - Full RB)




Plot 7-69. Upper Extended Band Edge Plot (LTE Band 4 - 15MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo E1 of 9E
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 51 of 85






Plot 7-70. Lower Band Edge Plot (LTE Band 4 – 10MHz QPSK – Full RB)




Plot 7-71. Lower Extended Band Edge Plot (LTE Band 4 – 10MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo E2 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 52 of 85





Plot 7-72. Upper Band Edge Plot (LTE Band 4 - 10MHz QPSK - Full RB)




Plot 7-63. Upper Extended Band Edge Plot (LTE Band 4 - 10MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo E2 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 53 of 85





Plot 7-73. Lower Band Edge Plot (LTE Band 4 - 5MHz QPSK - Full RB)




Plot 7-63. Lower Extended Band Edge Plot (LTE Band 4 - 5MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo 54 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 54 of 85





Plot 7-73. Upper Band Edge Plot (LTE Band 4 - 5MHz QPSK - Full RB)




Plot 7-75. Upper Extended Band Edge Plot (LTE Band 4 – 5MHz QPSK – Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo EE of 9E
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 55 of 85





Plot 7-76. Lower Band Edge Plot (LTE Band 4 - 3MHz QPSK - Full RB)



Plot 7-77. Lower Extended Band Edge Plot (LTE Band 4 - 3MHz QPSK - Full RB)

FCC ID: A3LSMF721JPN	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	Dogo E6 of 95
1M2206140073-03.A3L	06/17/2022 - 07/07/2022	Portable Handset	Page 56 of 85