# APPENDIX J: IEEE 802.11AX RU SAR EXCLUSION

#### J.1 IEEE 802.11ax RU SAR Exclusion

To make the most efficient use of the additional available subcarriers (data tones), IEEE 802.11ax can utilize Orthogonal Frequency-Division Multiple Access (OFDMA) which divides the existing 802.11 channels into smaller subchannels called Resource Units (RUs). Possible RU sizes are: 26T, 52T, 106T, 242T, 484T, 996T and 996Tx2.

Per FCC Guidance, 802.11ax was considered a higher order 802.11 mode when compared to a/b/g/n/ac to apply KDB Publication 248227 D01v02r02 for OFDM mode selection. Therefore, SAR tests were not required for 802.11ax based on the maximum allowed output powers of OFDM modes and the reported SAR values. Per FCC Guidance, maximum conducted powers were performed for each RU size to demonstrate that the output powers would not be higher than the other OFDM 802.11 modes. Please refer to 1M2303170032-12.A3L and 1M2303170032-10.A3L for IEEE 802.11ax RU powers.

### J.2 IEEE 802.11ax RU Target Powers

### J.2.1 Maximum 802.11ax RU WLAN Output Power - 2.4GHz WLAN

		IEEE 802.11ax RU (in dBm)								
Mode			SISO Ant	2 (in dBm)		Antenna 1 & Antenna 2 in MIMO				
		26T	52T	106T	242T	26T	52T	106T	242T	
		14	15	16	17	14	15	16	17	
				ch. 1: 15.0	ch. 1: 16.0			ch. 1: 15.0	ch. 1: 16.0	
				ch. 9: 15.0				ch. 9: 15.0		
	Maximum			ch. 10: 15.0	ch. 10: 16.0			ch. 10: 15.0	ch. 10: 16.0	
				ch. 11: 15.0	ch. 11: 16.0			ch. 11: 15.0	ch. 11: 16.0	
		ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	
2.4 GHzWIFI		ch. 13: -6.0	ch. 13: -3.0	ch. 13: 0.0	ch. 13: 0.0	ch. 13: -6.0	ch. 13: -3.0	ch. 13: 0.0	ch. 13: 0.0	
2.4 GHZ WIFI		13	14	15	16	13	14	15	16	
				ch. 1: 14.0	ch. 1: 15.0			ch. 1: 14.0	ch. 1: 15.0	
				ch. 9: 14.0				ch. 9: 14.0		
	Nominal			ch. 10: 14.0	ch. 10: 15.0			ch. 10: 14.0	ch. 10: 15.0	
				ch. 11: 14.0	ch. 11: 15.0			ch. 11: 14.0	ch. 11: 15.0	
		ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	
		ch. 13: -7.0	ch. 13: -4.0	ch. 13: -1.0	ch. 13: -1.0	ch. 13: -7.0	ch. 13: -4.0	ch. 13: -1.0	ch. 13: -1.0	

## J.2.2 Reduced 802.11ax RU WLAN Output Power – 2.4 GHz WLAN

The table below is applicable in the following conditions:

#### RCV Active

		IEEE 802.11axRU (in dBm)									
Mode		SISO Ant 2 (in dBm)				Antenna 1 & Antenna 2 in MIMO					
		26T	52T	106T	242T	26T	52T	106T	242T		
		12	12	12	12	9	9	9	9		
	Maximum	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0	ch. 12: 6.0		
2.4 GHz WIFI		ch. 13: -6.0	ch. 13: -3.0	ch. 13: 0.0	ch. 13: 0.0	ch. 13: -6.0	ch. 13: -3.0	ch. 13: 0.0	ch. 13: 0.0		
2.4 GHZ WII I		11	11	11	11	8	8	8	8		
	Nominal	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0	ch. 12: 5.0		
		ch. 13: -7.0	ch. 13: -4.0	ch. 13: -1.0	ch. 13: -1.0	ch. 13: -7.0	ch. 13: -4.0	ch. 13: -1.0	ch. 13: -1.0		

FCC ID: A3LSMF731B	SAR EVALUATION REPORT	Approved by: Technical Manager	
DUT Type: Portable Handset		APPENDIX J: Page 1 of 2	

# J.2.3 Maximum 802.11ax RU WLAN Output Power – 5GHz WLAN

				IE	EE 802.11ax RU (in dB	m)				
Mode		Antenna 1 & Antenna 2 in MIMO								
	•	26T	52T	106T	242T	484T	996T	996T*2		
5 GHz WIFI	Maximum	10.5	13.0	16.0	16.0					
(20MHz BW)	Nominal	9.5	12.0	15.0	15.0					
5 GHz WIFI	Maximum	10.5	13.0	16.0	15.0	15.0				
(40MHz BW)	Nominal	9.5	12.0	15.0	14.0	14.0				
5 GHz WIFI	Maximum	10.5	13.0	16.0	14.0	14.0	14.0			
(80MHz BW)	Nominal	9.5	12.0	15.0	13.0	13.0	13.0			
5 GHz WIFI	Maximum	10.5	13.0	16.0	13.0	13.0	13.0	13.0		
(160MHz BW)	Nominal	9.5	12.0	15.0	12.0	12.0	12.0	12.0		

# J.2.4 Maximum 802.11ax RU WLAN Output Power – 6GHz WLAN

				IE	EE 802.11ax RU (in dB	m)						
Mode			Antenna 1 & Antenna 2 in MIMO									
		26T	52T	106T	242T	484T	996T	996T*2				
6 GHz WIFI	Maximum	3.5	5.5	12.0	11.0							
(20MHz BW)	Nominal	2.5	4.5	11.0	10.0							
6 GHz WIFI	Maximum	4.0	5.0	12.0	11.0	11.0						
(40MHz BW)	Nominal	3.0	4.0	11.0	10.0	10.0						
6 GHz WIFI	Maximum	5.0	8.5	12.0	12.0	12.0	12.0					
(80MHz BW)	Nominal	4.0	7.5	11.0	11.0	11.0	11.0					
6 GHz WIFI (160MHz BW)	Maximum	5.0	5.0	12.0	12.0	12.0	12.0	12.0				
	Nominal	4.0	4.0	11.0	11.0	11.0	11.0	11.0				

FCC ID: A3LSMF731B	SAR EVALUATION REPORT	Approved by: Technical Manager
<b>DUT Type:</b> Portable Handset		APPENDIX J: Page 2 of 2