

<b>FCC ID:</b>	A3LSMF916JPN
<b>Date:</b>	6/4/2020
<b>Test Procedure:</b>	KDB 680106 D01 v03

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.271	0.271	0.282	0.262	0.262	0.262	614.00
B (Right)	0.291	0.291	0.292	0.292	0.291	0.272	614.00
C (Top)	0.272	0.262	0.271	0.262	0.262	0.262	614.00
D (Left)	0.262	0.262	0.271	0.262	0.262	0.262	614.00
E (Front)	0.390	0.292	0.390	0.271	0.351	0.262	614.00
F (Back)	0.403	0.292	0.322	0.282	0.341	0.300	614.00

**Table 1. E-field Measurement by distance/battery level (D2D)**

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
B (Right)	0.094	0.094	0.101	0.094	0.101	0.094	1.63
C (Top)	0.094	0.094	0.094	0.094	0.094	0.098	1.63
D (Left)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
E (Front)	0.094	0.094	0.094	0.094	0.094	0.094	1.63
F (Back)	0.094	0.094	0.094	0.094	0.094	0.094	1.63

**Table 2. H-field Measurement by distance/battery level (D2D)**

A	B	C	D	E	F
BOTTOM EDGE	RIGHT EDGE	TOP EDGE	LEFT EDGE	FRONT (SCREEN)	Back

**Table 5. EUT Position Description**

**Note:**

The right and left edge are determined with the EUT screen facing the user.

**Description of Test Setup**

- Testing was performed with a calibrated field probe.
- Measurement was performed on each side of the EUT as described per Table 4.
- Testing was performed at the distances and different battery level as indicated on Table 1 and Table 2.
- Measurement procedure was performed per FCC Guidance.

**Test Equipment**

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electric & Magnetic Field Probe	6/27/2019	Annual	6/27/2020	170WX60209