PCTEST
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctest.com



# PART 27 MEASUREMENT REPORT

**Applicant Name:**
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

**Date of Testing:**
04/28/2021 - 6/25/2021
**Test Site/Location:**
PCTEST Lab. Columbia, MD, USA
**Test Report Serial No.:**
1M2104190044-4.A3L

| | |
|---|---|
| **FCC ID:** | **A3LSMF926B** |
| **APPLICANT:** | **Samsung Electronics Co., Ltd.** |

| | |
|---|---|
| **Application Type:** | Certification |
| **Model:** | SM-F926B |
| **Additional Model(s):** | SM-F926B/DS |
| **EUT Type:** | Portable Handset |
| **FCC Classification:** | PCS Licensed Transmitter Held to Ear (PCE) |
| **FCC Rule Part:** | 27 |
| **Test Procedure(s):** | ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01, KDB 648474 D03 v01r04 |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez
President

ACCREDITED
CERT #2041.01

# TABLE OF CONTENTS



# MEASUREMENT REPORT
## FCC Part 27



| Mode | Bandwidth | Modulation | Tx Frequency Range [MHz] | ERP | | EIRP | | Emission Designator |
|---|---|---|---|---|---|---|---|---|
| | | | | Max. Power [W] | Max. Power [dBm] | Max. Power [W] | Max. Power [dBm] | |
| LTE Band 12/17 | 10 MHz | QPSK | 704.0 - 711.0 | 0.068 | 18.34 | 0.112 | 20.49 | 8M98G7D |
| | | 16QAM | 704.0 - 711.0 | 0.060 | 17.81 | 0.099 | 19.96 | 8M98W7D |
| | 5 MHz | QPSK | 701.5 - 713.5 | 0.071 | 18.51 | 0.116 | 20.66 | 4M56G7D |
| | | 16QAM | 701.5 - 713.5 | 0.057 | 17.56 | 0.093 | 19.71 | 4M51W7D |
| LTE Band 12 | 3 MHz | QPSK | 700.5 - 714.5 | 0.069 | 18.37 | 0.113 | 20.52 | 2M71G7D |
| | | 16QAM | 700.5 - 714.5 | 0.062 | 17.89 | 0.101 | 20.04 | 2M71W7D |
| | 1.4 MHz | QPSK | 699.7 - 715.3 | 0.066 | 18.22 | 0.109 | 20.37 | 1M10G7D |
| | | 16QAM | 699.7 - 715.3 | 0.058 | 17.63 | 0.095 | 19.78 | 1M10W7D |
| LTE Band 13 | 10 MHz | QPSK | 782.0 | 0.082 | 19.13 | 0.134 | 21.28 | 8M97G7D |
| | | 16QAM | 782.0 | 0.043 | 16.38 | 0.071 | 18.53 | 8M98W7D |
| | 5 MHz | QPSK | 779.5 - 784.5 | 0.088 | 19.44 | 0.144 | 21.59 | 4M58G7D |
| | | 16QAM | 779.5 - 784.5 | 0.046 | 16.65 | 0.076 | 18.80 | 4M53W7D |

**Overview Table (<1GHz Bands)**

| Mode | Bandwidth | Modulation | Tx Frequency Range [MHz] | EIRP | | Emission Designator |
|---|---|---|---|---|---|---|
| | | | | Max. Power [W] | Max. Power [dBm] | |
| LTE Band 66/4 | 20 MHz | QPSK | 1720.0 - 1770.0 | 0.336 | 25.26 | 18M0G7D |
| | | 16QAM | 1720.0 - 1770.0 | 0.297 | 24.73 | 17M9W7D |
| | 15 MHz | QPSK | 1717.5 - 1772.5 | 0.337 | 25.27 | 13M5G7D |
| | | 16QAM | 1717.5 - 1772.5 | 0.299 | 24.75 | 13M5W7D |
| | 10 MHz | QPSK | 1715.0 - 1775.0 | 0.317 | 25.00 | 9M01G7D |
| | | 16QAM | 1715.0 - 1775.0 | 0.272 | 24.34 | 8M98W7D |
| | 5 MHz | QPSK | 1712.5 - 1777.5 | 0.320 | 25.05 | 4M51G7D |
| | | 16QAM | 1712.5 - 1777.5 | 0.248 | 23.94 | 4M51W7D |
| | 3 MHz | QPSK | 1711.5 - 1778.5 | 0.322 | 25.08 | 2M70G7D |
| | | 16QAM | 1711.5 - 1778.5 | 0.251 | 23.99 | 2M71W7D |
| | 1.4 MHz | QPSK | 1710.7 - 1779.3 | 0.330 | 25.18 | 1M10G7D |
| | | 16QAM | 1710.7 - 1779.3 | 0.249 | 23.96 | 1M10W7D |
| | | 64QAM | 1710.7 - 1779.3 | 0.180 | 22.55 | 1M10W7D |
| | | 256QAM | 1710.7 - 1779.3 | 0.108 | 20.34 | 1M09W7D |
| NR Band n66 | 20 MHz | π/2 BPSK | 1720.0 - 1770.0 | 0.282 | 24.51 | 17M9G7D |
| | | QPSK | 1720.0 - 1770.0 | 0.278 | 24.44 | 19M0G7D |
| | | 16QAM | 1720.0 - 1770.0 | 0.222 | 23.46 | 19M0W7D |
| | 15 MHz | π/2 BPSK | 1717.5 - 1772.5 | 0.293 | 24.66 | 13M5G7D |
| | | QPSK | 1717.5 - 1772.5 | 0.290 | 24.62 | 14M2G7D |
| | | 16QAM | 1717.5 - 1772.5 | 0.241 | 23.82 | 14M2W7D |
| | 10 MHz | π/2 BPSK | 1715.0 - 1775.0 | 0.300 | 24.77 | 9M00G7D |
| | | QPSK | 1715.0 - 1775.0 | 0.278 | 24.45 | 9M33G7D |
| | | 16QAM | 1715.0 - 1775.0 | 0.236 | 23.73 | 9M36W7D |
| | 5 MHz | π/2 BPSK | 1712.5 - 1777.5 | 0.300 | 24.78 | 4M51G7D |
| | | QPSK | 1712.5 - 1777.5 | 0.286 | 24.57 | 4M52G7D |
| | | 16QAM | 1712.5 - 1777.5 | 0.232 | 23.65 | 4M50W7D |

**Overview Table (>1GHz Bands)**

| Mode | Modulation | Tx Frequency Range [MHz] | EIRP | | Emission Designator |
|---|---|---|---|---|---|
| | | | Max. Power [W] | Max. Power [dBm] | |
| WCDMA1700 | Spread Spectrum | 1712.4 - 1752.6 | 0.248 | 23.95 | 4M16F9W |

**Overview Table (>1GHz Bands)**

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.

- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).

- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

# 2.0 PRODUCT INFORMATION

## 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMF926B**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 27.

**Test Device Serial No.:** 0682M, 0714M, 0450M, 0440M, 0441M

## 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR (n5, n66), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer, UWB

## 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

This device supports two configurations: one is with screen open and one is with screen closed. Both configurations are tested, and the worst case radiated emissions data is shown in this report.

For LTE Bands 12 and 13, this device supports two additional antenna configurations: one is with two antennas transmitting from one feed, and one is with a singular antenna transmitting. Both configurations are tested, and the worst case radiated emissions data is shown in this report.

## 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

# 3.0 DESCRIPTION OF TESTS

## 3.1 Evaluation Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03r01) were used in the measurement of the EUT**.**

## 3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_{d\ [dBm]} = P_{g\ [dBm]} - \text{cable loss}_{\ [dB]} + \text{antenna gain}_{\ [dBd/dBi]}$$

Where, $P_d$ is the dipole equivalent power, $P_g$ is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_{g\ [dBm]}$ – cable loss $_{[dB]}$.

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

# 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the $U_{CISPR}$ measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution | Expanded Uncertainty (±dB) |
|---|---|
| Conducted Bench Top Measurements | 1.13 |
| Radiated Disturbance (<1GHz) | 4.98 |
| Radiated Disturbance (>1GHz) | 5.07 |
| Radiated Disturbance (>18GHz) | 5.09 |

# 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|---|---|---|---|---|---|---|
| - | AP2 | EMC Cable and Switch System | 3/4/2021 | Annual | 3/4/2022 | AP2 |
| - | AP1 | EMC Cable and Switch System | 3/9/2021 | Annual | 3/9/2022 | AP1 |
| - | ETS | EMC Cable and Switch System | 3/4/2021 | Annual | 3/4/2022 | ETS |
| - | LTx2 | Licensed Transmitter Cable Set | 3/12/2021 | Annual | 3/12/2022 | LTx2 |
| - | LTx4 | Licensed Transmitter Cable Set | 3/12/2021 | Annual | 3/12/2022 | LTx4 |
| Agilent | E5515C | Wireless Communications Test Set | N/A | | | GB46310798 |
| Agilent | N9030A | 50GHz PXA Signal Analyzer | 1/20/2021 | Annual | 1/20/2022 | US51350301 |
| Anritsu | MT8821C | Radio Communication Analyzer | N/A | | | 6201525694 |
| Com-Power | AL-130R | Active Loop Antenna | 8/22/2019 | Biennial | 8/22/2021 | 121085 |
| Emco | 3115 | Horn Antenna (1-18GHz) | 6/18/2020 | Biennial | 6/18/2022 | 9704-5182 |
| Emco | 3116 | Horn Antenna (18 - 40GHz) | 8/7/2018 | Triennial | 8/7/2021 | 9203-2178 |
| Espec | ESX-2CA | Environmental Chamber | 8/27/2020 | Annual | 8/27/2022 | 17620 |
| ETS Lindgren | 3164-08 | Quad Ridge Horn Antenna | 3/12/2020 | Biennial | 3/12/2022 | 128337 |
| ETS Lindgren | 3816/2NM | LISN | 7/9/2020 | Biennial | 7/9/2022 | 00114451 |
| Keysight Technologies | N9020A | MXA Signal Analyzer | 9/22/2020 | Annual | 9/22/2021 | MY54500644 |
| Keysight Technologies | N9030A | PXA Signal Analyzer (44GHz) | 8/17/2020 | Annual | 8/17/2021 | MY52350166 |
| Keysight Technologies | N9038A | MXE EMI Receiver | 8/11/2020 | Annual | 8/11/2021 | MY51210133 |
| Mini-Circuits | SSG-4000HP | Synthesized Signal Generator | N/A | | | 11403100002 |
| Rohde & Schwarz | CMW500 | Radio Communication Tester | N/A | | | 100976 |
| Rohde & Schwarz | ESU26 | EMI Test Receiver (26.5GHz) | 7/15/2020 | Annual | 7/15/2021 | 100342 |
| Rohde & Schwarz | ESU40 | EMI Test Receiver (40GHz) | 9/9/2020 | Annual | 9/9/2021 | 100348 |
| Rohde & Schwarz | FSW67 | Signal / Spectrum Analyzer | 8/10/2020 | Annual | 8/10/2021 | 103200 |
| Sunol | JB5 | Bi-Log Antenna (30M - 5GHz) | 7/27/2020 | Biennial | 7/27/2022 | A051107 |

**Table 5-1. Summary of Test Results**

**Notes:**

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

2. Equipment with a calibration date of “N/A” shown in this list was not used to make direct calibrated measurements.

# 6.0 SAMPLE CALCULATIONS

## Emission Designator

### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission, telemetry, telecommand

### QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission, telemetry, telecommand

## Spurious Radiated Emission – LTE Band

**Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analzyer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

# 7.0 TEST RESULTS

## 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.

FCC ID: A3LSMF926B

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)

Mode(s): LTE/NR/WCDMA

| Test Condition | Test Description | FCC Part Section(s) | RSS Section(s) | Test Limit | Test Result | Reference |
|---|---|---|---|---|---|---|
| CONDUCTED | Occupied Bandwidth | 2.1049 | RSS-Gen(6.7) | N/A | PASS | Section 7.2 |
| | Conducted Band Edge / Spurious Emissions | 2.1051, 27.53 | RSS-139(6.6) | > 43 + 10log10(P[Watts]) at Band Edge and for all out-of-band emissions | PASS | Sections 7.3, 7.4 |
| | Transmitter Conducted Output Power | 2.1046 | RSS-139(4.1) | N/A | PASS | See RF Exposure Report |
| | Frequency Stability | 2.1055, 27.54 | RSS-139(6.4) | Fundamental emissions stay within authorized frequency block | PASS | Section 7.8 |
| RADIATED | Effective Radiated Power / Equivalent Isotropic Radiated Power (LTE Band 12) | 27.50(b)(10) | RSS-130(4.4) | < 3 Watts max. ERP<br>< 5 Watts max. EIRP | PASS | Section 7.6 |
| | Effective Radiated Power / Equivalent Isotropic Radiated Power (LTE Band 13) | 27.50(c)(10) | RSS-130(4.4) | < 3 Watts max. ERP<br>< 5 Watts max. EIRP | PASS | Section 7.6 |
| | Equivalent Isotropic Radiated Power (WCDMA) | 27.50(d)(4) | RSS-139(6.5) | < 1 Watts max. EIRP | PASS | Section 7.6 |
| | Equivalent Isotropic Radiated Power (NR Band n66) | | | | PASS | Section 7.6 |
| | Equivalent Isotropic Radiated Power (LTE Band 4/66) | | | | PASS | Section 7.6 |
| | Radiated Spurious Emissions (LTE Band 13) | 2.1053, 27.53(f) | RSS-139(6.6) | < -70 dBW/MHz (for wideband signals)<br>< -80 dBW (for discrete emissions less than 700Hz BW)<br>For all emissions in the band 1559 - 1610 MHz | PASS | Section 7.7 |
| | Radiated Spurious Emissions | 2.1053, 27.53 | RSS-139(6.6) | > 43 + 10 log10 (P[Watts]) for all out-of-band emissions | PASS | Section 7.7 |

**Table 7-1. Summary of Test Results**

**Notes:**

1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST 2G/3G Automation Version 4.2.

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.


**Plot 7-1. Occupied Bandwidth Plot (LTE Band 12/17 - 10MHz QPSK - Full RB)**


**Plot 7-2. Occupied Bandwidth Plot (LTE Band 12/17 - 10MHz 16-QAM - Full RB)**




**Plot 7-3. Occupied Bandwidth Plot (LTE Band 12/17 - 5MHz QPSK - Full RB)**


**Plot 7-4. Occupied Bandwidth Plot (LTE Band 12/17 - 5MHz 16-QAM - Full RB)**




**Plot 7-5. Occupied Bandwidth Plot (LTE Band 12 - 3MHz QPSK - Full RB)**




**Plot 7-6. Occupied Bandwidth Plot (LTE Band 12 - 3MHz 16-QAM - Full RB)**


**Plot 7-7. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz QPSK - Full RB)**


**Plot 7-8. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz 16-QAM - Full RB)**




**Plot 7-9. Occupied Bandwidth Plot (LTE Band 13 - 10MHz QPSK - Full RB)**


**Plot 7-10. Occupied Bandwidth Plot (LTE Band 13 - 10MHz 16-QAM - Full RB)**




**Plot 7-11. Occupied Bandwidth Plot (LTE Band 13 - 5MHz QPSK - Full RB)**




**Plot 7-12. Occupied Bandwidth Plot (LTE Band 13 - 5MHz 16-QAM - Full RB)**




**Plot 7-13. Occupied Bandwidth Plot (LTE Band 66/4 - 20MHz QPSK - Full RB)**




**Plot 7-14. Occupied Bandwidth Plot (LTE Band 66/4 - 20MHz 16-QAM - Full RB)**




**Plot 7-15. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz QPSK - Full RB)**




**Plot 7-16. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz 16-QAM - Full RB)**




**Plot 7-17. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz QPSK - Full RB)**




**Plot 7-18. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz 16-QAM - Full RB)**




**Plot 7-19. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz QPSK - Full RB)**




**Plot 7-20. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz 16-QAM - Full RB)**




**Plot 7-21. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz QPSK - Full RB)**




**Plot 7-22. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz 16-QAM - Full RB)**




**Plot 7-23. Occupied Bandwidth Plot (LTE Band 66/4 - 1.4MHz QPSK - Full RB)**




**Plot 7-24. Occupied Bandwidth Plot (LTE Band 66/4 - 1.4MHz 16-QAM - Full RB)**


**Plot 7-25. Occupied Bandwidth Plot (NR Band n66 - 20.0MHz CP-OFDM QPSK - Full RB)**


**Plot 7-26. Occupied Bandwidth Plot (NR Band n66 - 20.0MHz CP-OFDM 16QAM - Full RB)**




**Plot 7-27. Occupied Bandwidth Plot (NR Band n66 - 15.0MHz CP-OFDM QPSK - Full RB)**




**Plot 7-28. Occupied Bandwidth Plot (NR Band n66 - 15.0MHz CP-OFDM 16QAM - Full RB)**




**Plot 7-29. Occupied Bandwidth Plot (NR Band n66 - 10.0MHz CP-OFDM QPSK - Full RB)**




**Plot 7-30. Occupied Bandwidth Plot (NR Band n66 - 10.0MHz CP-OFDM 16QAM - Full RB)**




**Plot 7-31. Occupied Bandwidth Plot (NR Band n66 - 5.0MHz CP-OFDM QPSK - Full RB)**




**Plot 7-32. Occupied Bandwidth Plot (NR Band n66 - 5.0MHz CP-OFDM 16QAM - Full RB)**

## WCDMA AWS




**Plot 7-33. Occupied Bandwidth Plot (WCDMA, Ch. 1413)**

## 7.3 Spurious and Harmonic Emissions at Antenna Terminal

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is 43 + 10 $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.***

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 18GHz (separated into at least two plots per channel)
2. RBW ≥ 100kHz
3. VBW ≥ 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**

### Test Notes

1. Per Part 27 and RSS-139, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.




**Plot 7-34. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-35. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**


**Plot 7-36. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-37. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-38. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**


**Plot 7-39. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-40. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-41. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**


**Plot 7-42. Conducted Spurious Plot (LTE Band 12/17 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-43. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0)**




**Plot 7-44. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0)**


**Plot 7-45. Conducted Spurious Plot (LTE Band 13 - 10MHz QPSK - RB Size 1, RB Offset 0)**




**Plot 7-46. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-47. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-48. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-49. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-50. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-51. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-52. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-53. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-54. Conducted Spurious Plot (LTE Band 66/4 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)**


**Plot 7-55. Conducted Spurious Plot (NR Band n66 -20.0MHz - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-56. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - Low Channel)**




**Plot 7-57. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - Low Channel)**


**Plot 7-58. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-59. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - Mid Channel)**




**Plot 7-60. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - Mid Channel)**


**Plot 7-61. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-62. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - High Channel)**




**Plot 7-63. Conducted Spurious Plot (NR Band n66 - 20.0MHz - RB Size 1, RB Offset 0 - High Channel)**

## WCDMA AWS




**Plot 7-64. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)**




**Plot 7-65. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)**




**Plot 7-66. Conducted Spurious Plot (WCDMA Ch. 1312- Low Channel)**




**Plot 7-67. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)**




**Plot 7-68. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)**




**Plot 7-69. Conducted Spurious Plot (WCDMA Ch. 1413- Mid Channel)**




**Plot 7-70. Conducted Spurious Plot (WCDMA Ch. 1513- High Channel)**




**Plot 7-71. Conducted Spurious Plot (WCDMA Ch. 1513- High Channel)**




**Plot 7-72. Conducted Spurious Plot (WCDMA Ch. 1513- High Channel)**

## 7.4 Band Edge Emissions at Antenna Terminal

**Test Overview**

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is 43 + 10 $log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.***

**Test Procedure Used**

KDB 971168 D01 v03r01 – Section 6.0

**Test Settings**

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW ≥ 1% of the emission bandwidth
4. VBW ≥ 3 x RBW
5. Detector = RMS
6. Number of sweep points ≥ 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**

## Test Notes

Per 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 663 - 698 MHz and 698 – 746MHz bands, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(c)(5) for operations in the 776-788 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

For all plots showing emissions in the 763 – 775MHz and 793 – 805MHz band, the FCC limit per 27.53(c)(4) is $65 + 10 \log_{10}(P) = -35$dBm in a 6.25kHz bandwidth.

## LTE Band 12/17




**Plot 7-73. Lower Band Edge Plot (LTE Band 12 - 10MHz QPSK – Full RB)**




**Plot 7-74. Lower Band Edge Plot (LTE Band 17 - 10MHz QPSK – Full RB)**


**Plot 7-75. Upper Band Edge Plot (LTE Band 12/17 - 10MHz QPSK – Full RB)**




**Plot 7-76. Lower Band Edge Plot (LTE Band 12 - 5MHz QPSK – Full RB)**


**Plot 7-77. Lower Band Edge Plot (LTE Band 17 - 5MHz QPSK – Full RB)**


**Plot 7-78. Upper Band Edge Plot (LTE Band 12/17 - 5MHz QPSK – Full RB)**

## LTE Band 12




**Plot 7-79. Lower Band Edge Plot (LTE Band 12 - 3MHz QPSK – Full RB)**


**Plot 7-80. Upper Band Edge Plot (LTE Band 12 - 3MHz QPSK – Full RB)**


**Plot 7-81. Lower Band Edge Plot (LTE Band 12 – 1.4MHz QPSK – Full RB)**


**Plot 7-82. Upper Band Edge Plot (LTE Band 12 – 1.4MHz QPSK – Full RB)**

## LTE Band 13


**Plot 7-83. Lower Band Edge Plot (LTE Band 13 - 10MHz QPSK – Full RB)**




**Plot 7-84. Lower Emission Mask Plot (LTE Band 13 - 10MHz QPSK – Full RB)**




**Plot 7-85. Upper Band Edge Plot (LTE Band 13 - 10MHz QPSK – Full RB)**




**Plot 7-86. Upper Emission Mask Plot (LTE Band 13 - 10MHz QPSK – Full RB)**


**Plot 7-87. Lower Band Edge Plot (LTE Band 13 - 5MHz QPSK – Full RB)**




**Plot 7-88. Lower Emission Mask Plot (LTE Band 13 - 5MHz QPSK – Full RB)**


**Plot 7-89. Upper Band Edge Plot (LTE Band 13 - 5MHz QPSK – Full RB)**




**Plot 7-90. Upper Emission Mask Plot (LTE Band 13 - 5MHz QPSK – Full RB)**




**Plot 7-91. Lower Band Edge Plot (LTE Band 66/4 - 20MHz QPSK – Full RB)**




**Plot 7-92. Lower Extended Band Edge Plot (LTE Band 66/4 - 20MHz QPSK – Full RB)**




**Plot 7-93. Upper Band Edge Plot (LTE Band 4 - 20MHz QPSK – Full RB)**




**Plot 7-94. Upper Extended Band Edge Plot (LTE Band 4 - 20MHz QPSK – Full RB)**




**Plot 7-95. Upper Band Edge Plot (LTE Band 66 - 20MHz QPSK – Full RB)**




**Plot 7-96. Channel Edge Plot (LTE Band 66 - 20MHz QPSK – Full RB)**




**Plot 7-97. Lower Band Edge Plot (LTE Band 66/4 - 15MHz QPSK – Full RB)**




**Plot 7-98. Lower Extended Band Edge Plot (LTE Band 66/4 - 15MHz QPSK – Full RB)**




**Plot 7-99. Upper Band Edge Plot (LTE Band 4 - 15MHz QPSK – Full RB)**




**Plot 7-100. Upper Extended Band Edge Plot (LTE Band 4 - 15MHz QPSK – Full RB)**