



WIFI 6 GHZ RF EXPOSURE EVALUATION

Applicant Name

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing

05/24/2021 – 06/01/2021

Test Site/Location

PCTEST, Columbia, MD, USA

Document Serial No:

1M2104190044-23.A3L (Rev 1)

FCC ID:

A3LSMF926B

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

SM-F926B/DS

Additional Models:

SM-F926B

Band & Mode	Tx Frequency MHz	SAR					APD					PD psPD (W/m ²)
		1g Head (W/kg)	1g Body-worn (W/kg)	10g Phablet (W/kg)	1g UMPC Body (W/kg)	10g UMPC Extremity (W/kg)	Head (W/m ²)	Body-worn (W/m ²)	Phablet (W/m ²)	UMPC Body (W/m ²)	UMPC Extremity (W/m ²)	
WIFI 6 GHz	5935-7115	0.258	0.007	0.150	0.023	0.166	1.370	0.063	3.630	0.207	4.010	6.387

Values above represent RF exposure evaluations during MIMO operations.

Note: This revised Test Report supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: A3LSMF926B		WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 1 of 31	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
1.1	Device Overview	3
1.2	Nominal and Maximum Output Power Specifications	4
1.3	DUT Antenna Locations	5
1.4	Miscellaneous Testing Considerations	6
1.5	Guidance Applied	6
2	RF EXPOSURE LIMITS	7
2.1	Uncontrolled Environment	7
2.2	Controlled Environment	7
2.3	RF Exposure Limits for Frequencies Below 6 GHz	7
2.4	RF Exposure Limits for Frequencies Above 6 GHz	8
3	RF CONDUCTED POWERS	9
4	SYSTEM VERIFICATION	14
4.1	SAR Test System Verification	14
4.2	Power Density Test System Verification	16
5	DATA SUMMARY	18
5.1	SAR and Absorbed Power Density Results	18
5.2	Power Density Results	23
6	EQUIPMENT LIST	25
7	MEASUREMENT UNCERTAINTIES	26
9	CONCLUSION	28
9.1	Measurement Conclusion	28
10	REFERENCES	29

APPENDIX A: TEST PLOTS

APPENDIX B: SYSTEM VERIFICATION PLOTS

APPENDIX C: DUT ANTENNA DIAGRAM AND TEST SETUP PHOTOGRAPHS

APPENDIX D: PROBE AND VERIFICATION SOURCE CALIBRATION CERTIFICATES

APPENDIX E: SAR TISSUE SPECIFICATIONS



APPENDIX F: SAR SYSTEM VALIDATION

FCC ID: A3LSMF926B	 PCTEST Proud to be part of	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 2 of 31	

1 DEVICE UNDER TEST

1.1 Device Overview




Band & Mode	Tx Frequency
U-NII-5	5935 - 6415 MHz
U-NII-6	6435 - 6525 MHz
U-NII-7	6535 - 6875 MHz
U-NII-8	6895 - 7115 MHz

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of element</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 3 of 31	

1.2 Nominal and Maximum Output Power Specifications

The device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB publication 447498 D01v06.

Mode	IEEE 802.11 (in dBm)			
	MIMO			
	a (CDD + STBC)		ax (SU) (CDD + STBC, SDM)	
	Nominal	Maximum	Nominal	Maximum
6 GHz WIFI (20MHz BW)	12.5	13.5	12.5	13.5
6 GHz WIFI (40MHz BW)			12.0	13.0
6 GHz WIFI (80MHz BW)			12.0	13.0
6 GHz WIFI (160MHz BW)			12.0	13.0

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 4 of 31	

1.3 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in SAR Part 1 Report Appendix E. This device is considered a "phablet" when it is in closed configuration and a "UMPC mini-tablet" when it is in open configuration. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filing.




**Table 1-1
Device Surfaces for Closed Configuration**

Mode	Back	Front	Top	Bottom	Right	Left
6 GHz WLAN MIMO	Yes	Yes	Yes	Yes	No	Yes

**Table 1-2
Device Surfaces for Open Configuration**

Mode	Back	Front	Top	Bottom	Right	Left
6 GHz WLAN MIMO	Yes	Yes	Yes	Yes	No	No

Note: Particular DUT edges were not required to be evaluated for phablet SAR or UMPC mini-tablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III, FCC KDB Publication 941225 D07v01r02 and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. Wireless router mode is disabled for all 6 GHz WLAN operations.

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of</small> 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 5 of 31

1.4 Miscellaneous Testing Considerations



Per FCC guidance, SAR was performed using 6.5 GHz SAR probe calibration factors. FCC KDB 648474 and FCC KDB 248227 were followed for test positions, distances, and modes. Per TCB workshop October 2020 notes, 5 channels were tested. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements. Incident power density is evaluated at 2mm ensuring that the resolution is sufficient such that integrated power density (iPD) between d=2mm and d= λ /5mm varies by < 1dB per equipment manufacturer guidance. Power density results are scaled up for uncertainty above 30%.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" when it is closed configuration since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was evaluated for 6 GHz WIFI since wireless router is not supported for this mode. Per FCC KDB Publication 941225 D07v01r02, this device is a "UMPC mini-tablet" when it is in open configuration. SAR tests were performed at 0mm (10g) and 10mm (1g) per KDB 941225 D07v01r02.

6 GHz WIFI SAR results are used for simultaneous transmission analysis with the other transmitters. Analysis can be found in the SAR report.

1.5 Guidance Applied

- November 2017, October 2018, April 2019, November 2019, October 2020 TCBC Workshop Notes
- SPEAG DASY6 System Handbook
- SPEAG DASY6 Application Note (Interim Procedures for Devices Operating at 6-10 GHz)
- IEEE 1528-2013
- IEC TR 63170:2018
- IEC 62479:2010
- FCC KDB 865664 D02 v01r02
- FCC KDB 648474 D04 v01r03
- FCC KDB 248227 D01 v02r02
- FCC KDB 447498 D01 v06
- FCC KDB 865664 D01 v01r04
- FCC KDB 941225 D07v01r02

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of</small> 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 6 of 31	

2

RF EXPOSURE LIMITS

2.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

2.2 Controlled Environment


CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

2.3 RF Exposure Limits for Frequencies Below 6 GHz

Table 2-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 7 of 31

2.4 RF Exposure Limits for Frequencies Above 6 GHz

Per §1.1310 (d)(3), the MPE limits are applied for frequencies above 6 GHz. Power Density is expressed in units of W/m² or mW/cm².

Peak Spatially Averaged Power Density was evaluated over a circular area of 4 cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Table 2-2
Human Exposure Limits Specified in FCC 47 CFR §1.1310

Human Exposure to Radiofrequency (RF) Radiation Limits		
Frequency Range [MHz]	Power Density [mW/cm ²]	Average Time [Minutes]
(A) Limits For Occupational / Controlled Environments		
1,500 – 100,000	5.0	6
(B) Limits For General Population / Uncontrolled Environments		
1,500 – 100,000	1.0	30

Note: 1.0 mW/cm² is 10 W/m²



FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of element</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 8 of 31

Table 3-1
6 GHz WLAN Maximum Average RF Power – 802.11a 20 MHz BW

6GHz (20MHz) 802.11a Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5935	2	10.49	10.29	13.40
6075	25	10.24	9.83	13.05
6175	45	10.28	10.08	13.19
6275	65	10.25	9.93	13.10
6415	93	10.42	10.49	13.47
6435	97	10.38	10.49	13.45
6475	105	10.16	10.32	13.25
6515	113	10.12	10.38	13.26
6535	117	10.45	10.49	13.48
6675	145	10.47	10.49	13.49
6695	149	10.32	10.56	13.45
6875	185	10.26	10.52	13.40
6895	189	10.31	10.48	13.41
6995	209	10.28	10.31	13.31
7115	233	10.2	10.21	13.22




FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 9 of 31

Table 3-2
6 GHz WLAN Maximum Average RF Power – 802.11ax 20 MHz BW

6GHz (20MHz) 802.11ax Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5935	2	10.42	10.17	13.31
6075	25	10.12	9.71	12.93
6175	45	10.26	10.03	13.16
6275	65	10.23	9.95	13.10
6415	93	10.44	10.49	13.48
6435	97	10.40	10.53	13.48
6475	105	10.11	10.47	13.30
6515	113	10.49	10.38	13.45
6535	117	10.45	10.49	13.48
6675	145	10.37	10.38	13.39
6695	149	10.39	10.49	13.45
6875	185	10.26	10.56	13.42
6895	189	10.17	10.49	13.34
6995	209	10.10	10.33	13.23
7115	233	10.14	10.23	13.20



FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of element</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 10 of 31	

Table 3-3
6 GHz WLAN Maximum Average RF Power – 802.11ax 40 MHz BW

6GHz (40MHz) 802.11ax Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5965	3	9.91	9.52	12.73
6085	27	9.99	9.60	12.81
6165	43	9.58	9.22	12.41
6285	67	9.47	9.58	12.54
6405	91	9.97	9.99	12.99
6445	99	9.87	9.99	12.94
6485	107	9.60	9.96	12.79
6525	115	9.66	9.74	12.71
6565	123	9.58	9.97	12.79
6685	147	9.95	9.99	12.98
6725	155	9.64	9.52	12.59
6845	179	9.71	9.87	12.80
6885	187	9.73	9.99	12.87
7005	211	9.75	9.78	12.78
7085	227	9.81	9.51	12.67




FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of</small> 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 11 of 31	

Table 3-4
6 GHz WLAN Maximum Average RF Power – 802.11ax 80 MHz BW

6GHz (80MHz) 802.11ax Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5985	7	9.90	9.62	12.77
6065	23	9.99	9.74	12.88
6145	39	9.64	9.37	12.52
6305	71	9.88	9.70	12.80
6385	87	9.99	9.77	12.89
6465	103	9.72	9.96	12.85
6545	119	9.61	9.75	12.69
6705	151	9.91	9.99	12.96
6785	167	9.64	9.48	12.57
6865	183	9.88	9.99	12.95
6945	199	9.62	9.48	12.56
7025	215	9.99	9.87	12.94



FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of element</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 12 of 31

Table 3-5
6 GHz WLAN Maximum Average RF Power – 802.11ax 160 MHz BW

6GHz (160MHz) 802.11ax Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
6025	15	9.99	9.71	12.86
6185	47	9.61	9.25	12.44
6345	79	9.96	9.74	12.86
6505	111	9.72	9.97	12.86
6665	143	9.82	9.80	12.82
6825	175	9.70	9.99	12.86
6985	207	9.58	9.64	12.62

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.




Figure 3-1
Power Measurement Setup

FCC ID: A3LSMF926B	 <small>Proud to be part of</small> 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 13 of 31	

4 SYSTEM VERIFICATION




4.1 SAR Test System Verification

Table 4-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
05/28/2021	6500 Head	21.0	6000	5.406	33.122	5.480	35.100	-1.35%	-5.64%
			6065	5.469	32.806	5.557	35.022	-1.58%	-6.33%
			6305	5.785	32.566	5.840	34.734	-0.94%	-6.24%
			6485	6.016	32.277	6.052	34.518	-0.59%	-6.49%
			6500	6.019	32.225	6.070	34.500	-0.84%	-6.59%
			6545	6.089	32.085	6.122	34.446	-0.54%	-6.85%
			6785	6.371	31.607	6.400	34.158	-0.45%	-7.47%
			7000	6.559	31.237	6.650	33.900	-1.37%	-7.86%
			7025	6.618	31.140	6.680	33.870	-0.93%	-8.06%
			7500	7.153	30.305	7.240	33.300	-1.20%	-8.99%
05/31/2021	6500 Head	20.7	6000	5.510	35.441	5.480	35.100	0.55%	0.97%
			6065	5.594	35.008	5.557	35.022	0.67%	-0.04%
			6305	5.987	34.980	5.840	34.734	2.52%	0.71%
			6485	6.225	34.619	6.052	34.518	2.86%	0.29%
			6500	6.225	34.564	6.070	34.500	2.55%	0.19%
			6545	6.303	34.432	6.122	34.446	2.96%	-0.04%
			6785	6.594	33.944	6.400	34.158	3.03%	-0.63%
			7000	6.789	33.525	6.650	33.900	2.09%	-1.11%
			7025	6.875	33.453	6.680	33.870	2.92%	-1.23%
			7500	7.461	32.613	7.240	33.300	3.05%	-2.06%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

The SAR measurement systems have implemented the SAR error compensation algorithms documented in IEC 62209-2 to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters for all frequencies. The test lab has verified that the required SAR error compensation algorithm has been correctly applied to only scale up the measured SAR, not downward.

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 14 of 31

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix F.

Table 4-2
System Verification Results

TARGET & MEASURED																							
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)	Measured 4cm ² APD (W/m ²)	1W Target 4cm ² APD (W/m ²)	1 W Normalized 4cm ² APD (W/m ²)	Deviation 4cm ² APD (%)			
M	6500	Head	05/28/2021	23.6	21.0	0.050	1018	7570	14.100	292.000	282.000	-3.42%	2.630	53.800	52.600	-2.23%	65.7000	1350.0000	1314.000	-2.67%			
M	6500	Head	05/31/2021	21.5	20.8	0.050	1018	7570	13.900	292.000	278.000	-4.79%	2.550	53.800	51.000	-5.20%	63.8000	1350.0000	1276.000	-5.48%			




Figure 4-1
System Verification Setup Diagram



Figure 4-2
System Verification Setup Photo

FCC ID: A3LSMF926B	 PCTEST Proud to be part of  element	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 15 of 31

4.2 Power Density Test System Verification

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check.

The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.










Figure 4-3
System Verification Setup Photo

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 16 of 31

**Table 4-3
10 GHz Verifications**

System Verification											
System	Frequency (GHz)	Date	Source S/N	Probe S/N	Prad (mW)	Normal psPD (W/m ² over 4 cm ²)		Deviation (dB)	Total psPD (W/m ² over 4 cm ²)		Deviation (dB)
						Measured	Target		Measured	Target	
Q	10	05/24/2021	1004	9389	74.8	44.30	42.70	0.16	44.60	42.90	0.17
R	10	05/24/2021	1004	9523	74.8	42.20	42.70	-0.05	42.40	42.90	-0.05
Q	10	05/26/2021	1004	9389	74.8	46.80	42.70	0.40	47.10	42.90	0.41
R	10	05/26/2021	1004	9523	74.8	46.20	42.70	0.34	46.40	42.90	0.34
Q	10	05/28/2021	1004	9389	74.8	42.40	42.70	-0.03	42.70	42.90	-0.02
R	10	05/28/2021	1004	9523	74.8	43.00	42.70	0.03	43.10	42.90	0.02
R	10	06/01/2021	1004	9523	74.8	41.20	42.70	-0.16	41.30	42.90	-0.17

Note: A **10 mm distance spacing** was used from the reference horn antenna aperture to the probe element.

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of </small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 17 of 31	

5

DATA SUMMARY

5.1 SAR and Absorbed Power Density Results

Table 5-1
6 GHz WLAN Head MIMO SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															(W/kg)			(W/kg)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	Right	Cheek	MIMO	UD70537M	16.3	99.7	0.176	1.030	1.003	0.182	
6075.00	25	802.11ax	OFDM	20	10.5	10.12	10.5	9.71	-0.03	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.035	1.199	1.003	0.042	
6275.00	65	802.11ax	OFDM	20	10.5	10.23	10.5	9.95	0.06	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.099	1.135	1.003	0.113	
6475.00	105	802.11ax	OFDM	20	10.5	10.11	10.5	10.47	0.01	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.171	1.094	1.003	0.188	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.07	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.177	1.030	1.003	0.183	
6995.00	209	802.11ax	OFDM	20	10.5	10.10	10.5	10.33	0.18	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.235	1.096	1.003	0.258	A1
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	Left	Cheek	MIMO	UD70537M	16.3	99.7	0.110	1.030	1.003	0.114	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.07	Left	Tilt	MIMO	UD70537M	16.3	99.7	0.131	1.030	1.003	0.135	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak												Head 1.6 W/kg (mW/g) averaged over 1 gram								
Uncontrolled Exposure/General Population																				

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-2
6 GHz WLAN Body-worn MIMO SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															(W/kg)			(W/kg)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	15	MIMO	UD70537M	16.3	Back	99.7	0.007	1.030	1.003	0.007	A2
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

FCC ID: A3LSMF926B			WIFI 6 GHZ RF EXPOSURE EVALUATION			Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021		DUT Type: Portable Handset		Page 18 of 31	

Table 5-3
6 GHz WLAN Phablet MIMO SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.																(W/kg)			(W/kg)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.13	0	MIMO	-	UD70537M	16.3	Back	99.7	0.005	1.030	1.003	0.005	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	0	MIMO	1	UD70537M	16.3	Front	99.7	0.136	1.030	1.003	0.141	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.06	0	MIMO	2	UD70537M	16.3	Front	99.7	0.088	1.030	1.003	0.091	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.02	0	MIMO	-	UD70537M	16.3	Top	99.7	0.137	1.030	1.003	0.142	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.145	1.030	1.003	0.150	A3
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.18	0	MIMO	-	UD70537M	16.3	Left	99.7	0.005	1.030	1.003	0.005	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Phablet 4 W/kg (mW/g) averaged over 10 gram											

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-4
6 GHz WLAN UMPC Body MIMO SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.																(W/kg)			(W/kg)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	10	MIMO	-	UD70537M	16.3	Back	99.7	0.015	1.030	1.003	0.015	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.20	10	MIMO	1	UD70537M	16.3	Front	99.7	0.022	1.030	1.003	0.023	A4
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.20	10	MIMO	2	UD70537M	16.3	Front	99.7	0.006	1.030	1.003	0.006	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.04	10	MIMO	-	UD70537M	16.3	Top	99.7	0.014	1.030	1.003	0.014	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.03	10	MIMO	-	UD70537M	16.3	Bottom	99.7	0.021	1.030	1.003	0.022	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										UMPC Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-5
6 GHz WLAN UMPC Extremity MIMO SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.																(W/kg)			(W/kg)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.04	0	MIMO	1	UD70537M	16.3	Back	99.7	0.130	1.030	1.003	0.134	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.02	0	MIMO	2	UD70537M	16.3	Back	99.7	0.048	1.030	1.003	0.050	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.08	0	MIMO	1	UD70537M	16.3	Front	99.7	0.129	1.030	1.003	0.133	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	0	MIMO	2	UD70537M	16.3	Front	99.7	0.046	1.030	1.003	0.048	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.08	0	MIMO	-	UD70537M	16.3	Top	99.7	0.127	1.030	1.003	0.131	
6075.00	25	802.11ax	OFDM	20	10.5	10.12	10.5	9.71	-0.01	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.125	1.199	1.003	0.150	
6275.00	65	802.11ax	OFDM	20	10.5	10.23	10.5	9.95	0.00	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.160	1.135	1.003	0.182	
6475.00	105	802.11ax	OFDM	20	10.5	10.11	10.5	10.47	-0.02	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.147	1.094	1.003	0.161	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.01	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.161	1.030	1.003	0.166	A5
6995.00	209	802.11ax	OFDM	20	10.5	10.10	10.5	10.33	0.05	0	MIMO	-	UD70537M	16.3	Bottom	99.7	0.160	1.096	1.003	0.176	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										UMPC Extremity 4 W/kg (mW/g) averaged over 10 gram											

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.



FCC ID: A3LSMF926B	 Proud to be part of elements	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 19 of 31

Table 5-6
6 GHz WLAN Head MIMO Absorbed Power Density

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Measured APD	Plot #
MHz	Ch.															W/m² (4cm²)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	Right	Cheek	MIMO	UD70537M	16.3	99.7	0.984	
6075.00	25	802.11ax	OFDM	20	10.5	10.12	10.5	9.71	-0.03	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.234	
6275.00	65	802.11ax	OFDM	20	10.5	10.23	10.5	9.95	0.06	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.490	
6475.00	105	802.11ax	OFDM	20	10.5	10.11	10.5	10.47	0.01	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.857	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.07	Right	Tilt	MIMO	UD70537M	16.3	99.7	0.939	
6995.00	209	802.11ax	OFDM	20	10.5	10.10	10.5	10.33	0.18	Right	Tilt	MIMO	UD70537M	16.3	99.7	1.370	A1
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	Left	Cheek	MIMO	UD70537M	16.3	99.7	0.829	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.07	Left	Tilt	MIMO	UD70537M	16.3	99.7	1.030	

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-7
6 GHz WLAN Body-worn MIMO Absorbed Power Density

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Measured APD	Plot #
MHz	Ch.															W/m² (4cm²)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	15.0	MIMO	UD70537M	16.3	Back	99.7	0.063	A2

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-8
6 GHz WLAN Phablet MIMO Absorbed Power Density

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Measured APD	Plot #
MHz	Ch.																W/m² (4cm²)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.13	0	MIMO	-	UD70537M	16.3	Back	99.7	0.132	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	0	MIMO	1	UD70537M	16.3	Front	99.7	3.410	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.06	0	MIMO	2	UD70537M	16.3	Front	99.7	2.200	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.02	0	MIMO	-	UD70537M	16.3	Top	99.7	3.420	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	0	MIMO	-	UD70537M	16.3	Bottom	99.7	3.630	A3
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.18	0	MIMO	-	UD70537M	16.3	Left	99.7	0.124	

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.




FCC ID: A3LSMF926B	 Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 20 of 31

Table 5-9
6 GHz WLAN UMPC Body MIMO Absorbed Power Density




MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Measured APD	Plot #
MHz	Ch.																W/m² (4cm²)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.03	10	MIMO	-	UD70537M	16.3	Back	99.7	0.136	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.20	10	MIMO	1	UD70537M	16.3	Front	99.7	0.207	A4
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.20	10	MIMO	2	UD70537M	16.3	Front	99.7	0.035	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.04	10	MIMO	-	UD70537M	16.3	Top	99.7	0.079	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.03	10	MIMO	-	UD70537M	16.3	Bottom	99.7	0.138	

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.

Table 5-10
6 GHz WLAN UMPC Extremity MIMO Absorbed Power Density

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Drift [dB]	Spacing (mm)	Antenna Config.	Peak Number	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Measured APD	Plot #
MHz	Ch.																W/m ² (4cm ²)	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.04	0	MIMO	1	UD70537M	16.3	Back	99.7	3.260	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.02	0	MIMO	2	UD70537M	16.3	Back	99.7	1.210	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.08	0	MIMO	1	UD70537M	16.3	Front	99.7	3.220	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.00	0	MIMO	2	UD70537M	16.3	Front	99.7	1.160	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	0.08	0	MIMO	-	UD70537M	16.3	Top	99.7	3.180	
6075.00	25	802.11ax	OFDM	20	10.5	10.12	10.5	9.71	-0.01	0	MIMO	-	UD70537M	16.3	Bottom	99.7	3.130	
6275.00	65	802.11ax	OFDM	20	10.5	10.23	10.5	9.95	0.00	0	MIMO	-	UD70537M	16.3	Bottom	99.7	3.990	
6475.00	105	802.11ax	OFDM	20	10.5	10.11	10.5	10.47	-0.02	0	MIMO	-	UD70537M	16.3	Bottom	99.7	3.670	
6675.00	145	802.11ax	OFDM	20	10.5	10.37	10.5	10.38	-0.01	0	MIMO	-	UD70537M	16.3	Bottom	99.7	4.010	A5
6995.00	209	802.11ax	OFDM	20	10.5	10.10	10.5	10.33	0.05	0	MIMO	-	UD70537M	16.3	Bottom	99.7	4.010	

Note: To achieve the 13.5 dBm maximum allowed MIMO power shown in the documentation, each antenna transmits at a maximum allowed power of 10.5 dBm.



FCC ID: A3LSMF926B	 Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 21 of 31	

SAR and Absorbed Power Density General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" when in closed condition since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
9. Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.
10. Per FCC guidance, SAR was performed using 6.5 GHz SAR probe calibration factors. Per October 2020 TCB Workshop notes, 5 channels were tested. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements.
11. Per FCC KDB Publication 941225 D07v01r02, this device is considered a "UMPC mini-tablet" when it is in open configuration. UMPC body 1g SAR tests are required on all surfaces and edges ≤ 25 mm from a transmitting antenna. Therefore, to address hand exposure, UMPC extremity 10g SAR tests are required at a test separation distance of 0 mm for all measured 1g SAR (at 10 mm) configurations.

WLAN Notes:

1. WIFI 6 GHz operations are limited to MIMO operations only (does not support stand-alone mode). Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by making a SAR measurement with both antennas transmitting simultaneously.
2. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
3. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
4. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
5. When multiple SAR peaks were observed due to separation of the Ant 1 and Ant 2 while operating in MIMO mode, separate zoom scans were evaluated over each antenna location. Peak 1 represents the zoom scan centered over WIFI Antenna 1, while Peak 2 represents the zoom scan centered over WIFI Antenna 2.

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of element</small>	WIFI 6 GHz RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 22 of 31



5.2 Power Density Results

Table 5-11
6 GHz WLAN MIMO Power Density - Closed

MEASUREMENT RESULTS																				
Frequency (MHz)	Channel	Mode	Service	Bandwidth (MHz)	Power Drift (dB)	Spacing (mm)	Antenna Config.	Peak Number	DUT Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Grid Step (A)	IPD (W/m²)	Scaling Factor for Measurement Uncertainty per IEC 62479	Normal psPD (W/m²)	Scaled Normal psPD (W/m²)	Total psPD (W/m²)	Scaled Total psPD (W/m²)	Plot #
6675.00	145	802.11ax	OFDM	20	-0.03	2	MIMO	1	UD70537M	16.3	Back	99.7	0.05	N/A	1.554	0.275	0.427	0.278	0.432	
6675.00	145	802.11ax	OFDM	20	-0.13	2	MIMO	2	UD70537M	16.3	Back	99.7	0.05	N/A	1.554	0.439	0.682	0.444	0.690	
6675.00	145	802.11ax	OFDM	20	-0.03	2	MIMO	1	UD70537M	16.3	Front	99.7	0.05	N/A	1.554	0.809	1.257	0.960	1.492	
6675.00	145	802.11ax	OFDM	20	0.08	2	MIMO	2	UD70537M	16.3	Front	99.7	0.05	1.92	1.554	1.120	1.740	1.270	1.974	
6675.00	145	802.11ax	OFDM	20	0.08	8.98	MIMO	2	UD70537M	16.3	Front	99.7	0.05	1.64	1.554	0.636	0.988	0.665	1.033	
6675.00	145	802.11ax	OFDM	20	0.06	2	MIMO	-	UD70543M	16.3	Top	99.7	0.05	N/A	1.554	0.134	0.208	0.159	0.247	
6675.00	145	802.11ax	OFDM	20	0.16	2	MIMO	-	UD70543M	16.3	Bottom	99.7	0.05	N/A	1.554	0.285	0.443	0.377	0.586	
6675.00	145	802.11ax	OFDM	20	0.00	2	MIMO	1	UD70543M	16.3	Left	99.7	0.05	N/A	1.554	0.148	0.230	0.153	0.238	
6675.00	145	802.11ax	OFDM	20	0.00	2	MIMO	2	UD70543M	16.3	Left	99.7	0.05	N/A	1.554	0.100	0.155	0.109	0.169	
6075.00	25	802.11ax	OFDM	20	0.05	2	MIMO	2	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	2.210	3.434	2.320	3.605	
6275.00	65	802.11ax	OFDM	20	-0.11	2	MIMO	2	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	3.910	6.076	4.110	6.387	A6
6475.00	105	802.11ax	OFDM	20	-0.18	2	MIMO	2	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	2.920	4.538	3.040	4.724	
6995.00	209	802.11ax	OFDM	20	0.07	2	MIMO	2	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	2.980	4.631	3.110	4.833	
47 CFR §1.1310 - SAFETY LIMIT Spatial Average Uncontrolled Exposure / General Population									Power Density 10 W/m² averaged over 4 cm²											


Table 5-12
6 GHz WLAN MIMO Power Density – Open

MEASUREMENT RESULTS																				
Frequency (MHz)	Channel	Mode	Service	Bandwidth (MHz)	Power Drift (dB)	Spacing (mm)	Antenna Config.	Peak Number	DUT Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Grid Step (A)	IPD (W/m²)	Scaling Factor for Measurement Uncertainty per IEC 62479	Normal psPD (W/m²)	Scaled Normal psPD (W/m²)	Total psPD (W/m²)	Scaled Total psPD (W/m²)	Plot #
6675.00	145	802.11ax	OFDM	20	0.04	2	MIMO	1	UD70537M	16.3	Back	99.7	0.05	N/A	1.554	0.542	0.842	0.568	0.883	
6675.00	145	802.11ax	OFDM	20	-0.12	2	MIMO	2	UD70537M	16.3	Back	99.7	0.05	N/A	1.554	0.955	1.484	1.050	1.632	A7
6675.00	145	802.11ax	OFDM	20	0.04	2	MIMO	1	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	0.207	0.322	0.262	0.407	
6675.00	145	802.11ax	OFDM	20	0.30	2	MIMO	2	UD70543M	16.3	Front	99.7	0.05	N/A	1.554	0.316	0.491	0.361	0.561	
6675.00	145	802.11ax	OFDM	20	0.07	2	MIMO	-	UD70543M	16.3	Top	99.7	0.05	N/A	1.554	0.600	0.932	0.794	1.234	
6675.00	145	802.11ax	OFDM	20	0.12	2	MIMO	-	UD70543M	16.3	Bottom	99.7	0.05	N/A	1.554	0.561	0.872	0.635	0.987	
47 CFR §1.1310 - SAFETY LIMIT Spatial Average Uncontrolled Exposure / General Population									Power Density 10 W/m² averaged over 4 cm²											

FCC ID: A3LSMF926B			WIFI 6 GHz RF EXPOSURE EVALUATION			Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021		DUT Type: Portable Handset		Page 23 of 31	

Power Density General Notes

1. The manufacturer has confirmed that the devices tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
2. Batteries are fully charged at the beginning of the measurements. The DUT was connected to a wall charger for some measurements due to the test duration. It was confirmed that the charger plugged into this DUT did not impact the near-field PD test results.
3. Power density was calculated by repeated E-field measurements on two measurement planes separated by $\lambda/4$.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools.
5. Per FCC guidance and equipment manufacturer guidance, power density results were scaled according to IEC 62479:2010 for the portion of the measurement uncertainty > 30%. Total expanded uncertainty of 2.68 dB (85.4%) was used to determine the psPD measurement scaling factor.
6. Per equipment manufacturer guidance, power density was measured at $d=2\text{mm}$ and $d=\lambda/5\text{mm}$ using the same grid size and grid step size for some frequencies and surfaces. The integrated Power Density (iPD) was calculated based on these measurements. Since iPD ratio between the two distances is < 1dB, the grid step was sufficient for determining compliance at $d=2\text{mm}$.
7. WIFI 6 GHz operations are limited to MIMO operations only (does not support stand-alone mode). psPD for MIMO was evaluated by making a measurement with both antennas transmitting simultaneously.
8. When multiple peaks were observed due to separation of the Ant 1 and Ant 2 while operating in MIMO mode, separate scans were evaluated over each antenna location. Peak 1 represents the zoom scan centered over WIFI Antenna 1, while Peak 2 represents the zoom scan centered over WIFI Antenna 2. Data for additional channels was performed for the antenna with the highest peak.

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 24 of 31


6

EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	9/16/2020	Annual	9/16/2021	WL25-1
Agilent	N9038A	MXE EMI Receiver	8/11/2020	Annual	8/11/2021	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY52350166
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/9/2020	Annual	9/9/2021	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/10/2020	Annual	8/10/2021	103200
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107
SPEAG	EUmmWV3	EUmmWV3 Probe	11/16/2020	Annual	11/16/2021	9389
SPEAG	EUmmWV4	EUmmWV4 Probe	1/11/2021	Annual	1/11/2022	9523
SPEAG	SM 003 100 AA	10GHz System Verification Antenna	8/14/2020	Annual	8/14/2021	1004
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/7/2021	Annual	4/7/2022	1582
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/10/2021	Annual	3/10/2022	1368
Agilent	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY52350166
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Keysight Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	7/17/2020	Annual	7/17/2021	MY49430494
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	7/15/2020	Annual	7/15/2021	100342
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107
SPEAG	EX3DV4	SAR Probe	12/15/2020	Annual	12/15/2021	7570
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/7/2020	Annual	12/7/2021	859
SPEAG	D6.5GHzV2	6.5GHz SAR Dipole	12/11/2020	Annual	12/11/2021	1018
Control Company	4352	Long Stem Thermometer	6/26/2019	Biennial	6/26/2021	192282753
Agilent	SMF100A	Signal Generator	5/7/2020	Biennial	5/7/2022	101590
Amplifier Research	15S1G6	Amplifier	N/A	CBT	N/A	433975
Rohde & Schwarz	SMU200A	Vector Signal Generator	5/12/2020	Biennial	5/12/2022	104145
Rohde & Schwarz	ZNLE6	Vector Network Analyzer	9/29/2020	Annual	9/29/2021	101307

Note:


- Each equipment item was used solely within its respective calibration period.
- CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 25 of 31

7 MEASUREMENT UNCERTAINTIES



Applicable for SAR measurements:

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i lgm	c _i l0 gms	lgm u (± %)	l0gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	9.3	N	1	1	1	9.3	9.3	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	E.2.3	2	R	1.732	1	1	1.2	1.2	∞
Linearity	E.2.4	0.3	N	1	1	1	0.3	0.3	∞
System Detection Limits	E.2.4	0.25	R	1.732	1	1	0.1	0.1	∞
Readout Electronics	E.2.6	0.3	N	1	1	1	0.3	0.3	∞
Response Time	E.2.7	0.8	R	1.732	1	1	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Conditions - Noise	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.732	1	1	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	6.7	R	1.732	1	1	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	4	R	1.732	1	1	2.3	2.3	∞
Test Sample Related									
Test Sample Positioning	E.4.2	2.70	N	1	1	1	2.7	2.7	35
Device Holder Uncertainty	E.4.1	1.67	N	1	1	1	1.7	1.7	5
Output Power Variation - SAR drift measurement	E.2.9	5	R	1.732	1	1	2.9	2.9	∞
SAR Scaling	E.6.5	0	R	1.732	1	1	0.0	0.0	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	E.3.3	4.2	N	1	0.78	0.71	3.3	3.0	76
Liquid Permittivity - measurement uncertainty	E.3.3	4.1	N	1	0.23	0.26	0.9	1.1	75
Liquid Conductivity - Temperature Uncertainty	E.3.4	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	E.3.4	0.6	R	1.732	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)							RSS	13.3	13.1
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	26.5	26.1

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 26 of 31

Applicable for Power Density Measurements:




a	b	c	d	e	f = c x f/e	g
Uncertainty Component	Unc. (± dB)	Prob. Dist.	Div.	c _i	u _i (± dB)	v _i
Measurement System						
Calibration	0.49	N	1	1	0.49	∞
Probe Correction	0.00	R	1.73	1	0.00	∞
Frequency Response	0.20	R	1.73	1	0.12	∞
Sensor Cross Coupling	0.00	R	1.73	1	0.00	∞
Isotropy	0.50	R	1.73	1	0.29	∞
Linearity	0.20	R	1.73	1	0.12	∞
Probe Scattering	0.00	R	1.73	1	0.00	∞
Probe Positioning offset	0.30	R	1.73	1	0.17	∞
Probe Positioning Repeatability	0.04	R	1.73	1	0.02	∞
Sensor Mechanical Offset	0.00	R	1.73	1	0.00	∞
Probe Spatial Resolution	0.00	R	1.73	1	0.00	∞
Field Impedance Dependence	0.00	R	1.73	1	0.00	∞
Amplitude and Phase Drift	0.00	R	1.73	1	0.00	∞
Amplitude and Phase Noise	0.04	R	1.73	1	0.02	∞
Measurement Area Truncation	0.00	R	1.73	1	0.00	∞
Data Acquisition	0.03	N	1	1	0.03	∞
Sampling	0.00	R	1.73	1	0.00	∞
Field Reconstruction	2.00	R	1.73	1	1.15	∞
Forward Transformation	0.00	R	1.73	1	0.00	∞
Power Density Scaling	0.00	R	1.73	1	0.00	∞
Spatial Averaging	0.10	R	1.73	1	0.06	∞
System Detection Limit	0.04	R	1.73	1	0.02	∞
Test Sample Related						
Probe Coupling with DUT	0.00	R	1.73	1	0.00	∞
Modulation Response	0.40	R	1.73	1	0.23	∞
Integration Time	0.00	R	1.73	1	0.00	∞
Response Time	0.00	R	1.73	1	0.00	∞
Device Holder Influence	0.10	R	1.73	1	0.06	∞
DUT alignment	0.00	R	1.73	1	0.00	∞
RF Ambient Conditions	0.04	R	1.73	1	0.02	∞
Ambient Reflections	0.04	R	1.73	1	0.02	∞
Immunity/Secondary Reception	0.00	R	1.73	1	0.00	∞
Drift of DUT	0.21	R	1.73	1	0.12	∞
Combined Standard Uncertainty (k=1)					RSS	1.34
Expanded Uncertainty (95% CONFIDENCE LEVEL)					k=2	2.68

FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 27 of 31

9.1 Measurement Conclusion


The SAR and power density measurements indicate that the DUT complies with the RF radiation exposure limits of the FCC, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the RF Exposure and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.



FCC ID: A3LSMF926B	 PCTEST Proud to be part of 	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 28 of 31

10 REFERENCES



- [1] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [2] IEC TR 63170:2018, Measurement Procedure for the Evaluation of Power Density Related to Human Exposure to Radiofrequency Fields from Wireless Communication Devices Operating between 6 GHz and 100 GHz
- [3] IEC TR 62630 : 2010, Guidance for Evaluating Exposure from Multiple Electromagnetic Sources
- [4] K. Pokovic, T. Schmid, J. Frohlich, and N. Kuster. Novel Probes and Evaluation Procedures to Assess Field Magnitude and Polarization. IEEE Transactions on Electromagnetic Compatibility 42(2): 240 -244, 2000
- [5] R. W. Gerchberg and W. O. Saxton. A Practical Algorithm for the Determination of Phase from Image and Diffraction Plane Pictures. Optik 35(2): 237 – 246, 1972
- [6] A. P. Anderson and S. Sali. New Possibilities for Phaseless Microwave Diagnostics. Part 1: Error Reduction Techniques. IEE Proceedings H – Microwaves, Antennas and Propagation 132(5): 290 – 298, 1985
- [7] FCC KDB 865664 D02 v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz. Federal Communications Commission – Office of Engineering and Technology, Laboratory Division.
- [8] FCC KDB 447498 D01 v02r01: RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices. Federal Communications Commission – Office of Engineering and Technology, Laboratory Division.
- [9] November 2017 Telecommunications Certification Body Council (TCBC) Workshop Notes
- [10] October 2018 Telecommunications Certification Body Council (TCBC) Workshop Notes
- [11] April 2019 Telecommunications Certification Body Council (TCBC) Workshop Notes
- [12] November 2019 Telecommunications Certification Body Council (TCBC) Workshop Notes
- [13] SPEAG DASY6 System Handbook (September 2019)
- [14] SPEAG DASY6 Application Note (Interim Procedures for Devices Operating at 6-10 GHz)
- [15] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [16] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [17] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 29 of 31

- [18] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [19] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [20] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [21] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [22] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [23] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [24] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [25] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [26] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [27] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [28] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [29] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [30] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [31] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [32] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [33] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [34] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.

FCC ID: A3LSMF926B	 PCTEST <small>Proud to be part of</small>	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset		Page 30 of 31

- [35] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [36] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [37] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [38] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [39] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [40] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [41] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [42] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [43] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMF926B	 PCTEST Proud to be part of	WIFI 6 GHZ RF EXPOSURE EVALUATION		Approved by: Technical Manager
Document S/N: 1M2104190044-23.A3L (Rev 1)	Test Dates: 05/24/2021 – 06/01/2021	DUT Type: Portable Handset	Page 31 of 31	