Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5845MHz
Channel:	169



Plot 7-372. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-373. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5885MHz
Channel:	177



Plot 7-374. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-375. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)

7.6.4 MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-376. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)



Plot 7-377. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-378. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-379. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102



Plot 7-380. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-381. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159



Plot 7-382. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5835MHz
Channel:	167



Plot 7-383. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-384. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5875MHz
Channel:	175



Plot 7-385. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-386. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)

7.6.5 MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42



Plot 7-387. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)



Plot 7-388. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-389. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-390. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106



Plot 7-391. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-392. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-393. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5855MHz
Channel:	171



Plot 7-394. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-395. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5855MHz
Channel:	171



Plot 7-396. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)



Plot 7-397. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)

7.6.6 MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50



Plot 7-398. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)



Plot 7-399. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50



Plot 7-400. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-401. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5570MHz
Channel:	114



Plot 7-402. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-403. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5815MHz
Channel:	163



Plot 7-404. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5815MHz
Channel:	163



Plot 7-405. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)

7.6.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-45 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [µV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-45. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



Figure 7-6. Radiated Test Setup < 30MHz



Figure 7-7. Radiated Test Setup < 1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-45.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

MIMO Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209



Plot 7-406. Radiated Spurious Plot below 1GHz MIMO (802.11a – U3 Ch. 157)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
32.36	Quasi-Peak	V	-	-	-96.96	26.09	36.13	40.00	-3.87
35.98	Quasi-Peak	V	-	-	-98.32	22.54	31.22	40.00	-8.78
81.00	Quasi-Peak	V	-	-	-96.47	14.80	25.33	40.00	-14.67
711.00	Quasi-Peak	V	-	-	-95.24	28.85	40.61	46.02	-5.41

Table 7-46. Radiated Spurious Emissions below 1GHz MIMO

7.7 Line-Conducted Test Data

§15.407

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-47. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
5. Margin (dB) = QP/AV Limit (dBμV) - QP/AV Level (dBμV)
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.



Plot 7-407. Line Conducted Plot with 802.11a UNII Band 1 (L1) - Open



Plot 7-408. Line Conducted Plot with 802.11a UNII Band 1 (N) - Open



Plot 7-409. Line Conducted Plot with 802.11a UNII Band 2A (L1) - Open



Plot 7-410. Line Conducted Plot with 802.11a UNII Band 2A (N) - Open



Plot 7-411. Line Conducted Plot with 802.11a UNII Band 2C (L1) - Open



Plot 7-412. Line Conducted Plot with 802.11a UNII Band 2C (N) - Open



Plot 7-413. Line Conducted Plot with 802.11a UNII Band 3 (L1) - Open



Plot 7-414. Line Conducted Plot with 802.11a UNII Band 3 (N) - Open



Plot 7-415. Line Conducted Plot with 802.11a UNII Band 1 (L1) - Closed



Plot 7-416. Line Conducted Plot with 802.11a UNII Band 1 (N) - Closed



Plot 7-417. Line Conducted Plot with 802.11a UNII Band 2A (L1) - Closed



Plot 7-418. Line Conducted Plot with 802.11a UNII Band 2A (N) - Closed



Plot 7-419. Line Conducted Plot with 802.11a UNII Band 2C (L1) - Closed



Plot 7-420. Line Conducted Plot with 802.11a UNII Band 2C (N) - Closed



Plot 7-421. Line Conducted Plot with 802.11a UNII Band 3 (L1) - Closed



Plot 7-422. Line Conducted Plot with 802.11a UNII Band 3 (N) - Closed

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF936B** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.