



PART 0 SAR CHAR REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

04/20/2022 - 06/23/2022

Test Site/Location:

Element, Columbia, MD, USA

Document Serial No.:

1M2204010046-28.A3L(Rev1)

FCC ID:

A3LSMF936U

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD

Report Type:

Part 0 SAR Characterization

DUT Type:

Portable Handset

Model(s):

SM-F936U

Additional Model:

SM-F936U1

Note: This revised Test Report (S/N: 1M2204010046-28.A3L (Rev1)) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Test results reported herein relate only to the item(s) tested.



RJ Ortanez
Executive Vice President



FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 1 of 12

REV 1.1
04/08/2022

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
1.1	Device Overview	3
1.2	Time-Averaging for SAR and Power Density	4
1.3	Nomenclature for Part 0 Report	4
1.4	Bibliography	4
2	SAR AND POWER DENSITY MEASUREMENTS	5
2.1	SAR Definition	5
2.2	SAR Measurement Procedure	5
3	SAR CHARACTERIZATION	7
3.1	DSI and SAR Determination	7
3.2	SAR Design Target	7
3.3	SAR Char	8
4	EQUIPMENT LIST	11
5	MEASUREMENT UNCERTAINTIES	12
	APPENDIX A: SAR TEST RESULTS FOR P_{Limit} CALCULATIONS	1

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 2 of 12

1 DEVICE UNDER TEST

1.1 Device Overview

This device uses the Qualcomm® Gen2 Smart Transmit feature to control and manage transmitting power in real time and to ensure the time-averaged RF exposure is in compliance with the FCC requirement at all times for 2G/3G/4G/5G WWAN operations. Additionally, this device supports WLAN/BT/NFC/UWB technologies, but the output power of these modems is not controlled by the Smart Transmit algorithm.

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 14	Voice/Data	790.5 - 795.5 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
LTE Band 38	Voice/Data	2572.5 - 2617.5 MHz
LTE Band 48	Voice/Data	3552.5 - 3697.5 MHz
NR Band n71	Voice/Data	665.5 - 695.5 MHz
NR Band n12	Voice/Data	701.5 - 713.5 MHz
NR Band n5 (Cell)	Voice/Data	826.5 - 846.5 MHz
NR Band n66 (AWS)	Voice/Data	1712.5 - 1777.5 MHz
NR Band n25 (PCS)	Voice/Data	1852.5 - 1912.5 MHz
NR Band n2 (PCS)	Voice/Data	1852.5 - 1907.5 MHz
NR Band n30	Voice/Data	2307.5 - 2312.5 MHz
NR Band n7	Voice/Data	2502.5 - 2567.5 MHz
NR Band n41	Voice/Data	2506.02 - 2679.99 MHz
NR Band n38	Voice/Data	2575 - 2615 MHz
NR Band n48	Voice/Data	3555 - 3694.98 MHz
NR Band n77 DoD	Voice/Data	3455.01 - 3544.98 MHz
NR Band n77	Voice/Data	3705 - 3975 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
U-NII-4	Voice/Data	5845 - 5885 MHz
U-NII-5	Voice/Data	5935 - 6415 MHz
U-NII-6	Voice/Data	6435 - 6525 MHz
U-NII-7	Voice/Data	6535 - 6875 MHz
U-NII-8	Voice/Data	6895 - 7115 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
NR Band n258	Data	24250 - 24450 MHz; 24750 - 25250 MHz
NR Band n260	Data	37000 - 40000 MHz
NR Band n261	Data	27500 - 28350 MHz
UWB	Data	6489.6 - 7987.2 MHz

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 3 of 12

1.2 Time-Averaging for SAR and Power Density

This device is enabled with Qualcomm® Gen2 Smart Transmit algorithm to control and manage transmitting power in real time and to ensure that the time-averaged RF exposure from 2G/3G/4G/5G Sub-6 NR WWAN is in compliance with FCC requirements. This Part 0 report shows SAR characterization of WWAN radios for 2G/3G/4G/5G Sub-6 NR. Characterization is achieved by determining P_{Limit} for 2G/3G/4G/5G Sub-6 NR that corresponds to the exposure design targets after accounting for all device design related uncertainties, i.e., SAR_design_target (< FCC SAR limit) for sub-6 radio. The SAR characterization is denoted as SAR Char in this report. Section 1.3 includes a nomenclature of the specific terms used in this report.

The compliance test under the static transmission scenario and simultaneous transmission analysis are reported in Part 1 report. The validation of the time-averaging algorithm and compliance under the dynamic (time-varying) transmission scenario for WWAN technologies are reported in Part 2 report (report SN could be found in Section 1.4 – Bibliography).

1.3 Nomenclature for Part 0 Report

Technology	Term	Description
2G/3G/4G/5G Sub-6 NR	P_{limit}	Power level that corresponds to the exposure design target (<i>SAR_design_target</i>) after accounting for all device design related uncertainties
	P_{max}	Maximum tune up output power
	<i>SAR_design_target</i>	Target SAR level < FCC SAR limit after accounting for all device design related uncertainties
	<i>SAR Char</i>	Table containing P_{limit} for all technologies and bands

1.4 Bibliography

Report Type	Report Serial Number
FCC Part 0 PD Characterization Report	
FCC SAR Evaluation Report (Part 1)	1M2204010046-22.A3L
FCC PD Evaluation Report (Part 1)	1M2204010046-25.A3L
RF Exposure Part 2 Test Report	1M2204010046-26.A3L
RF Exposure Compliance Summary	1M2204010046-27.A3L

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 4 of 12

2 SAR AND POWER DENSITY MEASUREMENTS

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

Equation 2-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ	=	conductivity of the tissue-simulating material (S/m)
ρ	=	mass density of the tissue-simulating material (kg/m ³)
E	=	Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

2.2 SAR Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 2-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 2-1) and IEEE 1528-2013. On the




Figure 2-1
Sample SAR Area Scan

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 5 of 12

basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):

- a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 2-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

**Table 2-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04***

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{area}, \Delta y_{area}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{zoom}, \Delta y_{zoom}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 6 of 12

3 SAR CHARACTERIZATION

3.1 DSI and SAR Determination

This device uses different Device State Index (DSI) to configure different time averaged power levels based on certain exposure scenarios. Depending on the detection scheme implemented in the smartphone, the worst-case SAR was determined by measurements for the relevant exposure conditions for that DSI. Detailed descriptions of the detection mechanisms are included in the operational description.

When 1g SAR and 10g SAR exposure comparison is needed, the worst-case was determined from SAR normalized to 1g or 10g SAR limit.

The device state index (DSI) conditions used in Table 3-1 represent different exposure scenarios.

**Table 3-1
DSI and Corresponding Exposure Scenarios**

Scenario	Description	SAR Test Cases
Head – Folder Open (DSI = 4)	<ul style="list-style-type: none"> ▪ Device positioned next to head ▪ Receiver Active ▪ Folder Open 	<i>Head SAR per KDB Publication 648474 D04</i>
Head – Folder Closed (DSI = 5)	<ul style="list-style-type: none"> ▪ Device positioned next to head ▪ Receiver Active ▪ Folder Closed 	<i>Head SAR per KDB Publication 648474 D04</i>
Hotspot mode – Folder Open (DSI = 2/6)	<ul style="list-style-type: none"> ▪ Device transmits in hotspot mode near body ▪ Hotspot Mode Active ▪ Folder Open 	<i>UMPC Mini-Tablet SAR per KDB 941225 D07v01r02</i>
Hotspot mode – Folder Closed (DSI = 7)	<ul style="list-style-type: none"> ▪ Device transmits in hotspot mode near body ▪ Hotspot Mode Active ▪ Folder Closed 	<i>Hotspot SAR per KDB Publication 941225 D06</i>
Extremity Grip – Folder Open (DSI=2 or 8)	<ul style="list-style-type: none"> ▪ Device is held with hand and grip sensor is triggered ▪ Grip sensor triggered or earjack is active ▪ Folder Open 	<i>Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04</i>
Phablet Grip – Folder Closed (DSI=3 or 9)	<ul style="list-style-type: none"> ▪ Device is held with hand and grip sensor is triggered ▪ Grip sensor triggered or earjack is active ▪ Folder Closed 	<i>Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04</i>
Extremity – Folder Open (DSI = 0)	<ul style="list-style-type: none"> ▪ Device is held with hand and grip sensor is not triggered ▪ Distance grip sensor not triggered ▪ Folder Open 	<i>UMPC Mini-Tablet SAR per KDB 941225 D07v01r02</i>
Phablet – Folder Closed (DSI = 1)	<ul style="list-style-type: none"> ▪ Device is held with hand and grip sensor is not triggered ▪ Distance grip sensor not triggered ▪ Folder Closed 	<i>Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04</i>
Body-worn – Folder Open (DSI = 0)	<ul style="list-style-type: none"> ▪ Device being used with a body-worn accessory ▪ Folder Open 	<i>UMPC Mini-Tablet SAR per KDB 941225 D07v01r02</i>
Body-worn – Folder Closed (DSI = 1)	<ul style="list-style-type: none"> ▪ Device being used with a body-worn accessory ▪ Folder Closed 	<i>Body-worn SAR per KDB Publication 648474 D04</i>

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 7 of 12

3.2 SAR Design Target

SAR_design_target is determined by ensuring that it is less than FCC SAR limit after accounting for total device designed related uncertainties specified by the manufacturer (see Table 3-2).

Table 3-2
***SAR_design_target* Calculations**

<i>SAR_design_target</i>			
$SAR_design_target < SAR_regulatory_limit \times 10^{\frac{-Total\ Uncertainty}{10}}$			
1g SAR (W/kg)		10g SAR (W/kg)	
<i>Total Uncertainty</i>	1.0 dB	<i>Total Uncertainty</i>	1.0 dB
<i>SAR_regulatory_limit</i>	1.6 W/kg	<i>SAR_regulatory_limit</i>	4.0 W/kg
<i>SAR_design_target</i>	1.0 W/kg	<i>SAR_design_target</i>	2.5 W/kg

3.3 SAR Char

SAR test results corresponding to *Pmax* for each antenna/technology/band/DSI can be found in Appendix A.

Plimit is calculated by linearly scaling with the measured SAR at the Ppart0 to correspond to the *SAR_design_target*. When *Plimit* < *Pmax*, *Ppart0* was used as *Plimit* in the Smart Transmit EFS. When *Plimit* > *Pmax* and *Ppart0*=*Pmax*, calculated *Plimit* was used in the Smart Transmit EFS. All reported SAR obtained from the Ppart0 SAR tests was less than *SAR_Design_target*+ 1 dB Uncertainty. The final *Plimit* determination for each exposure scenario corresponding to *SAR_design_target* are shown in Table 3-3.

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 8 of 12

**Table 3-3
PLimit Determination**

Device State Index (DSI)	PLimit Determination Scenarios
0 or 1	<p>The worst-case SAR exposure is determined as maximum SAR normalized to the limit (i.e. lowest plimit) among:</p> <ol style="list-style-type: none"> 1. UMPC 1g SAR folder open <ol style="list-style-type: none"> a. For AG0: Measured SAR at 14, 12 and 18 mm for back, front, and bottom surfaces respectively and measured SAR at 10 mm for right surface. b. For AG1: Measured SAR at 10 mm for back, front, top, and right surfaces. 2. Body Worn SAR folder closed. 3. UMPC 10g SAR folder open. <ol style="list-style-type: none"> a. For AG0: Measured SAR at 14, 12 and 18 mm for back, front, and bottom surfaces respectively and measured SAR at 0 mm for right surface. b. For AG1: Measured SAR at 0 mm for back, front, top, and right surfaces. 4. Extremity SAR folder closed. <ol style="list-style-type: none"> a. For AG0: Measured SAR at 12 and 14 mm spacing for back and bottom respectively, and measured SAR at 0mm for front, left, and right surfaces b. For AG1: Measured SAR at 0 mm for back, front, top, left and right surfaces
2 or 8	<p>P_{limit} is calculated based on:</p> <ol style="list-style-type: none"> 1. For AG0: 1g Body SAR at 10 mm for back, front, bottom, and right surfaces and 10g Extremity SAR at 0 mm for back, front, bottom, and right surfaces with folder open 2. For AG1: 1g Body SAR at 10 mm for back, front, top, and right surfaces and 10g Extremity SAR at 0 mm for back, front, top, and right surfaces with folder open
3 or 9	<p>P_{limit} is calculated based on:</p> <ol style="list-style-type: none"> 1. For AG0: 10g Extremity SAR at 0 mm for back, front, bottom, left, and right surfaces with folder closed <p>For AG1: 10g Extremity SAR at 0 mm for back, front, top, left, and right surfaces with folder closed</p>
4 or 5	P_{limit} is calculated based on 1g Head SAR
6 or 7	P_{limit} is calculated based on 1g Hotspot SAR at 10 mm

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 9 of 12

**Table 3-4
SAR Characterizations**

Exposure Scenario	Folder Closed - Body-Worn		Folder Closed - Phablet Max		Folder Open - Body		Folder Open - Extremity		Folder Closed - Head		Folder Open - Head		Folder Closed - Grip Sensor Active		Folder Open - Grip Sensor Active		Folder Closed - Hotspot		Folder Open - Hotspot		Folder Closed - Earjack		Folder Open - Earjack		Maximum Tune-Up Output Power*
	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	
Averaging Volume	15 mm	14, 12, 0 mm	18, 14, 12, 10 mm	18, 14, 12, 10 mm	0 mm	0 mm	0 mm	0 mm	10 mm	0 mm	0 mm	10 mm	0 mm	10 mm	10 mm	10 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	
Spacing	1	1	0	0	5	4	3	2	2	7	6	9	8												
Configuration	1	1	0	0	5	4	3	2	2	7	6	9	8												
DSI	1	1	0	0	5	4	3	2	2	7	6	9	8												
Technology/Band	Antenna	Antenna Group																						P _{max}	
GSM 850	A, A+B	AGD		29.5				34.7		29.1		27.5		30.3		29.0		29.1		27.5				25.3	
GSM 1900	B	AGD		27.4				34.8		16.8		16.8		16.8		16.8		16.8		16.8				22.1	
UMTS 850	A, A+B	AGD		28.0				32.6		28.0		28.5		30.0		29.5		28.0		28.5				24.5	
UMTS 1750	B	AGD		27.7				34.1		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
UMTS 1900	B	AGD		27.5				35.6		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
LTE Band 71	A, A+B	AGD		27.8				33.3		27.8		28.3		30.4		28.3		27.8		29.0				24.5	
LTE Band 12	A, A+B	AGD		27.8				32.4		27.8		28.7		30.2		29.0		27.8		28.7				24.5	
LTE Band 13	A, A+B	AGD		28.2				32.6		28.2		28.2		30.1		28.5		28.2		29.4				24.5	
LTE Band 14	A, A+B	AGD		28.2				32.0		28.2		28.2		30.4		28.9		28.2		29.3				24.5	
LTE Band 26 (Cell)	A, A+B	AGD		26.8				33.1		26.8		27.2		30.1		28.2		26.8		27.2				24.5	
LTE Band 5 (Cell)	A, A+B	AGD		27.0				33.0		27.0		28.3		29.4		28.8		27.0		28.3				24.5	
LTE Band 66/4 (AWS)	B	AGD		28.5				34.3		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
LTE Band 66 (AWS)	F	AGI		19.5				21.0		19.5		19.5		19.5		19.5		19.5		19.5				24.0	
LTE Band 4 (AWS)	F	AGI		19.5		N/A		21.0		N/A		19.5		N/A		19.5		N/A		19.5		N/A		24.0	
LTE Band 25/2 (PCS)	B	AGD		27.9				34.9		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
LTE Band 25/2 (PCS)	F	AGI		19.5		N/A		21.5		N/A		19.5		N/A		19.5		N/A		19.5		N/A		24.0	
LTE Band 30	B	AGD		21.5				21.5		16.0		16.0		16.0		16.0		16.0		16.0				23.0	
LTE Band 30	F	AGI		19.5		N/A		26.5		N/A		19.5		N/A		19.5		N/A		19.5		N/A		23.0	
LTE Band 7	B	AGD		21.5				21.5		17.0		17.0		17.0		17.0		17.0		17.0				24.0	
LTE Band 7	F	AGI		18.0		N/A		26.2		N/A		18.0		N/A		18.0		N/A		18.0		N/A		24.0	
LTE Band 48	F	AGI		17.5				19.0		17.5		17.5		17.5		17.5		17.5		17.5				22.0	
LTE Band 41/38 (PC3)	B	AGD		20.0				20.0		16.0		16.0		16.0		16.0		16.0		16.0				22.0	
LTE Band 41 (PC2)	B	AGD		20.0				20.0		16.0		16.0		16.0		16.0		16.0		16.0				22.1	
LTE Band 41 (PC3)	F	AGI		18.0		N/A		27.2		N/A		18.0		N/A		18.0		N/A		18.0		N/A		22.0	
LTE Band 41 (PC2)	F	AGI		18.0		N/A		27.2		N/A		18.0		N/A		18.0		N/A		18.0		N/A		22.1	
NR Band n71	A, A+B	AGD		28.0		28.0		32.5		28.0		28.0		29.7		28.8		28.0		28.0				24.5	
NR Band n12	A, A+B	AGD		28.4				32.9		28.4		27.7		29.4		28.9		28.4		27.7				24.5	
NR Band n5 (Cell)	A, A+B	AGD		27.2				32.7		27.2		28.3		28.5		28.3		27.2		28.4				24.5	
NR Band n66 (AWS)	B	AGD		27.4				37.5		18.0		18.0		18.0		18.0		18.0		18.0				23.5	
NR Band n66 (AWS)	F	AGI		19.5				22.0		19.5		19.5		19.5		19.5		19.5		19.5				23.5	
NR Band n25/n2 (PCS)	B	AGD		25.8				33.3		18.0		18.0		18.0		18.0		18.0		18.0				23.5	
NR Band n25/n2 (PCS)	F	AGI		19.5				21.5		19.5		19.5		19.5		19.5		19.5		19.5				23.5	
NR Band n30	B	AGD		21.5				21.5		16.0		16.0		16.0		16.0		16.0		16.0				22.5	
NR Band n30	F	AGI		19.5				26.5		19.5		19.5		19.5		19.5		19.5		19.5				22.5	
NR Band n7	B	AGD		21.5				21.5		17.0		17.0		17.0		17.0		17.0		17.0				23.0	
NR Band n7	F	AGI		18.0		N/A		26.1		N/A		18.0		N/A		18.0		N/A		18.0		N/A		23.0	
NR Band n41 (PC3)/n38	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
NR Band n41 (PC2)	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				26.0	
NR Band n41 (PC3)	B	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				16.0	
NR Band n41 (PC2)	B	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				18.0	
NR Band n41 (PC3)	E	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				19.0	
NR Band n41 (PC2)	E	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				21.0	
NR Band n41 (PC3)	C	AGD		11.0				11.0		11.0		11.0		11.0		11.0		11.0		11.0				14.0	
NR Band n41 (PC2)	C	AGD		11.0				11.0		11.0		11.0		11.0		11.0		11.0		11.0				16.0	
NR Band n48	F	AGI		17.5				17.5		17.5		17.5		17.5		17.5		17.5		17.5				23.0	
NR Band n48	E	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				22.0	
NR Band n48	G	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				22.5	
NR Band n48	D	AGD		12.0				12.0		12.0		12.0		12.0		12.0		12.0		12.0				16.5	
NR Band n77 DoD (PC3)	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
NR Band n77 DoD (PC2)	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				26.0	
NR Band n77 DoD (PC3)	E	AGI		18.5				18.5		18.5		18.5		18.5		18.5		18.5		18.5				23.0	
NR Band n77 DoD (PC2)	E	AGI		18.5				18.5		18.5		18.5		18.5		18.5		18.5		18.5				25.0	
NR Band n77 DoD (PC3)	G	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				23.0	
NR Band n77 DoD (PC2)	G	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				25.0	
NR Band n77 DoD (PC3)	D	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				20.0	
NR Band n77 DoD (PC2)	D	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				22.0	
NR Band n77 (PC3)	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				24.0	
NR Band n77 (PC2)	F	AGI		18.0				18.0		18.0		18.0		18.0		18.0		18.0		18.0				26.0	
NR Band n77 (PC3)	E	AGI		18.5				18.5		18.5		18.5		18.5		18.5		18.5		18.5				23.0	
NR Band n77 (PC2)	E	AGI		18.5				18.5		18.5		18.5		18.5		18.5		18.5		18.5				25.0	
NR Band n77 (PC3)	G	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				23.0	
NR Band n77 (PC2)	G	AGI		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				25.0	
NR Band n77 (PC3)	D	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				20.0	
NR Band n77 (PC2)	D	AGD		15.0				15.0		15.0		15.0		15.0		15.0		15.0		15.0				22.0	

Notes:

- For all modes/bands, when Hotspot Mode (DSI=6/7) and Extremity sensor (DSI=2/3) are triggered at the same time, DSI=2/3 takes priority, thus the P_{limit} for DSI=2/3 is set to be less or equal to P_{limit} for DSI=6/7.
- When $P_{max} < P_{limit}$, the DUT will operate at a power level up to P_{max} .
- P_{limit} for DSI=2/8 and DSI =3/9 are the same.
- For all bands when RCV is active, DSI=4/5 takes priority over all levels.

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 10 of 12

4 EQUIPMENT LIST

For SAR measurements

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E4404B	Spectrum Analyzer	N/A	N/A	N/A	MF4511242
Agilent	E4438C	ESG Vector Signal Generator	5/10/2022	Annual	5/10/2023	MF42062659
Agilent	E4438C	ESG Vector Signal Generator	2/14/2022	Annual	2/14/2023	MF42082385
Agilent	N5380A	MWG Vector Signal Generator	6/22/2021	Annual	6/22/2022	MF42426668
Agilent	N5380A	MWG Vector Signal Generator	7/6/2021	Annual	7/6/2022	MF43023966
Agilent	8733ES	S-Parameter Vector Network Analyzer	2/11/2021	Annual	2/11/2022	MF40003841
Agilent	8733ES	S-Parameter Vector Network Analyzer	12/17/2021	Annual	12/17/2022	MF40003670
Agilent	ES515C	Wireless Communications Test Set	5/12/2022	Annual	5/12/2023	GB4384278
Agilent	ES515C	Wireless Communications Test Set	5/6/2022	Annual	5/6/2023	GB44002869
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB45170464
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433974
Amplifier Research	1551G6	Amplifier	9/15/2021	Annual	9/15/2022	433974
Amritus	MA-2466A	Power Meter	4/23/2021	Annual	4/23/2022	1351201
Amritus	MA-2466A	Power Meter	3/31/2022	Annual	3/31/2023	1138001
Amritus	MA2411B	Pulse Power Sensor	4/28/2022	Annual	4/28/2023	1207470
Amritus	MA2411B	Pulse Power Sensor	9/21/2021	Annual	9/21/2022	1349028
Amritus	MF8821C	Radio Communication Analyzer MF8821C	5/24/2022	Annual	5/24/2023	6201544518
Amritus	MF8821C	Radio Communication Analyzer MF8821C	3/31/2022	Annual	3/31/2023	6201664756
Amritus	MF8821C	Radio Communication Analyzer MF8821C	9/26/2021	Annual	9/26/2022	6201524637
Amritus	MF8821C	Radio Communication Analyzer MF8821C	8/10/2021	Annual	8/10/2022	6262242000
Amritus	MF8000A	Radio Communication Test Station	8/2/2021	Annual	8/2/2022	6272324868
Amritus	MF8000A	Radio Communication Test Station	8/2/2021	Annual	8/2/2022	6272337436
Amritus	MF8000A	Radio Communication Test Station	8/2/2021	Annual	8/2/2022	6272337437
Amritus	MA24105A	USB Power Sensor	6/1/2022	Annual	6/1/2023	1349514
Amritus	MA24105A	USB Power Sensor	7/7/2022	Annual	7/7/2023	1712553
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670623
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670613
Control Company	4040	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670635
Control Company	4040	Therm / Clock / Humidity Monitor	1/21/2021	Biennial	1/21/2023	21627418
Control Company	4040	Therm / Clock / Humidity Monitor	3/12/2021	Biennial	3/12/2023	216202100
Minutony	500-196-30	CD-6°ASX 6inch Digital Caliper	2/16/2022	Triennial	2/16/2025	A20238413
Keysight Technologies	N6700B	DC Power Analyzer	5/5/2021	Triennial	5/5/2024	MYS3004059
Keysight Technologies	N9320A	MSX Signal Analyzer	4/14/2022	Annual	4/14/2023	MH40020333
NCL	BW-NGV5+	GB Attenuator	CBT	N/A	CBT	1139
Mini-Circuits	VLF-6000+	Low Pass Filter DC to 6000 MHz	7/6/2021	Annual	7/6/2022	31634
Mini-Circuits	VLF-6000+	Low Pass Filter DC to 6000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 38 GHz Precision Fixed Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1200 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	ZUC-DB-83-5e	Directional Coupler	CBT	N/A	CBT	2056
Mini-Circuits	ZUC-DB-83-5e	Directional Coupler	9/15/2021	Annual	9/15/2022	2113
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Senkoni	T5F-100	Torque Wrench	7/8/2021	Annual	7/8/2022	47639-29
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	4/18/2022	Annual	4/18/2023	12863
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	3/28/2022	Annual	3/28/2023	171075
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	4/8/2022	Annual	4/8/2023	162125
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	4/7/2022	Annual	4/7/2023	1617283
SPEAG	DAK-3.5	Portable Dielectric Assessment Kit	1/6/2022	Annual	1/6/2023	1079
SPEAG	DAK-3.5	Dielectric Assessment Kit	10/20/2021	Annual	10/20/2022	1091
SPEAG	DAK3-3.5	Portable Dielectric Assessment Kit	8/18/2021	Annual	8/18/2022	1041
SPEAG	DAK3-3.5	Portable Dielectric Assessment Kit	7/15/2021	Annual	7/15/2022	1039
SPEAG	MA13	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1079
SPEAG	CLA13	13 MHz SAR Dipole	9/16/2021	Annual	9/16/2022	1002
SPEAG	D750V3	750 MHz SAR Dipole	2/14/2022	Annual	2/14/2023	1046
SPEAG	D750V3	750 MHz SAR Dipole	3/14/2022	Annual	3/14/2023	1054
SPEAG	D750V3	750 MHz SAR Dipole	5/11/2021	Annual	5/11/2022	1030
SPEAG	D750V3	750 MHz SAR Dipole	10/19/2021	Annual	10/19/2022	1163
SPEAG	D835V2	835 MHz SAR Dipole	5/11/2021	Annual	5/11/2022	46180
SPEAG	D835V2	835 MHz SAR Dipole	4/14/2022	Annual	4/14/2023	46119
SPEAG	D835V2	835 MHz SAR Dipole	3/24/2022	Annual	3/24/2023	46061
SPEAG	D835V2	835 MHz SAR Dipole	10/19/2021	Annual	10/19/2022	46133
SPEAG	D1765V2	1750 MHz SAR Dipole	5/14/2021	Biennial	5/14/2023	1008
SPEAG	D1800V2	1800 MHz SAR Dipole	10/27/2021	Annual	10/27/2022	56980
SPEAG	D1800V2	1800 MHz SAR Dipole	9/21/2021	Annual	9/21/2022	56148
SPEAG	D1800V2	1800 MHz SAR Dipole	6/10/2021	Annual	6/10/2022	1073
SPEAG	D2300V2	2300 MHz SAR Dipole	8/18/2021	Annual	8/18/2022	1073
SPEAG	D2300V2	2300 MHz SAR Dipole	6/3/2021	Annual	6/3/2022	1116
SPEAG	D2450V2	2450 MHz SAR Dipole	8/18/2021	Annual	8/18/2022	719
SPEAG	D2450V2	2450 MHz SAR Dipole	9/20/2020	Biennial	9/20/2022	797
SPEAG	D2450V2	2450 MHz SAR Dipole	11/25/2021	Annual	11/25/2022	981
SPEAG	D2600V2	2600 MHz SAR Dipole	6/14/2021	Triennial	6/14/2022	1064
SPEAG	D2600V2	2600 MHz SAR Dipole	11/12/2020	Triennial	11/12/2022	1071
SPEAG	D2600V2	2600 MHz SAR Dipole	4/14/2021	Biennial	4/14/2022	1006
SPEAG	D3000V2	3000 MHz SAR Dipole	1/18/2021	Biennial	1/18/2023	1059
SPEAG	D3000V2	3000 MHz SAR Dipole	1/21/2020	Triennial	1/21/2023	1097
SPEAG	D3700V2	3700 MHz SAR Dipole	1/21/2020	Triennial	1/21/2023	1067
SPEAG	D3200V2	3200 MHz SAR Dipole	1/19/2021	Biennial	1/19/2023	1036
SPEAG	D3900V2	3900 MHz SAR Dipole	10/9/2020	Biennial	10/9/2022	1056
SPEAG	D3900V2	3900 MHz SAR Dipole	6/10/2021	Annual	6/10/2022	1073
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/10/2022	Annual	1/10/2023	1057
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/15/2021	Annual	9/15/2022	1191
SPEAG	DAE4	Day Data Acquisition Electronics	2/21/2022	Annual	2/21/2023	1645
SPEAG	DAE4	Day Data Acquisition Electronics	8/3/2021	Annual	8/3/2022	1681
SPEAG	DAE4	Day Data Acquisition Electronics	5/11/2021	Annual	5/11/2022	728
SPEAG	DAE4	Day Data Acquisition Electronics	3/16/2022	Annual	3/16/2023	1372
SPEAG	DAE4	Day Data Acquisition Electronics	7/13/2021	Annual	7/13/2022	1583
SPEAG	DAE4	Day Data Acquisition Electronics	1/14/2022	Annual	1/14/2023	1558
SPEAG	DAE4	Day Data Acquisition Electronics	11/1/2021	Annual	11/1/2022	1466
SPEAG	DAE4	Day Data Acquisition Electronics	8/16/2021	Annual	8/16/2022	1450
SPEAG	DAE4	Day Data Acquisition Electronics	5/10/2022	Annual	5/10/2023	1678
SPEAG	DAE4	Day Data Acquisition Electronics	12/8/2021	Annual	12/8/2022	859
SPEAG	DAE4	Day Data Acquisition Electronics	6/21/2021	Annual	6/21/2022	1676
SPEAG	DAE4	Day Data Acquisition Electronics	6/21/2021	Annual	6/21/2022	1344
SPEAG	DAE4	Day Data Acquisition Electronics	2/22/2022	Annual	2/22/2023	665
SPEAG	DAE4	Day Data Acquisition Electronics	8/4/2021	Annual	8/4/2022	1680
SPEAG	DAE4	Day Data Acquisition Electronics	11/10/2021	Annual	11/10/2022	1323
SPEAG	EX3DV4	SAR Probe	8/5/2021	Annual	8/5/2022	7676
SPEAG	EX3DV4	SAR Probe	5/18/2021	Annual	5/18/2022	3914
SPEAG	EX3DV4	SAR Probe	3/21/2022	Annual	3/21/2023	7527
SPEAG	EX3DV4	SAR Probe	7/20/2021	Annual	7/20/2022	7410
SPEAG	EX3DV4	SAR Probe	1/19/2022	Annual	1/19/2023	7570
SPEAG	EX3DV4	SAR Probe	11/15/2021	Annual	11/15/2022	7565
SPEAG	EX3DV4	SAR Probe	2/24/2022	Annual	2/24/2023	7640
SPEAG	EX3DV4	SAR Probe	6/28/2021	Annual	6/28/2022	7665
SPEAG	EX3DV4	SAR Probe	5/18/2022	Annual	5/18/2023	7660
SPEAG	EX3DV4	SAR Probe	1/10/2022	Annual	1/10/2023	7571
SPEAG	EX3DV4	SAR Probe	7/20/2021	Annual	7/20/2022	7406
SPEAG	EX3DV4	SAR Probe	6/21/2021	Annual	6/21/2022	7409
SPEAG	EX3DV4	SAR Probe	2/22/2022	Annual	2/22/2023	7417
SPEAG	EX3DV4	SAR Probe	9/20/2021	Annual	9/20/2022	7538
SPEAG	EX3DV4	SAR Probe	11/16/2021	Annual	11/16/2022	7538

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 11 of 12

5 MEASUREMENT UNCERTAINTIES

For SAR Measurements

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	7	N	1	1	1	7.0	7.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	E.2.3	2	R	1.732	1	1	1.2	1.2	∞
Linearity	E.2.4	0.3	N	1	1	1	0.3	0.3	∞
System Detection Limits	E.2.4	0.25	R	1.732	1	1	0.1	0.1	∞
Modulation Response	E.2.5	4.8	R	1.732	1	1	2.8	2.8	∞
Readout Electronics	E.2.6	0.3	N	1	1	1	0.3	0.3	∞
Response Time	E.2.7	0.8	R	1.732	1	1	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Conditions - Noise	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.8	R	1.732	1	1	0.5	0.5	∞
Probe Positioning w/ respect to Phantom	E.6.3	6.7	R	1.732	1	1	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	4	R	1.732	1	1	2.3	2.3	∞
Test Sample Related									
Test Sample Positioning	E.4.2	3.12	N	1	1	1	3.1	3.1	35
Device Holder Uncertainty	E.4.1	1.67	N	1	1	1	1.7	1.7	5
Output Power Variation - SAR drift measurement	E.2.9	5	R	1.732	1	1	2.9	2.9	∞
SAR Scaling	E.6.5	0	R	1.732	1	1	0.0	0.0	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	E.3.3	4.3	N	1	0.78	0.71	3.3	3.0	76
Liquid Permittivity - measurement uncertainty	E.3.3	4.2	N	1	0.23	0.26	1.0	1.1	75
Liquid Conductivity - Temperature Uncertainty	E.3.4	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	E.3.4	0.6	R	1.732	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS						12.2	12.0	191
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2						24.4	24.0	

The above measurement uncertainties are according to IEEE Std. 1528-2013

FCC ID: A3LSMF936U	PART 0 SAR CHAR REPORT	Approved by: Technical Manager
Document S/N: 1M2204010046-28.A3L (Rev1)	DUT Type: Portable Handset	Page 12 of 12