



FCC CFR47 PART 15 SUBPART C

ANT+

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS b/g/n and ANT+

MODEL NUMBER : SM-G1600

FCC ID: A3LSMG1600

REPORT NUMBER: 16K23557-E5V2

ISSUE DATE: JUN 28, 2016

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	06/20/16	Initial issue	Junwhan Lee
V2	06/28/16	Revised section 5.4	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	5
4.2. <i>SAMPLE CALCULATION</i>	5
4.3. <i>MEASUREMENT UNCERTAINTY</i>	5
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>MAXIMUM OUTPUT POWER</i>	6
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	6
5.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	6
5.5. <i>DESCRIPTION OF TEST SETUP</i>	7
6. TEST AND MEASUREMENT EQUIPMENT	9
7. LIMITS AND RESULTS	10
7.1. <i>99% BANDWIDTH</i>	10
7.2. <i>TRANSMITTER RADIATED EMISSIONS</i>	12
7.2.1. <i>DUTY CYCLE</i>	13
7.2.2. <i>FUNDAMENTAL FREQUENCY RADIATED EMISSION</i>	14
7.2.3. <i>TRANSMITTER RESTRICTED BAND EDGES</i>	15
7.2.4. <i>SPURIOUS BELOW 1 GHz</i>	20
8. AC POWER LINE CONDUCTED EMISSIONS	22
9. SETUP PHOTOS	27

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS b/g/n and ANT+
MODEL NUMBER: SM-G1600
SERIAL NUMBER: R38H50RX02E (RADIATED);
R38H50RX09F (CONDUCTED)
DATE TESTED: JUN 03, 2016 - JUN 17, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
<input checked="" type="checkbox"/> Chamber 1
<input type="checkbox"/> Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+. This test report addresses the ANT+ operational mode.

5.2. MAXIMUM OUTPUT POWER

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range [MHz]	Mode	Peak E-field Strength [dBuV/m]	Avg E-field Strength [dBuV/m]	Distance [m]
2402 - 2480	ANT+	91.65	90.83	3.00

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antennas, with a maximum gain of -3.61 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

Also, Test results of flip cover open configuration were more worst cases in comparison with test results of flip cover closed configuration. Therefore, all radiated and power line conducted tests were conducted in the condition of flip cover open configuration.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50KWK	DK1GB23VS/A-E	N/A
Data Cable	SAMSUNG	EP-DG920UWE	N/A	N/A
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is set to continuously transmit in ANT + test mode.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	11-17-16
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-16
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166255	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-18-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-19-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-19-16
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-18-16
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-19-16
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-19-16
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-19-16
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	08-18-16
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	015	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	016	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	015	08-18-16
LISN	R&S	ENV-216	101836	08-19-16
LISN	R&S	ENV-216	101837	08-19-16

7. LIMITS AND RESULTS

7.1. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS


Channel	Frequency [MHz]	20dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	606.0	826.42
Mid	2441	607.3	827.99
High	2480	579.6	813.83
Worst			827.99

99% BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



7.2. TRANSMITTER RADIATED EMISSIONS

TEST PROCEDURE

ANSI C63.10: 2009

LIMIT

FCC 15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.


Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit. Per FCC part 15.31(o), test results were not reported.

RESULTS

7.2.1. DUTY CYCLE



7.2.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION



FCC
UL SUWON LAB
Chamber 1


Project #: 16K23557
Report #: 16K23557
Date & Time: 2016-06-16
Test Engr: JH Park

Company: Samsung
EUT Description: GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS/bl/g/n/ and ANT+
Test Configuration: Z POSITION
Type of Test: FCC
Mode of Operation: Transmitting : ANT+ mode

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
2402.00	97.18	96.16	27.85	-38.39	0.00	86.64	85.62	114.00	94.00	-27.36	-8.38	3mV	0.00	1.00
2402.00	102.19	101.37	27.85	-38.39	0.00	91.65	90.83	114.00	94.00	-22.35	-3.17	3mH	0.00	2.00
Mid channel														
2441.00	98.41	97.68	27.85	-38.39	0.00	87.87	87.14	114.00	94.00	-26.13	-6.86	3mV	0.00	1.00
2441.00	101.11	100.35	27.85	-38.39	0.00	90.57	89.81	114.00	94.00	-23.43	-4.19	3mH	0.00	2.00
High channel														
2480.00	97.67	96.99	27.85	-38.39	0.00	87.13	86.45	114.00	94.00	-26.87	-7.55	3mV	0.00	1.00
2480.00	99.96	99.14	27.85	-38.39	0.00	89.42	88.60	114.00	94.00	-24.58	-5.40	3mH	0.00	2.00

7.2.3. TRANSMITTER RESTRICTED BAND EDGES

BANDEDGE (LOW CHANNEL, HORIZONTAL)



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	47	Pk	31.8	-29	49.8	-	-	74	-24.2	199	397	H
2	2.4	54.9	Pk	31.8	-29	57.7	-	-	74	-16.3	199	397	H
3	2.4	38.46	V1TV	31.8	-29	41.26	54	-12.74	-	-	199	397	H
4	* 2.33	39.15	V1TV	31.7	-29	41.85	54	-12.15	-	-	199	397	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

V1TV - $VB=1/Ton$, Linear Voltage Average where: Ton is packet duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	49.99	Pk		-29	52.79	-	-	74	-21.21	180	400	V
2	2.4	51.86	Pk		-29	54.66	-	-	74	-19.34	180	400	V
3	2.4	38.16	V1TV		-29	40.96	54	-13.04	-	-	180	400	V
4	* 2.389	39.29	V1TV		-29	42.09	54	-11.91	-	-	180	400	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

V1TV - VB=1/Ton, Linear Voltage Average where: Ton is packet duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	46.5	Pk	32	-28.9	49.6	-	-	74	-24.4	179	379	H
2	2.554	49.9	Pk	32	-28.8	53.1	-	-	74	-20.9	179	379	H
3	* 2.484	37.51	V1TV	32	-28.9	40.61	54	-13.39	-	-	179	379	H
4	* 2.486	39.23	V1TV	32	-28.9	42.33	54	-11.67	-	-	179	379	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

V1TV - VB=1/Ton, Linear Voltage Average where: Ton is packet duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	46.83	Pk	32	-28.9	49.93	-	-	74	-24.07	179	379	V
2	2.539	49.63	Pk	32	-28.8	52.83	-	-	74	-21.17	179	379	V
3	* 2.484	37.71	V1TV	32	-28.9	40.81	54	-13.19	-	-	179	379	V
4	2.524	39.78	V1TV	32	-28.9	42.88	54	-11.12	-	-	179	379	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

V1TV - VB=1/Ton, Linear Voltage Average where: Ton is packet duration

HARMONICS AND SPURIOUS EMISSIONS ABOVE 1GHz

HARMONICS



FCC
UL SUWON LAB
Chamber 1


Project #: 16K23557
Report #: 16K23557
Date & Time: 2016-06-16
Test Engr: JH Park

Company: Samsung
EUT Description: GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS/b/g/n/, NFC and ANT+
Test Configuration: Z POSITION
Type of Test: FCC
Mode of Operation: Transmitting : ANT+ mode


Freq (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Cross (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
4804.00	47.74	34.97	32.00	-33.07	0.00	46.67	33.90	74.00	54.00	-27.33	-20.10	3mV	0.00	1.00
4804.00	48.24	35.03	32.00	-33.07	0.00	47.17	33.96	74.00	54.00	-26.83	-20.04	3mH	0.00	2.00
Mid channel														
4882.00	47.60	34.36	32.00	-33.07	0.00	46.53	33.29	74.00	54.00	-27.47	-20.71	3mV	0.00	1.00
4882.00	47.14	34.65	32.00	-33.07	0.00	46.07	33.58	74.00	54.00	-27.93	-20.42	3mH	0.00	2.00
High channel														
4960.00	46.89	34.37	32.00	-33.07	0.00	45.82	33.30	74.00	54.00	-28.18	-20.70	3mV	0.00	1.00
4960.00	47.10	34.27	32.00	-33.07	0.00	46.03	33.20	74.00	54.00	-27.97	-20.80	3mH	0.00	2.00

7.2.4. SPURIOUS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	97.915	39.3	Pk	11.1	-29.3	21.1	43.52	-22.42	0-360	300	H
2	* 115.7225	38.31	Pk	10.3	-29.1	19.51	43.52	-24.01	0-360	300	H
3	35.27	41.01	Pk	10.6	-30.4	21.21	40	-18.79	0-360	100	V
4	72.5425	42.15	Pk	8.9	-29.7	21.35	40	-18.65	0-360	100	V
5	437.5	32.54	Pk	16.1	-26.6	22.04	46.02	-23.98	0-360	200	H
6	437.5	35.77	Pk	16.1	-26.6	25.27	46.02	-20.75	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

8. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10 2009.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers


Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.159	32.11	Pk	10	0	42.11	65.52	-23.41	-	-
2	.159	12.26	Av	10	0	22.26	-	-	55.52	-33.26
3	.456	28.45	Pk	10.2	0	38.65	56.77	-18.12	-	-
4	.456	14.7	Av	10.2	0	24.9	-	-	46.77	-21.87
5	.789	25.25	Pk	10	0	35.25	56	-20.75	-	-
6	.798	10.37	Av	10	0	20.37	-	-	46	-25.63
7	1.689	24.8	Pk	9.8	.1	34.7	56	-21.3	-	-
8	1.689	7.82	Av	9.8	.1	17.72	-	-	46	-28.28
9	4.299	25.79	Pk	9.8	.1	35.69	56	-20.31	-	-
10	4.308	10.93	Av	9.8	.1	20.83	-	-	46	-25.17
11	19.635	22.57	Pk	10.4	.2	33.17	60	-26.83	-	-
12	19.572	7.03	Av	10.4	.2	17.63	-	-	50	-32.37

Pk - Peak detector

Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.159	33.39	Pk	10	0	43.39	65.52	-22.13	-	-
14	.168	12.56	Av	10.2	0	22.76	-	-	55.06	-32.3
15	.474	26.54	Pk	10.1	0	36.64	56.44	-19.8	-	-
16	.465	15.84	Av	10.1	0	25.94	-	-	46.6	-20.66
17	.789	22.55	Pk	10	0	32.55	56	-23.45	-	-
18	.816	8.89	Av	10	0	18.89	-	-	46	-27.11
19	1.797	23.47	Pk	9.8	.1	33.37	56	-22.63	-	-
20	1.797	6.98	Av	9.8	.1	16.88	-	-	46	-29.12
21	4.011	22.8	Pk	9.8	.1	32.7	56	-23.3	-	-
22	4.11	9.36	Av	9.8	.1	19.26	-	-	46	-26.74
23	21.66	21.05	Pk	10.7	.2	31.95	60	-28.05	-	-
24	21.642	8.67	Av	10.7	.2	19.57	-	-	50	-30.43

Pk - Peak detector

Av - Average detection