



FCC CFR47 PART 15 SUBPART C

BLUETOOTH LOW ENERGY

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA Phone + Bluetooth & WLAN 2.4GHz b/g/n

**MODEL NUMBER: SM-G355H/DS, SM-G355H
FCC ID: A3LSMG355H**

**REPORT NUMBER: 14I17666-3 Revision A
ISSUE DATE: May 12, 2014**

**Prepared for
SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	4/29/14	Initial Issue	P. Zhang
A	5/12/14	Updated radiated portion	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
2. FACILITIES AND ACCREDITATION	5
3. CALIBRATION AND UNCERTAINTY	5
3.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	5
3.2. <i>SAMPLE CALCULATION</i>	5
3.3. <i>MEASUREMENT UNCERTAINTY</i>	5
4. EQUIPMENT UNDER TEST	6
4.1. <i>DESCRIPTION OF EUT</i>	6
4.2. <i>MAXIMUM OUTPUT POWER</i>	6
4.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	6
4.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
4.5. <i>DESCRIPTION OF TEST SETUP</i>	8
5. TEST AND MEASUREMENT EQUIPMENT	10
6. SUMMARY	11
7. ANTENNA PORT TEST RESULTS	11
7.1. <i>6 dB BANDWIDTH</i>	12
7.2. <i>99% BANDWIDTH</i>	15
7.3. <i>OUTPUT POWER</i>	18
7.4. <i>AVERAGE POWER</i>	21
7.5. <i>POWER SPECTRAL DENSITY</i>	22
7.6. <i>CONDUCTED SPURIOUS EMISSIONS</i>	25
8. RADIATED TEST RESULTS	29
8.1. <i>LIMITS AND PROCEDURE</i>	29
8.2. <i>TRANSMITTER ABOVE 1 GHz</i>	30
8.3. <i>WORST-CASE BELOW 1 GHz</i>	43
9. AC POWER LINE CONDUCTED EMISSIONS	46
10. SETUP PHOTOS	50

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

EUT DESCRIPTION: GSM/WCDMA Phone + Bluetooth & WLAN 2.4GHz b/g/n

MODEL: SM-G355H/DS, SM-G355H

SERIAL NUMBER: FL-164-C (Radiated), FL-164-D (Conducted)

DATE TESTED: April 25 – 29, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

STEVEN TRAN
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

2. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

3. CALIBRATION AND UNCERTAINTY

3.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

3.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

3.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

4. EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA Phone + Bluetooth & WLAN 2.4GHz b/g/n

4.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402-2480	BLE	9.27	8.45

4.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.4 dBi.

4.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

4.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	G355H	N/A	N/A
Earphone	Samsung	G355H	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests. EUT was set in the Hidden menu mode to enable BLE communications.

SETUP DIAGRAM FOR TESTS



5. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C00986	4/1/2015
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01179	2/26/2015
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	8/8/2014
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	5/8/2014
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	10/22/2014
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	N/A	3/6/2015
Antenna, Horn, 18 GHz	ETS	3117	C01022	2/21/2015
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00589	12/17/2014
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/2014
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/2014
LISN, 30 MHz	FCC	50/250-25-2	C00626	1/14/2015

6. SUMMARY

7.

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-210 A8.2(a)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	0.763MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-44.31dBm
15.247	RSS-210 A8.4	TX conducted output power	<30dBm		Pass	9.27dBm
15.247	RSS-210 A8.2	PSD	<8dBm		Pass	-10.407dBm
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	48.59dBuV
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	51.91dBuV/m

ANTENNA PORT TEST RESULTS

7.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.790	0.5
Middle	2440	0.763	0.5
High	2480	0.793	0.5

6 dB BANDWIDTH





7.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.



TEST PROCEDURE


Reference to KDB558074 D01 DTS Meas Guidance v03r01: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0494
Middle	2440	1.0494
High	2480	1.0491

99% BANDWIDTH





7.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

IC RSS-210 A8.4

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.



TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r01 April 9, 2013 under section 9.1.1 utilizing spectrum analyzer.

RESULTS

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	8.57	30	-21.430
Middle	2440	9.27	30	-20.730
High	2480	9.25	30	-20.750

OUTPUT POWER





7.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	7.5
Middle	2440	8.5
High	2480	8.3

7.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

IC RSS-210 A8.2 (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.



TEST PROCEDURE


Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r01, April 9, 2013

RESULTS

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-10.989	8	-18.99
Middle	2440	-10.622	8	-18.62
High	2480	-10.407	8	-18.41

POWER SPECTRAL DENSITY





7.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS



SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4 - 2009. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor = $10 \log(1/x)$. For this sample: $DCF = 10\log(1/0.618)=2.08\text{dB}$ (Spectrum Analyzer round it up to 2.1dB)


For spurious emission measurement refer to MAV1 - KDB558074 Option 1 Maximum RMS Average

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

8.2. TRANSMITTER ABOVE 1 GHz

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.38	PK	32.1	-22.9		48.58	-	-	74	-25.42	147	350	H
2	* 2.389	43.3	PK	32.1	-22.9		52.5	-	-	74	-21.5	147	350	H
3	* 2.39	30.28	RMS	32.1	-22.9	2.1	41.58	54	-12.42	-	-	147	350	H
4	* 2.389	32.52	RMS	32.1	-22.9	2.1	43.82	54	-10.18	-	-	147	350	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.79	PK	32.1	-22.9		48.99	-	-	74	-25.01	189	300	V
2	* 2.378	43.36	PK	32	-22.9		52.46	-	-	74	-21.54	189	300	V
3	* 2.39	30.52	RMS	32.1	-22.9	2.1	41.82	54	-12.18	-	-	189	300	V
4	* 2.389	32.45	RMS	32.1	-22.9	2.1	43.75	54	-10.25	-	-	189	300	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	43.5	PK	32.4	-22.6		53.3	-	-	74	-20.7	114	278	H
2	* 2.484	44.44	PK	32.4	-22.6		54.24	-	-	74	-19.76	114	278	H
3	* 2.484	35.9	RMS	32.4	-22.6	2.1	47.8	54	-6.2	-	-	114	278	H
4	* 2.484	36.04	RMS	32.4	-22.6	2.1	47.94	54	-6.06	-	-	114	278	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEGE (HIGH CHANNEL, VERTICAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	46	PK	32.4	-22.6		55.8	-	-	74	-18.2	172	351	V
2	* 2.484	46.07	PK	32.4	-22.6		55.87	-	-	74	-18.13	172	351	V
3	* 2.484	38.12	RMS	32.4	-22.6	2.1	50.02	54	-3.98	-	-	172	351	V
4	* 2.484	37.94	RMS	32.4	-22.6	2.1	49.84	54	-4.16	-	-	172	351	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection


HARMONICS AND SPURIOUS EMISSIONS

**LOW CHANNEL
HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 5.427	30.86	PK	34.5	-29.1	36.26	-	-	74	-37.74	0-360	99	H
5	* 4.773	30.64	PK	34.2	-29.3	35.54	-	-	74	-38.46	0-360	99	V
4	1.902	33.92	PK	31.1	-23.6	41.42	-	-	-	-	0-360	99	V
1	1.967	33.87	PK	31.3	-23.5	41.67	-	-	-	-	0-360	99	H
6	6.868	29.85	PK	35.6	-27.4	38.05	-	-	-	-	0-360	99	V
3	9.975	26.39	PK	37	-24	39.39	-	-	-	-	0-360	99	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 5.427	26.78	Avg	34.5	-29.1	2.1	34.28	54	-19.72	-	-	360	100	H
* 5.427	39.76	PK2	34.5	-29.1		45.16	-	-	74	-28.84	360	100	H
* 4.773	40.59	PK2	34.2	-29.3		45.49	-	-	74	-28.51	360	100	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.804	47.02	PK	34.2	-28.8	52.42	-	-	74	-21.58	0-360	99	H
5	* 4.804	44.66	PK	34.2	-28.8	50.06	-	-	74	-23.94	0-360	202	V
1	3.202	35.86	PK	32.8	-31.2	37.46	-	-	-	-	0-360	202	H
4	3.202	35.36	PK	32.8	-31.2	36.96	-	-	-	-	0-360	202	V
6	6.863	29.6	PK	35.6	-27.4	37.8	-	-	-	-	0-360	99	V
3	7.143	29.46	PK	35.6	-27.4	37.66	-	-	-	-	0-360	202	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.803	52.09	PK2	34.2	-28.8		57.49	-	-	74	-16.51	246	197	H
* 4.804	44.41	MAV1	34.2	-28.8	2.1	51.91	54	-2.09	-	-	246	197	H
* 4.804	50.51	PK2	34.2	-28.8		55.91	-	-	74	-18.09	231	223	V
* 4.804	42.28	MAV1	34.2	-28.8	2.1	49.78	54	-4.22	-	-	231	223	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.88	46.14	PK	34.2	-30.6	49.74	-	-	74	-24.26	0-360	201	H
5	* 4.88	45.47	PK	34.2	-30.6	49.07	-	-	74	-24.93	0-360	202	V
1	1.941	33.96	PK	31.2	-23.6	41.56	-	-	-	-	0-360	202	H
4	2.005	34.04	PK	31.3	-23.5	41.84	-	-	-	-	0-360	202	V
6	6.211	30.01	PK	35.4	-27.8	37.61	-	-	-	-	0-360	99	V
3	6.866	29.6	PK	35.6	-27.3	37.9	-	-	-	-	0-360	99	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	DC factor	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88	53.19	PK2	34.2	-30.6		56.79	-	-	74	-17.21	248	214	H
* 4.88	45.58	MAv1	34.2	-30.6	2.1	51.28	54	-2.72	-	-	248	214	H
* 4.88	53.02	PK2	34.2	-30.6		56.62	-	-	74	-17.38	228	239	V
* 4.88	45.46	MAv1	34.2	-30.6	2.1	51.16	54	-2.84	-	-	228	239	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

8.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)





Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* 109.135	40.28	PK	12.4	-28	24.68	43.52	-18.84	0-360	300	H
1	41.73	54.71	PK	12.7	-28.7	38.71	40	-1.29	0-360	101	V
2	70.1625	43.77	PK	8.1	-28.4	23.47	40	-16.53	0-360	200	H
3	95.875	44.64	PK	9.1	-28.1	25.64	43.52	-17.88	0-360	200	H
5	705	34.2	PK	20.2	-24.7	29.7	46.02	-16.32	0-360	300	V
6	748.8	31.5	PK	20.6	-24.2	27.9	46.02	-18.12	0-360	200	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE

ANSI C63.4 - 2009

RESULTS

6 WORST EMISSIONS

Line-L1 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.1725	46.7	PK	1.2	0	47.9	64.8	-16.9	-	-
2	.1725	26.04	Av	1.2	0	27.24	-	-	54.8	-27.56
3	.312	39.92	PK	.5	0	40.42	59.9	-19.48	-	-
4	.312	19.89	Av	.5	0	20.39	-	-	49.9	-29.51
5	.501	33.98	PK	.3	0	34.28	56	-21.72	-	-
6	.501	22.91	Av	.3	0	23.21	-	-	46	-22.79
7	.564	40	PK	.3	0	40.3	56	-15.7	-	-
8	.564	34.55	Av	.3	0	34.85	-	-	46	-11.15
9	1.194	29.85	PK	.2	.1	30.15	56	-25.85	-	-
10	1.194	23.27	Av	.2	.1	23.57	-	-	46	-22.43
11	5.514	26.73	PK	.2	.1	27.03	60	-32.97	-	-
12	5.514	10.55	Av	.2	.1	10.85	-	-	50	-39.15
13	8.8485	26.85	PK	.2	.1	27.15	60	-32.85	-	-
14	8.8485	9.96	Av	.2	.1	10.26	-	-	50	-39.74
15	17.9295	25.75	PK	.3	.2	26.25	60	-33.75	-	-
16	17.9295	21.3	Av	.3	.2	21.8	-	-	50	-28.2
17	29.958	28.37	PK	.3	.3	28.97	60	-31.03	-	-
18	29.958	14.25	Av	.3	.3	14.85	-	-	50	-35.15


Line-L2 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
19	.168	47.29	PK	1.3	0	48.59	65.1	-16.51	-	-
20	.168	21.59	Av	1.3	0	22.89	-	-	55.1	-32.21
21	.3165	41.68	PK	.6	0	42.28	59.8	-17.52	-	-
22	.3165	17.17	Av	.6	0	17.77	-	-	49.8	-32.03
23	.51	33.04	PK	.4	0	33.44	56	-22.56	-	-
24	.51	19.31	Av	.4	0	19.71	-	-	46	-26.29
25	.564	41.02	PK	.3	0	41.32	56	-14.68	-	-
26	.564	29.22	Av	.3	0	29.52	-	-	46	-16.48
27	1.068	22.55	PK	.3	.1	22.95	56	-33.05	-	-
28	1.068	9.95	Av	.3	.1	10.35	-	-	46	-35.65
29	5.5815	19.66	PK	.2	.1	19.96	60	-40.04	-	-
30	5.5815	4.13	Av	.2	.1	4.43	-	-	50	-45.57
31	8.8395	30	PK	.2	.1	30.3	60	-29.7	-	-
32	8.8395	10.83	Av	.2	.1	11.13	-	-	50	-38.87
33	17.9385	25.44	PK	.3	.2	25.94	60	-34.06	-	-
34	17.9385	18.29	Av	.3	.2	18.79	-	-	50	-31.21
35	29.913	28.01	PK	.3	.3	28.61	60	-31.39	-	-
36	29.913	15.64	Av	.3	.3	16.24	-	-	50	-33.76

PK - Peak detector
 Av - average detection

LINE 1 RESULTS



LINE 2 RESULTS

