



FCC CFR47 PART 15 SUBPART C

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC

MODEL NUMBER: SM-G3588V

FCC ID: A3LSMG3588V

REPORT NUMBER: 14I17331-4

ISSUE DATE: MARCH 21, 2014

Prepared for

SAMSUNG ELECTRONICS CO., LTD.

416, MAETAN 3-DONG, YEONGTONG-GU

SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

Prepared by

UL VERIFICATION SERVICES INC.

47173 BENICIA STREET

FREMONT, CA 94538, U.S.A.

TEL: (510) 771-1000

FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	3/21/14	Initial Issue	P. Kim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. WORST-CASE CONFIGURATION AND MODE	8
5.5. DESCRIPTION OF TEST SETUP	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. MEASUREMENT METHODS	12
8. SUMMARY TABLE	13
9. ANTENNA PORT TEST RESULTS	14
9.1. 6 dB BANDWIDTH	14
9.1.1. 802.11b MODE IN THE 2.4 GHz BAND	15
9.1.2. 802.11g MODE IN THE 2.4 GHz BAND	15
9.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	15
9.2. 99% BANDWIDTH	19
9.2.1. 802.11b MODE IN THE 2.4 GHz BAND	19
9.2.2. 802.11g MODE IN THE 2.4 GHz BAND	19
9.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	19
9.3. AVERAGE POWER	23
9.3.1. 802.11b MODE IN THE 2.4 GHz BAND	24
9.3.2. 802.11g MODE IN THE 2.4 GHz BAND	24
9.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	24
9.4. OUTPUT POWER	25
9.4.1. 802.11b MODE IN THE 2.4 GHz BAND	26
9.4.2. 802.11g MODE IN THE 2.4 GHz BAND	26
9.4.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	26
9.5. PSD	31
9.5.1. 802.11b MODE IN THE 2.4 GHz BAND	31
9.5.2. 802.11g MODE IN THE 2.4 GHz BAND	31
9.5.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	31

9.6.	<i>OUT-OF-BAND EMISSIONS</i>	35
9.6.1.	802.11b MODE IN THE 2.4 GHz BAND.....	36
9.6.2.	802.11g MODE IN THE 2.4 GHz BAND.....	42
9.6.3.	802.11n MODE IN THE 2.4 GHz BAND.....	48
10.	RADIATED TEST RESULTS	54
10.1.	<i>LIMITS AND PROCEDURE</i>	54
10.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	55
10.2.1.	TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND.....	55
10.2.2.	TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND.....	68
10.2.3.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	81
10.3.	<i>WORST-CASE BELOW 1 GHz</i>	94
11.	AC POWER LINE CONDUCTED EMISSIONS	97
12.	SETUP PHOTOS	101

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC
MODEL: SM-G3588V
SERIAL NUMBER: FL-102-D (Conducted); FL-102-A (Radiated)
DATE TESTED: MARCH 14 - 21, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released
For UL Verification Services Inc. By:

Tested By:



PHILIP KIM
CONSUMER TECHNOLOGY DIVISION
PROGRAM MANAGER
UL Verification Services Inc.

CHARLES VERGONIO
CONSUMER TECHNOLOGY DIVISION
LAB TECHNICIAN
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.4-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA Phone + Bluetooth, & DTS b/g/n.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	18.89	77.45
2412 - 2462	802.11g	22.48	177.01
2412 - 2462	802.11n HT20	23.08	203.24

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -3.04 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Based on the baseline scan, the worst-case data rates were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20mode: MCS0

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	ETA0U42CBC	N/A	N/A
Earphone	Samsung	N/A	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/14
Spectrum Analyzer, 9KHz-40GHz	HP	8564E	C00986	04/01/14
EMI Test Receiver, 9 kHz-7 GHz	R & S	ESCI 7	1000741	08/13/14
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	08/18/14
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/14
Antenna, Horn, 1-18 GHz	ETS	3117	C01022	02/21/15
Antenna, Horn, 18- 26 GHz	ARA	MWH-1826/B	C00946	11/12/14
Antenna, Horn, 26-40 GHz	ARA	MWH-2640	C00891	06/28/14
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	T243	03/06/15
RF Preamplifier, 100KHz -> 1300MHz	HP	TBD	C00825	06/01/14
RF Preamplifier, 1GHz - 18GHz	Miteq	NSP4000-SP2	924343	03/23/14
RF Preamplifier, 1GHz - 26.5GHz	HP	8449B	F00351	06/27/14
AC Power Supply, 2,500VA 45-500Hz	Elgar-Ametek	CW2501M	F00013	CNR
RF Preamplifier, 1GHz - 40GHz	Miteq	NSP4000-SP2	C00990	08/20/14
Attenuator / Switch driver	HP	11713A	F00204	CNR
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	F00219	05/23/14
High Pass Filter 5GHz	Micro-Tronics	HPS17542	F00222	05/22/14
High Pass Filter 6GHz	Micro-Tronics	HPM17543	F00224	05/22/14

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r01:Measurement Procedure PK2 is used for power and PKPSD is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.

8. SUMMARY TABLE

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-210 A8.2(a)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	8.08MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-25.83dBm
15.247	RSS-210 A8.4	TX conducted output power	<30dBm		Pass	23.08dBm
15.247	RSS-210 A8.2	PSD	<8dBm		Pass	-5.60dBm
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	52.21 dBuV
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	49.35dBuV/m

9. ANTENNA PORT TEST RESULTS

9.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to KDB 558074 D01 DTS Meas Guidance v03r01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

9.1.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	8.10	0.5
Mid	2437	8.10	0.5
High	2462	8.08	0.5
Worst		8.08	


9.1.2. 802.11g MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	16.46	0.5
Mid	2437	16.54	0.5
High	2462	16.54	0.5
Worst		16.46	


9.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	17.62	0.5
Mid	2437	17.75	0.5
High	2462	17.71	0.5
Worst		17.62	


802.11b 6 dB BANDWIDTH



802.11g 6 dB BANDWIDTH



802.11n 6 dB BANDWIDTH



9.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

9.2.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	12.59
Mid	2437	12.32
High	2462	12.21
Worst		12.59


9.2.2. 802.11g MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.46
Mid	2437	16.35
High	2462	16.34
Worst		16.46


9.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	17.44
Mid	2437	17.59
High	2462	17.50
Worst		17.59


802.11b 99% BANDWIDTH



802.11g 99% BANDWIDTH



802.11n 99% BANDWIDTH



9.3. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.2 dB (including 10 dB pad and 0.2 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.3.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	Avg Power (dBm)
Low	2412	15.80
Mid	2437	16.00
High	2462	16.30
Worst		16.300

9.3.2. 802.11g MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	Avg Power (dBm)
Low	2412	13.70
Mid	2437	14.00
High	2462	14.20
Worst		14.200

9.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency (MHz)	Avg Power (dBm)
Low	2412	13.30
Mid	2437	13.50
High	2462	12.90
Worst		13.500

9.4. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-210 A8.4

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS

9.4.1. 802.11b MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-3.04	30.00	30	36	30.00
Mid	2437	-3.04	30.00	30	36	30.00
High	2462	-3.04	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	18.29	18.29	30.00	-11.71
Mid	2437	18.71	18.71	30.00	-11.29
High	2462	18.89	18.89	30.00	-11.11
Worst			18.89		

9.4.2. 802.11g MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-3.04	30.00	30	36	30.00
Mid	2437	-3.04	30.00	30	36	30.00
High	2462	-3.04	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	21.91	21.91	30.00	-8.09
Mid	2437	22.43	22.43	30.00	-7.57
High	2462	22.48	22.48	30.00	-7.52
Worst			22.48		

9.4.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND


Limits

Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	-3.04	30.00	30	36	30.00
Mid	2437	-3.04	30.00	30	36	30.00
High	2462	-3.04	30.00	30	36	30.00


Results

Channel	Frequency (MHz)	Chain 0 Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	22.17	22.17	30.00	-7.83
Mid	2437	23.00	23.00	30.00	-7.00
High	2462	23.08	23.08	30.00	-6.92
Worst			23.08		


802.11b OUTPUT POWER, Chain 0



802.11g OUTPUT POWER, Chain 0



802.11n OUTPUT POWER, Chain 0



9.5. PSD

LIMITS

FCC §15.247

IC RSS-210 A8.2

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

9.5.1. 802.11b MODE IN THE 2.4 GHz BAND

PSD Results

Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-6.05	8.0	-14.1
Mid	2437	-5.60	8.0	-13.6
High	2462	-5.67	8.0	-13.7

9.5.2. 802.11g MODE IN THE 2.4 GHz BAND

PSD Results


Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-9.41	8.0	-17.4
Mid	2437	-9.43	8.0	-17.4
High	2462	-9.92	8.0	-17.9

9.5.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND


PSD Results

Channel	Frequency (MHz)	Chain 0 Meas (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-11.24	8.0	-19.2
Mid	2437	-11.19	8.0	-19.2
High	2462	-10.81	8.0	-18.8


802.11b PSD, Chain 0



802.11g PSD, Chain 0



802.11n PSD, Chain 0



9.6. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.


RESULTS

9.6.1. 802.11b MODE IN THE 2.4 GHz BAND


IN-BAND REFERENCE LEVEL




LOW CHANNEL BANDEDGE




HIGH CHANNEL BANDEDGE



OUT-OF-BAND EMISSIONS






OUT OF BAND HIGH CH

Agilent 08:04:50 Mar 14, 2014

R T



Freq/Channel
Center Freq 13.0150000 GHz
Start Freq 30.0000000 MHz
Stop Freq 26.0000000 GHz
CF Step 2.59700000 GHz Auto Man

Start 30 MHz Stop 26.00 GHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 2.482 s (601 pts)


Freq Offset 0.00000000 Hz
Signal Track On Off

Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Freq	2.45 GHz	8.99 dBm
1Δ	(1)	Freq	2.47 GHz	-60.71 dB
2	(1)	Freq	24.92 GHz	-49.14 dBm


Copyright 2000-2010 Agilent Technologies

9.6.2. 802.11g MODE IN THE 2.4 GHz BAND


IN-BAND REFERENCE LEVEL




LOW CHANNEL BANDEDGE





HIGH CHANNEL BANDEDGE



OUT-OF-BAND EMISSIONS









9.6.3. 802.11n MODE IN THE 2.4 GHz BAND


IN-BAND REFERENCE LEVEL




LOW CHANNEL BANDEDGE





HIGH CHANNEL BANDEDGE



OUT-OF-BAND EMISSIONS







10. RADIATED TEST RESULTS

10.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor= $10\log(1/x)$ For this sample B mode = 0dB (duty cycle >98%); G mode = 0.3dB; N mode = 0.32dB.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

10.2. TRANSMITTER ABOVE 1 GHz


10.2.1. TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND RESTRICTED BANDEDGE (LOW CHANNEL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38.14	PK	31.5	-20.6	0	49.04	-	-	74	-24.96	52	333	H
2	* 2.385	43.53	PK	31.5	-20.6	0	54.43	-	-	74	-19.57	52	333	H
3	* 2.39	28.19	RMS	31.5	-20.6	0	39.09	54	-14.91	-	-	52	333	H
4	* 2.389	28.89	RMS	31.5	-20.6	0	39.79	54	-14.21	-	-	52	333	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


LOW CHANNEL RESTRICTED, PEAK & AVERAGE, VERT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fitter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	37.03	PK	31.5	-20.6	0	47.93	-	-	74	-26.07	134	346	V
2	* 2.362	40.22	PK	31.3	-20.8	0	50.72	-	-	74	-23.28	134	346	V
3	* 2.39	28.41	RMS	31.5	-20.6	0	39.31	54	-14.69	-	-	134	346	V
4	* 2.371	29.07	RMS	31.4	-20.7	0	39.77	54	-14.23	-	-	134	346	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


AUTHORIZED BANDEDGE (HIGH CHANNEL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	36.39	PK	32.1	-20.6	0	47.89	-	-	74	-26.11	70	324	H
3	* 2.484	27.58	RMS	32.1	-20.6	0	39.08	54	-14.92	-	-	70	324	H
2	2.552	39.95	PK	32.1	-20.2	0	51.85	-	-	74	-22.15	70	324	H
4	2.552	28.96	RMS	32.1	-20.2	0	40.86	54	-13.14	-	-	70	324	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


HIGH CHANNEL BANDEDGE, PEAK & AVERAGE, VERT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.84	PK	32.1	-20.6	0	50.34	-	-	74	-23.66	111	324	V
3	* 2.484	28.37	RMS	32.1	-20.6	0	39.87	54	-14.13	-	-	111	324	V
2	2.525	40.69	PK	32.1	-20.5	0	52.29	-	-	74	-21.71	111	324	V
4	2.557	29.07	RMS	32	-20.4	0	40.67	54	-13.33	-	-	111	324	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.823	40.48	PK	34.2	-29.3	45.38	54	-8.62	74	-28.62	0-360	202	H
4	* 7.419	37.64	PK	35.6	-26.8	46.44	54	-7.56	74	-27.56	0-360	99	V
5	* 4.824	35.16	PK	34.2	-29.3	40.06	54	-13.94	74	-33.94	0-360	99	H
6	* 4.823	33.13	PK	34.2	-29.3	38.03	54	-15.97	74	-35.97	0-360	202	V
3	6.223	37.72	PK	35.4	-27.8	45.32	54	-8.68	74	-28.68	0-360	99	V
2	6.927	39	PK	35.6	-27.8	46.8	54	-7.2	74	-27.2	0-360	202	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

MID CHANNEL
 HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.559	40.44	PK	33	-31.2	42.24	54	-11.76	74	-31.76	0-360	202	H
4	* 3.8	40.42	PK	33.6	-30.8	43.22	54	-10.78	74	-30.78	0-360	202	V
2	6.137	39.64	PK	35.4	-29.1	45.94	54	-8.06	74	-28.06	0-360	99	H
5	6.298	38.01	PK	35.5	-28.1	45.41	54	-8.59	74	-28.59	0-360	202	V
3	6.553	38.27	PK	35.7	-27.3	46.67	54	-7.33	74	-27.33	0-360	99	H
6	7.753	37.01	PK	35.7	-26	46.71	54	-7.29	74	-27.29	0-360	99	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

**HIGH CHANNEL
 HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**HIGH CHANNEL
 VERTICAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


HIGH CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 5.032	38.58	PK	34.2	-28.8	43.98	54	-10.02	74	-30.02	0-360	99	H
4	* 3.981	40.24	PK	33.6	-30.9	42.94	54	-11.06	74	-31.06	0-360	202	V
5	* 4.8	38.9	PK	34.2	-28.8	44.3	54	-9.7	74	-29.7	0-360	202	V
6	* 8.367	35.78	PK	35.7	-25.5	45.98	54	-8.02	74	-28.02	0-360	99	V
1	4.482	38.97	PK	34	-29.2	43.77	54	-10.23	74	-30.23	0-360	99	H
3	6.892	38.15	PK	35.6	-27.5	46.25	54	-7.75	74	-27.75	0-360	201	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

**10.2.2. TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND
 RESTRICTED BANDEDGE (LOW CHANNEL)**




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	49.5	PK	31.5	-20.6	0	60.4	-	-	74	-13.6	69	219	H
2	* 2.39	51.2	PK	31.5	-20.6	0	62.1	-	-	74	-11.9	69	219	H
3	* 2.39	33.17	RMS	31.5	-20.6	.3	44.37	54	-9.63	-	-	69	219	H
4	* 2.39	33.92	RMS	31.5	-20.6	.3	45.12	54	-8.88	-	-	69	219	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

LOW CHANNEL RESTRICTED, PEAK & AVERAGE, VERT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	49.76	PK	31.5	-20.6	0	60.66	-	-	74	-13.34	109	330	V
2	* 2.39	50.11	PK	31.5	-20.6	0	61.01	-	-	74	-12.99	109	330	V
3	* 2.39	33.34	RMS	31.5	-20.6	.3	44.54	54	-9.46	-	-	109	330	V
4	* 2.39	34.99	RMS	31.5	-20.6	.3	46.19	54	-7.81	-	-	109	330	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	53.33	PK	32.1	-20.6	0	64.83	-	-	74	-9.17	223	265	H
2	* 2.485	54.99	PK	32.1	-20.6	0	66.49	-	-	74	-7.51	223	265	H
3	* 2.484	36.34	RMS	32.1	-20.6	.3	48.14	54	-5.86	-	-	223	265	H
4	* 2.484	37.55	RMS	32.1	-20.6	.3	49.35	54	-4.65	-	-	223	265	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

HIGH CHANNEL BANDEDGE, PEAK & AVERAGE, VERT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	50.06	PK	32.1	-20.6	0	61.56	-	-	74	-12.44	145	269	V
2	* 2.484	53.89	PK	32.1	-20.6	0	65.39	-	-	74	-8.61	145	269	V
3	* 2.484	35.11	RMS	32.1	-20.6	.3	46.91	54	-7.09	-	-	145	269	V
4	* 2.484	35.16	RMS	32.1	-20.6	.3	46.96	54	-7.04	-	-	145	269	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.98	39.19	PK	34.2	-29.8	43.59	54	-10.41	74	-30.41	0-360	99	H
4	* 4.275	40.97	PK	33.7	-31	43.67	54	-10.33	74	-30.33	0-360	99	V
1	3.468	41.67	PK	32.8	-31.2	43.27	54	-10.73	74	-30.73	0-360	99	H
5	6.223	37.45	PK	35.4	-27.8	45.05	54	-8.95	74	-28.95	0-360	99	V
3	6.937	38.74	PK	35.6	-28	46.34	54	-7.66	74	-27.66	0-360	99	H
6	8.741	35.32	PK	35.9	-25.1	46.12	54	-7.88	74	-27.88	0-360	202	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

MID CHANNEL
 HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.843	39.86	PK	33.7	-30.2	43.36	54	-10.64	74	-30.64	0-360	202	H
4	* 4.384	41.06	PK	33.8	-30.4	44.46	54	-9.54	74	-29.54	0-360	202	V
2	* 4.551	40.21	PK	34.1	-30.5	43.81	54	-10.19	74	-30.19	0-360	202	H
5	6.152	38.9	PK	35.4	-28.9	45.4	54	-8.6	74	-28.6	0-360	202	V
3	7.771	37.01	PK	35.7	-26	46.71	54	-7.29	74	-27.29	0-360	99	H
6	9.663	35.11	PK	36.8	-24	47.91	54	-6.09	74	-26.09	0-360	99	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

**HIGH CHANNEL
 HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**HIGH CHANNEL
 VERTICAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


HIGH CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.984	39.86	PK	33.6	-31	42.46	54	-11.54	74	-31.54	0-360	201	H
6	* 4.334	36.07	PK	33.7	-31	38.77	54	-15.23	74	-35.23	0-360	202	H
5	* 8.078	36.09	PK	35.7	-25.9	45.89	54	-8.11	74	-28.11	0-360	99	V
3	* 9.004	35.62	PK	36.2	-24.9	46.92	54	-7.08	74	-27.08	0-360	201	H
4	5.56	39.43	PK	34.5	-29.5	44.43	54	-9.57	74	-29.57	0-360	202	V
2	6.883	37.95	PK	35.6	-27.5	46.05	54	-7.95	74	-27.95	0-360	201	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

**10.2.3. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND
 RESTRICTED BANDEDGE (LOW CHANNEL)**




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fitter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	58.26	PK	32.1	-22.9	0	67.46	-	-	74	-6.54	238	101	H
2	* 2.39	58.26	PK	32.1	-22.9	0	67.46	-	-	74	-6.54	238	101	H
3	* 2.39	41.4	RMS	32.1	-22.9	.3	50.9	54	-3.1	-	-	238	101	H
4	* 2.39	41.54	RMS	32.1	-22.9	.3	51.04	54	-2.96	-	-	238	101	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

LOW CHANNEL RESTRICTED, PEAK & AVERAGE, VERT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	52.29	PK	32.1	-22.9	0	61.49	-	-	74	-12.51	39	324	V
2	* 2.39	54.7	PK	32.1	-22.9	0	63.9	-	-	74	-10.1	39	324	V
3	* 2.39	38.59	RMS	32.1	-22.9	.3	48.09	54	-5.91	-	-	39	324	V
4	* 2.39	38.59	RMS	32.1	-22.9	.3	48.09	54	-5.91	-	-	39	324	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	53.72	PK	32.4	-22.6	0	63.52	-	-	74	-10.48	276	104	H
3	* 2.484	40.53	RMS	32.4	-22.6	.3	50.63	54	-3.37	-	-	276	104	H
4	* 2.485	41.8	RMS	32.4	-22.6	.3	51.9	54	-2.1	-	-	276	104	H
2	* 2.486	58.95	PK	32.4	-22.6	0	68.75	-	-	74	-5.25	276	104	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

HIGH CHANNEL BANDEDGE, PEAK & AVERAGE, VERT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT345 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	51.29	PK	32.4	-22.6	0	61.09	-	-	74	-12.91	160	340	V
3	* 2.484	39.3	RMS	32.4	-22.6	.3	49.4	54	-4.6	-	-	160	340	V
4	* 2.484	39.3	RMS	32.4	-22.6	.3	49.4	54	-4.6	-	-	160	340	V
2	* 2.485	56.72	PK	32.4	-22.6	0	66.52	-	-	74	-7.48	160	340	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 7.48	36.12	PK	35.2	-25	46.32	54	-7.68	74	-27.68	0-360	201	H
3	* 3.622	38.71	PK	32.5	-28.3	42.91	54	-11.09	74	-31.09	0-360	100	V
4	* 4.777	39.12	PK	33.5	-27.6	45.02	54	-8.98	74	-28.98	0-360	201	V
5	* 4.334	33.1	PK	33.1	-27.6	38.6	54	-15.4	74	-35.4	0-360	100	V
6	* 4.9	33.03	PK	33.5	-27.4	39.13	54	-14.87	74	-34.87	0-360	201	V
1	5.292	38.02	PK	33.8	-27.6	44.22	54	-9.78	74	-29.78	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

MID CHANNEL
 HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL
 VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.99	39.92	PK	32.9	-28.3	44.52	54	-9.48	74	-29.48	0-360	100	V
2	* 4.79	39.25	PK	33.5	-27.3	45.45	54	-8.55	74	-28.55	0-360	201	V
3	* 7.431	35.73	PK	35.2	-24.9	46.03	54	-7.97	74	-27.97	0-360	201	V
4	4.486	33.26	PK	33.5	-28.2	38.56	54	-15.44	74	-35.44	0-360	201	H
5	6.91	31.43	PK	35.1	-25.8	40.73	54	-13.27	74	-33.27	0-360	100	H
6	9.576	29.86	PK	36.3	-22.1	44.06	54	-9.94	74	-29.94	0-360	201	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

**HIGH CHANNEL
 HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**HIGH CHANNEL
 VERTICAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T712 (dB/m)	Amp/Cbi/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 4.544	38.28	PK	33.5	-26.5	0	45.28	54	-8.72	74	-28.72	0-360	201	V
3	* 5.088	37.09	PK	33.6	-26	0	44.69	54	-9.31	74	-29.31	0-360	100	V
5	* 9.171	29.1	PK	35.9	-21.3	0	43.7	54	-10.3	74	-30.3	0-360	201	V
1	1.909	38.28	PK	30.2	-21.2	0	47.28	54	-6.72	74	-26.72	0-360	201	V
4	7.225	35.34	PK	35.1	-24.9	0	45.54	54	-8.46	74	-28.46	0-360	100	V
6	10.005	28.68	PK	36.8	-21	0	44.48	54	-9.52	74	-29.52	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK - Peak detector

10.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Below 1G Data

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AFT185 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	* 136.08	39.15	PK	13.4	-31.2	21.35	43.52	-22.17	0-360	100	H
6	* 169.6125	42.13	PK	11.4	-31	22.53	43.52	-20.99	0-360	100	H
1	45.0025	49.32	PK	10.1	-31.9	27.52	40	-12.48	0-360	100	V
2	50.0175	47.33	PK	7.7	-31.3	23.73	40	-16.27	0-360	100	V
3	305.2	32.91	PK	13.5	-30.3	16.11	46.02	-29.91	0-360	300	V
7	379.2	39.61	PK	15	-30.2	24.41	46.02	-21.61	0-360	100	H
4	710.4	32.74	PK	20.4	-29.3	23.84	46.02	-22.18	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4 2009.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS


6 WORST EMISSIONS

Line-L1 .15 - 30MHz										
Trace Markers										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin to Limit (dB)	CISPR 11/22 Class B Average	Margin to Limit (dB)
1	.393	51.81	PK	.4	0	52.21	58	-5.79	-	-
2	.393	42.65	Av	.4	0	43.05	-	-	48	-4.95
3	.8565	45.01	PK	.3	0	45.31	56	-10.69	-	-
4	.8565	32.87	Av	.3	0	33.17	-	-	46	-12.83
5	2.0445	48.23	PK	.2	.1	48.53	56	-7.47	-	-
6	2.0445	33.62	Av	.2	.1	33.92	-	-	46	-12.08
7	3.003	47.67	PK	.2	.1	47.97	56	-8.03	-	-
8	3.003	32.58	Av	.2	.1	32.88	-	-	46	-13.12
9	10.3155	35.24	PK	.2	.2	35.64	60	-24.36	-	-
10	10.3155	17.99	Av	.2	.2	18.39	-	-	50	-31.61
11	11.04	33.61	PK	.2	.2	34.01	60	-25.99	-	-
12	11.04	16.73	Av	.2	.2	17.13	-	-	50	-32.87

Line-L2 .15 - 30MHz										
Trace Markers										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin to Limit (dB)	CISPR 11/22 Class B Average	Margin to Limit (dB)
13	.3165	39.35	PK	.6	0	39.95	59.8	-19.85	-	-
14	.3165	25.25	Av	.6	0	25.85	-	-	49.8	-23.95
15	.3885	48.23	PK	.5	0	48.73	58.1	-9.37	-	-
16	.3885	38.61	Av	.5	0	39.11	-	-	48.1	-8.99
17	1.7025	44.79	PK	.2	.1	45.09	56	-10.91	-	-
18	1.7025	27.78	Av	.2	.1	28.08	-	-	46	-17.92
19	2.5935	45.02	PK	.2	.1	45.32	56	-10.68	-	-
20	2.5935	30	Av	.2	.1	30.3	-	-	46	-15.7
21	3.291	46.42	PK	.2	.1	46.72	56	-9.28	-	-
22	3.291	27.48	Av	.2	.1	27.78	-	-	46	-18.22
23	5.4285	37.85	PK	.2	.1	38.15	60	-21.85	-	-
24	5.4285	17.23	Av	.2	.1	17.53	-	-	50	-32.47
25	7.3185	36.96	PK	.2	.1	37.26	60	-22.74	-	-
26	7.3185	18.44	Av	.2	.1	18.74	-	-	50	-31.26
27	14.64	32.03	PK	.3	.2	32.53	60	-27.47	-	-
28	14.64	12.55	Av	.3	.2	13.05	-	-	50	-36.95
29	15.5985	29.33	PK	.3	.2	29.83	60	-30.17	-	-
30	15.5985	10.27	Av	.3	.2	10.77	-	-	50	-39.23

PK - Peak detector
 Av - average detection

LINE 1 RESULTS



LINE 2 RESULTS

