



SAR EVALUATION REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

For

GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHZ b/g/n & NFC

**Model: SM-G530FZ, SM-G530FZ/DS
FCC ID: A3LSMG530FZ**

**Report Number: 14U19433-S1A
Issue Date: 12/19/2014**

Prepared for

**SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, South Korea**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
--	12/17/2014	Initial Issue	--
A	12/19/2014	Section 6.1: Updated battery and battery cover information	Vinky Ip

Table of Contents

1. Attestation of Test Results 5

2. Test Specification, Methods and Procedures..... 6

3. Facilities and Accreditation 6

4. SAR Measurement System & Test Equipment 7

 4.1. SAR Measurement System 7

 4.2. SAR Scan Procedure 8

 4.3. Test Equipment..... 10

5. Measurement Uncertainty..... 10

6. Device Under Test (DUT) Information 11

 6.1. DUT Description..... 11

 6.2. Wireless Technologies 11

 6.3. Nominal and Maximum Output Power..... 12

 6.4. Simultaneous Transmission Condition 13

 6.5. General LTE SAR Test and Reporting Considerations..... 13

 6.6. RF Exposure Conditions (Test Configurations) 14

7. Conducted Output Power Measurements..... 15

 7.1. GSM850 and GSM1900..... 15

 7.2. WCDMA Band V and II 17

 7.3. LTE Band 5..... 24

 7.4. Wi-Fi (2.4 GHz Band)..... 26

 7.5. Bluetooth..... 26

8. Dielectric Property Measurements 27

 8.1. Tissue Dielectric Parameters 27

 8.2. Dielectric Property Measurements Results..... 28

9. System Check..... 30

 9.1. System Performance Check Measurement Conditions 30

 9.2. Reference Target SAR Values 30

 9.3. System Check Results 31

10. Measured and Reported (Scaled) SAR Results..... 32

 10.1. GSM850..... 33

 10.2. GSM1900..... 33

 10.3. WCDMA Band V 33

10.4. WCDMA Band II..... 34

10.5. LTE Band 5 (10MHz Bandwidth)..... 34

10.6. Wi-Fi (DTS Band)..... 34

10.7. Bluetooth..... 35

 10.7.1. Standalone SAR Test Exclusion Considerations 35

 10.7.2. Estimated SAR..... 35

11. SAR Measurement Variability..... 36

12. Simultaneous Transmission SAR Analysis..... 37

 12.1. Sum of the SAR for GSM850 & Wi-Fi & BT..... 37

 12.2. Sum of the SAR for GSM1900 & Wi-Fi & BT..... 37

 12.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT..... 37

 12.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT..... 38

 12.5. Sum of the SAR for LTE Band 5 & Wi-Fi & BT..... 38

13. Appendixes..... 39

 A. Photos and Antenna Locations 39

 B. System Performance Check Plots..... 39

 C. Highest SAR Test Plots..... 39

 D. Tissue Material Ingredients 39

 E. Calibration Certificates for E-Field Probes..... 39

 F. Calibration Certificates for Dipoles 39

1. Attestation of Test Results



Applicant Name	SAMSUNG ELECTRONICS CO., LTD.
FCC ID	A3LSMG530FZ
DUT Description	GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHZ b/g/n & NFC
Exposure Category	General Population/Uncontrolled Exposure
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013
Date tested	11/17/2014 – 11/25/2014

The Highest Reported SAR (W/kg)

RF Exposure Conditions	Equipment Class			
	Licensed	DTS	U-NII	DSS
Head	0.379	0.348	N/A	N/A
Body-worn or Body	0.540	0.343		
Hotspot				
Simultaneous Tx	Head: 0.727 Body: 0.811			

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.

Approved & Released By: 	Prepared By: 
Devin Chang Senior Engineer UL Verification Services Inc.	Vinky Ip Laboratory Technician UL Verification Services Inc.

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures, and TCB workshop updates:

- 447498 D01 General RF Exposure Guidance v05r02
- 648474 D04 Handset SAR v01r02
- 941225 D01 3G SAR Procedures v03
- 941225 D05 SAR for LTE Devices v02r03
- 941225 D06 Hotspot Mode SAR v01r01
- 248227 D01 SAR Meas for 802 11abg v01r02
- 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- 865664 D02 SAR Reporting v01r01
- 690783 D01 SAR Listings on Grants v01r03

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at


47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	SAR Lab 5
SAR Lab F	
SAR Lab G	
SAR Lab H	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

4.2. SAR Scan Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

		≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the area scan based <i>1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	Agilent	E753ES	MY40000980	4/7/2015
Dielectronic Probe kit	SPEAG	DAK-3.5	1082	9/16/2015
Dielectronic Probe kit	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	Control Company	4242	122529163	10/8/2015
Thermometer	EXTECH	445703	CCS-200	3/24/2015

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
HP Signal Generator	HP	8665B	3546A00784	6/23/2015
Power Meter	Agilent	N1911A	MY53060016	8/7/2015
Power Sensor	Agilent	E9323A	MY53070003	5/1/2015
Power Meter	HP	437B	3125U09516	10/6/2015
Power Sensor	HP	8481A	3318A95392	10/6/2015
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1622052	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2711	N/A
DC Power Supply	Sorensen Ametek	XT20-3	1318A00530	N/A
Synthesized Signal Generator	Agilent	8665B	3438A00633	8/29/2015
Power Meter	HP	437B	3125U11347	8/27/2015
Power Sensor	HP	8481A	1926A16917	10/10/2015
Power Meter	HP	437B	3125U16345	6/16/2015
Power Sensor	HP	8481A	2702A60780	6/16/2015
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1808938	N/A
Bi-directional coupler	Werlatone, Inc.	C8060-102	2710	N/A
DC Power Supply	HP	6296A	2841A-05955	N/A
E-Field Probe (SAR 1)	SPEAG	EX3DV4	3902	5/19/2015
E-Field Probe (SAR 3)	SPEAG	EX3DV4	3773	4/22/2015
E-Field Probe (SAR 4)	SPEAG	EX3DV4	3929	5/9/2015
Data Acquisition Electronics (SAR 1)	SPEAG	DAE3	427	1/21/2015
Data Acquisition Electronics (SAR 3)	SPEAG	DAE4	1380	7/23/2015
Data Acquisition Electronics (SAR 4)	SPEAG	DAE4	1377	8/27/2015
System Validation Dipole	SPEAG	D835V2	4d142	9/9/2015
System Validation Dipole	SPEAG	D1900V2	5d163	9/11/2015
System Validation Dipole	SPEAG	D2450V2	706	5/20/2015
Thermometer (SAR Lab 1)	EXTECH	445703	CCS-205	3/24/2015
Thermometer (SAR Lab 3)	EXTECH	445703	CCS-237	6/3/2015
Thermometer (SAR Lab 4)	EXTECH	445703	CCS-238	6/3/2015

Others

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Base Station Simulator	R & S	CMW500	135393	7/3/2015
Power Meter	Agilent	N1912A	MY53040015	7/10/2015
Power Sensor	Agilent	N1921A	MY52020011	5/6/2015

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

6. Device Under Test (DUT) Information

6.1. DUT Description

Model: SM-G530FZ, SM-G530FZ/DS	
Device Dimension	Overall (Length x Width): 144 mm x 72 mm Overall Diagonal: 155 mm Display Diagonal: 128 mm
Battery Back Cover	<input type="checkbox"/> Normal Battery Cover <input checked="" type="checkbox"/> Normal Battery Cover with NFC <input type="checkbox"/> Wireless Charger Battery Cover <input type="checkbox"/> Wireless Charger Battery Cover with NFC
Battery Options	<input checked="" type="checkbox"/> NFC – Lithium-ion battery, Rating 3.8Vdc, 9.88Wh <input type="checkbox"/> Extended (large capacity)
Accessory	Headset
Wireless Router (Hotspot)	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi-enabled devices. <input checked="" type="checkbox"/> Mobile Hotspot (Wi-Fi 2.4 GHz) <input type="checkbox"/> Mobile Hotspot (Wi-Fi 5 GHz)
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other <input checked="" type="checkbox"/> Wi-Fi Direct (Wi-Fi 2.4 GHz) <input type="checkbox"/> Wi-Fi Direct (Wi-Fi 5 GHz)

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode	Duty Cycle used for SAR testing
GSM	850, 1900	Voice (GMSK) GPRS (GMSK) EGPRS (8PSK)	GSM Voice: 12.5%; GPRS/EGPRS: 1 Slot: 12.5%; 2 Slots: 25%, 3 Slots: 37.5%, 4 Slots: 50%,
	GPRS Multi-Slot Class: <input type="checkbox"/> Class 8 - One Up <input type="checkbox"/> Class 10 - Two Up <input type="checkbox"/> Class 12 - Four Up <input checked="" type="checkbox"/> Class 33 - Four Up DTM (Dual Transfer Mode): Not supported		
WCDMA (UMTS)	Band V and II	UMTS Rel. 99 (Voice & Data) HSDPA HSUPA	100%
LTE (FDD)	Band 5	QPSK, 16QAM	100%
	Does this device SV-LTE (1xRTT-LTE)? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20)	100%
Bluetooth	2.4 GHz	Version 4.0 LE	32.25% (DH1), 66.68% (DH3), 77.52% (DH5)

6.3. Nominal and Maximum Output Power

RF Air interface	Mode	Target	Max. tune-up tolerance limit
GSM850	Voice	33.0	33.5
	GPRS 1 slot	33.0	33.5
	GPRS 2 slots	30.0	30.5
	GPRS 3 slots	28.0	28.5
	GPRS 4 slots	26.0	26.5
	EGPRS 1 slot	27.5	28.0
	EGPRS 2 slots	26.0	26.5
	EGPRS 3 slots	23.5	24.0
	EGPRS 4 slots	22.0	22.5
GSM1900	Voice	30.5	31.0
	GPRS 1 slot	30.5	31.0
	GPRS 2 slots	28.0	28.5
	GPRS 3 slots	25.5	26.0
	GPRS 4 slots	24.5	25.0
	EGPRS 1 slot	27.5	28.0
	EGPRS 2 slots	25.5	26.0
	EGPRS 3 slots	22.5	23.0
	EGPRS 4 slots	22.5	23.0
WCDMA Band V	R99	22.5	23.0
	HSDPA	22.5	23.0
	HSUPA	22.0	22.5
	DC-HSDPA	22.0	22.5
WCDMA Band II	R99	22.5	23.0
	HSDPA	22.5	23.0
	HSUPA	22.0	22.5
	DC-HSDPA	22.5	23.0
LTE Band 5	QPSK	22.0	22.5

Upper limit (dB): 0.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
WiFi 2.4 GHz	802.11b	17.0	17.5
	802.11g	13.0	13.5
	802.11n HT20	11.0	11.5
Bluetooth		10.0	10.5
Bluetooth LE		1.0	1.5

6.4. Simultaneous Transmission Condition

RF Exposure Condition	Capable Transmit Configurations
Head	1. GSM 850/1900 Voice + Wi-Fi 2.4GHz 2. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 3. WCDMA Band 2/5 + Wi-Fi 2.4GHz 4. LTE B5 + Wi-Fi 2.4GHz
Body-worn Accessory	1. GSM 850/1900 Voice + Wi-Fi 2.4GHz 2. GSM 850/1900 Voice + BT 3. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 4. GSM 850/1900 (GPRS/EDGE) + BT 5. WCDMA Band 2/5 + Wi-Fi 2.4GHz 6. WCDMA Band 2/5 + BT 7. LTE B5+ Wi-Fi 2.4GHz 8. LTE B5+ BT
Wireless Router (Hotspot)	1. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4GHz 2. WCDMA Band 2/5 + Wi-Fi 2.4GHz 3. LTE B5+ Wi-Fi 2.4GHz
Notes: 1. Wi-Fi 2.4GHz supports Hotspot. 2. GPRS/EDGE, WCDMA and LTE support Hotspot. 3. VoIP is supported in LTE, WCDMA and GPRS. 4. Wi-Fi 2.4 GHz Radio cannot transmit simultaneously with Bluetooth Radio.	

6.5. General LTE SAR Test and Reporting Considerations

Item	Description																																						
Frequency range, Channel Bandwidth, Numbers and Frequencies	Band 5 Frequency range: 824 - 849 MHz Channel Bandwidth 20 MHz 15 MHz 10 MHz 5 MHz 3 MHz 1.4 MHz																																						
	Low 20450/829 20425/826.5 20415/825.5 20407/824.7																																						
	Mid 20525/836.5 20525/836.5 20525/836.5 20525/836.5																																						
	High 20600/844 20625/846.5 20635/847.5 20643/848.3																																						
LTE transmitter and antenna implementation	LTE has one (1) Tx/Rx antenna and one (1) Diversity Rx antennas Refer to Appendix A.																																						
Maximum power reduction (MPR)	<p align="center">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>>5</td> <td>>4</td> <td>>8</td> <td>>12</td> <td>>16</td> <td>>18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>>5</td> <td>>4</td> <td>>8</td> <td>>12</td> <td>>16</td> <td>>18</td> <td>≤ 2</td> </tr> </tbody> </table> <p>MPR Built-in by design A-MPR (additional MPR) was disabled during SAR testing</p>	Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	>5	>4	>8	>12	>16	>18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	>5	>4	>8	>12	>16	>18	≤ 2
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																	
QPSK	>5	>4	>8	>12	>16	>18	≤ 1																																
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																
16 QAM	>5	>4	>8	>12	>16	>18	≤ 2																																
Power reduction	No																																						
Spectrum plots for RB configurations	A properly configured base station simulator was used for the SAR and power measurements; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																						

6.6. RF Exposure Conditions (Test Configurations)

Refer to “Photos and Antenna Locations” Appendix for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

Wireless technologies	RF Exposure Conditions	DUT-to-User Separation	Test Position	Antenna-to-edge/surface	SAR Required	Note
WWAN	Head	0 mm	Left Touch	N/A	Yes	
			Left Tilt (15°)	N/A	Yes	
			Right Touch	N/A	Yes	
			Right Tilt (15°)	N/A	Yes	
	Body	10 mm	Rear	N/A	Yes	
			Front	N/A	Yes	
	Hotspot	10 mm	Rear	< 25 mm	Yes	
			Front	< 25 mm	Yes	
			Edge 1 (Top)	> 25 mm	No	1
			Edge 2 (Right)	< 25 mm	Yes	
			Edge 3 (Bottom)	< 25 mm	Yes	
		Edge 4 (Left)	< 25 mm	Yes		
WLAN	Head	0 mm	Left Touch	N/A	Yes	
			Left Tilt (15°)	N/A	Yes	
			Right Touch	N/A	Yes	
			Right Tilt (15°)	N/A	Yes	
	Body	10 mm	Rear	N/A	Yes	
			Front	N/A	Yes	
	Hotspot / Wi-Fi Direct	10 mm	Rear	< 25 mm	Yes	
			Front	< 25 mm	Yes	
			Edge 1 (Top)	< 25 mm	Yes	
			Edge 2 (Right)	> 25 mm	No	1
			Edge 3 (Bottom)	> 25 mm	No	1
		Edge 4 (Left)	< 25 mm	Yes		

Notes:

- SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR.

7. Conducted Output Power Measurements

7.1. GSM850 and GSM1900

GSM850 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)	
850	GSM (Voice)	CS1	1	128	824.2	33.3	24.3	
				190	836.6	33.1	24.0	
				251	848.8	33.1	24.1	
	GPRS (GMSK)	CS1	1	1	128	824.2	33.3	24.3
					190	836.6	33.1	24.0
					251	848.8	33.1	24.1
			2	1	128	824.2	30.4	24.4
					190	836.6	30.3	24.3
					251	848.8	30.4	24.3
			3	1	128	824.2	28.1	23.9
					190	836.6	28.2	24.0
					251	848.8	28.1	23.8
			4	1	128	824.2	26.0	23.0
					190	836.6	26.4	23.3
					251	848.8	26.5	23.5
	EGPRS (8PSK)	MCS5	1	1	128	824.2	26.7	17.6
					190	836.6	26.7	17.6
					251	848.8	26.7	17.7
			2	1	128	824.2	24.6	18.6
					190	836.6	24.6	18.5
					251	848.8	24.7	18.7
			3	1	128	824.2	22.5	18.3
					190	836.6	22.8	18.6
					251	848.8	22.5	18.3
4			1	128	824.2	22.4	19.4	
				190	836.6	22.5	19.5	
				251	848.8	22.5	19.5	

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

GSM1900 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)	
1900	GSM (Voice)	CS1	1	512	1850.2	30.7	21.7	
				661	1880.0	31.0	22.0	
				810	1909.8	30.8	21.7	
	GPRS (GMSK)	CS1	1	1	512	1850.2	30.7	21.7
					661	1880.0	31.0	22.0
					810	1909.8	30.8	21.7
			2	1	512	1850.2	28.0	21.9
					661	1880.0	28.4	22.4
					810	1909.8	27.8	21.8
			3	1	512	1850.2	25.7	21.4
					661	1880.0	26.0	21.7
					810	1909.8	25.6	21.4
			4	1	512	1850.2	23.7	20.7
					661	1880.0	24.7	21.7
					810	1909.8	23.6	20.6
	EGPRS (8PSK)	MCS5	1	1	512	1850.2	26.1	17.0
					661	1880.0	26.4	17.4
					810	1909.8	26.0	17.0
			2	1	512	1850.2	24.0	18.0
					661	1880.0	24.4	18.4
					810	1909.8	24.0	18.0
			3	1	512	1850.2	21.9	17.6
					661	1880.0	22.5	18.2
					810	1909.8	21.8	17.5
4			1	512	1850.2	21.8	18.8	
				661	1880.0	22.4	19.3	
				810	1909.8	21.8	18.8	

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

7.2. WCDMA Band V and II

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
WCDMA Band V	Rel 99 (RMC, 12.2 kbps)	4132	826.4	22.2
		4183	836.6	22.2
		4233	846.6	22.2
WCDMA Band II	Rel 99 (RMC, 12.2 kbps)	9262	1852.4	22.9
		9400	1880.0	22.8
		9538	1907.6	23.0

HSDPA

The following 4 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
MPR (dB)	0	0	0.5	0.5	
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
WCDMA Band V	Subtest 1	4132	826.4	0	22.3
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 2	4132	826.4	0	22.3
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 3	4132	826.4	0.5	20.8
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.7
	Subtest 4	4132	826.4	0.5	20.8
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.7
WCDMA Band II	Subtest 1	9262	1852.4	0	22.9
		9400	1880.0	0	22.6
		9538	1907.6	0	22.9
	Subtest 2	9262	1852.4	0	22.9
		9400	1880.0	0	22.6
		9538	1907.6	0	22.9
	Subtest 3	9262	1852.4	0.5	21.2
		9400	1880.0	0.5	21.1
		9538	1907.6	0.5	20.8
	Subtest 4	9262	1852.4	0.5	21.2
		9400	1880.0	0.5	21.1
		9538	1907.6	0.5	20.8

Maximum output power levels that are possible for all subtests reported.

HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	11/15	15/9	2/15	15/0
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15 47/15	56/75	47/15
	CM (dB)	1	3	2	3	1
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	A _{hs} = β_{hs}/β_c	30/15				
HSUPA Specific Settings	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
Reference E-TFCI PO	27	27	27	27	27	
Maximum Channelization Codes	2xSF2				SF4	

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
WCDMA Band V	Subtest 1	4132	826.4	0	21.7
		4183	836.6	0	21.9
		4233	846.6	0	22.0
	Subtest 2	4132	826.4	2	19.9
		4183	836.6	2	20.0
		4233	846.6	2	19.5
	Subtest 3	4132	826.4	1	20.0
		4183	836.6	1	20.1
		4233	846.6	1	19.8
	Subtest 4	4132	826.4	2	19.9
		4183	836.6	2	20.0
		4233	846.6	2	19.5
	Subtest 5	4132	826.4	0	21.7
		4183	836.6	0	21.9
		4233	846.6	0	22.0
WCDMA Band II	Subtest 1	9262	1852.4	0	22.3
		9400	1880.0	0	21.7
		9538	1907.6	0	22.2
	Subtest 2	9262	1852.4	2	20.5
		9400	1880.0	2	20.5
		9538	1907.6	2	20.3
	Subtest 3	9262	1852.4	1	20.3
		9400	1880.0	1	20.6
		9538	1907.6	1	20.8
	Subtest 4	9262	1852.4	2	20.5
		9400	1880.0	2	20.5
		9538	1907.6	2	20.3
	Subtest 5	9262	1852.4	0	22.3
		9400	1880.0	0	21.7
		9538	1907.6	0	22.2

DC-HSDPA

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121. A summary of subtest settings are illustrated below:

Mode		HSDPA	HSDPA	HSDPA	HSDPA
Subtest		1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
MPR (dB)	0	0	0.5	0.5	
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack Repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

Up commands are set continuously to set the UE to Max power.

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
WCDMA Band V	Subtest 1	4132	826.4	0	22.3
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 2	4132	826.4	0	22.3
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 3	4132	826.4	0.5	20.8
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.7
	Subtest 4	4132	826.4	0.5	20.8
		4183	836.6	0.5	20.6
		4233	846.6	0.5	20.7
WCDMA Band II	Subtest 1	9262	1852.4	0	22.9
		9400	1880.0	0	22.6
		9538	1907.6	0	22.9
	Subtest 2	9262	1852.4	0	22.9
		9400	1880.0	0	22.6
		9538	1907.6	0	22.9
	Subtest 3	9262	1852.4	0.5	21.2
		9400	1880.0	0.5	21.1
		9538	1907.6	0.5	20.8
	Subtest 4	9262	1852.4	0.5	21.2
		9400	1880.0	0.5	21.1
		9538	1907.6	0.5	20.8

7.3. LTE Band 5

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE Band 5 Measured Results

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							829 MHz	836.5 MHz	844 MHz
LTE Band 5	10	QPSK	1	0	0	0	22.0	21.9	21.8
			1	25	0	0	21.8	21.7	21.8
			1	49	0	0	21.7	21.7	21.8
			25	0	1	1	20.9	20.9	20.8
			25	12	1	1	20.8	20.7	20.7
			25	25	1	1	20.8	20.7	20.8
			50	0	1	1	20.9	20.8	20.8
		16QAM	1	0	1	1	21.2	21.4	21.1
			1	25	1	1	21.2	21.2	21.3
			1	49	1	1	21.3	21.3	21.2
			25	0	2	2	19.8	19.7	19.9
			25	12	2	2	19.7	19.7	19.7
			25	25	2	2	19.6	19.7	19.8
			50	0	2	2	19.7	19.8	19.7
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							826.5 MHz	836.5 MHz	846.5 MHz
LTE Band 5	5	QPSK	1	0	0	0	21.7	21.8	21.8
			1	12	0	0	22.2	22.1	22.1
			1	24	0	0	21.6	21.9	21.7
			12	0	1	1	20.8	20.8	20.7
			12	6	1	1	20.8	20.7	20.8
			12	11	1	1	20.8	20.7	20.8
			25	0	1	1	20.8	20.8	20.7
		16QAM	1	0	1	1	21.2	21.0	21.2
			1	12	1	1	21.0	21.0	21.2
			1	24	1	1	21.0	20.7	21.2
			12	0	2	2	19.7	19.8	19.8
			12	6	2	2	19.8	19.8	19.8
			12	11	2	2	19.7	19.8	19.7
			25	0	2	2	19.9	19.7	19.7
Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							825.5 MHz	836.5 MHz	847.5 MHz
LTE Band 5	3	QPSK	1	0	0	0	21.8	21.8	21.7
			1	7	0	0	21.8	22.1	22.0
			1	14	0	0	21.7	21.7	21.7
			8	0	1	1	20.8	20.7	20.7
			8	4	1	1	20.8	20.7	20.8
			8	7	1	1	20.7	20.6	20.8
			15	0	1	1	20.8	20.7	20.8
		16QAM	1	0	1	1	21.2	21.4	21.1
			1	7	1	1	21.0	20.9	20.7
			1	14	1	1	21.0	21.5	21.5
			8	0	2	2	19.8	19.5	19.9
			8	4	2	2	19.8	19.7	19.9
			8	7	2	2	19.8	19.5	19.9
			15	0	2	2	19.8	19.7	19.7

LTE Band 5 Measured Results (continued)

Band	BW (MHz)	Mode	RB Allocation	RB offset	Target MPR	Meas. MPR	Avg Pwr (dBm)		
							824.7 MHz	836.5 MHz	848.3 MHz
LTE Band 5	1.4	QPSK	1	0	0	0	21.8	21.6	21.7
			1	2	0	0	21.9	21.6	21.8
			1	5	0	0	21.7	21.7	21.6
			3	0	0	0	21.9	21.6	21.8
			3	1	0	0	21.9	21.8	22.0
			3	2	0	0	21.9	21.8	21.9
		16QAM	6	0	1	1	20.8	20.7	20.8
			1	0	1	0	21.5	21.5	20.6
			1	2	1	0	21.5	21.5	21.2
			1	5	1	0	21.5	21.5	21.0
			3	0	1	1	21.0	20.5	20.9
			3	1	1	1	21.0	20.6	21.0
			3	2	1	1	21.0	21.1	20.8
			6	0	2	2	19.8	19.5	19.8

Note(s):

10/5 MHz Bandwidths does not support at least three non-overlapping channels in certain channel bandwidths. When a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing per KDB 941225 D05 SAR for LTE Devices

7.4. Wi-Fi (2.4 GHz Band)

Required Test Channels per KDB 248227 D01

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
2.4 (DTS)	802.11b	1 Mbps	1	2412	17.1	Yes
			6	2437	17.1	
			11	2462	17.5	
	802.11g	6 Mbps	1	2412	13.4	No
			6	2437	13.5	
			11	2462	13.1	
	802.11n (HT20)	MCS0	1	2412	11.5	No
			6	2437	11.5	
			11	2462	11.1	

Note(s):

- Per KDB 248227 D01, SAR is not required for 802.11g/n HT20 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.

Power measurements to determine worst-case data rates

Mode	Ch #	Freq. (MHz)	Data Rate	Avg Pwr (dBm)	SAR test (Yes/No)
802.11b	6	2437	1 Mbps	17.1	Yes
			2 Mbps	17.0	No
			5.5 Mbps	17.1	No
			11 Mbps	16.8	No

7.5. Bluetooth

Maximum tune-up tolerance limit is 10.5 dBm. This power level qualifies for exclusion of SAR testing. Refer to Standalone SAR Test Exclusion Considerations Section.

8. Dielectric Property Measurements

8.1. Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

8.2. Dielectric Property Measurements Results

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

SAR Lab 1

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
11/19/2014	Head 2450	e'	39.3000	Relative Permittivity (ϵ_r):	39.30	39.20	0.26	5
		e"	13.8700	Conductivity (σ):	1.89	1.80	4.97	5
	Head 2410	e'	39.5100	Relative Permittivity (ϵ_r):	39.51	39.28	0.59	5
		e"	13.7700	Conductivity (σ):	1.85	1.76	4.82	5
	Head 2475	e'	39.2100	Relative Permittivity (ϵ_r):	39.21	39.17	0.11	5
		e"	13.8900	Conductivity (σ):	1.91	1.83	4.62	5
11/19/2014	Body 2450	e'	50.2200	Relative Permittivity (ϵ_r):	50.22	52.70	-4.71	5
		e"	14.2100	Conductivity (σ):	1.94	1.95	-0.73	5
	Body 2410	e'	50.4200	Relative Permittivity (ϵ_r):	50.42	52.76	-4.43	5
		e"	14.0600	Conductivity (σ):	1.88	1.91	-1.23	5
	Body 2475	e'	50.0900	Relative Permittivity (ϵ_r):	50.09	52.67	-4.90	5
		e"	14.2800	Conductivity (σ):	1.97	1.99	-1.01	5

SAR Lab 3

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
11/21/2014	Head 835	e'	41.4100	Relative Permittivity (ϵ_r):	41.41	41.50	-0.22	5
		e"	19.4800	Conductivity (σ):	0.90	0.90	0.49	5
	Head 820	e'	41.6300	Relative Permittivity (ϵ_r):	41.63	41.60	0.07	5
		e"	19.4800	Conductivity (σ):	0.89	0.90	-1.14	5
	Head 850	e'	41.3100	Relative Permittivity (ϵ_r):	41.31	41.50	-0.46	5
		e"	19.4900	Conductivity (σ):	0.92	0.92	0.67	5
11/21/2014	Body 835	e'	52.5500	Relative Permittivity (ϵ_r):	52.55	55.20	-4.80	5
		e"	21.6000	Conductivity (σ):	1.00	0.97	3.39	5
	Body 820	e'	52.7000	Relative Permittivity (ϵ_r):	52.70	55.28	-4.66	5
		e"	21.6200	Conductivity (σ):	0.99	0.97	1.79	5
	Body 850	e'	52.4700	Relative Permittivity (ϵ_r):	52.47	55.16	-4.87	5
		e"	21.6100	Conductivity (σ):	1.02	0.99	3.46	5
11/24/2014	Head 835	e'	43.1300	Relative Permittivity (ϵ_r):	43.13	41.50	3.93	5
		e"	19.8200	Conductivity (σ):	0.92	0.90	2.25	5
	Head 820	e'	43.2800	Relative Permittivity (ϵ_r):	43.28	41.60	4.03	5
		e"	19.9600	Conductivity (σ):	0.91	0.90	1.29	5
	Head 850	e'	42.9200	Relative Permittivity (ϵ_r):	42.92	41.50	3.42	5
		e"	19.7700	Conductivity (σ):	0.93	0.92	2.12	5
11/24/2014	Body 835	e'	53.2800	Relative Permittivity (ϵ_r):	53.28	55.20	-3.48	5
		e"	21.5700	Conductivity (σ):	1.00	0.97	3.24	5
	Body 820	e'	53.4600	Relative Permittivity (ϵ_r):	53.46	55.28	-3.29	5
		e"	21.6800	Conductivity (σ):	0.99	0.97	2.07	5
	Body 850	e'	53.1900	Relative Permittivity (ϵ_r):	53.19	55.16	-3.57	5
		e"	21.4300	Conductivity (σ):	1.01	0.99	2.60	5

SAR Lab 4

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
11/17/2017	Head 1900	e'	38.2300	Relative Permittivity (ϵ_r):	38.23	40.00	-4.43	5
		e"	13.1100	Conductivity (σ):	1.39	1.40	-1.07	5
	Head 1850	e'	38.4500	Relative Permittivity (ϵ_r):	38.45	40.00	-3.87	5
		e"	13.0100	Conductivity (σ):	1.34	1.40	-4.41	5
	Head 1910	e'	38.1800	Relative Permittivity (ϵ_r):	38.18	40.00	-4.55	5
		e"	13.2500	Conductivity (σ):	1.41	1.40	0.51	5
11/17/2014	Body 1900	e'	50.8100	Relative Permittivity (ϵ_r):	50.81	53.30	-4.67	5
		e"	14.3100	Conductivity (σ):	1.51	1.52	-0.54	5
	Body 1850	e'	51.0100	Relative Permittivity (ϵ_r):	51.01	53.30	-4.30	5
		e"	14.1800	Conductivity (σ):	1.46	1.52	-4.04	5
	Body 1910	e'	50.8000	Relative Permittivity (ϵ_r):	50.80	53.30	-4.69	5
		e"	14.4000	Conductivity (σ):	1.53	1.52	0.61	5
11/20/2014	Head 1900	e'	38.5400	Relative Permittivity (ϵ_r):	38.54	40.00	-3.65	5
		e"	13.1300	Conductivity (σ):	1.39	1.40	-0.92	5
	Head 1850	e'	38.7500	Relative Permittivity (ϵ_r):	38.75	40.00	-3.13	5
		e"	13.0100	Conductivity (σ):	1.34	1.40	-4.41	5
	Head 1910	e'	38.5400	Relative Permittivity (ϵ_r):	38.54	40.00	-3.65	5
		e"	13.1700	Conductivity (σ):	1.40	1.40	-0.09	5
11/20/2014	Body 1900	e'	51.0800	Relative Permittivity (ϵ_r):	51.08	53.30	-4.17	5
		e"	14.3800	Conductivity (σ):	1.52	1.52	-0.05	5
	Body 1850	e'	51.2900	Relative Permittivity (ϵ_r):	51.29	53.30	-3.77	5
		e"	14.2600	Conductivity (σ):	1.47	1.52	-3.50	5
	Body 1910	e'	51.1000	Relative Permittivity (ϵ_r):	51.10	53.30	-4.13	5
		e"	14.4600	Conductivity (σ):	1.54	1.52	1.03	5

9. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

9.1. System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
 For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
 For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

9.2. Reference Target SAR Values

The reference SAR values are obtained from the calibration certificate of system validation dipoles. The measured values are normalized to 1 Watt.

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D835V2	4d142	9/9/2014	835	1g	8.91	9.22
				10g	5.77	6.05
D1900V2	5d163	9/11/2014	1900	1g	40.8	40.6
				10g	21.2	21.4
D2450V2	706	5/20/2014	2450	1g	53.0	50.2
				10g	24.5	23.4

9.3. System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Lab 1

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta ±10 %	Plot No.	
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W				
11/19/2014	D2450V2	706	Head	1g	5.61	56.1	53.00	5.85	1,2
				10g	2.52	25.2	24.50	2.86	
11/19/2014	D2450V2	706	Body	1g	5.12	51.2	50.20	1.99	
				10g	2.34	23.4	23.40	0.00	

SAR Lab 3

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta ±10 %	Plot No.	
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W				
11/21/2014	D835V2	4d142	Head	1g	0.948	9.480	8.91	6.40	3,4
				10g	0.623	6.230	5.77	7.97	
11/21/2014	D835V2	4d142	Body	1g	0.979	9.790	9.22	6.18	
				10g	0.642	6.420	6.05	6.12	
11/24/2014	D835V2	4d142	Head	1g	0.947	9.470	8.91	6.29	
				10g	0.620	6.200	5.77	7.45	
11/24/2014	D835V2	4d142	Body	1g	0.975	9.750	9.22	5.75	
				10g	0.642	6.420	6.05	6.12	

SAR Lab 4

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta ±10 %	Plot No.	
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W				
11/17/2014	1900	5d163	Head	1g	4.04	40.4	40.80	-0.98	
				10g	2.08	20.8	21.20	-1.89	
11/17/2014	1900	5d163	Body	1g	3.76	37.6	40.60	-7.39	5,6
				10g	1.96	19.6	21.40	-8.41	
11/21/2014	1900	5d163	Head	1g	4.13	41.3	40.80	1.23	
				10g	2.15	21.5	21.20	1.42	
11/21/2014	1900	5d163	Body	1g	3.87	38.7	40.60	-4.68	
				10g	2.02	20.2	21.40	-5.61	

10. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:

With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

KDB 941225 D01 SAR test for 3G devices:

Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least $\frac{1}{4}$ dB higher than that measured without HSPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2.

KDB 941225 D05 SAR for LTE Devices:

SAR test reduction is applied using the following criteria:

- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel.
- When the reported SAR is > 0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel.
- Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg. Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg.
- Testing for 16-QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of QPSK.
- Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/Kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

KDB 248227 D01 SAR Measurements Procedures for 802.11 a/b/g Transmitters v01r02 (pg.6):

Each channel should be tested at the lowest data rate in each a-b/g mode or 4.9 GHz channel BW configuration.

When the extrapolated maximum peak SAR for the maximum output channel is ≤ 1.6 W/kg and the 1-g averaged SAR is ≤ 0.8 W/kg, testing of other channels in the "default test channels" or "required test channels" configuration is optional.

10.1. GSM850

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	190	836.6	33.5	33.1	0.266	0.292	1
			Left Tilt	190	836.6	33.5	33.1	0.192	0.211	
			Right Touch	190	836.6	33.5	33.1	0.330	0.362	
			Right Tilt	190	836.6	33.5	33.1	0.224	0.246	
Head VoIP	GPRS 2 Slots	0	Left Touch	190	836.6	30.5	30.3	0.309	0.324	2
			Left Tilt	190	836.6	30.5	30.3	0.220	0.230	
			Right Touch	190	836.6	30.5	30.3	0.362	0.379	
			Right Tilt	190	836.6	30.5	30.3	0.244	0.255	
Body-worn	Voice	10	Rear	190	836.6	33.5	33.1	0.395	0.433	3
			Front	190	836.6	33.5	33.1	0.318	0.349	
Body-worn(VoIP) & Hotspot	GPRS 2 Slots	10	Rear	190	836.6	30.5	30.3	0.447	0.468	4
Front			190	836.6	30.5	30.3	0.371	0.388		
Hotspot			Edge 2	190	836.6	30.5	30.3	0.332	0.348	
			Edge 3	190	836.6	30.5	30.3	0.134	0.140	
			Edge 4	190	836.6	30.5	30.3	0.287	0.301	

10.2. GSM1900

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	661	1880.0	31.0	31.0	0.156	0.156	5
			Left Tilt	661	1880.0	31.0	31.0	0.032	0.032	
			Right Touch	661	1880.0	31.0	31.0	0.109	0.109	
			Right Tilt	661	1880.0	31.0	31.0	0.038	0.038	
Head VoIP	GPRS 2 Slots	0	Left Touch	661	1880.0	28.5	28.4	0.167	0.171	6
			Left Tilt	661	1880.0	28.5	28.4	0.034	0.035	
			Right Touch	661	1880.0	28.5	28.4	0.110	0.113	
			Right Tilt	661	1880.0	28.5	28.4	0.043	0.044	
Body-worn	Voice	10	Rear	661	1880.0	31.0	31.0	0.256	0.256	7
			Front	661	1880.0	31.0	31.0	0.288	0.288	
Body-worn(VoIP) & Hotspot	GPRS 2 Slots	10	Rear	661	1880.0	28.5	28.4	0.263	0.269	8
Front			661	1880.0	28.5	28.4	0.314	0.321		
Hotspot			Edge 2	661	1880.0	28.5	28.4	0.037	0.038	
			Edge 3	661	1880.0	28.5	28.4	0.224	0.229	
			Edge 4	661	1880.0	28.5	28.4	0.132	0.135	

10.3. WCDMA Band V

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	4183	836.6	23.0	22.2	0.206	0.248	9
			Left Tilt	4183	836.6	23.0	22.2	0.114	0.137	
			Right Touch	4183	836.6	23.0	22.2	0.190	0.228	
			Right Tilt	4183	836.6	23.0	22.2	0.118	0.142	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	4183	836.6	23.0	22.2	0.299	0.359	10
			Front	4183	836.6	23.0	22.2	0.243	0.292	
Hotspot	Rel 99 RMC	10	Edge 2	4183	836.6	23.0	22.2	0.148	0.178	
			Edge 3	4183	836.6	23.0	22.2	0.042	0.050	
			Edge 4	4183	836.6	23.0	22.2	0.178	0.214	

10.4. WCDMA Band II

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	9400	1880.0	23.0	22.8	0.269	0.282	11
			Left Tilt	9400	1880.0	23.0	22.8	0.053	0.055	
			Right Touch	9400	1880.0	23.0	22.8	0.155	0.162	
			Right Tilt	9400	1880.0	23.0	22.8	0.054	0.057	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	9400	1880.0	23.0	22.8	0.386	0.404	
			Front	9400	1880.0	23.0	22.8	0.516	0.540	12
Hotspot	Rel 99 RMC	10	Edge 2	9400	1880.0	23.0	22.8	0.054	0.057	
			Edge 3	9400	1880.0	23.0	22.8	0.331	0.347	
			Edge 4	9400	1880.0	23.0	22.8	0.192	0.201	

10.5. LTE Band 5 (10MHz Bandwidth)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	RB Allocation	RB Offset	Power (dBm)		1-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	
Head	QPSK	0	Left Touch	20525	836.5	1	0	22.5	21.9	0.209	0.238	
						25	0	21.5	20.9	0.153	0.177	
			Left Tilt	20525	836.5	1	0	22.5	21.9	0.166	0.189	
						25	0	21.5	20.9	0.114	0.132	
			Right Touch	20525	836.5	1	0	22.5	21.9	0.229	0.261	13
						25	0	21.5	20.9	0.165	0.191	
			Right Tilt	20525	836.5	1	0	22.5	21.9	0.157	0.179	
						25	0	21.5	20.9	0.116	0.134	
Body-worn & Hotspot	QPSK	10	Rear	20525	836.5	1	0	22.5	21.9	0.356	0.406	14
						25	0	21.5	20.9	0.256	0.296	
			Front	20525	836.5	1	0	22.5	21.9	0.278	0.317	
						25	0	21.5	20.9	0.201	0.232	
Hotspot	QPSK	10	Edge 2	20525	836.5	1	0	22.5	21.9	0.255	0.291	
						25	0	21.5	20.9	0.173	0.200	
			Edge 3	20525	836.5	1	0	22.5	21.9	0.073	0.083	
						25	0	21.5	20.9	0.054	0.063	
			Edge 4	20525	836.5	1	0	22.5	21.9	0.222	0.253	
						25	0	21.5	20.9	0.150	0.173	

10.6. Wi-Fi (DTS Band)

Frequency Band	RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	
2.4 GHz	Head	802.11b 1 Mbps	0	Left Touch	11	2462.0	17.5	17.5	0.150	0.150	
				Left Tilt	11	2462.0	17.5	17.5	0.138	0.138	
				Right Touch	11	2462.0	17.5	17.5	0.348	0.348	15
				Right Tilt	11	2462.0	17.5	17.5	0.195	0.195	
	Body-worn & Hotspot	802.11b 1 Mbps	10	Rear	11	2462.0	17.5	17.5	0.343	0.343	16
				Front	11	2462.0	17.5	17.5	0.095	0.095	
	Hotspot	802.11b 1 Mbps	10	Edge 1	11	2462.0	17.5	17.5	0.066	0.066	
				Edge 4	11	2462.0	17.5	17.5	0.253	0.253	

10.7. Bluetooth

10.7.1. Standalone SAR Test Exclusion Considerations

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Body-worn Accessory Exposure Conditions

Max. tune-up tolerance limit		Min. test separation distance (mm)	Frequency (GHz)	Result
(dBm)	(mW)			
10.5	11	10	2.480	1.7

Conclusion:

The computed value is < 3 ; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

10.7.2. Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}/x}] \text{ W/kg}$ for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Estimated SAR Result for Body-worn Accessory Conditions:

Test Configuration	Max. tune-up tolerance limit (mW)	Min. test separation distance (mm)	Frequency (GHz)	Estimated 1-g SAR (W/kg)
Rear/Front	11	10	2.480	0.231

11. SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is <1.6 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 1.6 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or 3 (1-g or 10-g respectively) or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg (~ 10% from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 or 3 (1-g or 10-g respectively).

Frequency Band (MHz)	Air Interface	RF Exposure Conditions	Test Position	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Repeated Measured SAR (W/kg)	Largest to Smallest SAR Ratio
850	GSM 850	Body-worn & Hotspot	Rear	No	0.447	N/A	N/A
	WCDMA Band V	Body-worn & Hotspot	Rear	No	0.299	N/A	N/A
	LTE Band 5	Body-worn & Hotspot	Rear	No	0.356	N/A	N/A
1900	GSM 1900	Body-worn & Hotspot	Front	No	0.314	N/A	N/A
	WCDMA Band II	Body-worn & Hotspot	Front	No	0.516	N/A	N/A
2400	Wi-Fi 2.4GHz	Head	Right Touch	No	0.348	N/A	N/A

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .

12. Simultaneous Transmission SAR Analysis

12.1. Sum of the SAR for GSM850 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM 850	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.324	0.150		0.474	No
	Left Tilt	① + ②	0.230	0.138		0.368	No
	Right Touch	① + ②	0.379	0.348		0.727	No
	Right Tilt	① + ②	0.255	0.195		0.450	No
Body-w orn Accessory & Hotspot	Rear	① + ②	0.468	0.343		0.811	No
		① + ③	0.468		0.231	0.699	No
	Front	① + ②	0.388	0.095		0.483	No
		① + ③	0.388		0.231	0.619	No
Hotspot	Edge 1	① + ②		0.066		0.066	No
	Edge 2	① + ②	0.348			0.348	No
	Edge 3	① + ②	0.140			0.140	No
	Edge 4	① + ②	0.301	0.253		0.554	No

12.2. Sum of the SAR for GSM1900 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM1900	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.171	0.150		0.321	No
	Left Tilt	① + ②	0.035	0.138		0.173	No
	Right Touch	① + ②	0.113	0.348		0.461	No
	Right Tilt	① + ②	0.044	0.195		0.239	No
Body-w orn Accessory & Hotspot	Rear	① + ②	0.269	0.343		0.612	No
		① + ③	0.269		0.231	0.500	No
	Front	① + ②	0.321	0.095		0.416	No
		① + ③	0.321		0.231	0.552	No
Hotspot	Edge 1	① + ②		0.066		0.066	No
	Edge 2	① + ②	0.038			0.038	No
	Edge 3	① + ②	0.229			0.229	No
	Edge 4	① + ②	0.135	0.253		0.388	No

12.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① WCDMA Band V	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.248	0.150		0.398	No
	Left Tilt	① + ②	0.137	0.138		0.275	No
	Right Touch	① + ②	0.228	0.348		0.576	No
	Right Tilt	① + ②	0.142	0.195		0.337	No
Body-w orn Accessory & Hotspot	Rear	① + ②	0.359	0.343		0.702	No
		① + ③	0.359		0.231	0.590	No
	Front	① + ②	0.292	0.095		0.387	No
		① + ③	0.292		0.231	0.523	No
Hotspot	Edge 1	① + ②		0.066		0.066	No
	Edge 2	① + ②	0.178			0.178	No
	Edge 3	① + ②	0.050			0.050	No
	Edge 4	① + ②	0.214	0.253		0.467	No

12.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① WCDMA Band II	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.282	0.150		0.432	No
	Left Tilt	① + ②	0.055	0.138		0.193	No
	Right Touch	① + ②	0.162	0.348		0.510	No
	Right Tilt	① + ②	0.056	0.195		0.251	No
Body-w orn Accessory & Hotspot	Rear	① + ②	0.404	0.343		0.747	No
		① + ③	0.404		0.231	0.635	No
	Front	① + ②	0.540	0.095		0.635	No
		① + ③	0.540		0.231	0.771	No
Hotspot	Edge 1	① + ②		0.066		0.066	No
	Edge 2	① + ②	0.057			0.057	No
	Edge 3	① + ②	0.347			0.347	No
	Edge 4	① + ②	0.201	0.253		0.454	No

12.5. Sum of the SAR for LTE Band 5 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① LTE Band 5	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.238	0.150		0.388	No
	Left Tilt	① + ②	0.189	0.138		0.327	No
	Right Touch	① + ②	0.261	0.348		0.609	No
	Right Tilt	① + ②	0.179	0.195		0.374	No
Body-w orn Accessory & Hotspot	Rear	① + ②	0.406	0.343		0.749	No
		① + ③	0.406		0.231	0.637	No
	Front	① + ②	0.317	0.095		0.412	No
		① + ③	0.317		0.231	0.548	No
Hotspot	Edge 1	① + ②		0.066		0.066	No
	Edge 2	① + ②	0.291			0.291	No
	Edge 3	① + ②	0.083			0.083	No
	Edge 4	① + ②	0.253	0.253		0.506	No

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

13. Appendixes

Refer to separated files for the following appendixes.

- A. Photos and Antenna Locations**
- B. System Performance Check Plots**
- C. Highest SAR Test Plots**
- D. Tissue Material Ingredients**
- E. Calibration Certificates for E-Field Probes**
- F. Calibration Certificates for Dipoles**

END OF REPORT