



FCC CFR47 PART 15 SUBPART C

Bluetooth

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS b/g/n and ANT+

MODEL NUMBER : SM-G610F/DD, SM-G610F/DS

FCC ID: A3LSMG610F

REPORT NUMBER: 16K23775-E3V1

ISSUE DATE: AUG 08, 2016

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	08/08/16	Initial issue	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	6
4.2. <i>SAMPLE CALCULATION</i>	6
4.3. <i>MEASUREMENT UNCERTAINTY</i>	6
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT</i>	7
5.2. <i>MAXIMUM OUTPUT POWER</i>	7
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	7
5.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.5. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. SUMMARY TABLE	11
8. ANTENNA PORT TEST RESULTS	12
8.1. <i>20 dB AND 99% BANDWIDTH</i>	12
8.1.1. <i>BASIC DATA RATE GFSK MODULATION</i>	12
8.1.2. <i>ENHANCED DATA RATE Pi/4-DQPSK MODULATION</i>	12
8.1.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	12
8.1.4. <i>20 dB AND 99% BANDWIDTH PLOTS</i>	13
8.2. <i>HOPPING FREQUENCY SEPARATION</i>	16
8.3. <i>NUMBER OF HOPPING CHANNELS</i>	17
8.4. <i>AVERAGE TIME OF OCCUPANCY</i>	19
8.5. <i>OUTPUT POWER</i>	23
8.5.1. <i>BASIC DATA RATE GFSK MODULATION</i>	23
8.5.2. <i>ENHANCED DATA RATE Pi/4-DPSK MODULATION</i>	23
8.5.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	23
8.5.4. <i>OUTPUT POWER PLOTS</i>	24
8.6. <i>AVERAGE POWER</i>	27
8.6.1. <i>BASIC DATA RATE GFSK MODULATION</i>	27
8.6.2. <i>DATA RATE PI/4-DQPSK MODULATION</i>	27
8.6.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	27
8.7. <i>CONDUCTED SPURIOUS EMISSIONS</i>	28
8.7.1. <i>BASIC DATA RATE GFSK MODULATION</i>	29

9. RADIATED TEST RESULTS.....	41
9.1. LIMITS AND PROCEDURE.....	41
9.2. TRANSMITTER ABOVE 1 GHz.....	43
9.2.1. BASIC DATA RATE GFSK MODULATION	43
9.2.2. ENHANCED DATA RATE 8PSK MODULATION	53
9.3. WORST-CASE BELOW 1 GHz	63
9.3.1. SM-G610F/DD	63
9.3.2. SM-G610F/DS	65
10. AC POWER LINE CONDUCTED EMISSIONS	67
10.1. SM-G610F/DD.....	68
10.2. SM-G610F/DS.....	72
11. SETUP PHOTOS.....	76

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS b/g/n and ANT+
MODEL NUMBER: SM-G610F/DD, SM-G610F/DS
SERIAL NUMBER: 5203a883e8304309, R38H70DHYVE (SM-G610F/DD, RADIATED);
R38H60EJB6X (SM-G610F/DS, RADIATED);
R38H60EJBGD (SM-G610F/DD, CONDUCTED)
DATE TESTED: JUL 18, 2016 - AUG 08, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + Bluetooth/BLE, DTS b/g/n and ANT+. This test report addresses the DSS (BT) operational mode.

SM-G610F/DD and SM-G610F/DS are same hardware. But travel charger and data cable of these two model were different.

In accordance with difference of travel charger and data cable, AC power line conducted test and radiated emissions test below 1GHz were conducted by each model. SM-G610F/DD was used for the other tests.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	Basic GFSK	Average	9.530	8.974
		Peak	10.105	10.245
	Enhanced Pi/4-DPSK	Average	5.620	3.648
		Peak	8.025	6.346
	Enhanced 8PSK	Average	5.630	3.656
		Peak	8.397	6.914

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -2.1 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

■ SM-G610F/DD

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50IWE	DK2H418VS/A-E	N/A
Data Cable	SAMSUNG	EP-DG915UWE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A

■ SM-G610F/DS

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50EWE	DK4H426VS/A-E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests. EUT was set in the Hidden menu mode to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	11-17-16
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-16
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-18-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-19-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-19-16
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-16
Average Power Sensor	R&S	NRZ-Z91	102681	08-18-16
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-18-16
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-19-16
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-19-16
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-19-16
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-18-16
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-18-16
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-18-16
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17542	009	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17542	016	08-18-16
LISN	R&S	ENV-216	101836	08-19-16
LISN	R&S	ENV-216	101837	08-19-16
Combiner	WEINSCHEL	1575	2152	08-20-16

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	Occupied Band width (99%)	N/A	Conducted	Pass	1.200 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-37.394 dBm
15.247 (b)(1)	TX conducted output power	<21dBm		Pass	10.105 dBm (Peak)
15.247 (a)(1)	Hopping frequency separation	> 25KHz		Pass	1 MHz
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4sec		Pass	0.34632 sec
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	56.07 dBuV (Qp)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	43.82 dBuV/m (Av)

8. ANTENNA PORT TEST RESULTS

8.1. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to \geq 1% of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS

8.1.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [KHz]
Low	2402	1.051	927.890
Mid	2441	1.050	903.540
High	2480	1.051	930.010
Worst		1.051	930.010

8.1.2. ENHANCED DATA RATE Pi/4-DQPSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.298	1.194
Mid	2441	1.351	1.194
High	2480	1.295	1.200
Worst		1.351	1.200

8.1.3. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.314	1.196
Mid	2441	1.313	1.196
High	2480	1.315	1.198
Worst		1.315	1.198

8.1.4. 20 dB AND 99% BANDWIDTH PLOTS


GFSK BANDWIDTH



Pi/4-DQPSK BANDWIDTH



8PSK BANDWIDTH



8.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS

Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS PLOTS

NUMBER OF HOPPING CHANNELS (100 MHZ SPAN)





8.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$.


RESULTS

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.382	32	0.122336	0.4	-0.2777
DH3	1.636	16	0.261760	0.4	-0.1382
DH5	2.886	12	0.346320	0.4	-0.0537
GFSK AFH					
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.382	8	0.030584	0.4	-0.36942
DH3	1.636	4	0.065440	0.4	-0.33456
DH5	2.886	3	0.086580	0.4	-0.31342


DH1



DH3



DH5



8.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

8.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	10.033	21	-10.967
Middle	2441	10.105	21	-10.895
High	2480	9.211	21	-11.789
Worst		10.105	21	-10.895

8.5.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION

Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	7.784	21	-13.216
Middle	2441	8.025	21	-12.975
High	2480	7.068	21	-13.932
Worst		8.025	21	-12.975

8.5.3. ENHANCED DATA RATE 8PSK MODULATION




Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	8.226	21	-12.774
Middle	2441	8.397	21	-12.603
High	2480	7.439	21	-13.561
Worst		8.397	21	-12.603

8.5.4. OUTPUT POWER PLOTS

GFSK OUTPUT POWER

<p>GFSK Low CH</p>	
<p>GFSK Middle CH</p>	
<p>GFSK High CH</p>	

Pi/4-DPSK OUTPUT POWER

<p>Pi/4-DPSK Low CH</p>	
<p>Pi/4-DPSK Middle CH</p>	
<p>Pi/4-DPSK High CH</p>	

8PSK OUTPUT POWER

<p>8PSK Low CH</p>	<p>Keysight Spectrum Analyzer - Swept SA RL RF 50 Ω DC CORREC SENSE:INTI ALIGN: AUTO 02:25:50 PM Jul 19, 2016 PNO: Fast Trig: Free Run #Avg Type: RMS IFGain:Low Atten: 30 dB AvgHold: 100/100 TRACE 1 2 3 4 5 6 TYPE: M W W W W W W W DET: P N N N N N N N Ref 20.00 dBm Mkr1 2.402 089 5 GHz 8.226 dBm 10 dB/div Log Center 2.4020895 GHz Span 10.00 MHz #Res BW 3.0 MHz #VBW 50 MHz Sweep 1.333 ms (20001 pts)</p>
<p>8PSK Middle CH</p>	<p>Keysight Spectrum Analyzer - Swept SA RL RF 50 Ω DC CORREC SENSE:INTI ALIGN: AUTO 02:26:11 PM Jul 19, 2016 PNO: Fast Trig: Free Run #Avg Type: RMS IFGain:Low Atten: 30 dB AvgHold: 100/100 TRACE 1 2 3 4 5 6 TYPE: M W W W W W W W DET: P N N N N N N N Ref 20.00 dBm Mkr1 2.441 020 5 GHz 8.397 dBm 10 dB/div Log Center 2.4410205 GHz Span 10.00 MHz #Res BW 3.0 MHz #VBW 50 MHz Sweep 1.333 ms (20001 pts)</p>
<p>8PSK High CH</p>	<p>Keysight Spectrum Analyzer - Swept SA RL RF 50 Ω DC CORREC SENSE:INTI ALIGN: AUTO 02:27:51 PM Jul 19, 2016 PNO: Fast Trig: Free Run #Avg Type: RMS IFGain:Low Atten: 30 dB AvgHold: 100/100 TRACE 1 2 3 4 5 6 TYPE: M W W W W W W W DET: P N N N N N N N Ref 20.00 dBm Mkr1 2.479 966 5 GHz 7.439 dBm 10 dB/div Log Center 2.4799665 GHz Span 10.00 MHz #Res BW 3.0 MHz #VBW 50 MHz Sweep 1.333 ms (20001 pts)</p>

8.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

8.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	9.530	8.97
Middle	2441	9.520	8.95
High	2480	8.430	6.97

8.6.2. DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	5.550	3.59
Middle	2441	5.620	3.65
High	2480	4.600	2.88

8.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	5.590	3.62
Middle	2441	5.630	3.66
High	2480	4.620	2.90

8.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

8.7.1. BASIC DATA RATE GFSK MODULATION

GFSK Mode









BandEdge Emission at GFSK Hopping Mode


[GFSK Hopping Mode] Low Channel BandEdge





[GFSK Hopping Mode] High Channel BandEdge



PI/4-DQPSK Mode









BandEdge Emission at PI/4-DQPSK Hopping Mode


[PI/4-DQPSK Hopping Mode] Low Channel BandEdge





[PI/4-DQPSK Hopping Mode] High Channel BandEdge



8PSK Mode









BandEdge Emission at 8PSK Hopping Mode

[8PSK Hopping Mode] Low Channel BandEdge



[8PSK Hopping Mode] High Channel BandEdge



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.

$GFSK = 1/T = 1 / 0.0029S = 350Hz.$

The spectrum from 1GHzHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.


Formula for converting the filed strength from uV/m to dBuV/m is:
 $Limit (dBuV/m) = 20 \log limit (uV/m)$

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	44.07	Pk	31.8	-29	46.87	-	-	74	-27.13	170	373	H
2	* 2.387	48.39	Pk	31.8	-29	51.19	-	-	74	-22.81	170	373	H
3	* 2.39	35.86	VA1T	31.8	-29	38.66	54	-15.34	-	-	170	373	H
4	* 2.36	36.4	VA1T	31.7	-29	39.1	54	-14.9	-	-	170	373	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	45.43	Pk	31.8	-29	48.23	-	-	74	-25.77	238	329	V
2	* 2.384	48.7	Pk	31.8	-29	51.5	-	-	74	-22.5	238	329	V
3	* 2.39	35.88	VA1T	31.8	-29	38.68	54	-15.32	-	-	238	329	V
4	* 2.351	36.35	VA1T	31.7	-29	39.05	54	-14.95	-	-	238	329	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	45.67	Pk	32	-28.9	48.77	-	-	74	-25.23	176	390	H
2	* 2.49	48.59	Pk	32	-28.9	51.69	-	-	74	-22.31	176	390	H
3	* 2.484	35.47	VA1T	32	-28.9	38.57	54	-15.43	-	-	176	390	H
4	2.561	35.98	VA1T	32	-28.8	39.18	54	-14.82	-	-	176	390	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $VB=1/Ton$ where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	45.17	Pk	32	-28.9	48.27	-	-	74	-25.73	232	390	V
2	2.52	48.47	Pk	32	-28.9	51.57	-	-	74	-22.43	232	390	V
3	* 2.484	36.03	VA1T	32	-28.9	39.13	54	-14.87	-	-	232	390	V
4	* 2.491	36.27	VA1T	32	-28.9	39.37	54	-14.63	-	-	232	390	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average $VB=1/Ton$ where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	41.89	PK	34	-33.8	42.09	-	-	74	-31.91	0-360	150	H
4	7.206	40	PK	35.7	-30.8	44.9	-	-	74	-29.1	0-360	150	H
5	9.604	30.32	PK	37	-27.3	40.02	-	-	74	-33.98	0-360	150	H
2	* 4.804	39.75	PK	34	-33.8	39.95	-	-	74	-34.05	0-360	250	V
3	7.206	39.02	PK	35.7	-30.8	43.92	-	-	74	-30.08	0-360	250	V
6	9.609	32.04	PK	37	-27.3	41.74	-	-	74	-32.26	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	49.71	PK2	34	-33.8	49.91	-	-	74	-24.09	292	100	H
* 4.804	41.77	VA1T	34	-33.8	41.97	54	-12.03	-	-	292	100	H
* 4.805	46.66	PK2	34	-33.8	46.86	-	-	74	-27.14	151	300	V
* 4.804	33.12	VA1T	34	-33.8	33.32	54	-20.68	-	-	151	300	V
7.206	46.4	PK2	35.7	-30.8	51.3	-	-	74	-22.7	17	300	V
7.207	46.52	PK2	35.7	-30.8	51.42	-	-	74	-22.58	311	317	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.882	39.56	PK	34	-34	39.56	-	-	74	-34.44	0-360	150	H
4	* 7.323	37.41	PK	35.8	-30.9	42.31	-	-	74	-31.69	0-360	150	H
5	9.764	31.16	PK	37.2	-26.6	41.76	-	-	74	-32.24	0-360	250	H
2	* 4.881	37.77	PK	34	-34	37.77	-	-	74	-36.23	0-360	150	V
3	* 7.323	37.51	PK	35.8	-30.9	42.41	-	-	74	-31.59	0-360	250	V
6	9.778	29.82	PK	37.2	-26.4	40.62	-	-	74	-33.38	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.323	47.56	PK2	35.8	-30.9	52.46	-	-	74	-21.54	302	264	H
* 7.323	38.92	VA1T	35.8	-30.9	43.82	54	-10.18	-	-	302	264	H
* 7.323	46.8	PK2	35.8	-30.9	51.7	-	-	74	-22.3	5	150	V
* 7.323	37.4	VA1T	35.8	-30.9	42.3	54	-11.7	-	-	5	150	V
* 4.882	48.17	PK2	34	-34	48.17	-	-	74	-25.83	1	100	V
* 4.882	36.46	VA1T	34	-34	36.46	54	-17.54	-	-	1	100	V
* 4.882	48.62	PK2	34	-34	48.62	-	-	74	-25.38	294	100	H
* 4.882	39.21	VA1T	34	-34	39.21	54	-14.79	-	-	294	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration