



**FCC CFR47 PART 15 SUBPART C**

**Bluetooth Low Energy**

**CERTIFICATION TEST REPORT**

**FOR**

**GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+**

**MODEL NUMBER : SM-G611M/DS. SM-G611M**

**FCC ID: A3LSMG611M**

**REPORT NUMBER: 4788312281-E2V3**

**ISSUE DATE: FEB 26, 2018**

*Prepared for*  
**SAMSUNG ELECTRONICS CO., LTD.**  
**129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,**  
**GYEONGGI-DO, 16677, KOREA**

*Prepared by*  
**UL Korea, Ltd.**  
**26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea**

**Suwon Test Site: UL Korea, Ltd. Suwon Laboratory**  
**218 Maeyeong-ro, Yeongtong-gu,**  
**Suwon-si, Gyeonggi-do, 16675, Korea**  
**TEL: (031) 337-9902**  
**FAX: (031) 213-5433**



Testing  
Laboratory

**TL-637**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	02/20/18	Initial issue	Junwhan Lee
V2	02/22/18	Updated to address TCB's question	Junwhan Lee
V3	02/26/18	Revised section 1.4	Junwhan Lee

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b> .....	<b>5</b>
1.1. INTRODUCTION OF TEST DATA REUSE.....	6
1.2. DIFFERENCE.....	6
1.3. SPOT CHECK VERIFICATION DATA.....	6
1.4. REFERENCE DETAIL.....	7
<b>2. TEST METHODOLOGY</b> .....	<b>8</b>
<b>3. FACILITIES AND ACCREDITATION</b> .....	<b>8</b>
<b>4. CALIBRATION AND UNCERTAINTY</b> .....	<b>8</b>
4.1. MEASURING INSTRUMENT CALIBRATION .....	8
4.2. SAMPLE CALCULATION.....	8
4.3. MEASUREMENT UNCERTAINTY.....	9
<b>5. EQUIPMENT UNDER TEST</b> .....	<b>10</b>
5.1. DESCRIPTION OF EUT.....	10
5.2. MAXIMUM OUTPUT POWER.....	10
5.3. DESCRIPTION OF AVAILABLE ANTENNAS.....	10
5.4. WORST-CASE CONFIGURATION AND MODE.....	10
5.5. DESCRIPTION OF TEST SETUP.....	11
<b>6. TEST AND MEASUREMENT EQUIPMENT</b> .....	<b>13</b>
<b>7. REFERENCE MEASUREMENT RESULTS</b> .....	<b>14</b>
7.1. ON TIME AND DUTY CYCLE RESULTS.....	14
7.2. 99% BANDWIDTH.....	15
<b>8. SUMMARY TABLE</b> .....	<b>17</b>
<b>9. ANTENNA PORT TEST RESULTS</b> .....	<b>18</b>
9.1. 6 dB BANDWIDTH .....	18
9.2. OUTPUT POWER.....	20
9.3. AVERAGE POWER.....	22
9.4. PSD.....	23
9.5. OUT-OF-BAND EMISSIONS.....	25
<b>10. RADIATED TEST RESULTS</b> .....	<b>29</b>
10.1. LIMITS AND PROCEDURE.....	29

---

10.2.	TRANSMITTER ABOVE 1 GHz.....	31
10.3.	WORST-CASE BELOW 1 GHz.....	41
<b>11.</b>	<b>AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>43</b>
<b>12.</b>	<b>SETUP PHOTOS.....</b>	<b>48</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SAMSUNG ELECTRONICS CO., LTD.  
**EUT DESCRIPTION:** GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+  
**MODEL NUMBER:** SM-G611M/DS, SM-G611M  
**SERIAL NUMBER:** R38K102TCNM, R38K102TCPK (RADIATED, Spot check);  
R38K102TD1Y (CONDUCTED, Spot check);  
R38K102WFSP (RADIATED, Original);  
R38K102WTZW (CONDUCTED. Original)  
**DATE TESTED:** JAN 22, 2018 - JAN 30, 2018 (Original)  
FEB 01, 2018 – FEB 09, 2018 (Spot check)


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Korea, Ltd. By:

Tested By:



SungGil Park  
Suwon Lab Engineer  
UL Korea, Ltd.

Junwhan Lee  
Suwon Lab Engineer  
UL Korea, Ltd.

### 1.1. INTRODUCTION OF TEST DATA REUSE

This report referenced from the FCC ID: A3LSMG611MT BLE(FCC CFR 47 Part 15C). And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

### 1.2. DIFFERENCE

The FCC ID: A3LSMG611M shares the same enclosure and circuit board as FCC ID: A3LSMTG611MT. The BLE circuitry and layout are identical between these two units. The BLE antennas and surrounding circuitry are the same between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMG611MT remains representative of FCC ID: A3LSMG611M. The test data of FCC ID: A3LSMG611MT being submitted for this application to cover BLE features.

Due to difference of charger, radiated emission under 1GHz and AC line conducted test were performed newly.

Also SM-G611M/DS and SM-G611M are same hardware, but for different number of SIM card slot. SM-G611M has one slot and SM-G611M/DS is dual SIM version. SM-G611M/DS used for the spot check tests.

### 1.3. SPOT CHECK VERIFICATION DATA

Band	Test Item	Frequency	Test Limit	Original model	Spot check model	Deviation	Remark
				SM-G611MT/DS Results	SM-G611M/DS Results		
				FCC ID : A3LSMG611MT	FCC ID : A3LSMG611M		
DTS BLE (2.4GHz)	Band Edge	2480 MHz	54 dBuV/m	43.66 dBuV/m	42.88 dBuV/m	-0.78 dB	
	RSE	2402 MHz	54 dBuV/m	40.77 dBuV/m	41.88 dBuV/m	1.11 dB	2nd Harmonic

Comparison of two models, higher deviation is within 3dB range and all test results are under FCC Technical Limits.

### 1.4. REFERENCE DETAIL

Reference application that contains the reused reference data.

Equipment Class	Reference FCC ID	Type Grant/Permissive Change	Reference Application	Folder Test/RF Exposure	Report Title / Section
DTS	A3LSMG611MT	Grant	4788312331-E1V3	Test	FCC Report DTS WLAN All sections (Except Section 10.3, 11)
			4788312331-E2V3	Test	FCC Report BLE All sections (Except Section 10.3, 11)
DSS	A3LSMG611MT	Grant	4788312331-E3V3	Test	FCC Report BT / All sections (Except Section 10.3, 11)
PCE	A3LSMG611MT	Grant	4788312331-E5V3	Test	FCC Report WWAN / All sections (Except Conducted Output Power)

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 DTS Meas Guidance v04.
4. KDB 484596 D01 Referencing Test Data DR01-42712
5. ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+. This test report addresses the DTS (BLE) operational mode.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	BLE	Peak	9.724	9.38
		Average	9.171	8.26

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of -2.1 dBi.

### 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Note : All radiated and power line conducted tests were performed connected with earphone and charger for evaluation of worst case mode.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50JWS	DK6J523VS-A -E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A


### I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A

### TEST SETUP

The EUT is a stand-alone unit during the tests.  
 Test software in hidden menu exercised the EUT to enable BLE mode.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-14-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-10-19
Antenna, Horn, 18 GHz	ETS	3117	00168724	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00168717	11-29-18
Antenna, Horn, 18 GHz	ETS	3117	00205959	05-31-19
Antenna, Horn, 40 GHz	ETS	3116C	00166155	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	11-13-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-11-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-08-18
Attenuator	PASTERNAK	PE7087-10	A001	08-08-18
Attenuator	PASTERNAK	PE7087-10	A008	08-08-18
Attenuator	PASTERNAK	PE7087-10	2	08-10-18
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-11-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-11-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-11-18
LISN	R&S	ENV-216	101837	08-09-18
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	


## 7. REFERENCE MEASUREMENT RESULTS

### 7.1. ON TIME AND DUTY CYCLE RESULTS

#### LIMITS

None: for reporting purposes only.

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
<b>2400MHz Bands</b>						
BLE	0.389	0.625	0.623	62.3%	2.06	2.569



## 7.2. 99% BANDWIDTH

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to  $\geq 3$  times the RBW. The spectrum analyzer internal 99% bandwidth function is utilized.

### RESULTS

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2402	1.066
Mid	2440	1.063
High	2480	1.060
Worst		1.066

**99% BANDWIDTH PLOTS**

<p>Low CH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.40200000 GHz          Trig: Free Run          #Atten: 30 dB          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 20.00 dBm</p> <p>Center 2.402 GHz Span 3 MHz          #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>6.25 dBm</td> </tr> <tr> <td><b>1.0659 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>23.105 kHz</td> <td>x dB</td> <td>-26.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td>1.229 MHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	6.25 dBm	<b>1.0659 MHz</b>			Transmit Freq Error	OBW Power	99.00 %	23.105 kHz	x dB	-26.00 dB	x dB Bandwidth	1.229 MHz	
Occupied Bandwidth	Total Power	6.25 dBm														
<b>1.0659 MHz</b>																
Transmit Freq Error	OBW Power	99.00 %														
23.105 kHz	x dB	-26.00 dB														
x dB Bandwidth	1.229 MHz															
<p>Middle CH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.44000000 GHz          Trig: Free Run          #Atten: 30 dB          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 20.00 dBm</p> <p>Center 2.44 GHz Span 3 MHz          #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>7.21 dBm</td> </tr> <tr> <td><b>1.0628 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>29.465 kHz</td> <td>x dB</td> <td>-26.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td>1.248 MHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	7.21 dBm	<b>1.0628 MHz</b>			Transmit Freq Error	OBW Power	99.00 %	29.465 kHz	x dB	-26.00 dB	x dB Bandwidth	1.248 MHz	
Occupied Bandwidth	Total Power	7.21 dBm														
<b>1.0628 MHz</b>																
Transmit Freq Error	OBW Power	99.00 %														
29.465 kHz	x dB	-26.00 dB														
x dB Bandwidth	1.248 MHz															
<p>High CH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.48000000 GHz          Trig: Free Run          #Atten: 30 dB          Radio Std: None          Radio Device: BTS</p> <p>10 dB/div Ref 20.00 dBm</p> <p>Center 2.48 GHz Span 3 MHz          #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>5.74 dBm</td> </tr> <tr> <td><b>1.0595 MHz</b></td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>31.818 kHz</td> <td>x dB</td> <td>-26.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td>1.248 MHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	5.74 dBm	<b>1.0595 MHz</b>			Transmit Freq Error	OBW Power	99.00 %	31.818 kHz	x dB	-26.00 dB	x dB Bandwidth	1.248 MHz	
Occupied Bandwidth	Total Power	5.74 dBm														
<b>1.0595 MHz</b>																
Transmit Freq Error	OBW Power	99.00 %														
31.818 kHz	x dB	-26.00 dB														
x dB Bandwidth	1.248 MHz															

## 8. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	711.9 kHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-37.722 dBm
15.247 (b)(3)	TX conducted output power	<30dBm		Pass	9.724 dBm (Peak)
15.247 (e)	PSD	<8dBm		Pass	-4.82 dBm (Peak)
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	43.29 dBuV (Pk)
15.205, 15.209	Radiated Spurious Emission	< 74dBuV/m	Radiated	Pass	64.27 dBuV/m (Pk)

## 9. ANTENNA PORT TEST RESULTS

### 9.1. 6 dB BANDWIDTH

#### LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.


#### TEST PROCEDURE

Reference to KDB 558074 D01 DTS Meas Guidance v04: The transmitter output is connected to a spectrum analyzer with the RBW set to 100kHz, the VBW  $\geq 3 \times$  RBW, peak detector and max hold.

#### RESULTS

Channel	Frequency [MHz]	6 dB Bandwidth [kHz]	Minimum Limit [kHz]
Low	2402	713.41	500.0
Mid	2440	713.51	500.0
High	2480	711.90	500.0
Worst		711.90	500.0

**6 dB BANDWIDTH PLOTS**



## 9.2. OUTPUT POWER

### LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.


### TEST PROCEDURE

Peak power is measured using KDB558074 D01 DTS Meas Guidance v04 under section 9.1.1 utilizing spectrum analyzer.

### RESULTS

Channel	Frequency [MHz]	Peak Power Reading [dBm]	Limit [dBm]	Margin [dB]
Low	2402	8.668	30.000	-21.332
Mid	2440	9.724	30.000	-20.276
High	2480	8.300	30.000	-21.700
Worst		9.724		-20.276

**OUTPUT POWER PLOTS**



### 9.3. AVERAGE POWER

#### LIMITS

None; for reporting purposes only.

#### TEST PROCEDURE

The transmitter output is connected to a power meter.

#### RESULTS

The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	8.271	6.716
Middle	2440	9.171	8.262
High	2480	7.765	5.977

## 9.4. PSD

### LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


### TEST PROCEDURE

Power Spectral Density was performed utilizing the “§10.2 Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v04

### RESULTS

Channel	Frequency [MHz]	PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2402	-5.81	8.00	-13.81
Mid	2440	-4.82	8.00	-12.82
High	2480	-6.03	8.00	-14.03

**POWER SPECTRAL DENSITY PLOTS**



## 9.5. OUT-OF-BAND EMISSIONS

### LIMITS

FCC §15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.

**RESULTS**


**BANDEDGE & SPURIOUS EMISSIONS, LOW CHANNEL**



**SPURIOUS EMISSIONS, MID CHANNEL**



**SPURIOUS EMISSIONS, HIGH CHANNEL**



## 10. RADIATED TEST RESULTS

### 10.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

## **TEST PROCEDURE**

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. (Restricted bandedge, Final detection of spurious harmonic emissions) Duty cycle factor =  $10 \log(1/x)$ . For this sample: DCF =  $10 \log(1/0.623) = 2.06 \text{dB}$  (Spectrum Analyzer round it up to 2.06dB)


Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

The spectrum from 1 GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.  
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 10.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEDGE (LOW CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA

#### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBu/m)	Det	20170531_3117_00168 717	10dB_ATT(dB)_170809	DC Corr (dB)	Corrected Reading (dBu/m)	Average Limit (dBu/m)	Margin (dB)	Peak Limit (dBu/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	43.32	PK	31.3	-25.7	0	48.92	-	-	74	-25.08	27	373	H
2	* 2.34	46.44	PK	31.2	-25.9	0	51.74	-	-	74	-22.26	27	373	H
3	* 2.39	33.59	RMS	31.3	-25.7	2.06	41.25	54	-12.75	-	-	27	373	H
4	* 2.389	33.7	RMS	31.3	-25.7	2.06	41.36	54	-12.64	-	-	27	373	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

RMS - RMS detection

**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**


**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBu/m)	Det	20170531_3117_00168 717	10dB_ATT(dB)_170809	DC Corr (dB)	Corrected Reading (dBu/m)	Average Limit (dBu/m)	Margin (dB)	Peak Limit (dBu/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.23	Pk	31.3	-25.7	0	47.83	-	-	74	-26.17	76	131	V
2	* 2.366	46.12	Pk	31.2	-25.8	0	51.52	-	-	74	-22.48	76	131	V
3	* 2.39	32.73	RMS	31.3	-25.7	2.06	40.39	54	-13.61	-	-	76	131	V
4	* 2.388	33.6	RMS	31.3	-25.7	2.06	41.26	54	-12.74	-	-	76	131	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 RMS - RMS detection

### AUTHORIZED BANDEDGE (HIGH CHANNEL)

#### HORIZONTAL PEAK AND AVERAGE PLOT



#### HORIZONTAL DATA

##### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_00168 717	10dB_ATT(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Pk Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	57.7	Pk	31.6	-25.5	0	63.8	-	-	74	-10.2	33	397	H
2	* 2.484	57.26	Pk	31.6	-25.5	0	63.36	-	-	74	-10.64	33	397	H
3	* 2.484	34.28	RMS	31.6	-25.5	2.06	42.44	54	-11.56	-	-	33	397	H
4	* 2.484	35.54	RMS	31.6	-25.5	2.06	43.7	54	-10.3	-	-	33	397	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_00168 717	10dB_ATT(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	56.36	Pk	31.6	-25.5	0	62.46	-	-	74	-11.54	117	103	V
2	* 2.484	58.17	Pk	31.6	-25.5	0	64.27	-	-	74	-9.73	117	103	V
3	* 2.484	34.28	RMS	31.6	-25.5	2.06	42.44	54	-11.56	-	-	117	103	V
4	* 2.484	35.5	RMS	31.6	-25.5	2.06	43.66	54	-10.34	-	-	117	103	V


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector


RMS - RMS detection

**HARMONICS AND SPURIOUS EMISSIONS**

**LOW CHANNEL HORIZONTAL**



**LOW CHANNEL VERTICAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**LOW CHANNEL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001687 17	3GHz_HP(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	35.94	PK	33.8	-31.7	0	38.04	-	-	74	-35.96	0-360	250	H
4	7.205	30.64	PK	35.9	-28.1	0	38.44	-	-	74	-35.56	0-360	150	H
5	9.604	27.05	PK	36.7	-23.5	0	40.25	-	-	74	-33.75	0-360	150	H
2	* 4.804	38.28	PK	33.8	-31.7	0	40.38	-	-	74	-33.62	0-360	150	V
3	7.206	29.79	PK	35.9	-28.1	0	37.59	-	-	74	-36.41	0-360	150	V
6	9.605	26.65	PK	36.7	-23.5	0	39.85	-	-	74	-34.15	0-360	251	V


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_00168717	3GHz_HP(dB)_1 70809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	43.57	PK2	33.8	-31.7	0	45.67	-	-	74	-28.33	141	367	H
* 4.804	32.62	MAv1	33.8	-31.7	2.06	36.78	54	-17.22	-	-	141	367	H
* 4.804	46.01	PK2	33.8	-31.7	0	48.11	-	-	74	-25.89	290	266	V
* 4.804	36.61	MAv1	33.8	-31.7	2.06	40.77	54	-13.23	-	-	290	266	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK2 - KDB558074 Method: Maximum Peak  
 MAv1 - KDB558074 Option 1 Maximum RMS Average

### MID CHANNEL HORIZONTAL



### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**MID CHANNEL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001687 17	3GHz_HP(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.88	35.54	PK	33.8	-31.7	0	37.64	-	-	74	-36.36	0-360	250	H
4	* 7.32	30.33	PK	35.9	-27.6	0	38.63	-	-	74	-35.37	0-360	150	H
5	9.761	27.5	PK	36.9	-24.2	0	40.2	-	-	74	-33.8	0-360	150	H
2	* 4.88	37.55	PK	33.8	-31.7	0	39.65	-	-	74	-34.35	0-360	250	V
3	* 7.32	30.65	PK	35.9	-27.6	0	38.95	-	-	74	-35.05	0-360	250	V
6	9.764	27.36	PK	36.9	-24.2	0	40.06	-	-	74	-33.94	0-360	250	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_00168717	3GHz_HP(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88	42.67	PK2	33.8	-31.7	0	44.77	-	-	74	-29.23	340	368	H
* 4.88	31.02	MAv1	33.8	-31.7	2.06	35.18	54	-18.82	-	-	340	368	H
* 4.88	45.11	PK2	33.8	-31.7	0	47.21	-	-	74	-26.79	281	189	V
* 4.88	34.65	MAv1	33.8	-31.7	2.06	38.81	54	-15.19	-	-	281	189	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

### HIGH CHANNEL HORIZONTAL



### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA

### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001687 17	3GHz_HP(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.959	33.62	PK	33.8	-31.7	0	35.72	-	-	74	-38.28	0-360	250	H
4	* 7.441	29.9	PK	35.9	-27.2	0	38.6	-	-	74	-35.4	0-360	150	H
5	9.922	26.19	PK	37.1	-22.3	0	40.99	-	-	74	-33.01	0-360	150	H
2	* 4.959	36.29	PK	33.8	-31.7	0	38.39	-	-	74	-35.61	0-360	150	V
3	* 7.439	30.11	PK	35.9	-27.2	0	38.81	-	-	74	-35.19	0-360	250	V
6	9.928	26.02	PK	37.1	-22.2	0	40.92	-	-	74	-33.08	0-360	150	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK – Peak Detector

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_00168717	3GHz_HP(dB)_170809	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96	43.1	PK2	33.8	-31.7	0	45.2	-	-	74	-28.8	56	315	H
* 4.96	32.32	MAv1	33.8	-31.6	2.06	36.58	54	-17.42	-	-	56	315	H
* 4.96	43.77	PK2	33.8	-31.7	0	45.87	-	-	74	-28.13	230	124	V
* 4.96	32.95	MAv1	33.8	-31.6	2.06	37.21	54	-16.79	-	-	230	124	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK2 - KDB558074 Method: Maximum Peak  
 MAv1 - KDB558074 Option 1 Maximum RMS Average


### 10.3. WORST-CASE BELOW 1 GHz

#### SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

#### HORIZONTAL PLOT



#### VERTICAL PLOT



**BELOW 1 GHz TABLE**

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	50.564	30.31	Pk	19.8	-29.2	20.91	40	-19.09	0-360	100	H
2	105.369	42.44	Pk	17.6	-28.3	31.74	43.52	-11.78	0-360	300	H
3	226.716	37.85	Pk	17.6	-27.5	27.95	46.02	-18.07	0-360	100	H
4	51.049	39	Pk	19.8	-29.1	29.7	40	-10.3	0-360	200	V
5	105.078	37.5	Pk	17.6	-28.4	26.7	43.52	-16.82	0-360	200	V
6	* 168.71	38.7	Pk	14.7	-27.9	25.5	43.52	-18.02	0-360	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

## 11. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

**RESULTS**

**WORST EMISSIONS**

**LINE 1 PLOT**



**LINE 1 RESULTS**

Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_wit h extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.408	27.24	Pk	9.8	.2	37.24	57.69	-20.45	-	-
2	.405	18.11	Av	9.8	.2	28.11	-	-	47.75	-19.64
3	1.035	22	Pk	9.8	.3	32.1	56	-23.9	-	-
4	1.038	7.43	Av	9.8	.3	17.53	-	-	46	-28.47
5	1.731	22.68	Pk	9.9	.3	32.88	56	-23.12	-	-
6	1.728	7.06	Av	9.9	.3	17.26	-	-	46	-28.74
7	2.418	20.73	Pk	9.8	.3	30.83	56	-25.17	-	-
8	2.421	6.08	Av	9.8	.3	16.18	-	-	46	-29.82
9	3.807	20.1	Pk	9.8	.3	30.2	56	-25.8	-	-
10	3.78	7.51	Av	9.8	.3	17.61	-	-	46	-28.39
11	21.183	32.79	Pk	10.1	.4	43.29	60	-16.71	-	-
12	21.183	15.36	Av	10.1	.4	25.86	-	-	50	-24.14

Pk - Peak detector

Av - Average detection

**LINE 2 PLOT**



## LINE 2 RESULTS

### Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.402	26.24	Pk	9.8	.2	36.24	57.81	-21.57	-	-
14	.402	17.58	Av	9.8	.2	27.58	-	-	47.81	-20.23
15	1.041	21.53	Pk	9.9	.3	31.73	56	-24.27	-	-
16	1.047	8.17	Av	9.9	.3	18.37	-	-	46	-27.63
17	1.728	19.01	Pk	9.9	.3	29.21	56	-26.79	-	-
18	1.728	7.47	Av	9.9	.3	17.67	-	-	46	-28.33
19	2.418	16.78	Pk	9.9	.3	26.98	56	-29.02	-	-
20	2.421	6.73	Av	9.9	.3	16.93	-	-	46	-29.07
21	6.858	20.63	Pk	9.8	.3	30.73	60	-29.27	-	-
22	6.864	10.21	Av	9.8	.3	20.31	-	-	50	-29.69
23	23.82	28.42	Pk	10.2	.4	39.02	60	-20.98	-	-
24	23.823	19.97	Av	10.2	.4	30.57	-	-	50	-19.43

Pk - Peak detector

Av - Average detection