



FCC CFR47 PART 15 SUBPART C

ANT+

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+

MODEL NUMBER : SM-G611M/DS. SM-G611M

FCC ID: A3LSMG611M

REPORT NUMBER: 4788312281-E4V3

ISSUE DATE: FEB 26, 2018

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Testing
Laboratory

TL-637

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	02/20/18	Initial issue	Junwhan Lee
V2	02/22/18	Updated to address TCB's question	Junwhan Lee
V3	02/26/18	Updated to address TCB's question	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	5
4.2. <i>SAMPLE CALCULATION</i>	5
4.3. <i>MEASUREMENT UNCERTAINTY</i>	5
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>MAXIMUM E-FIELD STRENGTH</i>	6
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	6
5.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	6
5.5. <i>DESCRIPTION OF TEST SETUP</i>	7
6. TEST AND MEASUREMENT EQUIPMENT	9
7. LIMITS AND RESULTS	10
7.1. <i>99% BANDWIDTH</i>	10
7.2. <i>TRANSMITTER RADIATED EMISSIONS</i>	12
7.2.1. <i>DUTY CYCLE</i>	15
7.2.2. <i>FUNDAMENTAL FIELD STRENGTH LEVEL</i>	16
7.2.3. <i>TRANSMITTER RESTRICTED BAND EDGES</i>	22
7.2.4. <i>HARMONICS AND SPURIOUS EMISSIONS</i>	26
7.2.5. <i>SPURIOUS BELOW 1 GHz</i>	32
8. AC POWER LINE CONDUCTED EMISSIONS	34
9. SETUP PHOTOS	39

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+
MODEL NUMBER: SM-G611MT/DS
SERIAL NUMBER: R38K102TCNM, R38K102TCPK (RADIATED)
R38K102TD1Y (CONDUCTED)
DATE TESTED: FEB 01, 2018 – FEB 26, 2018


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.

Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. ANSI C63.10-2013.
4. KDB 484596 D01 Referencing Test Data DR01-42712

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and ANT+. This test report addresses the ANT+ operational mode.

SM-G611M/DS and SM-G611M are same hardware, but for different number of SIM card slot. SM-G611M has one slot and SM-G611M/DS is dual SIM version. SM-G611M/DS used for the tests.

5.2. MAXIMUM E-FIELD STRENGTH

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range [MHz]	Mode	Peak E-field Strength [dBuV/m]	Avg E-field Strength [dBuV/m]	Distance [m]
2402 - 2480	ANT+	102.59	54.19	3.00

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of -2.1 dBi

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Note : All radiated and power line conducted tests were performed connected with earphone and charger for evaluation of worst case mode.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50JWS	DK6J523VS-A -E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A

TEST SETUP

The EUT is set to continuously transmit in ANT + test mode.
 Test software in hidden menu exercised the EUT to enable ANT+ mode.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-14-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-10-19
Antenna, Horn, 18 GHz	ETS	3117	00168724	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00168717	11-29-18
Antenna, Horn, 18 GHz	ETS	3117	00205959	05-31-19
Antenna, Horn, 40 GHz	ETS	3116C	00166155	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	11-13-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-11-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-08-18
Attenuator	PASTERNAK	PE7087-10	A001	08-08-18
Attenuator	PASTERNAK	PE7087-10	A008	08-08-18
Attenuator	PASTERNAK	PE7087-10	2	08-10-18
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-11-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-11-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-11-18
LISN	R&S	ENV-216	101837	08-09-18
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. LIMITS AND RESULTS

7.1. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS


Channel	Frequency [MHz]	99% Bandwidth [MHz]	20 dB Bandwidth [MHz]
Low	2402	1.012	1.035
Mid	2441	1.012	1.032
High	2480	1.013	1.034
Worst		1.013	1.035

99% BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



7.2. TRANSMITTER RADIATED EMISSIONS

TEST PROCEDURE

ANSI C63.10: 2013

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements.

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

LIMIT

FCC §15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.


RESULTS

7.2.1. DUTY CYCLE



7.2.2. FUNDAMENTAL FIELD STRENGTH LEVEL

LOW CHANNEL, HORIZONTAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.402	87.15	Pk	31.3	-18.2	100.25	323	335	H

Pk - Peak detector

** Pk Limit : 114dBuV/m
 Pk Margin : 13.75 dB


*** For marker 1, used the following method to do averaging:

DCCF=48.4

Corrected AV reading = Peak Reading – DCCF

= 100.25 – 48.4 = 51.85 dBuV/m

LOW CHANNEL, VERTICAL



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.402	88.55	Pk	31.3	-18.2	101.65	288	170	V

Pk - Peak detector

** Pk Limit : 114dBuV/m
 Pk Margin : 12.35 dB

*** For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 101.65 – 48.4 = 53.25 dBuV/m

MID CHANNEL, HORIZONTAL



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.441	89.19	Pk	31.5	-18.1	102.59	323	318	H

Pk - Peak detector

** Pk Limit : 114dBuV/m
 Pk Margin : 11.41 dB

*** For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 102.59 – 48.4 = 54.19 dBuV/m

MID CHANNEL, VERTICAL



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001687 17	10dB_ATT(dB)_170809	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.441	92.9	Pk	31.5	-25.6	98.8	47	225	V

Pk - Peak detector

** Pk Limit : 114dBuV/m
 Pk Margin : 15.2 dB

*** For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 98.8 – 48.4 = 50.4 dBuV/m

HIGH CHANNEL, HORIZONTAL



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.48	84.26	Pk	31.6	-18	97.86	62	310	H

Pk - Peak detector

** Pk Limit : 114dBu/Vm
 Pk Margin : 16.14 dB

*** For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 97.86 – 48.4 = 49.46 dBuV/m

HIGH CHANNEL, VERTICAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001687 17	10dB_ATT(dB)_170809 -25.4	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.48	90.37	Pk	31.6	-25.4	96.57	40	315	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector

** Pk Limit : 114dBuV/m
 Pk Margin : 17.43 dB

*** For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 96.57 – 48.4 = 48.17 dBuV/m

7.2.3. TRANSMITTER RESTRICTED BAND EDGES

BANDEDGE (LOW CHANNEL, HORIZONTAL)



HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	40.68	Pk	31.3	-18.2	53.78	74	-20.22	323	335	H
2	2.4	45.14	Pk	31.3	-18.2	58.24	74	-15.76	323	335	H

Pk - Peak detector

* For marker 1, used the following method to do averaging:

DCCF=48.4


Corrected AV reading = Peak Reading – DCCF
 = 53.78 – 48.4 = 5.38 dBuV/m

* For marker 2, used the following method to do averaging:

DCCF=48.4

Corrected AV reading = Peak Reading – DCCF
 = 58.24 – 48.4 = 9.84 dBuV/m

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	43.02	Pk	31.3	-18.2	56.12	74	-17.88	288	170	V
2	2.4	44.65	Pk	31.3	-18.2	57.75	74	-16.25	288	170	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector

* For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 56.12 – 48.4 = 7.72 dBuV/m

* For marker 2, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 57.75 – 48.4 = 9.35 dBuV/m

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117[00168724]	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.8	Pk	31.6	-18	55.4	74	-18.6	62	310	H
2	2.536	44.76	Pk	31.7	-18	58.46	74	-15.54	62	310	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

* For marker 1, used the following method to do averaging:

DCCF=48.4

Corrected AV reading = Peak Reading – DCCF

= 55.4 – 48.4 = 7 dBuV/m


* For marker 2, used the following method to do averaging:

DCCF=48.4

Corrected AV reading = Peak Reading – DCCF

= 58.46 – 48.4 = 10.06 dBuV/m

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_001 68717	10dB_ATT(dB)_1708 09	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	43.67	Pk	31.6	-25.5	49.77	74	-24.23	40	315	V
2	2.518	46.25	Pk	31.6	-25.3	52.55	74	-21.45	40	315	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector

* For marker 1, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 49.77 – 48.4 = 1.37 dBuV/m


* For marker 2, used the following method to do averaging:
 DCCF=48.4
 Corrected AV reading = Peak Reading – DCCF
 = 52.55 – 48.4 = 4.15 dBuV/m

7.2.4. HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_0 0168717	3GHz_HP(dB)_170 809	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	33.06	PK	33.8	-31.7	35.16	-	-	74	-38.84	0-360	150	H
4	7.206	29.89	PK	35.9	-28.1	37.69	-	-	74	-36.31	0-360	250	H
5	9.607	27.31	PK	36.7	-23.5	40.51	-	-	74	-33.49	0-360	250	H
2	* 4.803	33.63	PK	33.8	-31.6	35.83	-	-	74	-38.17	0-360	250	V
3	7.209	30.12	PK	35.9	-28.1	37.92	-	-	74	-36.08	0-360	250	V
6	9.611	27.38	PK	36.7	-23.5	40.58	-	-	74	-33.42	0-360	250	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK - Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_0 0168717	3GHz_HP(dB)_170 809	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.875	32.4	PK	33.8	-31.7	34.5	-	-	74	-39.5	0-360	250	H
4	* 7.322	30.17	PK	35.9	-27.6	38.47	-	-	74	-35.53	0-360	250	H
5	9.766	28.03	PK	36.9	-24.2	40.73	-	-	74	-33.27	0-360	150	H
2	* 4.871	33.27	PK	33.8	-31.7	35.37	-	-	74	-38.63	0-360	250	V
3	* 7.319	29.62	PK	35.9	-27.6	37.92	-	-	74	-36.08	0-360	250	V
6	9.765	28.08	PK	36.9	-24.2	40.78	-	-	74	-33.22	0-360	250	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_0 0168717	3GHz_HP(dB)_170 809	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.814	33.37	PK	33.8	-31.6	35.57	-	-	74	-38.43	0-360	150	H
4	7.204	30.07	PK	35.9	-28.1	37.87	-	-	74	-36.13	0-360	150	H
5	9.617	27.07	PK	36.7	-23.5	40.27	-	-	74	-33.73	0-360	150	H
2	* 4.813	32.95	PK	33.8	-31.6	35.15	-	-	74	-38.85	0-360	150	V
3	7.207	29.82	PK	35.9	-28.1	37.62	-	-	74	-36.38	0-360	250	V
6	9.622	26.99	PK	36.7	-23.6	40.09	-	-	74	-33.91	0-360	250	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK – Peak Detector


Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

7.2.5. SPURIOUS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	104.399	42.97	Pk	17.6	-28.4	32.17	43.52	-11.35	0-360	300	H
2	* 172.105	38.02	Pk	14.8	-27.7	25.12	43.52	-18.4	0-360	200	H
3	230.305	39.41	Pk	17.7	-27.5	29.61	46.02	-16.41	0-360	100	H
4	60.749	44.09	Pk	18.2	-29.1	33.19	40	-6.81	0-360	100	V
5	105.272	38.44	Pk	17.6	-28.3	27.74	43.52	-15.78	0-360	300	V
6	195.385	40.37	Pk	17	-27.6	29.77	43.52	-13.75	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

8. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_wit h extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.399	25.04	Pk	9.8	.2	35.04	57.87	-22.83	-	-
2	.4095	15.32	Av	9.8	.2	25.32	-	-	47.66	-22.34
3	1.137	15.74	Pk	9.8	.3	25.84	56	-30.16	-	-
4	1.134	5.56	Av	9.8	.3	15.66	-	-	46	-30.34
5	3.558	18.58	Pk	9.8	.3	28.68	56	-27.32	-	-
6	3.528	7.05	Av	9.8	.3	17.15	-	-	46	-28.85
7	6.57	19.08	Pk	9.7	.3	29.08	60	-30.92	-	-
8	6.564	6.86	Av	9.7	.3	16.86	-	-	50	-33.14
9	16.638	21.44	Pk	9.9	.4	31.74	60	-28.26	-	-
10	16.626	6.21	Av	9.9	.4	16.51	-	-	50	-33.49
11	21.249	23.02	Pk	10.1	.4	33.52	60	-26.48	-	-
12	21.231	6.89	Av	10.1	.4	17.39	-	-	50	-32.61

Pk - Peak detector

Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.408	27.49	Pk	9.8	.2	37.49	57.69	-20.2	-	-
14	.411	15.07	Av	9.8	.2	25.07	-	-	47.63	-22.56
15	.669	17.78	Pk	9.8	.2	27.78	56	-28.22	-	-
16	.669	6.05	Av	9.8	.2	16.05	-	-	46	-29.95
17	2.955	16.37	Pk	9.9	.3	26.57	56	-29.43	-	-
18	2.955	5.04	Av	9.9	.3	15.24	-	-	46	-30.76
19	7.236	18.4	Pk	9.8	.3	28.5	60	-31.5	-	-
20	7.257	7.27	Av	9.8	.3	17.37	-	-	50	-32.63
21	20.268	18.95	Pk	10.1	.4	29.45	60	-30.55	-	-
22	20.283	6.02	Av	10.1	.4	16.52	-	-	50	-33.48
23	23.226	25.57	Pk	10.2	.4	36.17	60	-23.83	-	-
24	23.214	7.24	Av	10.2	.4	17.84	-	-	50	-32.16

Pk - Peak detector
 Av - Average detection