



FCC 47 CFR PART 15 SUBPART C  
INDUSTRY CANADA RSS-210 ISSUE 8

CERTIFICATION TEST REPORT  
FOR  
GSM/WCDMA/LTE Phone + Bluetooth & DTS/UNII a/b/g/n/ac + NFC

MODEL NUMBER: SM-G710S; SM-G710L; SM-G710K

FCC ID: A3LSMG710S  
IC ID: 649E-SMG710S

REPORT NUMBER: 13U16613-2  
ISSUE DATE: December 19, 2013

*Prepared for*  
SAMSUNG ELECTRONICS CO., LTD.  
416, MAETAN 3-DONG, YEONGTONG-GU  
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

*Prepared by*  
UL VERIFICATION SERVICES INC.  
47173 BENICIA STREET  
FREMONT, CA 94538, U.S.A.  
TEL: (510) 771-1000  
FAX: (510) 661-0888

---

NVLAP®

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	12/19/13	Initial	P. Kim

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>6</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION.....</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>6</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>7</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>7</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>7</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>7</i>
5.4. <i>SOFTWARE AND FIRMWARE .....</i>	<i>7</i>
5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>8</i>
5.6. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>11</b>
<b>7. SUMMARY TABLE .....</b>	<b>12</b>
<b>8. ANTENNA PORT TEST RESULTS .....</b>	<b>13</b>
8.1. <i>20 dB AND 99% BANDWIDTH.....</i>	<i>13</i>
8.1.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>13</i>
8.1.2. <i>ENHANCED DATA RATE 8PSK MODULATION .....</i>	<i>13</i>
8.2. <i>HOPPING FREQUENCY SEPARATION .....</i>	<i>22</i>
8.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>24</i>
8.4. <i>AVERAGE TIME OF OCCUPANCY.....</i>	<i>27</i>
8.5. <i>OUTPUT POWER .....</i>	<i>31</i>
8.5.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>31</i>
8.5.2. <i>ENHANCED DATA RATE 8PSK MODULATION .....</i>	<i>31</i>
8.6. <i>AVERAGE POWER.....</i>	<i>36</i>
8.6.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>36</i>
8.6.2. <i>ENHANCED DATA RATE 8PSK MODULATION .....</i>	<i>36</i>
8.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>37</i>
8.7.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>38</i>
8.7.1. <i>ENHANCED DATA RATE 8PSK MODULATION .....</i>	<i>43</i>
<b>9. RADIATED TEST RESULTS .....</b>	<b>47</b>
9.1. <i>LIMITS AND PROCEDURE .....</i>	<i>47</i>

9.2. TRANSMITTER ABOVE 1 GHz .....	48
9.2.1. BASIC DATA RATE GFSK MODULATION.....	48
9.2.2. ENHANCED DATA RATE 8PSK MODULATION.....	62
9.3. WORST-CASE BELOW 1 GHz .....	76
<b>10. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>79</b>
<b>11. SETUP PHOTOS .....</b>	<b>83</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** Samsung  
**EUT DESCRIPTION:** GSM/WCDMA/LTE Phone + Bluetooth & DTS/UNII a/b/g/n/ac + NFC  
**MODEL:** SM-G710S; SM-G710L; SM-G710K  
**SERIAL NUMBER:** FK-366A, FK-366B, FK-366C, FK-366D  
**DATE TESTED:** December 2 - 19, 2013

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 ISSUE 8	Pass
INDUSTRY CANADA RSS-GEN ISSUE 3	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Verification Services Inc. By:



---

PHILIP KIM  
WiSE PROGRAM MANAGER  
UL Verification Services Inc.

Tested By:



---

STEVEN TRAN  
WiSE LAB TECHNICIAN  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + Bluetooth & DTS/UNII a/b/g/n/ac + NFC.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	9.05	8.04
2402 - 2480	Enhanced 8PSK	10.29	10.69

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.51dB

### 5.4. SOFTWARE AND FIRMWARE

Software version was 3.4.0-g9f6ebe1-00072-gcee1ab4b

The firmware used was M8974A-0.0.19.0.01.

## 5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

## 5.6. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	SM-G710S	E18WKTAOU	N/A
Earphone	Samsung	SM-G710S	N/A	N/A


### I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

### TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.  
EUT was set in the Hidden menu mode to enable BT communications.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	03/23/13	02/13/14
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/13	10/25/14
Antenna, Horn, 25.5 GHz	ARA	MWH-1826/B	C00980	11/14/13	11/14/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/13	01/28/14
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/13	10/22/14
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/12	12/20/13
CBT Bluetooth Tester	R & S	CBT	None	07/12/13	07/12/14
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/13	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/13	12/13/14
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/13	01/14/14
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR	CNR

## 7. SUMMARY TABLE

RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
RSS-GEN 4.6	Occupied Band width (99%)	N/A	Conducted	Pass	1.16MHz
RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-50.5dBc
RSS-210 A8.4	TX conducted output power	<21dBm		Pass	10.29dBm
RSS-210 A8.1(b)	Hopping frequency separation	> 25KHz		Pass	1MHz
RSS-210 A8.1(d)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
RSS-210 A8.1(d)	Avg Time of Occupancy	< 0.4sec		Pass	.347 s
RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	29.19dBuV
RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	45.56dBuV/m

## 8. ANTENNA PORT TEST RESULTS

### 8.1. 20 dB AND 99% BANDWIDTH

#### LIMIT

None; for reporting purposes only.

#### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq$  1% of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.

#### RESULTS



##### 8.1.1. BASIC DATA RATE GFSK MODULATION


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	922.9	965.4
Middle	2441	924.9	897.3
High	2480	924.3	903.6
Worst		924.88	965.4

##### 8.1.2. ENHANCED DATA RATE 8PSK MODULATION



Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	1.21	1.13
Middle	2441	1.21	1.16
High	2480	1.21	1.13
Worst		1.21	1.16


**GFSK 20 dB BANDWIDTH**








**GFSK 99% BANDWIDTH**








**8PSK 20 dB BANDWIDTH**





**QPSK 99% BANDWIDTH**





## 8.2. HOPPING FREQUENCY SEPARATION

### LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is coupled.

### RESULTS

## HOPPING FREQUENCY SEPARATION



### 8.3. NUMBER OF HOPPING CHANNELS

#### LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.



#### TEST PROCEDURE



DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

#### RESULTS

Normal Mode: 79 Channels observed.

## NUMBER OF HOPPING CHANNELS





## 8.4. AVERAGE TIME OF OCCUPANCY

### LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$ .

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels \* 0.4 seconds) is equal to  $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{pulse width}$ .


### RESULTS

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
<b>GFSK Normal Mode</b>					
DH1	0.38	32	0.122	0.4	-0.278
DH3	1.63	19	0.310	0.4	-0.090
DH5	2.89	12	0.347	0.4	-0.053
DH Packet	Pulse Width (msec)	Number of Pulses in 0.8 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
<b>GFSK AFH Mode</b>					
DH1	0.38	8	0.030	0.4	-0.370
DH3	1.63	5	0.082	0.4	-0.319
DH5	2.89	3	0.087	0.4	-0.313


## PULSE WIDTH - DH1




## NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1




### PULSE WIDTH – DH3




### NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



### PULSE WIDTH – DH5



### NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5



## 8.5. OUTPUT POWER

### LIMIT

§15.247 (b) (1)

RSS-210 Issue 7 Clause A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

### RESULTS



#### 8.5.1. BASIC DATA RATE GFSK MODULATION


Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	7.70	21	-13.30
Middle	2441	9.05	21	-11.95
High	2480	7.93	21	-13.07
Worst		9.05		-11.95

#### 8.5.2. ENHANCED DATA RATE 8PSK MODULATION



Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	8.96	21	-12.04
Middle	2441	10.29	21	-10.71
High	2480	9.18	21	-11.82
Worst		10.29		-10.71


**GFSK OUTPUT POWER**





## 8PSK OUTPUT POWER





## 8.6. AVERAGE POWER

### LIMIT

None; for reporting purposes only.

### TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

### RESULTS

The cable assembly insertion loss of 10.7 dB (including 10 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

#### 8.6.1. BASIC DATA RATE GFSK MODULATION

Frequency (MHz)	Average Power (dBm)
2402	7.4
2441	8.9
2480	7.4
	8.90

#### 8.6.2. ENHANCED DATA RATE 8PSK MODULATION

Frequency (MHz)	Average Power (dBm)
2402	6.0
2441	7.5
2480	6.0
	7.50

## 8.7. CONDUCTED SPURIOUS EMISSIONS

### LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.



### RESULTS

### 8.7.1. BASIC DATA RATE GFSK MODULATION



#### SPURIOUS EMISSIONS, LOW CHANNEL




**SPURIOUS EMISSIONS, MID CHANNEL**




**SPURIOUS EMISSIONS, HIGH CHANNEL**




**SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON**








### 8.7.1. ENHANCED DATA RATE 8PSK MODULATION

#### SPURIOUS EMISSIONS, LOW CHANNEL







**SPURIOUS EMISSIONS, MID CHANNEL**



**SPURIOUS EMISSIONS, HIGH CHANNEL**



## 9. RADIATED TEST RESULTS

### 9.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and reduce VBW to 1/T for average measurement. For this sample:  $1/T = 2.7\text{KHz}$


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 9.2. TRANSMITTER ABOVE 1 GHz


### 9.2.1. BASIC DATA RATE GFSK MODULATION


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**







**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**






**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**






## HARMONICS AND SPURIOUS EMISSIONS

### LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/C bl/10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.448	42.77	PK	29	-24.1	47.67	53.97	-6.3	74	-26.33	0-360	201	V
4	1.448	36.06	Avg	29	-24.1	40.96	53.97	-13.01	74	-33.04	0-360	200	V
2	1.684	42.89	PK	28.8	-23.7	47.99	53.97	-5.98	74	-26.01	0-360	201	V
3	1.7	37.13	Avg	29	-23.8	42.33	53.97	-11.64	74	-31.67	0-360	101	V

PK - Peak detector


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb l/3GHz HPF	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	5.137	39.44	PK	34.2	-27.4	46.24	53.97	-7.73	74	-27.76	0-360	200	V

MID CHANNEL  
HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.291	43.23	PK	30	-24.9	48.33	53.97	-5.64	74	-25.67	0-360	200	V
2	1.703	42.41	PK	29	-23.8	47.61	53.97	-6.36	74	-26.39	0-360	101	V

PK - Peak detector


Marker	Frequen cy (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/3GHz HPF	Correct ed Reading (dBuV/ m)	Avg Limit (dBuV/ m)	Margin (dB)	Peak Limit (dBuV/ m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	5.699	38.52	PK	34.8	-26.7	46.62	53.97	-7.35	74	-27.38	0-360	200	V
4	6.58	37.99	PK	35.8	-26.9	46.89	53.97	-7.08	74	-27.11	0-360	101	V
5	8.351	36.81	PK	36	-24.6	48.21	53.97	-5.76	74	-25.79	0-360	200	V

HIGH CHANNEL  
HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.449	42.18	PK	29	-24.1	47.08	53.97	-6.89	74	-26.92	0-360	200	V
3	1.449	36.96	Avg	29	-24.1	41.86	53.97	-12.11	74	-32.14	0-360	201	V
2	1.698	42.89	PK	28.9	-23.7	48.09	53.97	-5.88	74	-25.91	0-360	101	V
4	1.701	36.31	Avg	29	-23.8	41.51	53.97	-12.46	74	-32.49	0-360	101	V


PK - Peak detector

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.449	42.18	PK	29	-24.1	47.08	53.97	-6.89	74	-26.92	0-360	200	V
3	1.449	36.96	Avg	29	-24.1	41.86	53.97	-12.11	74	-32.14	0-360	201	V
2	1.698	42.89	PK	28.9	-23.7	48.09	53.97	-5.88	74	-25.91	0-360	101	V
4	1.701	36.31	Avg	29	-23.8	41.51	53.97	-12.46	74	-32.49	0-360	101	V


### 9.2.2. ENHANCED DATA RATE 8PSK MODULATION


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







### **RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**







**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**






**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**






## HARMONICS AND SPURIOUS EMISSIONS

### LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb/I 10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	1.449	36.72	Avg	29	-24.1	41.62	53.97	-12.35	74	-32.38	0-360	201	V
1	1.513	43.07	PK	28.7	-24.3	47.47	53.97	-6.5	74	-26.53	0-360	199	H
2	1.665	41.62	PK	28.6	-23.6	46.62	53.97	-7.35	74	-27.38	0-360	199	H
4	1.67	36.07	Avg	28.7	-23.6	41.17	53.97	-12.8	74	-32.83	0-360	101	V

PK - Peak detector


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb/I 3GHz HPF	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	3.765	40.89	PK	33.6	-29	45.49	53.97	-8.48	74	-28.51	0-360	201	V

MID CHANNEL  
HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cbl/ 10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.672	43.12	PK	28.7	-23.6	48.22	53.97	-5.75	74	-25.78	0-360	101	V
2	1.701	36.91	Avg	29	-23.8	42.11	53.97	-11.86	74	-31.89	0-360	100	V

PK - Peak detector


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/3GHz HPF	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	4.762	39.86	PK	34.1	-28.2	45.76	53.97	-8.21	74	-28.24	0-360	101	V
4	5.356	39.11	PK	34.6	-28.3	45.41	53.97	-8.56	74	-28.59	0-360	201	V
5	6.873	38.23	PK	35.7	-26.9	47.03	53.97	-6.94	74	-26.97	0-360	101	V

HIGH CHANNEL  
HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb/10dB Pad	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.41	42.88	PK	29.2	-24.1	47.98	53.97	-5.99	74	-26.02	0-360	200	V
3	1.449	36.26	Avg	29	-24.1	41.16	53.97	-12.81	74	-32.84	0-360	200	V
2	1.501	42.83	PK	28.7	-24.3	47.23	53.97	-6.74	74	-26.77	0-360	200	V
4	1.838	36.18	Avg	30.5	-23.1	43.58	53.97	-10.39	74	-30.42	0-360	200	V


PK - Peak detector

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T120 (dB/m)	Amp/Cb I/3GHz HPF	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	4.415	40.28	PK	33.7	-28.8	45.18	53.97	-8.79	74	-28.82	0-360	200	V
6	6.86	38.35	PK	35.7	-26.8	47.25	53.97	-6.72	74	-26.75	0-360	200	V

### 9.3. WORST-CASE BELOW 1 GHz

#### GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)





DATA

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T122 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	33.91	28.04	PK	18.5	-32.1	14.44	40	-25.56	0-360	400	H
6	37.6075	34.56	PK	15.7	-32	18.26	40	-21.74	0-360	100	V
7	172.035	40.51	PK	11.7	-31.3	20.91	43.52	-22.61	0-360	100	V
2	180.025	41.83	PK	11.2	-31.2	21.83	43.52	-21.69	0-360	200	H
3	191.33	39.72	PK	11.4	-31.2	19.92	43.52	-23.6	0-360	200	H
8	602.3	36.94	PK	18.7	-30.3	25.34	46.02	-20.68	0-360	100	V
4	602.4	36.34	PK	18.7	-30.3	24.74	46.02	-21.28	0-360	200	H
5	668	35.93	PK	19.8	-30	25.73	46.02	-20.29	0-360	300	H
9	680.3	37.72	PK	19.9	-30	27.62	46.02	-18.4	0-360	100	V

PK - Peak detector

## 10. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS


**6 WORST EMISSIONS****Line-L1 .15 - 30MHz****Trace Markers**

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin to Limit (dB)	CISPR 11/22 Class B Average	Margin to Limit (dB)
1	.33	28.08	PK	.1	0	28.18	59.5	-31.32	-	-
2	.33	8.56	Av	.1	0	8.66	-	-	49.5	-40.84
3	1.6575	22.26	PK	.1	.1	22.46	56	-33.54	-	-
4	1.6575	9.66	Av	.1	.1	9.86	-	-	46	-36.14
5	3.2595	21.76	PK	.1	.1	21.96	56	-34.04	-	-
6	3.2595	7.84	Av	.1	.1	8.04	-	-	46	-37.96
7	11.5485	44.84	PK	.2	.2	45.24	60	-14.76	-	-
8	11.5485	28.79	Av	.2	.2	29.19	-	-	50	-20.81
9	17.583	33.6	PK	.2	.2	34	60	-26	-	-
10	17.583	14.45	Av	.2	.2	14.85	-	-	50	-35.15

**Line-L2 .15 - 30MHz****Trace Markers**

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin to Limit (dB)	CISPR 11/22 Class B Average	Margin to Limit (dB)
11	1.626	42.6	PK	.1	.1	42.8	56	-13.2	-	-
12	1.626	.6	Av	.1	.1	.8	-	-	46	-45.2
13	1.923	26.4	PK	.1	.1	26.6	56	-29.4	-	-
14	1.923	-1.75	Av	.1	.1	-1.55	-	-	46	-47.55
15	15.6345	37.96	PK	.2	.2	38.36	60	-21.64	-	-
16	15.6345	12.64	Av	.2	.2	13.04	-	-	50	-36.96
17	17.1915	30.46	PK	.2	.2	30.86	60	-29.14	-	-
18	17.1915	9.86	Av	.2	.2	10.26	-	-	50	-39.74
20	18.276	32.9	PK	.2	.2	33.3	60	-26.7	-	-
21	19.473	48	PK	.3	.2	48.5	60	-11.5	-	-
22	19.473	14.44	Av	.3	.2	14.94	-	-	50	-35.06
19	19.878	23.41	PK	.3	.2	23.91	60	-36.09	-	-

## LINE 1 RESULTS



**LINE 2 RESULTS**

