

# FCC/IC LTE REPORT

## Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Date of Issue:**  
January 13, 2020

**Address:**  
129, Samsung-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Location:**  
HCT CO., LTD.,  
74, Seoicheon-ro 578beon-gil, Majang-myeon,  
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA  
**Report No.:** HCT-RF-2001-FI013

<b>FCC ID:</b>	<b>A3LSMG715U</b>
<b>IC:</b>	<b>649E-SMG715W</b>
<b>APPLICANT:</b>	<b>SAMSUNG Electronics Co., Ltd.</b>

Model(s): SM-G715U1  
 Additional Model(s): SM-G715W  
 EUT Type: Mobile Phone  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 FCC Rule Part(s): §27, §2  
 IC Rule(s): RSS-Gen Issue5, RSS-130 Issue2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band12 (1.4)	699.7 – 715.3	1M10G7D	QPSK	0.095	19.80
		1M10W7D	16QAM	0.072	18.54
		1M09W7D	64QAM	0.056	17.49
LTE – Band12 (3)	700.5 – 714.5	2M71G7D	QPSK	0.093	19.68
		2M72W7D	16QAM	0.074	18.69
		2M71W7D	64QAM	0.058	17.63
LTE – Band12 (5)	701.5 – 713.5	4M51G7D	QPSK	0.094	19.72
		4M52W7D	16QAM	0.073	18.62
		4M54W7D	64QAM	0.057	17.59
LTE – Band12 (10)	704.0 – 711.0	9M02G7D	QPSK	0.092	19.63
		8M99W7D	16QAM	0.069	18.38
		9M00W7D	64QAM	0.056	17.49

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



**Report prepared by : Jae Ryang Do**  
**Engineer of Telecommunication Testing Center**



**Report approved by : Kwon Jeong**  
**Manager of Telecommunication Testing Center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2001-FI013	January 13, 2020	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This laboratory is not accredited for the test results marked \*.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.(HCT Accreditation No.: KT197)

## Table of Contents

1. GENERAL INFORMATION .....	4
2. INTRODUCTION .....	5
2.1. DESCRIPTION OF EUT.....	5
2.2. MEASURING INSTRUMENT CALIBRATION .....	5
2.3. TEST FACILITY .....	5
3. DESCRIPTION OF TESTS.....	6
3.1 TEST PROCEDURE .....	6
3.2 RADIATED POWER.....	7
3.3 RADIATED SPURIOUS EMISSIONS .....	8
3.4 OCCUPIED BANDWIDTH. ....	9
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL .....	10
3.6 BAND EDGE .....	11
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	12
3.8 WORST CASE(RADIATED TEST) .....	13
3.9 WORST CASE(CONDUCTED TEST) .....	14
3.10 RECEIVER SPURIOUS EMISSIONS .....	15
4. LIST OF TEST EQUIPMENT .....	17
5. MEASUREMENT UNCERTAINTY .....	18
6. SUMMARY OF TEST RESULTS .....	19
7. SAMPLE CALCULATION.....	20
8. TEST DATA .....	22
8.1 EFFECTIVE RADIATED POWER.....	22
8.3 RADIATED SPURIOUS EMISSIONS .....	24
8.3 OCCUPIED BANDWIDTH .....	28
8.4 CONDUCTED SPURIOUS EMISSIONS .....	29
8.5 BAND EDGE .....	29
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	30
8.7 RECEIVER SPURIOUS EMISSIONS .....	42
8.7.1 LTE B12 .....	42
8.7.2 LTE B29 .....	42
9. TEST PLOTS.....	43
10. ANNEX A_ TEST SETUP PHOTO.....	94

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMG715U
<b>IC</b>	649E-SMG715W
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	§27, §2
<b>IC Rule(s):</b>	RSS-Gen Issue5, RSS-130 Issue2
<b>EUT Type:</b>	Mobile Phone
<b>Model(s):</b>	SM-G715U1
<b>Additional Model(s):</b>	SM-G715W
<b>Tx Frequency: (LTE B12)</b>	699.7 MHz – 715.3 MHz (LTE – Band 12 (1.4 MHz)) 700.5 MHz – 714.5 MHz (LTE – Band 12 (3 MHz)) 701.5 MHz – 713.5 MHz (LTE – Band 12(5 MHz)) 704.0 MHz – 711.0 MHz (LTE – Band 12(10 MHz))
<b>Rx Frequency: (LTE B29)</b>	718.5 MHz – 726.5 MHz (LTE – Band 12 (3 MHz)) 719.5 MHz – 725.5 MHz (LTE – Band 12(5 MHz)) 722.0 MHz – 723.0 MHz (LTE – Band 12(10 MHz))
<b>Date(s) of Tests:</b>	December 17, 2019 ~ January 08, 2020

**Note:**

1. LTE B29: RX Only

## **2. INTRODUCTION**

### **2.1. DESCRIPTION OF EUT**

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), Bluetooth, BT LE, NFC, ANT+.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where:  $P_g$  is the generator output power into the substitution antenna.

If the fundamatal frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

### 3.4 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Settings

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 \* Span / RBW

### 3.6 BAND EDGE



**Test setup**

#### **Test Overview**

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### **Test Settings**

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


#### **Test Notes**

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

### 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

#### Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

**3.8 WORST CASE(RADIATED TEST)**

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
  - All modes of operation were investigated and the worst case configuration results are reported.
  - SM-G715U1 & additional models were tested and the worst case results are reported.
- (Worst case : SM-G715U1)

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK,	1	0	Z
	16QAM,			
	64QAM			
Radiated Spurious and Harmonic Emissions	QPSK	1	0	X

**3.9 WORST CASE(CONDUCTED TEST)**

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- SM-G715U1 & additional models were tested and the worst case results are reported.

(Worst case : SM-G715U1)

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	1.4, 3, 5, 10	Mid	Full RB	0
Band Edge	* QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
1.4, 3, 5, 10	Low, High	Full RB	0		
	Spurious and Harmonic Emissions at Antenna Terminal	* QPSK	1.4, 3, 5, 10	Low, Mid, High	1

### 3.10 RECEIVER SPURIOUS EMISSIONS

#### Test Procedure of Receiver Spurious Emissions (Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 30 MHz – 1 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 100 kHz
    - VBW  $\geq$  3 x RBW
  - (2) Measurement Type(Quasi-peak):
    - Measured Frequency Range : 30 MHz – 1 GHz
    - Detector = Quasi-Peak
    - RBW = 120 kHz
6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

## **Above 1 GHz**

### **Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).
  - ◆ Distance extrapolation factor =  $20 \log(\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \times$  RBW
  - (2) Measurement Type(Average):
    - We performed using a reduced video BW method was done with the analyzer in linear mode
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds

The actual setting value of VBW = 1 kHz
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

#### 4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
WAINWRIGHT INSTRUMENT	WHNX6.0/26.5G-6SS/H.P.F	1	03/20/2019	Annual	03/20/2020
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/03/2019	Annual	05/03/2020
Agilent	E3632A/DC Power Supply	MY40004326	07/01/2019	Annual	07/01/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000717	08/14/2019	Annual	08/14/2020
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	01/28/2019	Biennial	01/28/2021
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	05/08/2019	Annual	05/08/2020
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2019	Annual	06/04/2020
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2019	Annual	10/14/2020
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/27/2019	Annual	08/27/2020
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/09/2019	Annual	08/09/2020
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/15/2019	Annual	07/15/2020
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	05/17/2019	Annual	05/17/2020
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	IC Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	RSS Gen(6.7)	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(g)	RSS 130(4.7)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	-	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §27.54	RSS 130(4.5)	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	IC Section(s)	Test Limit	Test Result
Effective Radiated Power	§27.50(c)(10)	RSS 130(4.6)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(g)	RSS 130(4.7)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS
Receiver Spurious Emissions	N/A	RSS Gen(7)	Section 8.7	PASS

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW  
GSM BW = 249 kHz  
G = Phase Modulation  
X = Cases not otherwise covered  
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W  
GSM BW = 249 kHz  
G = Phase Modulation  
7 = Quantized/Digital Info  
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W  
WCDMA BW = 4.17 MHz  
F = Frequency Modulation  
9 = Composite Digital Info  
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D  
LTE BW = 4.48 MHz  
G = Phase Modulation  
7 = Quantized/Digital Info  
D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D  
LTE BW = 4.48 MHz  
W = Amplitude/Angle Modulated  
7 = Quantized/Digital Info  
D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D  
LTE BW = 4.48 MHz  
W = Amplitude/Angle Modulated  
7 = Quantized/Digital Info  
D = Data transmission; telemetry; telecommand

## 8. TEST DATA

### 8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
699.7	LTE B12 (1.4 MHz)	QPSK	-30.63	30.13	-9.92	1.18	H	< 3.00	0.080	19.03
		16-QAM	-31.75	29.01	-9.92	1.18	H		0.062	17.91
		64-QAM	-32.83	27.93	-9.92	1.18	H		0.048	16.83
707.5		QPSK	-30.06	30.71	-9.93	1.18	H		0.091	19.60
		16-QAM	-31.12	29.65	-9.93	1.18	H		0.072	18.54
		64-QAM	-32.23	28.54	-9.93	1.18	H		0.055	17.43
715.3		QPSK	-29.57	30.93	-9.94	1.19	H		0.095	19.80
		16-QAM	-30.85	29.65	-9.94	1.19	H		0.071	18.52
		64-QAM	-31.88	28.62	-9.94	1.19	H		0.056	17.49

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
700.5	LTE B12 (3 MHz)	QPSK	-30.68	30.10	-9.92	1.18	H	< 3.00	0.079	19.00
		16-QAM	-31.74	29.04	-9.92	1.18	H		0.062	17.94
		64-QAM	-32.80	27.98	-9.92	1.18	H		0.049	16.88
707.5		QPSK	-30.13	30.64	-9.93	1.18	H		0.090	19.53
		16-QAM	-31.24	29.53	-9.93	1.18	H		0.070	18.42
		64-QAM	-32.13	28.64	-9.93	1.18	H		0.057	17.53
714.5		QPSK	-29.71	30.81	-9.94	1.19	H		0.093	19.68
		16-QAM	-30.70	29.82	-9.94	1.19	H		0.074	18.69
		64-QAM	-31.76	28.76	-9.94	1.19	H		0.058	17.63

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W
701.5	LTE B12 (5 MHz)	QPSK	-30.62	30.18	-9.92	1.18	H	< 3.00	0.081	19.08
		16-QAM	-31.71	29.09	-9.92	1.18	H		0.063	17.99
		64-QAM	-32.62	28.18	-9.92	1.18	H		0.051	17.08
707.5		QPSK	-30.04	30.73	-9.93	1.18	H		0.092	19.62
		16-QAM	-31.24	29.53	-9.93	1.18	H		0.070	18.42
		64-QAM	-32.23	28.54	-9.93	1.18	H		0.055	17.43
713.5		QPSK	-29.73	30.84	-9.94	1.18	H		0.094	19.72
		16-QAM	-30.83	29.74	-9.94	1.18	H		0.073	18.62
		64-QAM	-31.86	28.71	-9.94	1.18	H		0.057	17.59

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W
704.0	LTE B12 (10 MHz)	QPSK	-30.56	30.28	-9.92	1.18	H	< 3.00	0.083	19.18
		16-QAM	-31.78	29.06	-9.92	1.18	H		0.063	17.96
		64-QAM	-32.71	28.13	-9.92	1.18	H		0.050	17.03
707.5		QPSK	-30.18	30.59	-9.93	1.18	H		0.089	19.48
		16-QAM	-31.46	29.31	-9.93	1.18	H		0.066	18.20
		64-QAM	-32.32	28.45	-9.93	1.18	H		0.054	17.34
711.0		QPSK	-29.94	30.75	-9.94	1.18	H		0.092	19.63
		16-QAM	-31.19	29.50	-9.94	1.18	H		0.069	18.38
		64-QAM	-32.08	28.61	-9.94	1.18	H		0.056	17.49

### 8.3 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY: 715.3 MHz
- ▣ MEASURED OUTPUT POWER: 21.95 dBm = 0.157 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 1.4 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT:  $43 + 10 \log_{10}(W) =$  34.95 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23017 (699.7)	1,399.40	-42.83	7.60	-51.92	1.70	H	-46.02	67.96
	2,099.10	-53.25	9.80	-57.67	2.10	V	-49.97	71.92
	2,798.80	-55.92	10.90	-58.59	2.45	H	-50.14	72.09
23095 (707.5)	1,415.00	-48.59	7.72	-57.76	1.71	V	-51.75	73.69
	2,122.50	-54.67	9.55	-58.81	2.11	V	-51.37	73.31
	2,830.00	-55.98	10.95	-58.06	2.47	V	-49.58	71.52
23173 (715.3)	1,430.60	-45.33	7.75	-54.67	1.70	H	-48.62	70.57
	2,145.90	-53.21	9.37	-57.08	2.12	V	-49.83	71.78
	2,861.20	-55.01	11.03	-57.13	2.47	H	-48.57	70.52

- ▣ OPERATING FREQUENCY: 714.5 MHz
- ▣ MEASURED OUTPUT POWER: 21.83 dBm = 0.152 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 3 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT:  $43 + 10 \log_{10}(W) =$  34.83 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23025 (700.5)	1,401.00	-42.85	7.60	-51.94	1.70	H	-46.04	67.87
	2,101.50	-53.45	9.80	-57.87	2.10	H	-50.17	72.01
	2,802.00	-56.24	10.90	-58.91	2.45	V	-50.46	72.30
	3,502.50	-54.07	12.30	-55.03	2.75	H	-45.48	67.32
23095 (707.5)	1,415.00	-48.93	7.72	-58.10	1.71	V	-52.09	73.92
	2,122.50	-52.04	9.55	-56.18	2.11	H	-48.74	70.57
	2,830.00	-56.56	10.95	-58.64	2.47	V	-50.16	71.99
23165 (714.5)	1,429.00	-47.89	7.75	-57.23	1.70	V	-51.18	73.01
	2,143.50	-53.55	9.37	-57.42	2.12	H	-50.17	72.00
	2,858.00	-55.35	11.03	-57.47	2.47	H	-48.91	70.75

- ▣ OPERATING FREQUENCY: 713.5 MHz
- ▣ MEASURED OUTPUT POWER: 21.87 dBm = 0.154 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT:  $43 + 10 \log_{10}(W) =$  34.87 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23035 (701.5)	1,403.00	-42.31	7.60	-51.40	1.70	H	-45.50	67.37
	2,104.50	-53.29	9.74	-57.87	2.10	H	-50.23	72.10
	2,806.00	-56.89	10.92	-59.25	2.46	H	-50.79	72.66
23095 (707.5)	1,415.00	-46.04	7.72	-55.21	1.71	V	-49.20	71.07
	2,122.50	-54.22	9.55	-58.36	2.11	V	-50.92	72.79
	2,830.00	-56.53	10.95	-58.61	2.47	V	-50.13	72.00
23155 (713.5)	1,427.00	-50.63	7.75	-59.97	1.70	H	-53.92	75.79
	2,140.50	-51.83	9.43	-55.82	2.11	V	-48.50	70.38
	2,854.00	-56.13	11.02	-58.36	2.47	V	-49.81	71.68

- ▣ OPERATING FREQUENCY: 711.0 MHz
- ▣ MEASURED OUTPUT POWER: 21.78 dBm = 0.151 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT:  $43 + 10 \log_{10}(W) =$  34.78 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23060 (704.0)	1,408.00	-43.72	7.68	-53.18	1.70	H	-47.20	68.98
	2,112.00	-53.09	9.68	-57.83	2.10	V	-50.25	72.03
	2,816.00	-56.68	10.94	-58.88	2.47	H	-50.41	72.19
23095 (707.5)	1,415.00	-45.79	7.72	-54.96	1.71	H	-48.95	70.73
	2,122.50	-53.54	9.55	-57.68	2.11	V	-50.24	72.02
	2,830.00	-56.56	10.95	-58.64	2.47	H	-50.16	71.94
23130 (711.0)	1,422.00	-48.21	7.75	-57.08	1.71	V	-51.04	72.82
	2,133.00	-53.45	9.55	-57.69	2.11	H	-50.25	72.04
	2,844.00	-55.91	10.99	-58.14	2.46	H	-49.61	71.39

**8.3 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )
12	1.4 MHz	707.5	QPSK	6	0	1.0987
			16-QAM			1.1018
			64-QAM			1.0909
	3 MHz		QPSK	15		2.7140
			16-QAM			2.7152
			64-QAM			2.7142
	5 MHz		QPSK	25		4.5131
			16-QAM			4.5213
			64-QAM			4.5366
	10 MHz	QPSK	50	9.0199		
		16-QAM		8.9894		
		64-QAM		9.0006		

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 44 ~ 55.

**8.4 CONDUCTED SPURIOUS EMISSIONS**

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
12	1.4	699.7	3.6870	27.976	-67.214	-39.238	-13.00
		707.5	3.1865	27.976	-67.240	-39.264	
		715.3	3.7324	27.976	-67.408	-39.432	
	3	700.5	3.6885	27.976	-67.251	-39.275	
		707.5	3.6790	27.976	-67.251	-39.275	
		714.5	3.7044	27.976	-66.961	-38.985	
	5	701.5	3.7294	27.976	-67.304	-39.328	
		707.5	3.7129	27.976	-67.172	-39.196	
		713.5	3.7344	27.976	-67.331	-39.355	
	10	704.0	3.7179	27.976	-66.814	-38.838	
		707.5	3.6935	27.976	-67.046	-39.070	
		711.0	3.7024	27.976	-67.084	-39.108	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 82 ~ 93.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


**8.5 BAND EDGE**

- Plots of the EUT's Band Edge are shown Page 56 ~ 81.

**8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**


- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 699,700,000 Hz
- ▣ CHANNEL: 23017 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	699 699 998	0.0	0.000 000	0.000
100%		-30	699 700 001	2.9	0.000 000	0.004
100%		-20	699 700 001	2.8	0.000 000	0.004
100%		-10	699 700 001	2.7	0.000 000	0.004
100%		0	699 700 000	1.9	0.000 000	0.003
100%		+10	699 700 000	2.6	0.000 000	0.004
100%		+30	699 700 001	3.2	0.000 000	0.005
100%		+40	699 700 000	2.5	0.000 000	0.004
100%		+50	699 700 001	3.3	0.000 000	0.005
Batt. Endpoint	3.600	+20	699 699 995	-3.1	0.000 000	-0.004




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 700,500,000 Hz
- ▣ CHANNEL: 23025 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	700 499 998	0.0	0.000 000	0.000
100%		-30	700 499 996	-1.7	0.000 000	-0.002
100%		-20	700 499 996	-1.8	0.000 000	-0.003
100%		-10	700 499 994	-3.5	0.000 000	-0.005
100%		0	700 499 996	-2.2	0.000 000	-0.003
100%		+10	700 500 000	2.3	0.000 000	0.003
100%		+30	700 500 000	2.2	0.000 000	0.003
100%		+40	700 499 997	-1.2	0.000 000	-0.002
100%		+50	700 499 995	-2.9	0.000 000	-0.004
Batt. Endpoint	3.600	+20	700 499 995	-3.0	0.000 000	-0.004




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 701,500,000 Hz
- ▣ CHANNEL: 23035 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	701 500 003	0.0	0.000 000	0.000
100%		-30	701 500 001	-2.5	0.000 000	-0.004
100%		-20	701 500 001	-2.2	0.000 000	-0.003
100%		-10	701 500 005	2.3	0.000 000	0.003
100%		0	701 500 005	1.9	0.000 000	0.003
100%		+10	701 500 006	2.9	0.000 000	0.004
100%		+30	701 500 005	2.2	0.000 000	0.003
100%		+40	701 500 005	2.2	0.000 000	0.003
100%		+50	701 500 005	1.9	0.000 000	0.003
Batt. Endpoint	3.600	+20	701 500 007	4.3	0.000 001	0.006




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 704,000,000 Hz
- ▣ CHANNEL: 23060 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	704 000 004	0.0	0.000 000	0.000
100%		-30	704 000 007	3.3	0.000 000	0.005
100%		-20	704 000 006	1.9	0.000 000	0.003
100%		-10	704 000 001	-3.1	0.000 000	-0.004
100%		0	704 000 007	2.9	0.000 000	0.004
100%		+10	704 000 006	2.8	0.000 000	0.004
100%		+30	704 000 006	2.2	0.000 000	0.003
100%		+40	704 000 001	-3.1	0.000 000	-0.004
100%		+50	704 000 007	3.8	0.000 001	0.005
Batt. Endpoint	3.600	+20	704 000 007	3.0	0.000 000	0.004




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 996	0.0	0.000 000	0.000
100%		-30	707 499 999	3.1	0.000 000	0.004
100%		-20	707 500 000	4.5	0.000 001	0.006
100%		-10	707 499 998	1.9	0.000 000	0.003
100%		0	707 499 991	-4.3	-0.000 001	-0.006
100%		+10	707 499 992	-3.9	-0.000 001	-0.006
100%		+30	707 499 992	-4.0	-0.000 001	-0.006
100%		+40	707 499 992	-4.1	-0.000 001	-0.006
100%		+50	707 499 997	1.8	0.000 000	0.003
Batt. Endpoint	3.600	+20	707 499 992	-3.5	0.000 000	-0.005




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 995	0.0	0.000 000	0.000
100%		-30	707 499 992	-2.6	0.000 000	-0.004
100%		-20	707 499 993	-1.7	0.000 000	-0.002
100%		-10	707 499 991	-4.1	-0.000 001	-0.006
100%		0	707 499 993	-2.4	0.000 000	-0.003
100%		+10	707 499 990	-4.7	-0.000 001	-0.007
100%		+30	707 499 997	2.2	0.000 000	0.003
100%		+40	707 499 998	2.7	0.000 000	0.004
100%		+50	707 499 991	-4.4	-0.000 001	-0.006
Batt. Endpoint	3.600	+20	707 499 991	-4.0	-0.000 001	-0.006




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 500 004	0.0	0.000 000	0.000
100%		-30	707 500 009	4.6	0.000 001	0.007
100%		-20	707 500 006	2.1	0.000 000	0.003
100%		-10	707 500 001	-3.4	0.000 000	-0.005
100%		0	707 500 007	2.6	0.000 000	0.004
100%		+10	707 500 006	1.9	0.000 000	0.003
100%		+30	707 500 009	4.6	0.000 001	0.007
100%		+40	707 500 009	4.4	0.000 001	0.006
100%		+50	707 500 006	1.8	0.000 000	0.003
Batt. Endpoint	3.600	+20	707 500 007	2.6	0.000 000	0.004




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 500 003	0.0	0.000 000	0.000
100%		-30	707 500 007	3.6	0.000 001	0.005
100%		-20	707 500 008	4.2	0.000 001	0.006
100%		-10	707 500 007	3.5	0.000 000	0.005
100%		0	707 500 006	3.0	0.000 000	0.004
100%		+10	707 500 007	3.5	0.000 000	0.005
100%		+30	707 500 007	3.5	0.000 000	0.005
100%		+40	707 500 007	3.9	0.000 001	0.006
100%		+50	707 500 006	2.8	0.000 000	0.004
Batt. Endpoint	3.600	+20	707 500 000	-3.1	0.000 000	-0.004




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 715,300,000 Hz
- ▣ CHANNEL: 23173 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	715 299 996	0.0	0.000 000	0.000
100%		-30	715 299 992	-3.5	0.000 000	-0.005
100%		-20	715 299 993	-2.3	0.000 000	-0.003
100%		-10	715 299 991	-4.4	-0.000 001	-0.006
100%		0	715 299 990	-5.5	-0.000 001	-0.008
100%		+10	715 299 991	-4.5	-0.000 001	-0.006
100%		+30	715 299 991	-4.6	-0.000 001	-0.006
100%		+40	715 299 998	2.6	0.000 000	0.004
100%		+50	715 299 991	-4.6	-0.000 001	-0.006
Batt. Endpoint	3.600	+20	715 299 991	-4.1	-0.000 001	-0.006




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 714,500,000 Hz
- ▣ CHANNEL: 23165 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	714 499 994	0.0	0.000 000	0.000
100%		-30	714 499 989	-5.8	-0.000 001	-0.008
100%		-20	714 500 000	5.2	0.000 001	0.007
100%		-10	714 499 998	3.3	0.000 000	0.005
100%		0	714 500 000	5.3	0.000 001	0.007
100%		+10	714 499 986	-8.1	-0.000 001	-0.011
100%		+30	714 499 989	-5.3	-0.000 001	-0.007
100%		+40	714 499 987	-7.2	-0.000 001	-0.010
100%		+50	714 499 999	4.2	0.000 001	0.006
Batt. Endpoint	3.600	+20	714 500 000	5.2	0.000 001	0.007




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 713,500,000 Hz
- ▣ CHANNEL: 23155 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	713 500 004	0.0	0.000 000	0.000
100%		-30	713 500 000	-3.1	0.000 000	-0.004
100%		-20	713 500 007	3.8	0.000 001	0.005
100%		-10	713 500 000	-3.8	-0.000 001	-0.005
100%		0	713 500 007	3.4	0.000 000	0.005
100%		+10	713 500 001	-2.8	0.000 000	-0.004
100%		+30	713 500 001	-2.2	0.000 000	-0.003
100%		+40	713 500 000	-3.9	-0.000 001	-0.005
100%		+50	713 500 001	-2.7	0.000 000	-0.004
Batt. Endpoint	3.600	+20	713 500 000	-3.7	-0.000 001	-0.005



- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 711,000,000 Hz
- ▣ CHANNEL: 23130 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	711 000 003	0.0	0.000 000	0.000
100%		-30	711 000 006	3.6	0.000 001	0.005
100%		-20	711 000 004	1.7	0.000 000	0.002
100%		-10	711 000 004	1.8	0.000 000	0.003
100%		0	711 000 005	2.6	0.000 000	0.004
100%		+10	711 000 006	3.2	0.000 000	0.005
100%		+30	711 000 004	1.7	0.000 000	0.002
100%		+40	711 000 005	2.6	0.000 000	0.004
100%		+50	711 000 000	711 000 000	-2.3	0.000 000
Batt. Endpoint	3.600	+20	711 000 007	4.4	0.000 001	0.006



### 8.7 RECEIVER SPURIOUS EMISSIONS

#### 8.7.1 LTE B12

Frequency Range : 30 MHz ~ 1 GHz

Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	dB $\mu$ V	dB /m	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
No Peak Found						

Frequency Range : Above 1 GHz

Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	dB $\mu$ V	dB /m	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
No Peak Found						

#### Limit

Frequency (MHz)	Field Strength ( $\mu$ v/m at 3 meters)
30 – 88	100
88 - 216	150
216 – 960	200
Above 960	500

#### 8.7.2 LTE B29

Frequency Range : 30 MHz ~ 1 GHz

Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	dB $\mu$ V	dB /m	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
No Peak Found						

Frequency Range : Above 1 GHz


Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	dB $\mu$ V	dB /m	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
No Peak Found						

#### Limit


Frequency (MHz)	Field Strength ( $\mu$ v/m at 3 meters)
30 – 88	100
88 - 216	150
216 – 960	200
Above 960	500

## 9. TEST PLOTS


BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 QPSK\_RB6\_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 16QAM\_RB6\_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 64QAM\_RB6\_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 QPSK\_RB15\_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 16QAM\_RB15\_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 64QAM\_RB15\_0)




BAND 12. Occupied Bandwidth Plot (5M BW Ch.23095 QPSK\_RB25\_0)




BAND 12. Occupied Bandwidth Plot (5M BW Ch.23095 16QAM\_RB25\_0)




BAND 12. Occupied Bandwidth Plot (5M BW Ch.23095 64QAM\_RB25\_0)




BAND 12. Occupied Bandwidth Plot (10M BW Ch.23095 QPSK\_RB50\_0)




BAND 12. Occupied Bandwidth Plot (10M BW Ch.23095 16QAM\_RB50\_0)



BAND 12. Occupied Bandwidth Plot (10M BW Ch.23095 64QAM\_RB50\_0)




BAND 12. Lower Band Edge Plot (1.4M BW Ch.23017 QPSK\_RB1\_Offset 0)



BAND 12. Lower Band Edge Plot (1.4M BW Ch.23017 QPSK\_RB6\_Offset 0)



BAND 12. Lower Extended Band Edge Plot (1.4M BW Ch.23017 QPSK\_RB6\_0)




BAND 12. Lower Band Edge Plot (3M BW Ch.23025 QPSK\_RB1\_Offset 0)



BAND 12. Lower Band Edge Plot (3M BW Ch.23025 QPSK\_RB15\_Offset 0)



BAND 12. Lower Extended Band Edge Plot (3M BW Ch.23025 QPSK\_RB15\_0)



BAND 12. Lower Band Edge Plot (5M BW Ch.23035 QPSK\_RB1\_Offset 0)



BAND 12. Lower Band Edge Plot (5M BW Ch.23035 QPSK\_RB25\_Offset 0)



BAND 12. Lower Extended Band Edge Plot (5M BW Ch.23035 QPSK\_RB25\_0)



BAND 12. Lower Band Edge Plot (10M BW Ch.23060 QPSK\_RB1\_Offset 0)



BAND 12. Lower Band Edge Plot (10M BW Ch.23060 QPSK\_RB50\_Offset 0)



BAND 12. Lower Extended Band Edge Plot (10M BW Ch.23060 QPSK\_RB50\_0)



BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK\_RB1\_Offset 5)\_1




BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK\_RB1\_Offset 5)\_2



BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK\_RB6\_Offset 0)



BAND 12. Upper Extended Band Edge Plot (1.4M BW Ch.23173 QPSK\_RB6\_0)




BAND 12. Upper Band Edge Plot (3M BW Ch.23165 QPSK\_RB1\_Offset 14)-1








BAND 12. Upper Extended Band Edge Plot (3M BW Ch.23165 QPSK\_RB15\_0)



BAND 12. Upper Band Edge Plot (5M BW Ch.23155 QPSK\_RB1\_Offset 24)




BAND 12. Upper Band Edge Plot (5M BW Ch.23155 QPSK\_RB25\_Offset 0)



BAND 12. Upper Extended Band Edge Plot (5M BW Ch.23155 QPSK\_RB25\_0)




BAND 12. Upper Band Edge Plot (10M BW Ch.23130 QPSK\_RB1\_Offset 49)




BAND 12. Upper Band Edge Plot (10M BW Ch.23130 QPSK\_RB50\_Offset 0)




BAND 12. Upper Extended Band Edge Plot (10M BW Ch.23130 QPSK\_RB50\_0)




BAND 12. Conducted Spurious Plot \_ (23017ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23095ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23173ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23025ch\_3MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23095ch\_3MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23165ch\_3MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23035ch\_5MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23095ch\_5MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23155ch\_5MHz\_QPSK\_RB 1\_0)




BAND 12. Conducted Spurious Plot \_ (23060ch\_10MHz\_QPSK\_RB 1\_0)



BAND 12. Conducted Spurious Plot \_ (23095ch\_10MHz\_QPSK\_RB 1\_0)



BAND 12. Conducted Spurious Plot \_ (23130ch\_10MHz\_QPSK\_RB 1\_0)



## 10. ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2001-FI013-P