

# FCC NFC REPORT

## Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Address:**  
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,  
16677, Rep. of Korea

**Date of Issue:**  
July 16, 2021

**Test Site/Location:**  
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si,  
Gyeonggi-do, 17383 KOREA

**Report No.:** HCT-RF-2107-FC010

**FCC ID:** A3LSMG715U1

**APPLICANT:** SAMSUNG Electronics Co., Ltd.

According to the Evaluation report, all of the data contained herein is reused from the reference  
FCC ID : A3LSMG715U report.

**Model:** SM-G715U1  
**EUT Type:** Mobile Phone  
**RF Output Field Strength:** 17.15 dBuV/m @30 m  
**Frequency of Operation:** 13.5601 MHz  
**Modulation type:** ASK  
**FCC Classification:** Low Power Communication Device – Transmitter  
**FCC Rule Part(s):** FCC Part 15.225 Subpart C

**Engineering Statement:**

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Report No.: HCT-RF-2107-FC010

---

REVIEWED BY



---

Report prepared by : Jeong Ho Kim  
Engineer of Telecommunication Testing Center

---

Report approved by : Jong Seok Lee  
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked \*.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

\* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2107-FC010	July 16, 2021	- First Approval Report

If this report is required to confirmation of authenticity, please contact to [www.hct.co.kr](http://www.hct.co.kr)

# Table of Contents

REVIEWED BY .....	2
1. EUT DESCRIPTION .....	5
2. TEST METHODOLOGY .....	6
EUT CONFIGURATION .....	6
EUT EXERCISE .....	6
GENERAL TEST PROCEDURES .....	6
DESCRIPTION OF TEST MODES .....	6
3. INSTRUMENT CALIBRATION.....	7
4. FACILITIES AND ACCREDITATIONS .....	7
FACILITIES .....	7
EQUIPMENT .....	7
5. ANTENNA REQUIREMENTS .....	7
6. MEASUREMENT UNCERTAINTY .....	8
7. DESCRIPTION OF TESTS.....	9
8. TEST SUMMARY .....	17
9. TEST RESULT .....	18
9.1. Operation within the band 13.110 MHz – 14.010 MHz.....	18
9.2. Radiated Emission 9 kHz – 30 MHz .....	20
9.3. Radiated Emission 30 MHz – 1000 MHz .....	21
9.4. 20 dB Bandwidth .....	22
9.5. Frequency Stability .....	23
9.6. POWERLINE CONDUCTE EMISSIONS .....	27
10. LIST OF TEST EQUIPMENT .....	31
11. ANNEX A_ TEST SETUP PHOTO .....	33

## 1. EUT DESCRIPTION

<b>Model</b>	SM-G715U1
<b>Additional Model</b>	-
<b>EUT Type</b>	Mobile Phone
<b>Power Supply</b>	DC 3.85 V
<b>Frequency of Operation</b>	13.5601 MHz
<b>Transmit Power</b>	17.15 dBuV/m @30 m
<b>Modulation Type</b>	ASK
<b>Date(s) of Tests</b>	November 21, 2019 ~ December 11, 2019
<b>Serial number</b>	Conducted : R58R5376H1X Radiated : R38N502E9NW

## 2. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) is used in the measurement of the test device.

### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.225 under the FCC Rules Part 15 Subpart C.

## GENERAL TEST PROCEDURES

### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013).

## DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

### 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

### 4. FACILITIES AND ACCREDITATIONS

#### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

#### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5. ANTENNA REQUIREMENTS

#### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of §15.203

## 6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05



## 7. DESCRIPTION OF TESTS

### 7.1. Radiated Test

#### Limit (Operation within the band 13.110 MHz – 14.010 MHz)

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
13.553 – 13.567	15,848	30
13.410 ≤ f ≤ 13.553 13.567 ≤ f ≤ 13.710	334	30
13.110 ≤ f ≤ 13.410 13.710 ≤ f ≤ 14.010	106	30

Note:

1. 15,848 uV/m = 84.0 dBuV/m
2. 334 uV/m = 50.47 dBuV/m
3. 106 uV/m = 40.51 dBuV/m

#### Limit (Radiated Spurious Emissions)


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	* 100	3
88-216	* 150	3
216-960	* 200	3
Above 960	500	3

※:


Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Test Configuration**

Below 30 MHz



30 MHz - 1 GHz



**Test Procedure of inband**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor =  $40\log(3\text{ m}/30\text{ m}) = -40\text{ dB}$   
Measurement Distance : 3 m (Below 30 MHz)

7. Spectrum Setting

- Detector = Peak
- Trace = Maxhold
- RBW = 9 kHz
- VBW  $\geq 3 \times$  RBW

8. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

**Test Procedure of Radiated spurious emissions(Below 30 MHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) =  $40\log(3 \text{ m}/300 \text{ m}) = - 80 \text{ dB}$   
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) =  $40\log(3 \text{ m}/30 \text{ m}) = - 40 \text{ dB}$   
Measurement Distance : 3 m
8. Spectrum Setting
  - Frequency Range = 9 kHz ~ 30 MHz
  - Detector = Peak
  - Trace = Maxhold
  - RBW = 9 kHz
  - VBW  $\geq 3 \times$  RBW
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

**KDB 414788 OFS and Chamber Correlation Justification**

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.


OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

**Test Procedure of Radiated spurious emissions(Above 30 MHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. The Hybrid antenna was placed at a location 3m from the EUT, which is varied from 1m to 4m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting
  - Frequency Range = 30 MHz ~ 1 GHz
  - Detector = Peak
  - Trace = Maxhold
  - RBW = 100 kHz
  - VBW  $\geq$  3 x RBW
7. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

## 7.2. 20dB Bandwidth

### Test Configuration



### Test Procedure

The 20 dB bandwidth was measured by using a spectrum analyzer.

(Procedure 6.9.2 in ANSI 63.10-2013)

- 1) RBW = 1%~5% of the OBW
- 2) VBW = approximately three times RBW
- 3) Span = between two times and five times the OBW
- 4) Detector = Peak
- 5) Trace mode = Max hold
- 6) Allow the trace to stabilize

Note :


We tested Occupied Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

### 7.3. Frequency Stability

#### Limit

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency.

#### Test Configuration



#### Test Procedure

For battery operated equipment, the equipment tests shall be performed using a new battery.

- 1) Turn the EUT OFF and place it inside the environmental temperature chamber.  
For devices that have oscillator heaters, energize only the heater circuit.
- 2) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
- 3) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.
- 4) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency.

#### Note:

- 1) Temperature:  
The temperature is varied from  $-20^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  using an environmental chamber.
- 2) Primary Supply Voltage :  
The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment.  
For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

#### 7.4. AC Power line Conducted Emissions

##### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 <sup>(a)</sup>	56 to 46 <sup>(a)</sup>
0.50 to 5	56	46
5 to 30	60	50

<sup>(a)</sup>Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

##### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

##### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.
5. The EUT is the device operating below 30 MHz.
  - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
  - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

##### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

## **7.5. Worst case configuration and mode**

### **Radiated test**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone, Stand alone + external accessories(Earphone, etc)
  - Worstcase : Stand alone
2. EUT Axis : Y
3. All type and bitrate were investigated and the worst case results are reported.  
(Worst case : Type A, 106 kbps)
4. All position of loop antenna were investigated and the worst case configuration results are reported.
  - Position : Horizontal, Vertical, Parallel to the ground plane
  - Worstcase : Horizontal

### **AC Power line Conducted Emissions**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone+Earphone+Travel Adapter, Stand alone+Travel Adapter
  - Worstcase : Stand alone+Travel Adapter

### **20dB Bandwidth & Frequency Stability**

1. All type and bitrate were investigated and the worst case results are reported.  
(Worst case : Type A, 106 kbps)



## 8. TEST SUMMARY

Regulation	Requirement	Result
Part 15.225 (a)	Radiated Electric Field Emissions (13.553MHz to 13.567MHz)	Pass
Part 15.225 (b)	Radiated Electric Field Emissions (13.410 ≤ f ≤ 13.553, 13.567 ≤ f ≤ 13.710)	Pass
Part 15.225 (c)	Radiated Electric Field Emissions (13.110 ≤ f ≤ 13.410, 13.710 ≤ f ≤ 14.010)	Pass
Part 15.209	Radiated Electric Field Emissions (9kHz to 30MHz)	Pass
Part 15.209	Radiated Electric Field Emissions (30MHz to 1GHz)	Pass
Part 15.225 (e)	Frequency Stability	Pass
Part 15.207	AC power conducted emissions (150kHz to 30MHz)	Pass
Part 15.215 (c)	20 dB Bandwidth	Pass

## 9. TEST RESULT

### 9.1. Operation within the band 13.110 MHz – 14.010 MHz

Measured Frequency Range : 13.553 MHz-13.567 MHz							
Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor +Cable Loss (dB/m)	Distance Correction (dB)	Ant. POL	Total (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.5601	36.41	20.74	-40.00	Z-H	17.15	84.00	66.85
13.5596	34.79	20.74	-40.00	Y-V	15.53	84.00	68.47


Measured Frequency Range : 13.410 MHz-13.553 MHz and 13.567 MHz-13.710 MHz							
Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor +Cable Loss (dB/m)	Distance Correction (dB)	Ant. POL	Total (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.4546	24.41	20.74	-40.00	Z-H	5.15	50.47	45.32
13.5670	26.87	20.74	-40.00	Z-H	7.61	50.47	42.86

Measured Frequency Range : 13.110 MHz – 13.410 MHz and 13.710 MHz-14.010 MHz							
Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor +Cable Loss (dB/m)	Distance Correction (dB)	Ant. POL	Total (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.3488	20.43	20.74	-40.00	Z-H	1.17	40.51	39.34
13.7724	20.52	20.74	-40.00	Z-H	1.26	40.51	39.25

**Note:**

1. With Tag(worst case)

■ Test Plot



Date: 25.NOV.2019 10:00:59

**Note:**

Plot of worst case are only reported.

## 9.2. Radiated Emission 9 kHz – 30 MHz

Measured Frequency Range :							
9 kHz - 30 MHz							
Frequency (MHz)	Read Level (dBuV/m)@3m	Ant.Factor +Cable Loss (dB/m)	Distance Correction (dB)	Ant. POL	Total (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
3.5459	10.86	20.73	-40.00	Z-H	-8.41	29.54	37.95
14.0739	11.45	20.73	-40.00	Z-H	-7.82	29.54	37.36
27.1086	12.22	20.96	-40.00	Z-H	-6.82	29.54	36.36
27.1417	9.62	20.96	-40.00	Y-V	-9.42	29.54	38.96

**Note:**

1. With Tag(worst case)


### 9.3. Radiated Emission 30 MHz – 1000 MHz

Measured Frequency Range :							
30 MHz - 1000 MHz							
Frequency (MHz)	Read Level (dBuV/m) @3m	Ant.Factor (dB/m)	Cable Loss (dB)	Ant. Pol (H/V)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)
36.314*	12.55	11.72	0.66	H	24.93	40.0	15.07
38.389	15.61	12.38	0.78	H	28.77	40.0	11.23
73.2112	13.63	9.27	1.11	V	24.01	40.0	15.99
120.5738*	12.75	11.64	1.20	H	25.59	43.5	17.91
126.45*	13.03	12.84	1.34	H	27.21	43.5	16.29
173.46	12.84	13.41	1.40	V	27.65	43.5	15.85

**Note:**

1. '\*' is the result for restricted band.
2. With Tag(worst case)

■ **Test Plot**




Date: 25.NOV.2019 11:19:18

**Note:**

Plot of worst case are only reported

### 9.4. 20 dB Bandwidth



### 9.5. Frequency Stability

**Startup**

OPERATING FREQUENCY: 13.56 MHz  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ±0.01 % = ±1356 Hz

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (MHz)	Frequency Dev. (Hz)	Frequency Dev (%)
100%	3.85	-20	13.560047	47	0.0003459
100%		-10	13.560041	41	0.0002997
100%		0	13.560037	37	0.0002695
100%		+10	13.560033	33	0.0002458
100%		+20(Ref.)	13.560038	38	0.0002774
100%		+30	13.560032	32	0.0002337
100%		+40	13.560042	42	0.0003069
100%		+50	13.560046	46	0.0003386
High	4.35	+20	13.560044	44	0.0003279
End. Point	3.40	+20	13.560046	46	0.0003378

**2 minutes**

OPERATING FREQUENCY: 13.56 MHz  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ±0.01 % = ±1356 Hz

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (MHz)	Frequency Dev. (Hz)	Frequency Dev (%)
100%	3.85	-20	13.560045	45	0.0003316
100%		-10	13.560038	38	0.0002829
100%		0	13.560034	34	0.0002499
100%		+10	13.560030	30	0.0002246
100%		+20(Ref.)	13.560036	36	0.0002673
100%		+30	13.560032	32	0.0002341
100%		+40	13.560040	40	0.0002971
100%		+50	13.560044	44	0.0003278
High		4.35	+20	13.560044	44
End. Point	3.40	+20	13.560046	46	0.0003369



**5 minutes**

OPERATING FREQUENCY: 13.56 MHz  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ±0.01 % = ±1356 Hz

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (MHz)	Frequency Dev. (Hz)	Frequency Dev (%)
100%	3.85	-20	13.560045	45	0.0003310
100%		-10	13.560038	38	0.0002791
100%		0	13.560034	34	0.0002504
100%		+10	13.560032	32	0.0002344
100%		+20(Ref.)	13.560039	39	0.0002907
100%		+30	13.560033	33	0.0002409
100%		+40	13.560042	42	0.0003091
100%		+50	13.560046	46	0.0003387
High		4.35	+20	13.560044	44
End. Point	3.40	+20	13.560047	47	0.0003496

**10 minutes**

OPERATING FREQUENCY: 13.56 MHz  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ±0.01 % = ±1356 Hz

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (MHz)	Frequency Dev. (Hz)	Frequency Dev (%)
100%	3.85	-20	13.560045	45	0.0003295
100%		-10	13.560038	38	0.0002821
100%		0	13.560034	34	0.0002510
100%		+10	13.560030	30	0.0002248
100%		+20(Ref.)	13.560040	40	0.0002921
100%		+30	13.560032	32	0.0002355
100%		+40	13.560042	42	0.0003119
100%		+50	13.560048	48	0.0003529
High		4.35	+20	13.560046	46
End. Point	3.40	+20	13.560046	46	0.0003386

## 9.6. POWERLINE CONDUCTED EMISSIONS

### Conducted Emissions (Line 1)

Test


1 / 2

## HCT TEST Report

### Common Information

EUT: SM-G715FN/DS  
 Manufacturer: SAMSUNG  
 Test Site: SHIELD ROOM  
 Operating Conditions: NFC\_L1

FCC CLASS B\_Exten Cable



— FCC CLASS B\_QP      — FCC CLASS B\_AV      — Preview Result 1-PK+  
— Preview Result 2-AVG      x Final Result 1-QPK      x Final Result 2-CAV

### Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	46.1	9.000	Off	L1	9.8	19.8	65.9
0.156000	43.7	9.000	Off	L1	9.8	21.9	65.7
0.224000	40.1	9.000	Off	L1	9.8	22.6	62.7
0.230000	42.3	9.000	Off	L1	9.8	20.1	62.4
0.304000	38.7	9.000	Off	L1	9.8	21.5	60.1
0.310000	35.3	9.000	Off	L1	9.8	24.7	60.0
4.870000	38.5	9.000	Off	L1	10.1	17.5	56.0
4.956000	37.6	9.000	Off	L1	10.1	18.4	56.0
5.024000	38.7	9.000	Off	L1	10.1	21.3	60.0
5.032000	38.4	9.000	Off	L1	10.1	21.6	60.0
5.096000	37.6	9.000	Off	L1	10.1	22.4	60.0
5.102000	38.8	9.000	Off	L1	10.1	21.2	60.0
13.454000	39.7	9.000	Off	L1	10.4	20.3	60.0
13.480000	39.0	9.000	Off	L1	10.4	21.0	60.0
13.560000	51.3	9.000	Off	L1	10.4	8.7	60.0
13.636000	40.5	9.000	Off	L1	10.4	19.5	60.0
13.652000	40.7	9.000	Off	L1	10.4	19.3	60.0
13.662000	41.0	9.000	Off	L1	10.4	19.0	60.0

2019-12-09

오후 2:48:16

Test

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	32.6	9.000	Off	L1	9.8	23.3	55.9
0.156000	30.3	9.000	Off	L1	9.8	25.4	55.7
0.224000	24.8	9.000	Off	L1	9.8	27.9	52.7
0.228000	27.6	9.000	Off	L1	9.8	24.9	52.5
0.232000	25.3	9.000	Off	L1	9.8	27.1	52.4
0.304000	24.8	9.000	Off	L1	9.8	25.4	50.1
4.870000	26.0	9.000	Off	L1	10.1	20.0	46.0
4.876000	26.7	9.000	Off	L1	10.1	19.3	46.0
5.028000	27.5	9.000	Off	L1	10.1	22.5	50.0
5.032000	27.2	9.000	Off	L1	10.1	22.8	50.0
5.096000	25.8	9.000	Off	L1	10.1	24.2	50.0
5.100000	26.9	9.000	Off	L1	10.1	23.1	50.0
13.480000	30.7	9.000	Off	L1	10.4	19.3	50.0
13.560000	46.8	9.000	Off	L1	10.4	3.2	50.0
13.636000	31.2	9.000	Off	L1	10.4	18.8	50.0
13.662000	31.6	9.000	Off	L1	10.4	18.4	50.0
14.036000	29.8	9.000	Off	L1	10.5	20.2	50.0
14.098000	30.1	9.000	Off	L1	10.5	19.9	50.0

2019-12-09

오후 2:48:16

**Conducted Emissions (Line 2)**

Test


1 / 2

**HCT TEST Report**

**Common Information**

EUT: SM-G715FN/DS  
 Manufacturer: SAMSUNG  
 Test Site: SHIELD ROOM  
 Operating Conditions: NFC\_N

FCC CLASS B\_Exten Cable



**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	45.2	9.000	Off	N	9.8	20.8	66.0
0.230000	42.3	9.000	Off	N	9.8	20.2	62.4
0.300000	37.2	9.000	Off	N	9.8	23.0	60.2
0.304000	38.6	9.000	Off	N	9.8	21.6	60.1
0.308000	38.5	9.000	Off	N	9.8	21.5	60.0
0.384000	34.8	9.000	Off	N	9.8	23.4	58.2
4.724000	38.6	9.000	Off	N	10.0	17.4	56.0
4.870000	38.5	9.000	Off	N	10.1	17.5	56.0
4.948000	38.7	9.000	Off	N	10.1	17.3	56.0
5.022000	39.0	9.000	Off	N	10.1	21.0	60.0
5.032000	38.3	9.000	Off	N	10.1	21.7	60.0
5.100000	38.9	9.000	Off	N	10.1	21.1	60.0
13.560000	51.6	9.000	Off	N	10.5	8.4	60.0
13.642000	40.8	9.000	Off	N	10.5	19.2	60.0
13.668000	40.0	9.000	Off	N	10.5	20.0	60.0
13.764000	38.4	9.000	Off	N	10.5	21.6	60.0
13.918000	38.2	9.000	Off	N	10.5	21.8	60.0
14.016000	40.1	9.000	Off	N	10.5	19.9	60.0

2019-12-09

오후 2:39:40

Test

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	31.5	9.000	Off	N	9.8	24.5	56.0
0.154000	32.1	9.000	Off	N	9.8	23.6	55.8
0.226000	26.8	9.000	Off	N	9.8	25.7	52.6
0.232000	25.5	9.000	Off	N	9.8	26.9	52.4
0.300000	22.5	9.000	Off	N	9.8	27.7	50.2
0.304000	24.7	9.000	Off	N	9.8	25.4	50.1
4.870000	25.9	9.000	Off	N	10.1	20.1	46.0
4.948000	26.9	9.000	Off	N	10.1	19.1	46.0
5.022000	27.6	9.000	Off	N	10.1	22.4	50.0
5.026000	27.8	9.000	Off	N	10.1	22.2	50.0
5.032000	27.1	9.000	Off	N	10.1	22.9	50.0
5.100000	26.9	9.000	Off	N	10.1	23.1	50.0
13.508000	30.1	9.000	Off	N	10.5	19.9	50.0
13.560000	46.9	9.000	Off	N	10.5	3.1	50.0
13.618000	30.3	9.000	Off	N	10.5	19.7	50.0
13.654000	31.6	9.000	Off	N	10.5	18.4	50.0
13.668000	31.8	9.000	Off	N	10.5	18.2	50.0
14.210000	28.7	9.000	Off	N	10.5	21.3	50.0

2019-12-09

오후 2:39:40

## 10. LIST OF TEST EQUIPMENT

### Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/04/2020	Annual	102245
Rohde & Schwarz	ESR / EMI Test Receiver	06/17/2021	Annual	101910
ESPEC	SU-642 / Temperature Chamber	07/30/2020	Annual	0093000718
Agilent	N9020A / Signal Analyzer	05/03/2021	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	03/09/2021	Annual	MY49432108
Agilent	N1911A / Power Meter	04/08/2021	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/08/2021	Annual	MY57820067
Agilent	87300B / Directional Coupler	11/10/2020	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	02/09/2021	Annual	10545
HP	E3632A / DC Power Supply	09/16/2020	Annual	MY40004427
HP	8493C / Attenuator(10 dB)(DC-26.5 GHz)	06/18/2021	Annual	07560
HP	8493C / Attenuator(10 dB)(DC-26.5 GHz)	06/28/2021	Annual	08285
Rohde & Schwarz	18N-20dB / Attenuator(20 dB)	03/08/2021	Annual	8
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

**Radiated Test**

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
TNM system	FBSM-01B / Amp & Filter Bank Switch Controller	N/A	N/A	N/A
Schwarzbeck	Loop Antenna	03/19/2020	Biennial	1513-333
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/02/2019	Biennial	01039
Schwarzbeck	BBHA 9120D / Horn Antenna	08/01/2019	Biennial	912D-1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/12/2021	Biennial	BBHA9170124
Rohde & Schwarz	FSV(10 Hz ~ 40 GHz) / Spectrum Analyzer	05/14/2021	Annual	101055
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	01/06/2021	Annual	2
Wainwright Instruments	WRCJV12-4900-5100-5900-6100-50SS	06/24/2021	Annual	5
Wainwright Instruments	WRCJV12-4900-5100-5900-6100-50SS	06/24/2021	Annual	6
CERNEK	CBL18265035 / Power Amplifier	12/04/2020	Annual	22966
CERNEK	CBL26405040 / Power Amplifier	03/23/2021	Annual	25956
TNM system	FBSM-05B / HPF(3~18GHz) + LNA1(1~18GHz)	01/20/2021	Annual	F6
TNM system	FBSM-05B / ATT(10dB) + LNA1(1~18GHz)	01/20/2021	Annual	None
TNM system	FBSM-05B / ATT(3dB) + LNA1(1~18GHz)	01/20/2021	Annual	None
TNM system	FBSM-05B / LNA1(1~18GHz)	01/20/2021	Annual	25540
TNM system	FBSM-05B / HPF(7~18GHz) + LNA2(6~18GHz)	01/20/2021	Annual	28550
TNM system	FBSM-05B / Thru(30MHz ~ 18GHz)	01/20/2021	Annual	None
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	02/08/2021	Annual	1
Weinschel	2-3 / Attenuator (3 dB)	10/07/2020	Annual	BR0617
H+S	5910-N-50-010 / Attenuator(10 dB)	10/28/2020	Annual	None
Rohde & Schwarz	ESCI / Test Receiver	06/10/2021	Annual	100584

**Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).



## 11. ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2107-FC010-P