

FCC LTE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

October 31, 2019

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-1910-FC017

FCC ID: A3LSMG770F

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-G770F/DS
 Additional Model(s): SM-G770F/DSM, SM-G770F
 EUT Type: Mobile Phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 41 (5)	2498.5 – 2687.5	4M50G7D	QPSK	0.082	19.14
		4M50W7D	16QAM	0.071	18.53
		4M52W7D	64QAM	0.016	12.02
LTE – Band 41 (10)	2501.0 – 2685.0	8M99G7D	QPSK	0.082	19.12
		8M95W7D	16QAM	0.073	18.62
		8M99W7D	64QAM	0.016	12.09
LTE – Band 41 (15)	2503.5 – 2682.5	13M4G7D	QPSK	0.085	19.27
		13M5W7D	16QAM	0.075	18.77
		13M4W7D	64QAM	0.017	12.24
LTE – Band 41 (20)	2506.0 – 2680.0	17M9G7D	QPSK	0.084	19.22
		17M9W7D	16QAM	0.074	18.70
		17M9W7D	64QAM	0.016	12.17

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



Report prepared by : Jae Ryang Do
 Engineer of Telecommunication Testing Center



Report approved by : Jong Seok Lee
 Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1910-FC017	October 31, 2019	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.(HCT Accreditation No.: KT197)

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. DESCRIPTION OF EUT.....	5
2.2. MEASURING INSTRUMENT CALIBRATION	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 TEST PROCEDURE	6
3.2 RADIATED POWER.....	7
3.3 RADIATED SPURIOUS EMISSIONS	8
3.4 PEAK- TO- AVERAGE RATIO.....	9
3.5 OCCUPIED BANDWIDTH.	11
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	12
3.7 CHANNEL EDGE.....	13
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	15
3.9 WORST CASE(RADIATED TEST).....	16
3.10 WORST CASE(CONDUCTED TEST)	17
4. LIST OF TEST EQUIPMENT	18
5. MEASUREMENT UNCERTAINTY	19
6. SUMMARY OF TEST RESULTS	20
7. SAMPLE CALCULATION	21
8. TEST DATA	23
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	23
8.2 RADIATED SPURIOUS EMISSIONS	25
8.3 PEAK-TO-AVERAGE RATIO.....	29
8.4 OCCUPIED BANDWIDTH	30
8.5 CONDUCTED SPURIOUS EMISSIONS	31
8.6 CHANNEL EDGE.....	32
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	33
8.8 GEO-LOCATION MECHANISM	45
9. TEST PLOTS.....	54
10. ANNEX A_ TEST SETUP PHOTO.....	135

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMG770F
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-G770F/DS
Additional Model(s):	SM-G770F/DSM, SM-G770F
Tx Frequency:	2498.5 – 2687.5 : 5 MHz 2501.0 – 2685.0 : 10 MHz 2503.5 – 2682.5 : 15 MHz 2506.0 – 2680.0 : 20 MHz
Date(s) of Tests:	September 09, 2019 ~ October 14, 2019

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), Bluetooth, NFC, ANT+.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed NormalHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and NormalHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundalmatal frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.


1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:

Set $\geq [10 \times$ (number of points in sweep) \times (transmission period)] for single sweep
(automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6$ dB if the duty cycle is a constant 25%.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2% of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

1. The attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge,
2. $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge.
3. $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge.
4. The attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz.
5. $55 + 10 \log (P)$ dB at or below 2490.5 MHz.
6. X is the greater of 6MHz or the actual emission bandwidth
7. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation.
The tuner for this device was set to simulate a **"free space"** condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.
- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- All modes of operation were investigated and the worst case configuration results are reported.
- Please refer to the table below.
- SM-G770FDS & additional models were tested and the worst case results are reported.
(Worst case : SM-G770FDS)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM	1	0	X
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.10 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- SM-G770FDS & additional models were tested and the worst case results are reported.

(Worst case : SM-G770FDS)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset		
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0		
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0		
Channel Edge	QPSK	5	Low	1	0		
			High	1	24		
		10	Low	1	0		
			High	1	49		
		15	Low	1	0		
			High	1	74		
		20	Low	1	0		
			High	1	99		
				5, 10, 15, 20	Low, Mid, High	Full RB	0
		Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/03/2019	Annual	05/03/2020
Agilent	E3632A/DC Power Supply	MY40004326	07/01/2019	Annual	07/01/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000717	08/14/2019	Annual	08/14/2020
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	01/28/2019	Biennial	01/28/2021
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	05/08/2019	Annual	05/08/2020
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2019	Annual	06/04/2020
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2019	Annual	10/14/2020
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/27/2019	Annual	08/27/2020
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/09/2019	Annual	08/09/2020
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/15/2019	Annual	07/15/2020
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	05/17/2019	Annual	05/17/2020
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(m)(4)	<ul style="list-style-type: none"> ■ < 40 + 10log10 (P[Watts]) at Channel edges ■ < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges ■ < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges ■ < 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz 	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(h)(2)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(m)(4)	< 55 + 10log10 (P[Watts])	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
40620	2593.0	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2498.5	LTE B41/ 5 MHz	QPSK	-26.00	10.75	10.70	2.31	H	< 2.00	0.082	19.14
		16-QAM	-26.61	10.14	10.70	2.31	H		0.071	18.53
		64-QAM	-33.12	3.63	10.70	2.31	H		0.016	12.02
2593.0		QPSK	-27.89	8.90	10.98	2.35	H		0.057	17.53
		16-QAM	-28.45	8.34	10.98	2.35	H		0.050	16.97
		64-QAM	-34.97	1.82	10.98	2.35	H		0.011	10.45
2687.5		QPSK	-29.30	7.86	11.10	2.39	H		0.045	16.57
		16-QAM	-29.80	7.36	11.10	2.39	H		0.040	16.07
		64-QAM	-36.21	0.95	11.10	2.39	H		0.009	9.66

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2501.0	LTE B41/ 10 MHz	QPSK	-26.02	10.73	10.70	2.31	H	< 2.00	0.082	19.12
		16-QAM	-26.52	10.23	10.70	2.31	H		0.073	18.62
		64-QAM	-33.05	3.70	10.70	2.31	H		0.016	12.09
2593.0		QPSK	-27.96	8.83	10.98	2.35	H		0.056	17.46
		16-QAM	-28.51	8.28	10.98	2.35	H		0.049	16.91
		64-QAM	-35.00	1.79	10.98	2.35	H		0.011	10.42
2685.0		QPSK	-29.33	7.75	11.10	2.39	H		0.044	16.46
		16-QAM	-29.67	7.41	11.10	2.39	H		0.041	16.12
		64-QAM	-36.16	0.92	11.10	2.39	H		0.009	9.63

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2503.5	LTE B41/ 15 MHz	QPSK	-25.87	10.88	10.70	2.31	H	< 2.00	0.085	19.27
		16-QAM	-26.37	10.38	10.70	2.31	H		0.075	18.77
		64-QAM	-32.90	3.85	10.70	2.31	H		0.017	12.24
2593.0		QPSK	-27.73	9.06	10.98	2.35	H		0.059	17.69
		16-QAM	-28.23	8.56	10.98	2.35	H		0.052	17.19
		64-QAM	-34.75	2.04	10.98	2.35	H		0.012	10.67
2682.5		QPSK	-29.72	7.26	11.10	2.38	H		0.040	15.98
		16-QAM	-30.07	6.91	11.10	2.38	H		0.037	15.63
		64-QAM	-36.52	0.46	11.10	2.38	H		0.008	9.18

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2506.0	LTE B41/ 20 MHz	QPSK	-25.86	10.81	10.73	2.32	H	< 2.00	0.084	19.22
		16-QAM	-26.38	10.29	10.73	2.32	H		0.074	18.70
		64-QAM	-32.91	3.76	10.73	2.32	H		0.016	12.17
2593.0		QPSK	-28.17	8.62	10.98	2.35	H		0.053	17.25
		16-QAM	-28.73	8.06	10.98	2.35	H		0.047	16.69
		64-QAM	-35.22	1.57	10.98	2.35	H		0.010	10.20
2680.0		QPSK	-29.29	7.69	11.10	2.38	H		0.044	16.41
		16-QAM	-29.61	7.37	11.10	2.38	H		0.041	16.09
		64-QAM	-36.11	0.87	11.10	2.38	H		0.009	9.59

8.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY : 2498.50 MHz
- ▣ MEASURED OUTPUT POWER: 19.14 dBm = 0.082 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 44.14 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39675 (2498.5)	4,997.00	-38.16	12.70	-49.95	3.35	H	-40.60	59.75
	7,495.50	-37.14	11.20	-38.82	4.29	H	-31.91	51.05
	9,994.00	-53.17	11.89	-51.48	5.04	V	-44.63	63.77
40620 (2593.0)	5,186.00	-43.30	12.75	-55.07	3.44	H	-45.76	64.90
	7,779.00	-39.88	11.65	-42.52	4.36	H	-35.23	54.37
	10,372.00	-52.79	10.75	-49.53	5.16	H	-43.94	63.09
41565 (2687.5)	5,375.00	-41.93	13.52	-53.20	3.52	V	-43.20	62.35
	8,062.50	-49.60	10.93	-50.21	4.45	H	-43.73	62.87
	10,750.00	-43.86	10.90	-40.28	5.31	V	-34.69	53.83

- ▣ OPERATING FREQUENCY : 2501.00 MHz
- ▣ MEASURED OUTPUT POWER: 19.12 dBm = 0.082 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 44.12 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39700 (2501.0)	5,002.00	-37.30	12.70	-49.09	3.35	H	-39.74	58.87
	7,503.00	-45.23	11.20	-46.80	4.29	V	-39.89	59.01
	10,004.00	-53.33	10.84	-50.62	5.03	V	-44.81	63.94
40620 (2593.0)	5,186.00	-43.31	12.75	-55.08	3.44	V	-45.77	64.89
	7,779.00	-53.67	11.65	-56.31	4.36	V	-49.02	68.14
	10,372.00	-52.75	10.75	-49.49	5.16	H	-43.90	63.03
41540 (2685.0)	5,370.00	-41.24	13.25	-52.32	3.52	V	-42.59	61.71
	8,055.00	-53.63	10.92	-54.23	4.46	V	-47.77	66.89
	10,740.00	-44.10	10.90	-40.80	5.29	V	-35.19	54.31

- ▣ OPERATING FREQUENCY : 2503.50 MHz
- ▣ MEASURED OUTPUT POWER: 19.27 dBm = 0.085 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 44.27 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39725 (2503.5)	5,007.00	-37.23	12.65	-48.28	3.35	H	-38.98	58.26
	7,510.50	-48.36	11.25	-50.13	4.29	V	-43.17	62.44
	10,014.00	-54.46	11.02	-51.68	5.03	V	-45.69	64.96
40620 (2593.0)	5,186.00	-41.71	12.75	-53.48	3.44	V	-44.17	63.44
	7,779.00	-49.54	11.65	-52.18	4.36	V	-44.89	64.16
	10,372.00	-51.71	10.75	-48.45	5.16	V	-42.86	62.14
41515 (2682.5)	5,365.00	-41.49	13.27	-52.59	3.52	V	-42.84	62.11
	8,047.50	-53.91	10.90	-54.49	4.46	V	-48.05	67.33
	10,730.00	-44.63	10.90	-41.45	5.25	V	-35.80	55.07

- ▣ OPERATING FREQUENCY : 2506.00 MHz
- ▣ MEASURED OUTPUT POWER: 19.22 dBm = 0.084 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 44.22 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39750 (2506.0)	5,012.00	-38.15	12.65	-49.20	3.35	V	-39.90	59.12
	7,518.00	-48.14	11.30	-50.13	4.30	H	-43.13	62.36
	10,024.00	-55.16	11.05	-52.30	5.02	V	-46.27	65.49
40620 (2593.0)	5,186.00	-41.18	12.75	-52.95	3.44	V	-43.64	62.86
	7,779.00	-50.26	11.65	-52.90	4.36	H	-45.61	64.83
	10,372.00	-51.76	10.75	-48.50	5.16	V	-42.91	62.14
41490 (2680.0)	5,360.00	-42.10	13.28	-53.22	3.51	V	-43.45	62.68
	8,040.00	-52.93	10.93	-53.58	4.48	V	-47.13	66.35
	10,720.00	-45.42	10.90	-42.63	5.24	V	-36.97	56.20

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
41	5 MHz	2593.0	QPSK	25	0	5.10
			16-QAM			5.94
			64-QAM			6.50
	10 MHz		QPSK	50		5.25
			16-QAM			6.01
			64-QAM			6.57
	15 MHz		QPSK	75		5.13
			16-QAM			5.94
			64-QAM			6.56
	20 MHz		QPSK	100		5.12
			16-QAM			5.90
			64-QAM			6.55

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 67 ~ 78.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
41	5 MHz	2593.0	QPSK	25	0	4.5012
			16-QAM			4.4949
			64-QAM			4.5166
	10 MHz		QPSK	50		8.9903
			16-QAM			8.9533
			64-QAM			8.9919
	15 MHz		QPSK	75		13.436
			16-QAM			13.471
			64-QAM			13.441
	20 MHz		QPSK	100		17.942
			16-QAM			17.897
			64-QAM			17.885

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 55 ~ 66.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
41	5	2498.5	7.4896	28.591	-66.945	-38.354	-25.00
		2593.0	26.1584	30.131	-66.939	-36.808	
		2687.5	25.2616	30.131	-66.989	-36.858	
	10	2501.0	26.3783	30.131	-67.244	-37.113	
		2593.0	26.1118	30.131	-67.057	-36.926	
		2685.0	25.8354	30.131	-66.935	-36.804	
	15	2503.5	26.2013	30.131	-67.652	-37.521	
		2593.0	25.8750	30.131	-65.951	-35.820	
		2682.5	26.1259	30.131	-66.867	-36.736	
	20	2506.0	26.1349	30.131	-67.059	-36.928	
		2593.0	25.8874	30.131	-67.064	-36.933	
		2680.0	26.2203	30.131	-67.237	-37.106	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 107 ~ 134.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

8.6 CHANNEL EDGE

Band Width	Frequency (MHz)	Modulation	RB (Size/Offset)	2 495 MHz ~ 2 496 MHz	C.E ~ (C.E +1MHz)	2 490.5 MHz ~ 2 495 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	Below 2 490.5 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Above (C.E + X MHz)
				Lower	Upper	Lower	Upper	Lower	Upper	Upper
5 MHz	2498.5	QPSK	25/0	-26.42	-24.09	-21.96	-17.86	-34.70	-30.94	-32.57
10 MHz	2501.0	QPSK	50/0	-27.63	-23.58	-23.00	-19.30	-30.36	-22.15	-32.83
15 MHz	2503.5	QPSK	75/0	-25.84	-22.65	-23.86	-19.19	-28.29	-21.34	-35.70
20 MHz	2506.0	QPSK	100/0	-25.43	-22.42	-23.61	-19.29	-27.80	-22.11	-38.74
Limit				-13.0	-10.0	-13.0	-10.0	-25.0	-13.0	-25.0

Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
					Lower	Upper	Lower	Upper
5 MHz	2593.0	QPSK	25	0	-26.57	-25.92	-22.27	-22.39
	2687.5	QPSK	25	0	-23.02	-22.51	-15.58	-16.55
10 MHz	2593.0	QPSK	50	0	-28.96	-26.05	-24.30	-24.49
	2685.0	QPSK	50	0	-22.80	-23.45	-16.70	-17.85
15 MHz	2593.0	QPSK	75	0	-29.02	-27.92	-26.02	-25.09
	2682.5	QPSK	75	0	-22.47	-23.34	-18.61	-19.53
20 MHz	2593.0	QPSK	100	0	-28.15	-27.30	-26.34	-25.04
	2680.0	QPSK	100	0	-22.52	-24.18	-19.18	-20.73
Limit					-10.0		-10.0	

Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
					Lower	Upper	Lower	Upper
5 MHz	2593.0	QPSK	25	0	-28.75	-27.97	-31.24	-29.89
	2687.5	QPSK	25	0	-24.52	-24.59	-28.03	-27.75
10 MHz	2593.0	QPSK	50	0	-29.26	-28.73	-33.46	-32.11
	2685.0	QPSK	50	0	-22.16	-22.96	-29.04	-29.01
15 MHz	2593.0	QPSK	75	0	-27.66	-27.92	-33.10	-31.53
	2682.5	QPSK	75	0	-21.56	-23.27	-28.74	-30.00
20 MHz	2593.0	QPSK	100	0	-27.05	-26.85	-34.18	-32.73
	2680.0	QPSK	100	0	-21.98	-23.34	-29.61	-35.67
Limit					-13.0		-25.0	


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 79 ~ 106. (1RB & Full RB)

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2498,500,000 Hz
- ▣ BANDWIDTH: 39675 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2498 500 013	0.0	0.000 000	0.000
100%		-30	2498 500 023	9.9	0.000 000	0.004
100%		-20	2498 500 021	7.8	0.000 000	0.003
100%		-10	2498 500 032	18.1	0.000 001	0.007
100%		0	2498 500 033	19.8	0.000 001	0.008
100%		+10	2498 500 026	13.0	0.000 001	0.005
100%		+30	2498 500 030	16.8	0.000 001	0.007
100%		+40	2498 500 007	-6.5	0.000 000	-0.003
100%		+50	2498 500 029	15.8	0.000 001	0.006
85%		3.400	+20	2498 500 032	19.0	0.000 001




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2501,000,000 Hz
- ▣ BANDWIDTH: 39700 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2501 000 005	0.0	0.000 000	0.000
100%		-30	2500 999 998	-6.9	0.000 000	-0.003
100%		-20	2500 999 999	-6.2	0.000 000	-0.002
100%		-10	2501 000 001	-4.6	0.000 000	-0.002
100%		0	2500 999 995	-10.2	0.000 000	-0.004
100%		+10	2501 000 011	5.9	0.000 000	0.002
100%		+30	2500 999 996	-9.7	0.000 000	-0.004
100%		+40	2500 999 996	-8.9	0.000 000	-0.004
100%		+50	2501 000 000	-5.5	0.000 000	-0.002
85%	3.400	+20	2500 999 999	-5.9	0.000 000	-0.002




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2503,500,000 Hz
- ▣ BANDWIDTH: 39725 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2503 499 989	0.0	0.000 000	0.000
100%		-30	2503 499 994	4.7	0.000 000	0.002
100%		-20	2503 499 983	-6.4	0.000 000	-0.003
100%		-10	2503 499 997	7.4	0.000 000	0.003
100%		0	2503 499 996	6.5	0.000 000	0.003
100%		+10	2503 499 985	-4.1	0.000 000	-0.002
100%		+30	2503 499 987	-2.7	0.000 000	-0.001
100%		+40	2503 499 977	-12.7	-0.000 001	-0.005
100%		+50	2503 500 000	10.4	0.000 000	0.004
85%	3.400	+20	2503 500 000	11.0	0.000 000	0.004




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2506.000.000 Hz
- ▣ BANDWIDTH: 39750 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2506 000 019	0.0	0.000 000	0.000
100%		-30	2506 000 039	19.9	0.000 001	0.008
100%		-20	2506 000 036	17.3	0.000 001	0.007
100%		-10	2506 000 023	4.8	0.000 000	0.002
100%		0	2506 000 029	10.2	0.000 000	0.004
100%		+10	2506 000 027	8.7	0.000 000	0.003
100%		+30	2506 000 022	3.8	0.000 000	0.002
100%		+40	2506 000 036	17.5	0.000 001	0.007
100%		+50	2506 000 034	14.9	0.000 001	0.006
85%		3.400	+20	2506 000 024	5.1	0.000 000




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2593,000,000 Hz
- ▣ BANDWIDTH: 40620 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 007	0.0	0.000 000	0.000
100%		-30	2593 000 003	-3.9	0.000 000	-0.002
100%		-20	2593 000 027	19.9	0.000 001	0.008
100%		-10	2593 000 015	7.7	0.000 000	0.003
100%		0	2593 000 013	5.3	0.000 000	0.002
100%		+10	2593 000 025	17.6	0.000 001	0.007
100%		+30	2593 000 019	11.4	0.000 000	0.004
100%		+40	2593 000 012	4.5	0.000 000	0.002
100%		+50	2593 000 027	19.5	0.000 001	0.008
85%	3.400	+20	2593 000 019	11.7	0.000 000	0.005




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2593,000,000 Hz
- ▣ BANDWIDTH: 40620 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2592 999 995	0.0	0.000 000	0.000
100%		-30	2592 999 991	-4.7	0.000 000	-0.002
100%		-20	2593 000 010	14.8	0.000 001	0.006
100%		-10	2593 000 012	16.5	0.000 001	0.006
100%		0	2593 000 006	10.1	0.000 000	0.004
100%		+10	2593 000 013	17.2	0.000 001	0.007
100%		+30	2592 999 992	-3.9	0.000 000	-0.002
100%		+40	2592 999 992	-3.6	0.000 000	-0.001
100%		+50	2593 000 006	10.3	0.000 000	0.004
85%	3.400	+20	2593 000 002	6.7	0.000 000	0.003




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2593,000,000 Hz
- ▣ BANDWIDTH: 40620 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 015	0.0	0.000 000	0.000
100%		-30	2593 000 035	20.0	0.000 001	0.008
100%		-20	2593 000 024	8.8	0.000 000	0.003
100%		-10	2593 000 030	14.7	0.000 001	0.006
100%		0	2593 000 023	8.2	0.000 000	0.003
100%		+10	2593 000 034	18.5	0.000 001	0.007
100%		+30	2593 000 024	8.6	0.000 000	0.003
100%		+40	2593 000 009	-6.3	0.000 000	-0.002
100%		+50	2593 000 027	11.7	0.000 000	0.005
85%	3.400	+20	2593 000 030	15.0	0.000 001	0.006




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2593.000.000 Hz
- ▣ BANDWIDTH: 40620 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 008	0.0	0.000 000	0.000
100%		-30	2593 000 028	19.9	0.000 001	0.008
100%		-20	2593 000 021	12.6	0.000 000	0.005
100%		-10	2593 000 023	14.4	0.000 001	0.006
100%		0	2593 000 015	6.7	0.000 000	0.003
100%		+10	2593 000 022	13.1	0.000 001	0.005
100%		+30	2593 000 019	10.1	0.000 000	0.004
100%		+40	2593 000 026	17.7	0.000 001	0.007
100%		+50	2593 000 027	18.7	0.000 001	0.007
85%	3.400	+20	2593 000 028	19.2	0.000 001	0.007




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2687.500.000 Hz
- ▣ BANDWIDTH: 41565 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2687 499 982	0.0	0.000 000	0.000
100%		-30	2687 499 967	-15.0	-0.000 001	-0.006
100%		-20	2687 499 972	-10.1	0.000 000	-0.004
100%		-10	2687 499 971	-11.3	0.000 000	-0.004
100%		0	2687 499 975	-7.4	0.000 000	-0.003
100%		+10	2687 499 973	-9.7	0.000 000	-0.004
100%		+30	2687 499 965	-17.1	-0.000 001	-0.006
100%		+40	2687 499 988	5.7	0.000 000	0.002
100%		+50	2687 499 970	-12.0	0.000 000	-0.004
85%	3.400	+20	2687 499 978	-4.2	0.000 000	-0.002




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2685,000,000 Hz
- ▣ BANDWIDTH: 41540 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2685 000 005	0.0	0.000 000	0.000
100%		-30	2685 000 013	7.5	0.000 000	0.003
100%		-20	2685 000 002	-3.3	0.000 000	-0.001
100%		-10	2685 000 008	3.0	0.000 000	0.001
100%		0	2685 000 009	3.4	0.000 000	0.001
100%		+10	2684 999 999	-6.1	0.000 000	-0.002
100%		+30	2684 999 998	-7.7	0.000 000	-0.003
100%		+40	2685 000 014	8.8	0.000 000	0.003
100%		+50	2685 000 019	13.7	0.000 001	0.005
85%	3.400	+20	2685 000 019	13.9	0.000 001	0.005




- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2682.500.000 Hz
- ▣ BANDWIDTH: 41515 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2682 499 983	0.0	0.000 000	0.000
100%		-30	2682 499 964	-18.6	-0.000 001	-0.007
100%		-20	2682 499 966	-16.6	-0.000 001	-0.006
100%		-10	2682 499 964	-18.4	-0.000 001	-0.007
100%		0	2682 499 989	6.8	0.000 000	0.003
100%		+10	2682 499 970	-12.6	0.000 000	-0.005
100%		+30	2682 499 969	-13.1	0.000 000	-0.005
100%		+40	2682 499 979	-3.8	0.000 000	-0.001
100%		+50	2682 499 979	-3.9	0.000 000	-0.001
85%	3.400	+20	2682 499 975	-7.4	0.000 000	-0.003



- ▣ MODE: LTE 41
- ▣ OPERATING FREQUENCY: 2680.000.000 Hz
- ▣ BANDWIDTH: 41490 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2680 000 015	0.0	0.000 000	0.000
100%		-30	2680 000 023	7.3	0.000 000	0.003
100%		-20	2680 000 037	21.3	0.000 001	0.008
100%		-10	2680 000 026	11.2	0.000 000	0.004
100%		0	2680 000 019	3.8	0.000 000	0.001
100%		+10	2680 000 023	7.5	0.000 000	0.003
100%		+30	2680 000 033	18.0	0.000 001	0.007
100%		+40	2680 000 030	15.0	0.000 001	0.006
100%		+50	2680 000 009	-6.0	0.000 000	-0.002
85%	3.400	+20	2680 000 034	19.0	0.000 001	0.007



8.8 GEO-LOCATION MECHANISM


The device uses a geo-location mechanism based on the cellular MCC codes in order to only enable certain LTE bands when the device is not in the USA.


The validation of this mechanism is provided below. The device was configured for cellular communications to a test set and the MCC code was adjusted on the test set between the US MCC and then an MCC code valid for a country where the LTE band is supported.


Band	MCC = USA	MCC = non US
7	Did not connect	Connected (Canada)
38	Did not connect	Connected (Canada)
40	Did not connect	Connected (Canada)
41	Connected	Connected (Canada)


The verification tests confirmed the operational of the geo-location mechanism.


Verification test






















9. TEST PLOTS


BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 QPSK RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 16-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 64-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 QPSK RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 16-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 64-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 QPSK RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 16-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 64-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 QPSK RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 16-QAM RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 64-QAM RB 100)




BAND 41. PAR Plot (5M BW_Ch.40620_QPSK_RB25_0)




BAND 41. PAR Plot (5M BW_Ch.40620_16QAM_RB25_0)




BAND 41. PAR Plot (5M BW_Ch.40620_64QAM_RB25_0)




BAND 41. PAR Plot (10M BW_Ch.40620_QPSK_RB50_0)




BAND 41. PAR Plot (10M BW_Ch.40620_16QAM_RB50_0)




BAND 41. PAR Plot (10M BW_Ch.40620_64QAM_RB50_0)




BAND 41. PAR Plot (15M BW_Ch.40620_QPSK_RB75_0)



BAND 41. PAR Plot (15M BW_Ch.40620_16QAM_RB75_0)




BAND 41. PAR Plot (15M BW_Ch.40620_64QAM_RB75_0)



BAND 41. PAR Plot (20M BW_Ch.40620_QPSK_RB100_0)



BAND 41. PAR Plot (20M BW_Ch.40620_16QAM_RB100_0)



BAND 41. PAR Plot (20M BW_Ch.40620_64QAM_RB100_0)

