

FCC LTE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

August 25, 2020

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Report No.: HCT-RF-2008-FC048

FCC ID: A3LSMG781V

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-G781V
 EUT Type: Mobile Phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band71 (5)	665.5 - 695.5	4M49G7D	QPSK	0.077	18.85
		4M49W7D	16QAM	0.066	18.18
		4M50W7D	64QAM	0.050	17.02
LTE – Band71 (10)	668.0 - 693.0	8M97G7D	QPSK	0.080	19.02
		8M97W7D	16QAM	0.067	18.26
		8M97W7D	64QAM	0.040	16.04
LTE – Band71 (15)	670.5 - 690.5	13M4G7D	QPSK	0.082	19.15
		13M5W7D	16QAM	0.069	18.36
		13M5W7D	64QAM	0.045	16.55
LTE – Band71 (20)	673.0 - 688.0	18M0G7D	QPSK	0.087	19.42
		17M9W7D	16QAM	0.076	18.78
		17M9W7D	64QAM	0.058	17.65

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

Report No.: HCT-RF-2008-FC048

REVIEWED BY



Report prepared by : Jae Ryang Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2008-FC048	August 25, 2020	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

REVIEWED BY	2
1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE	7
3.2 RADIATED POWER.....	8
3.3 RADIATED SPURIOUS EMISSIONS	9
3.4 OCCUPIED BANDWIDTH.	10
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	11
3.6 BAND EDGE	12
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	13
3.8 WORST CASE(RADIATED TEST)	14
3.9 WORST CASE(CONDUCTED TEST)	15
4. LIST OF TEST EQUIPMENT	16
5. MEASUREMENT UNCERTAINTY	18
6. SUMMARY OF TEST RESULTS	19
7. SAMPLE CALCULATION	20
8. TEST DATA	22
8.1 EFFECTIVE RADIATED POWER.....	22
8.2 RADIATED SPURIOUS EMISSIONS	24
8.3 OCCUPIED BANDWIDTH	28
8.4 CONDUCTED SPURIOUS EMISSIONS	29
8.5 BAND EDGE	29
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	30
9. TEST PLOTS.....	42
10. ANNEX A_ TEST SETUP PHOTO.....	91

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMG781V
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-G781V
Tx Frequency:	665.5 MHz – 695.5 MHz (LTE – Band 71 (5 MHz)) 668.0 MHz – 693.0 MHz (LTE – Band 71 (10 MHz)) 670.5 MHz – 690.5 MHz (LTE – Band 71 (15 MHz)) 673.0 MHz – 688.0 MHz (LTE – Band 71 (20 MHz))
Date(s) of Tests:	July 06, 2020 ~ August 12, 2020

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS, CDMA(BC0, 1, 10) and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac/ax (HT20/40/80), Bluetooth, BT LE, NFC, WPT, mmWave(n260/261).

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundalmatal frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

.- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

.- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature

(20°C to provide a reference).

2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter.

Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at

least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM	1	0	Z
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Y

3.9 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5,10,15,20	Mid	Full RB	0
Band Edge	QPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		5,10,15,20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5,10,15,20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
WAINWRIGHT INSTRUMENT	WHNX6.0/26.5G-6SS/H.P.F	1	03/19/2020	Annual	03/19/2021
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	04/27/2020	Annual	04/27/2021
Hewlett Packard	E3632A/DC Power Supply	MY4004427	09/27/2019	Annual	09/27/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93008124	03/18/2020	Annual	03/18/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	02/11/2020	Biennial	02/11/2022
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	04/27/2020	Annual	04/27/2021
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2020	Annual	06/04/2021
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2019	Annual	10/14/2020
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/27/2019	Annual	08/27/2020
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/26/2019	Biennial	04/26/2021
Schwarzbeck	VULB9160/ Bilog Antenna	3150	03/12/2019	Biennial	03/12/2021
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6262116770	07/22/2020	Annual	07/22/2021
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/22/2020	Annual	01/22/2021
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/13/2020	Annual	07/13/2021
KEYSIGHT	E7515B / 5G Wireless Tester	MY58300756	01/07/2020	Annual	01/07/2021
KEYSIGHT	N9030B / Signal Analyzer(5Hz~40.0GHz)	MY55480167	06/04/2020	Annual	06/04/2021
Mini-Circuits	ZC4PD-K1844+ / 4-Way Divider	942907	09/05/2019	Annual	09/05/2020
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(g)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§27.50(c)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(g)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
665.5	LTE B71 (5 MHz)	QPSK	-30.04	28.91	-9.76	1.25	H	< 3.00	0.062	17.90
		16-QAM	-30.76	28.19	-9.76	1.25	H		0.052	17.18
		64-QAM	-32.38	26.57	-9.76	1.25	H		0.036	15.56
680.5		QPSK	-29.51	29.89	-9.78	1.26	H		0.077	18.85
		16-QAM	-30.18	29.22	-9.78	1.26	H		0.066	18.18
		64-QAM	-31.34	28.06	-9.78	1.26	H		0.050	17.02
695.5		QPSK	-30.52	28.70	-9.79	1.28	H		0.058	17.63
		16-QAM	-31.24	27.98	-9.79	1.28	H		0.049	16.91
		64-QAM	-33.52	25.70	-9.79	1.28	H		0.029	14.63

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
668.0	LTE B71 (10 MHz)	QPSK	-30.06	29.01	-9.76	1.25	H	< 3.00	0.063	18.00
		16-QAM	-30.74	28.33	-9.76	1.25	H		0.054	17.32
		64-QAM	-32.24	26.83	-9.76	1.25	H		0.038	15.82
680.5		QPSK	-29.34	30.06	-9.78	1.26	H		0.080	19.02
		16-QAM	-30.10	29.30	-9.78	1.26	H		0.067	18.26
		64-QAM	-32.32	27.08	-9.78	1.26	H		0.040	16.04
693.0		QPSK	-31.49	27.68	-9.79	1.27	H		0.046	16.62
		16-QAM	-32.28	26.89	-9.79	1.27	H		0.038	15.83
		64-QAM	-34.68	24.49	-9.79	1.27	H		0.022	13.43

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
670.5	LTE B71 (15 MHz)	QPSK	-30.06	29.13	-9.77	1.25	H	< 3.00	0.065	18.11
		16-QAM	-30.72	28.47	-9.77	1.25	H		0.056	17.45
		64-QAM	-32.05	27.14	-9.77	1.25	H		0.041	16.12
680.5		QPSK	-29.21	30.19	-9.78	1.26	H		0.082	19.15
		16-QAM	-30.00	29.40	-9.78	1.26	H		0.069	18.36
		64-QAM	-32.23	27.17	-9.78	1.26	H		0.041	16.13
690.5		QPSK	-29.81	29.43	-9.79	1.27	H		0.069	18.37
		16-QAM	-30.63	28.61	-9.79	1.27	H		0.057	17.55
		64-QAM	-31.63	27.61	-9.79	1.27	H		0.045	16.55

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W dBm
673.0	LTE B71 (20 MHz)	QPSK	-30.01	29.23	-9.77	1.25	H	< 3.00	0.066	18.21
		16-QAM	-30.73	28.51	-9.77	1.25	H		0.056	17.49
		64-QAM	-32.44	26.80	-9.77	1.25	H		0.038	15.78
680.5		QPSK	-28.94	30.46	-9.78	1.26	H		0.087	19.42
		16-QAM	-29.58	29.82	-9.78	1.26	H		0.076	18.78
		64-QAM	-30.71	28.69	-9.78	1.26	H		0.058	17.65
688.0		QPSK	-29.39	29.91	-9.78	1.27	H		0.077	18.86
		16-QAM	-30.12	29.18	-9.78	1.27	H		0.065	18.13
		64-QAM	-31.24	28.06	-9.78	1.27	H		0.050	17.01

8.2 RADIATED SPURIOUS EMISSIONS

- ▣ MODE: LTE B71
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
133147 (665.5)	1,331.00	-50.81	6.95	-58.82	1.79	V	-53.66	-13.00
	1,996.50	-48.03	10.39	-54.86	2.21	H	-46.68	-13.00
	2,662.00	-54.79	11.10	-57.07	2.59	V	-48.56	-13.00
133297 (680.5)	1,361.00	-50.75	7.23	-58.60	1.81	V	-53.18	-13.00
	2,041.50	-48.33	10.25	-53.85	2.23	H	-45.83	-13.00
	2,722.00	-54.86	11.05	-57.33	2.61	V	-48.89	-13.00
133447 (695.5)	1,391.00	-50.77	7.48	-59.60	1.84	V	-53.96	-13.00
	2,086.50	-48.43	9.95	-52.71	2.26	H	-45.02	-13.00
	2,782.00	-54.93	10.95	-56.52	2.62	V	-48.19	-13.00

MODE: LTE B71
 MODULATION SIGNAL: 10 MHz QPSK
 DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
133172 (668.0)	1,336.00	-50.88	6.99	-58.52	1.80	V	-53.33	-13.00
	2,004.00	-48.41	10.38	-54.98	2.22	H	-46.82	-13.00
	2,672.00	-54.73	11.10	-57.22	2.57	V	-48.69	-13.00
133297 (680.5)	1,361.00	-50.78	7.23	-58.63	1.81	V	-53.21	-13.00
	2,041.50	-48.35	10.25	-53.87	2.23	H	-45.85	-13.00
	2,722.00	-54.68	11.05	-57.15	2.61	V	-48.71	-13.00
133422 (693.0)	1,386.00	-50.88	7.42	-59.42	1.83	V	-53.83	-13.00
	2,079.00	-48.05	10.00	-52.62	2.26	H	-44.88	-13.00
	2,772.00	-54.72	10.95	-56.49	2.64	V	-48.18	-13.00

- ▣ MODE: LTE B71
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
133197 (670.5)	1,341.00	-50.64	7.03	-57.93	1.80	V	-52.70	-13.00
	2,011.50	-48.18	10.35	-54.62	2.22	H	-46.49	-13.00
	2,682.00	-54.78	11.10	-56.79	2.57	V	-48.26	-13.00
133297 (680.5)	1,361.00	-50.60	7.23	-58.45	1.81	V	-53.03	-13.00
	2,041.50	-48.40	10.25	-53.92	2.23	H	-45.90	-13.00
	2,722.00	-54.73	11.05	-57.20	2.61	V	-48.76	-13.00
133397 (690.5)	1,381.00	-50.54	7.35	-58.79	1.82	V	-53.26	-13.00
	2,071.50	-48.24	10.00	-52.69	2.26	H	-44.95	-13.00
	2,762.00	-54.96	10.98	-56.94	2.66	V	-48.62	-13.00

MODE: LTE B71
 MODULATION SIGNAL: 20 MHz QPSK
 DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
133222 (673.0)	1,346.00	-50.70	7.07	-58.57	1.80	V	-53.30	-13.00
	2,019.00	-48.18	10.30	-54.08	2.23	H	-46.01	-13.00
	2,692.00	-54.86	11.10	-57.20	2.59	V	-48.69	-13.00
133297 (680.5)	1,361.00	-50.45	7.23	-58.30	1.81	V	-52.88	-13.00
	2,041.50	-47.98	10.25	-53.50	2.23	H	-45.48	-13.00
	2,722.00	-54.60	11.05	-57.07	2.61	V	-48.63	-13.00
133372 (688.0)	1,376.00	-50.69	7.35	-59.17	1.82	V	-53.64	-13.00
	2,064.00	-48.15	10.05	-52.97	2.25	H	-45.17	-13.00
	2,752.00	-54.87	11.00	-57.26	2.65	V	-48.91	-13.00

8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
71	5 MHz	680.5	QPSK	25	0	4.4929
			16-QAM			4.4848
			64-QAM			4.5040
	10 MHz		QPSK	50		8.9661
			16-QAM			8.9668
			64-QAM			8.9726
	15 MHz		QPSK	75		13.420
			16-QAM			13.462
			64-QAM			13.457
	20 MHz	QPSK	100	17.946		
		16-QAM		17.890		
		64-QAM		17.919		

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 43 ~ 54.

8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
71	5	665.5	3.7393	27.976	-67.561	-39.585	-13.00
		680.5	3.7089	27.976	-67.323	-39.347	
		695.5	3.7089	27.976	-67.094	-39.118	
	10	668.0	3.7000	27.976	-66.840	-38.864	
		680.5	3.6780	27.976	-67.207	-39.231	
		693.0	3.7104	27.976	-67.519	-39.543	
	15	670.5	3.6865	27.976	-67.377	-39.401	
		680.5	3.7104	27.976	-67.233	-39.257	
		690.5	3.7104	27.976	-66.957	-38.981	
	20	673.0	3.7109	27.976	-67.114	-39.138	
		680.5	3.6795	27.976	-66.797	-38.821	
		688.0	3.6835	27.976	-66.657	-38.681	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 79 ~ 90.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 55 ~ 78.

8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 665,500,000 Hz
- ▣ CHANNEL: 133147 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	665 500 003	0.0	0.000 000	0.000
100%		-30	665 500 008	4.2	0.000 001	0.006
100%		-20	665 500 010	6.4	0.000 001	0.010
100%		-10	665 500 008	4.8	0.000 001	0.007
100%		0	665 500 007	3.9	0.000 001	0.006
100%		+10	665 500 007	3.8	0.000 001	0.006
100%		+30	665 500 010	6.7	0.000 001	0.010
100%		+40	665 500 008	4.7	0.000 001	0.007
100%		+50	665 500 008	4.9	0.000 001	0.007
Batt. Endpoint		3.400	+20	665 500 009	6.0	0.000 001




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 668,000,000 Hz
- ▣ CHANNEL: 133172 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	668 000 005	0.0	0.000 000	0.000
100%		-30	668 000 010	4.7	0.000 001	0.007
100%		-20	668 000 009	3.6	0.000 001	0.005
100%		-10	668 000 009	4.5	0.000 001	0.007
100%		0	668 000 009	4.3	0.000 001	0.006
100%		+10	668 000 010	4.8	0.000 001	0.007
100%		+30	668 000 012	7.0	0.000 001	0.010
100%		+40	668 000 010	5.0	0.000 001	0.007
100%		+50	668 000 014	9.2	0.000 001	0.014
Batt. Endpoint		3.400	+20	668 000 009	3.6	0.000 001




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 670,500,000 Hz
- ▣ CHANNEL: 133197 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	670 500 007	0.0	0.000 000	0.000
100%		-30	670 500 011	4.1	0.000 001	0.006
100%		-20	670 500 014	7.4	0.000 001	0.011
100%		-10	670 500 013	6.5	0.000 001	0.010
100%		0	670 500 012	5.9	0.000 001	0.009
100%		+10	670 500 014	7.3	0.000 001	0.011
100%		+30	670 500 012	5.5	0.000 001	0.008
100%		+40	670 500 011	4.1	0.000 001	0.006
100%		+50	670 500 014	7.1	0.000 001	0.011
Batt. Endpoint	3.400	+20	670 500 013	6.5	0.000 001	0.010




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 673,000,000 Hz
- ▣ CHANNEL: 133222 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	673 000 004	0.0	0.000 000	0.000
100%		-30	673 000 008	4.0	0.000 001	0.006
100%		-20	673 000 007	3.8	0.000 001	0.006
100%		-10	673 000 007	3.3	0.000 000	0.005
100%		0	673 000 002	-1.2	0.000 000	-0.002
100%		+10	673 000 007	3.1	0.000 000	0.005
100%		+30	673 000 009	5.5	0.000 001	0.008
100%		+40	673 000 007	3.2	0.000 000	0.005
100%		+50	673 000 008	4.5	0.000 001	0.007
Batt. Endpoint	3.400	+20	673 000 006	2.1	0.000 000	0.003




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 680,500,000 Hz
- ▣ CHANNEL: 133297 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	680 499 999	0.0	0.000 000	0.000
100%		-30	680 500 001	2.6	0.000 000	0.004
100%		-20	680 499 996	-2.5	0.000 000	-0.004
100%		-10	680 500 001	2.1	0.000 000	0.003
100%		0	680 500 001	2.6	0.000 000	0.004
100%		+10	680 500 002	2.9	0.000 000	0.004
100%		+30	680 500 002	3.3	0.000 000	0.005
100%		+40	680 500 004	5.0	0.000 001	0.007
100%		+50	680 500 002	3.4	0.000 000	0.005
Batt. Endpoint	3.400	+20	680 500 001	1.9	0.000 000	0.003




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 680,500,000 Hz
- ▣ CHANNEL: 133297 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	680 500 006	0.0	0.000 000	0.000
100%		-30	680 500 011	4.8	0.000 001	0.007
100%		-20	680 500 011	5.2	0.000 001	0.008
100%		-10	680 500 013	7.0	0.000 001	0.010
100%		0	680 500 012	6.2	0.000 001	0.009
100%		+10	680 500 013	6.7	0.000 001	0.010
100%		+30	680 500 012	5.9	0.000 001	0.009
100%		+40	680 500 012	6.0	0.000 001	0.009
100%		+50	680 500 013	7.0	0.000 001	0.010
Batt. Endpoint	3.400	+20	680 500 012	5.8	0.000 001	0.009




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 680,500,000 Hz
- ▣ CHANNEL: 133297 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	680 500 004	0.0	0.000 000	0.000
100%		-30	680 500 011	6.4	0.000 001	0.009
100%		-20	680 500 010	5.4	0.000 001	0.008
100%		-10	680 500 008	3.4	0.000 000	0.005
100%		0	680 500 010	5.4	0.000 001	0.008
100%		+10	680 500 009	4.7	0.000 001	0.007
100%		+30	680 500 008	4.0	0.000 001	0.006
100%		+40	680 500 007	2.9	0.000 000	0.004
100%		+50	680 500 009	4.5	0.000 001	0.007
Batt. Endpoint	3.400	+20	680 500 008	3.3	0.000 000	0.005




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 680,500,000 Hz
- ▣ CHANNEL: 133297 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	680 500 005	0.0	0.000 000	0.000
100%		-30	680 500 009	3.9	0.000 001	0.006
100%		-20	680 500 007	1.5	0.000 000	0.002
100%		-10	680 500 013	8.1	0.000 001	0.012
100%		0	680 500 011	5.5	0.000 001	0.008
100%		+10	680 500 012	7.3	0.000 001	0.011
100%		+30	680 500 011	6.2	0.000 001	0.009
100%		+40	680 500 010	4.9	0.000 001	0.007
100%		+50	680 500 011	6.3	0.000 001	0.009
Batt. Endpoint	3.400	+20	680 500 013	7.8	0.000 001	0.011




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 695,500,000 Hz
- ▣ CHANNEL: 133447 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	695 500 002	0.0	0.000 000	0.000
100%		-30	695 500 007	4.7	0.000 001	0.007
100%		-20	695 500 006	4.5	0.000 001	0.006
100%		-10	695 500 007	5.2	0.000 001	0.007
100%		0	695 500 006	4.0	0.000 001	0.006
100%		+10	695 500 005	3.4	0.000 000	0.005
100%		+30	695 500 001	-1.0	0.000 000	-0.001
100%		+40	695 500 006	3.8	0.000 001	0.005
100%		+50	695 500 012	9.9	0.000 001	0.014
Batt. Endpoint	3.400	+20	695 500 000	-1.9	0.000 000	-0.003




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 693,000,000 Hz
- ▣ CHANNEL: 133422 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	692 999 995	0.0	0.000 000	0.000
100%		-30	692 999 990	-4.4	-0.000 001	-0.006
100%		-20	692 999 989	-5.4	-0.000 001	-0.008
100%		-10	692 999 988	-7.1	-0.000 001	-0.010
100%		0	692 999 988	-7.3	-0.000 001	-0.011
100%		+10	692 999 992	-3.0	0.000 000	-0.004
100%		+30	692 999 986	-8.4	-0.000 001	-0.012
100%		+40	692 999 989	-5.8	-0.000 001	-0.008
100%		+50	692 999 987	-7.7	-0.000 001	-0.011
Batt. Endpoint	3.400	+20	692 999 989	-5.5	-0.000 001	-0.008




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 690,500,000 Hz
- ▣ CHANNEL: 133397 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	690 499 997	0.0	0.000 000	0.000
100%		-30	690 499 991	-6.5	-0.000 001	-0.009
100%		-20	690 499 990	-6.9	-0.000 001	-0.010
100%		-10	690 499 994	-3.4	0.000 000	-0.005
100%		0	690 499 991	-6.1	-0.000 001	-0.009
100%		+10	690 499 991	-6.3	-0.000 001	-0.009
100%		+30	690 499 991	-5.9	-0.000 001	-0.009
100%		+40	690 499 990	-6.8	-0.000 001	-0.010
100%		+50	690 499 989	-7.9	-0.000 001	-0.011
Batt. Endpoint	3.400	+20	690 499 994	-3.1	0.000 000	-0.004




- ▣ MODE: LTE B71
- ▣ OPERATING FREQUENCY: 688,000,000 Hz
- ▣ CHANNEL: 133372 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	687 999 995	0.0	0.000 000	0.000
100%		-30	687 999 992	-3.2	0.000 000	-0.005
100%		-20	687 999 989	-6.1	-0.000 001	-0.009
100%		-10	687 999 988	-7.3	-0.000 001	-0.011
100%		0	687 999 990	-5.1	-0.000 001	-0.007
100%		+10	687 999 989	-6.8	-0.000 001	-0.010
100%		+30	687 999 992	-3.9	-0.000 001	-0.006
100%		+40	687 999 989	-6.4	-0.000 001	-0.009
100%		+50	687 999 991	-4.9	-0.000 001	-0.007
Batt. Endpoint	3.400	+20	687 999 990	-5.1	-0.000 001	-0.007




9. TEST PLOTS


BAND 71. Occupied Bandwidth Plot (5M BW Ch.133297 QPSK_RB6_0)




BAND 71. Occupied Bandwidth Plot (5M BW Ch.133297 16QAM_RB6_0)




BAND 71. Occupied Bandwidth Plot (5M BW Ch.133297 64QAM_RB6_0)




BAND 71. Occupied Bandwidth Plot (10M BW Ch.133297 QPSK_RB15_0)




BAND 71. Occupied Bandwidth Plot (10M BW Ch.133297 16QAM_RB15_0)




BAND 71. Occupied Bandwidth Plot (10M BW Ch.133297 64QAM_RB15_0)




BAND 71. Occupied Bandwidth Plot (15M BW Ch.133297 QPSK_RB25_0)




BAND 71. Occupied Bandwidth Plot (15M BW Ch.133297 16QAM_RB25_0)




BAND 71. Occupied Bandwidth Plot (15M BW Ch.133297 64QAM_RB25_0)




BAND 71. Occupied Bandwidth Plot (20M BW Ch.133297 QPSK_RB50_0)




BAND 71. Occupied Bandwidth Plot (20M BW Ch.133297 16QAM_RB50_0)



BAND 71. Occupied Bandwidth Plot (20M BW Ch.133297 64QAM_RB50_0)



BAND 71. Lower Band Edge Plot (5M BW Ch.133147 QPSK_RB1_Offset 0)



BAND 71. Lower Extended Band Edge Plot (5M BW Ch.133147 QPSK_RB6_0)




BAND 71. Lower Band Edge Plot (10M BW Ch.133172 QPSK_RB1_Offset 0)



BAND 71. Lower Band Edge Plot (10M BW Ch.133172 QPSK_RB15_Offset 0)



BAND 71. Lower Extended Band Edge Plot (10M BW Ch.133172 QPSK_RB15_0)



BAND 71. Lower Extended Band Edge Plot (15M BW Ch.133197 QPSK_RB25_0)



BAND 71. Lower Band Edge Plot (20M BW Ch.133222 QPSK_RB50_Offset 0)



BAND 71. Lower Extended Band Edge Plot (20M BW Ch.133222 QPSK_RB50_0)



BAND 71. Upper Band Edge Plot (5M BW Ch.133447 QPSK_RB1_Offset 5)_1



BAND 71. Upper Extended Band Edge Plot (5M BW Ch.133447 QPSK_RB6_0)



BAND 71. Upper Band Edge Plot (10M BW Ch.133422 QPSK_RB1_Offset 14)-1



BAND 71. Upper Band Edge Plot (10M BW Ch.133422 QPSK_RB1_Offset 14)-2



BAND 71. Upper Extended Band Edge Plot (10M BW Ch.133422 QPSK_RB15_0)



BAND 71. Upper Band Edge Plot (15M BW Ch.133397 QPSK_RB1_Offset 24)



BAND 71. Upper Extended Band Edge Plot (15M BW Ch.133397 QPSK_RB25_0)



BAND 71. Upper Band Edge Plot (20M BW Ch.133372 QPSK_RB1_Offset 49)




BAND 71. Upper Band Edge Plot (20M BW Ch.133372 QPSK_RB50_Offset 0)




BAND 71. Upper Extended Band Edge Plot (20M BW Ch.133372 QPSK_RB50_0)




BAND 71. Conducted Spurious Plot _ (133147ch_5MHz_QPSK_RB 1_0)




BAND 71. Conducted Spurious Plot _ (133297ch_5MHz_QPSK_RB 1_0)




BAND 71. Conducted Spurious Plot _ (133447ch_5MHz_QPSK_RB 1_0)



BAND 71. Conducted Spurious Plot _ (133397ch_15MHz_QPSK_RB 1_0)



BAND 71. Conducted Spurious Plot _ (133297ch_20MHz_QPSK_RB 1_0)



10. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2008-FC048-P