



## SAR EVALUATION REPORT

**Applicant Name:**  
 Samsung Electronics, Co. Ltd.  
 129, Samsung-ro, Maetan dong,  
 Yeongtong-gu, Suwon-si  
 Gyeonggi-do 443-742, Korea

**Date of Testing:**  
 06/09/14 - 07/24/14  
**Test Site/Location:**  
 PCTEST Lab, Columbia, MD, USA  
**Document Serial No.:**  
 OY1407111375.A3L

**FCC ID:** A3LSMG850M


**APPLICANT:** SAMSUNG ELECTRONICS, CO. LTD.

**DUT Type:** Portable Handset  
**Application Type:** Certification  
**FCC Rule Part(s):** CFR §2.1093  
**Model(s):** SM-G850M

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.32	0.49	0.56
PCE	UMTS 850	826.40 - 846.60 MHz	0.27	0.44	0.46
PCE	UMTS 1750	1712.4 - 1752.5 MHz	0.29	0.69	1.02
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.56	0.40	0.71
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.47	0.50	0.77
PCE	LTE Band 17	706.5 - 713.5 MHz	0.11	0.19	0.22
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.28	0.40	0.40
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.33	0.62	0.92
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.41	0.54	0.68
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.13	0.13	0.16
DTS	5.8 GHz WLAN	5745 - 5825 MHz	0.16	< 0.1	
NII	5.2 GHz WLAN	5180 - 5240 MHz	< 0.1	< 0.1	
NII	5.3 GHz WLAN	5260 - 5320 MHz	0.15	< 0.1	
NII	5.5 GHz WLAN	5500 - 5700 MHz	0.11	< 0.1	
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A		
<b>Simultaneous SAR per KDB 690783 D01v01r03:</b>			0.76	0.96	1.02



This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

  
 Randy Ortanez  
 President





The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMG850M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 1 of 71

# T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST .....	3
2	LTE INFORMATION .....	9
3	INTRODUCTION .....	10
4	DOSIMETRIC ASSESSMENT .....	11
5	DEFINITION OF REFERENCE POINTS .....	12
6	TEST CONFIGURATION POSITIONS FOR HANDSETS .....	13
7	RF EXPOSURE LIMITS .....	16
8	FCC MEASUREMENT PROCEDURES.....	17
9	RF CONDUCTED POWERS.....	22
10	SYSTEM VERIFICATION.....	40
11	SAR DATA SUMMARY .....	43
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	55
13	SAR MEASUREMENT VARIABILITY .....	64
14	EQUIPMENT LIST.....	65
15	MEASUREMENT UNCERTAINTIES .....	67
16	CONCLUSION.....	69
17	REFERENCES .....	70
APPENDIX A:	SAR TEST PLOTS	
APPENDIX B:	SAR DIPOLE VERIFICATION PLOTS	
APPENDIX C:	PROBE AND DIPOLE CALIBRATION CERTIFICATES	
APPENDIX D:	SAR TISSUE SPECIFICATIONS	
APPENDIX E:	SAR SYSTEM VALIDATION	
APPENDIX F:	SAR TEST SETUP PHOTOGRAPHS	

<b>FCC ID:</b> A3LSMG850M	 <b>PCTEST</b> <small>ENGINEERING LEADERSHIP, INC.</small>	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset	Page 2 of 71	

# 1 DEVICE UNDER TEST

## 1.1 Device Overview



Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.5 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
5.8 GHz WLAN	Data	5745 - 5825 MHz
5.2 GHz WLAN	Data	5180 - 5240 MHz
5.3 GHz WLAN	Data	5260 - 5320 MHz
5.5 GHz WLAN	Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz

## 1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.



Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
			1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots
GSM/GPRS/EDGE 850	Maximum	34.0	34.0	31.5	29.5	28.5	28.0	25.5	24.0	22.5
	Nominal	33.5	33.5	31.0	29.0	28.0	27.5	25.0	23.5	22.0
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	28.0	26.5	25.0	26.0	23.5	22.0	20.5
	Nominal	30.0	30.0	27.5	26.0	24.5	25.5	23.0	21.5	20.0

Mode / Band		Modulated Average (dBm)			
		3GPP Rel 99	3GPP Rel 5	3GPP Rel 6	3GPP Rel 8
		WCDMA	HSDPA	HSUPA	DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	24.5	24.5	24.5	24.5
	Nominal	24.0	24.0	24.0	24.0
UMTS Band 4 (1750 MHz)	Maximum	21.5	21.5	21.5	21.5
	Nominal	21.0	21.0	21.0	21.0
UMTS Band 2 (1900 MHz)	Maximum	22.0	22.0	22.0	22.0
	Nominal	21.5	21.5	21.5	21.5


FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 3 of 71

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	<b>24.0</b>
	Nominal	<b>23.5</b>
LTE Band 5 (Cell)	Maximum	<b>23.5</b>
	Nominal	<b>23.0</b>
LTE Band 4 (AWS)	Maximum	<b>22.0</b>
	Nominal	<b>21.5</b>
LTE Band 2 (PCS)	Maximum	<b>22.5</b>
	Nominal	<b>22.0</b>

Mode / Band		Modulated Average (dBm)
SISO IEEE 802.11b (2.4 GHz)	Maximum	<b>17.5</b>
	Nominal	<b>17.0</b>
SISO IEEE 802.11g (2.4 GHz)	Maximum	<b>11.5</b>
	Nominal	<b>11.0</b>
SISO IEEE 802.11n (2.4 GHz)	Maximum	<b>10.5</b>
	Nominal	<b>10.0</b>
MIMO IEEE 802.11n (2.4 GHz)	Maximum	<b>10.5</b>
	Nominal	<b>10.0</b>
SISO IEEE 802.11a (5 GHz)	Maximum	<b>10.5</b>
	Nominal	<b>10.0</b>
SISO & MIMO IEEE 802.11n (5 GHz) 20 MHz Bandwidth	Maximum	<b>10.5</b>
	Nominal	<b>10.0</b>
SISO & MIMO IEEE 802.11n (5 GHz) 40 MHz Bandwidth	Maximum	<b>9.5</b>
	Nominal	<b>9.0</b>
SISO & MIMO IEEE 802.11ac (5 GHz) 80 MHz Bandwidth	Maximum	<b>8.5</b>
	Nominal	<b>8.0</b>
Bluetooth	Maximum	<b>11.0</b>
	Nominal	<b>10.5</b>
Bluetooth LE	Maximum	<b>7.0</b>
	Nominal	<b>6.5</b>

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: 0Y1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 4 of 71

### 1.3 DUT Antenna Locations



1. Main Antenna
  - 850/1900 MHz GSM/GPRS/EDGE (Tx/Rx)
  - 850/1750/1900 MHz UMTS (Tx/Rx)
  - LTE B/17/5/4/2 (Tx/Rx)
2. BT/WIFI Antenna 1
  - 2.4/5 GHz WIFI (Tx/Rx)
  - 2.4 GHz BT (Tx/Rx)
3. WIFI Antenna 2
  - 2.4/5 GHz WIFI (Tx/Rx)
4. Antenna 4
  - GPS (Rx only)
  - 850/1750/1900 MHz UMTS (Rx only)
  - LTE B17/5/4/2 (Rx only)

Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

**Figure 1-1  
DUT Antenna Locations**

**Table 1-1  
Mobile Hotspot Sides for SAR Testing**


Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 17	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz Antenna 1 WLAN	Yes	Yes	Yes	No	No	Yes
2.4 GHz Antenna 2 WLAN	Yes	Yes	Yes	No	Yes	No
2.4 GHz MIMO WLAN	Yes	Yes	Yes	No	Yes	Yes

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, all 5 GHz bands are disabled. Therefore 5 GHz WIFI is not considered in this section.

FCC ID: A3LSMG850M	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 5 of 71

## 1.4 Near Field Communications (NFC) Antenna


This DUT has NFC operations. The NFC antenna is integrated into the specialized battery. The SAR tests were performed with the specialize battery (model: EB-BG850BBE).



**Figure 1-2**  
NFC Antenna Locations



## 1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-3 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another. This device supports MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.



**Figure 1-3**  
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 6 of 71

**Table 1-2  
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	
5	UMTS + 5 GHz WI-FI	Yes	Yes	N/A	
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
7	LTE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	*-Pre-installed VOIP applications are considered.
8	LTE + 2.4 GHz Bluetooth	N/A	Yes*	N/A	*-Pre-installed VOIP applications are considered.
9	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes	
10	LTE + 5 GHz WI-FI	N/A	N/A	N/A	Not supported by SW
11	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	N/A	Not supported by SW

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. When wireless router mode is enabled, all 5GHz bands are disabled.
5. This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.

## 1.6 SAR Test Exclusions Applied

### (A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using 5 GHz WIFI, only 2.4 GHz WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v01.



Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required;  $[(13/10) * \sqrt{2.480}] = 2.0 < 3.0$ . Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) No new 5 GHz channels

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 7 of 71

## (B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

## 1.7 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.



## 1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v02, D03v01, D05v02r03, D06v01r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- April 2013 TCB Workshop Notes (IEEE 802.11ac)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

## 1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.



	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	1107-1	1107-1	1107-1
UMTS 850	1107-1	1107-1	1107-1
UMTS 1750	1107-1	1107-2	1107-2
GSM/GPRS/EDGE 1900	1107-2	1107-2	1107-2
UMTS 1900	1107-2	1107-2	1107-2
LTE Band 17	1107-1	1107-1	1107-1
LTE Band 5 (Cell)	1107-1	1107-1	1107-1
LTE Band 4 (AWS)	1107-1	1107-2	1107-2
LTE Band 2 (PCS)	1107-1	1107-2	1107-2
2.4 GHz WLAN	0707-1	0906-1	0906-1
5 GHz WLAN	0906-1	0906-2	-

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 8 of 71

## 2

## LTE INFORMATION

LTE Information			
FCC ID	A3LSMG850M		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	4		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 9 of 71

## 3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**  
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$



**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material ( $\text{kg/m}^3$ )
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 10 of 71

## 4 DOSIMETRIC ASSESSMENT

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.





**Figure 4-1**  
Sample SAR Area Scan

**Table 4-1**  
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01\*

Frequency	Maximum Area Scan Resolution (mm) ( $\Delta x_{area}, \Delta y_{area}$ )	Maximum Zoom Scan Resolution (mm) ( $\Delta x_{zoom}, \Delta y_{zoom}$ )	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid $\Delta z_{zoom}(n)$	Graded Grid		
				$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22

\*Also compliant to IEEE 1528-2013 Table 6


FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 11 of 71

# 5

## DEFINITION OF REFERENCE POINTS

### 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**  
Close-Up Side view of ERP

### 5.2 HANDSET REFERENCE POINTS



Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 5-2**  
Front, back and side view of SAM Twin Phantom



**Figure 5-3**  
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 12 of 71

## 6 TEST CONFIGURATION POSITIONS FOR HANDSETS

### 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ .

### 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position


2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

### 6.3 Positioning for Ear / 15° Tilt


With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 13 of 71



**Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position**



**Figure 6-3 Side view w/ relevant markings**


## 6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04\_v01. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.



## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



**Figure 6-4 Sample Body-Worn Diagram**

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 14 of 71

that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations



Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset	Page 15 of 71	

# 7 RF EXPOSURE LIMITS

## 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



## 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1  
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
<b>Peak Spatial Average SAR</b> Head	1.6	8.0
<b>Whole Body SAR</b>	0.08	0.4
<b>Peak Spatial Average SAR</b> Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 16 of 71

## 8 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

### 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

### 8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

### 8.3 SAR Measurement Conditions for UMTS



#### 8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

#### 8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 17 of 71

### 8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”.

### 8.3.4 SAR Measurements for Handsets with Rel 5 HSDPA

Body SAR for HSDPA is not required for handsets with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of  $\beta_c=9$  and  $\beta_d=15$ , and power offset parameters of  $\Delta_{ACK} = \Delta_{NACK} = 5$  and  $\Delta_{CQI}=2$  is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

Sub-Test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{HS} = \beta_{HS}/\beta_c = 30/15 \Leftrightarrow \beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 8$  ( $A_{HS} = 30/15$ ) with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 7$  ( $A_{HS} = 24/15$ ) with  $\beta_{HS} = 24/15 * \beta_c$ .



Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

**Figure 8-1**  
**Table C.10.1.4 of TS 234.121-1**

### 8.3.5 SAR Measurements for Handsets with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under “Release 6 HSPA data devices”

Head SAR for VOIP operations under HSPA is not required when maximum average output of each RF channel with HSPA is less than 0.25 dB higher than as measured using 12.2 kbps RMC. Otherwise SAR is measured using same HSPA configuration as used for body SAR.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 18 of 71

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed}: 47/15$ $\beta_{ec}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{15} = \beta_{15}/\beta_c = 30/15 \Leftrightarrow \beta_{15} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{15}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

### 8.3.6 SAR Measurement Conditions for DC-HSDPA

SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion. DC-HSDPA uplink maximum output power measurements using the four Rel. 5 HSDPA subtests in Table C.10.1.4 of TS 234.121-1 is required.

When the maximum average output power of each RF channel with DC-HSDPA active is  $\leq 1/4$  dB higher than that measured using 12.2 kbps RMC, or the maximum reported SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit, SAR evaluation for DC-HSDPA is not required.

## 8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.4.1 Spectrum Plots for RB Configurations



A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 19 of 71

## 8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

## 8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n/ac transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.



### 8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

### 8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power than the default channels, these "required channels" were considered instead of the default channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was higher than 0.25 dB or more than the 802.11a mode. 802.11ac SAR was



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 20 of 71

evaluated for highest 802.11a configuration in each 5 GHz band and each exposure condition. 802.11ac modes were additionally evaluated for SAR if the output power for the respective mode was more than 0.25 dB higher than powers of 802.11a modes.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

### 8.5.3 MIMO SAR considerations

Per KDB 248227, SAR for MIMO was measured with both transmitting simultaneously and was evaluated independently of SISO operation. For 2.4 GHz MIMO, 802.11n was evaluated. For 5 GHz MIMO, 20 MHz bandwidth 802.11n was evaluated. Other IEEE 802.11 modes and bandwidths were not investigated for MIMO operations since the maximum allowed output power (including tolerance) was not higher for these modes.

FCC ID: A3LSMG850M	 <b>PCTEST</b> <small>ENGINEERING LABORATORY, INC.</small>	<b>SAR EVALUATION REPORT</b>	 <b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset	Page 21 of 71

# 9 RF CONDUCTED POWERS


## 9.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	33.58	33.64	30.88	29.29	<b>27.87</b>	27.65	25.13	23.55	22.16
	190	33.62	33.63	30.85	29.20	<b>27.84</b>	27.64	25.15	23.47	22.15
	251	33.76	33.76	31.24	29.48	<b>28.15</b>	27.67	25.19	23.53	22.18
GSM 1900	512	30.39	30.49	27.91	<b>26.23</b>	24.84	25.91	23.33	21.72	20.33
	661	30.24	30.33	27.76	<b>26.11</b>	24.64	25.70	23.10	21.49	20.06
	810	30.31	30.40	27.78	<b>26.09</b>	24.69	25.61	23.02	21.40	20.11
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	24.55	24.61	24.86	25.03	<b>24.86</b>	18.62	19.11	19.29	19.15
	190	24.59	24.60	24.83	24.94	<b>24.83</b>	18.61	19.13	19.21	19.14
	251	24.73	24.73	25.22	25.22	<b>25.14</b>	18.64	19.17	19.27	19.17
GSM 1900	512	21.36	21.46	21.89	<b>21.97</b>	21.83	16.88	17.31	17.46	17.32
	661	21.21	21.30	21.74	<b>21.85</b>	21.63	16.67	17.08	17.23	17.05
	810	21.28	21.37	21.76	<b>21.83</b>	21.68	16.58	17.00	17.14	17.10
GSM 850	Frame	24.47	24.47	24.98	24.74	<b>24.99</b>	18.47	18.98	19.24	18.99
GSM 1900	Avg.Targets:	20.97	20.97	21.48	<b>21.74</b>	21.49	16.47	16.98	17.24	16.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. Per October 2013 TCB Workshop Notes, the configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

**GSM Class: B**  
**GPRS Multislot class: 33 (Max 4 Tx uplink slots)**  
**EDGE Multislot class: 33 (Max 4 Tx uplink slots)**  
**DTM Multislot Class: N/A**



**Figure 9-1**  
**Power Measurement Setup**

FCC ID: A3LSMG850M	PCTEST INDEPENDENT LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 22 of 71

## 9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1862	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.07	24.29	24.35	21.41	21.48	21.13	21.92	21.68	21.46	-
99		12.2 kbps AMR	24.05	24.25	24.32	21.38	21.46	21.19	21.97	21.75	21.51	-
6	HSDPA	Subtest 1	23.90	24.13	24.21	21.40	21.38	21.02	21.87	21.65	21.44	0
6		Subtest 2	23.61	23.79	23.86	21.15	21.09	20.74	21.63	21.43	21.26	0
6		Subtest 3	23.34	23.52	23.61	20.85	20.83	20.47	21.34	21.12	20.97	0.5
6		Subtest 4	23.17	23.28	23.42	20.61	20.62	20.25	21.12	20.90	20.72	0.5
6	HSUPA	Subtest 1	23.02	23.20	23.31	21.15	21.09	20.76	21.63	21.44	21.20	0
6		Subtest 2	20.76	20.94	21.10	19.20	19.36	19.08	19.92	19.47	19.53	2
6		Subtest 3	21.56	21.76	21.85	20.17	20.12	19.80	20.68	20.45	20.25	1
6		Subtest 4	20.92	21.10	21.33	19.66	19.60	19.28	20.17	19.98	19.73	2
6		Subtest 5	23.00	23.22	23.27	21.19	21.05	20.74	21.67	21.47	21.22	0
8	DC-HSDPA	Subtest 1	23.89	24.06	24.10	21.43	21.48	21.16	21.73	21.57	21.38	0
8		Subtest 2	23.49	23.63	24.06	21.42	21.44	21.12	21.67	21.53	21.42	0
8		Subtest 3	22.95	23.14	23.80	21.28	21.29	20.89	21.42	21.29	21.25	0.5
8		Subtest 4	22.93	23.14	23.79	21.29	21.24	20.87	21.41	21.32	21.20	0.5

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.



### DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- Measured maximum output powers for DC-HSDPA were not greater than 1/4 dB higher than the WCDMA 12.2 kbps RMC maximum output, as a result, SAR is not required for DC-HSDPA
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.



**Figure 9-2**  
**Power Measurement Setup**

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 23 of 71

## 9.3 LTE Conducted Powers

### 9.3.1 LTE Band 17

**Table 9-1**  
**LTE Band 17 Conducted Powers - 10 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
710.0	23790	10	QPSK	1	0	23.75	0	0
710.0	23790	10	QPSK	1	25	23.60	0	0
710.0	23790	10	QPSK	1	49	23.62	0	0
710.0	23790	10	QPSK	25	0	22.70	0-1	1
710.0	23790	10	QPSK	25	12	22.64	0-1	1
710.0	23790	10	QPSK	25	25	22.67	0-1	1
710.0	23790	10	QPSK	50	0	22.65	0-1	1
710.0	23790	10	16QAM	1	0	22.96	0-1	1
710.0	23790	10	16QAM	1	25	22.78	0-1	1
710.0	23790	10	16QAM	1	49	22.89	0-1	1
710.0	23790	10	16QAM	25	0	21.76	0-2	2
710.0	23790	10	16QAM	25	12	21.67	0-2	2
710.0	23790	10	16QAM	25	25	21.70	0-2	2
710.0	23790	10	16QAM	50	0	21.68	0-2	2

Note: LTE Band 17 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-2**  
**LTE Band 17 Conducted Powers - 5 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
710.0	23790	5	QPSK	1	0	23.79	0	0
710.0	23790	5	QPSK	1	12	23.41	0	0
710.0	23790	5	QPSK	1	24	23.76	0	0
710.0	23790	5	QPSK	12	0	22.61	0-1	1
710.0	23790	5	QPSK	12	6	22.48	0-1	1
710.0	23790	5	QPSK	12	13	22.59	0-1	1
710.0	23790	5	QPSK	25	0	22.58	0-1	1
710.0	23790	5	16-QAM	1	0	23.00	0-1	1
710.0	23790	5	16-QAM	1	12	22.68	0-1	1
710.0	23790	5	16-QAM	1	24	22.98	0-1	1
710.0	23790	5	16-QAM	12	0	21.79	0-2	2
710.0	23790	5	16-QAM	12	6	21.60	0-2	2
710.0	23790	5	16-QAM	12	13	21.73	0-2	2
710.0	23790	5	16-QAM	25	0	21.72	0-2	2



Note: LTE Band 17 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

### 9.3.2 LTE Band 5 (Cell)

**Table 9-3**  
**LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
836.5	20525	10	QPSK	1	0	23.09	0	0
836.5	20525	10	QPSK	1	25	23.04	0	0
836.5	20525	10	QPSK	1	49	23.01	0	0
836.5	20525	10	QPSK	25	0	22.22	0-1	1
836.5	20525	10	QPSK	25	12	22.15	0-1	1
836.5	20525	10	QPSK	25	25	22.12	0-1	1
836.5	20525	10	QPSK	50	0	22.15	0-1	1
836.5	20525	10	16QAM	1	0	22.44	0-1	1
836.5	20525	10	16QAM	1	25	22.39	0-1	1
836.5	20525	10	16QAM	1	49	22.42	0-1	1
836.5	20525	10	16QAM	25	0	21.26	0-2	2
836.5	20525	10	16QAM	25	12	21.18	0-2	2
836.5	20525	10	16QAM	25	25	21.17	0-2	2
836.5	20525	10	16QAM	50	0	21.18	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 24 of 71

**Table 9-4**  
**LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]		
Low	826.5	20425	5	QPSK	1	0	23.24	0	0	
	826.5	20425	5	QPSK	1	12	22.89	0	0	
	826.5	20425	5	QPSK	1	24	23.14	0	0	
	826.5	20425	5	QPSK	12	0	21.97	0-1	1	
	826.5	20425	5	QPSK	12	6	21.82	0-1	1	
	826.5	20425	5	QPSK	12	13	21.90	0-1	1	
	826.5	20425	5	QPSK	25	0	21.92	0-1	1	
	826.5	20425	5	16-QAM	1	0	22.48	0-1	1	
	826.5	20425	5	16-QAM	1	12	22.20	0-1	1	
	826.5	20425	5	16-QAM	1	24	22.46	0-1	1	
	826.5	20425	5	16-QAM	12	0	21.02	0-2	2	
	826.5	20425	5	16-QAM	12	6	20.86	0-2	2	
	826.5	20425	5	16-QAM	12	13	20.96	0-2	2	
	826.5	20425	5	16-QAM	25	0	20.88	0-2	2	
	Mid	836.5	20525	5	QPSK	1	0	23.15	0	0
		836.5	20525	5	QPSK	1	12	22.84	0	0
		836.5	20525	5	QPSK	1	24	23.12	0	0
		836.5	20525	5	QPSK	12	0	22.09	0-1	1
836.5		20525	5	QPSK	12	6	21.96	0-1	1	
836.5		20525	5	QPSK	12	13	22.02	0-1	1	
836.5		20525	5	QPSK	25	0	22.05	0-1	1	
836.5		20525	5	16-QAM	1	0	22.30	0-1	1	
836.5		20525	5	16-QAM	1	12	22.09	0-1	1	
836.5		20525	5	16-QAM	1	24	22.26	0-1	1	
836.5		20525	5	16-QAM	12	0	21.22	0-2	2	
836.5		20525	5	16-QAM	12	6	21.10	0-2	2	
836.5		20525	5	16-QAM	12	13	21.15	0-2	2	
836.5		20525	5	16-QAM	25	0	21.15	0-2	2	
High		846.5	20625	5	QPSK	1	0	23.06	0	0
		846.5	20625	5	QPSK	1	12	22.64	0	0
		846.5	20625	5	QPSK	1	24	22.98	0	0
		846.5	20625	5	QPSK	12	0	21.96	0-1	1
	846.5	20625	5	QPSK	12	6	21.80	0-1	1	
	846.5	20625	5	QPSK	12	13	21.85	0-1	1	
	846.5	20625	5	QPSK	25	0	21.90	0-1	1	
	846.5	20625	5	16-QAM	1	0	22.26	0-1	1	
	846.5	20625	5	16-QAM	1	12	21.90	0-1	1	
	846.5	20625	5	16-QAM	1	24	22.17	0-1	1	
	846.5	20625	5	16-QAM	12	0	21.12	0-2	2	
	846.5	20625	5	16-QAM	12	6	20.90	0-2	2	
	846.5	20625	5	16-QAM	12	13	20.97	0-2	2	
	846.5	20625	5	16-QAM	25	0	20.97	0-2	2	

**Table 9-5**  
**LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]		
Low	825.5	20415	3	QPSK	1	0	22.85	0	0	
	825.5	20415	3	QPSK	1	7	22.86	0	0	
	825.5	20415	3	QPSK	1	14	22.77	0	0	
	825.5	20415	3	QPSK	8	0	21.88	0-1	1	
	825.5	20415	3	QPSK	8	4	21.88	0-1	1	
	825.5	20415	3	QPSK	8	7	21.87	0-1	1	
	825.5	20415	3	QPSK	15	0	21.90	0-1	1	
	825.5	20415	3	16-QAM	1	0	22.08	0-1	1	
	825.5	20415	3	16-QAM	1	7	22.07	0-1	1	
	825.5	20415	3	16-QAM	1	14	22.08	0-1	1	
	825.5	20415	3	16-QAM	8	0	21.12	0-2	2	
	825.5	20415	3	16-QAM	8	4	21.03	0-2	2	
	825.5	20415	3	16-QAM	8	7	21.04	0-2	2	
	825.5	20415	3	16-QAM	15	0	20.91	0-2	2	
	Mid	836.5	20525	3	QPSK	1	0	23.09	0	0
		836.5	20525	3	QPSK	1	7	23.06	0	0
		836.5	20525	3	QPSK	1	14	23.09	0	0
		836.5	20525	3	QPSK	8	0	22.16	0-1	1
836.5		20525	3	QPSK	8	4	22.15	0-1	1	
836.5		20525	3	QPSK	8	7	22.12	0-1	1	
836.5		20525	3	QPSK	15	0	22.15	0-1	1	
836.5		20525	3	16-QAM	1	0	22.34	0-1	1	
836.5		20525	3	16-QAM	1	7	22.33	0-1	1	
836.5		20525	3	16-QAM	1	14	22.33	0-1	1	
836.5		20525	3	16-QAM	8	0	21.06	0-2	2	
836.5		20525	3	16-QAM	8	4	21.01	0-2	2	
836.5		20525	3	16-QAM	8	7	21.04	0-2	2	
836.5		20525	3	16-QAM	15	0	21.08	0-2	2	
High		847.5	20635	3	QPSK	1	0	22.85	0	0
		847.5	20635	3	QPSK	1	7	22.81	0	0
		847.5	20635	3	QPSK	1	14	22.85	0	0
		847.5	20635	3	QPSK	8	0	22.01	0-1	1
	847.5	20635	3	QPSK	8	4	21.88	0-1	1	
	847.5	20635	3	QPSK	8	7	21.94	0-1	1	
	847.5	20635	3	QPSK	15	0	21.91	0-1	1	
	847.5	20635	3	16-QAM	1	0	22.06	0-1	1	
	847.5	20635	3	16-QAM	1	7	21.98	0-1	1	
	847.5	20635	3	16-QAM	1	14	21.95	0-1	1	
	847.5	20635	3	16-QAM	8	0	20.88	0-2	2	
	847.5	20635	3	16-QAM	8	4	20.85	0-2	2	
	847.5	20635	3	16-QAM	8	7	20.83	0-2	2	
	847.5	20635	3	16-QAM	15	0	20.94	0-2	2	

**Table 9-6**  
**LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth**



Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
824.7	20407	1.4	QPSK	1	0	22.94	0	0	
	20407	1.4	QPSK	1	2	22.92	0	0	
	20407	1.4	QPSK	1	5	22.84	0	0	
	20407	1.4	QPSK	3	0	23.05	0	0	
	20407	1.4	QPSK	3	2	23.07	0	0	
	20407	1.4	QPSK	3	3	23.07	0	0	
	20407	1.4	QPSK	6	0	22.03	0-1	1	
	20407	1.4	16-QAM	1	0	22.21	0-1	1	
	20407	1.4	16-QAM	1	2	22.17	0-1	1	
	20407	1.4	16-QAM	1	5	22.18	0-1	1	
	20407	1.4	16-QAM	3	0	22.10	0-1	1	
	20407	1.4	16-QAM	3	2	22.04	0-1	1	
	20407	1.4	16-QAM	3	3	22.04	0-1	1	
	20407	1.4	16-QAM	6	0	21.18	0-2	2	
	836.5	20525	1.4	QPSK	1	0	23.31	0	0
		20525	1.4	QPSK	1	2	23.31	0	0
		20525	1.4	QPSK	1	5	23.30	0	0
		20525	1.4	QPSK	3	0	23.33	0	0
20525		1.4	QPSK	3	2	23.24	0	0	
20525		1.4	QPSK	3	3	23.23	0	0	
20525		1.4	QPSK	6	0	22.25	0-1	1	
20525		1.4	16-QAM	1	0	22.10	0-1	1	
20525		1.4	16-QAM	1	2	22.08	0-1	1	
20525		1.4	16-QAM	1	5	22.11	0-1	1	
20525		1.4	16-QAM	3	0	22.28	0-1	1	
20525		1.4	16-QAM	3	2	22.24	0-1	1	
20525		1.4	16-QAM	3	3	22.28	0-1	1	
20525		1.4	16-QAM	6	0	21.45	0-2	2	
848.3		20643	1.4	QPSK	1	0	22.93	0	0
		20643	1.4	QPSK	1	2	22.93	0	0
		20643	1.4	QPSK	1	5	22.93	0	0
		20643	1.4	QPSK	3	0	23.03	0	0
	20643	1.4	QPSK	3	2	23.05	0	0	
	20643	1.4	QPSK	3	3	23.04	0	0	
	20643	1.4	QPSK	6	0	22.01	0-1	1	
	20643	1.4	16-QAM	1	0	22.21	0-1	1	
	20643	1.4	16-QAM	1	2	22.17	0-1	1	
	20643	1.4	16-QAM	1	5	22.18	0-1	1	
	20643	1.4	16-QAM	3	0	22.24	0-1	1	
	20643	1.4	16-QAM	3	2	22.22	0-1	1	
	20643	1.4	16-QAM	3	3	22.26	0-1	1	
	20643	1.4	16-QAM	6	0	21.12	0-2	2	

### 9.3.3 LTE Band 4 (AWS)

**Table 9-7**  
**LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
1732.5	20175	20	QPSK	1	0	<b>21.82</b>	0	0
	20175	20	QPSK	1	50	21.18	0	0
	20175	20	QPSK	1	99	21.24	0	0
	20175	20	QPSK	50	0	<b>20.61</b>	0-1	1
	20175	20	QPSK	50	25	20.33	0-1	1
	20175	20	QPSK	50	50	20.36	0-1	1
	20175	20	QPSK	100	0	20.49	0-1	1
	20175	20	16QAM	1	0	20.96	0-1	1
	20175	20	16QAM	1	50	20.53	0-1	1
	20175	20	16QAM	1	99	20.57	0-1	1
	20175	20	16QAM	50	0	19.63	0-2	2
	20175	20	16QAM	50	25	19.32	0-2	2
	20175	20	16QAM	50	50	19.34	0-2	2
	20175	20	16QAM	100	0	19.46	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 26 of 71

**Table 9-8**  
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1717.5	20025	15	QPSK	1	0	21.91	0	0
	1717.5	20025	15	QPSK	1	36	21.13	0	0
	1717.5	20025	15	QPSK	1	74	21.71	0	0
	1717.5	20025	15	QPSK	36	0	20.65	0-1	1
	1717.5	20025	15	QPSK	36	18	20.18	0-1	1
	1717.5	20025	15	QPSK	36	37	20.30	0-1	1
	1717.5	20025	15	QPSK	75	0	20.40	0-1	1
	1717.5	20025	15	16QAM	1	0	20.86	0-1	1
	1717.5	20025	15	16QAM	1	36	20.43	0-1	1
	1717.5	20025	15	16QAM	1	74	20.96	0-1	1
	1717.5	20025	15	16QAM	36	0	19.62	0-2	2
	1717.5	20025	15	16QAM	36	18	19.16	0-2	2
	1717.5	20025	15	16QAM	36	37	19.27	0-2	2
	1717.5	20025	15	16QAM	75	0	19.38	0-2	2
	Mid	1732.5	20175	15	QPSK	1	0	21.88	0
1732.5		20175	15	QPSK	1	36	21.04	0	0
1732.5		20175	15	QPSK	1	74	21.41	0	0
1732.5		20175	15	QPSK	36	0	20.39	0-1	1
1732.5		20175	15	QPSK	36	18	20.02	0-1	1
1732.5		20175	15	QPSK	36	37	20.05	0-1	1
1732.5		20175	15	QPSK	75	0	20.17	0-1	1
1732.5		20175	15	16QAM	1	0	20.85	0-1	1
1732.5		20175	15	16QAM	1	36	20.74	0-1	1
1732.5		20175	15	16QAM	1	74	20.92	0-1	1
1732.5		20175	15	16QAM	36	0	19.41	0-2	2
1732.5		20175	15	16QAM	36	18	19.06	0-2	2
1732.5		20175	15	16QAM	36	37	19.05	0-2	2
1732.5		20175	15	16QAM	75	0	19.18	0-2	2
High		1747.5	20325	15	QPSK	1	0	21.63	0
	1747.5	20325	15	QPSK	1	36	21.06	0	0
	1747.5	20325	15	QPSK	1	74	21.37	0	0
	1747.5	20325	15	QPSK	36	0	20.28	0-1	1
	1747.5	20325	15	QPSK	36	18	20.03	0-1	1
	1747.5	20325	15	QPSK	36	37	20.01	0-1	1
	1747.5	20325	15	QPSK	75	0	20.11	0-1	1
	1747.5	20325	15	16QAM	1	0	20.58	0-1	1
	1747.5	20325	15	16QAM	1	36	20.63	0-1	1
	1747.5	20325	15	16QAM	1	74	20.90	0-1	1
	1747.5	20325	15	16QAM	36	0	19.32	0-2	2
	1747.5	20325	15	16QAM	36	18	19.02	0-2	2
	1747.5	20325	15	16QAM	36	37	19.03	0-2	2
	1747.5	20325	15	16QAM	75	0	19.07	0-2	2

**Table 9-9**  
**LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1715	20000	10	QPSK	1	0	21.50	0	0
	1715	20000	10	QPSK	1	25	21.22	0	0
	1715	20000	10	QPSK	1	49	21.22	0	0
	1715	20000	10	QPSK	25	0	20.38	0-1	1
	1715	20000	10	QPSK	25	12	20.25	0-1	1
	1715	20000	10	QPSK	25	25	20.30	0-1	1
	1715	20000	10	QPSK	50	0	20.36	0-1	1
	1715	20000	10	16QAM	1	0	20.73	0-1	1
	1715	20000	10	16QAM	1	25	20.94	0-1	1
	1715	20000	10	16QAM	1	49	21.00	0-1	1
	1715	20000	10	16QAM	25	0	19.43	0-2	2
	1715	20000	10	16QAM	25	12	19.29	0-2	2
	1715	20000	10	16QAM	25	25	19.14	0-2	2
	1715	20000	10	16QAM	50	0	19.33	0-2	2
	Mid	1732.5	20175	10	QPSK	1	0	21.24	0
1732.5		20175	10	QPSK	1	25	21.22	0	0
1732.5		20175	10	QPSK	1	49	21.01	0	0
1732.5		20175	10	QPSK	25	0	20.29	0-1	1
1732.5		20175	10	QPSK	25	12	20.18	0-1	1
1732.5		20175	10	QPSK	25	25	20.11	0-1	1
1732.5		20175	10	QPSK	50	0	20.20	0-1	1
1732.5		20175	10	16QAM	1	0	21.00	0-1	1
1732.5		20175	10	16QAM	1	25	20.55	0-1	1
1732.5		20175	10	16QAM	1	49	20.78	0-1	1
1732.5		20175	10	16QAM	25	0	19.38	0-2	2
1732.5		20175	10	16QAM	25	12	19.35	0-2	2
1732.5		20175	10	16QAM	25	25	19.17	0-2	2
1732.5		20175	10	16QAM	50	0	19.20	0-2	2
High		1750	20350	10	QPSK	1	0	21.31	0
	1750	20350	10	QPSK	1	25	21.14	0	0
	1750	20350	10	QPSK	1	49	21.09	0	0
	1750	20350	10	QPSK	25	0	20.27	0-1	1
	1750	20350	10	QPSK	25	12	20.07	0-1	1
	1750	20350	10	QPSK	25	25	20.06	0-1	1
	1750	20350	10	QPSK	50	0	20.16	0-1	1
	1750	20350	10	16QAM	1	0	20.61	0-1	1
	1750	20350	10	16QAM	1	25	20.82	0-1	1
	1750	20350	10	16QAM	1	49	20.71	0-1	1
	1750	20350	10	16QAM	25	0	19.27	0-2	2
	1750	20350	10	16QAM	25	12	19.14	0-2	2
	1750	20350	10	16QAM	25	25	19.07	0-2	2
	1750	20350	10	16QAM	50	0	19.14	0-2	2



FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 27 of 71

**Table 9-10**  
**LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	21.55	0	0
	1712.5	19975	5	QPSK	1	12	21.14	0	0
	1712.5	19975	5	QPSK	1	24	21.41	0	0
	1712.5	19975	5	QPSK	12	0	20.35	0-1	1
	1712.5	19975	5	QPSK	12	6	20.13	0-1	1
	1712.5	19975	5	QPSK	12	13	20.20	0-1	1
	1712.5	19975	5	QPSK	25	0	20.39	0-1	1
	1712.5	19975	5	16-QAM	1	0	20.90	0-1	1
	1712.5	19975	5	16-QAM	1	12	20.82	0-1	1
	1712.5	19975	5	16-QAM	1	24	20.95	0-1	1
	1712.5	19975	5	16-QAM	12	0	19.36	0-2	2
	1712.5	19975	5	16-QAM	12	6	19.16	0-2	2
	1712.5	19975	5	16-QAM	12	13	19.28	0-2	2
	1712.5	19975	5	16-QAM	25	0	19.24	0-2	2
	Mid	1732.5	20175	5	QPSK	1	0	21.45	0
1732.5		20175	5	QPSK	1	12	21.11	0	0
1732.5		20175	5	QPSK	1	24	21.37	0	0
1732.5		20175	5	QPSK	12	0	20.29	0-1	1
1732.5		20175	5	QPSK	12	6	20.05	0-1	1
1732.5		20175	5	QPSK	12	13	20.18	0-1	1
1732.5		20175	5	QPSK	25	0	20.17	0-1	1
1732.5		20175	5	16-QAM	1	0	20.88	0-1	1
1732.5		20175	5	16-QAM	1	12	20.80	0-1	1
1732.5		20175	5	16-QAM	1	24	20.95	0-1	1
1732.5		20175	5	16-QAM	12	0	19.30	0-2	2
1732.5		20175	5	16-QAM	12	6	19.17	0-2	2
1732.5		20175	5	16-QAM	12	13	19.11	0-2	2
1732.5		20175	5	16-QAM	25	0	19.12	0-2	2
High		1752.5	20375	5	QPSK	1	0	21.32	0
	1752.5	20375	5	QPSK	1	12	21.00	0	0
	1752.5	20375	5	QPSK	1	24	21.17	0	0
	1752.5	20375	5	QPSK	12	0	20.13	0-1	1
	1752.5	20375	5	QPSK	12	6	20.09	0-1	1
	1752.5	20375	5	QPSK	12	13	20.06	0-1	1
	1752.5	20375	5	QPSK	25	0	20.10	0-1	1
	1752.5	20375	5	16-QAM	1	0	20.93	0-1	1
	1752.5	20375	5	16-QAM	1	12	20.62	0-1	1
	1752.5	20375	5	16-QAM	1	24	20.91	0-1	1
	1752.5	20375	5	16-QAM	12	0	19.25	0-2	2
	1752.5	20375	5	16-QAM	12	6	19.11	0-2	2
	1752.5	20375	5	16-QAM	12	13	19.10	0-2	2
	1752.5	20375	5	16-QAM	25	0	19.09	0-2	2

**Table 9-11**  
**LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	21.21	0	0
	1711.5	19965	3	QPSK	1	7	21.21	0	0
	1711.5	19965	3	QPSK	1	14	21.18	0	0
	1711.5	19965	3	QPSK	8	0	20.18	0-1	1
	1711.5	19965	3	QPSK	8	4	20.16	0-1	1
	1711.5	19965	3	QPSK	8	7	20.21	0-1	1
	1711.5	19965	3	QPSK	15	0	20.20	0-1	1
	1711.5	19965	3	16-QAM	1	0	20.87	0-1	1
	1711.5	19965	3	16-QAM	1	7	20.54	0-1	1
	1711.5	19965	3	16-QAM	1	14	20.87	0-1	1
	1711.5	19965	3	16-QAM	8	0	19.32	0-2	2
	1711.5	19965	3	16-QAM	8	4	19.23	0-2	2
	1711.5	19965	3	16-QAM	8	7	19.29	0-2	2
	1711.5	19965	3	16-QAM	15	0	19.21	0-2	2
	Mid	1732.5	20175	3	QPSK	1	0	21.13	0
1732.5		20175	3	QPSK	1	7	21.18	0	0
1732.5		20175	3	QPSK	1	14	21.12	0	0
1732.5		20175	3	QPSK	8	0	20.18	0-1	1
1732.5		20175	3	QPSK	8	4	20.13	0-1	1
1732.5		20175	3	QPSK	8	7	20.11	0-1	1
1732.5		20175	3	QPSK	15	0	20.16	0-1	1
1732.5		20175	3	16-QAM	1	0	20.83	0-1	1
1732.5		20175	3	16-QAM	1	7	20.87	0-1	1
1732.5		20175	3	16-QAM	1	14	20.54	0-1	1
1732.5		20175	3	16-QAM	8	0	19.40	0-2	2
1732.5		20175	3	16-QAM	8	4	19.31	0-2	2
1732.5		20175	3	16-QAM	8	7	19.36	0-2	2
1732.5		20175	3	16-QAM	15	0	19.22	0-2	2
High		1753.5	20385	3	QPSK	1	0	21.14	0
	1753.5	20385	3	QPSK	1	7	21.10	0	0
	1753.5	20385	3	QPSK	1	14	21.07	0	0
	1753.5	20385	3	QPSK	8	0	20.16	0-1	1
	1753.5	20385	3	QPSK	8	4	20.06	0-1	1
	1753.5	20385	3	QPSK	8	7	20.03	0-1	1
	1753.5	20385	3	QPSK	15	0	20.06	0-1	1
	1753.5	20385	3	16-QAM	1	0	20.34	0-1	1
	1753.5	20385	3	16-QAM	1	7	20.72	0-1	1
	1753.5	20385	3	16-QAM	1	14	20.64	0-1	1
	1753.5	20385	3	16-QAM	8	0	19.18	0-2	2
	1753.5	20385	3	16-QAM	8	4	19.21	0-2	2
	1753.5	20385	3	16-QAM	8	7	19.22	0-2	2
	1753.5	20385	3	16-QAM	15	0	19.08	0-2	2

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 28 of 71

**Table 9-12**  
**LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	21.37	0	0
	1710.7	19957	1.4	QPSK	1	2	21.28	0	0
	1710.7	19957	1.4	QPSK	1	5	21.26	0	0
	1710.7	19957	1.4	QPSK	3	0	21.40	0	0
	1710.7	19957	1.4	QPSK	3	2	21.40	0	0
	1710.7	19957	1.4	QPSK	3	3	21.33	0	0
	1710.7	19957	1.4	QPSK	6	0	20.37	0-1	1
	1710.7	19957	1.4	16-QAM	1	0	20.94	0-1	1
	1710.7	19957	1.4	16-QAM	1	2	20.92	0-1	1
	1710.7	19957	1.4	16-QAM	1	5	20.98	0-1	1
	1710.7	19957	1.4	16-QAM	3	0	20.61	0-1	1
	1710.7	19957	1.4	16-QAM	3	2	20.64	0-1	1
	1710.7	19957	1.4	16-QAM	3	3	20.69	0-1	1
	1710.7	19957	1.4	16-QAM	6	0	19.55	0-2	2
Mid	1732.5	20175	1.4	QPSK	1	0	21.25	0	0
	1732.5	20175	1.4	QPSK	1	2	21.27	0	0
	1732.5	20175	1.4	QPSK	1	5	21.29	0	0
	1732.5	20175	1.4	QPSK	3	0	21.27	0	0
	1732.5	20175	1.4	QPSK	3	2	21.28	0	0
	1732.5	20175	1.4	QPSK	3	3	21.22	0	0
	1732.5	20175	1.4	QPSK	6	0	20.23	0-1	1
	1732.5	20175	1.4	16-QAM	1	0	20.56	0-1	1
	1732.5	20175	1.4	16-QAM	1	2	20.95	0-1	1
	1732.5	20175	1.4	16-QAM	1	5	20.94	0-1	1
	1732.5	20175	1.4	16-QAM	3	0	20.57	0-1	1
	1732.5	20175	1.4	16-QAM	3	2	20.38	0-1	1
	1732.5	20175	1.4	16-QAM	3	3	20.55	0-1	1
	1732.5	20175	1.4	16-QAM	6	0	19.94	0-2	2
High	1754.3	20393	1.4	QPSK	1	0	21.09	0	0
	1754.3	20393	1.4	QPSK	1	2	21.13	0	0
	1754.3	20393	1.4	QPSK	1	5	21.22	0	0
	1754.3	20393	1.4	QPSK	3	0	21.31	0	0
	1754.3	20393	1.4	QPSK	3	2	21.21	0	0
	1754.3	20393	1.4	QPSK	3	3	21.15	0	0
	1754.3	20393	1.4	QPSK	6	0	20.14	0-1	1
	1754.3	20393	1.4	16-QAM	1	0	20.84	0-1	1
	1754.3	20393	1.4	16-QAM	1	2	20.72	0-1	1
	1754.3	20393	1.4	16-QAM	1	5	20.81	0-1	1
	1754.3	20393	1.4	16-QAM	3	0	20.40	0-1	1
	1754.3	20393	1.4	16-QAM	3	2	20.35	0-1	1
	1754.3	20393	1.4	16-QAM	3	3	20.27	0-1	1
	1754.3	20393	1.4	16-QAM	6	0	19.39	0-2	2

### 9.3.4 LTE Band 2 (PCS)

**Table 9-13**  
**LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]	
Low	1860	18700	20	QPSK	1	0	22.00	0	0	
	1860	18700	20	QPSK	1	50	21.88	0	0	
	1860	18700	20	QPSK	1	99	21.51	0	0	
	1860	18700	20	QPSK	50	0	21.03	0-1	1	
	1860	18700	20	QPSK	50	25	20.86	0-1	1	
	1860	18700	20	QPSK	50	50	20.74	0-1	1	
	1860	18700	20	QPSK	100	0	20.84	0-1	1	
	1860	18700	20	16QAM	1	0	21.20	0-1	1	
	1860	18700	20	16QAM	1	50	21.03	0-1	1	
	1860	18700	20	16QAM	1	99	20.72	0-1	1	
	1860	18700	20	16QAM	50	0	19.95	0-2	2	
	1860	18700	20	16QAM	50	25	19.78	0-2	2	
	1860	18700	20	16QAM	50	50	19.66	0-2	2	
	1860	18700	20	16QAM	100	0	19.77	0-2	2	
	Mid	1880.0	18900	20	QPSK	1	0	21.99	0	0
		1880.0	18900	20	QPSK	1	50	21.83	0	0
		1880.0	18900	20	QPSK	1	99	21.54	0	0
		1880.0	18900	20	QPSK	50	0	21.12	0-1	1
1880.0		18900	20	QPSK	50	25	21.08	0-1	1	
1880.0		18900	20	QPSK	50	50	20.79	0-1	1	
1880.0		18900	20	QPSK	100	0	20.89	0-1	1	
1880.0		18900	20	16QAM	1	0	21.45	0-1	1	
1880.0		18900	20	16QAM	1	50	21.09	0-1	1	
1880.0		18900	20	16QAM	1	99	21.05	0-1	1	
1880.0		18900	20	16QAM	50	0	20.09	0-2	2	
1880.0		18900	20	16QAM	50	25	19.84	0-2	2	
1880.0		18900	20	16QAM	50	50	19.69	0-2	2	
1880.0		18900	20	16QAM	100	0	19.82	0-2	2	
High		1900	19100	20	QPSK	1	0	22.18	0	0
		1900	19100	20	QPSK	1	50	21.90	0	0
		1900	19100	20	QPSK	1	99	21.68	0	0
		1900	19100	20	QPSK	50	0	21.14	0-1	1
	1900	19100	20	QPSK	50	25	20.93	0-1	1	
	1900	19100	20	QPSK	50	50	20.94	0-1	1	
	1900	19100	20	QPSK	100	0	21.09	0-1	1	
	1900	19100	20	16QAM	1	0	21.48	0-1	1	
	1900	19100	20	16QAM	1	50	21.18	0-1	1	
	1900	19100	20	16QAM	1	99	20.91	0-1	1	
	1900	19100	20	16QAM	50	0	20.13	0-2	2	
	1900	19100	20	16QAM	50	25	19.89	0-2	2	
	1900	19100	20	16QAM	50	50	19.84	0-2	2	
	1900	19100	20	16QAM	100	0	19.99	0-2	2	



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 29 of 71

Table 9-14

LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	22.46	0	0
	1857.5	18675	15	QPSK	1	36	21.88	0	0
	1857.5	18675	15	QPSK	1	74	22.15	0	0
	1857.5	18675	15	QPSK	36	0	21.00	0-1	1
	1857.5	18675	15	QPSK	36	18	20.74	0-1	1
	1857.5	18675	15	QPSK	36	37	20.78	0-1	1
	1857.5	18675	15	QPSK	75	0	20.88	0-1	1
	1857.5	18675	15	16QAM	1	0	21.34	0-1	1
	1857.5	18675	15	16QAM	1	36	21.42	0-1	1
	1857.5	18675	15	16QAM	1	74	21.32	0-1	1
	1857.5	18675	15	16QAM	36	0	20.02	0-2	2
	1857.5	18675	15	16QAM	36	18	19.77	0-2	2
	1857.5	18675	15	16QAM	36	37	19.76	0-2	2
	1857.5	18675	15	16QAM	75	0	19.79	0-2	2
	Mid	1880.0	18900	15	QPSK	1	0	22.37	0
1880.0		18900	15	QPSK	1	36	21.71	0	0
1880.0		18900	15	QPSK	1	74	22.27	0	0
1880.0		18900	15	QPSK	36	0	21.05	0-1	1
1880.0		18900	15	QPSK	36	18	20.69	0-1	1
1880.0		18900	15	QPSK	36	37	20.82	0-1	1
1880.0		18900	15	QPSK	75	0	21.01	0-1	1
1880.0		18900	15	16QAM	1	0	21.46	0-1	1
1880.0		18900	15	16QAM	1	36	21.41	0-1	1
1880.0		18900	15	16QAM	1	74	21.29	0-1	1
1880.0		18900	15	16QAM	36	0	20.05	0-2	2
1880.0		18900	15	16QAM	36	18	19.73	0-2	2
1880.0		18900	15	16QAM	36	37	19.80	0-2	2
1880.0		18900	15	16QAM	75	0	19.84	0-2	2
High		1902.5	19125	15	QPSK	1	0	22.50	0
	1902.5	19125	15	QPSK	1	36	21.88	0	0
	1902.5	19125	15	QPSK	1	74	22.33	0	0
	1902.5	19125	15	QPSK	36	0	21.15	0-1	1
	1902.5	19125	15	QPSK	36	18	20.76	0-1	1
	1902.5	19125	15	QPSK	36	37	20.87	0-1	1
	1902.5	19125	15	QPSK	75	0	20.95	0-1	1
	1902.5	19125	15	16QAM	1	0	21.46	0-1	1
	1902.5	19125	15	16QAM	1	36	21.06	0-1	1
	1902.5	19125	15	16QAM	1	74	21.40	0-1	1
	1902.5	19125	15	16QAM	36	0	20.06	0-2	2
	1902.5	19125	15	16QAM	36	18	19.78	0-2	2
	1902.5	19125	15	16QAM	36	37	19.82	0-2	2
	1902.5	19125	15	16QAM	75	0	19.91	0-2	2

Table 9-15

LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	22.08	0	0
	1855	18650	10	QPSK	1	25	22.06	0	0
	1855	18650	10	QPSK	1	49	21.79	0	0
	1855	18650	10	QPSK	25	0	20.97	0-1	1
	1855	18650	10	QPSK	25	12	20.83	0-1	1
	1855	18650	10	QPSK	25	25	20.82	0-1	1
	1855	18650	10	QPSK	50	0	20.90	0-1	1
	1855	18650	10	16QAM	1	0	21.36	0-1	1
	1855	18650	10	16QAM	1	25	21.28	0-1	1
	1855	18650	10	16QAM	1	49	21.14	0-1	1
	1855	18650	10	16QAM	25	0	20.08	0-2	2
	1855	18650	10	16QAM	25	12	20.00	0-2	2
	1855	18650	10	16QAM	25	25	19.87	0-2	2
	1855	18650	10	16QAM	50	0	19.86	0-2	2
	Mid	1880.0	18900	10	QPSK	1	0	22.02	0
1880.0		18900	10	QPSK	1	25	21.92	0	0
1880.0		18900	10	QPSK	1	49	21.76	0	0
1880.0		18900	10	QPSK	25	0	20.98	0-1	1
1880.0		18900	10	QPSK	25	12	20.88	0-1	1
1880.0		18900	10	QPSK	25	25	20.86	0-1	1
1880.0		18900	10	QPSK	50	0	20.91	0-1	1
1880.0		18900	10	16QAM	1	0	21.45	0-1	1
1880.0		18900	10	16QAM	1	25	21.36	0-1	1
1880.0		18900	10	16QAM	1	49	21.14	0-1	1
1880.0		18900	10	16QAM	25	0	19.98	0-2	2
1880.0		18900	10	16QAM	25	12	19.86	0-2	2
1880.0		18900	10	16QAM	25	25	19.89	0-2	2
1880.0		18900	10	16QAM	50	0	19.86	0-2	2
High		1905	19150	10	QPSK	1	0	22.07	0
	1905	19150	10	QPSK	1	25	21.88	0	0
	1905	19150	10	QPSK	1	49	21.84	0	0
	1905	19150	10	QPSK	25	0	20.97	0-1	1
	1905	19150	10	QPSK	25	12	20.75	0-1	1
	1905	19150	10	QPSK	25	25	20.77	0-1	1
	1905	19150	10	QPSK	50	0	20.82	0-1	1
	1905	19150	10	16QAM	1	0	21.40	0-1	1
	1905	19150	10	16QAM	1	25	21.11	0-1	1
	1905	19150	10	16QAM	1	49	21.08	0-1	1
	1905	19150	10	16QAM	25	0	19.91	0-2	2
	1905	19150	10	16QAM	25	12	19.79	0-2	2
	1905	19150	10	16QAM	25	25	19.72	0-2	2
	1905	19150	10	16QAM	50	0	19.78	0-2	2

**Table 9-16**  
**LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	22.14	0	0
	1852.5	18625	5	QPSK	1	12	21.83	0	0
	1852.5	18625	5	QPSK	1	24	22.07	0	0
	1852.5	18625	5	QPSK	12	0	20.94	0-1	1
	1852.5	18625	5	QPSK	12	6	20.87	0-1	1
	1852.5	18625	5	QPSK	12	13	20.92	0-1	1
	1852.5	18625	5	QPSK	25	0	20.87	0-1	1
	1852.5	18625	5	16-QAM	1	0	21.37	0-1	1
	1852.5	18625	5	16-QAM	1	12	21.39	0-1	1
	1852.5	18625	5	16-QAM	1	24	21.08	0-1	1
	1852.5	18625	5	16-QAM	12	0	19.90	0-2	2
	1852.5	18625	5	16-QAM	12	6	19.79	0-2	2
	1852.5	18625	5	16-QAM	12	13	19.84	0-2	2
	1852.5	18625	5	16-QAM	25	0	19.76	0-2	2
	1852.5	18625	5	16-QAM	25	0	19.76	0-2	2
Mid	1880.0	18900	5	QPSK	1	0	22.12	0	0
	1880.0	18900	5	QPSK	1	12	21.75	0	0
	1880.0	18900	5	QPSK	1	24	22.03	0	0
	1880.0	18900	5	QPSK	12	0	20.88	0-1	1
	1880.0	18900	5	QPSK	12	6	20.72	0-1	1
	1880.0	18900	5	QPSK	12	13	20.80	0-1	1
	1880.0	18900	5	QPSK	25	0	20.80	0-1	1
	1880.0	18900	5	16-QAM	1	0	21.40	0-1	1
	1880.0	18900	5	16-QAM	1	12	21.10	0-1	1
	1880.0	18900	5	16-QAM	1	24	21.25	0-1	1
	1880.0	18900	5	16-QAM	12	0	19.95	0-2	2
	1880.0	18900	5	16-QAM	12	6	19.71	0-2	2
	1880.0	18900	5	16-QAM	12	13	19.76	0-2	2
	1880.0	18900	5	16-QAM	25	0	19.85	0-2	2
	1880.0	18900	5	16-QAM	25	0	19.85	0-2	2
High	1907.5	19175	5	QPSK	1	0	22.07	0	0
	1907.5	19175	5	QPSK	1	12	21.77	0	0
	1907.5	19175	5	QPSK	1	24	22.13	0	0
	1907.5	19175	5	QPSK	12	0	20.92	0-1	1
	1907.5	19175	5	QPSK	12	6	20.68	0-1	1
	1907.5	19175	5	QPSK	12	13	20.77	0-1	1
	1907.5	19175	5	QPSK	25	0	20.78	0-1	1
	1907.5	19175	5	16-QAM	1	0	21.34	0-1	1
	1907.5	19175	5	16-QAM	1	12	21.06	0-1	1
	1907.5	19175	5	16-QAM	1	24	21.22	0-1	1
	1907.5	19175	5	16-QAM	12	0	19.85	0-2	2
	1907.5	19175	5	16-QAM	12	6	19.70	0-2	2
	1907.5	19175	5	16-QAM	12	13	19.68	0-2	2
	1907.5	19175	5	16-QAM	25	0	19.78	0-2	2
	1907.5	19175	5	16-QAM	25	0	19.78	0-2	2

**Table 9-17**  
**LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth**

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	21.92	0	0
	1851.5	18615	3	QPSK	1	7	21.95	0	0
	1851.5	18615	3	QPSK	1	14	21.88	0	0
	1851.5	18615	3	QPSK	8	0	20.88	0-1	1
	1851.5	18615	3	QPSK	8	4	20.77	0-1	1
	1851.5	18615	3	QPSK	8	7	20.81	0-1	1
	1851.5	18615	3	QPSK	15	0	20.79	0-1	1
	1851.5	18615	3	16-QAM	1	0	21.46	0-1	1
	1851.5	18615	3	16-QAM	1	7	21.47	0-1	1
	1851.5	18615	3	16-QAM	1	14	21.47	0-1	1
	1851.5	18615	3	16-QAM	8	0	19.93	0-2	2
	1851.5	18615	3	16-QAM	8	4	19.86	0-2	2
	1851.5	18615	3	16-QAM	8	7	19.90	0-2	2
	1851.5	18615	3	16-QAM	15	0	19.74	0-2	2
	1851.5	18615	3	16-QAM	15	0	19.74	0-2	2
Mid	1880.0	18900	3	QPSK	1	0	21.90	0	0
	1880.0	18900	3	QPSK	1	7	21.90	0	0
	1880.0	18900	3	QPSK	1	14	21.80	0	0
	1880.0	18900	3	QPSK	8	0	20.82	0-1	1
	1880.0	18900	3	QPSK	8	4	20.76	0-1	1
	1880.0	18900	3	QPSK	8	7	20.71	0-1	1
	1880.0	18900	3	QPSK	15	0	20.77	0-1	1
	1880.0	18900	3	16-QAM	1	0	21.44	0-1	1
	1880.0	18900	3	16-QAM	1	7	21.16	0-1	1
	1880.0	18900	3	16-QAM	1	14	21.47	0-1	1
	1880.0	18900	3	16-QAM	8	0	19.85	0-2	2
	1880.0	18900	3	16-QAM	8	4	19.93	0-2	2
	1880.0	18900	3	16-QAM	8	7	19.93	0-2	2
	1880.0	18900	3	16-QAM	15	0	19.84	0-2	2
	1880.0	18900	3	16-QAM	15	0	19.84	0-2	2
High	1908.5	19185	3	QPSK	1	0	21.78	0	0
	1908.5	19185	3	QPSK	1	7	21.80	0	0
	1908.5	19185	3	QPSK	1	14	21.82	0	0
	1908.5	19185	3	QPSK	8	0	20.80	0-1	1
	1908.5	19185	3	QPSK	8	4	20.73	0-1	1
	1908.5	19185	3	QPSK	8	7	20.74	0-1	1
	1908.5	19185	3	QPSK	15	0	20.69	0-1	1
	1908.5	19185	3	16-QAM	1	0	21.46	0-1	1
	1908.5	19185	3	16-QAM	1	7	21.44	0-1	1
	1908.5	19185	3	16-QAM	1	14	21.38	0-1	1
	1908.5	19185	3	16-QAM	8	0	19.73	0-2	2
	1908.5	19185	3	16-QAM	8	4	19.80	0-2	2
	1908.5	19185	3	16-QAM	8	7	19.93	0-2	2
	1908.5	19185	3	16-QAM	15	0	19.82	0-2	2
	1908.5	19185	3	16-QAM	15	0	19.82	0-2	2

**Table 9-18**  
**LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]		
Low	1850.7	18607	1.4	QPSK	1	0	22.04	0	0	
	1850.7	18607	1.4	QPSK	1	2	22.07	0	0	
	1850.7	18607	1.4	QPSK	1	5	22.03	0	0	
	1850.7	18607	1.4	QPSK	3	0	22.01	0	0	
	1850.7	18607	1.4	QPSK	3	2	22.01	0	0	
	1850.7	18607	1.4	QPSK	3	3	22.02	0	0	
	1850.7	18607	1.4	QPSK	6	0	21.00	0-1	1	
	1850.7	18607	1.4	16-QAM	1	0	21.48	0-1	1	
	1850.7	18607	1.4	16-QAM	1	2	21.30	0-1	1	
	1850.7	18607	1.4	16-QAM	1	5	21.47	0-1	1	
	1850.7	18607	1.4	16-QAM	3	0	21.23	0-1	1	
	1850.7	18607	1.4	16-QAM	3	2	21.08	0-1	1	
	1850.7	18607	1.4	16-QAM	3	3	21.06	0-1	1	
	1850.7	18607	1.4	16-QAM	6	0	20.09	0-2	2	
	Mid	1880.0	18900	1.4	QPSK	1	0	21.95	0	0
		1880.0	18900	1.4	QPSK	1	2	21.94	0	0
		1880.0	18900	1.4	QPSK	1	5	21.94	0	0
		1880.0	18900	1.4	QPSK	3	0	21.98	0	0
1880.0		18900	1.4	QPSK	3	2	22.02	0	0	
1880.0		18900	1.4	QPSK	3	3	22.01	0	0	
1880.0		18900	1.4	QPSK	6	0	20.88	0-1	1	
1880.0		18900	1.4	16-QAM	1	0	21.48	0-1	1	
1880.0		18900	1.4	16-QAM	1	2	21.50	0-1	1	
1880.0		18900	1.4	16-QAM	1	5	21.26	0-1	1	
1880.0		18900	1.4	16-QAM	3	0	21.05	0-1	1	
1880.0		18900	1.4	16-QAM	3	2	21.11	0-1	1	
1880.0		18900	1.4	16-QAM	3	3	21.07	0-1	1	
1880.0		18900	1.4	16-QAM	6	0	20.02	0-2	2	
High		1909.3	19193	1.4	QPSK	1	0	22.03	0	0
		1909.3	19193	1.4	QPSK	1	2	22.00	0	0
		1909.3	19193	1.4	QPSK	1	5	21.92	0	0
		1909.3	19193	1.4	QPSK	3	0	21.90	0	0
	1909.3	19193	1.4	QPSK	3	2	21.96	0	0	
	1909.3	19193	1.4	QPSK	3	3	21.93	0	0	
	1909.3	19193	1.4	QPSK	6	0	20.84	0-1	1	
	1909.3	19193	1.4	16-QAM	1	0	21.44	0-1	1	
	1909.3	19193	1.4	16-QAM	1	2	21.23	0-1	1	
	1909.3	19193	1.4	16-QAM	1	5	21.48	0-1	1	
	1909.3	19193	1.4	16-QAM	3	0	21.21	0-1	1	
	1909.3	19193	1.4	16-QAM	3	2	21.19	0-1	1	
	1909.3	19193	1.4	16-QAM	3	3	21.01	0-1	1	
	1909.3	19193	1.4	16-QAM	6	0	20.02	0-2	2	

**9.4 WLAN Antenna 1 Conducted Powers**

**Table 9-19**  
**IEEE 802.11b Average RF Power**



Mode	Freq [MHz]	Channel	802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1*	16.33	16.48	16.51	16.53
802.11b	2437	6*	16.34	16.45	16.53	16.58
802.11b	2462	11*	16.42	16.51	16.55	16.61

**Table 9-20**  
**IEEE 802.11g Average RF Power**

Mode	Freq [MHz]	Channel	802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	10.70	10.75	10.78	10.56	10.85	10.64	10.77	10.81
802.11g	2437	6	10.87	10.94	10.96	10.71	10.97	10.77	11.00	10.98
802.11g	2462	11	10.89	11.02	10.94	10.80	11.03	10.87	10.90	11.06

**Table 9-21**  
**IEEE 802.11n Average RF Power**

Mode	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	2412	1	9.35	9.32	9.33	9.55	9.60	9.49	9.54	9.55
802.11n	2437	6	9.57	9.61	9.55	9.74	9.91	9.77	9.82	9.73
802.11n	2462	11	9.64	9.56	9.64	9.78	9.91	9.78	9.84	9.83

FCC ID: A3LSMG850M		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 32 of 71

**Table 9-22**  
**IEEE 802.11a Average RF Power**



Mode	Freq [MHz]	Channel	802.11a Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11a	5180	36*	10.17	10.36	10.29	10.28	10.41	10.31	10.38	10.40
802.11a	5200	40	10.15	10.39	10.24	10.23	10.34	10.29	10.40	10.29
802.11a	5220	44	10.16	10.29	10.31	10.19	10.35	10.34	10.39	10.39
802.11a	5240	48*	10.00	10.14	10.13	10.05	10.23	10.10	10.15	10.22
802.11a	5260	52*	9.37	9.59	9.39	9.48	9.57	9.46	9.58	9.62
802.11a	5280	56	9.35	9.55	9.49	9.50	9.63	9.49	9.56	9.60
802.11a	5300	60	9.38	9.60	9.52	9.49	9.58	9.48	9.63	9.61
802.11a	5320	64*	9.43	9.63	9.50	9.62	9.62	9.51	9.59	9.66
802.11a	5500	100	10.08	10.32	10.20	10.22	10.26	10.26	10.28	10.24
802.11a	5520	104*	10.14	10.32	10.25	10.27	10.35	10.24	10.39	10.32
802.11a	5540	108	10.13	10.30	10.25	10.24	10.28	10.34	10.28	10.28
802.11a	5560	112	10.11	10.36	10.24	10.25	10.30	10.33	10.27	10.24
802.11a	5580	116*	10.14	10.41	10.24	10.20	10.33	10.30	10.42	10.32
802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5660	132	10.07	10.27	10.19	10.27	10.32	10.26	10.29	10.37
802.11a	5680	136*	10.19	10.33	10.35	10.27	10.34	10.34	10.34	10.42
802.11a	5700	140	10.12	10.17	10.10	10.09	10.29	10.17	10.23	10.22
802.11a	5745	149*	9.79	10.02	9.87	9.89	10.06	9.93	10.05	10.02
802.11a	5765	153	9.65	9.79	9.70	9.82	9.89	9.83	9.85	9.90
802.11a	5785	157*	9.78	10.02	9.82	9.86	9.95	9.86	9.98	10.00
802.11a	5805	161	9.76	9.92	9.91	9.94	9.93	9.94	9.92	9.99
802.11a	5825	165*	9.87	10.04	9.98	9.90	10.10	10.03	10.05	10.07

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(\*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power than the default channels, these “required channels” are considered for SAR testing instead of the default channels.

**Table 9-23**  
**IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	10.16	10.39	10.28	10.21	10.39	10.32	10.37	10.40
802.11n	5200	40	9.94	10.18	10.01	10.06	10.12	10.12	10.17	10.21
802.11n	5220	44	10.10	10.36	10.18	10.10	10.33	10.27	10.27	10.31
802.11n	5240	48	10.12	10.38	10.23	10.19	10.34	10.30	10.31	10.32
802.11n	5260	52	9.37	9.63	9.48	9.42	9.55	9.59	9.57	9.58
802.11n	5280	56	9.27	9.42	9.33	9.24	9.48	9.38	9.45	9.50
802.11n	5300	60	9.39	9.60	9.53	9.40	9.61	9.53	9.66	9.57
802.11n	5320	64	9.40	9.67	9.45	9.42	9.62	9.52	9.62	9.65
802.11n	5500	100	10.06	10.38	10.23	10.11	10.35	10.20	10.25	10.30
802.11n	5520	104	10.11	10.41	10.23	10.18	10.36	10.26	10.32	10.36
802.11n	5540	108	10.10	10.27	10.16	10.11	10.37	10.30	10.32	10.29
802.11n	5560	112	10.09	10.33	10.19	10.12	10.35	10.22	10.35	10.27
802.11n	5580	116	10.13	10.35	10.31	10.18	10.42	10.25	10.28	10.32
802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5660	132	10.06	10.30	10.16	10.05	10.26	10.17	10.27	10.26
802.11n	5680	136	10.16	10.38	10.35	10.19	10.38	10.24	10.38	10.35
802.11n	5700	140	10.00	10.17	10.12	10.02	10.16	10.19	10.13	10.30
802.11n	5745	149	9.39	9.60	9.51	9.43	9.66	9.54	9.60	9.64
802.11n	5765	153	9.40	9.61	9.53	9.46	9.64	9.55	9.65	9.69
802.11n	5785	157	9.32	9.60	9.35	9.31	9.56	9.47	9.61	9.63
802.11n	5805	161	9.30	9.55	9.46	9.34	9.46	9.37	9.51	9.56
802.11n	5825	165	9.29	9.56	9.39	9.31	9.46	9.44	9.48	9.52

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 33 of 71

**Table 9-24**  
**IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	9.30	9.32	9.24	9.48	9.47	9.48	9.49	9.42
802.11n	5230	46	9.11	9.08	8.99	9.22	9.21	9.28	9.30	9.18
802.11n	5270	54	8.55	8.60	8.51	8.70	8.64	8.66	8.72	8.70
802.11n	5310	62	8.58	8.58	8.60	8.75	8.74	8.77	8.76	8.70
802.11n	5510	102	9.03	9.06	8.96	9.21	9.21	9.14	9.21	9.18
802.11n	5550	110	9.10	9.10	9.07	9.22	9.23	9.27	9.25	9.28
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	9.13	9.20	9.10	9.28	9.24	9.35	9.34	9.32
802.11n	5755	151	8.25	8.20	8.16	8.40	8.45	8.48	8.42	8.32
802.11n	5795	159	8.36	8.41	8.31	8.55	8.49	8.59	8.55	8.45



Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.


**Table 9-25**  
**IEEE 802.11AC Average RF Power – 80 MHz Bandwidth**

Mode	Freq [MHz]	Channel	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
			Data Rate [Mbps]									
			29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac	5210	42	<b>8.34</b>	8.14	8.17	8.44	8.48	8.48	8.40	8.42	8.45	8.47
802.11ac	5290	58	<b>7.60</b>	7.34	7.44	7.67	7.71	7.79	7.71	7.67	7.70	7.72
802.11ac	5530	106	<b>8.08</b>	7.87	7.93	8.13	8.16	8.21	8.20	8.16	8.23	8.25
802.11ac	5775	155	<b>7.30</b>	7.20	7.17	7.31	7.39	7.43	7.37	7.36	7.41	7.44


Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For SISO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For SISO 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 34 of 71



**Figure 9-3**  
Power Measurement Setup for Bandwidths < 50 MHz



**Figure 9-4**  
Power Measurement Setup for Bandwidths > 50 MHz

## 9.5 WLAN Antenna 2 Conducted Powers

**Table 9-26**  
IEEE 802.11b Average RF Power



Mode	Freq [MHz]	Channel	802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1*	16.79	17.02	17.03	17.00
802.11b	2437	6*	16.52	16.73	16.75	16.69
802.11b	2462	11*	16.07	16.33	16.29	16.21

**Table 9-27**  
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	10.96	11.00	10.74	10.99	11.04	11.14	11.10	11.17
802.11g	2437	6	11.04	11.14	10.79	11.00	11.12	11.17	11.18	11.28
802.11g	2462	11	10.68	10.77	10.44	10.63	10.79	10.79	10.76	10.94

**Table 9-28**  
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	2412	1	9.74	9.68	9.58	9.96	10.03	9.91	9.92	9.89
802.11n	2437	6	9.51	9.48	9.33	9.78	9.81	9.72	9.66	9.64
802.11n	2462	11	9.30	9.25	9.15	9.54	9.61	9.49	9.42	9.46

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 35 of 71

**Table 9-29  
IEEE 802.11a Average RF Power**



Mode	Freq [MHz]	Channel	802.11a Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11a	5180	36*	10.23	10.10	10.02	10.05	10.14	10.25	10.34	10.33
802.11a	5200	40	10.23	10.10	10.07	9.99	10.09	10.29	10.33	10.24
802.11a	5220	44	10.35	10.24	10.19	10.24	10.26	10.31	10.48	10.45
802.11a	5240	48*	10.48	10.38	10.22	10.20	10.46	10.44	10.46	10.49
802.11a	5260	52*	9.67	9.63	9.55	9.61	9.75	9.77	9.67	9.85
802.11a	5280	56	9.92	9.88	9.84	9.83	10.07	9.96	9.97	10.15
802.11a	5300	60	9.83	9.84	9.71	9.76	9.99	9.93	9.82	10.03
802.11a	5320	64*	9.86	9.79	9.78	9.76	9.94	9.99	9.89	9.98
802.11a	5500	100	10.06	9.92	9.88	9.98	10.04	9.96	10.04	10.14
802.11a	5520	104*	9.97	9.83	9.77	9.92	9.94	9.83	9.94	9.96
802.11a	5540	108	9.97	9.91	9.76	9.96	9.93	9.82	9.95	10.04
802.11a	5560	112	10.09	9.97	9.94	9.98	10.09	9.99	10.03	10.16
802.11a	5580	116*	10.00	9.91	9.82	9.96	9.96	9.83	10.03	10.15
802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5660	132	10.01	9.83	9.84	9.97	10.01	9.89	9.92	10.01
802.11a	5680	136*	9.89	9.79	9.72	9.78	9.92	9.72	9.85	9.97
802.11a	5700	140	9.79	9.67	9.62	9.73	9.78	9.71	9.78	9.85
802.11a	5745	149*	9.69	9.73	9.45	9.53	9.74	9.71	9.78	9.92
802.11a	5765	153	9.64	9.65	9.34	9.45	9.64	9.67	9.74	9.93
802.11a	5785	157*	9.69	9.75	9.54	9.54	9.75	9.71	9.84	9.90
802.11a	5805	161	9.53	9.57	9.34	9.29	9.60	9.57	9.65	9.80
802.11a	5825	165*	9.42	9.47	9.22	9.28	9.46	9.36	9.44	9.66

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(\*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

**Table 9-30  
IEEE 802.11n Average RF Power – 20 MHz Bandwidth**

Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	9.95	10.00	9.95	10.42	10.40	10.17	10.42	10.22
802.11n	5200	40	10.03	10.03	10.10	10.49	10.41	10.19	10.49	10.22
802.11n	5220	44	10.08	10.20	10.09	10.49	10.46	10.26	10.48	10.40
802.11n	5240	48	9.15	9.22	9.18	9.53	9.51	9.37	9.55	9.38
802.11n	5260	52	9.50	9.50	9.49	9.89	9.89	9.69	9.70	9.78
802.11n	5280	56	9.70	9.75	9.75	10.08	10.11	9.92	9.84	9.98
802.11n	5300	60	9.62	9.56	9.63	10.00	9.93	9.82	9.91	9.95
802.11n	5320	64	9.76	9.75	9.74	10.14	10.15	10.02	10.03	10.06
802.11n	5500	100	9.80	9.67	9.85	10.21	10.13	10.01	10.22	10.04
802.11n	5520	104	9.81	9.65	9.89	10.24	10.10	10.05	10.24	10.02
802.11n	5540	108	9.84	9.75	9.88	10.28	10.13	10.04	10.25	10.05
802.11n	5560	112	9.81	9.73	9.93	10.15	10.21	10.08	10.28	10.05
802.11n	5580	116	9.73	9.58	9.77	10.11	10.09	9.95	10.13	9.98
802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5660	132	9.72	9.66	9.79	10.21	9.96	9.90	10.16	9.92
802.11n	5680	136	9.59	9.45	9.66	10.04	9.86	9.77	10.02	9.83
802.11n	5700	140	9.68	9.62	9.76	10.13	9.98	9.89	10.16	9.92
802.11n	5745	149	9.50	9.47	9.39	9.69	9.88	9.65	9.82	9.81
802.11n	5765	153	9.45	9.47	9.28	9.56	9.90	9.63	9.67	9.76
802.11n	5785	157	9.34	9.24	9.26	9.60	9.73	9.49	9.61	9.65
802.11n	5805	161	9.31	9.33	9.17	9.51	9.73	9.48	9.62	9.67
802.11n	5825	165	8.97	9.03	8.79	9.14	9.36	9.06	9.30	9.25

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 36 of 71

**Table 9-31  
IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	7.83	8.07	8.06	8.65	8.79	8.45	8.48	8.50
802.11n	5230	46	7.93	8.21	8.13	8.81	8.92	8.49	8.59	8.67
802.11n	5270	54	8.37	8.70	8.58	9.13	9.20	9.27	9.15	9.06
802.11n	5310	62	8.56	8.89	8.78	9.34	9.40	9.47	9.38	9.28
802.11n	5510	102	8.40	8.47	8.66	8.93	9.23	9.00	9.11	8.94
802.11n	5550	110	8.40	8.42	8.66	8.98	9.27	9.05	9.10	8.99
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	8.27	8.38	8.56	8.81	9.10	8.88	9.01	8.79
802.11n	5755	151	8.41	8.69	8.67	9.32	9.28	9.08	9.31	9.11
802.11n	5795	159	8.13	8.39	8.33	9.00	8.93	8.86	8.97	8.83



Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.


**Table 9-32  
IEEE 802.11AC Average RF Power – 80 MHz Bandwidth**

Mode	Freq [MHz]	Channel	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
			Data Rate [Mbps]									
			29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac	5210	42	8.18	8.24	8.12	7.78	7.81	7.67	7.66	7.71	7.76	7.71
802.11ac	5290	58	7.75	7.82	7.56	7.26	7.30	7.35	7.24	7.35	7.32	7.36
802.11ac	5530	106	7.60	7.74	7.45	7.30	7.35	7.24	7.25	7.33	7.26	7.29
802.11ac	5775	155	8.45	8.48	8.18	7.88	7.80	7.73	7.92	7.80	7.79	7.91


Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For SISO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For SISO 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 37 of 71



**Figure 9-5**  
Power Measurement Setup for Bandwidths < 50 MHz



**Figure 9-6**  
Power Measurement Setup for Bandwidths > 50 MHz

## 9.6 WLAN MIMO Conducted Powers

Per KDB 662911 D01v02r01, the individual spectra for each 2x2 MIMO WIFI antenna were summed mathematically in linear power units for the MIMO output power measurements.



**Table 9-33**  
IEEE 802.11n Average RF Power

802.11n (2.4GHz) Conducted Power [dBm]			
Mode	Freq [MHz]	Channel	Data Rate [Mbps]
			13
802.11n	2412	1	10.18
802.11n	2437	6	10.02
802.11n	2462	11	10.23

**Table 9-34**  
IEEE 802.11n Average RF Power – 20 MHz Bandwidth

20MHz BW 802.11n (5GHz) Conducted Power [dBm]			
Mode	Freq [MHz]	Channel	Data Rate [Mbps]
			13
802.11n	5180	36	9.73
802.11n	5200	40	9.63
802.11n	5220	44	9.58
802.11n	5240	48	9.58
802.11n	5260	52	9.81
802.11n	5280	56	9.89
802.11n	5300	60	9.82
802.11n	5320	64	9.85
802.11n	5500	100	10.25
802.11n	5520	104	10.23
802.11n	5540	108	10.18
802.11n	5560	112	10.27
802.11n	5580	116	10.19
802.11n	5600	120	N/A
802.11n	5620	124	N/A
802.11n	5640	128	N/A
802.11n	5660	132	10.25
802.11n	5680	136	10.21
802.11n	5700	140	10.20
802.11n	5745	149	10.19
802.11n	5765	153	10.31
802.11n	5785	157	10.21
802.11n	5805	161	10.18
802.11n	5825	165	10.11

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 38 of 71

**Table 9-35**  
**IEEE 802.11n Average RF Power – 40 MHz Bandwidth**

40MHz BW 802.11n (5GHz) Conducted Power [dBm]			
Mode	Freq [MHz]	Channel	Data Rate [Mbps]
			27
802.11n	5190	38	<b>9.35</b>
802.11n	5230	46	<b>9.39</b>
802.11n	5270	54	<b>8.55</b>
802.11n	5310	62	<b>8.66</b>
802.11n	5510	102	<b>9.00</b>
802.11n	5550	110	<b>8.97</b>
802.11n	5590	118	N/A
802.11n	5630	126	N/A
802.11n	5670	134	<b>8.92</b>
802.11n	5755	151	<b>9.04</b>
802.11n	5795	159	<b>9.05</b>



Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

**Table 9-36**  
**IEEE 802.11ac Average RF Power – 80 MHz Bandwidth**

80MHz BW 802.11ac (5GHz) Conducted Power [dBm]			
Mode	Freq [MHz]	Channel	Data Rate [Mbps]
			58.5
802.11ac	5210	42	<b>7.26</b>
802.11ac	5290	58	<b>7.56</b>
802.11ac	5530	106	<b>7.77</b>
802.11ac	5775	155	<b>7.74</b>

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- Per KDB 662911 D01v02r01, the individual spectra for each 2x2 MIMO WIFI Antenna were summed mathematically in linear power units for the MIMO output power measurements.
- For MIMO 2.4 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11n were selected for SAR evaluation.
- For MIMO 5 GHz, highest average RF output power channel for the lowest data rate for IEEE 802.11n 20 MHz Bandwidth were selected for SAR evaluation.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.

FCC ID: A3LSMG850M	 <b>PCTEST</b> <small>ENGINEERING LABORATORY, INC.</small>	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 39 of 71



# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1  
Measured Head Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
7/14/2014	750B	22.3	710	0.965	56.510	0.960	55.687	0.52%	1.48%
			725	0.980	56.367	0.961	55.629	1.98%	1.33%
			740	0.994	56.241	0.963	55.570	3.22%	1.21%
			755	1.010	56.124	0.964	55.512	4.77%	1.10%
7/21/2014	835B	22.9	820	0.995	54.599	0.969	55.258	2.68%	-1.19%
			835	1.010	54.452	0.970	55.200	4.12%	-1.36%
			850	1.024	54.282	0.988	55.154	3.64%	-1.58%
7/21/2014	1750B	21.0	1710	1.496	52.641	1.463	53.537	2.26%	-1.67%
			1750	1.539	52.495	1.488	53.432	3.43%	-1.75%
			1790	1.584	52.349	1.514	53.326	4.62%	-1.83%
7/24/2014	1900B	23.2	1850	1.451	51.415	1.520	53.300	-4.54%	-3.54%
			1880	1.484	51.316	1.520	53.300	-2.37%	-3.72%
			1910	1.519	51.222	1.520	53.300	-0.07%	-3.90%
6/12/2014	2450B	23.4	2401	1.915	51.764	1.903	52.765	0.63%	-1.90%
			2450	1.981	51.567	1.950	52.700	1.59%	-2.15%
			2499	2.043	51.406	2.019	52.638	1.19%	-2.34%
			5180	5.440	47.494	5.276	49.041	3.11%	-3.15%
06/16/2014	5200B-5800B	22.2	5200	5.454	47.504	5.299	49.014	2.93%	-3.08%
			5220	5.484	47.539	5.323	48.987	3.02%	-2.96%
			5240	5.473	47.483	5.346	48.960	2.38%	-3.02%
			5280	5.565	47.387	5.393	48.906	3.19%	-3.11%
			5300	5.592	47.351	5.416	48.879	3.25%	-3.13%
			5320	5.659	47.366	5.439	48.851	4.04%	-3.04%
			5500	5.881	47.322	5.650	48.607	4.09%	-2.64%
			5520	5.907	47.268	5.673	48.580	4.12%	-2.70%
			5540	5.931	47.226	5.696	48.553	4.13%	-2.73%
			5560	5.978	47.228	5.720	48.526	4.51%	-2.67%
			5600	6.014	47.230	5.766	48.471	4.30%	-2.56%
			5680	6.090	47.014	5.860	48.363	3.92%	-2.79%
			5745	6.148	46.909	5.936	48.275	3.57%	-2.83%
			5765	6.158	46.770	5.959	48.248	3.34%	-3.06%
			5785	6.188	46.692	5.982	48.220	3.44%	-3.17%
			5800	6.210	46.638	6.000	48.200	3.50%	-3.24%
			5825	6.233	46.688	6.029	48.166	3.38%	-3.07%



The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 40 of 71

**Table 10-2  
Measured Body Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
7/14/2014	750B	22.3	710	0.965	56.510	0.960	55.687	0.52%	1.48%
			725	0.980	56.367	0.961	55.629	1.98%	1.33%
			740	0.994	56.241	0.963	55.570	3.22%	1.21%
			755	1.010	56.124	0.964	55.512	4.77%	1.10%
7/21/2014	835B	22.9	820	0.995	54.599	0.969	55.258	2.68%	-1.19%
			835	1.010	54.452	0.970	55.200	4.12%	-1.36%
			850	1.024	54.282	0.988	55.154	3.64%	-1.58%
7/21/2014	1750B	21.0	1710	1.496	52.641	1.463	53.537	2.26%	-1.67%
			1750	1.539	52.495	1.488	53.432	3.43%	-1.75%
			1790	1.584	52.349	1.514	53.326	4.62%	-1.83%
7/24/2014	1900B	23.2	1850	1.449	51.415	1.520	53.300	-4.69%	-3.54%
			1880	1.484	51.316	1.520	53.300	-2.37%	-3.72%
			1910	1.517	51.222	1.520	53.300	-0.23%	-3.90%
6/12/2014	2450B	23.4	2401	1.915	51.764	1.903	52.765	0.63%	-1.90%
			2450	1.981	51.567	1.950	52.700	1.59%	-2.15%
			2499	2.043	51.406	2.019	52.638	1.19%	-2.34%
06/16/2014	5200B-5800B	22.2	5180	5.440	47.494	5.276	49.041	3.11%	-3.15%
			5200	5.454	47.504	5.299	49.014	2.93%	-3.08%
			5220	5.484	47.539	5.323	48.987	3.02%	-2.96%
			5240	5.473	47.483	5.346	48.960	2.38%	-3.02%
			5280	5.565	47.387	5.393	48.906	3.19%	-3.11%
			5300	5.592	47.351	5.416	48.879	3.25%	-3.13%
			5320	5.659	47.366	5.439	48.851	4.04%	-3.04%
			5500	5.881	47.322	5.650	48.607	4.09%	-2.64%
			5520	5.907	47.268	5.673	48.580	4.12%	-2.70%
			5540	5.931	47.226	5.696	48.553	4.13%	-2.73%
			5560	5.978	47.228	5.720	48.526	4.51%	-2.67%
			5600	6.014	47.230	5.766	48.471	4.30%	-2.56%
			5680	6.090	47.014	5.860	48.363	3.92%	-2.79%
			5745	6.148	46.909	5.936	48.275	3.57%	-2.83%
			5765	6.158	46.770	5.959	48.248	3.34%	-3.06%
			5785	6.188	46.692	5.982	48.220	3.44%	-3.17%
			5800	6.210	46.638	6.000	48.200	3.50%	-3.24%
5825	6.233	46.688	6.029	48.166	3.38%	-3.07%			

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 41 of 71

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-3**  
**System Verification Results**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR <sub>1g</sub> (W/kg)	1 W Target SAR <sub>1g</sub> (W/kg)	1 W Normalized SAR <sub>1g</sub> (W/kg)	Deviation <sub>1g</sub> (%)
I	750	HEAD	07/22/2014	24.5	22.5	0.100	1003	3209	0.891	8.370	8.910	6.45%
H	835	HEAD	07/23/2014	23.3	22.9	0.100	4d119	3319	0.931	9.220	9.310	0.98%
C	1750	HEAD	07/14/2014	23.4	22.4	0.100	1051	3213	3.650	36.200	36.500	0.83%
J	1900	HEAD	07/23/2014	22.7	23.4	0.100	5d141	3332	3.930	40.100	39.300	-2.00%
I	2450	HEAD	07/09/2014	23.2	23.4	0.100	797	3209	5.460	51.800	54.600	5.41%
E	5200	HEAD	06/09/2014	23.0	22.0	0.100	1057	3914	7.750	78.000	77.500	-0.64%
E	5300	HEAD	06/09/2014	23.0	22.1	0.100	1057	3914	8.250	83.000	82.500	-0.60%
E	5500	HEAD	06/09/2014	23.0	22.1	0.100	1057	3914	7.820	84.300	78.200	-7.24%
E	5600	HEAD	06/09/2014	23.0	22.1	0.100	1057	3914	8.240	83.500	82.400	-1.32%
E	5800	HEAD	06/09/2014	23.1	22.1	0.100	1057	3914	7.830	79.300	78.300	-1.26%
B	750	BODY	07/14/2014	24.2	22.5	0.100	1046	3288	0.886	8.540	8.860	3.75%
J	835	BODY	07/21/2014	22.6	22.9	0.100	4d119	3332	0.962	9.340	9.620	3.00%
C	1750	BODY	07/21/2014	23.3	21.0	0.100	1051	3213	3.670	37.400	36.700	-1.87%
B	1900	BODY	07/24/2014	23.5	23.2	0.100	5d148	3288	4.100	39.300	41.000	4.33%
H	2450	BODY	06/12/2014	23.1	23.5	0.100	719	3319	5.410	51.700	54.100	4.64%
A	5200	BODY	06/16/2014	24.4	22.4	0.100	1007	3920	7.400	72.600	74.000	1.93%
A	5300	BODY	06/16/2014	24.4	22.4	0.100	1007	3920	7.530	74.700	75.300	0.80%
A	5500	BODY	06/16/2014	24.5	22.5	0.100	1007	3920	7.620	75.900	76.200	0.40%
A	5600	BODY	06/16/2014	24.5	22.5	0.100	1007	3920	7.650	77.300	76.500	-1.03%
A	5800	BODY	06/16/2014	24.5	22.5	0.100	1007	3920	6.920	72.900	69.200	-5.08%



**Figure 10-1**  
**System Verification Setup Diagram**



**Figure 10-2**  
**System Verification Setup Photo**

FCC ID: A3LSMG850M	PCTEST INDEPENDENT LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 42 of 71

# 11 SAR DATA SUMMARY

## 11.1 Standalone Head SAR Data

**Table 11-1  
GSM 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.0	33.62	0.11	Right	Cheek	1107-1	1:8.3	0.278	1.091	0.303	
836.60	190	GSM 850	GSM	34.0	33.62	-0.02	Right	Tilt	1107-1	1:8.3	0.182	1.091	0.199	
836.60	190	GSM 850	GSM	34.0	33.62	0.00	Left	Cheek	1107-1	1:8.3	0.290	1.091	0.316	A1
836.60	190	GSM 850	GSM	34.0	33.62	0.00	Left	Tilt	1107-1	1:8.3	0.191	1.091	0.208	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-2  
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.5	24.29	0.04	Right	Cheek	1107-1	1:1	0.250	1.050	0.263	
836.60	4183	UMTS 850	RMC	24.5	24.29	0.07	Right	Tilt	1107-1	1:1	0.155	1.050	0.163	
836.60	4183	UMTS 850	RMC	24.5	24.29	-0.04	Left	Cheek	1107-1	1:1	0.256	1.050	0.269	A2
836.60	4183	UMTS 850	RMC	24.5	24.29	0.14	Left	Tilt	1107-1	1:1	0.163	1.050	0.171	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-3  
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.02	Right	Cheek	1107-1	1:1	0.293	1.005	0.294	A3
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.01	Right	Tilt	1107-1	1:1	0.150	1.005	0.151	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.04	Left	Cheek	1107-1	1:1	0.228	1.005	0.229	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.06	Left	Tilt	1107-1	1:1	0.185	1.005	0.186	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 43 of 71

**Table 11-4  
GSM 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.5	30.24	0.05	Right	Cheek	1107-2	1:8.3	0.436	1.062	0.463	
1880.00	661	GSM 1900	GSM	30.5	30.24	0.01	Right	Tilt	1107-2	1:8.3	0.296	1.062	0.314	
1880.00	661	GSM 1900	GSM	30.5	30.24	-0.07	Left	Cheek	1107-2	1:8.3	0.529	1.062	0.562	A4
1880.00	661	GSM 1900	GSM	30.5	30.24	0.05	Left	Tilt	1107-2	1:8.3	0.294	1.062	0.312	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram					

**Table 11-5  
UMTS 1900 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	-0.06	Right	Cheek	1107-2	1:1	0.402	1.076	0.433	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	0.08	Right	Tilt	1107-2	1:1	0.182	1.076	0.196	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	-0.21	Left	Cheek	1107-2	1:1	0.437	1.076	0.470	A5
1880.00	9400	UMTS 1900	RMC	22.0	21.68	0.01	Left	Tilt	1107-2	1:1	0.258	1.076	0.278	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram					

**Table 11-6  
LTE Band 17 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.21	0	Right	Cheek	QPSK	1	0	1107-1	1:1	0.082	1.059	0.087	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	0.02	1	Right	Cheek	QPSK	25	0	1107-1	1:1	0.061	1.072	0.065	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.16	0	Right	Tilt	QPSK	1	0	1107-1	1:1	0.048	1.059	0.051	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	0.16	1	Right	Tilt	QPSK	25	0	1107-1	1:1	0.039	1.072	0.042	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.11	0	Left	Cheek	QPSK	1	0	1107-1	1:1	0.102	1.059	0.108	A6
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	0.01	1	Left	Cheek	QPSK	25	0	1107-1	1:1	0.083	1.072	0.089	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.13	0	Left	Tilt	QPSK	1	0	1107-1	1:1	0.045	1.059	0.048	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	0.15	1	Left	Tilt	QPSK	25	0	1107-1	1:1	0.037	1.072	0.040	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-7  
LTE Band 5 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.07	0	Right	Cheek	QPSK	1	0	1107-1	1:1	0.199	1.099	0.219	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	0.07	1	Right	Cheek	QPSK	25	0	1107-1	1:1	0.163	1.067	0.174	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.04	0	Right	Tilt	QPSK	1	0	1107-1	1:1	0.117	1.099	0.129	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	0.09	1	Right	Tilt	QPSK	25	0	1107-1	1:1	0.095	1.067	0.101	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	-0.03	0	Left	Cheek	QPSK	1	0	1107-1	1:1	0.252	1.099	0.277	A7
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	0.02	1	Left	Cheek	QPSK	25	0	1107-1	1:1	0.199	1.067	0.212	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	-0.03	0	Left	Tilt	QPSK	1	0	1107-1	1:1	0.128	1.099	0.141	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	0.14	1	Left	Tilt	QPSK	25	0	1107-1	1:1	0.109	1.067	0.116	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									



FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 44 of 71

**Table 11-8  
LTE Band 4 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.01	0	Right	Cheek	QPSK	1	0	1107-1	1:1	0.319	1.042	0.332	A8
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	-0.03	1	Right	Cheek	QPSK	50	0	1107-1	1:1	0.258	1.094	0.282	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.01	0	Right	Tilt	QPSK	1	0	1107-1	1:1	0.181	1.042	0.189	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	-0.05	1	Right	Tilt	QPSK	50	0	1107-1	1:1	0.142	1.094	0.155	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.02	0	Left	Cheek	QPSK	1	0	1107-1	1:1	0.306	1.042	0.319	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	-0.01	1	Left	Cheek	QPSK	50	0	1107-1	1:1	0.242	1.094	0.265	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.06	0	Left	Tilt	QPSK	1	0	1107-1	1:1	0.239	1.042	0.249	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	0.03	1	Left	Tilt	QPSK	50	0	1107-1	1:1	0.196	1.094	0.214	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									



**Table 11-9  
LTE Band 2 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.20	0	Right	Cheek	QPSK	1	0	1107-1	1:1	0.380	1.076	0.409	A9
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.06	1	Right	Cheek	QPSK	50	0	1107-1	1:1	0.300	1.086	0.326	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	-0.13	0	Right	Tilt	QPSK	1	0	1107-1	1:1	0.141	1.076	0.152	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	-0.11	1	Right	Tilt	QPSK	50	0	1107-1	1:1	0.107	1.086	0.116	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.17	0	Left	Cheek	QPSK	1	0	1107-1	1:1	0.310	1.076	0.334	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.15	1	Left	Cheek	QPSK	50	0	1107-1	1:1	0.235	1.086	0.255	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	-0.03	0	Left	Tilt	QPSK	1	0	1107-1	1:1	0.202	1.076	0.217	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.04	1	Left	Tilt	QPSK	50	0	1107-1	1:1	0.157	1.086	0.171	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 45 of 71



**Table 11-10  
DTS Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.03	Right	Cheek	1	0707-1	1	1:1	0.101	1.282	0.129	A10
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.03	Right	Tilt	1	0707-1	1	1:1	0.061	1.282	0.078	
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.05	Left	Cheek	1	0707-1	1	1:1	0.041	1.282	0.053	
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.03	Left	Tilt	1	0707-1	1	1:1	0.026	1.282	0.033	
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.11	Right	Cheek	2	0707-1	1	1:1	0.013	1.178	0.015	
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.11	Right	Tilt	2	0707-1	1	1:1	0.013	1.178	0.015	
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.05	Left	Cheek	2	0707-1	1	1:1	0.032	1.178	0.038	
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.07	Left	Tilt	2	0707-1	1	1:1	0.024	1.178	0.028	
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.03	Right	Cheek	MIMO	0707-1	13	1:1	0.015	1.064	0.016	
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.09	Right	Tilt	MIMO	0707-1	13	1:1	0.009	1.064	0.010	
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.20	Left	Cheek	MIMO	0707-1	13	1:1	0.007	1.064	0.007	
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.02	Left	Tilt	MIMO	0707-1	13	1:1	0.006	1.064	0.006	
5825	165	IEEE 802.11a	OFDM	10.5	9.87	0.11	Right	Cheek	1	0906-1	6	1:1	0.114	1.156	0.132	
5825	165	IEEE 802.11a	OFDM	10.5	9.87	0.05	Right	Tilt	1	0906-1	6	1:1	0.122	1.156	0.141	
5775	155	IEEE 802.11ac	OFDM	8.5	7.30	0.10	Right	Tilt	1	0906-1	29.3	1:1	0.119	1.318	0.157	
5825	165	IEEE 802.11a	OFDM	10.5	9.87	0.03	Left	Cheek	1	0906-1	6	1:1	0.048	1.156	0.055	
5825	165	IEEE 802.11a	OFDM	10.5	9.87	-0.05	Left	Tilt	1	0906-1	6	1:1	0.079	1.156	0.091	
5745	149	IEEE 802.11a	OFDM	10.5	9.69	-0.05	Right	Cheek	2	0906-1	6	1:1	0.058	1.205	0.070	
5745	149	IEEE 802.11a	OFDM	10.5	9.69	0.08	Right	Tilt	2	0906-1	6	1:1	0.056	1.205	0.067	
5745	149	IEEE 802.11a	OFDM	10.5	9.69	0.14	Left	Cheek	2	0906-1	6	1:1	0.082	1.205	0.099	
5775	155	IEEE 802.11ac	OFDM	8.5	8.45	-0.07	Left	Cheek	2	0906-1	29.3	1:1	0.071	1.012	0.072	
5745	149	IEEE 802.11a	OFDM	10.5	9.69	-0.12	Left	Tilt	2	0906-1	6	1:1	0.057	1.205	0.069	
5765	153	IEEE 802.11n	OFDM	10.5	10.31	0.15	Right	Cheek	MIMO	0906-1	13	1:1	0.126	1.045	0.132	
5765	153	IEEE 802.11n	OFDM	10.5	10.31	0.02	Right	Tilt	MIMO	0906-1	13	1:1	0.198	1.045	0.207	A11
5765	153	IEEE 802.11n	OFDM	10.5	10.31	0.02	Left	Cheek	MIMO	0906-1	13	1:1	0.192	1.045	0.201	
5765	153	IEEE 802.11n	OFDM	10.5	10.31	-0.05	Left	Tilt	MIMO	0906-1	13	1:1	0.152	1.045	0.159	
<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population</b>								<b>Head 1.6 W/kg (mW/g) averaged over 1 gram</b>								

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 46 of 71

**Table 11-11  
NII Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
Mhz	Ch.												(W/kg)		(W/kg)	
5180	36	IEEE 802.11a	OFDM	10.5	10.17	0.08	Right	Cheek	1	0906-1	6	1:1	0.027	1.079	0.029	
5180	36	IEEE 802.11a	OFDM	10.5	10.17	-0.03	Right	Tilt	1	0906-1	6	1:1	0.030	1.079	0.032	
5210	42	IEEE 802.11ac	OFDM	8.5	8.34	0.02	Right	Tilt	1	0906-1	29.3	1:1	0.030	1.038	0.031	
5180	36	IEEE 802.11a	OFDM	10.5	10.17	0.09	Left	Cheek	1	0906-1	6	1:1	0.014	1.079	0.015	
5180	36	IEEE 802.11a	OFDM	10.5	10.17	-0.06	Left	Tilt	1	0906-1	6	1:1	0.014	1.079	0.015	
5320	64	IEEE 802.11a	OFDM	10.5	9.43	0.03	Right	Cheek	1	0906-1	6	1:1	0.096	1.279	0.123	
5320	64	IEEE 802.11a	OFDM	10.5	9.43	0.03	Right	Tilt	1	0906-1	6	1:1	0.115	1.279	0.147	
5290	58	IEEE 802.11ac	OFDM	8.5	7.60	0.18	Right	Tilt	1	0906-1	29.3	1:1	0.080	1.230	0.098	
5320	64	IEEE 802.11a	OFDM	10.5	9.43	-0.04	Left	Cheek	1	0906-1	6	1:1	0.049	1.279	0.063	
5320	64	IEEE 802.11a	OFDM	10.5	9.43	0.12	Left	Tilt	1	0906-1	6	1:1	0.048	1.279	0.061	
5680	136	IEEE 802.11a	OFDM	10.5	10.19	0.06	Right	Cheek	1	0906-1	6	1:1	0.070	1.074	0.075	
5680	136	IEEE 802.11a	OFDM	10.5	10.19	0.03	Right	Tilt	1	0906-1	6	1:1	0.095	1.074	0.102	
5530	106	IEEE 802.11ac	OFDM	8.5	8.08	0.07	Right	Tilt	1	0906-1	29.3	1:1	0.096	1.102	0.106	
5680	136	IEEE 802.11a	OFDM	10.5	10.19	0.02	Left	Cheek	1	0906-1	6	1:1	0.055	1.074	0.059	
5680	136	IEEE 802.11a	OFDM	10.5	10.19	-0.17	Left	Tilt	1	0906-1	6	1:1	0.058	1.074	0.062	
5240	48	IEEE 802.11a	OFDM	10.5	10.48	0.08	Right	Cheek	2	0906-1	6	1:1	0.031	1.005	0.031	
5240	48	IEEE 802.11a	OFDM	10.5	10.48	0.11	Right	Tilt	2	0906-1	6	1:1	0.030	1.005	0.030	
5240	48	IEEE 802.11a	OFDM	10.5	10.48	0.04	Left	Cheek	2	0906-1	6	1:1	0.076	1.005	0.076	
5210	42	IEEE 802.11ac	OFDM	8.5	8.18	-0.12	Left	Cheek	2	0906-1	29.3	1:1	0.043	1.076	0.046	
5240	48	IEEE 802.11a	OFDM	10.5	10.48	-0.04	Left	Tilt	2	0906-1	6	1:1	0.044	1.005	0.044	
5280	56	IEEE 802.11a	OFDM	10.5	9.92	0.08	Right	Cheek	2	0906-1	6	1:1	0.022	1.143	0.025	
5280	56	IEEE 802.11a	OFDM	10.5	9.92	0.20	Right	Tilt	2	0906-1	6	1:1	0.020	1.143	0.023	
5280	56	IEEE 802.11a	OFDM	10.5	9.92	0.09	Left	Cheek	2	0906-1	6	1:1	0.057	1.143	0.065	
5290	58	IEEE 802.11ac	OFDM	8.5	7.75	0.07	Left	Cheek	2	0906-1	29.3	1:1	0.033	1.189	0.039	
5280	56	IEEE 802.11a	OFDM	10.5	9.92	0.04	Left	Tilt	2	0906-1	6	1:1	0.031	1.143	0.035	
5560	112	IEEE 802.11a	OFDM	10.5	10.09	0.07	Right	Cheek	2	0906-1	6	1:1	0.043	1.099	0.047	
5560	112	IEEE 802.11a	OFDM	10.5	10.09	0.03	Right	Tilt	2	0906-1	6	1:1	0.040	1.099	0.044	
5560	112	IEEE 802.11a	OFDM	10.5	10.09	-0.04	Left	Cheek	2	0906-1	6	1:1	0.095	1.099	0.104	
5530	106	IEEE 802.11ac	OFDM	8.5	7.60	0.12	Left	Cheek	2	0906-1	29.3	1:1	0.043	1.230	0.053	
5560	112	IEEE 802.11a	OFDM	10.5	10.09	-0.10	Left	Tilt	2	0906-1	6	1:1	0.060	1.099	0.066	
5180	36	IEEE 802.11n	OFDM	10.5	9.73	0.07	Right	Cheek	MIMO	0906-1	13	1:1	0.041	1.194	0.049	
5180	36	IEEE 802.11n	OFDM	10.5	9.73	0.07	Right	Tilt	MIMO	0906-1	13	1:1	0.054	1.194	0.064	
5180	36	IEEE 802.11n	OFDM	10.5	9.73	0.15	Left	Cheek	MIMO	0906-1	13	1:1	0.089	1.194	0.106	
5180	36	IEEE 802.11n	OFDM	10.5	9.73	0.08	Left	Tilt	MIMO	0906-1	13	1:1	0.061	1.194	0.073	
5280	56	IEEE 802.11n	OFDM	10.5	9.89	0.04	Right	Cheek	MIMO	0906-1	13	1:1	0.107	1.151	0.123	
5280	56	IEEE 802.11n	OFDM	10.5	9.89	0.03	Right	Tilt	MIMO	0906-1	13	1:1	0.136	1.151	0.157	
5280	56	IEEE 802.11n	OFDM	10.5	9.89	0.01	Left	Cheek	MIMO	0906-1	13	1:1	0.108	1.151	0.124	
5280	56	IEEE 802.11n	OFDM	10.5	9.89	0.10	Left	Tilt	MIMO	0906-1	13	1:1	0.068	1.151	0.078	
5560	112	IEEE 802.11n	OFDM	10.5	10.27	0.04	Right	Cheek	MIMO	0906-1	13	1:1	0.113	1.054	0.119	
5560	112	IEEE 802.11n	OFDM	10.5	10.27	0.05	Right	Tilt	MIMO	0906-1	13	1:1	0.147	1.054	0.155	
5560	112	IEEE 802.11n	OFDM	10.5	10.27	0.05	Left	Cheek	MIMO	0906-1	13	1:1	0.154	1.054	0.162	A12
5560	112	IEEE 802.11n	OFDM	10.5	10.27	0.13	Left	Tilt	MIMO	0906-1	13	1:1	0.140	1.054	0.148	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 47 of 71

## 11.2 Standalone Body-Worn SAR Data

**Table 11-12  
GSM/UMTS Body-Worn SAR Data**



MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.0	33.62	0.00	10 mm	1107-1	1	1:8.3	back	0.452	1.091	0.493	A13
836.60	4183	UMTS 850	RMC	24.5	24.29	-0.04	10 mm	1107-1	N/A	1:1	back	0.418	1.050	0.439	A15
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.11	10 mm	1107-2	N/A	1:1	back	0.687	1.005	0.690	A17
1880.00	661	GSM 1900	GSM	30.5	30.24	0.06	10 mm	1107-2	1	1:8.3	back	0.378	1.062	0.401	A19
1880.00	9400	UMTS 1900	RMC	22.0	21.68	0.07	10 mm	1107-2	N/A	1:1	back	0.460	1.076	0.495	A21
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-13  
LTE Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.01	0	1107-1	QPSK	1	0	10 mm	back	1:1	0.176	1.059	0.186	A23
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.04	1	1107-1	QPSK	25	0	10 mm	back	1:1	0.163	1.072	0.175	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.02	0	1107-1	QPSK	1	0	10 mm	back	1:1	0.359	1.099	0.395	A25
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	-0.02	1	1107-1	QPSK	25	0	10 mm	back	1:1	0.283	1.067	0.302	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.02	0	1107-2	QPSK	1	0	10 mm	back	1:1	0.592	1.042	0.617	A26
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	0.00	1	1107-2	QPSK	50	0	10 mm	back	1:1	0.477	1.094	0.522	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.01	0	1107-2	QPSK	1	0	10 mm	back	1:1	0.498	1.076	0.536	A28
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	-0.01	1	1107-2	QPSK	50	0	10 mm	back	1:1	0.404	1.086	0.439	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



**Table 11-14  
DTS Body-Worn SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.04	10 mm	1	0906-1	1	back	1:1	0.102	1.282	0.131	A30
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.00	10 mm	2	0906-1	1	back	1:1	0.069	1.178	0.081	
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.04	10 mm	MIMO	0906-1	13	back	1:1	0.031	1.064	0.033	
5825	165	IEEE 802.11a	OFDM	10.5	9.87	0.15	10 mm	1	0906-2	6	back	1:1	0.020	1.156	0.023	
5775	155	IEEE 802.11ac	OFDM	8.5	7.30	0.14	10 mm	1	0906-2	29.3	back	1:1	0.024	1.318	0.032	A32
5745	149	IEEE 802.11a	OFDM	10.5	9.69	0.04	10 mm	2	0906-2	6	back	1:1	0.016	1.205	0.019	
5775	155	IEEE 802.11ac	OFDM	8.5	8.45	0.05	10 mm	2	0906-2	29.3	back	1:1	0.020	1.012	0.020	
5765	153	IEEE 802.11n	OFDM	10.5	10.31	0.08	10 mm	MIMO	0906-2	13	back	1:1	0.017	1.045	0.018	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMG850M		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 48 of 71

**Table 11-15  
NII Body-Worn SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Cover Type	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.													(W/kg)		(W/kg)	
5180	36	IEEE 802.11a	OFDM	10.5	10.17	0.10	10 mm	1	Standard	0906-2	6	back	1:1	0.025	1.079	0.027	
5210	42	IEEE 802.11ac	OFDM	8.5	8.34	0.07	10 mm	1	Standard	0906-2	29.3	back	1:1	0.011	1.038	0.011	
5320	64	IEEE 802.11a	OFDM	10.5	9.43	0.07	10 mm	1	Standard	0906-2	6	back	1:1	0.018	1.279	0.023	
5290	58	IEEE 802.11ac	OFDM	8.5	7.60	0.03	10 mm	1	Standard	0906-2	29.3	back	1:1	0.008	1.230	0.010	
5680	136	IEEE 802.11a	OFDM	10.5	10.19	-0.04	10 mm	1	Standard	0906-2	6	back	1:1	0.020	1.074	0.021	
5530	106	IEEE 802.11ac	OFDM	8.5	8.08	-0.05	10 mm	1	Standard	0906-2	29.3	back	1:1	0.028	1.102	0.031	
5240	48	IEEE 802.11a	OFDM	10.5	10.48	0.14	10 mm	2	Standard	0906-2	6	back	1:1	0.027	1.005	0.027	
5210	42	IEEE 802.11ac	OFDM	8.5	8.18	0.16	10 mm	2	Standard	0906-2	29.3	back	1:1	0.023	1.076	0.025	
5280	56	IEEE 802.11a	OFDM	10.5	9.92	-0.07	10 mm	2	Standard	0906-2	6	back	1:1	0.020	1.143	0.023	
5290	58	IEEE 802.11ac	OFDM	8.5	7.75	0.05	10 mm	2	Standard	0906-2	29.3	back	1:1	0.020	1.189	0.024	
5560	112	IEEE 802.11a	OFDM	10.5	10.09	0.14	10 mm	2	Standard	0906-2	6	back	1:1	0.015	1.099	0.016	
5530	106	IEEE 802.11ac	OFDM	8.5	7.60	0.13	10 mm	2	Standard	0906-2	29.3	back	1:1	0.019	1.230	0.023	
5180	36	IEEE 802.11n	OFDM	10.5	9.73	-0.05	10 mm	MIMO	Standard	0906-2	13	back	1:1	0.032	1.194	0.038	A33
5280	56	IEEE 802.11n	OFDM	10.5	9.89	-0.05	10 mm	MIMO	Standard	0906-2	13	back	1:1	0.025	1.151	0.029	
5560	112	IEEE 802.11n	OFDM	10.5	10.27	-0.18	10 mm	MIMO	Standard	0906-2	13	back	1:1	0.022	1.054	0.023	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram										



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 49 of 71

### 11.3 Standalone Wireless Router SAR Data

Table 11-16  
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	28.5	27.84	0.00	10 mm	1107-1	4	1:2.076	back	0.478	1.164	0.556	A14
836.60	190	GSM 850	GPRS	28.5	27.84	0.01	10 mm	1107-1	4	1:2.076	front	0.473	1.164	0.551	
836.60	190	GSM 850	GPRS	28.5	27.84	0.04	10 mm	1107-1	4	1:2.076	bottom	0.083	1.164	0.097	
836.60	190	GSM 850	GPRS	28.5	27.84	-0.07	10 mm	1107-1	4	1:2.076	right	0.237	1.164	0.276	
836.60	190	GSM 850	GPRS	28.5	27.84	0.01	10 mm	1107-1	4	1:2.076	left	0.306	1.164	0.356	
836.60	4183	UMTS 850	RMC	24.5	24.29	-0.04	10 mm	1107-1	N/A	1:1	back	0.418	1.050	0.439	
836.60	4183	UMTS 850	RMC	24.5	24.29	0.05	10 mm	1107-1	N/A	1:1	front	0.438	1.050	0.460	A16
836.60	4183	UMTS 850	RMC	24.5	24.29	-0.08	10 mm	1107-1	N/A	1:1	bottom	0.082	1.050	0.086	
836.60	4183	UMTS 850	RMC	24.5	24.29	-0.16	10 mm	1107-1	N/A	1:1	right	0.204	1.050	0.214	
836.60	4183	UMTS 850	RMC	24.5	24.29	0.04	10 mm	1107-1	N/A	1:1	left	0.243	1.050	0.255	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.11	10 mm	1107-2	N/A	1:1	back	0.687	1.005	0.690	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	0.08	10 mm	1107-2	N/A	1:1	front	0.691	1.005	0.694	
1712.40	1312	UMTS 1750	RMC	21.5	21.41	-0.01	10 mm	1107-2	N/A	1:1	bottom	0.918	1.021	0.937	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	-0.05	10 mm	1107-2	N/A	1:1	bottom	0.892	1.005	0.896	
1752.50	1862	UMTS 1750	RMC	21.5	21.13	0.02	10 mm	1107-2	N/A	1:1	bottom	0.940	1.089	1.024	A18
1732.40	1412	UMTS 1750	RMC	21.5	21.48	0.02	10 mm	1107-2	N/A	1:1	right	0.098	1.005	0.098	
1732.40	1412	UMTS 1750	RMC	21.5	21.48	0.05	10 mm	1107-2	N/A	1:1	left	0.270	1.005	0.271	
1752.50	1862	UMTS 1750	RMC	21.5	21.13	0.00	10 mm	1107-2	N/A	1:1	bottom	0.914	1.089	0.995	
1880.00	661	GSM 1900	GPRS	26.5	26.11	-0.04	10 mm	1107-2	3	1:2.76	back	0.471	1.094	0.515	
1880.00	661	GSM 1900	GPRS	26.5	26.11	-0.03	10 mm	1107-2	3	1:2.76	front	0.591	1.094	0.647	
1880.00	661	GSM 1900	GPRS	26.5	26.11	-0.21	10 mm	1107-2	3	1:2.76	bottom	0.646	1.094	0.707	A20
1880.00	661	GSM 1900	GPRS	26.5	26.11	-0.03	10 mm	1107-2	3	1:2.76	right	0.228	1.094	0.249	
1880.00	661	GSM 1900	GPRS	26.5	26.11	0.20	10 mm	1107-2	3	1:2.76	left	0.068	1.094	0.074	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	0.07	10 mm	1107-2	N/A	1:1	back	0.460	1.076	0.495	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	0.05	10 mm	1107-2	N/A	1:1	front	0.492	1.076	0.529	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	-0.05	10 mm	1107-2	N/A	1:1	bottom	0.716	1.076	0.770	A22
1880.00	9400	UMTS 1900	RMC	22.0	21.68	-0.02	10 mm	1107-2	N/A	1:1	right	0.236	1.076	0.254	
1880.00	9400	UMTS 1900	RMC	22.0	21.68	-0.17	10 mm	1107-2	N/A	1:1	left	0.071	1.076	0.076	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Variability data highlighted blue in the table above.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 50 of 71

**Table 11-17  
LTE Band 17 Hotspot SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.01	0	1107-1	QPSK	1	0	10 mm	back	1:1	0.176	1.059	0.186	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.04	1	1107-1	QPSK	25	0	10 mm	back	1:1	0.163	1.072	0.175	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	-0.03	0	1107-1	QPSK	1	0	10 mm	front	1:1	0.210	1.059	0.222	A24
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.02	1	1107-1	QPSK	25	0	10 mm	front	1:1	0.196	1.072	0.210	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	-0.03	0	1107-1	QPSK	1	0	10 mm	bottom	1:1	0.055	1.059	0.058	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.13	1	1107-1	QPSK	25	0	10 mm	bottom	1:1	0.049	1.072	0.053	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	-0.05	0	1107-1	QPSK	1	0	10 mm	right	1:1	0.057	1.059	0.060	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.04	1	1107-1	QPSK	25	0	10 mm	right	1:1	0.058	1.072	0.062	
710.00	23790	Mid	LTE Band 17	10	24.0	23.75	0.19	0	1107-1	QPSK	1	0	10 mm	left	1:1	0.079	1.059	0.084	
710.00	23790	Mid	LTE Band 17	10	23.0	22.70	-0.15	1	1107-1	QPSK	25	0	10 mm	left	1:1	0.079	1.072	0.085	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-18  
LTE Band 5 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.02	0	1107-1	QPSK	1	0	10 mm	back	1:1	0.359	1.099	0.395	A25
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	-0.02	1	1107-1	QPSK	25	0	10 mm	back	1:1	0.283	1.067	0.302	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.06	0	1107-1	QPSK	1	0	10 mm	front	1:1	0.348	1.099	0.382	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	-0.01	1	1107-1	QPSK	25	0	10 mm	front	1:1	0.277	1.067	0.296	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	-0.03	0	1107-1	QPSK	1	0	10 mm	bottom	1:1	0.058	1.099	0.064	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	0.02	1	1107-1	QPSK	25	0	10 mm	bottom	1:1	0.050	1.067	0.053	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.21	0	1107-1	QPSK	1	0	10 mm	right	1:1	0.241	1.099	0.265	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	-0.03	1	1107-1	QPSK	25	0	10 mm	right	1:1	0.168	1.067	0.179	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.09	0.01	0	1107-1	QPSK	1	0	10 mm	left	1:1	0.249	1.099	0.274	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.5	22.22	-0.02	1	1107-1	QPSK	25	0	10 mm	left	1:1	0.191	1.067	0.204	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-19  
LTE Band 4 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.																		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.02	0	1107-2	QPSK	1	0	10 mm	back	1:1	0.592	1.042	0.617	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	0.00	1	1107-2	QPSK	50	0	10 mm	back	1:1	0.477	1.094	0.522	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.04	0	1107-2	QPSK	1	0	10 mm	front	1:1	0.657	1.042	0.685	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	0.03	1	1107-2	QPSK	50	0	10 mm	front	1:1	0.528	1.094	0.578	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.07	0	1107-2	QPSK	1	0	10 mm	bottom	1:1	0.878	1.042	0.915	A27
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	0.01	1	1107-2	QPSK	50	0	10 mm	bottom	1:1	0.699	1.094	0.765	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.49	-0.02	1	1107-2	QPSK	100	0	10 mm	bottom	1:1	0.686	1.125	0.772	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	0.05	0	1107-2	QPSK	1	0	10 mm	right	1:1	0.093	1.042	0.097	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	-0.02	1	1107-2	QPSK	50	0	10 mm	right	1:1	0.077	1.094	0.084	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.82	-0.05	0	1107-2	QPSK	1	0	10 mm	left	1:1	0.235	1.042	0.245	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.61	-0.07	1	1107-2	QPSK	50	0	10 mm	left	1:1	0.176	1.094	0.193	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										



FCC ID: A3LSMG850M		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 51 of 71

**Table 11-20  
LTE Band 2 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.01	0	1107-2	QPSK	1	0	10 mm	back	1:1	0.498	1.076	0.536	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	-0.01	1	1107-2	QPSK	50	0	10 mm	back	1:1	0.404	1.086	0.439	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	-0.04	0	1107-2	QPSK	1	0	10 mm	front	1:1	0.540	1.076	0.581	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.13	1	1107-2	QPSK	50	0	10 mm	front	1:1	0.416	1.086	0.452	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.20	0	1107-2	QPSK	1	0	10 mm	bottom	1:1	0.629	1.076	0.677	A29
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.09	1	1107-2	QPSK	50	0	10 mm	bottom	1:1	0.487	1.086	0.529	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.03	0	1107-2	QPSK	1	0	10 mm	right	1:1	0.292	1.076	0.314	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	0.01	1	1107-2	QPSK	50	0	10 mm	right	1:1	0.226	1.086	0.245	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	22.18	0.14	0	1107-2	QPSK	1	0	10 mm	left	1:1	0.079	1.076	0.085	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	21.14	-0.01	1	1107-2	QPSK	50	0	10 mm	left	1:1	0.059	1.086	0.064	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-21  
WLAN Hotspot SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.												(W/kg)		(W/kg)		
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.04	10 mm	1	0906-1	1	back	1:1	0.102	1.282	0.131		
2462	11	IEEE 802.11b	DSSS	17.5	16.42	-0.02	10 mm	1	0906-1	1	front	1:1	0.068	1.282	0.087		
2462	11	IEEE 802.11b	DSSS	17.5	16.42	-0.07	10 mm	1	0906-1	1	top	1:1	0.122	1.282	0.156	A31	
2462	11	IEEE 802.11b	DSSS	17.5	16.42	0.10	10 mm	1	0906-1	1	left	1:1	0.040	1.282	0.051		
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.00	10 mm	2	0906-1	1	back	1:1	0.069	1.178	0.081		
2412	1	IEEE 802.11b	DSSS	17.5	16.79	-0.06	10 mm	2	0906-1	1	front	1:1	0.085	1.178	0.100		
2412	1	IEEE 802.11b	DSSS	17.5	16.79	-0.02	10 mm	2	0906-1	1	top	1:1	0.076	1.178	0.090		
2412	1	IEEE 802.11b	DSSS	17.5	16.79	0.04	10 mm	2	0906-1	1	right	1:1	0.068	1.178	0.080		
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.04	10 mm	MIMO	0906-1	13	back	1:1	0.031	1.064	0.033		
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.03	10 mm	MIMO	0906-1	13	front	1:1	0.032	1.064	0.034		
2462	11	IEEE 802.11n	OFDM	10.5	10.23	-0.01	10 mm	MIMO	0906-1	13	top	1:1	0.049	1.064	0.052		
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.20	10 mm	MIMO	0906-1	13	right	1:1	0.019	1.064	0.020		
2462	11	IEEE 802.11n	OFDM	10.5	10.23	0.05	10 mm	MIMO	0906-1	13	left	1:1	0.009	1.064	0.010		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 52 of 71

## 11.4 SAR Test Notes

### General Notes:



1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements. A specialized battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was  $\leq 1.2$  W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

### GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D03v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.

### UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel was used.



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 53 of 71

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI SISO operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other SISO IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for SISO 5 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE SISO 802.11 modes (including 802.11n 20 MHz and 40 MHz bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
3. Per April 2013 TCB Workshop notes, full SISO SAR tests for all IEEE 802.11ac configurations were not required because the average output power was not more than 0.25 dB higher than IEEE 802.11a mode. IEEE 802.11ac SISO was evaluated for the highest IEEE 802.11a position in each 5 GHz band and exposure condition.
4. When Hotspot is enabled, all 5 GHz bands are disabled. Therefore no 5 GHz WIFI Wireless Router SAR Data was required.
5. Per KDB 248227, SAR for MIMO was measured with both transmitting simultaneously and was evaluated in dependently of SISO operation. For 2.4 GHz MIMO, 802.11n was evaluated. For 5 GHz MIMO, 20 MHz bandwidth 802.11n was evaluated.
6. WIFI transmission was verified using an uncalibrated spectrum analyzer.
7. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other default channels was not required.

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset	Page 54 of 71	

# 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

## 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n/ac and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

## 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is  $\leq 1.6$  W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1  
Estimated SAR**



Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	11.00	10	0.273

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

## 12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2  
Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	$\Sigma$ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	$\Sigma$ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.129	<b>0.432</b>	Head SAR	Right Cheek	0.263	0.129	<b>0.392</b>
	Right Tilt	0.199	0.078	0.277		Right Tilt	0.163	0.078	0.241
	Left Cheek	0.316	0.053	0.369		Left Cheek	0.269	0.053	0.322
	Left Tilt	0.208	0.033	0.241		Left Tilt	0.171	0.033	0.204
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	$\Sigma$ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	$\Sigma$ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.129	<b>0.423</b>	Head SAR	Right Cheek	0.463	0.129	0.592
	Right Tilt	0.151	0.078	0.229		Right Tilt	0.314	0.078	0.392
	Left Cheek	0.229	0.053	0.282		Left Cheek	0.562	0.053	<b>0.615</b>
	Left Tilt	0.186	0.033	0.219		Left Tilt	0.312	0.033	0.345

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 55 of 71

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.129	<b>0.562</b>	Head SAR	Right Cheek	0.087	0.129	<b>0.216</b>
	Right Tilt	0.196	0.078	0.274		Right Tilt	0.051	0.078	0.129
	Left Cheek	0.470	0.053	0.523		Left Cheek	0.108	0.053	0.161
	Left Tilt	0.278	0.033	0.311		Left Tilt	0.048	0.033	0.081
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.219	0.129	<b>0.348</b>	Head SAR	Right Cheek	0.332	0.129	<b>0.461</b>
	Right Tilt	0.129	0.078	0.207		Right Tilt	0.189	0.078	0.267
	Left Cheek	0.277	0.053	0.330		Left Cheek	0.319	0.053	0.372
	Left Tilt	0.141	0.033	0.174		Left Tilt	0.249	0.033	0.282
Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)					
Head SAR	Right Cheek	0.409	0.129	<b>0.538</b>					
	Right Tilt	0.152	0.078	0.230					
	Left Cheek	0.334	0.053	0.387					
	Left Tilt	0.217	0.033	0.250					

**Table 12-3**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.015	0.318	Head SAR	Right Cheek	0.263	0.015	0.278
	Right Tilt	0.199	0.015	0.214		Right Tilt	0.163	0.015	0.178
	Left Cheek	0.316	0.038	<b>0.354</b>		Left Cheek	0.269	0.038	<b>0.307</b>
	Left Tilt	0.208	0.028	0.236		Left Tilt	0.171	0.028	0.199
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.015	<b>0.309</b>	Head SAR	Right Cheek	0.463	0.015	0.478
	Right Tilt	0.151	0.015	0.166		Right Tilt	0.314	0.015	0.329
	Left Cheek	0.229	0.038	0.267		Left Cheek	0.562	0.038	<b>0.600</b>
	Left Tilt	0.186	0.028	0.214		Left Tilt	0.312	0.028	0.340
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.015	0.448	Head SAR	Right Cheek	0.087	0.015	0.102
	Right Tilt	0.196	0.015	0.211		Right Tilt	0.051	0.015	0.066
	Left Cheek	0.470	0.038	<b>0.508</b>		Left Cheek	0.108	0.038	<b>0.146</b>
	Left Tilt	0.278	0.028	0.306		Left Tilt	0.048	0.028	0.076
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.219	0.015	0.234	Head SAR	Right Cheek	0.332	0.015	0.347
	Right Tilt	0.129	0.015	0.144		Right Tilt	0.189	0.015	0.204
	Left Cheek	0.277	0.038	<b>0.315</b>		Left Cheek	0.319	0.038	<b>0.357</b>
	Left Tilt	0.141	0.028	0.169		Left Tilt	0.249	0.028	0.277

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.409	0.015	<b>0.424</b>
	Right Tilt	0.152	0.015	0.167
	Left Cheek	0.334	0.038	0.372
	Left Tilt	0.217	0.028	0.245



**Table 12-4**  
**Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.016	0.319	Head SAR	Right Cheek	0.263	0.016	<b>0.279</b>
	Right Tilt	0.199	0.010	0.209		Right Tilt	0.163	0.010	0.173
	Left Cheek	0.316	0.007	<b>0.323</b>		Left Cheek	0.269	0.007	0.276
	Left Tilt	0.208	0.006	0.214		Left Tilt	0.171	0.006	0.177
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.016	<b>0.310</b>	Head SAR	Right Cheek	0.463	0.016	0.479
	Right Tilt	0.151	0.010	0.161		Right Tilt	0.314	0.010	0.324
	Left Cheek	0.229	0.007	0.236		Left Cheek	0.562	0.007	<b>0.569</b>
	Left Tilt	0.186	0.006	0.192		Left Tilt	0.312	0.006	0.318
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.016	0.449	Head SAR	Right Cheek	0.087	0.016	0.103
	Right Tilt	0.196	0.010	0.206		Right Tilt	0.051	0.010	0.061
	Left Cheek	0.470	0.007	<b>0.477</b>		Left Cheek	0.108	0.007	<b>0.115</b>
	Left Tilt	0.278	0.006	0.284		Left Tilt	0.048	0.006	0.054
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.219	0.016	0.235	Head SAR	Right Cheek	0.332	0.016	<b>0.348</b>
	Right Tilt	0.129	0.010	0.139		Right Tilt	0.189	0.010	0.199
	Left Cheek	0.277	0.007	<b>0.284</b>		Left Cheek	0.319	0.007	0.326
	Left Tilt	0.141	0.006	0.147		Left Tilt	0.249	0.006	0.255

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.409	0.016	<b>0.425</b>
	Right Tilt	0.152	0.010	0.162
	Left Cheek	0.334	0.007	0.341
	Left Tilt	0.217	0.006	0.223

**Table 12-5**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 1 (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.132	<b>0.435</b>	Head SAR	Right Cheek	0.263	0.132	<b>0.395</b>
	Right Tilt	0.199	0.157	0.356		Right Tilt	0.163	0.157	0.320
	Left Cheek	0.316	0.063	0.379		Left Cheek	0.269	0.063	0.332
	Left Tilt	0.208	0.091	0.299		Left Tilt	0.171	0.091	0.262

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 57 of 71

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.132	<b>0.426</b>	Head SAR	Right Cheek	0.463	0.132	0.595
	Right Tilt	0.151	0.157	0.308		Right Tilt	0.314	0.157	0.471
	Left Cheek	0.229	0.063	0.292		Left Cheek	0.562	0.063	<b>0.625</b>
	Left Tilt	0.186	0.091	0.277		Left Tilt	0.312	0.091	0.403

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.132	<b>0.565</b>
	Right Tilt	0.196	0.157	0.353
	Left Cheek	0.470	0.063	0.533
	Left Tilt	0.278	0.091	0.369

**Table 12-6**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.070	0.373	Head SAR	Right Cheek	0.263	0.070	0.333
	Right Tilt	0.199	0.067	0.266		Right Tilt	0.163	0.067	0.230
	Left Cheek	0.316	0.104	<b>0.420</b>		Left Cheek	0.269	0.104	<b>0.373</b>
	Left Tilt	0.208	0.069	0.277		Left Tilt	0.171	0.069	0.240

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.070	<b>0.364</b>	Head SAR	Right Cheek	0.463	0.070	0.533
	Right Tilt	0.151	0.067	0.218		Right Tilt	0.314	0.067	0.381
	Left Cheek	0.229	0.104	0.333		Left Cheek	0.562	0.104	<b>0.666</b>
	Left Tilt	0.186	0.069	0.255		Left Tilt	0.312	0.069	0.381

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.070	0.503
	Right Tilt	0.196	0.067	0.263
	Left Cheek	0.470	0.104	<b>0.574</b>
	Left Tilt	0.278	0.069	0.347

**Table 12-7**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Held to Ear)**

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.303	0.132	0.435	Head SAR	Right Cheek	0.263	0.132	0.395
	Right Tilt	0.199	0.207	0.406		Right Tilt	0.163	0.207	0.370
	Left Cheek	0.316	0.201	<b>0.517</b>		Left Cheek	0.269	0.201	<b>0.470</b>
	Left Tilt	0.208	0.159	0.367		Left Tilt	0.171	0.159	0.330

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.294	0.132	0.426	Head SAR	Right Cheek	0.463	0.132	0.595
	Right Tilt	0.151	0.207	0.358		Right Tilt	0.314	0.207	0.521
	Left Cheek	0.229	0.201	<b>0.430</b>		Left Cheek	0.562	0.201	<b>0.763</b>
	Left Tilt	0.186	0.159	0.345		Left Tilt	0.312	0.159	0.471

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	$\Sigma$ SAR (W/kg)
Head SAR	Right Cheek	0.433	0.132	0.565
	Right Tilt	0.196	0.207	0.403
	Left Cheek	0.470	0.201	<b>0.671</b>
	Left Tilt	0.278	0.159	0.437

## 12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-8**

### Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 1 (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	$\Sigma$ SAR (W/kg)
Back Side	GSM 850	0.493	0.131	0.624
Back Side	UMTS 850	0.439	0.131	0.570
Back Side	UMTS 1750	0.690	0.131	<b>0.821</b>
Back Side	GSM 1900	0.401	0.131	0.532
Back Side	UMTS 1900	0.495	0.131	0.626
Back Side	LTE Band 17	0.186	0.131	0.317
Back Side	LTE Band 5 (Cell)	0.395	0.131	0.526
Back Side	LTE Band 4 (AWS)	0.617	0.131	0.748
Back Side	LTE Band 2 (PCS)	0.536	0.131	0.667

**Table 12-9**



### Simultaneous Transmission Scenario with 2.4 GHz WLAN Antenna 2 (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	$\Sigma$ SAR (W/kg)
Back Side	GSM 850	0.493	0.081	0.574
Back Side	UMTS 850	0.439	0.081	0.520
Back Side	UMTS 1750	0.690	0.081	<b>0.771</b>
Back Side	GSM 1900	0.401	0.081	0.482
Back Side	UMTS 1900	0.495	0.081	0.576
Back Side	LTE Band 17	0.186	0.081	0.267
Back Side	LTE Band 5 (Cell)	0.395	0.081	0.476
Back Side	LTE Band 4 (AWS)	0.617	0.081	0.698
Back Side	LTE Band 2 (PCS)	0.536	0.081	0.617

**Table 12-10**

### Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	$\Sigma$ SAR (W/kg)
Back Side	GSM 850	0.493	0.033	0.526
Back Side	UMTS 850	0.439	0.033	0.472
Back Side	UMTS 1750	0.690	0.033	<b>0.723</b>
Back Side	GSM 1900	0.401	0.033	0.434
Back Side	UMTS 1900	0.495	0.033	0.528
Back Side	LTE Band 17	0.186	0.033	0.219
Back Side	LTE Band 5 (Cell)	0.395	0.033	0.428
Back Side	LTE Band 4 (AWS)	0.617	0.033	0.650
Back Side	LTE Band 2 (PCS)	0.536	0.033	0.569

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 59 of 71

**Table 12-11**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Ant 1 (Body-Worn at 1.0 cm)**

Configuration	Mode	2G/3G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.493	0.032	0.525
Back Side	UMTS 850	0.439	0.032	0.471
Back Side	UMTS 1750	0.690	0.032	<b>0.722</b>
Back Side	GSM 1900	0.401	0.032	0.433
Back Side	UMTS 1900	0.495	0.032	0.527

**Table 12-12**  
**Simultaneous Transmission Scenario with 5 GHz WLAN Antenna 2 (Body-Worn at 1.0 cm)**

Configuration	Mode	2G/3G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.493	0.027	0.520
Back Side	UMTS 850	0.439	0.027	0.466
Back Side	UMTS 1750	0.690	0.027	<b>0.717</b>
Back Side	GSM 1900	0.401	0.027	0.428
Back Side	UMTS 1900	0.495	0.027	0.522



**Table 12-13**  
**Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body-Worn at 1.0 cm)**

Configuration	Mode	2G/3G SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.493	0.038	0.531
Back Side	UMTS 850	0.439	0.038	0.477
Back Side	UMTS 1750	0.690	0.038	<b>0.728</b>
Back Side	GSM 1900	0.401	0.038	0.439
Back Side	UMTS 1900	0.495	0.038	0.533

**Table 12-14**  
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)**

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.493	0.273	0.766
Back Side	UMTS 850	0.439	0.273	0.712
Back Side	UMTS 1750	0.690	0.273	<b>0.963</b>
Back Side	GSM 1900	0.401	0.273	0.674
Back Side	UMTS 1900	0.495	0.273	0.768
Back Side	LTE Band 17	0.186	0.273	0.459
Back Side	LTE Band 5 (Cell)	0.395	0.273	0.668
Back Side	LTE Band 4 (AWS)	0.617	0.273	0.890
Back Side	LTE Band 2 (PCS)	0.536	0.273	0.809

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMG850M		<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 60 of 71



## 12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

**Table 12-15**  
**Simultaneous Transmission Scenario (2.4 GHz WLAN Antenna 1 Hotspot at 1.0 cm)**

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.556	0.131	<b>0.687</b>	Body SAR	Back	0.439	0.131	<b>0.570</b>
	Front	0.551	0.087	0.638		Front	0.460	0.087	0.547
	Top	-	0.156	0.156		Top	-	0.156	0.156
	Bottom	0.097	-	0.097		Bottom	0.086	-	0.086
	Right	0.276	-	0.276		Right	0.214	-	0.214
	Left	0.356	0.051	0.407		Left	0.255	0.051	0.306
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.690	0.131	0.821	Body SAR	Back	0.515	0.131	0.646
	Front	0.694	0.087	0.781		Front	0.647	0.087	<b>0.734</b>
	Top	-	0.156	0.156		Top	-	0.156	0.156
	Bottom	1.024	-	<b>1.024</b>		Bottom	0.707	-	0.707
	Right	0.098	-	0.098		Right	0.249	-	0.249
	Left	0.271	0.051	0.322		Left	0.074	0.051	0.125
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.495	0.131	0.626	Body SAR	Back	0.186	0.131	<b>0.317</b>
	Front	0.529	0.087	0.616		Front	0.222	0.087	0.309
	Top	-	0.156	0.156		Top	-	0.156	0.156
	Bottom	0.770	-	<b>0.770</b>		Bottom	0.058	-	0.058
	Right	0.254	-	0.254		Right	0.062	-	0.062
	Left	0.076	0.051	0.127		Left	0.085	0.051	0.136
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.395	0.131	<b>0.526</b>	Body SAR	Back	0.617	0.131	0.748
	Front	0.382	0.087	0.469		Front	0.685	0.087	0.772
	Top	-	0.156	0.156		Top	-	0.156	0.156
	Bottom	0.064	-	0.064		Bottom	0.915	-	<b>0.915</b>
	Right	0.265	-	0.265		Right	0.097	-	0.097
	Left	0.274	0.051	0.325		Left	0.245	0.051	0.296



Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.536	0.131	0.667
	Front	0.581	0.087	0.668
	Top	-	0.156	0.156
	Bottom	0.677	-	<b>0.677</b>
	Right	0.314	-	0.314
	Left	0.085	0.051	0.136

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 61 of 71

**Table 12-16**  
**Simultaneous Transmission Scenario (2.4 GHz WLAN Antenna 2 Hotspot at 1.0 cm)**

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.556	0.081	0.637	Body SAR	Back	0.439	0.081	0.520
	Front	0.551	0.100	<b>0.651</b>		Front	0.460	0.100	<b>0.560</b>
	Top	-	0.090	0.090		Top	-	0.090	0.090
	Bottom	0.097	-	0.097		Bottom	0.086	-	0.086
	Right	0.276	0.080	0.356		Right	0.214	0.080	0.294
	Left	0.356	-	0.356		Left	0.255	-	0.255
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.690	0.081	0.771	Body SAR	Back	0.515	0.081	0.596
	Front	0.694	0.100	0.794		Front	0.647	0.100	<b>0.747</b>
	Top	-	0.090	0.090		Top	-	0.090	0.090
	Bottom	1.024	-	<b>1.024</b>		Bottom	0.707	-	0.707
	Right	0.098	0.080	0.178		Right	0.249	0.080	0.329
	Left	0.271	-	0.271		Left	0.074	-	0.074
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.495	0.081	0.576	Body SAR	Back	0.186	0.081	0.267
	Front	0.529	0.100	0.629		Front	0.222	0.100	<b>0.322</b>
	Top	-	0.090	0.090		Top	-	0.090	0.090
	Bottom	0.770	-	<b>0.770</b>		Bottom	0.058	-	0.058
	Right	0.254	0.080	0.334		Right	0.062	0.080	0.142
	Left	0.076	-	0.076		Left	0.085	-	0.085
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.395	0.081	0.476	Body SAR	Back	0.617	0.081	0.698
	Front	0.382	0.100	<b>0.482</b>		Front	0.685	0.100	0.785
	Top	-	0.090	0.090		Top	-	0.090	0.090
	Bottom	0.064	-	0.064		Bottom	0.915	-	<b>0.915</b>
	Right	0.265	0.080	0.345		Right	0.097	0.080	0.177
	Left	0.274	-	0.274		Left	0.245	-	0.245

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.536	0.081	0.617
	Front	0.581	0.100	<b>0.681</b>
	Top	-	0.090	0.090
	Bottom	0.677	-	0.677
	Right	0.314	0.080	0.394
	Left	0.085	-	0.085



FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 62 of 71

**Table 12-17**  
**Simultaneous Transmission Scenario (2.4 GHz WLAN MIMO Hotspot at 1.0 cm)**

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.556	0.033	<b>0.589</b>	Body SAR	Back	0.439	0.033	0.472
	Front	0.551	0.034	0.585		Front	0.460	0.034	<b>0.494</b>
	Top	-	0.052	0.052		Top	-	0.052	0.052
	Bottom	0.097	-	0.097		Bottom	0.086	-	0.086
	Right	0.276	0.020	0.296		Right	0.214	0.020	0.234
	Left	0.356	0.010	0.366		Left	0.255	0.010	0.265
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.690	0.033	0.723	Body SAR	Back	0.515	0.033	0.548
	Front	0.694	0.034	0.728		Front	0.647	0.034	0.681
	Top	-	0.052	0.052		Top	-	0.052	0.052
	Bottom	1.024	-	<b>1.024</b>		Bottom	0.707	-	<b>0.707</b>
	Right	0.098	0.020	0.118		Right	0.249	0.020	0.269
	Left	0.271	0.010	0.281		Left	0.074	0.010	0.084
Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.495	0.033	0.528	Body SAR	Back	0.186	0.033	0.219
	Front	0.529	0.034	0.563		Front	0.222	0.034	<b>0.256</b>
	Top	-	0.052	0.052		Top	-	0.052	0.052
	Bottom	0.770	-	<b>0.770</b>		Bottom	0.058	-	0.058
	Right	0.254	0.020	0.274		Right	0.062	0.020	0.082
	Left	0.076	0.010	0.086		Left	0.085	0.010	0.095
Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.395	0.033	<b>0.428</b>	Body SAR	Back	0.617	0.033	0.650
	Front	0.382	0.034	0.416		Front	0.685	0.034	0.719
	Top	-	0.052	0.052		Top	-	0.052	0.052
	Bottom	0.064	-	0.064		Bottom	0.915	-	<b>0.915</b>
	Right	0.265	0.020	0.285		Right	0.097	0.020	0.117
	Left	0.274	0.010	0.284		Left	0.245	0.010	0.255
Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)					
Body SAR	Back	0.536	0.033	0.569					
	Front	0.581	0.034	0.615					
	Top	-	0.052	0.052					
	Bottom	0.677	-	<b>0.677</b>					
	Right	0.314	0.020	0.334					
	Left	0.085	0.010	0.095					

## 12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG850M	 PCTEST INDEPENDENT LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 63 of 71

# 13 SAR MEASUREMENT VARIABILITY

## 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:



- 1) When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 4) Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg

**Table 13-1  
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1752.50	1862	UMTS 1750	RMC	bottom	10 mm	0.940	0.914	1.03	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

## 13.2 Measurement Uncertainty



The measured SAR was  $< 1.5$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 64 of 71

# 14 EQUIPMENT LIST



Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E4438C	ESG Vector Signal Generator	3/31/2014	Annual	3/31/2015	MY42082659
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45091346
Agilent	E5515C	Wireless Communications Test Set	9/24/2012	Biennial	9/24/2014	GB43163447
Agilent	8753ES	S-Parameter Network Analyzer	5/22/2014	Annual	5/22/2015	US39170118
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45090700
Agilent	E4438C	ESG Vector Signal Generator	4/1/2014	Annual	4/1/2015	MY47270002
Agilent	8753ES	S-Parameter Network Analyzer	10/29/2013	Annual	10/29/2014	US39170122
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420800
Agilent	E4438C	ESG Vector Signal Generator	4/25/2014	Annual	4/25/2015	MY42082385
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420651
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629U00687
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	N9020A	MXA Signal Analyzer	10/29/2013	Annual	10/29/2014	US46470561
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433975
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433976
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433977
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433974
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433972
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433978
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MT8820C	Radio Communication Analyzer	12/12/2013	Annual	12/12/2014	6200901190
Anritsu	MA2411B	Pulse Power Sensor	11/14/2013	Annual	11/14/2014	1126066
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1244515
Anritsu	MA24106A	USB Power Sensor	12/18/2013	Annual	12/18/2014	1344559
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1248508
Anritsu	MA24106A	USB Power Sensor	5/15/2014	Annual	5/15/2015	1244512
Anritsu	MA24106A	USB Power Sensor	5/15/2014	Annual	5/15/2015	1244524
Anritsu	ML2495A	Power Meter	10/31/2013	Annual	10/31/2014	1039008
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1349501
Anritsu	MA2411B	Pulse Power Sensor	3/25/2014	Annual	3/25/2015	1207470
Anritsu	ML2469A	Power Meter	3/14/2014	Annual	3/14/2015	1306009
Anritsu	MA2411B	Pulse Power Sensor	2/3/2014	Annual	2/3/2015	1339018
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1344554
Anritsu	MA24106A	USB Power Sensor	1/3/2014	Annual	1/3/2015	1349509
Anritsu	MA2481A	Power Sensor	10/30/2013	Annual	10/30/2014	5605
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Control Company	61220-416	Long-Stem Thermometer	4/29/2014	Biennial	4/29/2016	111331323
Control Company	36934-158	Wall-Mounted Thermometer	4/29/2014	Biennial	4/29/2016	122014488
Control Company	4052	Long Stem Thermometer	9/27/2013	Biennial	9/27/2015	130567447
Control Company	4353	Long Stem Thermometer	9/25/2012	Biennial	9/25/2014	122541139
Control Company	4353	Long Stem Thermometer	9/25/2012	Biennial	9/25/2014	122541143
Fisher Scientific	S97611	Thermometer	4/12/2013	Biennial	4/12/2015	130219304
Fisher Scientific	15-077-960	Digital Thermometer	11/6/2012	Biennial	11/6/2014	122640025
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764551
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764558
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671826
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2013	Annual	10/30/2014	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2013	Annual	10/30/2014	8650319
Rohde & Schwarz	CMW500	Radio Communication Tester	4/23/2014	Annual	4/23/2015	112347
Rohde & Schwarz	CMW500	Radio Communication Tester	10/18/2013	Annual	10/18/2014	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	4/15/2014	Annual	4/15/2015	102060
Rohde & Schwarz	CMW500	Radio Communication Tester	10/4/2013	Biennial	10/4/2015	103962
Rohde & Schwarz	CMW500	Radio Communication Tester	4/18/2014	Annual	4/18/2015	101699
Rohde & Schwarz	NRV-232	Peak Power Sensor	10/12/2012	Biennial	10/12/2014	836019/013
Rohde & Schwarz	SME06	Signal Generator	10/30/2013	Annual	10/30/2014	832026
Rohde & Schwarz	NRVD	Dual Channel Power Meter	10/12/2012	Biennial	10/12/2014	101695
Rohde & Schwarz	NRVS	Single Channel Power Meter	10/31/2013	Annual	10/31/2014	835360/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/6/2014	Annual	6/6/2015	109892
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/16/2014	Annual	4/16/2015	B010177

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMG850M	 <b>PCTEST</b> INDEPENDENT LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 65 of 71

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/6/2014	Annual	5/6/2015	1070
SPEAG	DAK-3.5	Dielectric Assessment Kit	11/13/2013	Annual	11/13/2014	1091
SPEAG	DAKS-3.5	Portable Dielectric Assessment Kit	8/18/2013	Annual	8/18/2014	1008
SPEAG	DAKS-3.5	Portable Dielectric Assessment Kit	8/18/2013	Annual	8/18/2014	1009
SPEAG	D750V3	750 MHz Dipole	1/20/2014	Annual	1/20/2015	1003
SPEAG	D835V2	835 MHz SAR Dipole	4/7/2014	Annual	4/7/2015	4d119
SPEAG	D1750V2	1750 MHz SAR Dipole	4/10/2014	Annual	4/10/2015	1051
SPEAG	D1900V2	1900 MHz SAR Dipole	4/9/2014	Annual	4/9/2015	5d141
SPEAG	D2450V2	2450 MHz SAR Dipole	1/21/2014	Annual	1/21/2015	797
SPEAG	D5GHZV2	5 GHz SAR Dipole	1/27/2014	Annual	1/27/2015	1057
SPEAG	D750V3	750 MHz Dipole	2/27/2014	Annual	2/27/2015	1046
SPEAG	D1900V2	1900 MHz SAR Dipole	2/27/2014	Annual	2/27/2015	5d148
SPEAG	D2450V2	2450 MHz SAR Dipole	8/23/2013	Annual	8/23/2014	719
SPEAG	D5GHZV2	5 GHz SAR Dipole	9/23/2013	Annual	9/23/2014	1007
SPEAG	ES3DV3	SAR Probe	3/19/2014	Annual	3/19/2015	3209
SPEAG	ES3DV3	SAR Probe	4/17/2014	Annual	4/17/2015	3319
SPEAG	ES3DV3	SAR Probe	4/11/2014	Annual	4/11/2015	3213
SPEAG	ES3DV3	SAR Probe	11/25/2013	Annual	11/25/2014	3332
SPEAG	EX3DV4	SAR Probe	10/23/2013	Annual	10/23/2014	3914
SPEAG	ES3DV3	SAR Probe	9/23/2013	Annual	9/23/2014	3288
SPEAG	EX3DV4	SAR Probe	12/18/2013	Annual	12/18/2014	3920
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2014	Annual	4/11/2015	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/18/2013	Annual	11/18/2014	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2013	Annual	9/17/2014	1323
SPEAG	DAE5	Dasy Data Acquisition Electronics	12/12/2013	Annual	12/12/2014	649
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264165
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264162
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.



FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 66 of 71

# 15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> 1gm	c <sub>i</sub> 10 gms	1gm u <sub>i</sub> (± %)	10gms u <sub>i</sub> (± %)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
<b>Test Sample Related</b>									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
<b>Phantom &amp; Tissue Parameters</b>									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
<b>Combined Standard Uncertainty (k=1)</b>	RSS						12.1	11.7	299
<b>Expanded Uncertainty</b> (95% CONFIDENCE LEVEL)	k=2						24.2	23.5	



The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMG850M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1407111375.A3L	Test Dates: 06/09/14 - 07/24/14	DUT Type: Portable Handset		Page 67 of 71

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h= c x f/e	i= c x g/e	k	
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> 1gm	c <sub>i</sub> 10 gms	1gm u <sub>i</sub> (± %)	10gms u <sub>i</sub> (± %)	v <sub>i</sub>	
<b>Measurement System</b>										
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞	
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞	
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞	
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞	
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞	
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞	
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞	
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞	
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞	
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞	
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞	
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞	
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞	
<b>Test Sample Related</b>										
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287	
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞	
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞	
<b>Phantom &amp; Tissue Parameters</b>										
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞	
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞	
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6	
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞	
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6	
<b>Combined Standard Uncertainty (k=1)</b>							RSS	12.4	12.0	299
<b>Expanded Uncertainty</b> (95% CONFIDENCE LEVEL)							k=2	24.7	24.0	

The above measurement uncertainties are according to IEEE Std. 1528-2003



FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 68 of 71

## 16 CONCLUSION

### 16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 69 of 71

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> OY1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset	Page 70 of 71	

- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG850M	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	<b>SAR EVALUATION REPORT</b>		<b>Reviewed by:</b> Quality Manager
<b>Document S/N:</b> 0Y1407111375.A3L	<b>Test Dates:</b> 06/09/14 - 07/24/14	<b>DUT Type:</b> Portable Handset		Page 71 of 71

## APPENDIX A: SAR TEST DATA

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.935 \text{ S/m}$ ;  $\epsilon_r = 42.616$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-23-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3319; ConvF(6.27, 6.27, 6.27); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Left Head, Cheek, Mid.ch**


**Area Scan (8x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.30 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.389 W/kg

**SAR(1 g) = 0.290 W/kg**



0 dB = 0.320 W/kg = -4.95 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 0.935 \text{ S/m}$ ;  $\epsilon_r = 42.616$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-23-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3319; ConvF(6.27, 6.27, 6.27); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Left Head, Cheek, Mid.ch**


**Area Scan (8x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.19 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.340 W/kg

**SAR(1 g) = 0.256 W/kg**



0 dB = 0.284 W/kg = -5.47 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, AWS UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.381 \text{ S/m}$ ;  $\epsilon_r = 41.439$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-14-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3213; ConvF(5.18, 5.18, 5.18); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: AWS UMTS, Right Head, Cheek, Mid.ch**


**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.53 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.475 W/kg

**SAR(1 g) = 0.293 W/kg**



0 dB = 0.350 W/kg = -4.56 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.374 \text{ S/m}$ ;  $\epsilon_r = 39.175$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-23-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(5.06, 5.06, 5.06); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.38 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.616 W/kg

**SAR(1 g) = 0.529 W/kg**



0 dB = 0.560 W/kg = -2.52 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.374 \text{ S/m}$ ;  $\epsilon_r = 39.175$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-23-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(5.06, 5.06, 5.06); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Left Head, Cheek, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.38 V/m; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 0.982 W/kg

**SAR(1 g) = 0.437 W/kg**



0 dB = 0.513 W/kg = -2.90 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE Band 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used:

$f = 710 \text{ MHz}$ ;  $\sigma = 0.886 \text{ S/m}$ ;  $\epsilon_r = 41.923$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-22-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3209; ConvF(6.43, 6.43, 6.43); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 17, Left Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.57 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.127 W/kg

**SAR(1 g) = 0.102 W/kg**



0 dB = 0.111 W/kg = -9.55 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 0.935 \text{ S/m}$ ;  $\epsilon_r = 42.617$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-23-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3319; ConvF(6.27, 6.27, 6.27); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell), Left Head, Cheek, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.75 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.336 W/kg

**SAR(1 g) = 0.252 W/kg**



0 dB = 0.278 W/kg = -5.56 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE RF; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
Medium: 1750 Head Medium parameters used (interpolated):  
 $f = 1732.5 \text{ MHz}$ ;  $\sigma = 1.381 \text{ S/m}$ ;  $\epsilon_r = 41.438$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section

Test Date: 07-14-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3213; ConvF(5.18, 5.18, 5.18); Calibrated: 4/11/2014;  
Sensor-Surface: 3mm (Mechanical Surface Detection)  
Electronics: DAE4 Sn1364; Calibrated: 3/17/2014  
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Right Head, Cheek, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.98 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.519 W/kg

**SAR(1 g) = 0.319 W/kg**



0 dB = 0.383 W/kg = -4.17 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.395 \text{ S/m}$ ;  $\epsilon_r = 39.086$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-23-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(5.06, 5.06, 5.06); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Right Head, Cheek, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.13 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.684 W/kg

**SAR(1 g) = 0.380 W/kg**



0 dB = 0.483 W/kg = -3.16 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0707-1**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$ ;  $\sigma = 1.783 \text{ S/m}$ ;  $\epsilon_r = 39.109$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-09-2014; Ambient Temp: 23.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3209; ConvF(4.54, 4.54, 4.54); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b - Antenna 1, Right Head, Cheek, Ch 11, 1 Mbps**


**Area Scan (10x15x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (8x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.224 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.244 W/kg

**SAR(1 g) = 0.101 W/kg**



0 dB = 0.144 W/kg = -8.42 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-1**

Communication System: UID 0, IEEE 802.11n; Frequency: 5765 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5765 \text{ MHz}$ ;  $\sigma = 5.264 \text{ S/m}$ ;  $\epsilon_r = 35.839$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-09-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11n - MIMO, 5.8 GHz, Right Head, Tilt, Ch 153, 13 Mbps**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.637 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.985 W/kg

**SAR(1 g) = 0.198 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-1**

Communication System: UID 0, IEEE 802.11n; Frequency: 5560 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5560 \text{ MHz}$ ;  $\sigma = 5.031 \text{ S/m}$ ;  $\epsilon_r = 36.097$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-09-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.37, 4.37, 4.37); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11n - MIMO, 5.5 GHz, Left Head, Cheek, Ch 112, 13 Mbps**


**Area Scan (13x22x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.039 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.765 W/kg

**SAR(1 g) = 0.154 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.011 \text{ S/m}$ ;  $\epsilon_r = 54.434$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 850, Body SAR, Back side, Mid.ch**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.44 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.645 W/kg

**SAR(1 g) = 0.452 W/kg**



0 dB = 0.519 W/kg = -2.85 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.076

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.011 \text{ S/m}$ ;  $\epsilon_r = 54.434$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 850, Body SAR, Back side, Mid.ch, 4 Tx Slots**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.27 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.689 W/kg

**SAR(1 g) = 0.478 W/kg**



0 dB = 0.548 W/kg = -2.61 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.011 \text{ S/m}$ ;  $\epsilon_r = 54.434$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Back side, Mid.ch**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.11 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.595 W/kg

**SAR(1 g) = 0.418 W/kg**



0 dB = 0.480 W/kg = -3.19 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$ ;  $\sigma = 1.011 \text{ S/m}$ ;  $\epsilon_r = 54.434$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 850, Body SAR, Front side, Mid.ch**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.48 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.624 W/kg

**SAR(1 g) = 0.438 W/kg**



0 dB = 0.506 W/kg = -2.96 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, AWS UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$ ;  $\sigma = 1.52 \text{ S/m}$ ;  $\epsilon_r = 52.559$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.89, 4.89, 4.89); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: AWS UMTS, Body SAR, Back side, Mid.ch**


**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.15 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.14 W/kg

**SAR(1 g) = 0.687 W/kg**



0 dB = 0.844 W/kg = -0.74 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, AWS UMTS; Frequency: 1752.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1752.5$  MHz;  $\sigma = 1.542$  S/m;  $\epsilon_r = 52.486$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.89, 4.89, 4.89); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: AWS UMTS, Body SAR, Bottom Edge, High.ch**


**Area Scan (9x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.27 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.58 W/kg

**SAR(1 g) = 0.940 W/kg**



0 dB = 1.14 W/kg = 0.57 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880$  MHz;  $\sigma = 1.484$  S/m;  $\epsilon_r = 51.316$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: GSM 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.56 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.607 W/kg

**SAR(1 g) = 0.378 W/kg**



0 dB = 0.439 W/kg = -3.58 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, GSM1900 GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.484 \text{ S/m}$ ;  $\epsilon_r = 51.316$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 3 Tx Slots**


**Area Scan (9x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.73 V/m; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.646 W/kg**



0 dB = 0.786 W/kg = -1.05 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.484 \text{ S/m}$ ;  $\epsilon_r = 51.316$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Back side, Mid.ch**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.19 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.742 W/kg

**SAR(1 g) = 0.460 W/kg**



0 dB = 0.531 W/kg = -2.75 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$ ;  $\sigma = 1.484 \text{ S/m}$ ;  $\epsilon_r = 51.316$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: UMTS 1900, Body SAR, Bottom Edge, Mid.ch**


**Area Scan (9x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.64 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.716 W/kg**



0 dB = 0.878 W/kg = -0.57 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE BAND 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used:

$f = 710 \text{ MHz}$ ;  $\sigma = 0.965 \text{ S/m}$ ;  $\epsilon_r = 56.51$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2014; Ambient Temp: 24.2°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3288; ConvF(6.25, 6.25, 6.25); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 17, Body SAR, Back side, Mid.ch,  
10 Mhz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.02 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.299 W/kg

**SAR(1 g) = 0.176 W/kg**



0 dB = 0.212 W/kg = -6.74 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE BAND 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used:

$f = 710 \text{ MHz}$ ;  $\sigma = 0.965 \text{ S/m}$ ;  $\epsilon_r = 56.51$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2014; Ambient Temp: 24.2°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3288; ConvF(6.25, 6.25, 6.25); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 17, Body SAR, Front side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.86 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.395 W/kg

**SAR(1 g) = 0.210 W/kg**



0 dB = 0.264 W/kg = -5.78 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-1**

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$ ;  $\sigma = 1.011 \text{ S/m}$ ;  $\epsilon_r = 54.435$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,  
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.82 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.511 W/kg

**SAR(1 g) = 0.359 W/kg**



0 dB = 0.411 W/kg = -3.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, LTE RF; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.52$  S/m;  $\epsilon_r = 52.559$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.89, 4.89, 4.89); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.40 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.978 W/kg

**SAR(1 g) = 0.592 W/kg**



0 dB = 0.727 W/kg = -1.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, LTE RF; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$  MHz;  $\sigma = 1.52$  S/m;  $\epsilon_r = 52.559$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.89, 4.89, 4.89); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (11x7x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.42 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.42 W/kg

**SAR(1 g) = 0.878 W/kg**



0 dB = 1.07 W/kg = 0.29 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.507 \text{ S/m}$ ;  $\epsilon_r = 51.253$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.41 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.800 W/kg

**SAR(1 g) = 0.498 W/kg**



0 dB = 0.579 W/kg = -2.37 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 1107-2**

Communication System: UID 0, LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.507 \text{ S/m}$ ;  $\epsilon_r = 51.253$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, High.ch,  
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


**Area Scan (11x9x1):** Measurement grid: dx=5mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.43 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 1.04 W/kg

**SAR(1 g) = 0.629 W/kg**



0 dB = 0.751 W/kg = -1.24 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-1**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$ ;  $\sigma = 1.996 \text{ S/m}$ ;  $\epsilon_r = 51.528$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space; 1.0 cm

Test Date: 06-12-2014; Ambient Temp: 23.1°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b - Antenna 1, Body SAR, Ch 11, 1 Mbps, Back Side**


**Area Scan (9x16x1):** Measurement grid: dx=12mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.507 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.210 W/kg

**SAR(1 g) = 0.102 W/kg**



0 dB = 0.133 W/kg = -8.76 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-1**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$ ;  $\sigma = 1.996 \text{ S/m}$ ;  $\epsilon_r = 51.528$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2014; Ambient Temp: 23.1°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11b - Antenna 1, Body SAR, Ch 11, 1 Mbps, Top Edge**


**Area Scan (10x9x1):** Measurement grid: dx=5mm, dy=12mm

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.377 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.242 W/kg

**SAR(1 g) = 0.122 W/kg**



0 dB = 0.157 W/kg = -8.04 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-2**

Communication System: UID 0, IEEE 802.11ac 5.0-5.8 GHz Band; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5775 \text{ MHz}$ ;  $\sigma = 6.173 \text{ S/m}$ ;  $\epsilon_r = 46.731$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3920; ConvF(4, 4, 4); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11ac - Antenna 1, 5.8 GHz,  
Body SAR, Ch 155, 29.3 Mbps, Back Side**


**Area Scan (12x18x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 1.986 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.104 W/kg

**SAR(1 g) = 0.024 W/kg**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG850M; Type: Portable Handset; Serial: 0906-2**

Communication System: UID 0, IEEE 802.11n; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5180 \text{ MHz}$ ;  $\sigma = 5.44 \text{ S/m}$ ;  $\epsilon_r = 47.494$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3920; ConvF(4.23, 4.23, 4.23); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

**Mode: IEEE 802.11n - MIMO, 5.2 GHz, Body SAR, Ch 36, 13 Mbps, Back Side**


**Area Scan (12x18x1):** Measurement grid: dx=10mm, dy=10mm

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 2.538 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.230 W/kg

**SAR(1 g) = 0.032 W/kg**



## APPENDIX B: SYSTEM VERIFICATION

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 750 MHz; Type: D750V3; Serial: 1003**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 0.923 \text{ S/m}$ ;  $\epsilon_r = 41.337$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-22-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3209; ConvF(6.43, 6.43, 6.43); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification

**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.891 W/kg**

Deviation(1 g): 6.45%



0 dB = 1.04 W/kg = 0.17 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d119**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 0.934 \text{ S/m}$ ;  $\epsilon_r = 42.634$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-23-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3319; ConvF(6.27, 6.27, 6.27); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 0.931 W/kg**

Deviation(1 g): 0.98%



0 dB = 1.09 W/kg = 0.37 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.399 \text{ S/m}$ ;  $\epsilon_r = 41.356$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3213; ConvF(5.18, 5.18, 5.18); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification

**Area Scan (6x8x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.62 W/kg

**SAR(1 g) = 3.65 W/kg**

Deviation(1 g): 0.83%



0 dB = 4.50 W/kg = 6.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.395 \text{ S/m}$ ;  $\epsilon_r = 39.086$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-23-2014; Ambient Temp: 22.7°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3332; ConvF(5.06, 5.06, 5.06); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.11 W/kg

**SAR(1 g) = 3.93 W/kg**

Deviation(1 g): -2.00%



0 dB = 4.91 W/kg = 6.91 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 1.77 \text{ S/m}$ ;  $\epsilon_r = 39.15$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-09-2014; Ambient Temp: 23.2°C; Tissue Temp: 23.4°C

Probe: ES3DV3 - SN3209; ConvF(4.54, 4.54, 4.54); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 11.0 W/kg

**SAR(1 g) = 5.46 W/kg**

Deviation(1 g): 5.41%



0 dB = 6.99 W/kg = 8.44 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5200 \text{ MHz}$ ;  $\sigma = 4.653 \text{ S/m}$ ;  $\epsilon_r = 36.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3914; ConvF(4.99, 4.99, 4.99); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

## 5200 MHz System Verification

**Area Scan (7x8x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 31.9 W/kg

**SAR(1 g) = 7.75 W/kg**

Deviation(1 g): -0.64%



0 dB = 19.4 W/kg = 12.88 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 4.762 \text{ S/m}$ ;  $\epsilon_r = 36.436$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.82, 4.82, 4.82); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

## 5300 MHz System Verification

**Area Scan (7x8x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.4 W/kg

**SAR(1 g) = 8.25 W/kg**

Deviation(1 g): -0.60%



0 dB = 17.3 W/kg = 12.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 4.971 \text{ S/m}$ ;  $\epsilon_r = 36.16$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.55, 4.55, 4.55); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

## 5500 MHz System Verification

**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.3 W/kg

**SAR(1 g) = 7.82 W/kg**

Deviation(1 g): -7.24%



0 dB = 18.7 W/kg = 12.72 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5600 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 5.077 \text{ S/m}$ ;  $\epsilon_r = 36.017$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.37, 4.37, 4.37); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

## 5600 MHz System Verification

**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 36.9 W/kg

**SAR(1 g) = 8.24 W/kg**

Deviation(1 g): -1.32%



0 dB = 19.8 W/kg = 12.97 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 5.282 \text{ S/m}$ ;  $\epsilon_r = 35.771$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-09-2014; Ambient Temp: 23.1°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7331)

## 5800 MHz System Verification

**Area Scan (7x7x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 37.2 W/kg

**SAR(1 g) = 7.83 W/kg**

Deviation(1 g): -1.26%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 750 MHz; Type: D750V3; Serial: 1046**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 740 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$ ;  $\sigma = 1.005 \text{ S/m}$ ;  $\epsilon_r = 56.163$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-14-2014; Ambient Temp: 24.2°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3288; ConvF(6.25, 6.25, 6.25); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM Sub Dasy B; Type: SAM 5.0; Serial: TP-1626

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 750 MHz System Verification

**Area Scan (7x13x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.30 W/kg

**SAR(1 g) = 0.886 W/kg**

Deviation(1 g): 3.75%



0 dB = 1.02 W/kg = 0.09 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d119**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$ ;  $\sigma = 1.01 \text{ S/m}$ ;  $\epsilon_r = 54.452$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-21-2014; Ambient Temp: 22.6°C; Tissue Temp: 22.9°C

Probe: ES3DV3 - SN3332; ConvF(6.08, 6.08, 6.08); Calibrated: 11/25/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 11/18/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.40 W/kg

**SAR(1 g) = 0.962 W/kg**

Deviation(1 g): 3.00%



0 dB = 1.12 W/kg = 0.49 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1750 MHz; Type: D1750V2; Serial: 1051**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$ ;  $\sigma = 1.539 \text{ S/m}$ ;  $\epsilon_r = 52.495$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2014; Ambient Temp: 23.3°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.89, 4.89, 4.89); Calibrated: 4/11/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 3/17/2014

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 1750 MHz System Verification

**Area Scan (6x8x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.57 W/kg

**SAR(1 g) = 3.67 W/kg**

Deviation(1 g): -1.87%



0 dB = 4.59 W/kg = 6.62 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$ ;  $\sigma = 1.507 \text{ S/m}$ ;  $\epsilon_r = 51.253$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-24-2014; Ambient Temp: 23.5°C; Tissue Temp: 23.2°C

Probe: ES3DV3 - SN3288; ConvF(4.82, 4.82, 4.82); Calibrated: 9/23/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2013

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 1900 MHz System Verification

**Area Scan (5x7x1):** Measurement grid: dx=15mm, dy=15mm


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.22 W/kg

**SAR(1 g) = 4.1 W/kg**

Deviation(1 g): 4.33%



0 dB = 5.11 W/kg = 7.08 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$  MHz;  $\sigma = 1.981$  S/m;  $\epsilon_r = 51.567$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2014; Ambient Temp: 23.1°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3319; ConvF(4.24, 4.24, 4.24); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 11.2 W/kg

**SAR(1 g) = 5.41 W/kg**

Deviation(1 g): 4.64%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5200 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5200 \text{ MHz}$ ;  $\sigma = 5.454 \text{ S/m}$ ;  $\epsilon_r = 47.504$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3920; ConvF(4.23, 4.23, 4.23); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 5200 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 28.3 W/kg

**SAR(1 g) = 7.4 W/kg**

Deviation(1 g): 1.93%



0 dB = 18.1 W/kg = 12.58 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5300 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$ ;  $\sigma = 5.592 \text{ S/m}$ ;  $\epsilon_r = 47.351$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.4°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN3920; ConvF(4.11, 4.11, 4.11); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 5300 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.0 W/kg

**SAR(1 g) = 7.53 W/kg**

Deviation(1 g): 0.80%



0 dB = 18.9 W/kg = 12.76 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5500 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$ ;  $\sigma = 5.881 \text{ S/m}$ ;  $\epsilon_r = 47.322$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3920; ConvF(3.8, 3.8, 3.8); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 5500 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 35.7 W/kg

**SAR(1 g) = 7.62 W/kg**

Deviation(1 g): 0.40%



0 dB = 19.5 W/kg = 12.90 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5600 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$ ;  $\sigma = 6.014 \text{ S/m}$ ;  $\epsilon_r = 47.23$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3920; ConvF(3.62, 3.62, 3.62); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 5600 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 36.5 W/kg

**SAR(1 g) = 7.65 W/kg**

Deviation(1 g): -1.03%



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 5800 MHz; Type: D5GHzV2; Serial: 1007**

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$ ;  $\sigma = 6.21 \text{ S/m}$ ;  $\epsilon_r = 46.638$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-16-2014; Ambient Temp: 24.5°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3920; ConvF(4, 4, 4); Calibrated: 12/18/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 12/12/2013

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, Version 4.7 (80); SEMCAD X Version 14.6.10 (7331)

## 5800 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=10mm, dy=10mm


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.8 W/kg

**SAR(1 g) = 6.92 W/kg**

Deviation(1 g): -5.08%



## APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D750V3-1003\_Jan14**

## CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1003**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **January 20, 2014**

CC  
21/14 ✓

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-13 (No. 217-01736)	Apr-14
Type-N mismatch combination	SN: 5047.3 / 06327	04-Apr-13 (No. 217-01739)	Apr-14
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Israe El-Naouq** Laboratory Technician  
Approved by: **Katja Pokovic** Technical Manager

Signature  
*Israe El-Naouq*  
*Katja Pokovic*

Issued: January 21, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

### Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY5	V52.8.7
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	Modular Flat Phantom	
<b>Distance Dipole Center - TSL</b>	15 mm	with Spacer
<b>Zoom Scan Resolution</b>	dx, dy, dz = 5 mm	
<b>Frequency</b>	750 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Head TSL parameters</b>	22.0 °C	41.9	0.89 mho/m
<b>Measured Head TSL parameters</b>	(22.0 $\pm$ 0.2) °C	40.8 $\pm$ 6 %	0.92 mho/m $\pm$ 6 %
<b>Head TSL temperature change during test</b>	< 0.5 °C	----	----

## SAR result with Head TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b>	Condition	
SAR measured	250 mW input power	2.16 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>8.37 W/kg <math>\pm</math> 17.0 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b>	condition	
SAR measured	250 mW input power	1.40 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	<b>5.46 W/kg <math>\pm</math> 16.5 % (k=2)</b>

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Body TSL parameters</b>	22.0 °C	55.5	0.96 mho/m
<b>Measured Body TSL parameters</b>	(22.0 $\pm$ 0.2) °C	54.0 $\pm$ 6 %	0.98 mho/m $\pm$ 6 %
<b>Body TSL temperature change during test</b>	< 0.5 °C	----	----

## SAR result with Body TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b>	Condition	
SAR measured	250 mW input power	2.24 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>8.77 W/kg <math>\pm</math> 17.0 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b>	condition	
SAR measured	250 mW input power	1.47 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	<b>5.78 W/kg <math>\pm</math> 16.5 % (k=2)</b>

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.7 $\Omega$ - 0.2 j $\Omega$
Return Loss	- 27.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.5 $\Omega$ - 2.6 j $\Omega$
Return Loss	- 31.4 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.043 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 21, 2009

# DASY5 Validation Report for Head TSL

Date: 20.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1003**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.92$  S/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.37, 6.37, 6.37); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.711 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.27 W/kg

**SAR(1 g) = 2.16 W/kg; SAR(10 g) = 1.4 W/kg**

Maximum value of SAR (measured) = 2.51 W/kg



0 dB = 2.51 W/kg = 4.00 dBW/kg

# Impedance Measurement Plot for Head TSL

20 Jan 2014 16:36:06

CH1 S11 1 U FS

1: 54.678  $\Omega$  -156.25 m $\angle$  1.3581 nF


750.000 000 MHz

\*  
De1

C $\Delta$

Avg  
16

H1d



CH2 S11 LOG

5 dB/REF -20 dB


1: -26.992 dB

750.000 000 MHz

C $\Delta$

Avg  
16

H1d



## DASY5 Validation Report for Body TSL

Date: 20.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1003**

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.98$  S/m;  $\epsilon_r = 54$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.13, 6.13, 6.13); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.082 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.31 W/kg

**SAR(1 g) = 2.24 W/kg; SAR(10 g) = 1.47 W/kg**

Maximum value of SAR (measured) = 2.58 W/kg



0 dB = 2.58 W/kg = 4.12 dBW/kg

# Impedance Measurement Plot for Body TSL

20 Jan 2014 10:20:18


CH1 S11 1 U FS 1: 49.459  $\Omega$  -2.6367  $\Omega$  80.481 pF 750.000 000 MHz

\*  
De1

CA

Avg  
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -31.359 dB 750.000 000 MHz

CA

Avg  
16

H1d





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D835V2-4d119\_Apr14**

## CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d119**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

*CCV  
4/25/14*

Calibration date: **April 07, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by:	Name <b>Leif Klysner</b>	Function <b>Laboratory Technician</b>	Signature 
Approved by:	<b>Katja Pokovic</b>	<b>Technical Manager</b>	

Issued: April 9, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- d) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.6 $\pm$ 6 %	0.94 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.22 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.53 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.97 W/kg $\pm$ 16.5 % (k=2)

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.6 $\pm$ 6 %	1.02 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.44 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.34 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.59 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.15 W/kg $\pm$ 16.5 % (k=2)

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.2 $\Omega$ - 1.6 j $\Omega$
Return Loss	- 34.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.3 $\Omega$ - 4.5 j $\Omega$
Return Loss	- 24.4 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.386 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	June 29, 2010

## DASY5 Validation Report for Head TSL

Date: 07.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.94$  S/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.289 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.59 W/kg


**SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.53 W/kg**

Maximum value of SAR (measured) = 2.80 W/kg



0 dB = 2.80 W/kg = 4.47 dBW/kg

# Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 07.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d119**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 1.02$  S/m;  $\epsilon_r = 53.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.594 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.61 W/kg


**SAR(1 g) = 2.44 W/kg; SAR(10 g) = 1.59 W/kg**

Maximum value of SAR (measured) = 2.85 W/kg



0 dB = 2.85 W/kg = 4.55 dBW/kg

# Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **D1750V2-1051\_Apr14**

## CALIBRATION CERTIFICATE

Object **D1750V2 - SN: 1051**

Calibration procedure(s) **QA CAL-05.v9  
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **April 10, 2014**

✓  
KOK  
5/7/14

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	US37292783	09-Oct-13 (No. 217-01827)	Oct-14
Power sensor HP 8481A	MY41092317	09-Oct-13 (No. 217-01828)	Oct-14
Reference 20 dB Attenuator	SN: 5058 (20k)	03-Apr-14 (No. 217-01918)	Apr-15
Type-N mismatch combination	SN: 5047.2 / 06327	03-Apr-14 (No. 217-01921)	Apr-15
Reference Probe ES3DV3	SN: 3205	30-Dec-13 (No. ES3-3205_Dec13)	Dec-14
DAE4	SN: 601	25-Apr-13 (No. DAE4-601_Apr13)	Apr-14
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-13)	In house check: Oct-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-13)	In house check: Oct-14

Calibrated by: **Israe El-Naouq**      Name: **Israe El-Naouq**      Function: **Laboratory Technician**      Signature: *Israe El-Naouq*

Approved by: **Katja Pokovic**      Name: **Katja Pokovic**      Function: **Technical Manager**      Signature: *Katja Pokovic*

Issued: April 10, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.35 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.02 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	36.2 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	4.79 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	19.2 W/kg $\pm$ 16.5 % (k=2)

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.49 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	52.0 $\pm$ 6 %	1.48 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.37 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	37.4 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.04 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.1 W/kg $\pm$ 16.5 % (k=2)

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.7 $\Omega$ + 0.4 j $\Omega$
Return Loss	- 41.5 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.8 $\Omega$ + 0.8 j $\Omega$
Return Loss	- 29.3 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.222 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	February 19, 2010

## DASY5 Validation Report for Head TSL

Date: 10.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1051**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.35$  S/m;  $\epsilon_r = 39.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.23, 5.23, 5.23); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### **Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.631 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 16.2 W/kg

**SAR(1 g) = 9.02 W/kg; SAR(10 g) = 4.79 W/kg**

Maximum value of SAR (measured) = 11.3 W/kg




# Impedance Measurement Plot for Head TSL

10 Apr 2014 12:21:05


CH1 S11 1 U FS 1: 50.727  $\Omega$  0.4238  $\Omega$  38.545  $\mu\text{H}$  1 750.000 000 MHz

\*  
Del  
CA  
Avg  
16  
H1d



CH2 S11 LOG 5 dB/REF -20 dB 1:-41.536 dB 1 750.000 000 MHz

CA  
Avg  
16  
H1d



START 1 550.000 000 MHz

STOP 1 950.000 000 MHz

## DASY5 Validation Report for Body TSL

Date: 10.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1051**

Communication System: UID 0 - CW; Frequency: 1750 MHz

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.48$  S/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.89, 4.89, 4.89); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.321 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 16.1 W/kg

**SAR(1 g) = 9.37 W/kg; SAR(10 g) = 5.04 W/kg**

Maximum value of SAR (measured) = 11.8 W/kg




# Impedance Measurement Plot for Body TSL

10 Apr 2014 12:20:40

[CH1] S11 1 U FS 1: 46.787  $\Omega$  0.8086  $\Omega$  73.538 pF 1 750.000 000 MHz

\*  
De l  
CA



Avg  
16


H1 d

CH2 S11 LOG 5 dB/ REF -20 dB 1: -29.320 dB 1 750.000 000 MHz

CA

Avg  
16

H1 d



START 1 550.000 000 MHz

STOP 1 950.000 000 MHz