



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctest.com



MEASUREMENT REPORT FCC Parts 22, 27, & 27

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea


Date of Testing:
09/08/2017-10/04/2017
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M1709080250-02.A3L

FCC ID:	A3LSMG892U
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Certification
Model: SM-G892U
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): 22, 24, & 27
Test Procedure(s): ANSI/TIA-603-E-2016, KDB 971168 D01 v02r02,
KDB 648474 D03 v01r04, ANSI C63.26-2015
Test Device Serial No.: *identical prototype* [S/N: 20209, 20514, 20084, 20951, 18831]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President




FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 1 of 104	

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	PCS - Base Frequency Blocks	6
3.5	PCS - Mobile Frequency Blocks.....	7
3.6	AWS - Base Frequency Blocks	7
3.7	AWS - Mobile Frequency Blocks	7
3.8	Radiated Measurements	8
4.0	MEASUREMENT UNCERTAINTY	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS	11
7.0	TEST RESULTS	12
7.1	Summary.....	12
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	19
7.4	Band Edge Emissions at Antenna Terminal	52
7.5	Peak-Average Ratio	65
7.6	Radiated Power (ERP/EIRP).....	68
7.7	Radiated Spurious Emissions Measurements.....	73
7.8	Frequency Stability / Temperature Variation	89
8.0	CONCLUSION.....	104

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 2 of 104	



MEASUREMENT REPORT

GSM / GPRS / EDGE / CDMA / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GSM850	22H	824.2 - 848.8	0.852	29.30	1.40	31.45	243KGXW
EDGE850	22H	824.2 - 848.8	0.187	22.73	0.31	24.88	242KG7W
WCDMA850	22H	826.4 - 846.6	0.086	19.34	0.14	21.49	4M16F9W
CDMA850	22H	824.70 - 848.31	0.079	18.95	0.13	21.10	1M28F9W
WCDMA1700	27	1712.4 - 1752.6			0.311	24.93	4M15F9W
GSM1900	24E	1850.2 - 1909.8			0.901	29.55	244KGXW
EDGE1900	24E	1850.2 - 1909.8			0.394	25.96	245KG7W
WCDMA1900	24E	1852.4 - 1907.6			0.241	23.82	4M16F9W
CDMA1900	24E	1851.25 - 1908.75			0.175	22.44	1M28F9W

EUT Overview

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 3 of 104	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.


1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS)."
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 4 of 104	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMG892U**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad (WCP) FCC ID: A3LEPNG930 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 5 of 104	

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 6 of 104	

3.5 PCS - Mobile Frequency Blocks

§24.229



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)


BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

3.6 AWS - Base Frequency Blocks

§27.5(h)



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 4: 2135 – 2140 MHz (D)

BLOCK 2: 2120 – 2130 MHz (B)


BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 6: 2145 – 2155 MHz (F)

3.7 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 7 of 104

3.8 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/ITA-603-D-2010.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 8 of 104	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 9 of 104	

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX3	Licensed Transmitter Cable Set	8/10/2017	Annual	8/10/2018	LTX3
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Emco	6502	Active Loop Antenna (10k - 30 MHz)	8/9/2016	Biennial	8/9/2018	2936
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/23/2016	Biennial	8/23/2018	135427
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM1
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM2
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	CMU200	Base Station Simulator	5/22/2017	Annual	5/22/2018	109892
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/18/2015	Biennial	11/18/2017	91052523RX
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 10 of 104	

6.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 11 of 104	

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMG892U
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / EDGE / CDMA / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	Conducted Band Edge / Spurious Emissions	> 43 + log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	Radiated Spurious Emissions	> 43 + log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 12 of 104	

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 13 of 104	




Plot 7-1. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 14 of 104




Plot 7-3. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 15 of 104



Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)



Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 16 of 104




Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 7-8. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 17 of 104



Plot 7-9. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 18 of 104

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 19 of 104	




Plot 7-10. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-11. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 20 of 104




Plot 7-12. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-13. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 21 of 104




Plot 7-14. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-15. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 22 of 104




Plot 7-16. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-17. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 23 of 104




Plot 7-18. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 24 of 104




Plot 7-20. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-21. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 25 of 104




Plot 7-22. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-23. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 26 of 104




Plot 7-24. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-25. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 27 of 104




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 29 of 104




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 30 of 104




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 31 of 104




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 32 of 104




Plot 7-36. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 33 of 104




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 34 of 104




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 35 of 104




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 36 of 104




Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-45. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 37 of 104




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 38 of 104




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 39 of 104




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 40 of 104




Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 41 of 104




Plot 7-54. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-55. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 42 of 104




Plot 7-56. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-57. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 43 of 104




Plot 7-58. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1413)




Plot 7-59. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 44 of 104




Plot 7-60. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1413)




Plot 7-61. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 45 of 104




Plot 7-62. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)




Plot 7-63. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 46 of 104




Plot 7-64. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-65. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 47 of 104




Plot 7-66. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-67. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 48 of 104




Plot 7-68. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-69. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)


FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 49 of 104




Plot 7-70. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-71. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 50 of 104



Plot 7-72. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 51 of 104

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup


Test Notes

Per 22.917(b), 24.238(b), 27.53(h)(3) and RSS-132(5.5), RSS-133(6.5), RSS-139(6.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 52 of 104




Plot 7-73. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 7-74. Band Edge Plot (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 53 of 104




Plot 7-75. Band Edge Plot (PCS GSM Mode – Ch. 512)




Plot 7-76. 4MHz Span Plot (PCS GSM Mode – Ch. 512)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 54 of 104




Plot 7-77. Band Edge Plot (PCS GSM Mode – Ch. 810)



Plot 7-78. 4MHz Span Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSMG892U	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 55 of 104




Plot 7-81. Band Edge Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-82. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 57 of 104




Plot 7-83. Band Edge Plot (PCS CDMA Mode – Ch. 25)




Plot 7-84. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 58 of 104




Plot 7-85. Band Edge Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-86. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 59 of 104



Plot 7-87. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-88. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 60 of 104



Plot 7-89. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-90. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 61 of 104



Plot 7-93. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-94. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 63 of 104



Plot 7-95. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-96. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 64 of 104

7.5 Peak-Average Ratio

§24.232(d) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 65 of 104	




Plot 7-97. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 7-98. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 66 of 104



Plot 7-99. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-100. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 67 of 104

7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) 27.50(d.4) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 68 of 104	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 69 of 104	

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GSM850	H	150	358	29.58	1.50	28.92	0.780	38.45	-9.53	31.07	1.280	40.61	-9.54
836.60	GSM850	H	150	360	29.42	1.50	28.77	0.753	38.45	-9.68	30.92	1.236	40.61	-9.69
848.80	GSM850	H	150	358	29.95	1.50	29.30	0.852	38.45	-9.15	31.45	1.397	40.61	-9.15
848.80	GSM850	V	150	321	29.39	1.50	28.74	0.748	38.45	-9.71	30.89	1.227	40.61	-9.72
848.80	EDGE850	H	150	358	23.38	1.50	22.73	0.187	38.45	-15.72	24.88	0.308	40.61	-15.73
848.80	GSM850 (WCP)	H	150	359	29.19	1.50	28.53	0.713	38.45	-9.92	30.68	1.171	40.61	-9.92

Table 7-2. ERP/EIRP (Cellular GSM)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 70 of 104	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.70	CDMA850	V	150	231	19.60	1.50	18.95	0.079	38.45	-19.50	21.10	0.129	40.61	-19.51
836.52	CDMA850	V	150	238	19.57	1.50	18.92	0.078	38.45	-19.53	21.07	0.128	40.61	-19.54
848.31	CDMA850	V	150	344	17.81	1.50	17.16	0.052	38.45	-21.29	19.31	0.085	40.61	-21.30
824.70	CDMA850	H	150	67	19.38	1.50	18.73	0.075	38.45	-19.72	20.88	0.122	40.61	-19.73
824.70	CDMA850 (WCP)	V	150	216	19.05	1.50	18.40	0.069	38.45	-20.05	20.55	0.114	40.61	-20.06

Table 7-3. ERP/EIRP (Cellular CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	150	335	19.99	1.50	19.34	0.086	38.45	-19.11	21.49	0.141	40.61	-19.12
836.60	WCDMA850	H	150	338	19.00	1.50	18.35	0.068	38.45	-20.10	20.50	0.112	40.61	-20.11
846.60	WCDMA850	H	150	330	19.06	1.50	18.41	0.069	38.45	-20.04	20.56	0.114	40.61	-20.05
826.40	WCDMA850	V	150	2	18.87	1.50	18.22	0.066	38.45	-20.23	20.37	0.109	40.61	-20.24
826.40	WCDMA850 (WCP)	H	150	260	19.77	1.50	19.12	0.082	38.45	-19.33	21.27	0.134	40.61	-19.34



Table 7-4. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	H	150	340	18.85	5.63	24.48	0.280	30.00	-5.52
1732.60	WCDMA1700	H	150	336	19.52	5.41	24.93	0.311	30.00	-5.07
1752.60	WCDMA1700	H	150	355	19.09	5.19	24.28	0.268	30.00	-5.72
1732.60	WCDMA1700	V	150	284	18.90	5.41	24.31	0.269	30.00	-5.69
1732.60	WCDMA1700 (WCP)	H	150	248	17.43	5.41	22.84	0.192	30.00	-7.16

Table 7-5. EIRP (AWS WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	H	150	282	24.73	4.82	29.55	0.901	33.01	-3.47
1880.00	GSM1900	H	150	278	24.45	4.74	29.19	0.829	33.01	-3.83
1909.80	GSM1900	H	150	289	24.76	4.68	29.44	0.879	33.01	-3.57
1850.20	GSM1900	V	150	110	23.61	4.79	28.40	0.692	33.01	-4.61
1850.20	EDGE1900	H	150	282	21.14	4.82	25.96	0.394	33.01	-7.05
1850.20	GSM1900 (WCP)	H	150	275	23.81	4.82	28.63	0.729	33.01	-4.38

Table 7-6. EIRP (PCS GSM)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 71 of 104	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	H	139	196	13.32	9.12	22.44	0.175	33.01	-10.57
1880.00	CDMA1900	H	136	199	13.14	9.10	22.24	0.168	33.01	-10.77
1908.75	CDMA1900	H	134	211	12.11	9.16	21.27	0.134	33.01	-11.74
1851.25	CDMA1900	V	111	201	13.40	8.97	22.37	0.173	33.01	-10.64
1851.25	CDMA1900 (WCP)	H	135	195	13.09	9.10	22.19	0.166	33.01	-10.82

Table 7-7. EIRP (PCS CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	150	209	18.90	4.81	23.71	0.235	33.01	-9.30
1880.00	WCDMA1900	H	150	207	19.08	4.74	23.82	0.241	33.01	-9.19
1907.60	WCDMA1900	H	150	217	19.01	4.68	23.69	0.234	33.01	-9.32
1880.00	WCDMA1900	V	150	309	13.54	4.84	18.38	0.069	33.01	-14.63
1880.00	WCDMA1900 (WCP)	H	150	353	17.81	4.74	22.55	0.180	33.01	-10.46

Table 7-8. EIRP (PCS WCDMA)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 72 of 104	

7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a) 27.53(h) RSS-132(5.5) RSS-133(5.5) RSS-139(6.6)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 73 of 104	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This device employs CDMA technology with EvDO capabilities. This EUT was teste under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 74 of 104	

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	164	177	-70.50	8.84	-61.66	-48.7
2472.60	H	164	183	-68.91	9.66	-59.25	-46.2
3296.80	H	-	-	-65.47	9.51	-55.96	-43.0

Table 7-9. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	157	173	-71.73	8.85	-62.89	-49.9
2509.80	H	203	360	-69.54	9.78	-59.77	-46.8
3346.40	H	-	-	-65.67	9.67	-56.00	-43.0

Table 7-10. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 75 of 104

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	168	205	-69.70	8.85	-60.85	-47.9
2546.40	H	133	0	-66.60	9.75	-56.86	-43.9
3395.20	H	-	-	-64.74	9.83	-54.91	-41.9

Table 7-11. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	110	1	-64.76	8.85	-55.91	-42.9
2546.40	H	150	249	-67.88	9.75	-58.14	-45.1
3395.20	H	-	-	-65.36	9.83	-55.53	-42.5

Table 7-12. Radiated Spurious Data with WCP (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 76 of 104	

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1649.40	H	-	-	-77.32	8.85	-68.47	-55.5
2474.10	H	-	-	-74.76	9.67	-65.09	-52.1

Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.04	H	-	-	-77.55	8.85	-68.71	-55.7
2509.56	H	-	-	-74.68	9.78	-64.91	-51.9

Table 7-14. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 77 of 104	

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1696.62	H	-	-	-77.16	8.85	-68.31	-55.3
2544.93	H	-	-	-74.65	9.75	-64.91	-51.9

Table 7-15. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1649.40	H	-	-	-77.37	8.85	-68.52	-55.5
2474.10	H	-	-	-74.87	9.67	-65.20	-52.2

Table 7-16. Radiated Spurious Data with WCP (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 78 of 104	

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	-	-	-77.27	8.85	-68.43	-55.4
2479.20	H	-	-	-73.76	9.69	-64.07	-51.1

Table 7-17. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	-	-	-85.20	8.85	-76.35	-63.3
2509.80	H	-	-	-74.42	9.78	-64.64	-51.6

Table 7-18. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 79 of 104	

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	-	-	-77.50	8.85	-68.65	-55.7
2539.80	H	-	-	-74.87	9.75	-65.12	-52.1

Table 7-19. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	-	-	-77.32	8.85	-68.48	-55.5
2479.20	H	-	-	-74.63	9.69	-64.94	-51.9

Table 7-20. Radiated Spurious Data with WCP (Cellular WCDMA Mode – Ch. 4132)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 80 of 104	

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3424.80	H	112	155	-68.08	9.87	-58.21	-45.2
5137.20	H	-	-	-67.42	10.76	-56.66	-43.7
6849.60	H	-	-	-62.00	11.67	-50.33	-37.3

Table 7-21. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	127	184	-68.35	9.91	-58.43	-45.4
5197.80	H	-	-	-66.95	10.75	-56.20	-43.2
6930.40	H	-	-	-62.43	11.76	-50.67	-37.7

Table 7-22. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 81 of 104	

OPERATING FREQUENCY: 1752.60 MHz
 CHANNEL: 1513
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3505.20	H	202	226	-68.64	9.95	-58.68	-45.7
5257.80	H	-	-	-67.20	10.71	-56.49	-43.5
7010.40	H	-	-	-61.74	11.83	-49.91	-36.9

Table 7-23. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	147	137	-68.52	9.91	-58.60	-45.6
5197.80	H	-	-	-66.96	10.75	-56.21	-43.2
6930.40	H	-	-	-62.38	11.76	-50.62	-37.6

Table 7-24. Radiated Spurious Data with WCP (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 82 of 104	

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	205	33	-57.08	9.53	-47.55	-34.5
5550.60	H	-	-	-65.37	11.01	-54.36	-41.4
7400.80	H	-	-	-58.33	10.94	-47.39	-34.4

Table 7-25. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	167	47	-56.22	9.39	-46.84	-33.8
5640.00	H	-	-	-65.54	11.22	-54.32	-41.3
7520.00	H	-	-	-58.14	11.10	-47.04	-34.0

Table 7-26. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 83 of 104	

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	H	187	41	-55.85	9.32	-46.53	-33.5
5729.40	H	-	-	-65.52	11.37	-54.15	-41.2
7639.20	H	-	-	-58.03	11.33	-46.70	-33.7

Table 7-27. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	164	59	-57.32	9.53	-47.79	-34.8
5550.60	H	-	-	-65.77	11.01	-54.76	-41.8
7400.80	H	-	-	-58.24	10.94	-47.30	-34.3

Table 7-28. Radiated Spurious Data with WCP (PCS GSM Mode – Ch. 512)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 84 of 104	

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3702.50	V	-	-	-68.55	9.53	-59.02	-46.0
5553.75	V	-	-	-67.10	10.94	-56.15	-43.2

Table 7-29. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	V	-	-	-67.55	9.38	-58.17	-45.2
5640.00	V	-	-	-66.95	11.15	-55.80	-42.8

Table 7-30. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 85 of 104	

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3817.50	V	-	-	-67.80	9.29	-58.51	-45.5
5726.25	V	-	-	-67.14	11.36	-55.77	-42.8

Table 7-31. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3702.50	V	110	360	-67.29	9.53	-57.76	-44.8
5553.75	V	-	-	-67.12	10.94	-56.17	-43.2
7405.00	V	-	-	-59.77	10.93	-48.84	-35.8

Table 7-32. Radiated Spurious Data with WCP (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 86 of 104	

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	-	-	-69.98	9.52	-60.46	-47.5
5557.20	H	-	-	-68.20	11.03	-57.17	-44.2
7409.60	H	-	-	-61.03	10.95	-50.07	-37.1

Table 7-33. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	-	-	-68.25	9.39	-58.87	-45.9
5640.00	H	-	-	-68.28	11.22	-57.06	-44.1
7520.00	H	-	-	-61.21	11.10	-50.11	-37.1

Table 7-34. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 87 of 104	

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	-	-	-69.01	9.32	-59.69	-46.7
5722.80	H	-	-	-68.22	11.35	-56.87	-43.9
7630.40	H	-	-	-60.85	11.32	-49.52	-36.5

Table 7-35. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	-	-	-67.59	9.39	-58.21	-45.2
5640.00	H	-	-	-68.32	11.22	-57.10	-44.1
7520.00	H	-	-	-60.90	11.10	-49.80	-36.8

Table 7-36. Radiated Spurious Data with WCP (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 88 of 104	

7.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 §27.54 RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, RSS-132 and RSS-133, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency. For Part 24 Part 27 and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 89 of 104	

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,139	139	0.0000166
100 %		- 30	836,599,949	-51	-0.0000061
100 %		- 20	836,599,890	-110	-0.0000131
100 %		- 10	836,600,110	110	0.0000131
100 %		0	836,600,003	3	0.0000004
100 %		+ 10	836,599,876	-124	-0.0000148
100 %		+ 20	836,600,307	307	0.0000367
100 %		+ 30	836,599,966	-34	-0.0000041
100 %		+ 40	836,600,328	328	0.0000392
100 %		+ 50	836,599,675	-325	-0.0000388
BATT. ENDPOINT	3.45	+ 20	836,599,969	-31	-0.0000037

Table 7-37. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 90 of 104	

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-8. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 91 of 104	

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,519,924	-76	-0.0000091
100 %		- 30	836,519,801	-199	-0.0000238
100 %		- 20	836,520,274	274	0.0000328
100 %		- 10	836,519,974	-26	-0.0000031
100 %		0	836,520,107	107	0.0000128
100 %		+ 10	836,519,992	-8	-0.0000010
100 %		+ 20	836,520,052	52	0.0000062
100 %		+ 30	836,519,937	-63	-0.0000075
100 %		+ 40	836,520,057	57	0.0000068
100 %		+ 50	836,519,898	-102	-0.0000122
BATT. ENDPOINT	3.45	+ 20	836,519,937	-63	-0.0000075

Table 7-38. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 92 of 104	

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-9. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset		Page 93 of 104

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 4183
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,600,142	142	0.0000170
100 %		- 30	836,600,097	97	0.0000116
100 %		- 20	836,599,833	-167	-0.0000200
100 %		- 10	836,600,195	195	0.0000233
100 %		0	836,599,859	-141	-0.0000169
100 %		+ 10	836,600,238	238	0.0000284
100 %		+ 20	836,599,854	-146	-0.0000175
100 %		+ 30	836,599,932	-68	-0.0000081
100 %		+ 40	836,600,087	87	0.0000104
100 %		+ 50	836,599,913	-87	-0.0000104
BATT. ENDPOINT	3.45	+ 20	836,600,388	388	0.0000464

Table 7-39. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 94 of 104	

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-10. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 95 of 104	

Frequency Stability / Temperature Variation
§2.1055 §27.54 RSS-139(6.4)

OPERATING FREQUENCY: 1,732,600,000 Hz
 CHANNEL: 1413
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,732,600,066	66	0.0000038
100 %		- 30	1,732,599,756	-244	-0.0000141
100 %		- 20	1,732,600,057	57	0.0000033
100 %		- 10	1,732,599,991	-9	-0.0000005
100 %		0	1,732,600,070	70	0.0000040
100 %		+ 10	1,732,599,975	-25	-0.0000014
100 %		+ 20	1,732,600,083	83	0.0000048
100 %		+ 30	1,732,599,844	-156	-0.0000090
100 %		+ 40	1,732,599,951	-49	-0.0000028
100 %		+ 50	1,732,599,968	-32	-0.0000018
BATT. ENDPOINT	3.45	+ 20	1,732,600,214	214	0.0000124

Table 7-40. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 96 of 104	

Frequency Stability / Temperature Variation
§2.1055 §27.54 RSS-139(6.4)




Figure 7-11. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 97 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,300	300	0.0000160
100 %		- 30	1,880,000,199	199	0.0000106
100 %		- 20	1,879,999,954	-46	-0.0000024
100 %		- 10	1,879,999,944	-56	-0.0000030
100 %		0	1,879,999,839	-161	-0.0000086
100 %		+ 10	1,880,000,050	50	0.0000027
100 %		+ 20	1,879,999,946	-54	-0.0000029
100 %		+ 30	1,879,999,992	-8	-0.0000004
100 %		+ 40	1,879,999,844	-156	-0.0000083
100 %		+ 50	1,880,000,003	3	0.0000002
BATT. ENDPOINT	3.45	+ 20	1,880,000,320	320	0.0000170

Table 7-41. Frequency Stability Data (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 98 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-12. Frequency Stability Graph (PCS GSM Mode – Ch. 661)


FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 99 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,388	388	0.0000206
100 %		- 30	1,880,000,165	165	0.0000088
100 %		- 20	1,880,000,220	220	0.0000117
100 %		- 10	1,879,999,976	-24	-0.0000013
100 %		0	1,879,999,685	-315	-0.0000168
100 %		+ 10	1,880,000,323	323	0.0000172
100 %		+ 20	1,880,000,014	14	0.0000007
100 %		+ 30	1,879,999,821	-179	-0.0000095
100 %		+ 40	1,879,999,857	-143	-0.0000076
100 %		+ 50	1,879,999,956	-44	-0.0000023
BATT. ENDPOINT	3.45	+ 20	1,879,999,944	-56	-0.0000030

Table 7-42. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 100 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-13. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 101 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 9400
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,016	16	0.0000009
100 %		- 30	1,879,999,923	-77	-0.0000041
100 %		- 20	1,879,999,768	-232	-0.0000123
100 %		- 10	1,879,999,709	-291	-0.0000155
100 %		0	1,879,999,947	-53	-0.0000028
100 %		+ 10	1,880,000,373	373	0.0000198
100 %		+ 20	1,880,000,031	31	0.0000016
100 %		+ 30	1,879,999,962	-38	-0.0000020
100 %		+ 40	1,880,000,325	325	0.0000173
100 %		+ 50	1,880,000,024	24	0.0000013
BATT. ENDPOINT	3.45	+ 20	1,879,999,761	-239	-0.0000127

Table 7-43. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 102 of 104	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-14. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 103 of 104	

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG892U** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules.

FCC ID: A3LSMG892U		FCC Pt. 22, 24, & 27 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709080250-02.A3L	Test Dates: 09/08/2017-10/04/2017	EUT Type: Portable Handset	Page 104 of 104	