




Antenna-2 Power Spectral Density Measurements


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	a	6	0.32	11.0	-10.68	Pass
	5200	40	a	6	0.48	11.0	-10.52	Pass
	5240	48	a	6	0.53	11.0	-10.47	Pass
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	-1.33	11.0	-12.33	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-0.84	11.0	-11.84	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	-0.87	11.0	-11.87	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	-4.15	11.0	-15.15	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	-3.82	11.0	-14.82	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-5.92	11.0	-16.92	Pass
Band 2A	5260	52	a	6	0.82	11.0	-10.18	Pass
	5280	56	a	6	0.85	11.0	-10.15	Pass
	5320	64	a	6	1.29	11.0	-9.71	Pass
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	-0.57	11.0	-11.57	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	-0.45	11.0	-11.45	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	-0.31	11.0	-11.31	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	-3.56	11.0	-14.56	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	-3.61	11.0	-14.61	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-5.43	11.0	-16.43	Pass
Band 2C	5500	100	a	6	1.49	11.0	-9.51	Pass
	5580	116	a	6	1.22	11.0	-9.79	Pass
	5720	144	a	6	1.21	11.0	-9.79	Pass
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	0.58	11.0	-10.42	Pass
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	0.10	11.0	-10.90	Pass
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	0.96	11.0	-10.04	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	-2.84	11.0	-13.84	Pass
	5550	110	n (40MHz)	13.5/15 (MCS0)	-3.05	11.0	-14.05	Pass
	5710	142	n (40MHz)	13.5/15 (MCS0)	-1.30	11.0	-12.30	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-4.99	11.0	-15.99	Pass
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-5.61	11.0	-16.61	Pass

Table 6-19. Conducted Power Spectral Density Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 86 of 214	




Plot 6-115. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-116. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 87 of 214




Plot 6-117. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-118. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 88 of 214




Plot 6-119. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-120. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 89 of 214




Plot 6-121. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-122. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 90 of 214




Plot 6-123. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 6-124. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 91 of 214




Plot 6-125. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 6-126. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 92 of 214




Plot 6-127. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 6-128. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 93 of 214




Plot 6-129. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 6-130. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 94 of 214




Plot 6-131. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 6-132. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 95 of 214




Plot 6-135. Power Spectral Density Plot (802.11a UNII Band 2C) – Ch. 144)




Plot 6-136. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 97 of 214




Plot 6-137. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)




Plot 6-138. Power Spectral Density Plot (20MHz 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: A3LSMG9200	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 98 of 214




Plot 6-139. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 6-140. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 99 of 214




Plot 6-141. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)



Plot 6-142. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 100 of 214




Plot 6-143. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 101 of 214	


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/500kHz]	Margin [dB]	Pass / Fail
Band 3	5745	149	a	6	-1.05	30.0	-31.05	Pass
	5785	157	a	6	-1.58	30.0	-31.58	Pass
	5825	165	a	6	-1.70	30.0	-31.70	Pass
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	-2.65	30.0	-32.65	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	-3.05	30.0	-33.05	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	-3.08	30.0	-33.08	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	-6.60	30.0	-36.60	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	-7.06	30.0	-37.06	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-8.52	30.0	-38.52	Pass

Table 6-20. Band 3 Conducted Power Spectral Density Measurements




Plot 6-144. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 102 of 214	




Plot 6-145. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 6-146. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 103 of 214



Plot 6-151. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 6-152. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 106 of 214

Summed MIMO Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed MIMO Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	n (20MHz)	6.5/7.2 (MCS0)	-0.62	-1.33	2.05	11.0	-8.95	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-0.32	-0.84	2.44	11.0	-8.56	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	-0.83	-0.87	2.16	11.0	-8.84	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	-4.22	-4.15	-1.18	11.0	-12.18	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	-4.14	-3.82	-0.97	11.0	-11.97	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-6.78	-5.92	-3.32	11.0	-14.32	Pass
Band 2A	5260	52	n (20MHz)	6.5/7.2 (MCS0)	-0.94	-0.57	2.26	11.0	-8.74	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	-0.84	-0.45	2.37	11.0	-8.63	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	-0.54	-0.31	2.59	11.0	-8.41	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	-4.13	-3.56	-0.82	11.0	-11.82	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	-3.86	-3.61	-0.72	11.0	-11.72	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-6.98	-5.43	-3.12	11.0	-14.12	Pass
Band 2C	5500	100	n (20MHz)	6.5/7.2 (MCS0)	-1.65	0.58	2.62	11.0	-8.38	Pass
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	-1.40	0.10	2.42	11.0	-8.58	Pass
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	-0.09	0.96	3.48	11.0	-7.52	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	-3.74	-2.84	-0.25	11.0	-11.25	Pass
	5550	110	n (40MHz)	13.5/15 (MCS0)	-3.82	-3.05	-0.41	11.0	-11.41	Pass
	5710	142	n (40MHz)	13.5/15 (MCS0)	-2.41	-1.30	1.19	11.0	-9.81	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-7.71	-4.99	-3.13	11.0	-14.13	Pass
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-6.36	-5.61	-2.96	11.0	-13.96	Pass

Table 6-21. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed MIMO Power Density [dBm]	Max Permissible Power Density [dBm/500kHz]	Margin [dB]	Pass / Fail
Band 3	5745	149	n (20MHz)	6.5/7.2 (MCS0)	-2.87	-2.65	0.25	30.0	-29.75	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	-3.46	-3.05	-0.24	30.0	-30.24	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	-3.40	-3.08	-0.23	30.0	-30.23	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	-6.24	-6.60	-3.40	30.0	-33.40	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	-6.40	-7.06	-3.71	30.0	-33.71	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-10.32	-8.52	-6.32	30.0	-36.32	Pass

Table 6-22. Band 3 MIMO Conducted Power Spectral Density Measurements

Note:



Per KDB 662911 v02r01 Section E)2), the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 5180MHz the average conducted power spectral density was measured to be -0.62 dBm for Antenna-1 and -1.33 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(-0.62 \text{ dBm} + -1.33 \text{ dBm}) = (0.87 \text{ mW} + 0.74 \text{ mW}) = 1.60 \text{ mW} = 2.05 \text{ dBm}$$

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 107 of 214

6.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,179,999,763	-237	-0.00000458
100 %		- 30	5,179,999,887	-113	-0.00000218
100 %		- 20	5,180,000,088	88	0.00000170
100 %		- 10	5,179,999,689	-311	-0.00000600
100 %		0	5,180,000,102	102	0.00000197
100 %		+ 10	5,180,000,035	35	0.00000068
100 %		+ 20	5,179,999,774	-226	-0.00000436
100 %		+ 30	5,180,000,014	14	0.00000027
100 %		+ 40	5,180,000,040	40	0.00000077
100 %		+ 50	5,179,999,832	-168	-0.00000324
BATT. ENDPOINT	3.45	+ 20	5,180,000,204	204	0.00000394

Table 6-23. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 108 of 214	

Frequency Stability §15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,259,999,757	-243	-0.00000462
100 %		- 30	5,259,999,875	-125	-0.00000238
100 %		- 20	5,259,999,964	-36	-0.00000068
100 %		- 10	5,260,000,179	179	0.00000340
100 %		0	5,260,000,198	198	0.00000376
100 %		+ 10	5,260,000,206	206	0.00000392
100 %		+ 20	5,259,999,801	-199	-0.00000378
100 %		+ 30	5,259,999,558	-442	-0.00000840
100 %		+ 40	5,260,000,068	68	0.00000129
100 %		+ 50	5,260,000,061	61	0.00000116
BATT. ENDPOINT	3.45	+ 20	5,260,000,342	342	0.00000650

Table 6-24. Frequency Stability Measurements for UNII Band 2A (Ch. 52)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 109 of 214	

Frequency Stability §15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,500,000,062	62	0.00000113
100 %		- 30	5,499,999,820	-180	-0.00000327
100 %		- 20	5,499,999,803	-197	-0.00000358
100 %		- 10	5,499,999,933	-67	-0.00000122
100 %		0	5,500,000,331	331	0.00000602
100 %		+ 10	5,500,000,446	446	0.00000811
100 %		+ 20	5,500,000,378	378	0.00000687
100 %		+ 30	5,500,000,057	57	0.00000104
100 %		+ 40	5,500,000,180	180	0.00000327
100 %		+ 50	5,499,999,850	-150	-0.00000273
BATT. ENDPOINT		3.45	+ 20	5,500,000,180	180

Table 6-25. Frequency Stability Measurements for UNII Band 2C (Ch. 100)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 110 of 214	

Frequency Stability §15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,745,000,000 Hz
 CHANNEL: 149
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,745,000,360	360	0.00000627
100 %		- 30	5,744,999,727	-273	-0.00000475
100 %		- 20	5,744,999,997	-3	-0.00000005
100 %		- 10	5,744,999,749	-251	-0.00000437
100 %		0	5,745,000,186	186	0.00000324
100 %		+ 10	5,744,999,853	-147	-0.00000256
100 %		+ 20	5,744,999,823	-177	-0.00000308
100 %		+ 30	5,744,999,917	-83	-0.00000144
100 %		+ 40	5,745,000,371	371	0.00000646
100 %		+ 50	5,745,000,007	7	0.00000012
BATT. ENDPOINT	3.45	+ 20	5,744,999,888	-112	-0.00000195

Table 6-26. Frequency Stability Measurements for UNII Band 3 (Ch. 149)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 111 of 214	

6.7 Radiated Spurious Emission Measurements

§15.407(b.1)(b.6) §15.205 §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle (>98%), at its maximum power control level, as defined in KDB 789033 D02 v01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW), 802.11n (40MHz BW), 802.11ac (80MHz BW)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-27 per Section 15.209.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 6-27. Radiated Limits

Test Procedures Used

KDB 789033 D02 v01 – Section G



Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 112 of 214	

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-5. Test Instrument & Measurement Setup

Test Notes

1. All radiated spurious emissions levels were measured in a radiated test setup per the guidance of KDB 789033 D02 v01 Section H.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-27.
3. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-11. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. This unit was tested with its standard battery.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 113 of 214	

6. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.
9. Radiated spurious emissions pre-scan plots are also reported in this section. The plots apply the appropriate system corrections, however, they do not show the fully maximized spectrum. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. Rohde & Schwarz EMC32, Version 9.15.00 automated test software was used to perform the Radiated Spurious Emissions Pre-Scan testing.

Sample Calculations



Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:


$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Pre-amplifier Gain}$$

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 114 of 214	

6.7.1 Antenna-1 Radiated Spurious Emission Measurements




Plot 6-153. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. H)




Plot 6-154. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 115 of 214




Plot 6-155. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. H)




Plot 6-156. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. V)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 116 of 214	




Plot 6-157. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. H)




Plot 6-158. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 117 of 214	




Plot 6-159. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 6-160. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 118 of 214	



Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz) §15.209



Plot 6-161. Radiated Spurious Plot above 18GHz (802.11a – Ant. Pol. H)



Plot 6-162. Radiated Spurious Plot above 18GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 119 of 214	

Antenna-1 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	-107.06	Peak	H	44.79	0.00	44.72	68.20	-23.48
* 15540.00	-118.17	Average	H	49.29	0.00	38.12	53.98	-15.86
* 15540.00	-106.62	Peak	H	49.29	0.00	49.67	73.98	-24.31
* 20720.00	-107.00	Average	H	44.20	-9.54	34.65	53.98	-19.33
* 20720.00	-99.95	Peak	H	44.20	-9.54	41.70	73.98	-32.28
25900.00	-102.16	Peak	H	45.08	-9.54	40.37	68.20	-27.83

Table 6-28. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	-106.31	Peak	H	44.87	0.00	45.57	68.20	-22.63
* 15600.00	-118.92	Average	H	49.31	0.00	37.39	53.98	-16.59
* 15600.00	-106.24	Peak	H	49.31	0.00	50.07	73.98	-23.91
* 20800.00	-107.26	Average	H	44.20	-9.54	34.40	53.98	-19.58
* 20800.00	-100.25	Peak	H	44.20	-9.54	41.41	73.98	-32.57
26000.00	-101.72	Peak	H	45.11	-9.54	40.85	68.20	-27.35

Table 6-29. Radiated Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 120 of 214	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10480.00	-106.06	Peak	H	45.08	0.00	46.02	68.20	-22.18
* 15720.00	-117.65	Average	H	49.40	0.00	38.75	53.98	-15.23
* 15720.00	-106.23	Peak	H	49.40	0.00	50.17	73.98	-23.81
* 20960.00	-105.78	Average	H	44.19	-9.54	35.86	53.98	-18.12
* 20960.00	-99.80	Peak	H	44.19	-9.54	41.84	73.98	-32.14
26200.00	-101.50	Peak	H	44.95	-9.54	40.91	68.20	-27.29

Table 6-30. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10520.00	-107.02	Peak	H	45.13	0.00	45.11	68.20	-23.09
* 15780.00	-118.12	Average	H	49.46	0.00	38.33	53.98	-15.65
* 15780.00	-105.93	Peak	H	49.46	0.00	50.52	73.98	-23.46
* 21040.00	-108.05	Average	H	44.18	-9.54	33.58	53.98	-20.39
* 21040.00	-102.43	Peak	H	44.18	-9.54	39.20	73.98	-34.77
26300.00	-100.47	Peak	H	44.95	-9.54	41.93	68.20	-26.27

Table 6-31. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10560.00	-104.71	Peak	H	45.13	0.00	47.42	68.20	-20.78
* 15840.00	-118.14	Average	H	49.54	0.00	38.41	53.98	-15.57
* 15840.00	-106.32	Peak	H	49.54	0.00	50.23	73.98	-23.75
* 21120.00	-107.85	Average	H	44.17	-9.54	33.78	53.98	-20.20
* 21120.00	-102.30	Peak	H	44.17	-9.54	39.33	73.98	-34.65
26400.00	-100.27	Peak	H	45.01	-9.54	42.19	68.20	-26.01

Table 6-32. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 10640.00	-117.60	Average	H	45.16	0.00	34.56	53.98	-19.42
* 10640.00	-106.69	Peak	H	45.16	0.00	45.47	73.98	-28.51
* 15960.00	-118.12	Average	H	49.75	0.00	38.63	53.98	-15.35
* 15960.00	-106.48	Peak	H	49.75	0.00	50.27	73.98	-23.71
* 21280.00	-108.29	Average	H	44.18	-9.54	33.34	53.98	-20.63
* 21280.00	-101.92	Peak	H	44.18	-9.54	39.71	73.98	-34.26
26600.00	-104.29	Peak	H	47.61	-9.54	40.78	68.20	-27.42

Table 6-33. Radiated Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 122 of 214	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11000.00	-117.25	Average	H	45.24	0.00	34.99	53.98	-18.99
* 11000.00	-105.43	Peak	H	45.24	0.00	46.81	73.98	-27.17
16500.00	-105.53	Peak	H	50.35	0.00	51.82	68.20	-16.38
22000.00	-103.15	Peak	H	44.47	-9.54	38.78	68.20	-29.42
27500.00	-105.25	Peak	H	47.92	-9.54	40.13	68.20	-28.07

Table 6-34. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11160.00	-116.80	Average	H	45.23	0.00	35.43	53.98	-18.55
* 11160.00	-104.74	Peak	H	45.23	0.00	47.49	73.98	-26.49
16740.00	-106.46	Peak	H	50.51	0.00	51.05	68.20	-17.15
* 22320.00	-114.34	Average	H	44.59	-9.54	27.71	53.98	-26.27
* 22320.00	-103.27	Peak	H	44.59	-9.54	38.78	73.98	-35.20
27900.00	-104.57	Peak	H	48.09	-9.54	40.98	68.20	-27.22

Table 6-35. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11440.00	-116.52	Average	H	45.38	0.00	35.86	53.98	-18.12
* 11440.00	-104.60	Peak	H	45.38	0.00	47.78	73.98	-26.20
17160.00	-106.85	Peak	H	50.43	0.00	50.58	68.20	-17.62
* 22880.00	-112.68	Average	H	44.62	-9.54	29.40	53.98	-24.58
* 22880.00	-103.33	Peak	H	44.62	-9.54	38.75	73.98	-35.23
28600.00	-105.07	Peak	H	48.35	-9.54	40.74	68.20	-27.46

Table 6-36. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11490.00	-117.79	Average	H	45.36	0.00	34.57	53.98	-19.41
* 11490.00	-105.93	Peak	H	45.36	0.00	46.43	73.98	-27.55
17235.00	-105.80	Peak	H	49.98	0.00	51.17	68.20	-17.03
* 22980.00	-110.75	Average	H	44.64	-9.54	31.34	53.98	-22.64
* 22980.00	-103.58	Peak	H	44.64	-9.54	38.51	73.98	-35.47
28725.00	-104.23	Peak	H	48.26	-9.54	41.49	68.20	-26.71

Table 6-37. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	-117.37	Average	H	45.46	0.00	35.09	53.98	-18.89
* 11570.00	-105.89	Peak	H	45.46	0.00	46.57	73.98	-27.41
17355.00	-106.62	Peak	H	50.40	0.00	50.78	68.20	-17.42
23140.00	-101.41	Peak	H	44.73	-9.54	40.78	68.20	-27.42
28925.00	-105.07	Peak	H	48.28	-9.54	40.66	68.20	-27.54

Table 6-38. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	-117.75	Average	H	45.57	0.00	34.82	53.98	-19.16
* 11650.00	-106.26	Peak	H	45.57	0.00	46.31	73.98	-27.67
17475.00	-106.02	Peak	H	50.74	0.00	51.72	68.20	-16.48
23300.00	-101.04	Peak	H	44.76	-9.54	41.18	68.20	-27.02
29125.00	-104.91	Peak	H	48.24	-9.54	40.79	68.20	-27.41

Table 6-39. Radiated Measurements


Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10480.00	-105.14	Peak	H	45.08	0.00	46.94	68.20	-21.26
* 15720.00	-120.67	Average	H	49.40	0.00	35.73	53.98	-18.25
* 15720.00	-108.15	Peak	H	49.40	0.00	48.25	73.98	-25.73
* 20960.00	-104.65	Average	H	44.19	-9.54	36.99	53.98	-16.99
* 20960.00	-96.63	Peak	H	44.19	-9.54	45.01	73.98	-28.97
26200.00	-96.94	Peak	H	44.95	-9.54	45.47	68.20	-22.73


Table 6-40. Radiated Measurements with WCC

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 126 of 214

6.7.2 Antenna-2 Radiated Spurious Emission Measurements




Plot 6-163. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. H)




Plot 6-164. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. V)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 127 of 214




Plot 6-165. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. H)




Plot 6-166. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. V)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 128 of 214	




Plot 6-167. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. H)




Plot 6-168. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. V)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 129 of 214	




Plot 6-169. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 6-170. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 130 of 214	

Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz) §15.209



Plot 6-171. Radiated Spurious Plot above 18GHz (802.11a – Ant. Pol. H)



Plot 6-172. Radiated Spurious Plot above 18GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 131 of 214

Antenna-2 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	-105.84	Peak	H	44.79	0.00	45.94	68.20	-22.26
* 15540.00	-117.92	Average	H	49.29	0.00	38.37	53.98	-15.61
* 15540.00	-105.33	Peak	H	49.29	0.00	50.96	73.98	-23.02
* 20720.00	-110.73	Average	H	44.20	-9.54	30.92	53.98	-23.06
* 20720.00	-103.19	Peak	H	44.20	-9.54	38.46	73.98	-35.52
25900.00	-102.02	Peak	H	45.08	-9.54	40.51	68.20	-27.69

Table 6-41. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	-106.49	Peak	H	44.87	0.00	45.39	68.20	-22.81
* 15600.00	-117.80	Average	H	49.31	0.00	38.51	53.98	-15.47
* 15600.00	-105.34	Peak	H	49.31	0.00	50.97	73.98	-23.01
* 20800.00	-110.39	Average	H	44.20	-9.54	31.27	53.98	-22.71
* 20800.00	-102.59	Peak	H	44.20	-9.54	39.07	73.98	-34.91
26000.00	-103.10	Peak	H	45.11	-9.54	39.47	68.20	-28.73

Table 6-42. Radiated Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 132 of 214	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10480.00	-105.79	Peak	H	45.08	0.00	46.29	68.20	-21.91
* 15720.00	-117.48	Average	H	49.40	0.00	38.92	53.98	-15.06
* 15720.00	-105.96	Peak	H	49.40	0.00	50.44	73.98	-23.54
* 20960.00	-110.89	Average	H	44.19	-9.54	30.75	53.98	-23.23
* 20960.00	-102.12	Peak	H	44.19	-9.54	39.52	73.98	-34.46
26200.00	-101.81	Peak	H	44.95	-9.54	40.60	68.20	-27.60

Table 6-43. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10520.00	-105.91	Peak	H	45.13	0.00	46.22	68.20	-21.98
* 15780.00	-118.13	Average	H	49.46	0.00	38.32	53.98	-15.66
* 15780.00	-106.34	Peak	H	49.46	0.00	50.11	73.98	-23.87
* 21040.00	-110.74	Average	H	44.18	-9.54	30.89	53.98	-23.08
* 21040.00	-103.82	Peak	H	44.18	-9.54	37.81	73.98	-36.16
26300.00	-101.13	Peak	H	44.95	-9.54	41.27	68.20	-26.93

Table 6-44. Radiated Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 133 of 214	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10560.00	-105.41	Peak	H	45.13	0.00	46.72	68.20	-21.48
* 15840.00	-118.29	Average	H	49.54	0.00	38.26	53.98	-15.72
* 15840.00	-106.77	Peak	H	49.54	0.00	49.78	73.98	-24.20
* 21120.00	-112.49	Average	H	44.17	-9.54	29.14	53.98	-24.84
* 21120.00	-103.39	Peak	H	44.17	-9.54	38.24	73.98	-35.74
26400.00	-101.13	Peak	H	45.01	-9.54	41.33	68.20	-26.87

Table 6-45. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 10640.00	-116.03	Average	H	45.16	0.00	36.13	53.98	-17.85
* 10640.00	-105.86	Peak	H	45.16	0.00	46.30	73.98	-27.68
* 15960.00	-116.53	Average	H	49.75	0.00	40.22	53.98	-13.76
* 15960.00	-106.95	Peak	H	49.75	0.00	49.80	73.98	-24.18
* 21280.00	-112.37	Average	H	44.18	-9.54	29.26	53.98	-24.71
* 21280.00	-103.12	Peak	H	44.18	-9.54	38.51	73.98	-35.46
26600.00	-103.66	Peak	H	47.61	-9.54	41.41	68.20	-26.79

Table 6-46. Radiated Measurements

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 134 of 214	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11000.00	-117.30	Average	H	45.24	0.00	34.94	53.98	-19.04
* 11000.00	-105.18	Peak	H	45.24	0.00	47.06	73.98	-26.92
16500.00	-105.58	Peak	H	50.35	0.00	51.77	68.20	-16.43
22000.00	-101.99	Peak	H	44.47	-9.54	39.94	68.20	-28.26
27500.00	-107.16	Peak	H	47.92	-9.54	38.22	68.20	-29.98

Table 6-47. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11160.00	-117.09	Average	H	45.23	0.00	35.14	53.98	-18.84
* 11160.00	-105.03	Peak	H	45.23	0.00	47.20	73.98	-26.78
16740.00	-106.02	Peak	H	50.51	0.00	51.49	68.20	-16.71
* 22320.00	-112.73	Average	H	44.59	-9.54	29.32	53.98	-24.66
* 22320.00	-104.22	Peak	H	44.59	-9.54	37.83	73.98	-36.15
27900.00	-104.96	Peak	H	48.09	-9.54	40.59	68.20	-27.61

Table 6-48. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	-117.72	Average	H	45.38	0.00	34.66	53.98	-19.32
* 11440.00	-107.87	Peak	H	45.38	0.00	44.51	73.98	-29.47
17160.00	-106.21	Peak	H	50.43	0.00	51.22	68.20	-16.98
* 22880.00	-113.66	Average	H	44.62	-9.54	28.42	53.98	-25.56
* 22880.00	-104.40	Peak	H	44.62	-9.54	37.68	73.98	-36.30
28600.00	-106.67	Peak	H	48.35	-9.54	39.14	68.20	-29.06

Table 6-49. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	-117.95	Average	H	45.36	0.00	34.41	53.98	-19.57
* 11490.00	-105.37	Peak	H	45.36	0.00	46.99	73.98	-26.99
17235.00	-106.06	Peak	H	49.98	0.00	50.91	68.20	-17.29
* 22980.00	-113.55	Average	H	44.64	-9.54	28.54	53.98	-25.44
* 22980.00	-104.36	Peak	H	44.64	-9.54	37.73	73.98	-36.25
28725.00	-104.39	Peak	H	48.26	-9.54	41.33	68.20	-26.87

Table 6-50. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11570.00	-117.32	Average	H	45.46	0.00	35.14	53.98	-18.84
* 11570.00	-105.60	Peak	H	45.46	0.00	46.86	73.98	-27.12
17355.00	-106.15	Peak	H	50.40	0.00	51.25	68.20	-16.95
23140.00	-102.02	Peak	H	44.73	-9.54	40.17	68.20	-28.03
28925.00	-104.65	Peak	H	48.28	-9.54	41.08	68.20	-27.12

Table 6-51. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11650.00	-117.79	Average	H	45.57	0.00	34.78	53.98	-19.20
* 11650.00	-105.94	Peak	H	45.57	0.00	46.63	73.98	-27.35
17475.00	-106.50	Peak	H	50.74	0.00	51.24	68.20	-16.96
23300.00	-102.23	Peak	H	44.76	-9.54	39.99	68.20	-28.21
29125.00	-105.52	Peak	H	48.24	-9.54	40.18	68.20	-28.02

Table 6-52. Radiated Measurements


Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 10640.00	-117.95	Average	H	45.16	0.00	34.21	53.98	-19.77
* 10640.00	-105.43	Peak	H	45.16	0.00	46.73	73.98	-27.25
* 15960.00	-120.32	Average	H	49.75	0.00	36.43	53.98	-17.55
* 15960.00	-108.96	Peak	H	49.75	0.00	47.79	73.98	-26.19
* 21280.00	-109.66	Average	H	44.18	-9.54	31.97	53.98	-22.00
* 21280.00	-98.39	Peak	H	44.18	-9.54	43.24	73.98	-30.73
26600.00	-104.18	Peak	H	47.61	-9.54	40.89	68.20	-27.31

Table 6-53. Radiated Measurements with WCC

6.7.3 Antenna-1 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36




Date: 23.JAN.2015 08:48:38

Plot 6-173. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 139 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 08:50:05

Plot 6-174. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 140 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64




Date: 23.JAN.2015 09:20:35

Plot 6-175. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 141 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:20:59

Plot 6-176. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 142 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100




Date: 23.JAN.2015 09:39:46

Plot 6-177. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 143 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:40:27


Plot 6-178. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 144 of 214	

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Date: 23.JAN.2015 10:22:34

Plot 6-179. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 145 of 214

6.7.4 Antenna-1 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 23.JAN.2015 08:58:46

Plot 6-180. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 146 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 08:56:05


Plot 6-181. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 147 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Date: 23.JAN.2015 09:25:04

Plot 6-182. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 148 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:26:00


Plot 6-183. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 149 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Date: 23.JAN.2015 09:43:41

Plot 6-184. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 150 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:44:50


Plot 6-185. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 151 of 214	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Date: 23.JAN.2015 10:34:18

Plot 6-186. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 152 of 214	

6.7.5 Antenna-1 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42




Date: 23.JAN.2015 09:07:18

Plot 6-187. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 153 of 214	

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:12:56


Plot 6-188. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 154 of 214	

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58




Date: 23.JAN.2015 09:31:35

Plot 6-189. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 155 of 214

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:33:01


Plot 6-190. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 156 of 214	

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Date: 23.JAN.2015 09:53:21

Plot 6-191. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 157 of 214

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 23.JAN.2015 09:54:18


Plot 6-192. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 158 of 214	

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155




Date: 23.JAN.2015 10:44:07

Plot 6-193. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 159 of 214	

6.7.6 Antenna-2 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36




Date: 24.JAN.2015 16:28:20

Plot 6-194. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 160 of 214	

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 16:28:48

Plot 6-195. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 161 of 214

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64




Date: 24.JAN.2015 16:57:11

Plot 6-196. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 162 of 214	

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 16:57:37


Plot 6-197. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 163 of 214	

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Date: 24.JAN.2015 17:39:31

Plot 6-198. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 164 of 214	

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 17:42:21


Plot 6-199. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 165 of 214	

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Date: 24.JAN.2015 18:35:43

Plot 6-200. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 166 of 214

6.7.7 Antenna-2 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 24.JAN.2015 16:40:59

Plot 6-201. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 167 of 214	

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 16:41:27


Plot 6-202. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 168 of 214	

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Date: 24.JAN.2015 17:20:14

Plot 6-203. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 169 of 214	

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 17:21:19


Plot 6-204. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 170 of 214	

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Date: 24.JAN.2015 17:47:20

Plot 6-205. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 171 of 214

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 17:46:30


Plot 6-206. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 172 of 214

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Date: 24.JAN.2015 18:34:11

Plot 6-207. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 173 of 214	

6.7.8 Antenna-2 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42




Date: 24.JAN.2015 16:50:02

Plot 6-208. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 174 of 214

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 16:50:55


Plot 6-209. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 175 of 214

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58




Date: 24.JAN.2015 17:29:13

Plot 6-210. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 176 of 214

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 17:27:42


Plot 6-211. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 177 of 214

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Date: 24.JAN.2015 17:50:56

Plot 6-212. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 178 of 214	

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 24.JAN.2015 17:52:13


Plot 6-213. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 179 of 214	

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Date: 24.JAN.2015 18:31:31


Plot 6-214. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 180 of 214

6.7.9 MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36




Date: 28.JAN.2015 16:14:55

Plot 6-215. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 181 of 214

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:15:32


Plot 6-216. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 182 of 214

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64




Date: 28.JAN.2015 16:27:40

Plot 6-217. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 183 of 214

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:32:36


Plot 6-218. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 184 of 214	

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Date: 28.JAN.2015 16:45:48

Plot 6-219. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 185 of 214

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:48:04


Plot 6-220. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 186 of 214

MIMO Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Date: 28.JAN.2015 17:13:03

Plot 6-221. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 187 of 214

6.7.10 MIMO Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 28.JAN.2015 16:17:42

Plot 6-222. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 188 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:17:02

Plot 6-223. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 189 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62




Date: 28.JAN.2015 16:36:13

Plot 6-224. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)



FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 190 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:35:25


Plot 6-225. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 191 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Date: 28.JAN.2015 16:50:37

Plot 6-226. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 192 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:49:55


Plot 6-227. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 193 of 214	

MIMO Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Date: 28.JAN.2015 17:12:09

Plot 6-228. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 194 of 214

6.7.11 MIMO Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42




Date: 28.JAN.2015 16:19:50

Plot 6-229. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 195 of 214

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:20:24


Plot 6-230. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 196 of 214	

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58




Date: 28.JAN.2015 16:38:17

Plot 6-231. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 197 of 214

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:39:14


Plot 6-232. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 198 of 214	

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Date: 28.JAN.2015 16:52:06

Plot 6-233. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 199 of 214	

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Date: 28.JAN.2015 16:52:55


Plot 6-234. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 200 of 214	

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Date: 28.JAN.2015 17:09:31

Plot 6-235. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 201 of 214

6.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-54 per Section 15.209.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-54. Radiated Limits



Test Procedures Used

ANSI C63.4-2009

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 202 of 214	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-6. Test Instrument & Measurement Setup


Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
9. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.


FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 203 of 214	

Antenna-1 Radiated Spurious Emissions Measurements (Below 1GHz)



§15.209



Plot 6-236. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 6-237. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)


FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 204 of 214

Antenna-2 Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209



Plot 6-238. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 6-239. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 205 of 214

6.9 Line-Conducted Test Data

\$15.407



Plot 6-240. Line Conducted Plot with 802.11a UNII Band 1 (L1)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 206 of 214

Line-Conducted Test Data

\$15.407



Plot 6-241. Line Conducted Plot with 802.11a UNII Band 1 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 207 of 214

Line-Conducted Test Data

\$15.407



Plot 6-242. Line Conducted Plot with 802.11a UNII Band 2A (L1)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 208 of 214

Line-Conducted Test Data

\$15.407



Plot 6-243. Line Conducted Plot with 802.11a UNII Band 2A (N)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 209 of 214

Line-Conducted Test Data

\$15.407



Plot 6-244. Line Conducted Plot with 802.11a UNII Band 2C (L1)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 210 of 214

Line-Conducted Test Data

\$15.407



Plot 6-245. Line Conducted Plot with 802.11a UNII Band 2C (N)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 211 of 214

Line-Conducted Test Data

\$15.407



Plot 6-246. Line Conducted Plot with 802.11a UNII Band 3 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 149. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 212 of 214

Line-Conducted Test Data

\$15.407



Plot 6-247. Line Conducted Plot with 802.11a UNII Band 3 (N)



Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 149. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset		Page 213 of 214

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG9200** is in compliance with Part 15E of the FCC Rules.

FCC ID: A3LSMG9200		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1501220216.A3L	Test Dates: 01/22 - 02/17/2015	EUT Type: Portable Handset	Page 214 of 214	