



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

01/26/15 - 02/06/15

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

0Y1501300326.A3L

FCC ID:

A3LSMG920A

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-G920A

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.22	0.41	0.60
PCE	UMTS 850	826.40 - 846.60 MHz	0.22	0.34	0.37
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.17	0.31	1.02
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.49	0.90	1.04
PCE	LTE Band 12	699.7 - 715.3 MHz	0.26	0.51	0.55
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.16	0.28	0.38
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.40	0.96	0.98
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.44	0.92	1.00
PCE	LTE Band 30	2307.5 - 2312.5 MHz	0.19	0.25	0.50
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.64	< 0.1	0.12
NII	U-NII-1	5180 - 5240 MHz	N/A		
NII	U-NII-2A	5260 - 5320 MHz	0.19	< 0.1	
NII	U-NII-2C < 5.65 GHz	5500 - 5580 MHz	0.21	< 0.1	
NII	U-NII-2C > 5.65 GHz + U-NII-3	5660 - 5825 MHz	0.22	< 0.1	< 0.1
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A		
Simultaneous SAR per KDB 690783 D01v01r03:			1.13	1.16	1.25

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 1 of 108	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	10
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS	14
6	TEST CONFIGURATION POSITIONS FOR HANDSETS	15
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS.....	25
10	SYSTEM VERIFICATION.....	77
11	SAR DATA SUMMARY	80
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	91
13	SAR MEASUREMENT VARIABILITY	102
14	EQUIPMENT LIST.....	103
15	MEASUREMENT UNCERTAINTIES	104
16	CONCLUSION.....	106
17	REFERENCES	107
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset
		Page 2 of 108

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C < 5.65 GHz	Data	5500 - 5580 MHz
U-NII-2C > 5.65 GHz + U-NII-3	Data	5660 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	1-8.3 kHz

1.2 Power Reduction for SAR

This device utilizes two single step independent power reduction mechanisms for SAR compliance. For the main transmitter, there is power reduction under portable hotspot conditions for UMTS Band 5/2, and LTE Band 12/17/5/2/4/30 All hotspot SAR evaluations for this device were performed with the maximum allowed output power in hotspot mode. Additionally for the unlicensed transmitter, this device utilizes a proximity sensor to reduce the output power for 2.4 GHz WLAN during voice or VoIP held-to-ear scenarios. Per FCC guidance, the held-to-ear exposure conditions were evaluated at reduced power level. The reduced powers for both mechanisms were confirmed via conducted power measurements at the RF port (See section 9). Detailed description of the hotspot power reduction and proximity sensor mechanisms are included in the operational description.

1.3 Nominal and Maximum Output Power Specifications

1.3.1 Maximum PCE Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)		Burst Average 8-PSK (dBm)	
		1 TX Slot	1 TX Slots	2 TX Slots	1 TX Slots	2 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.5	33.5	32.5	27.5	26.0
	Nominal	33.0	33.0	32.0	27.0	25.5
GSM/GPRS/EDGE 1900	Maximum	30.0	30.0	28.0	26.5	25.0
	Nominal	29.5	29.5	27.5	26.0	24.5

FCC ID: A3LSMG920A		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 3 of 108	

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	25.0	23.5	23.5
	Nominal	24.5	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	24.5	23.0	23.0
	Nominal	24.0	22.5	22.5

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	24.5
	Nominal	24.0
LTE Band 17	Maximum	24.5
	Nominal	24.0
LTE Band 5 (Cell)	Maximum	24.5
	Nominal	24.0
LTE Band 4 (AWS)	Maximum	24.5
	Nominal	24.0
LTE Band 2 (PCS)	Maximum	24.5
	Nominal	24.0
LTE Band 30	Maximum	23.5
	Nominal	23.0

1.3.2 Maximum DTS/DSS Power

SISO

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	15.5
	Nominal	15.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	13.5
	Nominal	13.0
Bluetooth	Maximum	11.5
	Nominal	11.0
Bluetooth LE	Maximum	9.0
	Nominal	8.5

MIMO

Mode / Band		Modulated Average (dBm)
IEEE 802.11n (2.4 GHz)	Maximum	13.5
	Nominal	13.0

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 4 of 108	

1.3.3 Maximum NII Power

SISO

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	12.5		
	Nominal	12.0		
IEEE 802.11n (5 GHz)	Maximum	12.5		
	Nominal	12.0		
IEEE 802.11ac (5 GHz)	Maximum	12.5	11.5	10.5
	Nominal	12.0	11.0	10.0

MIMO

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11n (5 GHz)	Maximum	15.5	14.5	
	Nominal	15.0	14.0	
IEEE 802.11ac (5 GHz)	Maximum	15.5	14.5	13.5
	Nominal	15.0	14.0	13.0

1.3.4 Reduced PCE Power – Hotspot Active

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	23.5	23.5	23.5
	Nominal	23.0	23.0	23.0
UMTS Band 2 (1900 MHz)	Maximum	21.5	21.5	21.5
	Nominal	21.0	21.0	21.0

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	23.5
	Nominal	23.0
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 5 (Cell)	Maximum	23.5
	Nominal	23.0
LTE Band 4 (AWS)	Maximum	21.0
	Nominal	20.5
LTE Band 2 (PCS)	Maximum	21.0
	Nominal	20.5
LTE Band 30	Maximum	22.5
	Nominal	22.0

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 5 of 108	

1.3.5 Reduced DTS Power –Held-To-Ear

SISO

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11g (2.4 GHz)	Maximum	14.5
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	12.5
	Nominal	12.0

MIMO

Mode / Band		Modulated Average (dBm)
IEEE 802.11n (2.4 GHz)	Maximum	12.5
	Nominal	12.0

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is <160 mm and the diagonal display is <150 mm. A diagram showing the location of the device antennas can be found in Appendix F.

Table 1-1
Mobile Hotspot Sides for SAR Testing

Mobile Hotspot Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 30	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN Antenna 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Antenna 2	Yes	Yes	Yes	No	Yes	No
U-NII-3 WLAN Antenna 1	Yes	Yes	Yes	No	No	Yes
U-NII-3 WLAN Antenna 2	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02 guidance, page 2. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, 5.2-5.7 GHz WLAN operations are disabled. Therefore 5.2-5.7 GHz WLAN operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC Operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 6 of 108	

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A
4	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes
5	UMTS + 5 GHz WI-FI	Yes	Yes	Yes
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A
7	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes
8	LTE + 5 GHz WI-FI	Yes	Yes	Yes
9	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A
10	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes
11	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	Yes

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
- This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.
- This Device supports VoLTE.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 7 of 108	

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB 248227 D01 DR02-41929.

Since this device supports the band gap channels, the channels in the U-NII-2C band above 5.65 GHz were grouped with the channels in the U-NII-3 as a single aggregate band. The channels in UNII-2C below 5.65 GHz were considered separately for SAR evaluation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) Band gap channels are supported

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(14/15) * \sqrt{2.480}] = 1.5 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r03.

This device supports both LTE Band 12 and LTE Band 17. Since the supported frequency span for LTE Band 17 falls completely within the supported frequency span for LTE Band 12, LTE Band 17 has a lower target power than LTE Band 12, and both LTE bands share the same transmission path, SAR was only assessed for LTE Band 12.

This device supports inter-band LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 8 of 108

1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v03, D05v02r03, D05Av01, D06v02 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01 DR02-41929 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	11624	11624	11624
UMTS 850	119C8	11656	11656
GSM/GPRS/EDGE 1900	11624	11634	11634
UMTS 1900	119C8	119C8	11656
LTE Band 12	1164B	1164B	11653
LTE Band 5 (Cell)	11653	11653	11653
LTE Band 4 (AWS)	11653	11653	11634
LTE Band 2 (PCS)	11634	11634	11634
LTE Band 30	1164B	1164B	1164B
2.4 GHz WLAN	119C8	1164B	1164B
5 GHz WLAN	11656	11656	11656

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset

2

LTE INFORMATION

LTE Information			
FCC ID	A3LSMG920A		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)		
	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
	LTE Band 30 (2307.5 - 2312.5 MHz)		
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 30: 5 MHz, 10 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
LTE Band 30: 5 MHz	2307.5 (27685)	2310 (27710)	2312.5 (27735)
LTE Band 30: 10 MHz	2310 (27710)	2310 (27710)	2310 (27710)
UE Category	6		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		
LTE Carrier Aggregation Possible Combinations	Please see next page for LTE Carrier Aggregation Possible Combinations		
LTE Carrier Aggregation Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WIFI Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.		

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 10 of 108

LTE Carrier Aggregation Possible Combinations

B4 (PCC) + B17 (SCC)	B2 (PCC) + B17 (SCC)	B17 (PCC) + B2 (SCC)	B2 (PCC) + B29 (SCC)	B4 (PCC) + B29 (SCC)	B2 (PCC) + B5 (SCC)
5MHz (B4) + 5MHz (B17)	5MHz (B2) + 5MHz (B17)	10MHz (B17) + 5MHz (B2)	5MHz (B2) + 3MHz (B29)	5MHz (B4) + 3MHz (B29)	5MHz (B2) + 5MHz (B5)
5MHz (B4) + 10MHz (B17)	5MHz (B2) + 10MHz (B17)	10MHz (B17) + 10MHz (B2)	5MHz (B2) + 5MHz (B29)	5MHz (B4) + 5MHz (B29)	5MHz (B2) + 10MHz (B5)
10MHz (B4) + 5MHz (B17)	10MHz (B2) + 5MHz (B17)	10MHz (B17) + 15MHz (B2)	5MHz (B2) + 10MHz (B29)	5MHz (B4) + 10MHz (B29)	10MHz (B2) + 5MHz (B5)
10MHz (B4) + 10MHz (B17)	10MHz (B2) + 10MHz (B17)	10MHz (B17) + 20MHz (B2)	10MHz (B2) + 3MHz (B29)	10MHz (B4) + 3MHz (B29)	10MHz (B2) + 10MHz (B5)
			10MHz (B2) + 5MHz (B29)	10MHz (B4) + 5MHz (B29)	15MHz (B2) + 5MHz (B5)
			10MHz (B2) + 10MHz (B29)	10MHz (B4) + 10MHz (B29)	15MHz (B2) + 10MHz (B5)
			15MHz (B2) + 3MHz (B29)	15MHz (B4) + 3MHz (B29)	20MHz (B2) + 5MHz (B5)
			15MHz (B2) + 5MHz (B29)	15MHz (B4) + 5MHz (B29)	20MHz (B2) + 10MHz (B5)
			15MHz (B2) + 10MHz (B29)	15MHz (B4) + 10MHz (B29)	
			20MHz (B2) + 3MHz (B29)	20MHz (B4) + 3MHz (B29)	
			20MHz (B2) + 5MHz (B29)	20MHz (B4) + 5MHz (B29)	
			20MHz (B2) + 10MHz (B29)	20MHz (B4) + 10MHz (B29)	
B5 (PCC) + B2 (SCC)	B4 (PCC) + B5 (SCC)	B5 (PCC) + B4 (SCC)	B2 (PCC) + B12 (SCC)	B12 (PCC) + B2 (SCC)	B4 (PCC) + B12 (SCC)
5MHz (B5) + 5MHz (B2)	5MHz (B4) + 5MHz (B5)	5MHz (B5) + 5MHz (B4)	5MHz (B2) + 3MHz (B12)	3MHz (B12) + 5MHz (B2)	1.4MHz (B4) + 3MHz (B12)
5MHz (B5) + 10MHz (B2)	5MHz (B4) + 10MHz (B5)	5MHz (B5) + 10MHz (B4)	5MHz (B2) + 5MHz (B12)	3MHz (B12) + 10MHz (B2)	1.4MHz (B4) + 5MHz (B12)
5MHz (B5) + 15MHz (B2)	10MHz (B4) + 5MHz (B5)	5MHz (B5) + 15MHz (B4)	5MHz (B2) + 10MHz (B12)	3MHz (B12) + 15MHz (B2)	1.4MHz (B4) + 10MHz (B12)
5MHz (B5) + 20MHz (B2)	10MHz (B4) + 10MHz (B5)	5MHz (B5) + 20MHz (B4)	10MHz (B2) + 3MHz (B12)	3MHz (B12) + 20MHz (B2)	3MHz (B4) + 3MHz (B12)
10MHz (B5) + 5MHz (B2)	15MHz (B4) + 5MHz (B5)	10MHz (B5) + 5MHz (B4)	10MHz (B2) + 5MHz (B12)	5MHz (B12) + 5MHz (B2)	3MHz (B4) + 5MHz (B12)
10MHz (B5) + 10MHz (B2)	15MHz (B4) + 10MHz (B5)	10MHz (B5) + 10MHz (B4)	10MHz (B2) + 10MHz (B12)	5MHz (B12) + 10MHz (B2)	3MHz (B4) + 10MHz (B12)
10MHz (B5) + 15MHz (B2)	20MHz (B4) + 5MHz (B5)	10MHz (B5) + 15MHz (B4)	15MHz (B2) + 3MHz (B12)	5MHz (B12) + 15MHz (B2)	5MHz (B4) +3MHz (B12)
10MHz (B5) + 20MHz (B2)	20MHz (B2) + 10MHz (B5)	10MHz (B5) + 20MHz (B4)	15MHz (B2) + 5MHz (B12)	5MHz (B12) + 20MHz (B2)	5MHz (B4) + 5MHz (B12)
			15MHz (B2) + 10MHz (B12)	10MHz (B12) + 5MHz (B2)	5MHz (B4) + 10MHz (B12)
			20MHz (B2) + 3MHz (B12)	10MHz (B12) + 10MHz (B2)	10MHz (B4) + 3MHz (B12)
			20MHz (B2) + 5MHz (B12)	10MHz (B12) + 15MHz (B2)	10MHz (B4) + 5MHz (B12)
			20MHz (B2) + 10MHz (B12)	10MHz (B12) + 20MHz (B2)	10MHz (B4) + 10MHz (B12)
B2 (PCC) + B30 (SCC)	B30 (PCC) + B2 (SCC)	B4 (PCC) + B30 (SCC)	B30 (PCC) + B4 (SCC)	B5 (PCC) + B30 (SCC)	B30 (PCC) + B5 (SCC)
5MHz (B2) + 5MHz (B30)	5MHz (B30) + 5MHz (B2)	5MHz (B4) + 5MHz (B30)	5MHz (B30) + 5MHz (B4)	5MHz (B5) + 5MHz (B30)	5MHz (B30) + 5MHz (B5)
5MHz (B2) + 10MHz (B30)	5MHz (B30) + 10MHz (B2)	5MHz (B4) + 10MHz (B30)	5MHz (B30) + 10MHz (B4)	5MHz (B5) + 10MHz (B30)	5MHz (B30) + 10MHz (B5)
10MHz (B2) + 5MHz (B30)	5MHz (B30) + 15MHz (B2)	10MHz (B4) + 5MHz (B30)	5MHz (B30) + 15MHz (B4)	10MHz (B5) + 5MHz (B30)	10MHz (B30) + 5MHz (B5)
10MHz (B2) + 10MHz (B30)	5MHz (B30) + 20MHz (B2)	10MHz (B4) + 10MHz (B30)	5MHz (B30) + 20MHz (B4)	10MHz (B5) + 10MHz (B30)	10MHz (B30) + 10MHz (B5)
15MHz (B2) + 5MHz (B30)	10MHz (B30) + 5MHz (B2)	15MHz (B4) + 5MHz (B30)	10MHz (B30) + 5MHz (B4)		
15MHz (B2) + 10MHz (B30)	10MHz (B30) + 10MHz (B2)	15MHz (B4) + 10MHz (B30)	10MHz (B30) + 10MHz (B4)		
20MHz (B2) + 5MHz (B30)	10MHz (B30) + 15MHz (B2)	20MHz (B4) + 5MHz (B30)	10MHz (B30) + 15MHz (B4)		
20MHz (B2) + 10MHz (B30)	10MHz (B30) + 20MHz (B2)	20MHz (B4) + 10MHz (B30)	10MHz (B30) + 20MHz (B4)		
B12 (PCC) + B30 (SCC)	B30 (PCC) + B12 (SCC)	B30 (PCC) + B29 (SCC)			
5MHz (B12) + 5MHz (B30)	5MHz (B30) + 5MHz (B12)	5MHz (B30) + 5MHz (B29)			
5MHz (B12) + 10MHz (B30)	5MHz (B30) + 10MHz (B12)	5MHz (B30) + 10MHz (B29)			
10MHz (B12) + 5MHz (B30)	10MHz (B30) + 5MHz (B12)	10MHz (B30) + 5MHz (B29)			
10MHz (B12) + 10MHz (B30)	10MHz (B30) + 10MHz (B12)	10MHz (B30) + 10MHz (B29)			

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 11 of 108	

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 12 of 108

4

DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 13 of 108

5

DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMG920A	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 14 of 108

6

TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 15 of 108




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04_v01. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

FCC ID: A3LSMG920A	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 16 of 108

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

There is power reduction for UMTS Band 5/2, and LTE Band 12/17/5/4/2/30 in hotspot scenarios. There is no power reduction for GSM/GPRS/EDGE 850/1900. The reduced powers were confirmed via conducted power measurements at the RF port (See Section 9). Detailed description of the hotspot power reduction mechanism is included in the operational description

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 17 of 108

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 18 of 108

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03 "3G SAR Measurement Procedures."

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 19 of 108

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r03 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 20 of 108	

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r03:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 Downlink Carrier Aggregation

LTE Carrier Aggregation (CA) measurements are made in accordance to 3GPP TS 36.521-1 V10.4.0 (2012-12). The RRC connection is only handled by one cell, the Primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds the Secondary component carrier (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. Additional output powers are measured using two carriers in the downlink for the release 8 configurations with the highest output power among all channels, RB configurations and bandwidths for each uplink band. Per FCC KDB Publication 941225 D05A v01r01, no SAR measurements are required when the average output power with downlink carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink carrier aggregation inactive.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 21 of 108

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01 DR02-41929 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, SAR must be considered for these channels. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz are grouped with the 5.8 GHz channels in U-NII-3 band or §15.247 5.8 GHz band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are disabled, each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 22 of 108

extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. If the average RF output powers of the highest identical transmission modes are within 0.25 dB of each other, mid channel of the transmission mode with highest average RF output power is the initial test channel. Otherwise, the channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 23 of 108

channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6).

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

8.6.9 MIMO SAR considerations

Per KDB 248227 D01 DR02-41929, the simultaneous SAR provisions in KDB Publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 24 of 108	

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power				
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	32.81	32.98	32.16	26.86	25.85
	190	32.96	33.00	32.25	27.19	25.97
	251	32.87	32.90	32.15	27.18	25.92
GSM 1900	512	29.98	29.97	26.60	25.91	24.89
	661	29.97	29.94	26.64	25.83	24.84
	810	30.00	30.00	26.84	26.23	25.00
		Calculated Maximum Frame-Averaged Output Power				
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	23.78	23.95	26.14	17.83	19.83
	190	23.93	23.97	26.23	18.16	19.95
	251	23.84	23.87	26.13	18.15	19.90
GSM 1900	512	20.95	20.94	20.58	16.88	18.87
	661	20.94	20.91	20.62	16.80	18.82
	810	20.97	20.97	20.82	17.20	18.98
GSM 850	Frame	23.47	23.47	25.98	17.97	19.48
GSM 1900	Avg.Targets:	20.47	20.47	21.48	16.97	18.48

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 10
EDGE Multislot class: 10
DTM Multislot Class: N/A




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 25 of 108	

9.2 UMTS Conducted Powers

9.2.1 Maximum Conducted Powers – Representing Hotspot Mode Inactive

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.14	24.09	24.03	23.48	23.46	23.42	-
99		12.2 kbps AMR	24.10	24.05	24.01	23.47	23.42	23.41	-
6	HSDPA	Subtest 1	22.82	22.77	22.56	22.30	22.13	22.40	0
6		Subtest 2	22.77	22.75	22.54	22.29	22.09	22.38	0
6		Subtest 3	22.80	22.79	22.53	22.28	22.11	22.40	0.5
6		Subtest 4	22.81	22.77	22.52	22.26	22.11	22.39	0.5
6	HSUPA	Subtest 1	23.28	23.46	23.48	22.12	22.56	22.76	0
6		Subtest 2	21.33	21.41	21.48	21.23	20.93	21.04	2
6		Subtest 3	23.27	23.38	23.43	22.70	22.42	22.65	1
6		Subtest 4	21.30	21.36	21.45	21.16	20.81	20.91	2
6		Subtest 5	23.31	23.44	23.50	22.85	22.49	22.69	0

9.2.2 Reduced Conducted Powers- Representing Hotspot Mode Active

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	23.21	23.13	23.03	21.16	21.15	21.18	-
99		12.2 kbps AMR	23.20	23.12	23.03	21.12	21.10	21.16	-
6	HSDPA	Subtest 1	22.60	22.72	22.38	21.39	21.19	21.17	0
6		Subtest 2	22.54	22.66	22.34	21.35	21.18	21.20	0
6		Subtest 3	21.66	21.77	21.44	21.37	21.30	21.26	0.5
6		Subtest 4	21.60	21.76	21.40	21.31	21.32	21.28	0.5
6	HSUPA	Subtest 1	22.20	22.32	22.00	20.75	20.52	20.54	0
6		Subtest 2	20.04	19.95	19.85	20.53	20.34	20.43	2
6		Subtest 3	21.05	20.95	21.87	20.68	20.46	20.49	1
6		Subtest 4	20.13	20.01	19.81	20.66	20.48	20.46	2
6		Subtest 5	23.07	23.31	22.88	21.35	21.18	21.19	0

This device does not support DC-HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 26 of 108

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

Table 9-1

LTE Band 12 Maximum Conducted Powers - 10 MHz Bandwidth - Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	707.5	23095	10	QPSK	1	0	23.97	0	0
	707.5	23095	10	QPSK	1	25	23.93	0	0
	707.5	23095	10	QPSK	1	49	23.76	0	0
	707.5	23095	10	QPSK	25	0	22.47	0-1	1
	707.5	23095	10	QPSK	25	12	22.56	0-1	1
	707.5	23095	10	QPSK	25	25	22.51	0-1	1
	707.5	23095	10	QPSK	50	0	22.47	0-1	1
	707.5	23095	10	16QAM	1	0	22.74	0-1	1
	707.5	23095	10	16QAM	1	25	22.69	0-1	1
	707.5	23095	10	16QAM	1	49	22.65	0-1	1
	707.5	23095	10	16QAM	25	0	21.54	0-2	2
	707.5	23095	10	16QAM	25	12	21.61	0-2	2
	707.5	23095	10	16QAM	25	25	21.57	0-2	2
	707.5	23095	10	16QAM	50	0	21.55	0-2	2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 27 of 108

Table 9-2

LTE Band 12 Maximum Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	701.5	23035	5	QPSK	1	0	24.00	0	0
	701.5	23035	5	QPSK	1	12	23.92	0	0
	701.5	23035	5	QPSK	1	24	23.86	0	0
	701.5	23035	5	QPSK	12	0	22.60	0-1	1
	701.5	23035	5	QPSK	12	6	22.53	0-1	1
	701.5	23035	5	QPSK	12	13	22.55	0-1	1
	701.5	23035	5	QPSK	25	0	22.64	0-1	1
	701.5	23035	5	16-QAM	1	0	22.88	0-1	1
	701.5	23035	5	16-QAM	1	12	22.77	0-1	1
	701.5	23035	5	16-QAM	1	24	22.79	0-1	1
	701.5	23035	5	16-QAM	12	0	21.55	0-2	2
	701.5	23035	5	16-QAM	12	6	21.50	0-2	2
Mid	701.5	23035	5	16-QAM	12	13	21.49	0-2	2
	701.5	23035	5	16-QAM	25	0	21.57	0-2	2
	707.5	23095	5	QPSK	1	0	23.73	0	0
	707.5	23095	5	QPSK	1	12	23.66	0	0
	707.5	23095	5	QPSK	1	24	23.71	0	0
	707.5	23095	5	QPSK	12	0	22.46	0-1	1
	707.5	23095	5	QPSK	12	6	22.53	0-1	1
	707.5	23095	5	QPSK	12	13	22.57	0-1	1
	707.5	23095	5	QPSK	25	0	22.53	0-1	1
	707.5	23095	5	16-QAM	1	0	22.81	0-1	1
	707.5	23095	5	16-QAM	1	12	22.69	0-1	1
	707.5	23095	5	16-QAM	1	24	22.71	0-1	1
	707.5	23095	5	16-QAM	12	0	21.53	0-2	2
	707.5	23095	5	16-QAM	12	6	21.45	0-2	2
High	707.5	23095	5	16-QAM	12	13	21.51	0-2	2
	707.5	23095	5	16-QAM	25	0	21.53	0-2	2
	713.5	23155	5	QPSK	1	0	23.81	0	0
	713.5	23155	5	QPSK	1	12	23.75	0	0
	713.5	23155	5	QPSK	1	24	23.81	0	0
	713.5	23155	5	QPSK	12	0	22.51	0-1	1
	713.5	23155	5	QPSK	12	6	22.49	0-1	1
	713.5	23155	5	QPSK	12	13	22.48	0-1	1
	713.5	23155	5	QPSK	25	0	22.38	0-1	1
	713.5	23155	5	16-QAM	1	0	22.91	0-1	1
	713.5	23155	5	16-QAM	1	12	22.78	0-1	1
	713.5	23155	5	16-QAM	1	24	23.00	0-1	1
	713.5	23155	5	16-QAM	12	0	21.31	0-2	2
	713.5	23155	5	16-QAM	12	6	21.33	0-2	2
	713.5	23155	5	16-QAM	12	13	21.32	0-2	2
	713.5	23155	5	16-QAM	25	0	21.37	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 28 of 108

Table 9-3

LTE Band 12 Maximum Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	700.5	23025	3	QPSK	1	0	24.00	0	0
	700.5	23025	3	QPSK	1	7	23.87	0	0
	700.5	23025	3	QPSK	1	14	23.85	0	0
	700.5	23025	3	QPSK	8	0	22.57	0-1	1
	700.5	23025	3	QPSK	8	4	22.57	0-1	1
	700.5	23025	3	QPSK	8	7	22.52	0-1	1
	700.5	23025	3	QPSK	15	0	22.58	0-1	1
	700.5	23025	3	16-QAM	1	0	22.84	0-1	1
	700.5	23025	3	16-QAM	1	7	22.93	0-1	1
	700.5	23025	3	16-QAM	1	14	22.82	0-1	1
	700.5	23025	3	16-QAM	8	0	21.41	0-2	2
	700.5	23025	3	16-QAM	8	4	21.33	0-2	2
Mid	700.5	23025	3	16-QAM	8	7	21.30	0-2	2
	700.5	23025	3	16-QAM	15	0	21.47	0-2	2
	707.5	23095	3	QPSK	1	0	24.00	0	0
	707.5	23095	3	QPSK	1	7	23.84	0	0
	707.5	23095	3	QPSK	1	14	23.92	0	0
	707.5	23095	3	QPSK	8	0	22.50	0-1	1
	707.5	23095	3	QPSK	8	4	22.51	0-1	1
	707.5	23095	3	QPSK	8	7	22.57	0-1	1
	707.5	23095	3	QPSK	15	0	22.52	0-1	1
	707.5	23095	3	16-QAM	1	0	22.74	0-1	1
	707.5	23095	3	16-QAM	1	7	22.68	0-1	1
	707.5	23095	3	16-QAM	1	14	22.81	0-1	1
	707.5	23095	3	16-QAM	8	0	21.43	0-2	2
	707.5	23095	3	16-QAM	8	4	21.41	0-2	2
High	707.5	23095	3	16-QAM	8	7	21.47	0-2	2
	707.5	23095	3	16-QAM	15	0	21.51	0-2	2
	714.5	23165	3	QPSK	1	0	23.80	0	0
	714.5	23165	3	QPSK	1	7	23.79	0	0
	714.5	23165	3	QPSK	1	14	23.84	0	0
	714.5	23165	3	QPSK	8	0	22.38	0-1	1
	714.5	23165	3	QPSK	8	4	22.39	0-1	1
	714.5	23165	3	QPSK	8	7	22.37	0-1	1
	714.5	23165	3	QPSK	15	0	22.34	0-1	1
	714.5	23165	3	16-QAM	1	0	22.88	0-1	1
	714.5	23165	3	16-QAM	1	7	22.74	0-1	1
	714.5	23165	3	16-QAM	1	14	22.72	0-1	1
	714.5	23165	3	16-QAM	8	0	21.23	0-2	2
	714.5	23165	3	16-QAM	8	4	21.16	0-2	2
	714.5	23165	3	16-QAM	8	7	21.16	0-2	2
	714.5	23165	3	16-QAM	15	0	21.29	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 29 of 108

Table 9-4
LTE Band 12 Maximum Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	699.7	23017	1.4	QPSK	1	0	23.91	0	0
	699.7	23017	1.4	QPSK	1	2	23.85	0	0
	699.7	23017	1.4	QPSK	1	5	23.87	0	0
	699.7	23017	1.4	QPSK	3	0	23.61	0	0
	699.7	23017	1.4	QPSK	3	2	23.59	0	0
	699.7	23017	1.4	QPSK	3	3	23.60	0	0
	699.7	23017	1.4	QPSK	6	0	22.44	0-1	1
	699.7	23017	1.4	16-QAM	1	0	23.00	0-1	1
	699.7	23017	1.4	16-QAM	1	2	22.87	0-1	1
	699.7	23017	1.4	16-QAM	1	5	22.92	0-1	1
	699.7	23017	1.4	16-QAM	3	0	22.43	0-1	1
	699.7	23017	1.4	16-QAM	3	2	22.43	0-1	1
	699.7	23017	1.4	16-QAM	3	3	22.41	0-1	1
Mid	699.7	23017	1.4	16-QAM	6	0	21.48	0-2	2
	707.5	23095	1.4	QPSK	1	0	23.95	0	0
	707.5	23095	1.4	QPSK	1	2	23.99	0	0
	707.5	23095	1.4	QPSK	1	5	24.00	0	0
	707.5	23095	1.4	QPSK	3	0	23.60	0	0
	707.5	23095	1.4	QPSK	3	2	23.71	0	0
	707.5	23095	1.4	QPSK	3	3	23.66	0	0
	707.5	23095	1.4	QPSK	6	0	22.46	0-1	1
	707.5	23095	1.4	16-QAM	1	0	22.78	0-1	1
	707.5	23095	1.4	16-QAM	1	2	22.74	0-1	1
	707.5	23095	1.4	16-QAM	1	5	22.82	0-1	1
	707.5	23095	1.4	16-QAM	3	0	22.44	0-1	1
	707.5	23095	1.4	16-QAM	3	2	22.47	0-1	1
	707.5	23095	1.4	16-QAM	3	3	22.46	0-1	1
High	707.5	23095	1.4	16-QAM	6	0	21.56	0-2	2
	715.3	23173	1.4	QPSK	1	0	23.85	0	0
	715.3	23173	1.4	QPSK	1	2	23.82	0	0
	715.3	23173	1.4	QPSK	1	5	23.83	0	0
	715.3	23173	1.4	QPSK	3	0	23.44	0	0
	715.3	23173	1.4	QPSK	3	2	23.52	0	0
	715.3	23173	1.4	QPSK	3	3	23.57	0	0
	715.3	23173	1.4	QPSK	6	0	22.41	0-1	1
	715.3	23173	1.4	16-QAM	1	0	22.96	0-1	1
	715.3	23173	1.4	16-QAM	1	2	22.79	0-1	1
	715.3	23173	1.4	16-QAM	1	5	22.84	0-1	1
	715.3	23173	1.4	16-QAM	3	0	22.46	0-1	1
	715.3	23173	1.4	16-QAM	3	2	22.42	0-1	1
	715.3	23173	1.4	16-QAM	3	3	22.39	0-1	1
	715.3	23173	1.4	16-QAM	6	0	21.35	0-2	2

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 30 of 108	

Table 9-5

LTE Band 12 Reduced Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	707.5	23095	10	QPSK	1	0	23.41	0	0
	707.5	23095	10	QPSK	1	25	23.45	0	0
	707.5	23095	10	QPSK	1	49	23.37	0	0
	707.5	23095	10	QPSK	25	0	23.07	0-1	0
	707.5	23095	10	QPSK	25	12	23.15	0-1	0
	707.5	23095	10	QPSK	25	25	23.14	0-1	0
	707.5	23095	10	QPSK	50	0	23.04	0-1	0
	707.5	23095	10	16QAM	1	0	23.44	0-1	0
	707.5	23095	10	16QAM	1	25	23.42	0-1	0
	707.5	23095	10	16QAM	1	49	23.45	0-1	0
	707.5	23095	10	16QAM	25	0	22.09	0-2	1
	707.5	23095	10	16QAM	25	12	22.09	0-2	1
	707.5	23095	10	16QAM	25	25	22.10	0-2	1
	707.5	23095	10	16QAM	50	0	21.94	0-2	1

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 31 of 108

Table 9-6

LTE Band 12 Reduced Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	701.5	23035	5	QPSK	1	0	23.32	0	0
	701.5	23035	5	QPSK	1	12	23.24	0	0
	701.5	23035	5	QPSK	1	24	23.21	0	0
	701.5	23035	5	QPSK	12	0	23.27	0-1	0
	701.5	23035	5	QPSK	12	6	23.22	0-1	0
	701.5	23035	5	QPSK	12	13	23.15	0-1	0
	701.5	23035	5	QPSK	25	0	23.25	0-1	0
	701.5	23035	5	16-QAM	1	0	23.44	0-1	0
	701.5	23035	5	16-QAM	1	12	23.49	0-1	0
	701.5	23035	5	16-QAM	1	24	23.35	0-1	0
	701.5	23035	5	16-QAM	12	0	22.20	0-2	1
	701.5	23035	5	16-QAM	12	6	22.09	0-2	1
Mid	701.5	23035	5	16-QAM	12	13	22.05	0-2	1
	701.5	23035	5	16-QAM	25	0	22.07	0-2	1
	707.5	23095	5	QPSK	1	0	23.47	0	0
	707.5	23095	5	QPSK	1	12	23.44	0	0
	707.5	23095	5	QPSK	1	24	23.42	0	0
	707.5	23095	5	QPSK	12	0	23.17	0-1	0
	707.5	23095	5	QPSK	12	6	23.22	0-1	0
	707.5	23095	5	QPSK	12	13	23.23	0-1	0
	707.5	23095	5	QPSK	25	0	23.19	0-1	0
	707.5	23095	5	16-QAM	1	0	23.45	0-1	0
	707.5	23095	5	16-QAM	1	12	23.35	0-1	0
	707.5	23095	5	16-QAM	1	24	23.41	0-1	0
	707.5	23095	5	16-QAM	12	0	22.08	0-2	1
	707.5	23095	5	16-QAM	12	6	22.05	0-2	1
High	707.5	23095	5	16-QAM	12	13	22.01	0-2	1
	707.5	23095	5	16-QAM	25	0	21.97	0-2	1
	713.5	23155	5	QPSK	1	0	23.40	0	0
	713.5	23155	5	QPSK	1	12	23.31	0	0
	713.5	23155	5	QPSK	1	24	23.36	0	0
	713.5	23155	5	QPSK	12	0	23.11	0-1	0
	713.5	23155	5	QPSK	12	6	23.03	0-1	0
	713.5	23155	5	QPSK	12	13	23.04	0-1	0
	713.5	23155	5	QPSK	25	0	23.08	0-1	0
	713.5	23155	5	16-QAM	1	0	23.02	0-1	0
	713.5	23155	5	16-QAM	1	12	22.96	0-1	0
	713.5	23155	5	16-QAM	1	24	23.06	0-1	0
	713.5	23155	5	16-QAM	12	0	21.91	0-2	1
	713.5	23155	5	16-QAM	12	6	21.83	0-2	1
	713.5	23155	5	16-QAM	12	13	21.84	0-2	1
	713.5	23155	5	16-QAM	25	0	21.93	0-2	1

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 32 of 108

Table 9-7

LTE Band 12 Reduced Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	700.5	23025	3	QPSK	1	0	23.00	0	0
	700.5	23025	3	QPSK	1	7	22.94	0	0
	700.5	23025	3	QPSK	1	14	23.10	0	0
	700.5	23025	3	QPSK	8	0	23.02	0-1	0
	700.5	23025	3	QPSK	8	4	23.03	0-1	0
	700.5	23025	3	QPSK	8	7	23.05	0-1	0
	700.5	23025	3	QPSK	15	0	22.82	0-1	0
	700.5	23025	3	16-QAM	1	0	22.86	0-1	0
	700.5	23025	3	16-QAM	1	7	22.89	0-1	0
	700.5	23025	3	16-QAM	1	14	22.95	0-1	0
	700.5	23025	3	16-QAM	8	0	22.03	0-2	1
	700.5	23025	3	16-QAM	8	4	22.01	0-2	1
Mid	700.5	23025	3	16-QAM	8	7	22.05	0-2	1
	700.5	23025	3	16-QAM	15	0	22.00	0-2	1
	707.5	23095	3	QPSK	1	0	23.06	0	0
	707.5	23095	3	QPSK	1	7	23.11	0	0
	707.5	23095	3	QPSK	1	14	23.02	0	0
	707.5	23095	3	QPSK	8	0	23.01	0-1	0
	707.5	23095	3	QPSK	8	4	22.94	0-1	0
	707.5	23095	3	QPSK	8	7	22.96	0-1	0
	707.5	23095	3	QPSK	15	0	22.95	0-1	0
	707.5	23095	3	16-QAM	1	0	22.99	0-1	0
	707.5	23095	3	16-QAM	1	7	23.01	0-1	0
	707.5	23095	3	16-QAM	1	14	22.94	0-1	0
	707.5	23095	3	16-QAM	8	0	21.95	0-2	1
	707.5	23095	3	16-QAM	8	4	21.86	0-2	1
High	707.5	23095	3	16-QAM	8	7	21.87	0-2	1
	707.5	23095	3	16-QAM	15	0	21.90	0-2	1
	714.5	23165	3	QPSK	1	0	22.95	0	0
	714.5	23165	3	QPSK	1	7	22.99	0	0
	714.5	23165	3	QPSK	1	14	23.06	0	0
	714.5	23165	3	QPSK	8	0	23.01	0-1	0
	714.5	23165	3	QPSK	8	4	23.00	0-1	0
	714.5	23165	3	QPSK	8	7	23.00	0-1	0
	714.5	23165	3	QPSK	15	0	23.01	0-1	0
	714.5	23165	3	16-QAM	1	0	22.94	0-1	0
	714.5	23165	3	16-QAM	1	7	22.97	0-1	0
	714.5	23165	3	16-QAM	1	14	22.98	0-1	0
	714.5	23165	3	16-QAM	8	0	21.69	0-2	1
	714.5	23165	3	16-QAM	8	4	22.03	0-2	1
	714.5	23165	3	16-QAM	8	7	22.02	0-2	1
	714.5	23165	3	16-QAM	15	0	22.00	0-2	1

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 33 of 108

Table 9-8
LTE Band 12 Reduced Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	699.7	23017	1.4	QPSK	1	0	23.01	0	0
	699.7	23017	1.4	QPSK	1	2	22.95	0	0
	699.7	23017	1.4	QPSK	1	5	23.16	0	0
	699.7	23017	1.4	QPSK	3	0	23.15	0	0
	699.7	23017	1.4	QPSK	3	2	23.16	0	0
	699.7	23017	1.4	QPSK	3	3	23.00	0	0
	699.7	23017	1.4	QPSK	6	0	23.05	0-1	0
	699.7	23017	1.4	16-QAM	1	0	23.01	0-1	0
	699.7	23017	1.4	16-QAM	1	2	22.95	0-1	0
	699.7	23017	1.4	16-QAM	1	5	22.81	0-1	0
	699.7	23017	1.4	16-QAM	3	0	22.86	0-1	0
	699.7	23017	1.4	16-QAM	3	2	22.83	0-1	0
	699.7	23017	1.4	16-QAM	3	3	22.89	0-1	0
Mid	699.7	23017	1.4	16-QAM	6	0	21.99	0-2	1
	707.5	23095	1.4	QPSK	1	0	23.00	0	0
	707.5	23095	1.4	QPSK	1	2	23.11	0	0
	707.5	23095	1.4	QPSK	1	5	23.12	0	0
	707.5	23095	1.4	QPSK	3	0	22.93	0	0
	707.5	23095	1.4	QPSK	3	2	22.79	0	0
	707.5	23095	1.4	QPSK	3	3	22.85	0	0
	707.5	23095	1.4	QPSK	6	0	22.99	0-1	0
	707.5	23095	1.4	16-QAM	1	0	22.94	0-1	0
	707.5	23095	1.4	16-QAM	1	2	23.15	0-1	0
	707.5	23095	1.4	16-QAM	1	5	23.10	0-1	0
	707.5	23095	1.4	16-QAM	3	0	22.95	0-1	0
	707.5	23095	1.4	16-QAM	3	2	23.00	0-1	0
High	707.5	23095	1.4	16-QAM	3	3	23.01	0-1	0
	707.5	23095	1.4	16-QAM	6	0	22.03	0-2	1
	715.3	23173	1.4	QPSK	1	0	23.06	0	0
	715.3	23173	1.4	QPSK	1	2	23.05	0	0
	715.3	23173	1.4	QPSK	1	5	23.05	0	0
	715.3	23173	1.4	QPSK	3	0	23.01	0	0
	715.3	23173	1.4	QPSK	3	2	22.95	0	0
	715.3	23173	1.4	QPSK	3	3	23.01	0	0
	715.3	23173	1.4	QPSK	6	0	22.97	0-1	0
	715.3	23173	1.4	16-QAM	1	0	22.98	0-1	0
	715.3	23173	1.4	16-QAM	1	2	22.99	0-1	0
	715.3	23173	1.4	16-QAM	1	5	22.90	0-1	0
	715.3	23173	1.4	16-QAM	3	0	23.10	0-1	0
	715.3	23173	1.4	16-QAM	3	2	23.01	0-1	0
	715.3	23173	1.4	16-QAM	3	3	23.15	0-1	0
	715.3	23173	1.4	16-QAM	6	0	22.03	0-2	1

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 34 of 108	

9.3.2

LTE Band 5 (Cell)

Table 9-9

LTE Band 5 (Cell) Maximum Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	24.47	0	0
	836.5	20525	10	QPSK	1	25	24.38	0	0
	836.5	20525	10	QPSK	1	49	24.28	0	0
	836.5	20525	10	QPSK	25	0	23.07	0-1	1
	836.5	20525	10	QPSK	25	12	23.01	0-1	1
	836.5	20525	10	QPSK	25	25	22.97	0-1	1
	836.5	20525	10	QPSK	50	0	23.02	0-1	1
	836.5	20525	10	16QAM	1	0	23.17	0-1	1
	836.5	20525	10	16QAM	1	25	23.16	0-1	1
	836.5	20525	10	16QAM	1	49	23.08	0-1	1
	836.5	20525	10	16QAM	25	0	21.96	0-2	2
	836.5	20525	10	16QAM	25	12	21.98	0-2	2
	836.5	20525	10	16QAM	25	25	21.86	0-2	2
	836.5	20525	10	16QAM	50	0	21.95	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 35 of 108

Table 9-10

LTE Band 5 (Cell) Maximum Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	24.25	0	0
	826.5	20425	5	QPSK	1	12	24.27	0	0
	826.5	20425	5	QPSK	1	24	24.27	0	0
	826.5	20425	5	QPSK	12	0	22.85	0-1	1
	826.5	20425	5	QPSK	12	6	22.89	0-1	1
	826.5	20425	5	QPSK	12	13	22.92	0-1	1
	826.5	20425	5	QPSK	25	0	22.83	0-1	1
	826.5	20425	5	16-QAM	1	0	23.27	0-1	1
	826.5	20425	5	16-QAM	1	12	23.29	0-1	1
	826.5	20425	5	16-QAM	1	24	23.31	0-1	1
	826.5	20425	5	16-QAM	12	0	21.99	0-2	2
	826.5	20425	5	16-QAM	12	6	21.92	0-2	2
Mid	826.5	20425	5	16-QAM	12	13	21.85	0-2	2
	826.5	20425	5	16-QAM	25	0	21.77	0-2	2
	836.5	20525	5	QPSK	1	0	24.44	0	0
	836.5	20525	5	QPSK	1	12	24.34	0	0
	836.5	20525	5	QPSK	1	24	24.39	0	0
	836.5	20525	5	QPSK	12	0	23.09	0-1	1
	836.5	20525	5	QPSK	12	6	23.02	0-1	1
	836.5	20525	5	QPSK	12	13	22.94	0-1	1
	836.5	20525	5	QPSK	25	0	22.99	0-1	1
	836.5	20525	5	16-QAM	1	0	23.44	0-1	1
	836.5	20525	5	16-QAM	1	12	23.35	0-1	1
	836.5	20525	5	16-QAM	1	24	23.46	0-1	1
High	836.5	20525	5	16-QAM	12	0	21.87	0-2	2
	836.5	20525	5	16-QAM	12	6	21.78	0-2	2
	836.5	20525	5	16-QAM	12	13	21.76	0-2	2
	836.5	20525	5	16-QAM	25	0	21.82	0-2	2
	846.5	20625	5	QPSK	1	0	24.26	0	0
	846.5	20625	5	QPSK	1	12	24.27	0	0
	846.5	20625	5	QPSK	1	24	24.13	0	0
	846.5	20625	5	QPSK	12	0	23.02	0-1	1
	846.5	20625	5	QPSK	12	6	22.94	0-1	1
	846.5	20625	5	QPSK	12	13	22.93	0-1	1
	846.5	20625	5	QPSK	25	0	22.97	0-1	1
	846.5	20625	5	16-QAM	1	0	23.49	0-1	1
	846.5	20625	5	16-QAM	1	12	23.45	0-1	1
	846.5	20625	5	16-QAM	1	24	23.32	0-1	1
	846.5	20625	5	16-QAM	12	0	21.92	0-2	2
	846.5	20625	5	16-QAM	12	6	21.90	0-2	2
	846.5	20625	5	16-QAM	12	13	21.77	0-2	2
	846.5	20625	5	16-QAM	25	0	21.81	0-2	2

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 36 of 108

Table 9-11

LTE Band 5 (Cell) Maximum Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	825.5	20415	3	QPSK	1	0	24.08	0	0
	825.5	20415	3	QPSK	1	7	24.00	0	0
	825.5	20415	3	QPSK	1	14	24.07	0	0
	825.5	20415	3	QPSK	8	0	22.63	0-1	1
	825.5	20415	3	QPSK	8	4	22.68	0-1	1
	825.5	20415	3	QPSK	8	7	22.70	0-1	1
	825.5	20415	3	QPSK	15	0	22.66	0-1	1
	825.5	20415	3	16-QAM	1	0	22.94	0-1	1
	825.5	20415	3	16-QAM	1	7	23.16	0-1	1
	825.5	20415	3	16-QAM	1	14	23.27	0-1	1
	825.5	20415	3	16-QAM	8	0	21.56	0-2	2
	825.5	20415	3	16-QAM	8	4	21.50	0-2	2
Mid	825.5	20415	3	16-QAM	8	7	21.53	0-2	2
	825.5	20415	3	16-QAM	15	0	21.58	0-2	2
	836.5	20525	3	QPSK	1	0	24.22	0	0
	836.5	20525	3	QPSK	1	7	24.14	0	0
	836.5	20525	3	QPSK	1	14	24.19	0	0
	836.5	20525	3	QPSK	8	0	22.86	0-1	1
	836.5	20525	3	QPSK	8	4	22.82	0-1	1
	836.5	20525	3	QPSK	8	7	22.80	0-1	1
	836.5	20525	3	QPSK	15	0	22.81	0-1	1
	836.5	20525	3	16-QAM	1	0	23.48	0-1	1
	836.5	20525	3	16-QAM	1	7	23.40	0-1	1
	836.5	20525	3	16-QAM	1	14	23.44	0-1	1
High	836.5	20525	3	16-QAM	8	0	21.76	0-2	2
	836.5	20525	3	16-QAM	8	4	21.68	0-2	2
	836.5	20525	3	16-QAM	8	7	21.65	0-2	2
	836.5	20525	3	16-QAM	15	0	21.67	0-2	2
	847.5	20635	3	QPSK	1	0	24.24	0	0
	847.5	20635	3	QPSK	1	7	24.16	0	0
	847.5	20635	3	QPSK	1	14	24.13	0	0
	847.5	20635	3	QPSK	8	0	22.74	0-1	1
	847.5	20635	3	QPSK	8	4	22.65	0-1	1
	847.5	20635	3	QPSK	8	7	22.62	0-1	1
	847.5	20635	3	QPSK	15	0	22.75	0-1	1
	847.5	20635	3	16-QAM	1	0	23.04	0-1	1
	847.5	20635	3	16-QAM	1	7	22.89	0-1	1
	847.5	20635	3	16-QAM	1	14	22.93	0-1	1
	847.5	20635	3	16-QAM	8	0	21.65	0-2	2
	847.5	20635	3	16-QAM	8	4	21.55	0-2	2
	847.5	20635	3	16-QAM	8	7	21.55	0-2	2
	847.5	20635	3	16-QAM	15	0	21.62	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 37 of 108

Table 9-12

LTE Band 5 (Cell) Maximum Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	24.15	0	0
	824.7	20407	1.4	QPSK	1	2	24.14	0	0
	824.7	20407	1.4	QPSK	1	5	24.18	0	0
	824.7	20407	1.4	QPSK	3	0	23.86	0	0
	824.7	20407	1.4	QPSK	3	2	23.93	0	0
	824.7	20407	1.4	QPSK	3	3	23.89	0	0
	824.7	20407	1.4	QPSK	6	0	22.79	0-1	1
	824.7	20407	1.4	16-QAM	1	0	23.18	0-1	1
	824.7	20407	1.4	16-QAM	1	2	23.25	0-1	1
	824.7	20407	1.4	16-QAM	1	5	23.28	0-1	1
	824.7	20407	1.4	16-QAM	3	0	23.02	0-1	1
	824.7	20407	1.4	16-QAM	3	2	23.00	0-1	1
Mid	824.7	20407	1.4	16-QAM	3	3	22.96	0-1	1
	824.7	20407	1.4	16-QAM	6	0	21.68	0-2	2
	836.5	20525	1.4	QPSK	1	0	24.49	0	0
	836.5	20525	1.4	QPSK	1	2	24.42	0	0
	836.5	20525	1.4	QPSK	1	5	24.43	0	0
	836.5	20525	1.4	QPSK	3	0	24.17	0	0
	836.5	20525	1.4	QPSK	3	2	24.20	0	0
	836.5	20525	1.4	QPSK	3	3	24.17	0	0
	836.5	20525	1.4	QPSK	6	0	22.96	0-1	1
	836.5	20525	1.4	16-QAM	1	0	23.14	0-1	1
	836.5	20525	1.4	16-QAM	1	2	23.17	0-1	1
	836.5	20525	1.4	16-QAM	1	5	23.34	0-1	1
High	836.5	20525	1.4	16-QAM	3	0	22.87	0-1	1
	836.5	20525	1.4	16-QAM	3	2	22.87	0-1	1
	836.5	20525	1.4	16-QAM	3	3	22.83	0-1	1
	836.5	20525	1.4	16-QAM	6	0	21.95	0-2	2
	848.3	20643	1.4	QPSK	1	0	24.21	0	0
	848.3	20643	1.4	QPSK	1	2	24.09	0	0
	848.3	20643	1.4	QPSK	1	5	24.12	0	0
	848.3	20643	1.4	QPSK	3	0	24.10	0	0
	848.3	20643	1.4	QPSK	3	2	24.01	0	0
	848.3	20643	1.4	QPSK	3	3	24.02	0	0
	848.3	20643	1.4	QPSK	6	0	22.91	0-1	1
	848.3	20643	1.4	16-QAM	1	0	23.31	0-1	1
	848.3	20643	1.4	16-QAM	1	2	23.25	0-1	1
	848.3	20643	1.4	16-QAM	1	5	23.18	0-1	1
	848.3	20643	1.4	16-QAM	3	0	22.83	0-1	1
	848.3	20643	1.4	16-QAM	3	2	22.73	0-1	1
	848.3	20643	1.4	16-QAM	3	3	22.79	0-1	1
	848.3	20643	1.4	16-QAM	6	0	21.69	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 38 of 108

Table 9-13

LTE Band 5 (Cell) Reduced Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	23.33	0	0
	836.5	20525	10	QPSK	1	25	23.38	0	0
	836.5	20525	10	QPSK	1	49	23.20	0	0
	836.5	20525	10	QPSK	25	0	23.03	0-1	0
	836.5	20525	10	QPSK	25	12	23.02	0-1	0
	836.5	20525	10	QPSK	25	25	22.98	0-1	0
	836.5	20525	10	QPSK	50	0	23.02	0-1	0
	836.5	20525	10	16QAM	1	0	23.47	0-1	0
	836.5	20525	10	16QAM	1	25	23.39	0-1	0
	836.5	20525	10	16QAM	1	49	23.33	0-1	0
	836.5	20525	10	16QAM	25	0	21.98	0-2	1
	836.5	20525	10	16QAM	25	12	22.01	0-2	1
	836.5	20525	10	16QAM	25	25	21.90	0-2	1
	836.5	20525	10	16QAM	50	0	21.95	0-2	1

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 39 of 108

Table 9-14

LTE Band 5 (Cell) Reduced Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	23.05	0	0
	826.5	20425	5	QPSK	1	12	23.07	0	0
	826.5	20425	5	QPSK	1	24	23.08	0	0
	826.5	20425	5	QPSK	12	0	22.94	0-1	0
	826.5	20425	5	QPSK	12	6	23.02	0-1	0
	826.5	20425	5	QPSK	12	13	22.98	0-1	0
	826.5	20425	5	QPSK	25	0	22.90	0-1	0
	826.5	20425	5	16-QAM	1	0	23.19	0-1	0
	826.5	20425	5	16-QAM	1	12	23.18	0-1	0
	826.5	20425	5	16-QAM	1	24	23.21	0-1	0
	826.5	20425	5	16-QAM	12	0	21.81	0-2	1
	826.5	20425	5	16-QAM	12	6	21.83	0-2	1
Mid	826.5	20425	5	16-QAM	12	13	21.87	0-2	1
	826.5	20425	5	16-QAM	25	0	21.83	0-2	1
	836.5	20525	5	QPSK	1	0	23.40	0	0
	836.5	20525	5	QPSK	1	12	23.39	0	0
	836.5	20525	5	QPSK	1	24	23.47	0	0
	836.5	20525	5	QPSK	12	0	23.16	0-1	0
	836.5	20525	5	QPSK	12	6	23.11	0-1	0
	836.5	20525	5	QPSK	12	13	23.10	0-1	0
	836.5	20525	5	QPSK	25	0	23.15	0-1	0
	836.5	20525	5	16-QAM	1	0	23.50	0-1	0
	836.5	20525	5	16-QAM	1	12	23.46	0-1	0
	836.5	20525	5	16-QAM	1	24	23.45	0-1	0
High	836.5	20525	5	16-QAM	12	0	22.18	0-2	1
	836.5	20525	5	16-QAM	12	6	22.10	0-2	1
	836.5	20525	5	16-QAM	12	13	22.04	0-2	1
	836.5	20525	5	16-QAM	25	0	22.00	0-2	1
	846.5	20625	5	QPSK	1	0	23.43	0	0
	846.5	20625	5	QPSK	1	12	23.42	0	0
	846.5	20625	5	QPSK	1	24	23.22	0	0
	846.5	20625	5	QPSK	12	0	23.08	0-1	0
	846.5	20625	5	QPSK	12	6	23.05	0-1	0
	846.5	20625	5	QPSK	12	13	22.98	0-1	0
	846.5	20625	5	QPSK	25	0	23.07	0-1	0
	846.5	20625	5	16-QAM	1	0	23.50	0-1	0
	846.5	20625	5	16-QAM	1	12	23.42	0-1	0
	846.5	20625	5	16-QAM	1	24	23.42	0-1	0
	846.5	20625	5	16-QAM	12	0	21.96	0-2	1
	846.5	20625	5	16-QAM	12	6	21.90	0-2	1
	846.5	20625	5	16-QAM	12	13	21.86	0-2	1
	846.5	20625	5	16-QAM	25	0	21.95	0-2	1

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 40 of 108

Table 9-15

LTE Band 5 (Cell) Reduced Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	825.5	20415	3	QPSK	1	0	23.37	0	0
	825.5	20415	3	QPSK	1	7	23.30	0	0
	825.5	20415	3	QPSK	1	14	23.29	0	0
	825.5	20415	3	QPSK	8	0	22.90	0-1	0
	825.5	20415	3	QPSK	8	4	22.93	0-1	0
	825.5	20415	3	QPSK	8	7	22.96	0-1	0
	825.5	20415	3	QPSK	15	0	22.91	0-1	0
	825.5	20415	3	16-QAM	1	0	23.50	0-1	0
	825.5	20415	3	16-QAM	1	7	23.48	0-1	0
	825.5	20415	3	16-QAM	1	14	23.38	0-1	0
	825.5	20415	3	16-QAM	8	0	21.72	0-2	1
	825.5	20415	3	16-QAM	8	4	21.73	0-2	1
Mid	825.5	20415	3	16-QAM	8	7	21.77	0-2	1
	825.5	20415	3	16-QAM	15	0	21.85	0-2	1
	836.5	20525	3	QPSK	1	0	23.50	0	0
	836.5	20525	3	QPSK	1	7	23.42	0	0
	836.5	20525	3	QPSK	1	14	23.42	0	0
	836.5	20525	3	QPSK	8	0	23.18	0-1	0
	836.5	20525	3	QPSK	8	4	23.13	0-1	0
	836.5	20525	3	QPSK	8	7	23.10	0-1	0
	836.5	20525	3	QPSK	15	0	23.21	0-1	0
	836.5	20525	3	16-QAM	1	0	23.50	0-1	0
	836.5	20525	3	16-QAM	1	7	23.37	0-1	0
	836.5	20525	3	16-QAM	1	14	23.27	0-1	0
High	847.5	20635	3	16-QAM	8	0	22.03	0-2	1
	847.5	20635	3	16-QAM	8	4	22.09	0-2	1
	847.5	20635	3	16-QAM	8	7	22.08	0-2	1
	847.5	20635	3	16-QAM	15	0	21.95	0-2	1
	847.5	20635	3	QPSK	1	0	23.44	0	0
	847.5	20635	3	QPSK	1	7	23.31	0	0
	847.5	20635	3	QPSK	1	14	23.28	0	0
	847.5	20635	3	QPSK	8	0	23.03	0-1	0
	847.5	20635	3	QPSK	8	4	23.01	0-1	0
	847.5	20635	3	QPSK	8	7	22.98	0-1	0
	847.5	20635	3	QPSK	15	0	23.07	0-1	0
	847.5	20635	3	16-QAM	1	0	23.43	0-1	0
	847.5	20635	3	16-QAM	1	7	23.49	0-1	0
	847.5	20635	3	16-QAM	1	14	23.39	0-1	0
	847.5	20635	3	16-QAM	8	0	21.89	0-2	1
	847.5	20635	3	16-QAM	8	4	21.74	0-2	1
	847.5	20635	3	16-QAM	8	7	21.73	0-2	1
	847.5	20635	3	16-QAM	15	0	21.89	0-2	1

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 41 of 108

Table 9-16

LTE Band 5 (Cell) Reduced Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	23.19	0	0
	824.7	20407	1.4	QPSK	1	2	23.21	0	0
	824.7	20407	1.4	QPSK	1	5	23.13	0	0
	824.7	20407	1.4	QPSK	3	0	23.03	0	0
	824.7	20407	1.4	QPSK	3	2	22.98	0	0
	824.7	20407	1.4	QPSK	3	3	22.95	0	0
	824.7	20407	1.4	QPSK	6	0	22.97	0-1	0
	824.7	20407	1.4	16-QAM	1	0	23.30	0-1	0
	824.7	20407	1.4	16-QAM	1	2	23.27	0-1	0
	824.7	20407	1.4	16-QAM	1	5	23.43	0-1	0
	824.7	20407	1.4	16-QAM	3	0	23.03	0-1	0
	824.7	20407	1.4	16-QAM	3	2	23.04	0-1	0
Mid	824.7	20407	1.4	16-QAM	3	3	22.94	0-1	0
	824.7	20407	1.4	16-QAM	6	0	21.80	0-2	1
	836.5	20525	1.4	QPSK	1	0	23.36	0	0
	836.5	20525	1.4	QPSK	1	2	23.38	0	0
	836.5	20525	1.4	QPSK	1	5	23.39	0	0
	836.5	20525	1.4	QPSK	3	0	23.12	0	0
	836.5	20525	1.4	QPSK	3	2	23.16	0	0
	836.5	20525	1.4	QPSK	3	3	23.13	0	0
	836.5	20525	1.4	QPSK	6	0	23.14	0-1	0
	836.5	20525	1.4	16-QAM	1	0	23.06	0-1	0
	836.5	20525	1.4	16-QAM	1	2	23.03	0-1	0
	836.5	20525	1.4	16-QAM	1	5	23.04	0-1	0
High	836.5	20525	1.4	16-QAM	3	0	23.13	0-1	0
	836.5	20525	1.4	16-QAM	3	2	23.09	0-1	0
	836.5	20525	1.4	16-QAM	3	3	23.05	0-1	0
	836.5	20525	1.4	16-QAM	6	0	22.17	0-2	1
	848.3	20643	1.4	QPSK	1	0	23.42	0	0
	848.3	20643	1.4	QPSK	1	2	23.29	0	0
	848.3	20643	1.4	QPSK	1	5	23.39	0	0
	848.3	20643	1.4	QPSK	3	0	23.00	0	0
	848.3	20643	1.4	QPSK	3	2	23.05	0	0
	848.3	20643	1.4	QPSK	3	3	23.03	0	0
	848.3	20643	1.4	QPSK	6	0	23.04	0-1	0
	848.3	20643	1.4	16-QAM	1	0	23.47	0-1	0
	848.3	20643	1.4	16-QAM	1	2	23.39	0-1	0
	848.3	20643	1.4	16-QAM	1	5	23.40	0-1	0
	848.3	20643	1.4	16-QAM	3	0	23.15	0-1	0
	848.3	20643	1.4	16-QAM	3	2	23.07	0-1	0
	848.3	20643	1.4	16-QAM	3	3	23.05	0-1	0
	848.3	20643	1.4	16-QAM	6	0	22.15	0-2	1

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 42 of 108

9.3.3

LTE Band 4 (AWS)

Table 9-17

LTE Band 4 (AWS) Maximum Conducted Powers - 20 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	23.95	0	0
	1732.5	20175	20	QPSK	1	50	24.00	0	0
	1732.5	20175	20	QPSK	1	99	23.96	0	0
	1732.5	20175	20	QPSK	50	0	22.68	0-1	1
	1732.5	20175	20	QPSK	50	25	22.70	0-1	1
	1732.5	20175	20	QPSK	50	50	22.68	0-1	1
	1732.5	20175	20	QPSK	100	0	22.64	0-1	1
	1732.5	20175	20	16QAM	1	0	23.00	0-1	1
	1732.5	20175	20	16QAM	1	50	22.95	0-1	1
	1732.5	20175	20	16QAM	1	99	22.92	0-1	1
	1732.5	20175	20	16QAM	50	0	21.76	0-2	2
	1732.5	20175	20	16QAM	50	25	21.68	0-2	2
	1732.5	20175	20	16QAM	50	50	21.68	0-2	2
	1732.5	20175	20	16QAM	100	0	21.69	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 43 of 108

Table 9-18

LTE Band 4 (AWS) Maximum Conducted Powers - 15 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	23.85	0	0
	1717.5	20025	15	QPSK	1	36	23.84	0	0
	1717.5	20025	15	QPSK	1	74	23.80	0	0
	1717.5	20025	15	QPSK	36	0	22.41	0-1	1
	1717.5	20025	15	QPSK	36	18	22.38	0-1	1
	1717.5	20025	15	QPSK	36	37	22.40	0-1	1
	1717.5	20025	15	QPSK	75	0	22.38	0-1	1
	1717.5	20025	15	16QAM	1	0	22.33	0-1	1
	1717.5	20025	15	16QAM	1	36	22.30	0-1	1
	1717.5	20025	15	16QAM	1	74	22.26	0-1	1
	1717.5	20025	15	16QAM	36	0	21.38	0-2	2
	1717.5	20025	15	16QAM	36	18	21.41	0-2	2
Mid	1717.5	20025	15	16QAM	36	37	21.40	0-2	2
	1717.5	20025	15	16QAM	75	0	21.33	0-2	2
	1732.5	20175	15	QPSK	1	0	24.00	0	0
	1732.5	20175	15	QPSK	1	36	23.98	0	0
	1732.5	20175	15	QPSK	1	74	23.99	0	0
	1732.5	20175	15	QPSK	36	0	22.76	0-1	1
	1732.5	20175	15	QPSK	36	18	22.82	0-1	1
	1732.5	20175	15	QPSK	36	37	22.86	0-1	1
	1732.5	20175	15	QPSK	75	0	22.73	0-1	1
	1732.5	20175	15	16QAM	1	0	22.99	0-1	1
	1732.5	20175	15	16QAM	1	36	22.91	0-1	1
	1732.5	20175	15	16QAM	1	74	23.00	0-1	1
High	1732.5	20175	15	16QAM	36	0	21.77	0-2	2
	1732.5	20175	15	16QAM	36	18	21.84	0-2	2
	1732.5	20175	15	16QAM	36	37	21.76	0-2	2
	1732.5	20175	15	16QAM	75	0	21.72	0-2	2
	1747.5	20325	15	QPSK	1	0	23.83	0	0
	1747.5	20325	15	QPSK	1	36	23.84	0	0
	1747.5	20325	15	QPSK	1	74	23.81	0	0
	1747.5	20325	15	QPSK	36	0	22.37	0-1	1
	1747.5	20325	15	QPSK	36	18	22.40	0-1	1
	1747.5	20325	15	QPSK	36	37	22.41	0-1	1
	1747.5	20325	15	QPSK	75	0	22.38	0-1	1
	1747.5	20325	15	16QAM	1	0	22.35	0-1	1
	1747.5	20325	15	16QAM	1	36	22.29	0-1	1
	1747.5	20325	15	16QAM	1	74	22.28	0-1	1
	1747.5	20325	15	16QAM	36	0	21.39	0-2	2
	1747.5	20325	15	16QAM	36	18	21.41	0-2	2
	1747.5	20325	15	16QAM	36	37	21.42	0-2	2
	1747.5	20325	15	16QAM	75	0	21.34	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 44 of 108

Table 9-19

LTE Band 4 (AWS) Maximum Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	23.82	0	0
	1715	20000	10	QPSK	1	25	23.83	0	0
	1715	20000	10	QPSK	1	49	23.72	0	0
	1715	20000	10	QPSK	25	0	22.47	0-1	1
	1715	20000	10	QPSK	25	12	22.46	0-1	1
	1715	20000	10	QPSK	25	25	22.45	0-1	1
	1715	20000	10	QPSK	50	0	22.42	0-1	1
	1715	20000	10	16QAM	1	0	22.86	0-1	1
	1715	20000	10	16QAM	1	25	22.83	0-1	1
	1715	20000	10	16QAM	1	49	22.77	0-1	1
	1715	20000	10	16QAM	25	0	21.46	0-2	2
	1715	20000	10	16QAM	25	12	21.47	0-2	2
	1715	20000	10	16QAM	25	25	21.46	0-2	2
Mid	1715	20000	10	16QAM	50	0	21.38	0-2	2
	1732.5	20175	10	QPSK	1	0	23.96	0	0
	1732.5	20175	10	QPSK	1	25	23.92	0	0
	1732.5	20175	10	QPSK	1	49	23.95	0	0
	1732.5	20175	10	QPSK	25	0	22.85	0-1	1
	1732.5	20175	10	QPSK	25	12	22.81	0-1	1
	1732.5	20175	10	QPSK	25	25	22.82	0-1	1
	1732.5	20175	10	QPSK	50	0	22.74	0-1	1
	1732.5	20175	10	16QAM	1	0	22.78	0-1	1
	1732.5	20175	10	16QAM	1	25	22.74	0-1	1
	1732.5	20175	10	16QAM	1	49	22.70	0-1	1
	1732.5	20175	10	16QAM	25	0	21.85	0-2	2
	1732.5	20175	10	16QAM	25	12	21.86	0-2	2
	1732.5	20175	10	16QAM	25	25	21.85	0-2	2
High	1732.5	20175	10	16QAM	50	0	21.76	0-2	2
	1750	20350	10	QPSK	1	0	23.98	0	0
	1750	20350	10	QPSK	1	25	23.90	0	0
	1750	20350	10	QPSK	1	49	23.88	0	0
	1750	20350	10	QPSK	25	0	22.78	0-1	1
	1750	20350	10	QPSK	25	12	22.79	0-1	1
	1750	20350	10	QPSK	25	25	22.75	0-1	1
	1750	20350	10	QPSK	50	0	22.72	0-1	1
	1750	20350	10	16QAM	1	0	23.00	0-1	1
	1750	20350	10	16QAM	1	25	22.87	0-1	1
	1750	20350	10	16QAM	1	49	22.94	0-1	1
	1750	20350	10	16QAM	25	0	21.72	0-2	2
	1750	20350	10	16QAM	25	12	21.73	0-2	2
	1750	20350	10	16QAM	25	25	21.68	0-2	2
	1750	20350	10	16QAM	50	0	21.58	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 45 of 108

Table 9-20

LTE Band 4 (AWS) Maximum Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	23.73	0	0
	1712.5	19975	5	QPSK	1	12	23.71	0	0
	1712.5	19975	5	QPSK	1	24	23.75	0	0
	1712.5	19975	5	QPSK	12	0	22.40	0-1	1
	1712.5	19975	5	QPSK	12	6	22.34	0-1	1
	1712.5	19975	5	QPSK	12	13	22.41	0-1	1
	1712.5	19975	5	QPSK	25	0	22.40	0-1	1
	1712.5	19975	5	16-QAM	1	0	22.84	0-1	1
	1712.5	19975	5	16-QAM	1	12	22.82	0-1	1
	1712.5	19975	5	16-QAM	1	24	22.78	0-1	1
	1712.5	19975	5	16-QAM	12	0	21.45	0-2	2
	1712.5	19975	5	16-QAM	12	6	21.42	0-2	2
Mid	1712.5	19975	5	16-QAM	12	13	21.39	0-2	2
	1712.5	19975	5	16-QAM	25	0	21.32	0-2	2
	1732.5	20175	5	QPSK	1	0	23.98	0	0
	1732.5	20175	5	QPSK	1	12	23.97	0	0
	1732.5	20175	5	QPSK	1	24	23.96	0	0
	1732.5	20175	5	QPSK	12	0	22.76	0-1	1
	1732.5	20175	5	QPSK	12	6	22.78	0-1	1
	1732.5	20175	5	QPSK	12	13	22.80	0-1	1
	1732.5	20175	5	QPSK	25	0	22.76	0-1	1
	1732.5	20175	5	16-QAM	1	0	22.97	0-1	1
	1732.5	20175	5	16-QAM	1	12	23.00	0-1	1
	1732.5	20175	5	16-QAM	1	24	22.84	0-1	1
High	1732.5	20175	5	16-QAM	12	0	21.61	0-2	2
	1732.5	20175	5	16-QAM	12	6	21.64	0-2	2
	1732.5	20175	5	16-QAM	12	13	21.65	0-2	2
	1732.5	20175	5	16-QAM	25	0	21.68	0-2	2
	1752.5	20375	5	QPSK	1	0	23.95	0	0
	1752.5	20375	5	QPSK	1	12	24.00	0	0
	1752.5	20375	5	QPSK	1	24	23.94	0	0
	1752.5	20375	5	QPSK	12	0	22.62	0-1	1
	1752.5	20375	5	QPSK	12	6	22.61	0-1	1
	1752.5	20375	5	QPSK	12	13	22.59	0-1	1
	1752.5	20375	5	QPSK	25	0	22.57	0-1	1
	1752.5	20375	5	16-QAM	1	0	22.91	0-1	1
	1752.5	20375	5	16-QAM	1	12	22.72	0-1	1
	1752.5	20375	5	16-QAM	1	24	22.64	0-1	1
	1752.5	20375	5	16-QAM	12	0	21.63	0-2	2
	1752.5	20375	5	16-QAM	12	6	21.52	0-2	2
	1752.5	20375	5	16-QAM	12	13	21.51	0-2	2
	1752.5	20375	5	16-QAM	25	0	21.67	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 46 of 108

Table 9-21

LTE Band 4 (AWS) Maximum Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	23.82	0	0
	1711.5	19965	3	QPSK	1	7	23.81	0	0
	1711.5	19965	3	QPSK	1	14	23.82	0	0
	1711.5	19965	3	QPSK	8	0	22.48	0-1	1
	1711.5	19965	3	QPSK	8	4	22.47	0-1	1
	1711.5	19965	3	QPSK	8	7	22.34	0-1	1
	1711.5	19965	3	QPSK	15	0	22.35	0-1	1
	1711.5	19965	3	16-QAM	1	0	22.87	0-1	1
	1711.5	19965	3	16-QAM	1	7	22.97	0-1	1
	1711.5	19965	3	16-QAM	1	14	22.99	0-1	1
	1711.5	19965	3	16-QAM	8	0	21.30	0-2	2
	1711.5	19965	3	16-QAM	8	4	21.29	0-2	2
Mid	1711.5	19965	3	16-QAM	8	7	21.28	0-2	2
	1711.5	19965	3	16-QAM	15	0	21.27	0-2	2
	1732.5	20175	3	QPSK	1	0	23.93	0	0
	1732.5	20175	3	QPSK	1	7	23.98	0	0
	1732.5	20175	3	QPSK	1	14	24.00	0	0
	1732.5	20175	3	QPSK	8	0	22.78	0-1	1
	1732.5	20175	3	QPSK	8	4	22.71	0-1	1
	1732.5	20175	3	QPSK	8	7	22.68	0-1	1
	1732.5	20175	3	QPSK	15	0	22.76	0-1	1
	1732.5	20175	3	16-QAM	1	0	22.93	0-1	1
	1732.5	20175	3	16-QAM	1	7	22.90	0-1	1
	1732.5	20175	3	16-QAM	1	14	22.94	0-1	1
High	1732.5	20175	3	16-QAM	8	0	21.80	0-2	2
	1732.5	20175	3	16-QAM	8	4	21.81	0-2	2
	1732.5	20175	3	16-QAM	8	7	21.82	0-2	2
	1732.5	20175	3	16-QAM	8	7	21.82	0-2	2
	1732.5	20175	3	16-QAM	15	0	21.78	0-2	2
	1753.5	20385	3	QPSK	1	0	23.92	0	0
	1753.5	20385	3	QPSK	1	7	23.91	0	0
	1753.5	20385	3	QPSK	1	14	23.98	0	0
	1753.5	20385	3	QPSK	8	0	22.74	0-1	1
	1753.5	20385	3	QPSK	8	4	22.60	0-1	1
	1753.5	20385	3	QPSK	8	7	22.59	0-1	1
	1753.5	20385	3	QPSK	15	0	22.58	0-1	1
	1753.5	20385	3	16-QAM	1	0	22.99	0-1	1
	1753.5	20385	3	16-QAM	1	7	22.98	0-1	1
	1753.5	20385	3	16-QAM	1	14	22.93	0-1	1
	1753.5	20385	3	16-QAM	8	0	21.48	0-2	2
	1753.5	20385	3	16-QAM	8	4	21.47	0-2	2
	1753.5	20385	3	16-QAM	8	7	21.44	0-2	2
	1753.5	20385	3	16-QAM	15	0	21.52	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 47 of 108

Table 9-22

LTE Band 4 (AWS) Maximum Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	23.82	0	0
	1710.7	19957	1.4	QPSK	1	2	23.81	0	0
	1710.7	19957	1.4	QPSK	1	5	23.86	0	0
	1710.7	19957	1.4	QPSK	3	0	23.58	0	0
	1710.7	19957	1.4	QPSK	3	2	23.55	0	0
	1710.7	19957	1.4	QPSK	3	3	23.51	0	0
	1710.7	19957	1.4	QPSK	6	0	22.43	0-1	1
	1710.7	19957	1.4	16-QAM	1	0	22.95	0-1	1
	1710.7	19957	1.4	16-QAM	1	2	22.73	0-1	1
	1710.7	19957	1.4	16-QAM	1	5	22.77	0-1	1
	1710.7	19957	1.4	16-QAM	3	0	22.46	0-1	1
	1710.7	19957	1.4	16-QAM	3	2	22.42	0-1	1
Mid	1710.7	19957	1.4	16-QAM	3	3	22.32	0-1	1
	1710.7	19957	1.4	16-QAM	6	0	21.34	0-2	2
	1732.5	20175	1.4	QPSK	1	0	24.00	0	0
	1732.5	20175	1.4	QPSK	1	2	23.98	0	0
	1732.5	20175	1.4	QPSK	1	5	23.95	0	0
	1732.5	20175	1.4	QPSK	3	0	23.78	0	0
	1732.5	20175	1.4	QPSK	3	2	23.85	0	0
	1732.5	20175	1.4	QPSK	3	3	23.81	0	0
	1732.5	20175	1.4	QPSK	6	0	22.78	0-1	1
	1732.5	20175	1.4	16-QAM	1	0	22.80	0-1	1
	1732.5	20175	1.4	16-QAM	1	2	22.86	0-1	1
	1732.5	20175	1.4	16-QAM	1	5	23.00	0-1	1
High	1732.5	20175	1.4	16-QAM	3	0	22.64	0-1	1
	1732.5	20175	1.4	16-QAM	3	2	22.73	0-1	1
	1732.5	20175	1.4	16-QAM	3	3	22.69	0-1	1
	1732.5	20175	1.4	16-QAM	6	0	21.83	0-2	2
	1754.3	20393	1.4	QPSK	1	0	23.95	0	0
	1754.3	20393	1.4	QPSK	1	2	23.98	0	0
	1754.3	20393	1.4	QPSK	1	5	24.00	0	0
	1754.3	20393	1.4	QPSK	3	0	23.86	0	0
	1754.3	20393	1.4	QPSK	3	2	23.83	0	0
	1754.3	20393	1.4	QPSK	3	3	23.74	0	0
	1754.3	20393	1.4	QPSK	6	0	22.62	0-1	1
	1754.3	20393	1.4	16-QAM	1	0	22.87	0-1	1
	1754.3	20393	1.4	16-QAM	1	2	22.76	0-1	1
	1754.3	20393	1.4	16-QAM	1	5	22.88	0-1	1
	1754.3	20393	1.4	16-QAM	3	0	22.66	0-1	1
	1754.3	20393	1.4	16-QAM	3	2	22.62	0-1	1
	1754.3	20393	1.4	16-QAM	3	3	22.55	0-1	1
	1754.3	20393	1.4	16-QAM	6	0	21.57	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 48 of 108

Table 9-23

LTE Band 4 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	20.84	0	0
	1732.5	20175	20	QPSK	1	50	20.91	0	0
	1732.5	20175	20	QPSK	1	99	20.88	0	0
	1732.5	20175	20	QPSK	50	0	20.69	0-1	0
	1732.5	20175	20	QPSK	50	25	20.75	0-1	0
	1732.5	20175	20	QPSK	50	50	20.65	0-1	0
	1732.5	20175	20	QPSK	100	0	20.67	0-1	0
	1732.5	20175	20	16QAM	1	0	20.89	0-1	0
	1732.5	20175	20	16QAM	1	50	20.83	0-1	0
	1732.5	20175	20	16QAM	1	99	20.87	0-1	0
	1732.5	20175	20	16QAM	50	0	20.79	0-2	0
	1732.5	20175	20	16QAM	50	25	20.70	0-2	0
	1732.5	20175	20	16QAM	50	50	20.79	0-2	0
	1732.5	20175	20	16QAM	100	0	20.80	0-2	0

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 49 of 108

Table 9-24

LTE Band 4 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	20.48	0	0
	1717.5	20025	15	QPSK	1	36	20.44	0	0
	1717.5	20025	15	QPSK	1	74	20.37	0	0
	1717.5	20025	15	QPSK	36	0	20.18	0-1	0
	1717.5	20025	15	QPSK	36	18	20.11	0-1	0
	1717.5	20025	15	QPSK	36	37	20.04	0-1	0
	1717.5	20025	15	QPSK	75	0	20.11	0-1	0
	1717.5	20025	15	16QAM	1	0	20.43	0-1	0
	1717.5	20025	15	16QAM	1	36	20.63	0-1	0
	1717.5	20025	15	16QAM	1	74	20.67	0-1	0
	1717.5	20025	15	16QAM	36	0	20.18	0-2	0
	1717.5	20025	15	16QAM	36	18	20.20	0-2	0
Mid	1717.5	20025	15	16QAM	36	37	20.19	0-2	0
	1717.5	20025	15	16QAM	75	0	20.15	0-2	0
	1732.5	20175	15	QPSK	1	0	20.60	0	0
	1732.5	20175	15	QPSK	1	36	20.61	0	0
	1732.5	20175	15	QPSK	1	74	20.56	0	0
	1732.5	20175	15	QPSK	36	0	20.41	0-1	0
	1732.5	20175	15	QPSK	36	18	20.50	0-1	0
	1732.5	20175	15	QPSK	36	37	20.36	0-1	0
	1732.5	20175	15	QPSK	75	0	20.35	0-1	0
	1732.5	20175	15	16QAM	1	0	20.45	0-1	0
	1732.5	20175	15	16QAM	1	36	20.64	0-1	0
	1732.5	20175	15	16QAM	1	74	20.59	0-1	0
High	1732.5	20175	15	16QAM	36	0	20.32	0-2	0
	1732.5	20175	15	16QAM	36	18	20.41	0-2	0
	1732.5	20175	15	16QAM	36	37	20.39	0-2	0
	1732.5	20175	15	16QAM	75	0	20.36	0-2	0
	1747.5	20325	15	QPSK	1	0	20.73	0	0
	1747.5	20325	15	QPSK	1	36	20.81	0	0
	1747.5	20325	15	QPSK	1	74	20.72	0	0
	1747.5	20325	15	QPSK	36	0	20.42	0-1	0
	1747.5	20325	15	QPSK	36	18	20.39	0-1	0
	1747.5	20325	15	QPSK	36	37	20.33	0-1	0
	1747.5	20325	15	QPSK	75	0	20.36	0-1	0
	1747.5	20325	15	16QAM	1	0	20.50	0-1	0
	1747.5	20325	15	16QAM	1	36	20.47	0-1	0
	1747.5	20325	15	16QAM	1	74	20.69	0-1	0
	1747.5	20325	15	16QAM	36	0	20.29	0-2	0
	1747.5	20325	15	16QAM	36	18	20.42	0-2	0
	1747.5	20325	15	16QAM	36	37	20.39	0-2	0
	1747.5	20325	15	16QAM	75	0	20.37	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 50 of 108

Table 9-25

LTE Band 4 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	20.43	0	0
	1715	20000	10	QPSK	1	25	20.53	0	0
	1715	20000	10	QPSK	1	49	20.39	0	0
	1715	20000	10	QPSK	25	0	20.13	0-1	0
	1715	20000	10	QPSK	25	12	20.20	0-1	0
	1715	20000	10	QPSK	25	25	20.13	0-1	0
	1715	20000	10	QPSK	50	0	20.09	0-1	0
	1715	20000	10	16QAM	1	0	20.60	0-1	0
	1715	20000	10	16QAM	1	25	20.50	0-1	0
	1715	20000	10	16QAM	1	49	20.59	0-1	0
	1715	20000	10	16QAM	25	0	20.27	0-2	0
	1715	20000	10	16QAM	25	12	20.28	0-2	0
	1715	20000	10	16QAM	25	25	20.11	0-2	0
Mid	1715	20000	10	16QAM	50	0	20.14	0-2	0
	1732.5	20175	10	QPSK	1	0	20.83	0	0
	1732.5	20175	10	QPSK	1	25	20.68	0	0
	1732.5	20175	10	QPSK	1	49	20.67	0	0
	1732.5	20175	10	QPSK	25	0	20.43	0-1	0
	1732.5	20175	10	QPSK	25	12	20.40	0-1	0
	1732.5	20175	10	QPSK	25	25	20.36	0-1	0
	1732.5	20175	10	QPSK	50	0	20.39	0-1	0
	1732.5	20175	10	16QAM	1	0	20.85	0-1	0
	1732.5	20175	10	16QAM	1	25	20.90	0-1	0
	1732.5	20175	10	16QAM	1	49	20.53	0-1	0
	1732.5	20175	10	16QAM	25	0	20.52	0-2	0
	1732.5	20175	10	16QAM	25	12	20.54	0-2	0
High	1732.5	20175	10	16QAM	25	25	20.62	0-2	0
	1732.5	20175	10	16QAM	50	0	20.55	0-2	0
	1750	20350	10	QPSK	1	0	20.81	0	0
	1750	20350	10	QPSK	1	25	20.74	0	0
	1750	20350	10	QPSK	1	49	20.68	0	0
	1750	20350	10	QPSK	25	0	20.40	0-1	0
	1750	20350	10	QPSK	25	12	20.42	0-1	0
	1750	20350	10	QPSK	25	25	20.35	0-1	0
	1750	20350	10	QPSK	50	0	20.31	0-1	0
	1750	20350	10	16QAM	1	0	20.43	0-1	0
	1750	20350	10	16QAM	1	25	20.64	0-1	0
	1750	20350	10	16QAM	1	49	20.53	0-1	0
	1750	20350	10	16QAM	25	0	20.42	0-2	0
	1750	20350	10	16QAM	25	12	20.45	0-2	0
	1750	20350	10	16QAM	25	25	20.39	0-2	0
	1750	20350	10	16QAM	50	0	20.42	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 51 of 108

Table 9-26

LTE Band 4 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth-

Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	20.10	0	0
	1712.5	19975	5	QPSK	1	12	20.09	0	0
	1712.5	19975	5	QPSK	1	24	20.10	0	0
	1712.5	19975	5	QPSK	12	0	20.17	0-1	0
	1712.5	19975	5	QPSK	12	6	20.16	0-1	0
	1712.5	19975	5	QPSK	12	13	20.15	0-1	0
	1712.5	19975	5	QPSK	25	0	20.11	0-1	0
	1712.5	19975	5	16-QAM	1	0	20.47	0-1	0
	1712.5	19975	5	16-QAM	1	12	20.53	0-1	0
	1712.5	19975	5	16-QAM	1	24	20.54	0-1	0
	1712.5	19975	5	16-QAM	12	0	20.08	0-2	0
	1712.5	19975	5	16-QAM	12	6	20.06	0-2	0
Mid	1712.5	19975	5	16-QAM	12	13	20.07	0-2	0
	1712.5	19975	5	16-QAM	25	0	20.03	0-2	0
	1732.5	20175	5	QPSK	1	0	20.67	0	0
	1732.5	20175	5	QPSK	1	12	20.66	0	0
	1732.5	20175	5	QPSK	1	24	20.68	0	0
	1732.5	20175	5	QPSK	12	0	20.42	0-1	0
	1732.5	20175	5	QPSK	12	6	20.43	0-1	0
	1732.5	20175	5	QPSK	12	13	20.45	0-1	0
	1732.5	20175	5	QPSK	25	0	20.41	0-1	0
	1732.5	20175	5	16-QAM	1	0	20.77	0-1	0
	1732.5	20175	5	16-QAM	1	12	20.64	0-1	0
	1732.5	20175	5	16-QAM	1	24	20.82	0-1	0
High	1732.5	20175	5	16-QAM	12	0	20.48	0-2	0
	1732.5	20175	5	16-QAM	12	6	20.50	0-2	0
	1732.5	20175	5	16-QAM	12	13	20.52	0-2	0
	1732.5	20175	5	16-QAM	25	0	20.46	0-2	0
	1752.5	20375	5	QPSK	1	0	20.52	0	0
	1752.5	20375	5	QPSK	1	12	20.58	0	0
	1752.5	20375	5	QPSK	1	24	20.47	0	0
	1752.5	20375	5	QPSK	12	0	20.37	0-1	0
	1752.5	20375	5	QPSK	12	6	20.37	0-1	0
	1752.5	20375	5	QPSK	12	13	20.34	0-1	0
	1752.5	20375	5	QPSK	25	0	20.33	0-1	0
	1752.5	20375	5	16-QAM	1	0	20.47	0-1	0
	1752.5	20375	5	16-QAM	1	12	20.69	0-1	0
	1752.5	20375	5	16-QAM	1	24	20.75	0-1	0
	1752.5	20375	5	16-QAM	12	0	20.35	0-2	0
	1752.5	20375	5	16-QAM	12	6	20.32	0-2	0
	1752.5	20375	5	16-QAM	12	13	20.27	0-2	0
	1752.5	20375	5	16-QAM	25	0	20.28	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 52 of 108

Table 9-27

LTE Band 4 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	20.43	0	0
	1711.5	19965	3	QPSK	1	7	20.34	0	0
	1711.5	19965	3	QPSK	1	14	20.36	0	0
	1711.5	19965	3	QPSK	8	0	20.14	0-1	0
	1711.5	19965	3	QPSK	8	4	20.12	0-1	0
	1711.5	19965	3	QPSK	8	7	20.11	0-1	0
	1711.5	19965	3	QPSK	15	0	20.10	0-1	0
	1711.5	19965	3	16-QAM	1	0	20.37	0-1	0
	1711.5	19965	3	16-QAM	1	7	20.39	0-1	0
	1711.5	19965	3	16-QAM	1	14	20.38	0-1	0
	1711.5	19965	3	16-QAM	8	0	20.11	0-2	0
	1711.5	19965	3	16-QAM	8	4	20.07	0-2	0
Mid	1711.5	19965	3	16-QAM	8	7	20.16	0-2	0
	1711.5	19965	3	16-QAM	15	0	20.11	0-2	0
	1732.5	20175	3	QPSK	1	0	20.71	0	0
	1732.5	20175	3	QPSK	1	7	20.66	0	0
	1732.5	20175	3	QPSK	1	14	20.66	0	0
	1732.5	20175	3	QPSK	8	0	20.33	0-1	0
	1732.5	20175	3	QPSK	8	4	20.35	0-1	0
	1732.5	20175	3	QPSK	8	7	20.36	0-1	0
	1732.5	20175	3	QPSK	15	0	20.32	0-1	0
	1732.5	20175	3	16-QAM	1	0	20.60	0-1	0
	1732.5	20175	3	16-QAM	1	7	20.61	0-1	0
	1732.5	20175	3	16-QAM	1	14	20.59	0-1	0
High	1732.5	20175	3	16-QAM	8	0	20.29	0-2	0
	1732.5	20175	3	16-QAM	8	4	20.29	0-2	0
	1732.5	20175	3	16-QAM	8	7	20.31	0-2	0
	1732.5	20175	3	16-QAM	15	0	20.30	0-2	0
	1753.5	20385	3	QPSK	1	0	20.53	0	0
	1753.5	20385	3	QPSK	1	7	20.54	0	0
	1753.5	20385	3	QPSK	1	14	20.48	0	0
	1753.5	20385	3	QPSK	8	0	20.33	0-1	0
	1753.5	20385	3	QPSK	8	4	20.32	0-1	0
	1753.5	20385	3	QPSK	8	7	20.31	0-1	0
	1753.5	20385	3	QPSK	15	0	20.29	0-1	0
	1753.5	20385	3	16-QAM	1	0	20.88	0-1	0
	1753.5	20385	3	16-QAM	1	7	20.70	0-1	0
	1753.5	20385	3	16-QAM	1	14	20.74	0-1	0
	1753.5	20385	3	16-QAM	8	0	20.14	0-2	0
	1753.5	20385	3	16-QAM	8	4	20.13	0-2	0
	1753.5	20385	3	16-QAM	8	7	20.13	0-2	0
	1753.5	20385	3	16-QAM	15	0	20.19	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 53 of 108

Table 9-28

LTE Band 4 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	20.28	0	0
	1710.7	19957	1.4	QPSK	1	2	20.29	0	0
	1710.7	19957	1.4	QPSK	1	5	20.35	0	0
	1710.7	19957	1.4	QPSK	3	0	20.22	0	0
	1710.7	19957	1.4	QPSK	3	2	20.18	0	0
	1710.7	19957	1.4	QPSK	3	3	20.11	0	0
	1710.7	19957	1.4	QPSK	6	0	20.12	0-1	0
	1710.7	19957	1.4	16-QAM	1	0	20.55	0-1	0
	1710.7	19957	1.4	16-QAM	1	2	20.56	0-1	0
	1710.7	19957	1.4	16-QAM	1	5	20.66	0-1	0
	1710.7	19957	1.4	16-QAM	3	0	20.21	0-1	0
	1710.7	19957	1.4	16-QAM	3	2	20.23	0-1	0
Mid	1710.7	19957	1.4	16-QAM	3	3	20.09	0-1	0
	1710.7	19957	1.4	16-QAM	6	0	20.00	0-2	0
	1732.5	20175	1.4	QPSK	1	0	20.75	0	0
	1732.5	20175	1.4	QPSK	1	2	20.67	0	0
	1732.5	20175	1.4	QPSK	1	5	20.66	0	0
	1732.5	20175	1.4	QPSK	3	0	20.40	0	0
	1732.5	20175	1.4	QPSK	3	2	20.45	0	0
	1732.5	20175	1.4	QPSK	3	3	20.42	0	0
	1732.5	20175	1.4	QPSK	6	0	20.33	0-1	0
	1732.5	20175	1.4	16-QAM	1	0	20.66	0-1	0
	1732.5	20175	1.4	16-QAM	1	2	20.62	0-1	0
	1732.5	20175	1.4	16-QAM	1	5	20.72	0-1	0
High	1732.5	20175	1.4	16-QAM	3	0	20.36	0-1	0
	1732.5	20175	1.4	16-QAM	3	2	20.37	0-1	0
	1732.5	20175	1.4	16-QAM	3	3	20.36	0-1	0
	1732.5	20175	1.4	16-QAM	6	0	20.40	0-2	0
	1754.3	20393	1.4	QPSK	1	0	20.48	0	0
	1754.3	20393	1.4	QPSK	1	2	20.50	0	0
	1754.3	20393	1.4	QPSK	1	5	20.58	0	0
	1754.3	20393	1.4	QPSK	3	0	20.28	0	0
	1754.3	20393	1.4	QPSK	3	2	20.24	0	0
	1754.3	20393	1.4	QPSK	3	3	20.27	0	0
	1754.3	20393	1.4	QPSK	6	0	20.27	0-1	0
	1754.3	20393	1.4	16-QAM	1	0	20.59	0-1	0
	1754.3	20393	1.4	16-QAM	1	2	20.53	0-1	0
	1754.3	20393	1.4	16-QAM	1	5	20.58	0-1	0
	1754.3	20393	1.4	16-QAM	3	0	20.20	0-1	0
	1754.3	20393	1.4	16-QAM	3	2	20.17	0-1	0
	1754.3	20393	1.4	16-QAM	3	3	20.13	0-1	0
	1754.3	20393	1.4	16-QAM	6	0	20.14	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 54 of 108

9.3.4

LTE Band 2 (PCS)

Table 9-29

LTE Band 2 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	23.88	0	0
	1860	18700	20	QPSK	1	50	23.99	0	0
	1860	18700	20	QPSK	1	99	23.96	0	0
	1860	18700	20	QPSK	50	0	22.65	0-1	1
	1860	18700	20	QPSK	50	25	22.75	0-1	1
	1860	18700	20	QPSK	50	50	22.68	0-1	1
	1860	18700	20	QPSK	100	0	22.66	0-1	1
	1860	18700	20	16QAM	1	0	22.82	0-1	1
	1860	18700	20	16QAM	1	50	22.95	0-1	1
	1860	18700	20	16QAM	1	99	22.96	0-1	1
	1860	18700	20	16QAM	50	0	21.55	0-2	2
	1860	18700	20	16QAM	50	25	21.61	0-2	2
	1860	18700	20	16QAM	50	50	21.63	0-2	2
	1860	18700	20	16QAM	100	0	21.62	0-2	2
Mid	1880.0	18900	20	QPSK	1	0	23.77	0	0
	1880.0	18900	20	QPSK	1	50	23.78	0	0
	1880.0	18900	20	QPSK	1	99	23.90	0	0
	1880.0	18900	20	QPSK	50	0	22.76	0-1	1
	1880.0	18900	20	QPSK	50	25	22.79	0-1	1
	1880.0	18900	20	QPSK	50	50	22.78	0-1	1
	1880.0	18900	20	QPSK	100	0	22.70	0-1	1
	1880.0	18900	20	16QAM	1	0	22.93	0-1	1
	1880.0	18900	20	16QAM	1	50	22.95	0-1	1
	1880.0	18900	20	16QAM	1	99	23.00	0-1	1
	1880.0	18900	20	16QAM	50	0	21.64	0-2	2
	1880.0	18900	20	16QAM	50	25	21.67	0-2	2
	1880.0	18900	20	16QAM	50	50	21.73	0-2	2
	1880.0	18900	20	16QAM	100	0	21.73	0-2	2
High	1900	19100	20	QPSK	1	0	23.94	0	0
	1900	19100	20	QPSK	1	50	23.89	0	0
	1900	19100	20	QPSK	1	99	24.00	0	0
	1900	19100	20	QPSK	50	0	22.78	0-1	1
	1900	19100	20	QPSK	50	25	22.60	0-1	1
	1900	19100	20	QPSK	50	50	22.61	0-1	1
	1900	19100	20	QPSK	100	0	22.62	0-1	1
	1900	19100	20	16QAM	1	0	23.00	0-1	1
	1900	19100	20	16QAM	1	50	22.84	0-1	1
	1900	19100	20	16QAM	1	99	22.83	0-1	1
	1900	19100	20	16QAM	50	0	21.70	0-2	2
	1900	19100	20	16QAM	50	25	21.62	0-2	2
	1900	19100	20	16QAM	50	50	21.61	0-2	2
	1900	19100	20	16QAM	100	0	21.70	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 55 of 108

Table 9-30

LTE Band 2 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	23.62	0	0
	1857.5	18675	15	QPSK	1	36	23.77	0	0
	1857.5	18675	15	QPSK	1	74	23.50	0	0
	1857.5	18675	15	QPSK	36	0	22.75	0-1	1
	1857.5	18675	15	QPSK	36	18	22.77	0-1	1
	1857.5	18675	15	QPSK	36	37	22.61	0-1	1
	1857.5	18675	15	QPSK	75	0	22.74	0-1	1
	1857.5	18675	15	16QAM	1	0	22.75	0-1	1
	1857.5	18675	15	16QAM	1	36	22.81	0-1	1
	1857.5	18675	15	16QAM	1	74	22.31	0-1	1
	1857.5	18675	15	16QAM	36	0	21.62	0-2	2
	1857.5	18675	15	16QAM	36	18	21.77	0-2	2
	1857.5	18675	15	16QAM	36	37	21.78	0-2	2
	1857.5	18675	15	16QAM	75	0	21.73	0-2	2
Mid	1880.0	18900	15	QPSK	1	0	23.87	0	0
	1880.0	18900	15	QPSK	1	36	23.88	0	0
	1880.0	18900	15	QPSK	1	74	23.87	0	0
	1880.0	18900	15	QPSK	36	0	22.51	0-1	1
	1880.0	18900	15	QPSK	36	18	22.49	0-1	1
	1880.0	18900	15	QPSK	36	37	22.44	0-1	1
	1880.0	18900	15	QPSK	75	0	22.36	0-1	1
	1880.0	18900	15	16QAM	1	0	22.65	0-1	1
	1880.0	18900	15	16QAM	1	36	22.57	0-1	1
	1880.0	18900	15	16QAM	1	74	22.49	0-1	1
	1880.0	18900	15	16QAM	36	0	21.37	0-2	2
	1880.0	18900	15	16QAM	36	18	21.39	0-2	2
	1880.0	18900	15	16QAM	36	37	21.37	0-2	2
	1880.0	18900	15	16QAM	75	0	21.40	0-2	2
High	1902.5	19125	15	QPSK	1	0	23.95	0	0
	1902.5	19125	15	QPSK	1	36	23.88	0	0
	1902.5	19125	15	QPSK	1	74	23.87	0	0
	1902.5	19125	15	QPSK	36	0	22.84	0-1	1
	1902.5	19125	15	QPSK	36	18	22.88	0-1	1
	1902.5	19125	15	QPSK	36	37	22.74	0-1	1
	1902.5	19125	15	QPSK	75	0	22.71	0-1	1
	1902.5	19125	15	16QAM	1	0	22.80	0-1	1
	1902.5	19125	15	16QAM	1	36	22.66	0-1	1
	1902.5	19125	15	16QAM	1	74	22.69	0-1	1
	1902.5	19125	15	16QAM	36	0	21.75	0-2	2
	1902.5	19125	15	16QAM	36	18	21.79	0-2	2
	1902.5	19125	15	16QAM	36	37	21.77	0-2	2
	1902.5	19125	15	16QAM	75	0	21.62	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 56 of 108

Table 9-31

LTE Band 2 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	23.60	0	0
	1855	18650	10	QPSK	1	25	23.51	0	0
	1855	18650	10	QPSK	1	49	23.55	0	0
	1855	18650	10	QPSK	25	0	22.46	0-1	1
	1855	18650	10	QPSK	25	12	22.31	0-1	1
	1855	18650	10	QPSK	25	25	22.57	0-1	1
	1855	18650	10	QPSK	50	0	22.75	0-1	1
	1855	18650	10	16QAM	1	0	22.77	0-1	1
	1855	18650	10	16QAM	1	25	22.71	0-1	1
	1855	18650	10	16QAM	1	49	22.76	0-1	1
	1855	18650	10	16QAM	25	0	21.79	0-2	2
	1855	18650	10	16QAM	25	12	21.64	0-2	2
Mid	1880.0	18900	10	QPSK	1	0	23.74	0	0
	1880.0	18900	10	QPSK	1	25	23.84	0	0
	1880.0	18900	10	QPSK	1	49	23.80	0	0
	1880.0	18900	10	QPSK	25	0	22.76	0-1	1
	1880.0	18900	10	QPSK	25	12	22.78	0-1	1
	1880.0	18900	10	QPSK	25	25	22.79	0-1	1
	1880.0	18900	10	QPSK	50	0	22.77	0-1	1
	1880.0	18900	10	16QAM	1	0	22.16	0-1	1
	1880.0	18900	10	16QAM	1	25	22.84	0-1	1
	1880.0	18900	10	16QAM	1	49	22.91	0-1	1
	1880.0	18900	10	16QAM	25	0	21.85	0-2	2
	1880.0	18900	10	16QAM	25	12	21.80	0-2	2
High	1905	19150	10	QPSK	1	0	23.70	0	0
	1905	19150	10	QPSK	1	25	23.84	0	0
	1905	19150	10	QPSK	1	49	23.84	0	0
	1905	19150	10	QPSK	25	0	22.77	0-1	1
	1905	19150	10	QPSK	25	12	22.79	0-1	1
	1905	19150	10	QPSK	25	25	22.80	0-1	1
	1905	19150	10	QPSK	50	0	22.74	0-1	1
	1905	19150	10	16QAM	1	0	22.81	0-1	1
	1905	19150	10	16QAM	1	25	22.82	0-1	1
	1905	19150	10	16QAM	1	49	22.81	0-1	1
	1905	19150	10	16QAM	25	0	21.81	0-2	2
	1905	19150	10	16QAM	25	12	21.65	0-2	2
	1905	19150	10	16QAM	25	25	21.66	0-2	2
	1905	19150	10	16QAM	50	0	21.72	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 57 of 108

Table 9-32

LTE Band 2 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	23.62	0	0
	1852.5	18625	5	QPSK	1	12	23.66	0	0
	1852.5	18625	5	QPSK	1	24	23.65	0	0
	1852.5	18625	5	QPSK	12	0	22.44	0-1	1
	1852.5	18625	5	QPSK	12	6	22.49	0-1	1
	1852.5	18625	5	QPSK	12	13	22.44	0-1	1
	1852.5	18625	5	QPSK	25	0	22.40	0-1	1
	1852.5	18625	5	16-QAM	1	0	22.67	0-1	1
	1852.5	18625	5	16-QAM	1	12	22.61	0-1	1
	1852.5	18625	5	16-QAM	1	24	22.71	0-1	1
	1852.5	18625	5	16-QAM	12	0	21.40	0-2	2
	1852.5	18625	5	16-QAM	12	6	21.47	0-2	2
Mid	1852.5	18625	5	16-QAM	12	13	21.43	0-2	2
	1852.5	18625	5	16-QAM	25	0	21.37	0-2	2
	1880.0	18900	5	QPSK	1	0	23.85	0	0
	1880.0	18900	5	QPSK	1	12	23.90	0	0
	1880.0	18900	5	QPSK	1	24	24.00	0	0
	1880.0	18900	5	QPSK	12	0	22.45	0-1	1
	1880.0	18900	5	QPSK	12	6	22.49	0-1	1
	1880.0	18900	5	QPSK	12	13	22.47	0-1	1
	1880.0	18900	5	QPSK	25	0	22.46	0-1	1
	1880.0	18900	5	16-QAM	1	0	22.88	0-1	1
	1880.0	18900	5	16-QAM	1	12	22.87	0-1	1
	1880.0	18900	5	16-QAM	1	24	22.93	0-1	1
High	1880.0	18900	5	16-QAM	12	0	21.54	0-2	2
	1880.0	18900	5	16-QAM	12	6	21.51	0-2	2
	1880.0	18900	5	16-QAM	12	13	21.55	0-2	2
	1880.0	18900	5	16-QAM	25	0	21.43	0-2	2
	1907.5	19175	5	QPSK	1	0	23.66	0	0
	1907.5	19175	5	QPSK	1	12	23.73	0	0
	1907.5	19175	5	QPSK	1	24	23.75	0	0
	1907.5	19175	5	QPSK	12	0	22.37	0-1	1
	1907.5	19175	5	QPSK	12	6	22.45	0-1	1
	1907.5	19175	5	QPSK	12	13	22.45	0-1	1
	1907.5	19175	5	QPSK	25	0	22.35	0-1	1
	1907.5	19175	5	16-QAM	1	0	22.81	0-1	1
	1907.5	19175	5	16-QAM	1	12	22.81	0-1	1
	1907.5	19175	5	16-QAM	1	24	22.86	0-1	1
	1907.5	19175	5	16-QAM	12	0	21.35	0-2	2
	1907.5	19175	5	16-QAM	12	6	21.34	0-2	2
	1907.5	19175	5	16-QAM	12	13	21.36	0-2	2
	1907.5	19175	5	16-QAM	25	0	21.26	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 58 of 108

Table 9-33

LTE Band 2 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	23.83	0	0
	1851.5	18615	3	QPSK	1	7	23.83	0	0
	1851.5	18615	3	QPSK	1	14	23.96	0	0
	1851.5	18615	3	QPSK	8	0	22.30	0-1	1
	1851.5	18615	3	QPSK	8	4	22.36	0-1	1
	1851.5	18615	3	QPSK	8	7	22.41	0-1	1
	1851.5	18615	3	QPSK	15	0	22.35	0-1	1
	1851.5	18615	3	16-QAM	1	0	22.55	0-1	1
	1851.5	18615	3	16-QAM	1	7	22.61	0-1	1
	1851.5	18615	3	16-QAM	1	14	22.63	0-1	1
	1851.5	18615	3	16-QAM	8	0	21.28	0-2	2
	1851.5	18615	3	16-QAM	8	4	21.31	0-2	2
Mid	1851.5	18615	3	16-QAM	8	7	21.28	0-2	2
	1851.5	18615	3	16-QAM	15	0	21.25	0-2	2
	1880.0	18900	3	QPSK	1	0	23.91	0	0
	1880.0	18900	3	QPSK	1	7	23.96	0	0
	1880.0	18900	3	QPSK	1	14	24.00	0	0
	1880.0	18900	3	QPSK	8	0	22.43	0-1	1
	1880.0	18900	3	QPSK	8	4	22.49	0-1	1
	1880.0	18900	3	QPSK	8	7	22.52	0-1	1
	1880.0	18900	3	QPSK	15	0	22.46	0-1	1
	1880.0	18900	3	16-QAM	1	0	22.67	0-1	1
	1880.0	18900	3	16-QAM	1	7	22.67	0-1	1
	1880.0	18900	3	16-QAM	1	14	22.74	0-1	1
High	1880.0	18900	3	16-QAM	8	0	21.36	0-2	2
	1880.0	18900	3	16-QAM	8	4	21.40	0-2	2
	1880.0	18900	3	16-QAM	8	7	21.43	0-2	2
	1880.0	18900	3	16-QAM	15	0	21.34	0-2	2
	1908.5	19185	3	QPSK	1	0	23.82	0	0
	1908.5	19185	3	QPSK	1	7	23.85	0	0
	1908.5	19185	3	QPSK	1	14	23.81	0	0
	1908.5	19185	3	QPSK	8	0	22.41	0-1	1
	1908.5	19185	3	QPSK	8	4	22.44	0-1	1
	1908.5	19185	3	QPSK	8	7	22.47	0-1	1
	1908.5	19185	3	QPSK	15	0	22.34	0-1	1
	1908.5	19185	3	16-QAM	1	0	22.43	0-1	1
	1908.5	19185	3	16-QAM	1	7	22.57	0-1	1
	1908.5	19185	3	16-QAM	1	14	22.38	0-1	1
	1908.5	19185	3	16-QAM	8	0	21.28	0-2	2
	1908.5	19185	3	16-QAM	8	4	21.31	0-2	2
	1908.5	19185	3	16-QAM	8	7	21.32	0-2	2
	1908.5	19185	3	16-QAM	15	0	21.24	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 59 of 108

Table 9-34

LTE Band 2 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	23.73	0	0
	1850.7	18607	1.4	QPSK	1	2	23.76	0	0
	1850.7	18607	1.4	QPSK	1	5	23.78	0	0
	1850.7	18607	1.4	QPSK	3	0	23.50	0	0
	1850.7	18607	1.4	QPSK	3	2	23.50	0	0
	1850.7	18607	1.4	QPSK	3	3	23.48	0	0
	1850.7	18607	1.4	QPSK	6	0	22.35	0-1	1
	1850.7	18607	1.4	16-QAM	1	0	22.74	0-1	1
	1850.7	18607	1.4	16-QAM	1	2	22.69	0-1	1
	1850.7	18607	1.4	16-QAM	1	5	22.78	0-1	1
	1850.7	18607	1.4	16-QAM	3	0	22.21	0-1	1
	1850.7	18607	1.4	16-QAM	3	2	22.21	0-1	1
	1850.7	18607	1.4	16-QAM	3	3	22.18	0-1	1
	1850.7	18607	1.4	16-QAM	6	0	21.34	0-2	2
Mid	1880.0	18900	1.4	QPSK	1	0	23.85	0	0
	1880.0	18900	1.4	QPSK	1	2	23.88	0	0
	1880.0	18900	1.4	QPSK	1	5	23.91	0	0
	1880.0	18900	1.4	QPSK	3	0	23.57	0	0
	1880.0	18900	1.4	QPSK	3	2	23.66	0	0
	1880.0	18900	1.4	QPSK	3	3	23.64	0	0
	1880.0	18900	1.4	QPSK	6	0	22.47	0-1	1
	1880.0	18900	1.4	16-QAM	1	0	22.85	0-1	1
	1880.0	18900	1.4	16-QAM	1	2	22.80	0-1	1
	1880.0	18900	1.4	16-QAM	1	5	22.87	0-1	1
	1880.0	18900	1.4	16-QAM	3	0	22.34	0-1	1
	1880.0	18900	1.4	16-QAM	3	2	22.41	0-1	1
	1880.0	18900	1.4	16-QAM	3	3	22.40	0-1	1
	1880.0	18900	1.4	16-QAM	6	0	21.35	0-2	2
High	1909.3	19193	1.4	QPSK	1	0	23.73	0	0
	1909.3	19193	1.4	QPSK	1	2	23.75	0	0
	1909.3	19193	1.4	QPSK	1	5	23.71	0	0
	1909.3	19193	1.4	QPSK	3	0	23.54	0	0
	1909.3	19193	1.4	QPSK	3	2	23.60	0	0
	1909.3	19193	1.4	QPSK	3	3	23.53	0	0
	1909.3	19193	1.4	QPSK	6	0	22.45	0-1	1
	1909.3	19193	1.4	16-QAM	1	0	22.73	0-1	1
	1909.3	19193	1.4	16-QAM	1	2	22.82	0-1	1
	1909.3	19193	1.4	16-QAM	1	5	22.83	0-1	1
	1909.3	19193	1.4	16-QAM	3	0	22.45	0-1	1
	1909.3	19193	1.4	16-QAM	3	2	22.39	0-1	1
	1909.3	19193	1.4	16-QAM	3	3	22.33	0-1	1
	1909.3	19193	1.4	16-QAM	6	0	21.21	0-2	2

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 60 of 108

Table 9-35

LTE Band 2 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	20.91	0	0
	1860	18700	20	QPSK	1	50	20.87	0	0
	1860	18700	20	QPSK	1	99	20.79	0	0
	1860	18700	20	QPSK	50	0	20.57	0-1	0
	1860	18700	20	QPSK	50	25	20.60	0-1	0
	1860	18700	20	QPSK	50	50	20.54	0-1	0
	1860	18700	20	QPSK	100	0	20.54	0-1	0
	1860	18700	20	16QAM	1	0	20.82	0-1	0
	1860	18700	20	16QAM	1	50	20.83	0-1	0
	1860	18700	20	16QAM	1	99	20.69	0-1	0
	1860	18700	20	16QAM	50	0	20.55	0-2	0
	1860	18700	20	16QAM	50	25	20.59	0-2	0
Mid	1880.0	18900	20	QPSK	1	0	20.87	0	0
	1880.0	18900	20	QPSK	1	50	20.86	0	0
	1880.0	18900	20	QPSK	1	99	20.97	0	0
	1880.0	18900	20	QPSK	50	0	20.50	0-1	0
	1880.0	18900	20	QPSK	50	25	20.57	0-1	0
	1880.0	18900	20	QPSK	50	50	20.64	0-1	0
	1880.0	18900	20	QPSK	100	0	20.55	0-1	0
	1880.0	18900	20	16QAM	1	0	20.72	0-1	0
	1880.0	18900	20	16QAM	1	50	20.71	0-1	0
	1880.0	18900	20	16QAM	1	99	20.75	0-1	0
	1880.0	18900	20	16QAM	50	0	20.66	0-2	0
	1880.0	18900	20	16QAM	50	25	20.61	0-2	0
High	1900	19100	20	QPSK	1	0	20.92	0	0
	1900	19100	20	QPSK	1	50	20.87	0	0
	1900	19100	20	QPSK	1	99	20.91	0	0
	1900	19100	20	QPSK	50	0	20.51	0-1	0
	1900	19100	20	QPSK	50	25	20.57	0-1	0
	1900	19100	20	QPSK	50	50	20.49	0-1	0
	1900	19100	20	QPSK	100	0	20.51	0-1	0
	1900	19100	20	16QAM	1	0	20.68	0-1	0
	1900	19100	20	16QAM	1	50	20.65	0-1	0
	1900	19100	20	16QAM	1	99	20.71	0-1	0
	1900	19100	20	16QAM	50	0	20.62	0-2	0
	1900	19100	20	16QAM	50	25	20.56	0-2	0
	1900	19100	20	16QAM	50	50	20.59	0-2	0
	1900	19100	20	16QAM	100	0	20.58	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 61 of 108

Table 9-36

LTE Band 2 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	20.64	0	0
	1857.5	18675	15	QPSK	1	36	20.70	0	0
	1857.5	18675	15	QPSK	1	74	20.72	0	0
	1857.5	18675	15	QPSK	36	0	20.55	0-1	0
	1857.5	18675	15	QPSK	36	18	20.54	0-1	0
	1857.5	18675	15	QPSK	36	37	20.55	0-1	0
	1857.5	18675	15	QPSK	75	0	20.46	0-1	0
	1857.5	18675	15	16QAM	1	0	21.00	0-1	0
	1857.5	18675	15	16QAM	1	36	20.90	0-1	0
	1857.5	18675	15	16QAM	1	74	20.96	0-1	0
	1857.5	18675	15	16QAM	36	0	20.60	0-2	0
	1857.5	18675	15	16QAM	36	18	20.53	0-2	0
	1857.5	18675	15	16QAM	36	37	20.56	0-2	0
	1857.5	18675	15	16QAM	75	0	20.50	0-2	0
Mid	1880.0	18900	15	QPSK	1	0	20.68	0	0
	1880.0	18900	15	QPSK	1	36	20.68	0	0
	1880.0	18900	15	QPSK	1	74	20.82	0	0
	1880.0	18900	15	QPSK	36	0	20.64	0-1	0
	1880.0	18900	15	QPSK	36	18	20.64	0-1	0
	1880.0	18900	15	QPSK	36	37	20.66	0-1	0
	1880.0	18900	15	QPSK	75	0	20.56	0-1	0
	1880.0	18900	15	16QAM	1	0	20.88	0-1	0
	1880.0	18900	15	16QAM	1	36	20.89	0-1	0
	1880.0	18900	15	16QAM	1	74	20.93	0-1	0
	1880.0	18900	15	16QAM	36	0	20.57	0-2	0
	1880.0	18900	15	16QAM	36	18	20.51	0-2	0
	1880.0	18900	15	16QAM	36	37	20.59	0-2	0
	1880.0	18900	15	16QAM	75	0	20.56	0-2	0
High	1902.5	19125	15	QPSK	1	0	20.67	0	0
	1902.5	19125	15	QPSK	1	36	20.56	0	0
	1902.5	19125	15	QPSK	1	74	20.56	0	0
	1902.5	19125	15	QPSK	36	0	20.43	0-1	0
	1902.5	19125	15	QPSK	36	18	20.41	0-1	0
	1902.5	19125	15	QPSK	36	37	20.42	0-1	0
	1902.5	19125	15	QPSK	75	0	20.38	0-1	0
	1902.5	19125	15	16QAM	1	0	20.63	0-1	0
	1902.5	19125	15	16QAM	1	36	20.56	0-1	0
	1902.5	19125	15	16QAM	1	74	20.55	0-1	0
	1902.5	19125	15	16QAM	36	0	20.52	0-2	0
	1902.5	19125	15	16QAM	36	18	20.47	0-2	0
	1902.5	19125	15	16QAM	36	37	20.45	0-2	0
	1902.5	19125	15	16QAM	75	0	20.42	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 62 of 108

Table 9-37

LTE Band 2 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	20.64	0	0
	1855	18650	10	QPSK	1	25	20.66	0	0
	1855	18650	10	QPSK	1	49	20.68	0	0
	1855	18650	10	QPSK	25	0	20.43	0-1	0
	1855	18650	10	QPSK	25	12	20.53	0-1	0
	1855	18650	10	QPSK	25	25	20.57	0-1	0
	1855	18650	10	QPSK	50	0	20.49	0-1	0
	1855	18650	10	16QAM	1	0	20.87	0-1	0
	1855	18650	10	16QAM	1	25	20.89	0-1	0
	1855	18650	10	16QAM	1	49	20.91	0-1	0
	1855	18650	10	16QAM	25	0	20.59	0-2	0
	1855	18650	10	16QAM	25	12	20.55	0-2	0
Mid	1880.0	18900	10	QPSK	1	0	20.85	0	0
	1880.0	18900	10	QPSK	1	25	20.79	0	0
	1880.0	18900	10	QPSK	1	49	20.84	0	0
	1880.0	18900	10	QPSK	25	0	20.53	0-1	0
	1880.0	18900	10	QPSK	25	12	20.58	0-1	0
	1880.0	18900	10	QPSK	25	25	20.65	0-1	0
	1880.0	18900	10	QPSK	50	0	20.57	0-1	0
	1880.0	18900	10	16QAM	1	0	20.82	0-1	0
	1880.0	18900	10	16QAM	1	25	20.67	0-1	0
	1880.0	18900	10	16QAM	1	49	20.76	0-1	0
	1880.0	18900	10	16QAM	25	0	20.56	0-2	0
	1880.0	18900	10	16QAM	25	12	20.59	0-2	0
High	1905	19150	10	QPSK	1	0	20.79	0	0
	1905	19150	10	QPSK	1	25	20.81	0	0
	1905	19150	10	QPSK	1	49	20.78	0	0
	1905	19150	10	QPSK	25	0	20.52	0-1	0
	1905	19150	10	QPSK	25	12	20.53	0-1	0
	1905	19150	10	QPSK	25	25	20.54	0-1	0
	1905	19150	10	QPSK	50	0	20.53	0-1	0
	1905	19150	10	16QAM	1	0	20.33	0-1	0
	1905	19150	10	16QAM	1	25	20.27	0-1	0
	1905	19150	10	16QAM	1	49	20.27	0-1	0
	1905	19150	10	16QAM	25	0	20.57	0-2	0
	1905	19150	10	16QAM	25	12	20.66	0-2	0
	1905	19150	10	16QAM	25	25	20.65	0-2	0
	1905	19150	10	16QAM	50	0	20.58	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 63 of 108

Table 9-38

LTE Band 2 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	20.63	0	0
	1852.5	18625	5	QPSK	1	12	20.55	0	0
	1852.5	18625	5	QPSK	1	24	20.59	0	0
	1852.5	18625	5	QPSK	12	0	20.59	0-1	0
	1852.5	18625	5	QPSK	12	6	20.59	0-1	0
	1852.5	18625	5	QPSK	12	13	20.53	0-1	0
	1852.5	18625	5	QPSK	25	0	20.54	0-1	0
	1852.5	18625	5	16-QAM	1	0	20.93	0-1	0
	1852.5	18625	5	16-QAM	1	12	20.97	0-1	0
	1852.5	18625	5	16-QAM	1	24	20.99	0-1	0
	1852.5	18625	5	16-QAM	12	0	20.45	0-2	0
	1852.5	18625	5	16-QAM	12	6	20.42	0-2	0
Mid	1852.5	18625	5	16-QAM	12	13	20.44	0-2	0
	1852.5	18625	5	16-QAM	25	0	20.46	0-2	0
	1880.0	18900	5	QPSK	1	0	20.80	0	0
	1880.0	18900	5	QPSK	1	12	20.83	0	0
	1880.0	18900	5	QPSK	1	24	20.90	0	0
	1880.0	18900	5	QPSK	12	0	20.53	0-1	0
	1880.0	18900	5	QPSK	12	6	20.54	0-1	0
	1880.0	18900	5	QPSK	12	13	20.62	0-1	0
	1880.0	18900	5	QPSK	25	0	20.53	0-1	0
	1880.0	18900	5	16-QAM	1	0	20.52	0-1	0
	1880.0	18900	5	16-QAM	1	12	20.51	0-1	0
	1880.0	18900	5	16-QAM	1	24	20.52	0-1	0
High	1880.0	18900	5	16-QAM	12	0	20.62	0-2	0
	1880.0	18900	5	16-QAM	12	6	20.63	0-2	0
	1880.0	18900	5	16-QAM	12	13	20.71	0-2	0
	1880.0	18900	5	16-QAM	25	0	20.62	0-2	0
	1907.5	19175	5	QPSK	1	0	20.61	0	0
	1907.5	19175	5	QPSK	1	12	20.65	0	0
	1907.5	19175	5	QPSK	1	24	20.67	0	0
	1907.5	19175	5	QPSK	12	0	20.48	0-1	0
	1907.5	19175	5	QPSK	12	6	20.54	0-1	0
	1907.5	19175	5	QPSK	12	13	20.49	0-1	0
	1907.5	19175	5	QPSK	25	0	20.48	0-1	0
	1907.5	19175	5	16-QAM	1	0	20.74	0-1	0
	1907.5	19175	5	16-QAM	1	12	20.67	0-1	0
	1907.5	19175	5	16-QAM	1	24	20.72	0-1	0
	1907.5	19175	5	16-QAM	12	0	20.45	0-2	0
	1907.5	19175	5	16-QAM	12	6	20.52	0-2	0
	1907.5	19175	5	16-QAM	12	13	20.51	0-2	0
	1907.5	19175	5	16-QAM	25	0	20.51	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 64 of 108

Table 9-39

LTE Band 2 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	20.70	0	0
	1851.5	18615	3	QPSK	1	7	20.78	0	0
	1851.5	18615	3	QPSK	1	14	20.78	0	0
	1851.5	18615	3	QPSK	8	0	20.46	0-1	0
	1851.5	18615	3	QPSK	8	4	20.49	0-1	0
	1851.5	18615	3	QPSK	8	7	20.54	0-1	0
	1851.5	18615	3	QPSK	15	0	20.48	0-1	0
	1851.5	18615	3	16-QAM	1	0	20.95	0-1	0
	1851.5	18615	3	16-QAM	1	7	20.97	0-1	0
	1851.5	18615	3	16-QAM	1	14	20.90	0-1	0
	1851.5	18615	3	16-QAM	8	0	20.42	0-2	0
	1851.5	18615	3	16-QAM	8	4	20.46	0-2	0
Mid	1880.0	18900	3	QPSK	1	0	20.75	0	0
	1880.0	18900	3	QPSK	1	7	20.85	0	0
	1880.0	18900	3	QPSK	1	14	20.86	0	0
	1880.0	18900	3	QPSK	8	0	20.55	0-1	0
	1880.0	18900	3	QPSK	8	4	20.59	0-1	0
	1880.0	18900	3	QPSK	8	7	20.54	0-1	0
	1880.0	18900	3	QPSK	15	0	20.57	0-1	0
	1880.0	18900	3	16-QAM	1	0	20.81	0-1	0
	1880.0	18900	3	16-QAM	1	7	20.72	0-1	0
	1880.0	18900	3	16-QAM	1	14	20.72	0-1	0
	1880.0	18900	3	16-QAM	8	0	20.49	0-2	0
	1880.0	18900	3	16-QAM	8	4	20.54	0-2	0
High	1908.5	19185	3	QPSK	1	0	20.66	0	0
	1908.5	19185	3	QPSK	1	7	20.77	0	0
	1908.5	19185	3	QPSK	1	14	20.67	0	0
	1908.5	19185	3	QPSK	8	0	20.49	0-1	0
	1908.5	19185	3	QPSK	8	4	20.50	0-1	0
	1908.5	19185	3	QPSK	8	7	20.51	0-1	0
	1908.5	19185	3	QPSK	15	0	20.49	0-1	0
	1908.5	19185	3	16-QAM	1	0	20.54	0-1	0
	1908.5	19185	3	16-QAM	1	7	20.48	0-1	0
	1908.5	19185	3	16-QAM	1	14	20.51	0-1	0
	1908.5	19185	3	16-QAM	8	0	20.40	0-2	0
	1908.5	19185	3	16-QAM	8	4	20.42	0-2	0
	1908.5	19185	3	16-QAM	8	7	20.46	0-2	0
	1908.5	19185	3	16-QAM	15	0	20.44	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 65 of 108

Table 9-40

LTE Band 2 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	20.57	0	0
	1850.7	18607	1.4	QPSK	1	2	20.59	0	0
	1850.7	18607	1.4	QPSK	1	5	20.60	0	0
	1850.7	18607	1.4	QPSK	3	0	20.50	0	0
	1850.7	18607	1.4	QPSK	3	2	20.48	0	0
	1850.7	18607	1.4	QPSK	3	3	20.44	0	0
	1850.7	18607	1.4	QPSK	6	0	20.43	0-1	0
	1850.7	18607	1.4	16-QAM	1	0	20.99	0-1	0
	1850.7	18607	1.4	16-QAM	1	2	20.97	0-1	0
	1850.7	18607	1.4	16-QAM	1	5	20.95	0-1	0
	1850.7	18607	1.4	16-QAM	3	0	20.41	0-1	0
	1850.7	18607	1.4	16-QAM	3	2	20.34	0-1	0
	1850.7	18607	1.4	16-QAM	3	3	20.31	0-1	0
	1850.7	18607	1.4	16-QAM	6	0	20.36	0-2	0
Mid	1880.0	18900	1.4	QPSK	1	0	20.83	0	0
	1880.0	18900	1.4	QPSK	1	2	20.89	0	0
	1880.0	18900	1.4	QPSK	1	5	20.91	0	0
	1880.0	18900	1.4	QPSK	3	0	20.59	0	0
	1880.0	18900	1.4	QPSK	3	2	20.60	0	0
	1880.0	18900	1.4	QPSK	3	3	20.56	0	0
	1880.0	18900	1.4	QPSK	6	0	20.57	0-1	0
	1880.0	18900	1.4	16-QAM	1	0	20.56	0-1	0
	1880.0	18900	1.4	16-QAM	1	2	20.64	0-1	0
	1880.0	18900	1.4	16-QAM	1	5	20.95	0-1	0
	1880.0	18900	1.4	16-QAM	3	0	20.41	0-1	0
	1880.0	18900	1.4	16-QAM	3	2	20.41	0-1	0
	1880.0	18900	1.4	16-QAM	3	3	20.34	0-1	0
	1880.0	18900	1.4	16-QAM	6	0	20.47	0-2	0
High	1909.3	19193	1.4	QPSK	1	0	20.65	0	0
	1909.3	19193	1.4	QPSK	1	2	20.69	0	0
	1909.3	19193	1.4	QPSK	1	5	20.68	0	0
	1909.3	19193	1.4	QPSK	3	0	20.52	0	0
	1909.3	19193	1.4	QPSK	3	2	20.48	0	0
	1909.3	19193	1.4	QPSK	3	3	20.43	0	0
	1909.3	19193	1.4	QPSK	6	0	20.43	0-1	0
	1909.3	19193	1.4	16-QAM	1	0	20.61	0-1	0
	1909.3	19193	1.4	16-QAM	1	2	20.38	0-1	0
	1909.3	19193	1.4	16-QAM	1	5	20.34	0-1	0
	1909.3	19193	1.4	16-QAM	3	0	20.42	0-1	0
	1909.3	19193	1.4	16-QAM	3	2	20.51	0-1	0
	1909.3	19193	1.4	16-QAM	3	3	20.45	0-1	0
	1909.3	19193	1.4	16-QAM	6	0	20.40	0-2	0

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 66 of 108

9.3.5

LTE Band 30

Table 9-41

LTE Band 30 Maximum Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	2310.0	27710	10	QPSK	1	0	23.44	0	0
	2310.0	27710	10	QPSK	1	25	23.50	0	0
	2310.0	27710	10	QPSK	1	49	23.49	0	0
	2310.0	27710	10	QPSK	25	0	22.49	0-1	1
	2310.0	27710	10	QPSK	25	12	22.47	0-1	1
	2310.0	27710	10	QPSK	25	25	22.46	0-1	1
	2310.0	27710	10	QPSK	50	0	22.44	0-1	1
	2310.0	27710	10	16QAM	1	0	22.28	0-1	1
	2310.0	27710	10	16QAM	1	25	22.47	0-1	1
	2310.0	27710	10	16QAM	1	49	22.31	0-1	1
	2310.0	27710	10	16QAM	25	0	21.26	0-2	2
	2310.0	27710	10	16QAM	25	12	21.44	0-2	2
	2310.0	27710	10	16QAM	25	25	21.41	0-2	2
	2310.0	27710	10	16QAM	50	0	21.46	0-2	2

Table 9-42

LTE Band 30 Maximum Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Inactive

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	2310.0	27710	5	QPSK	1	0	23.50	0	0
	2310.0	27710	5	QPSK	1	12	23.50	0	0
	2310.0	27710	5	QPSK	1	24	23.50	0	0
	2310.0	27710	5	QPSK	12	0	22.43	0-1	1
	2310.0	27710	5	QPSK	12	6	22.31	0-1	1
	2310.0	27710	5	QPSK	12	13	22.30	0-1	1
	2310.0	27710	5	QPSK	25	0	22.43	0-1	1
	2310.0	27710	5	16-QAM	1	0	22.46	0-1	1
	2310.0	27710	5	16-QAM	1	12	22.41	0-1	1
	2310.0	27710	5	16-QAM	1	24	22.43	0-1	1
	2310.0	27710	5	16-QAM	12	0	21.23	0-2	2
	2310.0	27710	5	16-QAM	12	6	21.16	0-2	2
	2310.0	27710	5	16-QAM	12	13	21.19	0-2	2
	2310.0	27710	5	16-QAM	25	0	21.31	0-2	2

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 67 of 108

Table 9-43

LTE Band 30 Reduced Conducted Powers - 10 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	2310.0	27710	10	QPSK	1	0	22.29	0	0
	2310.0	27710	10	QPSK	1	25	22.50	0	0
	2310.0	27710	10	QPSK	1	49	22.39	0	0
	2310.0	27710	10	QPSK	25	0	22.32	0-1	0
	2310.0	27710	10	QPSK	25	12	22.26	0-1	0
	2310.0	27710	10	QPSK	25	25	22.19	0-1	0
	2310.0	27710	10	QPSK	50	0	22.20	0-1	0
	2310.0	27710	10	16QAM	1	0	22.40	0-1	0
	2310.0	27710	10	16QAM	1	25	22.49	0-1	0
	2310.0	27710	10	16QAM	1	49	22.50	0-1	0
	2310.0	27710	10	16QAM	25	0	21.28	0-2	1
	2310.0	27710	10	16QAM	25	12	21.34	0-2	1
	2310.0	27710	10	16QAM	25	25	21.25	0-2	1
	2310.0	27710	10	16QAM	50	0	21.31	0-2	1

Table 9-44

LTE Band 30 Reduced Conducted Powers - 5 MHz Bandwidth- Representing Hotspot Mode Active

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	2310.0	27710	5	QPSK	1	0	22.47	0	0
	2310.0	27710	5	QPSK	1	12	22.46	0	0
	2310.0	27710	5	QPSK	1	24	22.50	0	0
	2310.0	27710	5	QPSK	12	0	22.44	0-1	0
	2310.0	27710	5	QPSK	12	6	22.38	0-1	0
	2310.0	27710	5	QPSK	12	13	22.33	0-1	0
	2310.0	27710	5	QPSK	25	0	22.41	0-1	0
	2310.0	27710	5	16-QAM	1	0	22.36	0-1	0
	2310.0	27710	5	16-QAM	1	12	22.50	0-1	0
	2310.0	27710	5	16-QAM	1	24	22.32	0-1	0
	2310.0	27710	5	16-QAM	12	0	21.28	0-2	1
	2310.0	27710	5	16-QAM	12	6	21.22	0-2	1
	2310.0	27710	5	16-QAM	12	13	21.18	0-2	1
	2310.0	27710	5	16-QAM	25	0	21.34	0-2	1

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 68 of 108

9.3.6 LTE Carrier Aggregation Maximum Conducted Powers

Table 9-45

LTE Carrier Aggregation Maximum Conducted Powers – Band 4 (PCC) 5 MHz + Band 17 (SCC) 10 MHz BW

Band 4 (PCC) 5 MHz + Band 17 (SCC), 10 MHz				
1752.5 MHz / ch.20375 + 740 MHz / ch. 5790	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	12	23.82	24.00

Table 9-46

LTE Carrier Aggregation Maximum Conducted Powers – Band 2 (PCC) 5 MHz + Band 17 (SCC) 10 MHz BW

Band 2 (PCC) 5 MHz+ Band 17 (SCC), 10 MHz				
1880 MHz / ch.18900 + 740 MHz / ch. 5790	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	24	23.91	24.00

Table 9-47

LTE Carrier Aggregation Maximum Conducted Powers – Band 17 (PCC) 5 MHz + Band 2 (SCC) 10 MHz BW

Band 17 (PCC) 5 MHz + Band 2 (SCC), 10 MHz				
706.5 MHz / ch.23755 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B17 Rel. 8 Tx.Power (dBm)
	1	0	23.88	24.00

Table 9-48

LTE Carrier Aggregation Maximum Conducted Powers – Band 2 (PCC) 20 MHz + Band 29 (SCC) 10 MHz BW

Band 2 (PCC) 20 MHz+ Band 29 (SCC), 10 MHz				
1900 MHz / ch.19100 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	23.90	24.00

Table 9-49

LTE Carrier Aggregation Maximum Conducted Powers – Band 4 (PCC) 20 MHz + Band 29 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 29 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	23.87	24.00

Table 9-50

LTE Carrier Aggregation Maximum Conducted Powers – Band 2 (PCC) 20 MHz + Band 5 (SCC) 10 MHz BW

Band 2 (PCC) 20 MHz+ Band 5 (SCC), 10 MHz				
1900 MHz / ch.19100 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	23.99	24.00

Table 9-51

LTE Carrier Aggregation Maximum Conducted Powers – Band 5 (PCC) 10 MHz + Band 2 (SCC) 20 MHz BW

Band 5 (PCC) 10 MHz + Band 2 (SCC), 20 MHz				
836.5 MHz / ch.20525 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	24.36	24.47

Table 9-52

LTE Carrier Aggregation Maximum Conducted Powers – Band 4 (PCC) 20 MHz + Band 5 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 5 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	23.82	24.00

Table 9-53

LTE Carrier Aggregation Maximum Conducted Powers – Band 5 (PCC) 10 MHz + Band 4 (SCC) 20 MHz BW

Band 5 (PCC) 10 MHz + Band 4 (SCC), 20 MHz				
836.5 MHz / ch.20525 + 2132.5 MHz / ch.2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	24.49	24.47

FCC ID: A3LSMG920A			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset			Page 69 of 108

Table 9-54

LTE Carrier Aggregation Maximum Conducted Powers – Band 2 (PCC) 20 MHz + Band 12 (SCC) 10 MHz BW

Band 2 (PCC) 20 MHz+ Band 12 (SCC), 10 MHz				
1900 MHz / ch.19100 + 737.5 MHz / ch. 5095	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	23.81	24.00

Table 9-55

LTE Carrier Aggregation Maximum Conducted Powers – Band 12 (PCC) 5 MHz + Band 2 (SCC) 20 MHz BW

Band 12 (PCC) 5 MHz+ Band 2 (SCC), 20 MHz				
701.5 MHz / ch.23035 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B12 Rel. 8 Tx.Power (dBm)
	1	0	23.99	24.00

Table 9-56

LTE Carrier Aggregation Maximum Conducted Powers – Band 4 (PCC) 20 MHz + Band 12 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 12 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 737.5 MHz / ch. 5095	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	23.88	24.00

Table 9-57

LTE Carrier Aggregation Maximum Conducted Powers – Band 2 (PCC) 20 MHz + Band 30 (SCC) 10 MHz BW

Band 2 (PCC) 20 MHz+ Band 30 (SCC), 10 MHz				
1900 MHz / ch.19100 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	23.96	24.00

Table 9-58

LTE Carrier Aggregation Maximum Conducted Powers – Band 30 (PCC) 10 MHz + Band 2 (SCC) 20 MHz BW

Band 30 (PCC) 10 MHz+ Band 2 (SCC), 20 MHz				
2310.0 MHz / ch.27710 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	23.44	23.50

Table 9-59

LTE Carrier Aggregation Maximum Conducted Powers – Band 4 (PCC) 20 MHz + Band 30 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 30 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	23.83	24.00

Table 9-60

LTE Carrier Aggregation Maximum Conducted Powers – Band 30 (PCC) 10 MHz + Band 4 (SCC) 20 MHz BW

Band 30 (PCC) 10 MHz+ Band 4 (SCC), 20 MHz				
2310.0 MHz / ch.27710 + 2132.5 MHz / ch.2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	23.36	23.50

Table 9-61

LTE Carrier Aggregation Maximum Conducted Powers – Band 5 (PCC) 10 MHz + Band 30 (SCC) 10 MHz BW

Band 5 (PCC) 10 MHz+ Band 30 (SCC), 10 MHz				
836.5 MHz / ch.20525 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	24.41	24.47

Table 9-62

LTE Carrier Aggregation Maximum Conducted Powers – Band 30 (PCC) 10 MHz + Band 5 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 5 (SCC), 10 MHz				
2310 MHz / ch. 27710 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	23.43	23.50

Table 9-63

LTE Carrier Aggregation Maximum Conducted Powers – Band 12 (PCC) 5 MHz + Band 30 (SCC) 10 MHz BW

Band 12 (PCC) 5 MHz+ Band 30 (SCC), 10 MHz				
701.5 MHz / ch.23035 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B12 Rel. 8 Tx.Power (dBm)
	1	0	23.96	24.00

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 70 of 108

Table 9-64

LTE Carrier Aggregation Maximum Conducted Powers – Band 30 (PCC) 10 MHz + Band 12 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 12 (SCC), 10 MHz				
2310 MHz / ch.27710 + 737.5 MHz / ch. 5095	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	23.40	23.50

Table 9-65

LTE Carrier Aggregation Maximum Conducted Powers – Band 30 (PCC) 10 MHz + Band 29 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 29 (SCC), 10 MHz				
2310 MHz / ch.27710 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	23.44	23.50

9.3.7 LTE Carrier Aggregation Reduced Conducted Powers

Table 9-66

LTE Carrier Aggregation Reduced Conducted Powers – Band 4 (PCC) 10 MHz + Band 17 (SCC) 10 MHz BW

Band 4 (PCC), 10 MHz + Band 17 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 740 MHz / ch. 5790	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	25	20.98	20.90

Table 9-67

LTE Carrier Aggregation Reduced Conducted Powers – Band 2 (PCC) 5 MHz + Band 17 (SCC) 10 MHz BW

Band 2 (PCC) 5 MHz+ Band 17 (SCC), 10 MHz				
1852.5 MHz / ch.18625 + 740 MHz / ch. 5790	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	24	20.87	20.99

Table 9-68

LTE Carrier Aggregation Reduced Conducted Powers – Band 17 (PCC) 5 MHz + Band 2 (SCC) 10 MHz BW

Band 17 (PCC), 5 MHz + Band 2 (SCC), 10 MHz				
706.5 / ch. 23755 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B17 Rel. 8 Tx.Power (dBm)
	1	12	23.40	23.49

Table 9-69

LTE Carrier Aggregation Reduced Conducted Powers – Band 2 (PCC) 15 MHz + Band 29 (SCC) 10 MHz BW

Band 2 (PCC) 15 MHz+ Band 29 (SCC), 10 MHz				
1857.5 MHz / ch.18675 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	0	20.99	21.00

Table 9-70

LTE Carrier Aggregation Reduced Conducted Powers – Band 4 (PCC) 20 MHz + Band 29 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 29 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	20.94	20.91

Table 9-71

LTE Carrier Aggregation Reduced Conducted Powers – Band 2 (PCC) 15 MHz + Band 5 (SCC) 10 MHz BW

Band 2 (PCC) 15 MHz+ Band 5 (SCC), 10 MHz				
1857.5 MHz / ch.18675 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	20.87	20.97

Table 9-72

LTE Carrier Aggregation Reduced Conducted Powers – Band 5 (PCC) 5 MHz + Band 2 (SCC) 20 MHz BW

Band 5 (PCC) 5 MHz + Band 2 (SCC), 20 MHz				
836.5 MHz / ch.20525 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	23.32	23.50

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 71 of 108

Table 9-73

LTE Carrier Aggregation Reduced Conducted Powers – Band 4 (PCC) 20 MHz + Band 5 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 5 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	20.90	20.91

Table 9-74

LTE Carrier Aggregation Reduced Conducted Powers – Band 5 (PCC) 5 MHz + Band 4 (SCC) 20 MHz BW

Band 5 (PCC) 5 MHz+ Band 4 (SCC), 20 MHz				
836.5 MHz / ch.20525 + 2132.5 MHz / ch.2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	23.41	23.50

Table 9-75

LTE Carrier Aggregation Reduced Conducted Powers – Band 2 (PCC) 15 MHz + Band 12 (SCC) 10 MHz BW

Band 2 (PCC) 15 MHz+ Band 12 (SCC), 10 MHz				
1857.5 MHz / ch.18675 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	20.88	21.00

Table 9-76

LTE Carrier Aggregation Reduced Conducted Powers – Band 12 (PCC) 5 MHz + Band 2 (SCC) 20 MHz BW

Band 12 (PCC) 5 MHz+ Band 2 (SCC), 20 MHz				
701.5 / ch. 23035 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B12 Rel. 8 Tx.Power (dBm)
	1	12	23.46	23.49

Table 9-77

LTE Carrier Aggregation Reduced Conducted Powers – Band 4 (PCC) 20 MHz + Band 12 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 12 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 737.5 MHz / ch. 5095	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	20.83	20.91

Table 9-78

LTE Carrier Aggregation Reduced Conducted Powers – Band 2 (PCC) 15 MHz + Band 30 (SCC) 10 MHz BW

Band 2 (PCC) 15 MHz+ Band 30 (SCC), 10 MHz				
1857.5 MHz / ch.18675 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B2 Rel. 8 Tx.Power (dBm)
	1	99	20.96	21.00

Table 9-79

LTE Carrier Aggregation Reduced Conducted Powers – Band 30 (PCC) 10 MHz + Band 2 (SCC) 20 MHz BW

Band 30 (PCC) 10 MHz+ Band 2 (SCC), 20 MHz				
2310.0 MHz / ch.27710 + 1960 MHz / ch.900	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	22.36	22.50

Table 9-80

LTE Carrier Aggregation Reduced Conducted Powers – Band 4 (PCC) 20 MHz + Band 30 (SCC) 10 MHz BW

Band 4 (PCC) 20 MHz+ Band 30 (SCC), 10 MHz				
1732.5 MHz / ch.20175 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B4 Rel. 8 Tx.Power (dBm)
	1	50	20.86	20.91

Table 9-81

LTE Carrier Aggregation Reduced Conducted Powers – Band 30 (PCC) 10 MHz + Band 4 (SCC) 20 MHz BW

Band 30 (PCC) 10 MHz+ Band 4 (SCC), 20 MHz				
2310.0 MHz / ch.27710 + 2132.5 MHz / ch.2175	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	22.34	22.50

Table 9-82

LTE Carrier Aggregation Reduced Conducted Powers – Band 5 (PCC) 5 MHz + Band 30 (SCC) 10 MHz BW

Band 5 (PCC) 5 MHz+ Band 30 (SCC), 10 MHz				
836.5 MHz / ch.20525 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B5 Rel. 8 Tx.Power (dBm)
	1	0	23.44	23.50

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 72 of 108

Table 9-83

LTE Carrier Aggregation Reduced Conducted Powers – Band 30 (PCC) 10 MHz + Band 5 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 5 (SCC), 10 MHz				
2310 MHz/ ch. 27710 + 881.5 MHz / ch.2525	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	22.43	22.50

Table 9-84

LTE Carrier Aggregation Reduced Conducted Powers – Band 12 (PCC) 5 MHz + Band 30 (SCC) 10 MHz BW

Band 12 (PCC) 5 MHz+ Band 30 (SCC), 10 MHz				
701.5 / ch. 23035 + 2355 MHz / ch.9820	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B12 Rel. 8 Tx.Power (dBm)
	1	12	23.47	23.49

Table 9-85

LTE Carrier Aggregation Reduced Conducted Powers – Band 30 (PCC) 10 MHz + Band 12 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 12 (SCC), 10 MHz				
2310 MHz / ch.27710 + 737.5 MHz / ch. 5095	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	22.45	22.50

Table 9-86

LTE Carrier Aggregation Reduced Conducted Powers – Band 30 (PCC) 10 MHz + Band 29 (SCC) 10 MHz BW

Band 30 (PCC) 10 MHz+ Band 29 (SCC), 10 MHz				
2310 MHz / ch.27710 + 722.7 MHz / ch. 9717	PCC UL# RB	PCC UL RB Offset	LTE Rel 10 Tx.Power (dBm)	LTE B30 Rel. 8 Tx.Power (dBm)
	1	25	22.38	22.50

Notes:

1. The device does not support all Rel. 10 Carrier Aggregation features due to modem chipset limitation.
2. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. Power measurements were performed with two DL carriers for the Release 8 configuration that had the highest output power (across all bandwidths, channels and RB Configurations) for each band
3. This device only supports inter-band CA with 2 carriers (B4+B17, B2+B17, B17+B2, B2+B29, B4+B29, B2+B5, B5+B2, B4+B5, B5+B4, B2+B12, B12+B2, B4+B12, B2+B30, B30+B2, B4+B30, B30+B4, B5+B30, B30+B5, B12+B30, B30+B12, B30+B29).
4. All control and acknowledge data is sent on uplink channels that operate identical to release 8 specifications.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 73 of 108

9.4 WLAN Conducted Powers

Table 9-47
2.4 GHz Antenna 1 Maximum Average RF Power

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	15.26
2437	6	14.65
2462	11	15.42

Table 9-48
2.4 GHz Antenna 2 Maximum Average RF Power

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	14.72
2437	6	15.13
2462	11	15.41

Table 9-49
2.4 GHz Antenna 1 Reduced Average RF Power – Held-to-Ear

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	14.10
2437	6	13.83
2462	11	14.30

Table 9-50
2.4 GHz Antenna 2 Reduced Average RF Power – Held-to-Ear

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11b
2412	1	13.60
2437	6	13.96
2462	11	14.21

Table 9-51
2.4 GHz MIMO Reduced Average RF Power – Held-to-Ear

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]
		IEEE Transmission Mode
		802.11n
2412	1	12.07
2437	6	11.71
2462	11	12.35

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 74 of 108

Table 9-51
5 GHz Antenna 1 Average RF Power - 20 MHz Bandwidth

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	12.09	12.12	12.21
5200	40	12.08	12.11	12.16
5220	44	11.96	11.97	12.08
5240	48	11.90	12.11	12.21
5260	52	12.15	12.16	12.40
5280	56	12.27	12.23	12.34
5300	60	12.13	12.26	12.19
5320	64	12.19	12.26	12.09
5500	100	12.42	12.49	11.87
5540	108	12.34	12.42	12.45
5580	116	12.42	12.20	12.18
5660	132	12.36	12.22	12.34
5745	149	11.92	11.91	11.84
5825	165	11.94	11.94	11.93

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

Table 9-52
5 GHz Antenna 2 Average RF Power - 20 MHz Bandwidth

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	11.91	11.62	11.70
5200	40	11.83	11.51	11.51
5220	44	11.73	11.56	11.52
5240	48	11.73	11.58	11.51
5260	52	11.89	11.58	11.55
5280	56	11.75	11.42	11.52
5300	60	11.86	11.50	11.50
5320	64	11.94	11.40	11.51
5500	100	11.87	11.55	11.57
5540	108	11.58	11.98	11.98
5580	116	11.64	11.99	11.73
5660	132	12.23	11.85	11.81
5745	149	12.16	11.81	11.73
5825	165	12.12	11.67	11.80

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 75 of 108	

Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-4
Power Measurement Setup for Bandwidths < 50 MHz




Figure 9-5
Power Measurement Setup for Bandwidths > 50 MHz

FCC ID: A3LSMG920A	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 SAMSUNG	Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 76 of 108	

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
01/29/2015	750H	21.7	695	0.878	42.604	0.889	42.227	-1.24%	0.89%
			710	0.893	42.399	0.890	42.149	0.34%	0.59%
			725	0.906	42.221	0.891	42.071	1.68%	0.36%
			740	0.920	42.051	0.893	41.994	3.02%	0.14%
			755	0.935	41.892	0.894	41.916	4.59%	-0.06%
01/31/2015	835H	21.1	820	0.895	41.442	0.899	41.578	-0.44%	-0.33%
			835	0.914	41.238	0.900	41.500	1.56%	-0.63%
			850	0.925	41.020	0.916	41.500	0.98%	-1.16%
01/26/2015	1750H	21.7	1710	1.349	39.410	1.348	40.142	0.07%	-1.82%
			1750	1.392	39.242	1.371	40.079	1.53%	-2.09%
			1790	1.430	39.043	1.394	40.016	2.58%	-2.43%
01/26/2015	1900H	22.1	1850	1.361	38.362	1.400	40.000	-2.79%	-4.10%
			1880	1.391	38.258	1.400	40.000	-0.64%	-4.35%
			1910	1.421	38.116	1.400	40.000	1.50%	-4.71%
02/06/2015	2300H	24.0	2300	1.684	38.687	1.670	39.500	0.84%	-2.06%
			2310	1.696	38.649	1.679	39.480	1.01%	-2.10%
			2320	1.706	38.611	1.687	39.460	1.13%	-2.15%
02/02/2015	2450H	21.9	2401	1.745	38.159	1.756	39.287	-0.63%	-2.87%
			2450	1.797	37.953	1.800	39.200	-0.17%	-3.18%
			2499	1.853	37.796	1.853	39.138	0.00%	-3.43%
01/27/2015	5200H-5800H	21.6	5260	4.600	37.180	4.717	35.917	-2.48%	3.52%
			5300	4.627	37.125	4.758	35.871	-2.75%	3.50%
			5320	4.658	37.090	4.778	35.849	-2.51%	3.46%
			5500	4.847	36.818	4.963	35.643	-2.34%	3.30%
			5580	4.921	36.704	5.045	35.551	-2.46%	3.24%
			5600	4.951	36.628	5.065	35.529	-2.25%	3.09%
			5660	5.022	36.602	5.127	35.460	-2.05%	3.22%

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 77 of 108

Table 10-2
Measured Body Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C°)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
01/29/2015	750B	21.7	695	0.919	54.331	0.959	55.745	-4.17%	-2.54%
			710	0.935	54.216	0.960	55.687	-2.60%	-2.64%
			725	0.949	54.050	0.961	55.629	-1.25%	-2.84%
			740	0.961	53.909	0.963	55.570	-0.21%	-2.99%
			755	0.975	53.734	0.964	55.512	1.14%	-3.20%
01/27/2015	835B	22.3	820	0.972	53.062	0.969	55.258	0.31%	-3.97%
			835	0.984	52.961	0.970	55.200	1.44%	-4.06%
			850	1.004	52.835	0.988	55.154	1.62%	-4.20%
01/28/2015	1750B	22.5	1710	1.409	51.986	1.463	53.537	-3.69%	-2.90%
			1750	1.454	51.870	1.488	53.432	-2.28%	-2.92%
			1790	1.496	51.704	1.514	53.326	-1.19%	-3.04%
01/26/2015	1900B	21.2	1850	1.519	51.381	1.520	53.300	-0.07%	-3.60%
			1880	1.549	51.262	1.520	53.300	1.91%	-3.82%
			1910	1.589	51.162	1.520	53.300	4.54%	-4.01%
01/29/2015	1900B	20.7	1850	1.503	51.538	1.520	53.300	-1.12%	-3.31%
			1880	1.536	51.448	1.520	53.300	1.05%	-3.47%
			1910	1.574	51.350	1.520	53.300	3.55%	-3.66%
02/06/2015	1900B	22.1	1850	1.525	52.464	1.520	53.300	0.33%	-1.57%
			1880	1.555	52.357	1.520	53.300	2.30%	-1.77%
			1910	1.591	52.250	1.520	53.300	4.67%	-1.97%
02/02/2015	2300B	23.5	2300	1.756	53.194	1.809	52.900	-2.93%	0.56%
			2310	1.769	53.142	1.816	52.887	-2.59%	0.48%
			2320	1.780	53.101	1.826	52.873	-2.52%	0.43%
01/26/2015	2450B	23.5	2401	1.931	51.976	1.903	52.765	1.47%	-1.50%
			2450	1.997	51.723	1.950	52.700	2.41%	-1.85%
			2499	2.062	51.582	2.019	52.638	2.13%	-2.01%
01/30/2015	5200B-5800B	20.8	5260	5.540	47.774	5.369	48.933	3.18%	-2.37%
			5300	5.592	47.736	5.416	48.879	3.25%	-2.34%
			5320	5.601	47.596	5.439	48.851	2.98%	-2.57%
			5500	5.863	47.307	5.650	48.607	3.77%	-2.67%
			5580	5.937	47.241	5.743	48.499	3.38%	-2.59%
			5600	5.989	47.154	5.766	48.471	3.87%	-2.72%
			5660	6.049	47.094	5.837	48.390	3.63%	-2.68%
			5745	6.190	46.889	5.936	48.275	4.28%	-2.87%
			5800	6.257	46.878	6.000	48.200	4.28%	-2.74%
			5825	6.302	46.809	6.029	48.166	4.53%	-2.82%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 78 of 108	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
I	750	HEAD	01/29/2015	22.5	21.7	0.100	1054	3209	0.824	8.330	8.240	-1.08%
J	835	HEAD	01/31/2015	23.0	21.1	0.100	4d133	3022	0.932	9.200	9.320	1.30%
J	1750	HEAD	01/26/2015	22.9	21.7	0.100	1008	3022	3.450	36.900	34.500	-6.50%
D	1900	HEAD	01/26/2015	23.5	21.1	0.100	5d149	3263	4.320	40.200	43.200	7.46%
I	2300	HEAD	02/06/2015	23.1	24.0	0.100	1008	3318	4.610	49.900	46.100	-7.62%
G	2450	HEAD	02/02/2015	24.1	23.0	0.100	719	3258	5.070	52.100	50.700	-2.69%
H	5300	HEAD	01/27/2015	24.5	21.6	0.100	1120	3920	8.170	83.400	81.700	-2.04%
H	5500	HEAD	01/27/2015	24.0	21.6	0.100	1120	3920	8.360	84.900	83.600	-1.53%
H	5600	HEAD	01/27/2015	23.3	21.6	0.100	1120	3920	8.430	82.200	84.300	2.55%
D	750	BODY	01/29/2015	24.0	22.0	0.100	1054	3263	0.867	8.640	8.670	0.35%
J	835	BODY	01/27/2015	20.8	22.3	0.100	4d133	3022	0.950	9.350	9.500	1.60%
K	1750	BODY	01/28/2015	23.9	22.1	0.100	1008	3288	3.640	37.600	36.400	-3.19%
J	1900	BODY	01/26/2015	22.4	21.2	0.100	5d149	3022	3.860	40.400	38.600	-4.46%
J	1900	BODY	01/29/2015	23.4	22.6	0.100	5d149	3022	3.740	40.400	37.400	-7.43%
E	1900	BODY	02/06/2015	23.8	22.1	0.100	5d149	3332	4.130	40.400	41.300	2.23%
I	2300	BODY	02/02/2015	24.4	23.5	0.100	1008	3318	4.560	48.100	45.600	-5.20%
I	2450	BODY	01/26/2015	22.5	23.5	0.100	719	3209	5.470	51.800	54.700	5.60%
H	5300	BODY	01/30/2015	22.5	20.8	0.100	1120	3920	7.990	75.800	79.900	5.41%
H	5500	BODY	01/30/2015	22.8	20.8	0.100	1120	3920	8.160	79.200	81.600	3.03%
H	5600	BODY	01/30/2015	23.0	20.8	0.100	1120	3920	8.120	79.400	81.200	2.27%
H	5800	BODY	01/30/2015	23.8	20.8	0.100	1120	3920	7.490	74.400	74.900	0.67%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMG920A	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 79 of 108

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.96	0.04	Right	Cheek	11624	1:8.3	0.190	1.132	0.215	A1
836.60	190	GSM 850	GSM	33.5	32.96	0.02	Right	Tilt	11624	1:8.3	0.097	1.132	0.110	
836.60	190	GSM 850	GSM	33.5	32.96	0.13	Left	Cheek	11624	1:8.3	0.127	1.132	0.144	
836.60	190	GSM 850	GSM	33.5	32.96	-0.10	Left	Tilt	11624	1:8.3	0.079	1.132	0.089	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-2
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.0	24.09	0.09	Right	Cheek	119C8	1:1	0.178	1.233	0.219	A2
836.60	4183	UMTS 850	RMC	25.0	24.09	-0.04	Right	Tilt	119C8	1:1	0.096	1.233	0.118	
836.60	4183	UMTS 850	RMC	25.0	24.09	0.13	Left	Cheek	119C8	1:1	0.114	1.233	0.141	
836.60	4183	UMTS 850	RMC	25.0	24.09	-0.05	Left	Tilt	119C8	1:1	0.076	1.233	0.094	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-3
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.0	29.97	0.03	Right	Cheek	11624	1:8.3	0.089	1.007	0.090	
1880.00	661	GSM 1900	GSM	30.0	29.97	0.02	Right	Tilt	11624	1:8.3	0.074	1.007	0.075	
1880.00	661	GSM 1900	GSM	30.0	29.97	0.00	Left	Cheek	11624	1:8.3	0.164	1.007	0.165	A3
1880.00	661	GSM 1900	GSM	30.0	29.97	0.02	Left	Tilt	11624	1:8.3	0.046	1.007	0.046	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMG920A	PCTEST ENGINEERING LABORATORY, INC. SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: 0Y1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 80 of 108

Table 11-4
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.5	23.46	0.01	Right	Cheek	119C8	1:1	0.226	1.271	0.287	
1880.00	9400	UMTS 1900	RMC	24.5	23.46	0.02	Right	Tilt	119C8	1:1	0.132	1.271	0.168	
1880.00	9400	UMTS 1900	RMC	24.5	23.46	-0.13	Left	Cheek	119C8	1:1	0.386	1.271	0.491	A4
1880.00	9400	UMTS 1900	RMC	24.5	23.46	0.05	Left	Tilt	119C8	1:1	0.116	1.271	0.147	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-5
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.5	23.97	0.03	0	Right	Cheek	QPSK	1	0	1164B	1:1	0.226	1.130	0.255	A5
707.50	23095	Mid	LTE Band 12	10	23.5	22.56	0.06	1	Right	Cheek	QPSK	25	12	1164B	1:1	0.172	1.242	0.214	
707.50	23095	Mid	LTE Band 12	10	24.5	23.97	0.06	0	Right	Tilt	QPSK	1	0	1164B	1:1	0.107	1.130	0.121	
707.50	23095	Mid	LTE Band 12	10	23.5	22.56	0.06	1	Right	Tilt	QPSK	25	12	1164B	1:1	0.080	1.242	0.099	
707.50	23095	Mid	LTE Band 12	10	24.5	23.97	0.05	0	Left	Cheek	QPSK	1	0	1164B	1:1	0.214	1.130	0.242	
707.50	23095	Mid	LTE Band 12	10	23.5	22.56	0.04	1	Left	Cheek	QPSK	25	12	1164B	1:1	0.145	1.242	0.180	
707.50	23095	Mid	LTE Band 12	10	24.5	23.97	0.03	0	Left	Tilt	QPSK	1	0	1164B	1:1	0.124	1.130	0.140	
707.50	23095	Mid	LTE Band 12	10	23.5	22.56	0.04	1	Left	Tilt	QPSK	25	12	1164B	1:1	0.080	1.242	0.099	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-6
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.47	0.14	0	Right	Cheek	QPSK	1	0	11653	1:1	0.159	1.007	0.160	A6
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.07	0.10	1	Right	Cheek	QPSK	25	0	11653	1:1	0.123	1.104	0.136	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.47	0.03	0	Right	Tilt	QPSK	1	0	11653	1:1	0.074	1.007	0.075	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.07	-0.01	1	Right	Tilt	QPSK	25	0	11653	1:1	0.063	1.104	0.070	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.47	-0.08	0	Left	Cheek	QPSK	1	0	11653	1:1	0.129	1.007	0.130	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.07	0.06	1	Left	Cheek	QPSK	25	0	11653	1:1	0.088	1.104	0.097	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.47	0.00	0	Left	Tilt	QPSK	1	0	11653	1:1	0.091	1.007	0.092	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.07	0.10	1	Left	Tilt	QPSK	25	0	11653	1:1	0.065	1.104	0.072	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 81 of 108

Table 11-7
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.00	0.18	0	Right	Cheek	QPSK	1	50	11653	1:1	0.231	1.122	0.259	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	0.04	1	Right	Cheek	QPSK	50	25	11653	1:1	0.172	1.202	0.207	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.00	-0.01	0	Right	Tilt	QPSK	1	50	11653	1:1	0.183	1.122	0.205	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	0.01	1	Right	Tilt	QPSK	50	25	11653	1:1	0.137	1.202	0.165	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.00	-0.06	0	Left	Cheek	QPSK	1	50	11653	1:1	0.352	1.122	0.395	A7
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.03	1	Left	Cheek	QPSK	50	25	11653	1:1	0.254	1.202	0.305	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.00	-0.05	0	Left	Tilt	QPSK	1	50	11653	1:1	0.185	1.122	0.208	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	-0.02	1	Left	Tilt	QPSK	50	25	11653	1:1	0.134	1.202	0.161	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-8
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	24.00	-0.03	0	Right	Cheek	QPSK	1	99	11634	1:1	0.257	1.122	0.288	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.79	0.06	1	Right	Cheek	QPSK	50	25	11634	1:1	0.197	1.178	0.232	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	24.00	0.00	0	Right	Tilt	QPSK	1	99	11634	1:1	0.175	1.122	0.196	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.79	0.00	1	Right	Tilt	QPSK	50	25	11634	1:1	0.145	1.178	0.171	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	24.00	0.06	0	Left	Cheek	QPSK	1	99	11634	1:1	0.389	1.122	0.436	A8
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.79	0.04	1	Left	Cheek	QPSK	50	25	11634	1:1	0.327	1.178	0.385	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	24.00	0.07	0	Left	Tilt	QPSK	1	99	11634	1:1	0.121	1.122	0.136	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.79	0.04	1	Left	Tilt	QPSK	50	25	11634	1:1	0.098	1.178	0.115	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
LTE Band 30 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2310.00	27710	Mid	LTE Band 30	10	23.5	23.50	-0.03	0	Right	Cheek	QPSK	1	25	1164B	1:1	0.193	1.000	0.193	A9
2310.00	27710	Mid	LTE Band 30	10	22.5	22.49	-0.09	1	Right	Cheek	QPSK	25	0	1164B	1:1	0.160	1.002	0.160	
2310.00	27710	Mid	LTE Band 30	10	23.5	23.50	0.04	0	Right	Tilt	QPSK	1	25	1164B	1:1	0.064	1.000	0.064	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.49	0.05	1	Right	Tilt	QPSK	25	0	1164B	1:1	0.050	1.002	0.050	
2310.00	27710	Mid	LTE Band 30	10	23.5	23.50	0.11	0	Left	Cheek	QPSK	1	25	1164B	1:1	0.084	1.000	0.084	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.49	0.10	1	Left	Cheek	QPSK	25	0	1164B	1:1	0.064	1.002	0.064	
2310.00	27710	Mid	LTE Band 30	10	23.5	23.50	0.03	0	Left	Tilt	QPSK	1	25	1164B	1:1	0.093	1.000	0.093	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.49	0.15	1	Left	Tilt	QPSK	25	0	1164B	1:1	0.066	1.002	0.066	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Head									
Spatial Peak										1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 1 gram									

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 82 of 108

**Table 11-10
DTS Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	14.5	14.30	0.06	Right	Cheek	1	119C8	1	99.31	0.334	0.247	1.047	1.007	0.261	
2462	11	802.11b	DSSS	22	14.5	14.30	0.05	Right	Tilt	1	119C8	1	99.31	0.577	0.407	1.047	1.007	0.429	
2462	11	802.11b	DSSS	22	14.5	14.30	-	Left	Cheek	1	119C8	1	99.31	0.246	-	1.047	1.007	-	
2462	11	802.11b	DSSS	22	14.5	14.30	-	Left	Tilt	1	119C8	1	99.31	0.299	-	1.047	1.007	-	
2462	11	802.11b	DSSS	22	14.5	14.21	-	Right	Cheek	2	119C8	1	99.46	0.249	-	1.069	1.005	-	
2462	11	802.11b	DSSS	22	14.5	14.21	-	Right	Tilt	2	119C8	1	99.46	0.150	-	1.069	1.005	-	
2462	11	802.11b	DSSS	22	14.5	14.21	0.07	Left	Cheek	2	119C8	1	99.46	0.806	0.596	1.069	1.005	0.640	A10
2462	11	802.11b	DSSS	22	14.5	14.21	0.20	Left	Tilt	2	119C8	1	99.46	0.603	0.451	1.069	1.005	0.484	
2462	11	802.11n	OFDM	20	12.5	12.35	-	Right	Cheek	MMO	119C8	13	98.41	0.455	-	1.035	1.016	-	
2462	11	802.11n	OFDM	20	12.5	12.35	0.11	Right	Tilt	MMO	119C8	13	98.41	0.512	0.380	1.035	1.016	0.399	
2462	11	802.11n	OFDM	20	12.5	12.35	-	Left	Cheek	MMO	119C8	13	98.41	0.463	-	1.035	1.016	-	
2462	11	802.11n	OFDM	20	12.5	12.35	-	Left	Tilt	MMO	119C8	13	98.41	0.307	-	1.035	1.016	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-11
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g) (W/kg)	Plot #
MHz	Ch.													W/kg	(W/kg)				
5260	52	802.11ac	OFDM	20	12.5	12.40	0.06	Right	Cheek	1	11656	6.5	98.39	0.479	0.182	1.023	1.016	0.189	
5260	52	802.11ac	OFDM	20	12.5	12.40	-	Right	Tilt	1	11656	6.5	98.39	0.455	-	1.023	1.016	-	
5260	52	802.11ac	OFDM	20	12.5	12.40	-	Left	Cheek	1	11656	6.5	98.39	0.284	-	1.023	1.016	-	
5260	52	802.11ac	OFDM	20	12.5	12.40	-	Left	Tilt	1	11656	6.5	98.39	0.190	-	1.023	1.016	-	
5320	64	802.11a	OFDM	20	12.5	11.94	-	Right	Cheek	2	11656	6	99.24	0.076	-	1.138	1.008	-	
5320	64	802.11a	OFDM	20	12.5	11.94	-	Right	Tilt	2	11656	6	99.24	0.079	-	1.138	1.008	-	
5320	64	802.11a	OFDM	20	12.5	11.94	0.12	Left	Cheek	2	11656	6	99.24	0.170	0.076	1.138	1.008	0.087	
5320	64	802.11a	OFDM	20	12.5	11.94	-	Left	Tilt	2	11656	6	99.24	0.154	-	1.138	1.008	-	
5500	100	802.11n	OFDM	20	12.5	12.49	0.11	Right	Cheek	1	11656	6.5	98.89	0.610	0.203	1.002	1.011	0.205	
5500	100	802.11n	OFDM	20	12.5	12.49	-	Right	Tilt	1	11656	6.5	98.89	0.576	-	1.002	1.011	-	
5500	100	802.11n	OFDM	20	12.5	12.49	-	Left	Cheek	1	11656	6.5	98.89	0.337	-	1.002	1.011	-	
5500	100	802.11n	OFDM	20	12.5	12.49	-	Left	Tilt	1	11656	6.5	98.89	0.223	-	1.002	1.011	-	
5580	116	802.11n	OFDM	20	12.5	11.99	-	Right	Cheek	2	11656	6.5	99.32	0.058	-	1.125	1.007	-	
5580	116	802.11n	OFDM	20	12.5	11.99	-	Right	Tilt	2	11656	6.5	99.32	0.053	-	1.125	1.007	-	
5580	116	802.11n	OFDM	20	12.5	11.99	0.12	Left	Cheek	2	11656	6.5	99.32	0.119	0.055	1.125	1.007	0.062	
5580	116	802.11n	OFDM	20	12.5	11.99	-	Left	Tilt	2	11656	6.5	99.32	0.097	-	1.125	1.007	-	
5660	132	802.11a	OFDM	20	12.5	12.36	0.05	Right	Cheek	1	11656	6	98.96	0.600	0.214	1.033	1.011	0.223	A11
5660	132	802.11a	OFDM	20	12.5	12.36	-	Right	Tilt	1	11656	6	98.96	0.588	-	1.033	1.011	-	
5660	132	802.11a	OFDM	20	12.5	12.36	-	Left	Cheek	1	11656	6	98.96	0.333	-	1.033	1.011	-	
5660	132	802.11a	OFDM	20	12.5	12.36	-	Left	Tilt	1	11656	6	98.96	0.260	-	1.033	1.011	-	
5660	132	802.11a	OFDM	20	12.5	12.23	-	Right	Cheek	2	11656	6	99.24	0.055	-	1.064	1.008	-	
5660	132	802.11a	OFDM	20	12.5	12.23	-	Right	Tilt	2	11656	6	99.24	0.046	-	1.064	1.008	-	
5660	132	802.11a	OFDM	20	12.5	12.23	0.08	Left	Cheek	2	11656	6	99.24	0.089	0.044	1.064	1.008	0.047	
5660	132	802.11a	OFDM	20	12.5	12.23	-	Left	Tilt	2	11656	6	99.24	0.077	-	1.064	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 83 of 108

11.2 Standalone Body-Worn SAR Data

Table 11-12
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.96	0.07	15 mm	11624	1	1:8.3	back	0.364	1.132	0.412	A12
836.60	4183	UMTS 850	RMC	25.0	24.09	0.00	15 mm	11656	N/A	1:1	back	0.274	1.233	0.338	A14
1880.00	661	GSM 1900	GSM	30.0	29.97	0.04	15 mm	11634	1	1:8.3	back	0.304	1.007	0.306	A16
1852.40	9262	UMTS 1900	RMC	24.5	23.48	-0.04	15 mm	119C8	N/A	1:1	back	0.708	1.265	0.896	A18
1880.00	9400	UMTS 1900	RMC	24.5	23.46	-0.01	15 mm	119C8	N/A	1:1	back	0.652	1.271	0.829	
1907.60	9538	UMTS 1900	RMC	24.5	23.42	-0.05	15 mm	119C8	N/A	1:1	back	0.589	1.282	0.755	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

Table 11-13
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.5	23.97	0.02	0	1164B	QPSK	1	0	15 mm	back	1:1	0.451	1.130	0.510	A20
707.50	23095	Mid	LTE Band 12	10	23.5	22.56	-0.07	1	1164B	QPSK	25	12	15 mm	back	1:1	0.336	1.242	0.417	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.47	0.05	0	11653	QPSK	1	0	15 mm	back	1:1	0.275	1.007	0.277	A22
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.07	0.01	1	11653	QPSK	25	0	15 mm	back	1:1	0.186	1.104	0.205	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	24.5	24.00	-0.04	0	11653	QPSK	1	50	15 mm	back	1:1	0.857	1.122	0.962	A24
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.70	0.01	1	11653	QPSK	50	25	15 mm	back	1:1	0.637	1.202	0.766	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.5	22.64	-0.06	1	11653	QPSK	100	0	15 mm	back	1:1	0.638	1.219	0.778	
1860.00	18700	Low	LTE Band 2 (PCS)	20	24.5	23.99	-0.01	0	11634	QPSK	1	50	15 mm	back	1:1	0.802	1.125	0.902	A26
1880.00	18900	Mid	LTE Band 2 (PCS)	20	24.5	23.90	-0.02	0	11634	QPSK	1	99	15 mm	back	1:1	0.797	1.148	0.915	
1900.00	19100	High	LTE Band 2 (PCS)	20	24.5	24.00	-0.12	0	11634	QPSK	1	99	15 mm	back	1:1	0.754	1.122	0.846	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.79	-0.03	1	11634	QPSK	50	25	15 mm	back	1:1	0.551	1.178	0.649	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.70	-0.10	1	11634	QPSK	100	0	15 mm	back	1:1	0.616	1.202	0.740	
2310.00	27710	Mid	LTE Band 30	10	23.5	23.50	0.04	0	1164B	QPSK	1	25	15 mm	back	1:1	0.254	1.000	0.254	A28
2310.00	27710	Mid	LTE Band 30	10	22.5	22.49	-0.04	1	1164B	QPSK	25	0	15 mm	back	1:1	0.201	1.002	0.201	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body									
Spatial Peak										1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 1 gram									

Table 11-14
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	15.5	15.42	0.03	10 mm	1	1164B	1	back	99.31	0.051	0.041	1.019	1.007	0.042	
2462	11	802.11b	DSSS	22	15.5	15.41	-0.05	10 mm	2	1164B	1	back	99.46	0.097	0.075	1.021	1.005	0.077	A30
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 84 of 108

Table 11-15
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)	(W/kg)			
5260	52	802.11ac	OFDM	20	12.5	12.40	0.12	10 mm	1	11656	6.5	back	98.39	0.031	0.011	1.023	1.016	0.011	A32
5320	64	802.11a	OFDM	20	12.5	11.94	0.05	10 mm	2	11656	6	back	99.24	0.083	0.032	1.138	1.008	0.036	
5500	100	802.11n	OFDM	20	12.5	12.49	0.05	10 mm	1	11656	6.5	back	98.89	0.052	0.019	1.002	1.011	0.019	
5580	116	802.11n	OFDM	20	12.5	11.99	0.04	10 mm	2	11656	6.5	back	99.32	0.029	0.003	1.125	1.007	0.003	
5660	132	802.11a	OFDM	20	12.5	12.36	0.04	10 mm	1	11656	6	back	98.96	0.023	0.008	1.033	1.011	0.008	
5660	132	802.11a	OFDM	20	12.5	12.23	0.05	10 mm	2	11656	6	back	99.24	0.047	0.015	1.064	1.008	0.016	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram											

11.3 Standalone Wireless Router SAR Data

Table 11-16
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	32.5	32.25	0.01	10 mm	11624	2	1:4.15	back	0.567	1.059	0.600	A13
836.60	190	GSM 850	GPRS	32.5	32.25	0.04	10 mm	11624	2	1:4.15	front	0.461	1.059	0.488	
836.60	190	GSM 850	GPRS	32.5	32.25	-0.01	10 mm	11624	2	1:4.15	bottom	0.306	1.059	0.324	
836.60	190	GSM 850	GPRS	32.5	32.25	-0.03	10 mm	11624	2	1:4.15	right	0.545	1.059	0.577	
836.60	190	GSM 850	GPRS	32.5	32.25	-0.03	10 mm	11624	2	1:4.15	left	0.174	1.059	0.184	
836.60	4183	UMTS 850	RMC	23.5	23.13	0.00	10 mm	11656	N/A	1:1	back	0.338	1.089	0.368	A15
836.60	4183	UMTS 850	RMC	23.5	23.13	-0.01	10 mm	11656	N/A	1:1	front	0.286	1.089	0.311	
836.60	4183	UMTS 850	RMC	23.5	23.13	0.01	10 mm	11656	N/A	1:1	bottom	0.173	1.089	0.188	
836.60	4183	UMTS 850	RMC	23.5	23.13	-0.01	10 mm	11656	N/A	1:1	right	0.338	1.089	0.368	
836.60	4183	UMTS 850	RMC	23.5	23.13	0.05	10 mm	11656	N/A	1:1	left	0.109	1.089	0.119	
1880.00	661	GSM 1900	GPRS	28.0	26.64	-0.05	10 mm	11634	2	1:4.15	back	0.551	1.368	0.754	
1880.00	661	GSM 1900	GPRS	28.0	26.64	-0.10	10 mm	11634	2	1:4.15	front	0.525	1.368	0.718	
1850.20	512	GSM 1900	GPRS	28.0	26.60	0.01	10 mm	11634	2	1:4.15	bottom	0.681	1.380	0.940	
1880.00	661	GSM 1900	GPRS	28.0	26.64	0.06	10 mm	11634	2	1:4.15	bottom	0.746	1.368	1.021	A17
1909.80	810	GSM 1900	GPRS	28.0	26.84	0.08	10 mm	11634	2	1:4.15	bottom	0.707	1.306	0.923	
1880.00	661	GSM 1900	GPRS	28.0	26.64	0.12	10 mm	11634	2	1:4.15	right	0.028	1.368	0.038	
1880.00	661	GSM 1900	GPRS	28.0	26.64	0.02	10 mm	11634	2	1:4.15	left	0.203	1.368	0.278	
1880.00	9400	UMTS 1900	RMC	21.5	21.15	-0.10	10 mm	11656	N/A	1:1	back	0.694	1.084	0.752	
1880.00	9400	UMTS 1900	RMC	21.5	21.15	-0.10	10 mm	11656	N/A	1:1	front	0.703	1.084	0.762	
1852.40	9262	UMTS 1900	RMC	21.5	21.16	0.09	10 mm	11656	N/A	1:1	bottom	0.875	1.081	0.946	
1880.00	9400	UMTS 1900	RMC	21.5	21.15	0.07	10 mm	11656	N/A	1:1	bottom	0.956	1.084	1.036	
1907.60	9538	UMTS 1900	RMC	21.5	21.18	-0.06	10 mm	11656	N/A	1:1	bottom	0.957	1.076	1.030	A19
1880.00	9400	UMTS 1900	RMC	21.5	21.15	-0.18	10 mm	11656	N/A	1:1	right	0.048	1.084	0.052	
1880.00	9400	UMTS 1900	RMC	21.5	21.15	0.04	10 mm	11656	N/A	1:1	left	0.271	1.084	0.294	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 85 of 108	

Table 11-17
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maxium Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	23.5	23.45	0.08	0	11653	QPSK	1	25	10 mm	back	1:1	0.539	1.012	0.545	A21
707.50	23095	Mid	LTE Band 12	10	23.5	23.15	0.05	0	11653	QPSK	25	12	10 mm	back	1:1	0.488	1.084	0.529	
707.50	23095	Mid	LTE Band 12	10	23.5	23.45	-0.02	0	11653	QPSK	1	25	10 mm	front	1:1	0.451	1.012	0.456	
707.50	23095	Mid	LTE Band 12	10	23.5	23.15	-0.05	0	11653	QPSK	25	12	10 mm	front	1:1	0.418	1.084	0.453	
707.50	23095	Mid	LTE Band 12	10	23.5	23.45	0.01	0	11653	QPSK	1	25	10 mm	bottom	1:1	0.232	1.012	0.235	
707.50	23095	Mid	LTE Band 12	10	23.5	23.15	0.12	0	11653	QPSK	25	12	10 mm	bottom	1:1	0.168	1.084	0.182	
707.50	23095	Mid	LTE Band 12	10	23.5	23.45	0.03	0	11653	QPSK	1	25	10 mm	right	1:1	0.270	1.012	0.273	
707.50	23095	Mid	LTE Band 12	10	23.5	23.15	0.00	0	11653	QPSK	25	12	10 mm	right	1:1	0.242	1.084	0.262	
707.50	23095	Mid	LTE Band 12	10	23.5	23.45	0.07	0	11653	QPSK	1	25	10 mm	left	1:1	0.232	1.012	0.235	
707.50	23095	Mid	LTE Band 12	10	23.5	23.15	0.02	0	11653	QPSK	25	12	10 mm	left	1:1	0.216	1.084	0.234	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-18
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
															(W/kg)		(W/kg)		
MHz	Ch.																		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.38	-0.02	0	11653	QPSK	1	25	10 mm	back	1:1	0.374	1.028	0.384	A23
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.03	-0.10	0	11653	QPSK	25	0	10 mm	back	1:1	0.263	1.114	0.293	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.38	-0.02	0	11653	QPSK	1	25	10 mm	front	1:1	0.309	1.028	0.318	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.03	0.02	0	11653	QPSK	25	0	10 mm	front	1:1	0.216	1.114	0.241	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.38	-0.12	0	11653	QPSK	1	25	10 mm	bottom	1:1	0.200	1.028	0.206	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.03	-0.10	0	11653	QPSK	25	0	10 mm	bottom	1:1	0.142	1.114	0.158	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.38	0.09	0	11653	QPSK	1	25	10 mm	right	1:1	0.360	1.028	0.370	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.03	-0.02	0	11653	QPSK	25	0	10 mm	right	1:1	0.268	1.114	0.299	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.38	0.00	0	11653	QPSK	1	25	10 mm	left	1:1	0.135	1.028	0.139	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.5	23.03	0.05	0	11653	QPSK	25	0	10 mm	left	1:1	0.107	1.114	0.119	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-19
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	-0.04	0	11634	QPSK	1	50	10 mm	back	1:1	0.645	1.021	0.659	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.75	-0.03	0	11634	QPSK	50	25	10 mm	back	1:1	0.636	1.059	0.674	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	-0.03	0	11634	QPSK	1	50	10 mm	front	1:1	0.644	1.021	0.658	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.75	-0.01	0	11634	QPSK	50	25	10 mm	front	1:1	0.634	1.059	0.671	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	0.01	0	11634	QPSK	1	50	10 mm	bottom	1:1	0.934	1.021	0.954	A25
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.75	0.01	0	11634	QPSK	50	25	10 mm	bottom	1:1	0.921	1.059	0.975	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.67	-0.02	0	11634	QPSK	100	0	10 mm	bottom	1:1	0.903	1.079	0.974	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	0.06	0	11634	QPSK	1	50	10 mm	right	1:1	0.071	1.021	0.072	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.75	0.01	0	11634	QPSK	50	25	10 mm	right	1:1	0.071	1.059	0.075	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	0.05	0	11634	QPSK	1	50	10 mm	left	1:1	0.191	1.021	0.195	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.75	0.01	0	11634	QPSK	50	25	10 mm	left	1:1	0.180	1.059	0.191	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	21.0	20.91	-0.04	0	11634	QPSK	1	50	10 mm	bottom	1:1	0.876	1.021	0.894	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																			

Note: Blue entry represents variability measurement

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 86 of 108	

Table 11-20
LTE Band 2 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	-0.03	0	11634	QPSK	1	99	10 mm	back	1:1	0.764	1.007	0.769	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.64	-0.02	0	11634	QPSK	50	50	10 mm	back	1:1	0.714	1.086	0.775	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	0.04	0	11634	QPSK	1	99	10 mm	front	1:1	0.683	1.007	0.688	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.64	0.05	0	11634	QPSK	50	50	10 mm	front	1:1	0.631	1.086	0.685	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.0	20.91	-0.08	0	11634	QPSK	1	0	10 mm	bottom	1:1	0.866	1.021	0.884	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	0.01	0	11634	QPSK	1	99	10 mm	bottom	1:1	0.982	1.007	0.989	A27
1900.00	19100	High	LTE Band 2 (PCS)	20	21.0	20.92	-0.03	0	11634	QPSK	1	0	10 mm	bottom	1:1	0.941	1.019	0.959	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.0	20.60	-0.10	0	11634	QPSK	50	25	10 mm	bottom	1:1	0.831	1.096	0.911	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.64	-0.03	0	11634	QPSK	50	50	10 mm	bottom	1:1	0.855	1.086	0.929	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.0	20.57	-0.07	0	11634	QPSK	50	25	10 mm	bottom	1:1	0.903	1.104	0.997	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.55	-0.08	0	11634	QPSK	100	0	10 mm	bottom	1:1	0.894	1.109	0.991	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	0.13	0	11634	QPSK	1	99	10 mm	right	1:1	0.046	1.007	0.046	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.64	-0.01	0	11634	QPSK	50	50	10 mm	right	1:1	0.039	1.086	0.042	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	0.11	0	11634	QPSK	1	99	10 mm	left	1:1	0.276	1.007	0.278	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.64	0.02	0	11634	QPSK	50	50	10 mm	left	1:1	0.265	1.086	0.288	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.0	20.97	-0.02	0	11634	QPSK	1	99	10 mm	bottom	1:1	0.856	1.007	0.862	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak								Body 1.6 W/kg (mW/g) averaged over 1 gram											
Uncontrolled Exposure/General Population																			

Note: Blue entry represents variability measurement

Table 11-21
LTE Band 30 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														[W/kg]		[W/kg]		
2310.00	27710	Mid	LTE Band 30	10	22.5	22.50	-0.01	0	1164B	QPSK	1	25	10 mm	back	1:1	0.496	1.000	0.496	A29
2310.00	27710	Mid	LTE Band 30	10	22.5	22.32	0.00	0	1164B	QPSK	25	0	10 mm	back	1:1	0.367	1.042	0.382	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.50	-0.06	0	1164B	QPSK	1	25	10 mm	front	1:1	0.237	1.000	0.237	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.32	-0.03	0	1164B	QPSK	25	0	10 mm	front	1:1	0.226	1.042	0.235	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.50	-0.15	0	1164B	QPSK	1	25	10 mm	bottom	1:1	0.044	1.000	0.044	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.32	-0.11	0	1164B	QPSK	25	0	10 mm	bottom	1:1	0.047	1.042	0.049	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.50	-0.15	0	1164B	QPSK	1	25	10 mm	right	1:1	0.084	1.000	0.084	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.32	-0.12	0	1164B	QPSK	25	0	10 mm	right	1:1	0.086	1.042	0.090	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.50	0.06	0	1164B	QPSK	1	25	10 mm	left	1:1	0.006	1.000	0.006	
2310.00	27710	Mid	LTE Band 30	10	22.5	22.32	0.15	0	1164B	QPSK	25	0	10 mm	left	1:1	0.006	1.042	0.006	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 87 of 108	

Table 11-22
WLAN Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Scaled SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	15.5	15.42	-	10 mm	1	1164B	1	back	99.31	0.051	-	1.019	1.007	-	
2462	11	802.11b	DSSS	22	15.5	15.42	-	10 mm	1	1164B	1	front	99.31	0.078	-	1.019	1.007	-	
2462	11	802.11b	DSSS	22	15.5	15.42	-0.07	10 mm	1	1164B	1	top	99.31	0.145	0.114	1.019	1.007	0.117	A31
2462	11	802.11b	DSSS	22	15.5	15.42	-	10 mm	1	1164B	1	left	99.31	0.059	-	1.019	1.007	-	
2462	11	802.11b	DSSS	22	15.5	15.41	-	10 mm	2	1164B	1	back	99.46	0.097	-	1.021	1.005	-	
2462	11	802.11b	DSSS	22	15.5	15.41	0.17	10 mm	2	1164B	1	front	99.46	0.124	0.093	1.021	1.005	0.095	
2462	11	802.11b	DSSS	22	15.5	15.41	-	10 mm	2	1164B	1	top	99.46	0.026	-	1.021	1.005	-	
2462	11	802.11b	DSSS	22	15.5	15.41	-	10 mm	2	1164B	1	right	99.46	0.029	-	1.021	1.005	-	
5825	165	802.11a	OFDM	20	12.5	11.94	-	10 mm	1	11656	6	back	98.96	0.115	-	1.138	1.011	-	
5825	165	802.11a	OFDM	20	12.5	11.94	-0.07	10 mm	1	11656	6	front	98.96	0.132	0.053	1.138	1.011	0.061	A33
5825	165	802.11a	OFDM	20	12.5	11.94	-	10 mm	1	11656	6	top	98.96	0.019	-	1.138	1.011	-	
5825	165	802.11a	OFDM	20	12.5	11.94	-	10 mm	1	11656	6	left	98.96	0.026	-	1.138	1.011	-	
5745	149	802.11a	OFDM	20	12.5	12.16	0.05	10 mm	2	11656	6	back	99.24	0.043	0.012	1.081	1.008	0.013	
5745	149	802.11a	OFDM	20	12.5	12.16	-	10 mm	2	11656	6	front	99.24	0.015	-	1.081	1.008	-	
5745	149	802.11a	OFDM	20	12.5	12.16	-	10 mm	2	11656	6	top	99.24	0.009	-	1.081	1.008	-	
5745	149	802.11a	OFDM	20	12.5	12.16	-	10 mm	2	11656	6	right	99.24	0.011	-	1.081	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

11.4 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance. A test separation distance of 10 mm for Body-worn SAR was used for 2.4/5 GHz WLAN as it is more conservative.
- Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was activated (See Section 6.7 for more details).
- This device utilizes power reduction for UMTS 850/1900 and LTE Band 12/17/5/4/2/30 under some portable hotspot conditions for SAR compliance. Therefore, these wireless router configurations were tested at reduced output power levels.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 88 of 108

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r03. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r01, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 89 of 108	

3. Justification for test configurations for WLAN per KDB Publication 248227 D01DR02-41929 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
4. Per KDB Publication 248227 D01DR02-41929, MIMO SAR was measured with both antennas transmitting simultaneously at the specified maximum output power in MIMO mode following the initial test configuration procedures for 2.4 GHz head SAR. Per KDB Publication 248227 D01DR02-41929, SAR for MIMO for all other bands and exposure conditions was evaluated by following the simultaneous SAR provisions from KDB Publication 447498. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
6. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
7. Only channels in the U-NII-2C > 5.65 GHz and U-NII-3 aggregate band that support wireless router were considered for hotspot SAR testing.
8. For SAR compliance, this device always uses power reduction when the device is in a held-to-ear RF exposure condition with 2.4 GHz WIFI data modes. Therefore, WIFI head SAR was evaluated at reduced power levels

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 90 of 108

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05r02 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	11.50	15	0.196

Notes:

- 1) Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.
- 2) Head SAR for 2.4 GHz MIMO was measured with both antennas transmitting simultaneously at the specified maximum output power in MIMO mode following the initial test configuration procedures.
- 3) Since the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, MIMO SAR for 5 GHz head and all body-worn and hotspot exposure conditions was determined by the sum of 1g single transmission chain SAR values because the summation represents higher output power and yields more conservative result per KDB 248227 D01 DR02-41929.
- 4) The highest reported SAR for each exposure condition is used for SAR summation purpose.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 91 of 108

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.429	0.644
	UMTS 850	0.219	0.429	0.648
	GSM 1900	0.165	0.429	0.594
	UMTS 1900	0.491	0.429	0.920
	LTE Band 12	0.255	0.429	0.684
	LTE Band 5 (Cell)	0.160	0.429	0.589
	LTE Band 4 (AWS)	0.395	0.429	0.824
	LTE Band 2 (PCS)	0.436	0.429	0.865
	LTE Band 30	0.193	0.429	0.622

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.640	0.855
	UMTS 850	0.219	0.640	0.859
	GSM 1900	0.165	0.640	0.805
	UMTS 1900	0.491	0.640	1.131
	LTE Band 12	0.255	0.640	0.895
	LTE Band 5 (Cell)	0.160	0.640	0.800
	LTE Band 4 (AWS)	0.395	0.640	1.035
	LTE Band 2 (PCS)	0.436	0.640	1.076
	LTE Band 30	0.193	0.640	0.833

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 92 of 108

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.399	0.614
	UMTS 850	0.219	0.399	0.618
	GSM 1900	0.165	0.399	0.564
	UMTS 1900	0.491	0.399	0.890
	LTE Band 12	0.255	0.399	0.654
	LTE Band 5 (Cell)	0.160	0.399	0.559
	LTE Band 4 (AWS)	0.395	0.399	0.794
	LTE Band 2 (PCS)	0.436	0.399	0.835
	LTE Band 30	0.193	0.399	0.592

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 1 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.223	0.438
	UMTS 850	0.219	0.223	0.442
	GSM 1900	0.165	0.223	0.388
	UMTS 1900	0.491	0.223	0.714
	LTE Band 12	0.255	0.223	0.478
	LTE Band 5 (Cell)	0.160	0.223	0.383
	LTE Band 4 (AWS)	0.395	0.223	0.618
	LTE Band 2 (PCS)	0.436	0.223	0.659
	LTE Band 30	0.193	0.223	0.416

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 93 of 108	

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 2 (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.087	0.302
	UMTS 850	0.219	0.087	0.306
	GSM 1900	0.165	0.087	0.252
	UMTS 1900	0.491	0.087	0.578
	LTE Band 12	0.255	0.087	0.342
	LTE Band 5 (Cell)	0.160	0.087	0.247
	LTE Band 4 (AWS)	0.395	0.087	0.482
	LTE Band 2 (PCS)	0.436	0.087	0.523
	LTE Band 30	0.193	0.087	0.280

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Head SAR	GSM 850	0.215	0.223	0.087	0.525
	UMTS 850	0.219	0.223	0.087	0.529
	GSM 1900	0.165	0.223	0.087	0.475
	UMTS 1900	0.491	0.223	0.087	0.801
	LTE Band 12	0.255	0.223	0.087	0.565
	LTE Band 5 (Cell)	0.160	0.223	0.087	0.470
	LTE Band 4 (AWS)	0.395	0.223	0.087	0.705
	LTE Band 2 (PCS)	0.436	0.223	0.087	0.746
	LTE Band 30	0.193	0.223	0.087	0.503

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 94 of 108	

12.4 Body-Worn Simultaneous Transmission Analysis

1. For SAR summation for body-worn back side at 15mm, the SAR values at 10mm for some transmission modes were used since the 10mm test distance was more conservative. "<" denotes that the 10mm SAR values were used for summation purposes.
2. Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used for SAR summation for body-worn back side at 15mm to determine simultaneous transmission SAR test exclusion.

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.042	<0.454
	UMTS 850	0.338	<0.042	<0.380
	GSM 1900	0.306	<0.042	<0.348
	UMTS 1900	0.896	<0.042	<0.938
	LTE Band 12	0.510	<0.042	<0.552
	LTE Band 5 (Cell)	0.277	<0.042	<0.319
	LTE Band 4 (AWS)	0.962	<0.042	<1.004
	LTE Band 2 (PCS)	0.915	<0.042	<0.957
	LTE Band 30	0.254	<0.042	<0.296

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 2 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.077	<0.489
	UMTS 850	0.338	<0.077	<0.415
	GSM 1900	0.306	<0.077	<0.383
	UMTS 1900	0.896	<0.077	<0.973
	LTE Band 12	0.510	<0.077	<0.587
	LTE Band 5 (Cell)	0.277	<0.077	<0.354
	LTE Band 4 (AWS)	0.962	<0.077	<1.039
	LTE Band 2 (PCS)	0.915	<0.077	<0.992
	LTE Band 30	0.254	<0.077	<0.331

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 95 of 108

Table 12-10
Simultaneous Transmission Scenario with 2.4 GHz WLAN MIMO (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.042	<0.077	<0.531
	UMTS 850	0.338	<0.042	<0.077	<0.457
	GSM 1900	0.306	<0.042	<0.077	<0.425
	UMTS 1900	0.896	<0.042	<0.077	<1.015
	LTE Band 12	0.510	<0.042	<0.077	<0.629
	LTE Band 5 (Cell)	0.277	<0.042	<0.077	<0.396
	LTE Band 4 (AWS)	0.962	<0.042	<0.077	<1.081
	LTE Band 2 (PCS)	0.915	<0.042	<0.077	<1.034
	LTE Band 30	0.254	<0.042	<0.077	<0.373

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 1 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.019	<0.431
	UMTS 850	0.338	<0.019	<0.357
	GSM 1900	0.306	<0.019	<0.325
	UMTS 1900	0.896	<0.019	<0.915
	LTE Band 12	0.510	<0.019	<0.529
	LTE Band 5 (Cell)	0.277	<0.019	<0.296
	LTE Band 4 (AWS)	0.962	<0.019	<0.981
	LTE Band 2 (PCS)	0.915	<0.019	<0.934
	LTE Band 30	0.254	<0.019	<0.273

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 96 of 108	

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN Ant 2 (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.036	<0.448
	UMTS 850	0.338	<0.036	<0.374
	GSM 1900	0.306	<0.036	<0.342
	UMTS 1900	0.896	<0.036	<0.932
	LTE Band 12	0.510	<0.036	<0.546
	LTE Band 5 (Cell)	0.277	<0.036	<0.313
	LTE Band 4 (AWS)	0.962	<0.036	<0.998
	LTE Band 2 (PCS)	0.915	<0.036	<0.951
	LTE Band 30	0.254	<0.036	<0.290

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN MIMO (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	<0.019	<0.036	<0.467
	UMTS 850	0.338	<0.019	<0.036	<0.393
	GSM 1900	0.306	<0.019	<0.036	<0.361
	UMTS 1900	0.896	<0.019	<0.036	<0.951
	LTE Band 12	0.510	<0.019	<0.036	<0.565
	LTE Band 5 (Cell)	0.277	<0.019	<0.036	<0.332
	LTE Band 4 (AWS)	0.962	<0.019	<0.036	<1.017
	LTE Band 2 (PCS)	0.915	<0.019	<0.036	<0.970
	LTE Band 30	0.254	<0.019	<0.036	<0.309

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 97 of 108	

Table 12-14
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Body-Worn	GSM 850	0.412	0.196	0.608
	UMTS 850	0.338	0.196	0.534
	GSM 1900	0.306	0.196	0.502
	UMTS 1900	0.896	0.196	1.092
	LTE Band 12	0.510	0.196	0.706
	LTE Band 5 (Cell)	0.277	0.196	0.473
	LTE Band 4 (AWS)	0.962	0.196	1.158
	LTE Band 2 (PCS)	0.915	0.196	1.111
	LTE Band 30	0.254	0.196	0.450

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("–").

Table 12-15
Simultaneous Transmission Scenario (2.4 GHz WLAN Ant 1 at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.117	0.717
	UMTS 850	0.368	0.117	0.485
	GPRS 1900	1.021	0.117	1.138
	UMTS 1900	1.036	0.117	1.153
	LTE Band 12	0.545	0.117	0.662
	LTE Band 5 (Cell)	0.384	0.117	0.501
	LTE Band 4 (AWS)	0.975	0.117	1.092
	LTE Band 2 (PCS)	0.997	0.117	1.114
	LTE Band 30	0.496	0.117	0.613

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 98 of 108

Table 12-16
Simultaneous Transmission Scenario (2.4 GHz WLAN Ant 2 at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.095	0.695
	UMTS 850	0.368	0.095	0.463
	GPRS 1900	1.021	0.095	1.116
	UMTS 1900	1.036	0.095	1.131
	LTE Band 12	0.545	0.095	0.640
	LTE Band 5 (Cell)	0.384	0.095	0.479
	LTE Band 4 (AWS)	0.975	0.095	1.070
	LTE Band 2 (PCS)	0.997	0.095	1.092
	LTE Band 30	0.496	0.095	0.591

Table 12-17
Simultaneous Transmission Scenario (2.4 GHz WLAN MIMO at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.117	0.095	0.812
	UMTS 850	0.368	0.117	0.095	0.580
	GPRS 1900	1.021	0.117	0.095	1.233
	UMTS 1900	1.036	0.117	0.095	1.248
	LTE Band 12	0.545	0.117	0.095	0.757
	LTE Band 5 (Cell)	0.384	0.117	0.095	0.596
	LTE Band 4 (AWS)	0.975	0.117	0.095	1.187
	LTE Band 2 (PCS)	0.997	0.117	0.095	1.209
	LTE Band 30	0.496	0.117	0.095	0.708

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 99 of 108	

Table 12-18
Simultaneous Transmission Scenario (5 GHz WLAN Ant 1 at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.061	0.661
	UMTS 850	0.368	0.061	0.429
	GPRS 1900	1.021	0.061	1.082
	UMTS 1900	1.036	0.061	1.097
	LTE Band 12	0.545	0.061	0.606
	LTE Band 5 (Cell)	0.384	0.061	0.445
	LTE Band 4 (AWS)	0.975	0.061	1.036
	LTE Band 2 (PCS)	0.997	0.061	1.058
	LTE Band 30	0.496	0.061	0.557

Table 12-19
Simultaneous Transmission Scenario (5 GHz WLAN Ant 2 at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.013	0.613
	UMTS 850	0.368	0.013	0.381
	GPRS 1900	1.021	0.013	1.034
	UMTS 1900	1.036	0.013	1.049
	LTE Band 12	0.545	0.013	0.558
	LTE Band 5 (Cell)	0.384	0.013	0.397
	LTE Band 4 (AWS)	0.975	0.013	0.988
	LTE Band 2 (PCS)	0.997	0.013	1.010
	LTE Band 30	0.496	0.013	0.509

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 100 of 108	

Table 12-20
Simultaneous Transmission Scenario (5 GHz WLAN MIMO at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
Hotspot SAR	GPRS 850	0.600	0.061	0.013	0.674
	UMTS 850	0.368	0.061	0.013	0.442
	GPRS 1900	1.021	0.061	0.013	1.095
	UMTS 1900	1.036	0.061	0.013	1.110
	LTE Band 12	0.545	0.061	0.013	0.619
	LTE Band 5 (Cell)	0.384	0.061	0.013	0.458
	LTE Band 4 (AWS)	0.975	0.061	0.013	1.049
	LTE Band 2 (PCS)	0.997	0.061	0.013	1.071
	LTE Band 30	0.496	0.061	0.013	0.570

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 101 of 108

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1732.50	20175	LTE Band 4 (AWS)	QPSK, 1 RB, 50 RB Offset	bottom	10 mm	0.934	0.876	1.07	N/A	N/A	N/A	N/A
1900	1880.00	18900	LTE Band 2 (PCS)	QPSK, 1 RB, 99 RB Offset	bottom	10 mm	0.982	0.856	1.15	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram						

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 102 of 108

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	8753E	(30kHz-6GHz) Network Analyzer	12/30/2014	Annual	12/30/2015	JP38020182
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629U00687
Agilent	E4438C	ESG Vector Signal Generator	4/25/2014	Annual	4/25/2015	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	3/31/2014	Annual	3/31/2015	MY42082659
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45090700
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45091346
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Agilent	N5182A	MXG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY47420800
Agilent	8753ES	S-Parameter Network Analyzer	5/22/2014	Annual	5/22/2015	US39170118
Agilent	E5515C	Wireless Communications Test Set	11/5/2013	Biennial	11/5/2015	GB46310798
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	ML2469A	Power Meter	3/14/2014	Annual	3/14/2015	1306009
Anritsu	MA2411B	Pulse Power Sensor	11/17/2014	Annual	11/17/2015	1126066
Anritsu	MA2411B	Pulse Power Sensor	11/17/2014	Annual	11/17/2015	1207364
Anritsu	MT8820C	Radio Communication Analyzer	11/18/2014	Annual	11/18/2015	6201300731
Anritsu	MT8820C	Radio Communication Analyzer	8/28/2014	Annual	8/28/2015	6201240328
Anritsu	MA24106A	USB Power Sensor	5/15/2014	Annual	5/15/2015	1244524
Anritsu	MA24106A	USB Power Sensor	5/14/2014	Annual	5/14/2015	1248508
Anritsu	ML2495A	Power Meter	10/31/2013	Biennial	10/31/2015	941001
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	MISSA00-009
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764551
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764558
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671801
Fisher Scientific	S407993	Long Stem Thermometer	11/4/2013	Biennial	11/4/2015	130671821
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2014	Annual	10/30/2015	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2014	Annual	10/30/2015	8650319
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	4/24/2014	Annual	4/24/2015	836371/0079
Rohde & Schwarz	CMW500	Radio Communication Tester	10/3/2014	Annual	10/3/2015	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	2/20/2014	Annual	2/20/2015	128633
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	22313
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	D1765V2	1765 MHz SAR Dipole	5/7/2014	Annual	5/7/2015	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	7/23/2014	Annual	7/23/2015	5d149
SPEAG	D2300V2	2300 MHz SAR Dipole	1/27/2015	Annual	1/27/2016	1008
SPEAG	D2450V2	2450 MHz SAR Dipole	8/11/2014	Annual	8/11/2015	719
SPEAG	D5GHZV2	5 GHz SAR Dipole	2/26/2014	Annual	2/26/2015	1120
SPEAG	D750V3	750 MHz Dipole	3/17/2014	Annual	3/17/2015	1054
SPEAG	D835V2	835 MHz SAR Dipole	7/24/2014	Annual	7/24/2015	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/14/2014	Annual	5/14/2015	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/14/2015	Annual	1/14/2016	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/12/2014	Annual	8/12/2015	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2014	Annual	9/17/2015	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/18/2014	Annual	9/18/2015	1364
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2014	Annual	4/11/2015	1368
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/6/2014	Annual	5/6/2015	1070
SPEAG	ES3DV2	SAR Probe	8/19/2014	Annual	8/19/2015	3022
SPEAG	ES3DV3	SAR Probe	3/19/2014	Annual	3/19/2015	3209
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	ES3DV3	SAR Probe	5/15/2014	Annual	5/15/2015	3263
SPEAG	ES3DV3	SAR Probe	9/24/2014	Annual	9/24/2015	3288
SPEAG	ES3DV3	SAR Probe	1/23/2015	Annual	1/23/2016	3318
SPEAG	ES3DV3	SAR Probe	9/18/2014	Annual	9/18/2015	3332
SPEAG	EX3DV4	SAR Probe	12/12/2014	Annual	12/12/2015	3920

Notes: 1) CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

2) Each piece of equipment was used solely within its valid calibration period.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 103 of 108	

15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty							k=2	24.2	23.5
(95% CONFIDENCE LEVEL)									

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 104 of 108

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMG920A	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset	Page 105 of 108

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 106 of 108

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMG920A		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 107 of 108

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01 DR02-41929
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMG920A			SAR EVALUATION REPORT	 Reviewed by: Quality Manager
Document S/N: OY1501300326.A3L	Test Dates: 01/26/15 - 02/06/15	DUT Type: Portable Handset		Page 108 of 108

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11624

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.915 \text{ S/m}$; $\epsilon_r = 41.215$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 21.1°C

Probe: ES3DV2 - SN3022; ConvF(6.18, 6.18, 6.18); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.090 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.248 W/kg

SAR(1 g) = 0.190 W/kg



0 dB = 0.206 W/kg = -6.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 119C8

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.915 \text{ S/m}$; $\epsilon_r = 41.215$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 21.1°C

Probe: ES3DV2 - SN3022; ConvF(6.18, 6.18, 6.18); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.356 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.228 W/kg

SAR(1 g) = 0.178 W/kg



0 dB = 0.194 W/kg = -7.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11624

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.391 \text{ S/m}$; $\epsilon_r = 38.258$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-26-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3263; ConvF(5.08, 5.08, 5.08); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.472 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.263 W/kg

SAR(1 g) = 0.164 W/kg



0 dB = 0.188 W/kg = -7.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 119C8

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.391 \text{ S/m}$; $\epsilon_r = 38.258$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-26-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3263; ConvF(5.08, 5.08, 5.08); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.508 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.608 W/kg

SAR(1 g) = 0.386 W/kg



0 dB = 0.260 W/kg = -5.85 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.89 \text{ S/m}$; $\epsilon_r = 42.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-29-2015; Ambient Temp: 22.5°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3209; ConvF(6.43, 6.43, 6.43); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Right Head, Cheek, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.827 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.265 W/kg

SAR(1 g) = 0.226 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.915 \text{ S/m}$; $\epsilon_r = 41.216$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 21.1°C

Probe: ES3DV2 - SN3022; ConvF(6.18, 6.18, 6.18); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.905 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.196 W/kg

SAR(1 g) = 0.159 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE RF Band 4; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.373 \text{ S/m}$; $\epsilon_r = 39.316$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-26-2015; Ambient Temp: 22.9°C; Tissue Temp: 21.7°C

Probe: ES3DV2 - SN3022; ConvF(5.04, 5.04, 5.04); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,
QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.832 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.548 W/kg

SAR(1 g) = 0.352 W/kg



0 dB = 0.420 W/kg = -3.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 38.163$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 01-26-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3263; ConvF(5.08, 5.08, 5.08); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Left Head, Cheek, High.ch

QPSK, 20 MHz Bandwidth, 1 RB, 99 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.550 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.609 W/kg

SAR(1 g) = 0.389 W/kg



0 dB = 0.457 W/kg = -3.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Head Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.696 \text{ S/m}$; $\epsilon_r = 38.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 02-06-2015; Ambient Temp: 23.1°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3318; ConvF(4.78, 4.78, 4.78); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 30, Right Head, Cheek, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.283 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.352 W/kg

SAR(1 g) = 0.193 W/kg



0 dB = 0.240 W/kg = -6.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 119C8

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.811 \text{ S/m}$; $\epsilon_r = 37.915$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 02-02-2015; Ambient Temp: 24.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Left Head, Cheek, Ch 11, 1 Mbps, Antenna 2


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.615 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.596 W/kg



0 dB = 0.806 W/kg = -0.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 5.022 \text{ S/m}$; $\epsilon_r = 36.602$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 01-27-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.35, 4.35, 4.35); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-2C, Right Head, Cheek, Ch 132, 6 Mbps, Antenna 1


Area Scan (13x20x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 5.786 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.93 W/kg

SAR(1 g) = 0.214 W/kg



0 dB = 0.600 W/kg = -2.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11624

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.712 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.364 W/kg



0 dB = 0.451 W/kg = -3.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11624

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.717 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.567 W/kg



0 dB = 0.703 W/kg = -1.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.860 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.274 W/kg



0 dB = 0.301 W/kg = -5.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.860 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.449 W/kg

SAR(1 g) = 0.338 W/kg



0 dB = 0.377 W/kg = -4.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.536 \text{ S/m}$; $\epsilon_r = 51.448$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.931 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.477 W/kg

SAR(1 g) = 0.304 W/kg



0 dB = 0.349 W/kg = -4.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.536 \text{ S/m}$; $\epsilon_r = 51.448$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 2 Tx Slots


Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.486 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.23 W/kg

SAR(1 g) = 0.746 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 119C8

Communication System: UID 0, WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1852.4 \text{ MHz}$; $\sigma = 1.527 \text{ S/m}$; $\epsilon_r = 52.455$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-06-2015; Ambient Temp: 23.8°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3332; ConvF(4.64, 4.64, 4.64); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back side, Low.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.386 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.708 W/kg



0 dB = 0.846 W/kg = -0.73 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.586 \text{ S/m}$; $\epsilon_r = 51.17$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-26-2015; Ambient Temp: 22.4°C; Tissue Temp: 21.2°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Bottom Edge, High.ch


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.246 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.957 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 54.235$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(6.19, 6.19, 6.19); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Back side, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.522 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.641 W/kg

SAR(1 g) = 0.451 W/kg



0 dB = 0.513 W/kg = -2.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 54.235$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(6.19, 6.19, 6.19); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Back side, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x8x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.560 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.986 W/kg

SAR(1 g) = 0.539 W/kg



0 dB = 0.673 W/kg = -1.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.986$ S/m; $\epsilon_r = 52.948$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.197 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.344 W/kg

SAR(1 g) = 0.275 W/kg



0 dB = 0.299 W/kg = -5.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.986 \text{ S/m}$; $\epsilon_r = 52.948$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.592 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.669 W/kg

SAR(1 g) = 0.374 W/kg



0 dB = 0.455 W/kg = -3.42 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11653

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.434 \text{ S/m}$; $\epsilon_r = 51.921$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-28-2015; Ambient Temp: 23.9°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch
QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.115 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.857 W/kg



0 dB = 1.02 W/kg = 0.09 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.434 \text{ S/m}$; $\epsilon_r = 51.921$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-28-2015; Ambient Temp: 23.9°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch
QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset


Area Scan (11x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.419 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.934 W/kg



0 dB = 1.15 W/kg = 0.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1860 \text{ MHz}$; $\sigma = 1.535 \text{ S/m}$; $\epsilon_r = 52.428$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-06-2015; Ambient Temp: 23.8°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3332; ConvF(4.64, 4.64, 4.64); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch
QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.424 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.802 W/kg



0 dB = 0.949 W/kg = -0.23 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11634

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.536 \text{ S/m}$; $\epsilon_r = 51.448$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, Mid.ch

QPSK, 20 MHz Bandwidth, 1 RB, 99 RB Offset


Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.044 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.982 W/kg



0 dB = 1.19 W/kg = 0.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.769 \text{ S/m}$; $\epsilon_r = 53.142$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 02-02-2015; Ambient Temp: 24.4°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3318; ConvF(4.52, 4.52, 4.52); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 30, Body SAR, Back side, Mid.ch
QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.461 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.487 W/kg

SAR(1 g) = 0.254 W/kg



0 dB = 0.318 W/kg = -4.98 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.769 \text{ S/m}$; $\epsilon_r = 53.142$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-02-2015; Ambient Temp: 24.4°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3318; ConvF(4.52, 4.52, 4.52); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 30, Body SAR, Back side, Mid.ch

QPSK, 10 MHz Bandwidth, 1 RB, 25 RB Offset


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.532 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.496 W/kg



0 dB = 0.657 W/kg = -1.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.013 \text{ S/m}$; $\epsilon_r = 51.688$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 1-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3209; ConvF(4.2, 4.2, 4.2); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side, Antenna 2


Area Scan (11x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.107 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.164 W/kg

SAR(1 g) = 0.075 W/kg



0 dB = 0.0967 W/kg = -10.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 1164B

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.013 \text{ S/m}$; $\epsilon_r = 51.688$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 1-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3209; ConvF(4.2, 4.2, 4.2); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Top Edge, Antenna 1


Area Scan (11x10x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.768 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.228 W/kg

SAR(1 g) = 0.114 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5320 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5320 \text{ MHz}$; $\sigma = 5.601 \text{ S/m}$; $\epsilon_r = 47.596$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 22.5°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(4.16, 4.16, 4.16); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-2A, Body SAR, Ch 64, 6 Mbps, Back Side, Antenna 2


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 2.534 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.171 W/kg

SAR(1 g) = 0.0315 W/kg



0 dB = 0.0825 W/kg = -10.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMG920A; Type: Portable Handset; Serial: 11656

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.302 \text{ S/m}$; $\epsilon_r = 46.809$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 23.8°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(3.93, 3.93, 3.93); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-3, Body SAR, Ch 165, 6 Mbps, Front Side, Antenna 1


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 2.745 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.264 W/kg

SAR(1 g) = 0.053 W/kg



0 dB = 0.132 W/kg = -8.79 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.93 \text{ S/m}$; $\epsilon_r = 41.945$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 22.5°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3209; ConvF(6.43, 6.43, 6.43); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.22 W/kg

SAR(1 g) = 0.824 W/kg

Deviation = -1.08%



0 dB = 0.963 W/kg = -0.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.914 \text{ S/m}$; $\epsilon_r = 41.238$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-31-2015; Ambient Temp: 23.0°C; Tissue Temp: 21.1°C

Probe: ES3DV2 - SN3022; ConvF(6.18, 6.18, 6.18); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.932 W/kg

Deviation = 1.30%



0 dB = 1.09 W/kg = 0.37 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.392 \text{ S/m}$; $\epsilon_r = 39.242$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-26-2015; Ambient Temp: 22.9°C; Tissue Temp: 21.7°C

Probe: ES3DV2 - SN3022; ConvF(5.04, 5.04, 5.04); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.20 W/kg

SAR(1 g) = 3.45 W/kg

Deviation = -6.50%



PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 38.163$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-26-2015; Ambient Temp: 23.5°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3263; ConvF(5.08, 5.08, 5.08); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.98 W/kg

SAR(1 g) = 4.32 W/kg

Deviation = 7.46%



0 dB = 5.48 W/kg = 7.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300 Head Medium parameters used:

$f = 2300 \text{ MHz}$; $\sigma = 1.684 \text{ S/m}$; $\epsilon_r = 38.687$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2015; Ambient Temp: 23.1°C; Tissue Temp: 24.0°C

Probe: ES3DV3 - SN3318; ConvF(4.78, 4.78, 4.78); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 1/14/2015

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2300 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 9.46 W/kg

SAR(1 g) = 4.61 W/kg

Deviation = -7.62%



0 dB = 6.07 W/kg = 7.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.797 \text{ S/m}$; $\epsilon_r = 37.953$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-02-2015; Ambient Temp: 24.1°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 10.5 W/kg

SAR(1 g) = 5.07 W/kg

Deviation = -2.69%



0 dB = 7.01 W/kg = 8.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5300 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 4.627 \text{ S/m}$; $\epsilon_r = 37.125$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 24.5°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.69, 4.69, 4.69); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.0 W/kg

SAR(1 g) = 8.17 W/kg

Deviation = -2.04%



0 dB = 20.2 W/kg = 13.05 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5500 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 4.847 \text{ S/m}$; $\epsilon_r = 36.818$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 24.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.44, 4.44, 4.44); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 33.8 W/kg

SAR(1 g) = 8.36 W/kg

Deviation = -1.53%



0 dB = 21.0 W/kg = 13.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5600 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.951 \text{ S/m}$; $\epsilon_r = 36.628$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-27-2015; Ambient Temp: 23.3°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3920; ConvF(4.35, 4.35, 4.35); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM, Left; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 36.8 W/kg

SAR(1 g) = 8.43 W/kg

Deviation = 2.55%



0 dB = 21.7 W/kg = 13.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.97 \text{ S/m}$; $\epsilon_r = 53.792$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-29-2015; Ambient Temp: 24.0°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3263; ConvF(6.19, 6.19, 6.19); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.867 W/kg

Deviation = 0.35%



0 dB = 1.01 W/kg = 0.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.984 \text{ S/m}$; $\epsilon_r = 52.961$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 01-27-2015; Ambient Temp: 20.8°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(5.98, 5.98, 5.98); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.950 W/kg

Deviation = 1.60%



0 dB = 1.11 W/kg = 0.45 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.454 \text{ S/m}$; $\epsilon_r = 51.87$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-28-2015; Ambient Temp: 23.9°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3288; ConvF(5.03, 5.03, 5.03); Calibrated: 9/24/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1364; Calibrated: 9/18/2014

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.39 W/kg

SAR(1 g) = 3.64 W/kg

Deviation = -3.19%



0 dB = 4.49 W/kg = 6.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.561 \text{ S/m}$; $\epsilon_r = 51.383$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-29-2015; Ambient Temp: 23.4°C; Tissue Temp: 22.6°C

Probe: ES3DV2 - SN3022; ConvF(4.49, 4.49, 4.49); Calibrated: 8/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 8/12/2014

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 6.62 W/kg

SAR(1 g) = 3.74 W/kg

Deviation = -7.43%



0 dB = 4.73 W/kg = 6.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900$ MHz; $\sigma = 1.579$ S/m; $\epsilon_r = 52.286$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-06-2015; Ambient Temp: 23.8°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3332; ConvF(4.64, 4.64, 4.64); Calibrated: 9/18/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 9/17/2014

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 7.29 W/kg

SAR(1 g) = 4.13 W/kg

Deviation = 2.23%



0 dB = 5.14 W/kg = 7.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2300 \text{ MHz}$; $\sigma = 1.756 \text{ S/m}$; $\epsilon_r = 53.194$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 02-02-2015; Ambient Temp: 24.4°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3318; ConvF(4.52, 4.52, 4.52); Calibrated: 1/23/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2300 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 9.04 W/kg

SAR(1 g) = 4.56 W/kg

Deviation = -5.20%



0 dB = 5.98 W/kg = 7.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.997 \text{ S/m}$; $\epsilon_r = 51.723$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 1-26-2015; Ambient Temp: 22.5°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3209; ConvF(4.2, 4.2, 4.2); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM left; Type: QD000P40CD; Serial: TP:1715

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 5.47 W/kg

Deviation = 5.60%



0 dB = 7.23 W/kg = 8.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5300 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.592 \text{ S/m}$; $\epsilon_r = 47.736$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 22.5°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(4.16, 4.16, 4.16); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 32.8 W/kg

SAR(1 g) = 7.99 W/kg

Deviation = 5.41%



PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5500 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.863 \text{ S/m}$; $\epsilon_r = 47.307$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 22.8°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(3.79, 3.79, 3.79); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5500 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.3 W/kg

SAR(1 g) = 8.16 W/kg

Deviation = 3.03%



0 dB = 21.0 W/kg = 13.22 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5600 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.989 \text{ S/m}$; $\epsilon_r = 47.154$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 23.0°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(3.66, 3.66, 3.66); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.8 W/kg

SAR(1 g) = 8.12 W/kg

Deviation = 2.27%



0 dB = 21.3 W/kg = 13.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 5800 MHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.257 \text{ S/m}$; $\epsilon_r = 46.878$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-30-2015; Ambient Temp: 23.8°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3920; ConvF(3.93, 3.93, 3.93); Calibrated: 12/12/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: ELI Front; Type: QDOVA002AA; Serial: TP:1202

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power = 20.0 dBm (100 mW)

Peak SAR (extrapolated) = 34.1 W/kg

SAR(1 g) = 7.49 W/kg

Deviation = 0.67%



0 dB = 18.7 W/kg = 12.72 dBW/kg