




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 15.247 WLAN 802.11 b/g/n

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:
4/12 - 4/24/2017
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
1M1703080095-04.A3L

FCC ID:	A3LSMG9500
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Class II Permissive Change
Model: SM-G9500
EUT Type: Portable Handset
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15.247
Test Procedure(s): KDB 558074 D01 v04, KDB 662911 D01 v02r01, KDB 648474 D03 v01r04
Class II Permissive Change: Please see FCC change document
Original Grant Date: 3/10/2017

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01 v04. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortañez
President




FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 1 of 42

TABLE OF CONTENTS


FCC PART 15.247 MEASUREMENT REPORT		3
1.0 INTRODUCTION		4
1.1 Scope		4
1.2 PCTEST Test Location		4
2.0 PRODUCT INFORMATION		5
2.1 Equipment Description		5
2.2 Device Capabilities		5
2.3 Test Configuration		7
2.4 EMI Suppression Device(s)/Modifications		7
3.0 DESCRIPTION OF TESTS		8
3.1 Evaluation Procedure		8
3.2 Radiated Emissions		8
3.3 Environmental Conditions		8
4.0 ANTENNA REQUIREMENTS		9
5.0 MEASUREMENT UNCERTAINTY		10
6.0 TEST EQUIPMENT CALIBRATION DATA		11
7.0 TEST RESULTS		12
7.1 Summary		12
7.2 Radiated Spurious Emission Measurements – Above 1 GHz		13
7.2.1 Antenna-1 Radiated Spurious Emission Measurements		17
7.2.2 Antenna-2 Radiated Spurious Emission Measurements		21
7.2.3 Antenna-1 Radiated Restricted Band Edge Measurements		25
7.2.4 Antenna-2 Radiated Restricted Band Edge Measurements		29
7.2.5 MIMO Radiated Restricted Band Edge Measurements		33
7.3 Radiated Spurious Emissions Measurements – Below 1GHz		37
8.0 CONCLUSION		42

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 2 of 42	



MEASUREMENT REPORT

FCC Part 15.247



§ 2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.

APPLICANT ADDRESS: 129, Samsung-ro,
Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.247

BASE MODEL: SM-G9500

FCC ID: A3LSMG9500

FCC CLASSIFICATION: Digital Transmission System (DTS)



Test Device Serial No.: 50677, 50964, Production Pre-Production Engineering
50966, 22248

DATE(S) OF TEST: 4/12 - 4/24/2017



TEST REPORT S/N: 1M1703080095-04.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 3 of 42	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'tl (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017		EUT Type: Portable Handset	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMG9500**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850 CDMA/EvDO Rev0/A (BC0), 850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+



Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Table 2-1. Frequency/ Channel Operations

Note: The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v04. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles				
802.11 Mode/Band		Duty Cycle [%]		
		ANT1	ANT2	MIMO
2.4GHz	b	99.1	98.9	N/A
	g	98.6	93.5	99.6
	n	98.9	93.0	97.3

Table 2-2. Measured Duty Cycles

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 5 of 42

The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CCD	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
2.4GHz	11b	✓	✓	✗	✗	✗	✗
	11g	✓	✓	✗	✗	✓	✓
	11n	✓	✓	✓	✓	✓	✓

Table 2-3. Frequency / Channel Operations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity - 2Tx Function

Data Rates Supported: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)
 6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,
 52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n)
 13/14.4Mbps, 26/28.9Mbps, 39/43.3Mbps, 52/57.8Mbps, 78/86.7Mbps,
 104/115.6Mbps, 117/130Mbps, 130/144.4Mbps (MIMO n)

This device supports simultaneous transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. The following tables show the worst case configurations determined during testing. The data for these configurations is contained in the UNII test report.

Scenario A – Config-1: ANT1 transmitting in 2.4GHz mode and ANT2 in 5GHz mode



Description	2.4 GHz Emission	5 GHz Emission
Antenna	1	2
Channel	6	48
Operating Frequency(MHz)	2437	5240
Data Rate (Mbps)	1	6
Mode	802.11b	802.11g

Table 2-4. Config-1 (ANT1 2.4GHz & ANT2 5GHz)

Scenario B – Config-2: ANT1 transmitting in 5GHz mode and ANT2 in 2.4GHz mode

Description	2.4 GHz Emission	5 GHz Emission
Antenna	2	1
Channel	6	56
Operating Frequency(MHz)	2437	5280
Data Rate (Mbps)	1	6
Mode	802.11b	802.11g

Table 2-5. Config-2 (ANT1 5GHz & ANT2 2.4GHz)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 6 of 42	

Scenario C – Config-3: ANT1 transmitting in 2.4GHz + 5GHz mode and ANT2 in 2.4GHz + 5GHz mode

Description	2.4 & 5 GHz Tx	2.4 & 5 GHz Tx
Antenna	1 & 2	1 & 2
Channel	6 & 56	6 & 56
Operating Frequency(MHz)	2437 & 5280	2437 & 5280
Data Rate (Mbps)	6 & MCS8	6 & MCS8
Mode	802.11g/n/a/ac	802.11g/n/a/ac

Table 2-6. Config-3 (ANT1 2.4 + 5GHz & ANT2 2.4 + 5GHz)

Note: 802.11a/g modes are capable of transmitting simultaneously on two antennas in this device using Cyclic Delay Diversity. 802.11n/ac modes are capable of transmitting simultaneously on two antennas using Cyclic Delay Diversity and Spatial Diversity Multiplexing (2x2 MIMO).



2.3 Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing. See Section 3.2 for radiated emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v04. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 7 of 42

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v04 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 Radiated Emissions



The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, a high density expanded polystyrene block is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 8 of 42	

4.0 ANTENNA REQUIREMENTS



Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:



The EUT unit complies with the requirement of §15.203.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 9 of 42	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 10 of 42	

6.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/11/2016	Annual	7/11/2017	RE1
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/23/2016	Biennial	8/23/2018	135427
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	4/26/2016	Annual	4/26/2017	251425001
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	7/27/2016	Annual	7/27/2017	103200
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/7/2016	Annual	5/7/2017	100040
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 11 of 42

7.0 TEST RESULTS

7.1 Summary



Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMG9500
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Sections 7.2, 7.3

Table 7-1. Summary of Test Results

Notes:

All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset			Page 12 of 42

7.2 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-2 per Section 15.209.

Frequency	Field Strength [$\mu\text{V}/\text{m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-2. Radiated Limits

Test Procedures Used

KDB 558074 D01 v04 – Section 12.1, 12.2.7



Test Settings

Average Field Strength Measurements per Section 12.2.5.1 of KDB 558074 D01 v04

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span}/\text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01 v04

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 13 of 42	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.








Figure 7-1. Test Instrument & Measurement Setup

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 14 of 42	

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v04 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-2.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Based on the proposed EUT changes in this C2PC filing, the only emissions reported are those found to be the worst-case emissions from preliminary scans.
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. Rohde & Schwarz EMC32, Version 9.15.00 automated test software was used to perform the Radiated Spurious Emissions Pre-Scan testing.
10. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
11. For the radiated band edge plots, please see the table below for the final average levels.

Ant.	Channel	Operating Frequency (MHz)	Measurement Freq. (MHz)	MODE	RAW(PREVIOUS) AVE. VALUES (dBm)	Offset (dB)	FINAL AVE. VALUES (dBm)
ANT1	11	2462	2483.5	802.11g	51.09	0	51.09
ANT1-WCP	11	2462	2483.5	802.11g	47.97	0	47.97
ANT2	11	2462	2483.5	802.11g	49.15	0.59	49.74
ANT2-WCP	11	2462	2483.5	802.11g	48	0.59	48.59
MIMO	11	2462	2483.5	802.11n	48.9	0.24	49.14
MIMO-WCP	11	2462	2483.5	802.11n	50.82	0.24	51.06

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset			Page 15 of 42

Sample Calculations



Determining Spurious Emissions Levels

- Field Strength Level $_{[dB_{\mu V/m}]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB_{\mu V/m}]} - \text{Limit }_{[dB_{\mu V/m}]}$

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.2 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 16 of 42

7.2.1 Antenna-1 Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209





Plot 7-1. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1, Ant. Pol. H)




Plot 7-2. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1, Ant. Pol. V)




Plot 7-3. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6, Ant. Pol. H)


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 17 of 42	





Plot 7-4. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6, Ant. Pol. V)



Plot 7-5. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11, Ant. Pol. H)




Plot 7-6. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11, Ant. Pol. V)


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 18 of 42	

Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz)

\$15.209



Plot 7-7. Radiated Spurious Plot above 18GHz (Pol. H)



Plot 7-8. Radiated Spurious Plot above 18GHz (Pol. V)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 19 of 42

Antenna-1 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	H	100	51	-65.80	1.16	42.36	53.98	-11.62
4924.00	Peak	H	100	51	-57.46	1.16	50.70	73.98	-23.28
7386.00	Avg	H	-	-	-71.67	9.96	45.29	53.98	-8.69
7386.00	Peak	H	-	-	-60.01	9.96	56.95	73.98	-17.03
12310.00	Avg	H	-	-	-72.18	15.99	50.81	53.98	-3.17
12310.00	Peak	H	-	-	-60.25	15.99	62.74	73.98	-11.24

Table 7-3. Radiated Measurements

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	H	110	52	-66.82	1.16	41.34	53.98	-12.64
4924.00	Peak	H	110	52	-57.51	1.16	50.65	73.98	-23.33
7386.00	Avg	H	-	-	-71.67	9.96	45.29	53.98	-8.69
7386.00	Peak	H	-	-	-60.49	9.96	56.47	73.98	-17.51
12310.00	Avg	H	-	-	-72.23	15.99	50.76	53.98	-3.22
12310.00	Peak	H	-	-	-60.37	15.99	62.62	73.98	-11.36

Table 7-4. Radiated Measurements with WCP


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 20 of 42	

7.2.2 Antenna-2 Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209



Plot 7-9. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1, Ant. Pol. H)




Plot 7-10. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1, Ant. Pol. V)




Plot 7-11. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6, Ant. Pol. H)


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 21 of 42





Plot 7-12. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6, Ant. Pol. V)




Plot 7-13. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11, Ant. Pol. H)



Plot 7-14. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11, Ant. Pol. V)


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 22 of 42	

Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz) §15.209



22:09:51 21.04.2017

Plot 7-15. Radiated Spurious Plot above 18GHz (Pol. H)



22:14:31 21.04.2017

Plot 7-16. Radiated Spurious Plot above 18GHz (Pol. V)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 23 of 42

Antenna-2 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	H	117	233	-68.24	1.16	39.92	53.98	-14.06
4924.00	Peak	H	117	233	-57.90	1.16	50.26	73.98	-23.72
7386.00	Avg	H	-	-	-71.45	9.96	45.51	53.98	-8.47
7386.00	Peak	H	-	-	-69.46	9.96	47.50	73.98	-26.48
12310.00	Avg	H	-	-	-72.16	15.99	50.83	53.98	-3.15
12310.00	Peak	H	-	-	-60.39	15.99	62.60	73.98	-11.38

Table 7-5. Radiated Measurements

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4924.00	Avg	H	112	175	-67.66	1.16	40.50	53.98	-13.48
4924.00	Peak	H	112	175	-57.69	1.16	50.47	73.98	-23.51
7386.00	Avg	H	-	-	-71.19	9.96	45.77	53.98	-8.21
7386.00	Peak	H	-	-	-59.73	9.96	57.23	73.98	-16.75
12310.00	Avg	H	-	-	-72.10	15.99	50.89	53.98	-3.09
12310.00	Peak	H	-	-	-60.36	15.99	62.63	73.98	-11.35


Table 7-6. Radiated Measurements with WCP

FCC ID: A3LSMG9500	 FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) 		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 24 of 42

7.2.3 Antenna-1 Radiated Restricted Band Edge Measurements §15.205 §15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11g
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11




Date: 13.APR.2017 21:38:49

Plot 7-17. Radiated Restricted Upper Band Edge Measurement (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 25 of 42

Antenna-1 Radiated Restricted Band Edge Measurements

\$15.205 \$15.209



Date: 13.APR.2017 21:37:38

Plot 7-18. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 26 of 42	

Antenna-1 WCP Radiated Restricted Band Edge Measurements

§15.205 §15.209


Worst Case Mode: 802.11g

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz


Channel: 11



Date: 13.APR.2017 21:44:25

Plot 7-19. Radiated Restricted Band Edge Measurement with WCP (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 27 of 42	



Date: 13.APR.2017 21:44:46


Plot 7-20. Radiated Restricted Band Edge Measurement with WCP (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 28 of 42	

7.2.4 Antenna-2 Radiated Restricted Band Edge Measurements §15.205 §15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


Worst Case Mode: 802.11g
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Date: 3.MAY.2017 21:41:26



Plot 7-21. Radiated Restricted Upper Band Edge Measurement (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 29 of 42



Date: 3.MAY.2017 21:44:03

Plot 7-22. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 30 of 42	

Antenna-2 WCP Radiated Restricted Band Edge Measurements

§15.205 §15.209


Worst Case Mode: 802.11g

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz


Channel: 11



Date: 13.APR.2017 22:07:18



Plot 7-23. Radiated Restricted Band Edge Measurement with WCP (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 31 of 42



Date: 13.APR.2017 22:07:35

Plot 7-24. Radiated Restricted Band Edge Measurement with WCP (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 32 of 42	

7.2.5 MIMO Radiated Restricted Band Edge Measurements

§15.205 §15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


Worst Case Mode: 802.11n

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz

Channel: 11




Date: 13.APR.2017 22:18:48

Plot 7-25. Radiated Restricted Upper Band Edge Measurement (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 33 of 42

MIMO Radiated Restricted Band Edge Measurements

§15.205 §15.209



Date: 13.APR.2017 22:19:06

Plot 7-26. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 34 of 42

MIMO WCP Radiated Restricted Band Edge Measurements

§15.205 §15.209


Worst Case Mode: 802.11g

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz

Channel: 11




Date: 14.APR.2017 00:09:15

Plot 7-27. Radiated Restricted Band Edge Measurement with WCP (Average)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 35 of 42

MIMO WCP Radiated Restricted Band Edge Measurements

§15.205 §15.209



Date: 14.APR.2017 00:09:37

Plot 7-28. Radiated Restricted Band Edge Measurement with WCP (Peak)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset		Page 36 of 42

7.3 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-7 per Section 15.209.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-7. Radiated Limits



Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 37 of 42	

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-2. Radiated Test Setup < 30Mhz








Figure 7-3. Radiated Test Setup < 1GHz

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 38 of 42	


Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-7.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 39 of 42	

Antenna-1 Radiated Spurious Emissions Measurements (Below 1GHz)



§15.209



Plot 7-29. Radiated Spurious Plot below 1GHz (Pol. H)




Plot 7-30. Radiated Spurious Plot below 1GHz (Pol. V)


FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 40 of 42	

Antenna-2 Radiated Spurious Emissions Measurements (Below 1GHz)



§15.209



Plot 7-31. Radiated Spurious Plot below 1GHz (Pol. H)





Plot 7-32. Radiated Spurious Plot below 1GHz (Pol. V)

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 41 of 42	

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG9500** is in compliance with Part 15C of the FCC Rules.

FCC ID: A3LSMG9500		FCC Pt. 15.247 802.11 b/g/n MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Quality Manager
Test Report S/N: 1M1703080095-04.A3L	Test Dates: 4/12 - 4/24/2017	EUT Type: Portable Handset	Page 42 of 42	