



Antenna-2 Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	a	6	4.38	11.0	-6.62	Pass
	5200	40	a	6	4.60	11.0	-6.40	Pass
	5240	48	a	6	4.67	11.0	-6.33	Pass
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	4.13	11.0	-6.87	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	4.28	11.0	-6.72	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	4.59	11.0	-6.41	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	1.42	11.0	-9.58	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	1.71	11.0	-9.29	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-3.36	11.0	-14.36	Pass
Band 2A	5260	52	a	6	4.84	11.0	-6.16	Pass
	5280	56	a	6	4.90	11.0	-6.10	Pass
	5320	64	a	6	4.79	11.0	-6.21	Pass
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	4.72	11.0	-6.28	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	4.43	11.0	-6.57	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	5.29	11.0	-5.71	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	1.65	11.0	-9.35	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	1.63	11.0	-9.37	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-3.10	11.0	-14.10	Pass
Band 2C	5500	100	a	6	5.27	11.0	-5.73	Pass
	5600	120	a	6	5.01	11.0	-5.99	Pass
	5720	144	a	6	5.20	11.0	-5.80	Pass
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	4.68	11.0	-6.32	Pass
	5600	120	n (20MHz)	6.5/7.2 (MCS0)	4.41	11.0	-6.59	Pass
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	4.54	11.0	-6.46	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	1.13	11.0	-9.87	Pass
	5590	118	n (40MHz)	13.5/15 (MCS0)	1.36	11.0	-9.64	Pass
	5710	142	n (40MHz)	13.5/15 (MCS0)	1.34	11.0	-9.67	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-3.64	11.0	-14.64	Pass
	5610	122	ac (80MHz)	29.3/32.5 (MCS0)	-3.23	11.0	-14.23	Pass
5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-6.18	11.0	-17.18	Pass	

Table 7-19. Conducted Power Spectral Density Measurements




Plot 7-118. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 7-119. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)



FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 87 of 227




Plot 7-120. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 7-121. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 88 of 227




Plot 7-122. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 80)




Plot 7-123. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 89 of 227




Plot 7-124. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 7-125. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 90 of 227




Plot 7-126. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 7-127. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 91 of 227




Plot 7-128. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-129. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 92 of 227




Plot 7-130. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 7-131. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 93 of 227




Plot 7-132. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-133. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 94 of 227



Plot 7-134. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-135. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 95 of 227




Plot 7-136. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-137. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 120)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 96 of 227




Plot 7-138. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-139. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 97 of 227




Plot 7-140. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 120)




Plot 7-141. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 98 of 227




Plot 7-142. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)



Plot 7-143. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 99 of 227



Plot 7-144. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)





Plot 7-145. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 100 of 227




Plot 7-146. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 101 of 227

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/500kHz]	Margin [dB]	Pass / Fail
Band 3	5745	149	a	6	2.48	30.0	-27.52	Pass
	5785	157	a	6	2.84	30.0	-27.16	Pass
	5825	165	a	6	2.65	30.0	-27.35	Pass
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	2.00	30.0	-28.01	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	1.97	30.0	-28.03	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	2.23	30.0	-27.77	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	-1.01	30.0	-31.01	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	-1.39	30.0	-31.39	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-2.97	30.0	-32.97	Pass

Table 7-20. Band 3 Conducted Power Spectral Density Measurements




Plot 7-147. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 102 of 227




Plot 7-148. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-149. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 103 of 227




Plot 7-150. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-151. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 104 of 227




Plot 7-152. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 7-153. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 105 of 227



Plot 7-154. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 161)



Plot 7-155. Power Spectral Density Plot (80MHz BW 802.11a/n/ac (UNII Band 3) – Ch. 155)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 106 of 227

Summed MIMO Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed MIMO Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	n (20MHz)	6.5/7.2 (MCS0)	5.26	4.13	7.74	11.0	-3.26	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	5.51	4.28	7.95	11.0	-3.05	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	5.95	4.59	8.34	11.0	-2.66	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	3.44	1.42	5.56	11.0	-5.44	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	3.90	1.71	5.95	11.0	-5.05	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-0.07	-3.36	1.60	11.0	-9.40	Pass
Band 2A	5260	52	n (20MHz)	6.5/7.2 (MCS0)	5.43	4.72	8.10	11.0	-2.90	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	5.15	4.43	7.82	11.0	-3.18	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	4.90	5.29	8.11	11.0	-2.89	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	4.18	1.65	6.10	11.0	-4.90	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	3.35	1.63	5.58	11.0	-5.42	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	0.04	-3.10	1.76	11.0	-9.24	Pass
Band 2C	5500	100	n (20MHz)	6.5/7.2 (MCS0)	5.43	4.68	8.08	11.0	-2.92	Pass
	5600	120	n (20MHz)	6.5/7.2 (MCS0)	4.68	4.41	7.56	11.0	-3.44	Pass
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	5.19	4.54	7.89	11.0	-3.11	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	4.00	1.13	5.81	11.0	-5.19	Pass
	5590	118	n (40MHz)	13.5/15 (MCS0)	2.94	1.36	5.23	11.0	-5.77	Pass
	5710	142	n (40MHz)	13.5/15 (MCS0)	3.51	1.34	5.57	11.0	-5.43	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-1.39	-3.64	0.64	11.0	-10.36	Pass
	5610	122	ac (80MHz)	29.3/32.5 (MCS0)	-2.37	-3.23	0.23	11.0	-10.77	Pass
Band 3	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-4.32	-6.18	-2.14	11.0	-13.14	Pass
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	2.50	2.00	5.26	30.0	-24.74	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	2.07	1.97	5.03	30.0	-24.97	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	1.55	2.23	4.91	30.0	-25.09	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	0.57	-1.01	2.86	30.0	-27.14	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	0.44	-1.39	2.63	30.0	-27.37	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-1.47	-2.97	0.85	30.0	-29.15	Pass

Table 7-21. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed MIMO Power Density [dBm]	Max Permissible Power Density [dBm/500kHz]	Margin [dB]	Pass / Fail
Band 3	5745	149	n (20MHz)	6.5/7.2 (MCS0)	2.50	2.00	5.26	30.0	-24.74	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	2.07	1.97	5.03	30.0	-24.97	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	1.55	2.23	4.91	30.0	-25.09	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	0.57	-1.01	2.86	30.0	-27.14	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	0.44	-1.39	2.63	30.0	-27.37	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-1.47	-2.97	0.85	30.0	-29.15	Pass

Table 7-22. Band 3 MIMO Conducted Power Spectral Density Measurements

Note:



Per KDB 662911 v02r01 Section E)2), the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 5180MHz the average conducted power spectral density was measured to be 5.26 dBm for Antenna-1 and 4.13 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(5.26 \text{ dBm} + 4.13 \text{ dBm}) = (3.36 \text{ mW} + 2.59 \text{ mW}) = 5.95 \text{ mW} = 7.74 \text{ dBm}$$

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 107 of 227	

7.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,179,999,884	-116	-0.00000224
100 %		- 30	5,180,000,324	324	0.00000625
100 %		- 20	5,180,000,142	142	0.00000274
100 %		- 10	5,179,999,554	-446	-0.00000861
100 %		0	5,179,999,850	-150	-0.00000290
100 %		+ 10	5,180,000,087	87	0.00000168
100 %		+ 20	5,179,999,768	-232	-0.00000448
100 %		+ 30	5,179,999,955	-45	-0.00000087
100 %		+ 40	5,180,000,383	383	0.00000739
100 %		+ 50	5,180,000,195	195	0.00000376
BATT. ENDPOINT		3.45	+ 20	5,180,000,030	30

Table 7-23. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,260,000,101	101	0.00000192
100 %		- 30	5,260,000,041	41	0.00000078
100 %		- 20	5,260,000,132	132	0.00000251
100 %		- 10	5,259,999,969	-31	-0.00000059
100 %		0	5,259,999,967	-33	-0.00000063
100 %		+ 10	5,259,999,804	-196	-0.00000373
100 %		+ 20	5,259,999,829	-171	-0.00000325
100 %		+ 30	5,259,999,944	-56	-0.00000106
100 %		+ 40	5,260,000,262	262	0.00000498
100 %		+ 50	5,260,000,091	91	0.00000173
BATT. ENDPOINT		3.45	+ 20	5,259,999,905	-95

Table 7-24. Frequency Stability Measurements for UNII Band 2A (Ch. 52)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,499,999,663	-337	-0.00000613
100 %		- 30	5,499,999,859	-141	-0.00000256
100 %		- 20	5,499,999,563	-437	-0.00000795
100 %		- 10	5,500,000,164	164	0.00000298
100 %		0	5,499,999,639	-361	-0.00000656
100 %		+ 10	5,500,000,204	204	0.00000371
100 %		+ 20	5,499,999,966	-34	-0.00000062
100 %		+ 30	5,500,000,172	172	0.00000313
100 %		+ 40	5,499,999,958	-42	-0.00000076
100 %		+ 50	5,500,000,159	159	0.00000289
BATT. ENDPOINT		3.45	+ 20	5,499,999,881	-119

Table 7-25. Frequency Stability Measurements for UNII Band 2C (Ch. 100)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,745,000,000 Hz
 CHANNEL: 149
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,745,000,159	159	0.00000277
100 %		- 30	5,745,000,030	30	0.00000052
100 %		- 20	5,745,000,159	159	0.00000277
100 %		- 10	5,744,999,968	-32	-0.00000056
100 %		0	5,744,999,952	-48	-0.00000084
100 %		+ 10	5,745,000,187	187	0.00000326
100 %		+ 20	5,744,999,785	-215	-0.00000374
100 %		+ 30	5,744,999,846	-154	-0.00000268
100 %		+ 40	5,744,999,744	-256	-0.00000446
100 %		+ 50	5,744,999,961	-39	-0.00000068
BATT. ENDPOINT		3.45	+ 20	5,744,999,684	-316

Table 7-26. Frequency Stability Measurements for UNII Band 3 (Ch. 149)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

7.7 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 v01r03, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW), 802.11n (40MHz BW), and 802.11ac (80MHz)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-27 per Section 15.209.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-27. Radiated Limits



Test Procedures Used

KDB 789033 D02 v01r03 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 112 of 227	

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.








Figure 7-5. Test Instrument & Measurement Setup

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 113 of 227	

Test Notes

1. All radiated spurious emissions levels were measured in a radiated test setup per the guidance of KDB 789033 D02 v01r03 Section G.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 7-27.
3. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-27. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. This unit was tested with its standard battery.
6. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. Rohde & Schwarz EMC32, Version 9.15.00 automated test software was used to perform the Radiated Spurious Emissions Pre-Scan testing.
10. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 114 of 227	

Sample Calculations



Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:


$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 115 of 227	


7.7.1 Antenna-1 Radiated Spurious Emission Measurements





Plot 7-156. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. H)




Plot 7-157. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. V)




Plot 7-158. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. H)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 116 of 227	




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-159. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. V)



Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+


Plot 7-160. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 120, Ant. Pol. H)



Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+


Plot 7-161. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 120, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 117 of 227	



Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-162. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-163. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 118 of 227	


Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz)

\$15.209



16:07:34 04.01.2017

Plot 7-164. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a – Ant. Pol. H)




16:32:21 04.01.2017

Plot 7-165. Radiated Spurious Plot above 18GHz - 26.5GHz (802.11a – Ant. Pol. V)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 119 of 227

Antenna-1 Radiated Spurious Emissions Measurements (Above 18GHz)

\$15.209



Plot 7-166. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a – Ant. Pol. H)



Plot 7-167. Radiated Spurious Plot above 26.5GHz - 40GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 120 of 227	

Antenna-1 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	H	-	-	-60.75	12.28	0.00	58.53	68.20	-9.67
* 15540.00	Average	H	-	-	-73.56	16.89	0.00	50.33	53.98	-3.65
* 15540.00	Peak	H	-	-	-57.38	16.89	0.00	66.51	73.98	-7.47
* 20720.00	Average	H	-	-	-71.14	7.93	-9.54	34.25	53.98	-19.73
* 20720.00	Peak	H	-	-	-59.81	7.93	-9.54	45.58	73.98	-28.40
25900.00	Peak	H	-	-	-56.48	8.42	-9.54	49.40	68.20	-18.80

Table 7-28. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	H	-	-	-57.86	12.44	0.00	61.58	68.20	-6.62
* 15600.00	Average	H	-	-	-73.15	16.99	0.00	50.84	53.98	-3.14
* 15600.00	Peak	H	-	-	-59.83	16.99	0.00	64.16	73.98	-9.82
* 20800.00	Average	H	-	-	-71.45	7.84	-9.54	33.85	53.98	-20.13
* 20800.00	Peak	H	-	-	-59.68	7.84	-9.54	45.62	73.98	-28.36
26000.00	Peak	H	-	-	-56.28	8.60	-9.54	49.78	68.20	-18.42

Table 7-29. Radiated Measurements

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 121 of 227	

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	H	-	-	-57.39	13.05	0.00	62.66	68.20	-5.54
* 15720.00	Average	H	-	-	-75.65	16.38	0.00	47.73	53.98	-6.25
* 15720.00	Peak	H	-	-	-59.50	16.38	0.00	63.88	73.98	-10.10
* 20960.00	Average	H	-	-	-72.03	7.88	-9.54	33.31	53.98	-20.67
* 20960.00	Peak	H	-	-	-59.36	7.88	-9.54	45.98	73.98	-28.00
26200.00	Peak	H	-	-	-56.88	8.59	-9.54	49.16	68.20	-19.04

Table 7-30. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	H	-	-	-60.22	12.28	0.00	59.06	68.20	-9.14
* 15540.00	Average	H	-	-	-73.85	16.89	0.00	50.04	53.98	-3.94
* 15540.00	Peak	H	-	-	-57.91	16.89	0.00	65.98	73.98	-8.00
* 20720.00	Average	H	-	-	-71.98	7.93	-9.54	33.41	53.98	-20.57
* 20720.00	Peak	H	-	-	-60.33	7.93	-9.54	45.06	73.98	-28.92
25900.00	Peak	H	-	-	-67.69	8.42	-9.54	38.19	68.20	-30.01

Table 7-31. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	-	-	-59.14	12.46	0.00	60.32	68.20	-7.88
* 15780.00	Average	H	-	-	-74.10	16.43	0.00	49.33	53.98	-4.65
* 15780.00	Peak	H	-	-	-61.63	16.43	0.00	61.80	73.98	-12.18
* 21040.00	Average	H	-	-	-71.16	8.12	-9.54	34.42	53.98	-19.56
* 21040.00	Peak	H	-	-	-59.86	8.12	-9.54	45.72	73.98	-28.26
26300.00	Peak	H	-	-	-56.69	8.91	-9.54	49.68	68.20	-18.52

Table 7-32. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	H	-	-	-59.55	12.59	0.00	60.04	68.20	-8.16
* 15840.00	Average	H	-	-	-72.21	16.07	0.00	50.86	53.98	-3.12
* 15840.00	Peak	H	-	-	-58.79	16.07	0.00	64.28	73.98	-9.70
* 21120.00	Average	H	-	-	-71.28	7.97	-9.54	34.15	53.98	-19.83
* 21120.00	Peak	H	-	-	-58.60	7.97	-9.54	46.83	73.98	-27.15
26400.00	Peak	H	-	-	-56.83	8.99	-9.54	49.62	68.20	-18.58

Table 7-33. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-72.03	12.78	0.00	47.75	53.98	-6.23
* 10640.00	Peak	H	-	-	-58.73	12.78	0.00	61.05	73.98	-12.93
* 15960.00	Average	H	-	-	-73.65	16.21	0.00	49.56	53.98	-4.42
* 15960.00	Peak	H	-	-	-61.60	16.21	0.00	61.61	73.98	-12.37
* 21280.00	Average	H	-	-	-71.35	7.93	-9.54	34.03	53.98	-19.94
* 21280.00	Peak	H	-	-	-58.86	7.93	-9.54	46.52	73.98	-27.45
26600.00	Peak	H	-	-	-46.60	-8.13	-9.54	42.73	68.20	-25.47

Table 7-34. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	-	-	-59.46	12.46	0.00	60.00	68.20	-8.20
* 15780.00	Average	H	-	-	-73.21	16.43	0.00	50.22	53.98	-3.76
* 15780.00	Peak	H	-	-	-57.57	16.43	0.00	65.86	73.98	-8.12
* 21040.00	Average	H	-	-	-72.56	8.12	0.00	42.56	53.98	-11.42
* 21040.00	Peak	H	-	-	-58.63	8.12	-9.54	46.95	73.98	-27.03
26300.00	Peak	H	-	-	-56.12	8.91	-9.54	50.25	68.20	-17.95

Table 7-35. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	-	-	-72.45	12.51	0.00	47.06	53.98	-6.92
* 11000.00	Peak	H	-	-	-58.86	12.51	0.00	60.65	73.98	-13.33
16500.00	Peak	H	-	-	-62.15	15.70	0.00	60.55	68.20	-7.65
22000.00	Peak	H	-	-	-56.80	8.43	-9.54	49.08	68.20	-19.12
27500.00	Peak	H	-	-	-46.02	-8.80	-9.54	42.64	68.20	-25.56

Table 7-36. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	H	-	-	-71.68	12.68	0.00	48.00	53.98	-5.98
* 11200.00	Peak	H	-	-	-61.10	12.68	0.00	58.58	73.98	-15.40
16800.00	Peak	H	-	-	-62.73	16.25	0.00	60.52	68.20	-7.68
* 22400.00	Average	H	-	-	-71.75	8.36	-9.54	34.07	53.98	-19.91
* 22400.00	Peak	H	-	-	-59.96	8.36	-9.54	45.86	73.98	-28.12
28000.00	Peak	H	-	-	-45.78	-9.12	-9.54	42.56	68.20	-25.64

Table 7-37. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	H	-	-	-72.81	13.98	0.00	48.17	53.98	-5.81
* 11440.00	Peak	H	-	-	-60.05	13.98	0.00	60.93	73.98	-13.05
17160.00	Peak	H	-	-	-61.38	19.26	0.00	64.88	68.20	-3.32
* 22880.00	Average	H	-	-	-71.86	8.33	-9.54	33.92	53.98	-20.06
* 22880.00	Peak	H	-	-	-58.89	8.33	-9.54	46.89	73.98	-27.09
28600.00	Peak	H	-	-	-44.72	-9.22	-9.54	43.51	68.20	-24.69

Table 7-38. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	H	-	-	-72.88	13.98	0.00	48.10	53.98	-5.88
* 11440.00	Peak	H	-	-	-59.90	13.98	0.00	61.08	73.98	-12.90
17160.00	Peak	H	-	-	-61.44	19.26	0.00	64.82	68.20	-3.38
* 22880.00	Average	H	-	-	-70.48	8.33	-9.54	35.30	53.98	-18.68
* 22880.00	Peak	H	-	-	-59.96	8.33	-9.54	45.82	73.98	-28.16
28600.00	Peak	H	-	-	-45.83	-9.22	-9.54	42.40	68.20	-25.80

Table 7-39. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-70.48	14.14	0.00	50.66	53.98	-3.32
* 11490.00	Peak	H	-	-	-59.83	14.14	0.00	61.31	73.98	-12.67
17235.00	Peak	H	-	-	-62.37	19.18	0.00	63.81	68.20	-4.39
* 22980.00	Average	H	-	-	-71.98	8.11	-9.54	33.59	53.98	-20.39
* 22980.00	Peak	H	-	-	-59.86	8.11	-9.54	45.71	73.98	-28.27
28725.00	Peak	H	-	-	-44.00	-9.43	-9.54	44.02	68.20	-24.18

Table 7-40. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	H	-	-	-73.31	13.88	0.00	47.57	53.98	-6.41
* 11570.00	Peak	H	-	-	-61.54	13.88	0.00	59.34	73.98	-14.64
17355.00	Peak	H	-	-	-62.48	20.47	0.00	64.99	68.20	-3.21
23140.00	Peak	H	-	-	-60.63	8.21	-9.54	45.04	68.20	-23.16
28925.00	Peak	H	-	-	-45.96	-9.65	-9.54	41.85	68.20	-26.35

Table 7-41. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-71.15	14.22	0.00	50.07	53.98	-3.91
* 11650.00	Peak	H	-	-	-59.48	14.22	0.00	61.74	73.98	-12.24
17475.00	Peak	H	-	-	-64.83	21.94	0.00	64.11	68.20	-4.09
23300.00	Peak	H	-	-	-59.34	8.28	-9.54	46.39	68.20	-21.81
29125.00	Peak	H	-	-	-44.79	-9.90	-9.54	42.77	68.20	-25.43


Table 7-42. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-73.43	14.22	0.00	47.79	53.98	-6.19
* 11650.00	Peak	H	-	-	-60.59	14.22	0.00	60.63	73.98	-13.35
17475.00	Peak	H	-	-	-64.76	21.94	0.00	64.18	68.20	-4.02
23300.00	Peak	H	-	-	-60.82	8.28	-9.54	44.91	68.20	-23.29
29125.00	Peak	H	-	-	-45.65	-9.90	-9.54	41.91	68.20	-26.29

Table 7-43. Radiated Measurements with WCP


7.7.2 Antenna-2 Radiated Spurious Emission Measurements



Plot 7-168. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. H)




Plot 7-169. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. V)




Plot 7-170. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. H)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 129 of 227




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-171. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. V)



Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+


Plot 7-172. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 120, Ant. Pol. H)




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-173. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 120, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 130 of 227



Plot 7-174. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 7-175. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 131 of 227	

Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209



Plot 7-176. Radiated Spurious Plot above 18GHz - 26.5GHz (802.11a – Ant. Pol. H)




Plot 7-177. Radiated Spurious Plot above 18GHz - 26.5GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 132 of 227	


Antenna-2 Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209



16:07:34 04.01.2017

Plot 7-178. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a – Ant. Pol. H)



16:32:21 04.01.2017

Plot 7-179. Radiated Spurious Plot above 26.5GHz - 40GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 133 of 227	

Antenna-2 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	H	-	-	-59.83	12.28	0.00	59.45	68.20	-8.75
* 15540.00	Average	H	-	-	-74.51	16.89	0.00	49.38	53.98	-4.60
* 15540.00	Peak	H	-	-	-59.37	16.89	0.00	64.52	73.98	-9.46
* 20720.00	Average	H	-	-	-71.15	7.93	-9.54	34.24	53.98	-19.74
* 20720.00	Peak	H	-	-	-59.53	7.93	-9.54	45.86	73.98	-28.12
25900.00	Peak	H	-	-	-57.10	8.42	-9.54	48.78	68.20	-19.42

Table 7-44. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	H	-	-	-60.15	12.44	0.00	59.29	68.20	-8.91
* 15600.00	Average	H	-	-	-73.19	16.99	0.00	50.80	53.98	-3.18
* 15600.00	Peak	H	-	-	-58.53	16.99	0.00	65.46	73.98	-8.52
* 20800.00	Average	H	-	-	-71.65	7.84	-9.54	33.65	53.98	-20.33
* 20800.00	Peak	H	-	-	-59.80	7.84	-9.54	45.50	73.98	-28.48
26000.00	Peak	H	-	-	-57.56	8.60	-9.54	48.50	68.20	-19.70

Table 7-45. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	H	-	-	-58.76	13.05	0.00	61.29	68.20	-6.91
* 15720.00	Average	H	-	-	-73.15	16.38	0.00	50.23	53.98	-3.75
* 15720.00	Peak	H	-	-	-61.47	16.38	0.00	61.91	73.98	-12.07
* 20960.00	Average	H	-	-	-72.45	7.88	-9.54	32.89	53.98	-21.09
* 20960.00	Peak	H	-	-	-59.74	7.88	-9.54	45.60	73.98	-28.38
26200.00	Peak	H	-	-	-57.63	8.59	-9.54	48.41	68.20	-19.79

Table 7-46. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	H	-	-	-60.50	12.28	0.00	58.78	68.20	-9.42
* 15600.00	Average	H	-	-	-73.38	16.89	0.00	50.51	53.98	-3.47
* 15600.00	Peak	H	-	-	-58.40	16.89	0.00	65.49	73.98	-8.49
* 20800.00	Average	H	-	-	-71.16	7.93	-9.54	34.23	53.98	-19.75
* 20800.00	Peak	H	-	-	-59.83	7.93	-9.54	45.56	73.98	-28.42
26000.00	Peak	H	-	-	-56.75	8.42	-9.54	49.13	68.20	-19.07

Table 7-47. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	-	-	-59.13	12.46	0.00	60.33	68.20	-7.87
* 15780.00	Average	H	-	-	-73.47	16.43	0.00	49.96	53.98	-4.02
* 15780.00	Peak	H	-	-	-61.30	16.43	0.00	62.13	73.98	-11.85
* 21040.00	Average	H	-	-	-71.70	8.12	-9.54	33.88	53.98	-20.10
* 21040.00	Peak	H	-	-	-59.80	8.12	-9.54	45.78	73.98	-28.20
26300.00	Peak	H	-	-	-56.13	8.91	-9.54	50.24	68.20	-17.96

Table 7-48. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	H	-	-	-57.15	12.59	0.00	62.44	68.20	-5.76
* 15840.00	Average	H	-	-	-73.44	16.07	0.00	49.63	53.98	-4.35
* 15840.00	Peak	H	-	-	-61.37	16.07	0.00	61.70	73.98	-12.28
* 21120.00	Average	H	-	-	-72.78	7.97	-9.54	32.65	53.98	-21.33
* 21120.00	Peak	H	-	-	-59.80	7.97	-9.54	45.63	73.98	-28.35
26400.00	Peak	H	-	-	-56.17	8.99	-9.54	50.28	68.20	-17.92

Table 7-49. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-73.18	12.78	0.00	46.60	53.98	-7.38
* 10640.00	Peak	H	-	-	-60.65	12.78	0.00	59.13	73.98	-14.85
* 15960.00	Average	H	-	-	-72.54	16.21	0.00	50.67	53.98	-3.31
* 15960.00	Peak	H	-	-	-59.20	16.21	0.00	64.01	73.98	-9.97
* 21280.00	Average	H	-	-	-72.50	7.93	-9.54	32.88	53.98	-21.09
* 21280.00	Peak	H	-	-	-58.47	7.93	-9.54	46.91	73.98	-27.06
26600.00	Peak	H	-	-	-56.48	-8.13	-9.54	32.85	68.20	-35.35

Table 7-50. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-73.38	12.78	0.00	46.40	53.98	-7.58
* 10640.00	Peak	H	-	-	-60.86	12.78	0.00	58.92	73.98	-15.06
* 15960.00	Average	H	-	-	-72.68	16.21	0.00	50.53	53.98	-3.45
* 15960.00	Peak	H	-	-	-58.46	16.21	0.00	64.75	73.98	-9.23
* 21280.00	Average	H	-	-	-71.21	7.93	-9.54	34.17	53.98	-19.80
* 21280.00	Peak	H	-	-	-58.53	7.93	-9.54	46.85	73.98	-27.12
26600.00	Peak	H	-	-	-57.58	-8.13	-9.54	31.75	68.20	-36.45

Table 7-51. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	-	-	-73.00	12.51	0.00	46.51	53.98	-7.47
* 11000.00	Peak	H	-	-	-60.41	12.51	0.00	59.10	73.98	-14.88
16500.00	Peak	H	-	-	-58.24	15.70	0.00	64.46	68.20	-3.74
22000.00	Peak	H	-	-	-58.60	8.43	-9.54	47.28	68.20	-20.92
27500.00	Peak	H	-	-	-45.47	-8.80	-9.54	43.19	68.20	-25.01

Table 7-52. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	H	-	-	-71.88	12.68	0.00	47.80	53.98	-6.18
* 11200.00	Peak	H	-	-	-59.78	12.68	0.00	59.90	73.98	-14.08
16800.00	Peak	H	-	-	-65.82	16.25	0.00	57.43	68.20	-10.77
* 22400.00	Average	H	-	-	-71.45	8.36	-9.54	34.37	53.98	-19.61
* 22400.00	Peak	H	-	-	-59.66	8.36	-9.54	46.16	73.98	-27.82
28000.00	Peak	H	-	-	-47.32	-9.12	-9.54	41.02	68.20	-27.18

Table 7-53. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11400.00	Average	H	-	-	-72.48	13.98	0.00	48.50	53.98	-5.48
* 11400.00	Peak	H	-	-	-60.12	13.98	0.00	60.86	73.98	-13.12
17100.00	Peak	H	-	-	-65.02	19.26	0.00	61.24	68.20	-6.96
* 22800.00	Average	H	-	-	-72.78	8.33	-9.54	33.00	53.98	-20.98
* 22800.00	Peak	H	-	-	-59.18	8.33	-9.54	46.60	73.98	-27.38
28500.00	Peak	H	-	-	-45.36	-9.22	-9.54	42.87	68.20	-25.33

Table 7-54. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	H	-	-	-73.43	12.68	0.00	46.25	53.98	-7.73
* 11160.00	Peak	H	-	-	-60.47	12.68	0.00	59.21	73.98	-14.77
16740.00	Peak	H	-	-	-58.82	16.25	0.00	64.43	68.20	-3.77
* 22320.00	Average	H	-	-	-71.36	8.36	-9.54	34.46	53.98	-19.52
* 22320.00	Peak	H	-	-	-59.68	8.36	-9.54	46.14	73.98	-27.84
27900.00	Peak	H	-	-	-45.38	-9.12	-9.54	42.96	68.20	-25.24

Table 7-55. Radiated Measurements with WCP

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-71.00	14.14	0.00	50.14	53.98	-3.84
* 11490.00	Peak	H	-	-	-60.98	14.14	0.00	60.16	73.98	-13.82
17235.00	Peak	H	-	-	-65.48	19.18	0.00	60.70	68.20	-7.50
* 22980.00	Average	H	-	-	-72.03	8.11	-9.54	33.54	53.98	-20.44
* 22980.00	Peak	H	-	-	-59.78	8.11	-9.54	45.79	73.98	-28.19
28725.00	Peak	H	-	-	-44.69	-9.43	-9.54	43.33	68.20	-24.87

Table 7-56. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	H	-	-	-71.65	13.88	0.00	49.23	53.98	-4.75
* 11570.00	Peak	H	-	-	-58.89	13.88	0.00	61.99	73.98	-11.99
17355.00	Peak	H	-	-	-63.34	20.47	0.00	64.13	68.20	-4.07
23140.00	Peak	H	-	-	-59.38	8.21	-9.54	46.29	68.20	-21.91
28925.00	Peak	H	-	-	-44.13	-9.65	-9.54	43.68	68.20	-24.52

Table 7-57. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-73.28	14.22	0.00	47.94	53.98	-6.04
* 11650.00	Peak	H	-	-	-60.58	14.22	0.00	60.64	73.98	-13.34
17475.00	Peak	H	-	-	-63.97	21.94	0.00	64.97	68.20	-3.23
23300.00	Peak	H	-	-	-59.78	8.28	-9.54	45.95	68.20	-22.25
29125.00	Peak	H	-	-	-44.31	-9.90	-9.54	43.25	68.20	-24.95

Table 7-58. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-73.39	14.14	0.00	47.75	53.98	-6.23
* 11490.00	Peak	H	-	-	-60.10	14.14	0.00	61.04	73.98	-12.94
17235.00	Peak	H	-	-	-61.70	19.18	0.00	64.48	68.20	-3.72
* 22980.00	Average	H	-	-	-71.63	8.11	-9.54	33.94	53.98	-20.04
* 22980.00	Peak	H	-	-	-59.29	8.11	-9.54	46.28	73.98	-27.70
28725.00	Peak	H	-	-	-45.91	-9.43	-9.54	42.11	68.20	-26.09

Table 7-59. Radiated Measurements with WCP


7.7.3 Simultaneous Tx Radiated Spurious Emissions Measurements §15.247(d) §15.205 & §15.209

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1	2
Channel	11	52
Operating Frequency(MHz)	2462	5260
Data Rate (Mbps)	1	6
Mode	802.11b	802.11a


Table 7-60. Simultaneous Transmission Config-1




Plot 7-180. Radiated Spurious Plot above 1GHz (2.4GHz – 5GHz, Ant. Pol. H)



Plot 7-181. Radiated Spurious Plot above 1GHz (2.4GHz – 5GHz, Ant. Pol. V)




Plot 7-182. Radiated Spurious Plot 18GHz – 26.5GHz (Config-1 RSDB, Ant. Pol. H)




Plot 7-183. Radiated Spurious Plot 18GHz – 26.5GHz (Config-1 RSDB, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 143 of 227	



Plot 7-184. Radiated Spurious Plot above 26.5GHz (Config-1 RSDB, Ant. Pol. H)



Plot 7-185. Radiated Spurious Plot above 26.5GHz (Config-1 RSDB, Ant. Pol. V)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 144 of 227	

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
3134.00	Average	H	122	34	-61.35	1.17	46.82	53.98	-7.16
3134.00	Peak	H	122	34	-52.54	1.17	55.63	73.98	-18.35
4924.00	Average	H	100	132	-70.14	0.45	37.31	53.98	-16.67
4924.00	Peak	H	100	132	-57.54	0.45	49.91	73.98	-24.07
8058.00	Average	H	-	-	-72.45	11.50	46.05	53.98	-7.93
8058.00	Peak	H	-	-	-61.30	11.50	57.20	73.98	-16.78

Table 7-61. Radiated Measurements (ANT1 2.4GHz – ANT2 5GHz)


Description	5 GHz Emission	2.4 GHz Emission
Antenna	1	2
Channel	120	6
Operating Frequency(MHz)	5600	2437
Data Rate (Mbps)	6	1
Mode	802.11a	802.11b

Table 7-62. Simultaneous Transmission Config-2




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-186. Radiated Spurious Plot above 1GHz (5GHz – 2.4 GHz, Ant. Pol. H)




Preview Result 1-PK+ FCC Part 15.209 RSE Peak Including Restricted Bands (15E) Final_Result PK+

Plot 7-187. Radiated Spurious Plot above 1GHz (5GHz – 2.4 GHz, Ant. Pol. V)




Plot 7-188. Radiated Spurious Plot 18GHz – 26.5GHz (Config-2 RSDB, Ant. Pol. H)




Plot 7-189. Radiated Spurious Plot 18GHz – 26.5GHz (Config-2 RSDB, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 147 of 227	



Plot 7-190. Radiated Spurious Plot above 26.5GHz (Config-2 RSDB, Ant. Pol. H)



Plot 7-191. Radiated Spurious Plot above 26.5GHz (Config-2 RSDB, Ant. Pol. V)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 148 of 227	

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
3889.00	Average	H	108	66	-61.12	3.46	49.34	53.98	-4.64
3889.00	Peak	H	108	66	-50.47	3.46	59.99	73.98	-13.99
4874.00	Average	H	100	176	-66.15	0.25	41.10	53.98	-12.88
4874.00	Peak	H	100	176	-57.81	0.25	49.44	73.98	-24.54
8763.00	Average	H	-	-	-71.86	13.07	48.21	53.98	-5.77
8763.00	Peak	H	-	-	-62.04	13.07	58.03	73.98	-15.95


Table 7-63. Radiated Measurements (ANT1 5GHz – ANT2 2.4GHz)

Description	2.4 GHz Emission	5 GHz Emission
Antenna	MIMO	MIMO
Channel	6	52
Operating Frequency(MHz)	2437	5260
Data Rate (Mbps)	6	MCS0
Mode	802.11g	802.11n


Table 7-64. Simultaneous Transmission MIMO




Plot 7-192. Radiated Spurious Plot above 1GHz (MIMO RSDB, Ant. Pol. H)



Plot 7-193. Radiated Spurious Plot above 1GHz (MIMO RSDB, Ant. Pol. V)




Plot 7-194. Radiated Spurious Plot 18GHz – 26.5GHz (MIMO RSDB, Ant. Pol. H)




Plot 7-195. Radiated Spurious Plot 18GHz – 26.5GHz (MIMO RSDB, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 151 of 227	



Plot 7-196. Radiated Spurious Plot above 26.5GHz (MIMO RSDB, Ant. Pol. H)



Plot 7-197. Radiated Spurious Plot above 26.5GHz (MIMO RSDB, Ant. Pol. V)



FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 152 of 227	

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
3209.00	Average	H	124.00	71.00	-63.48	1.26	44.78	53.98	-9.20
3209.00	Peak	H	124.00	71.00	-55.83	1.26	52.43	73.98	-21.55
4874.00	Average	H	-	-	-71.55	0.25	35.70	53.98	-18.28
4874.00	Peak	H	-	-	-62.35	0.25	44.90	73.98	-29.08
8083.00	Average	H	-	-	-72.13	11.12	45.99	53.98	-7.99
8083.00	Peak	H	-	-	-61.84	11.12	56.28	73.98	-17.70

Table 7-65. Radiated Measurements (MIMO RSDB)

7.7.4 Antenna-1 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Date: 4.JAN.2017 18:46:33

Plot 7-198. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 154 of 227

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 4.JAN.2017 19:02:18

Plot 7-199. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 155 of 227

Antenna-1 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100




Date: 4.JAN.2017 19:31:18

Plot 7-200. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 156 of 227

Antenna-1 Radiated Band Edge Measurements (20MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165



Date: 6.FEB.2017 18:19:29

Plot 7-201. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 157 of 227

Antenna-1 WCP Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64




Date: 16.JAN.2017 18:16:35

Plot 7-202. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 158 of 227

7.7.5 Antenna-1 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 4.JAN.2017 18:50:03

Plot 7-203. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 159 of 227	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209



Date: 4.JAN.2017 18:50:30

Plot 7-204. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 160 of 227

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62




Date: 5.JAN.2017 14:53:12

Plot 7-205. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 161 of 227

Antenna-1 Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209



Date: 4.JAN.2017 19:18:31

Plot 7-206. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 162 of 227

Antenna-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102




Date: 4.JAN.2017 19:38:14

Plot 7-207. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 163 of 227

Antenna-1 Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209




Date: 4.JAN.2017 19:38:49

Plot 7-208. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 164 of 227	

Antenna-1 Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159



Date: 6.FEB.2017 18:21:12

Plot 7-209. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 165 of 227

Antenna-1 WCP Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62





Date: 16.JAN.2017 18:21:54

Plot 7-210. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 166 of 227

7.7.6 Antenna-1 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42



Date: 4.JAN.2017 18:52:36


Plot 7-211. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 167 of 227

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58




Date: 4.JAN.2017 19:21:42

Plot 7-212. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 168 of 227

Antenna-1 Radiated Band Edge Measurements (80MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209




Date: 4.JAN.2017 19:22:11

Plot 7-213. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 169 of 227

Antenna-1 Radiated Band Edge Measurements (80MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Date: 4.JAN.2017 19:55:16

Plot 7-214. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)



FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 170 of 227

Antenna-1 Radiated Band Edge Measurements (80MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209



Date: 4.JAN.2017 19:55:43

Plot 7-215. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 171 of 227	

Antenna-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5775MHz

Channel: 155





Date: 6.FEB.2017 18:23:54

Plot 7-216. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 172 of 227

7.7.7 Antenna-2 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Date: 4.JAN.2017 20:39:56

Plot 7-218. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 174 of 227

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 4.JAN.2017 20:53:08

Plot 7-219. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 175 of 227

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100



Date: 4.JAN.2017 21:06:50

Plot 7-220. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 176 of 227

Antenna-2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5825MHz

Channel: 165



Date: 6.FEB.2017 18:33:17

Plot 7-221. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 177 of 227

Antenna-2 WCP Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64





Date: 16.JAN.2017 18:34:10

Plot 7-222. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 178 of 227

7.7.8 Antenna-2 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38



Date: 4.JAN.2017 20:42:07

Plot 7-223. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 179 of 227

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62



Date: 4.JAN.2017 20:55:25

Plot 7-224. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 180 of 227

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102



Date: 4.JAN.2017 21:08:43

Plot 7-225. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 181 of 227

Antenna-2 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5795MHz

Channel: 159



Date: 6.FEB.2017 18:36:41

Plot 7-226. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 182 of 227

Antenna-2 WCP Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62





Date: 16.JAN.2017 18:35:44

Plot 7-227. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 183 of 227

7.7.9 Antenna-2 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42



Date: 4.JAN.2017 20:45:30

Plot 7-228. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 184 of 227

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58



Date: 4.JAN.2017 20:58:19

Plot 7-229. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 185 of 227

Antenna-2 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106




Date: 4.JAN.2017 21:11:00

Plot 7-230. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 186 of 227

Antenna-2 Radiated Band Edge Measurements (80MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Date: 6.FEB.2017 18:38:35

Plot 7-231. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 187 of 227

Antenna-2 WCP Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58



Date: 16.JAN.2017 18:37:53

Plot 7-232. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 188 of 227

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 4.JAN.2017 21:44:07

Plot 7-234. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 190 of 227

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100



Date: 4.JAN.2017 21:56:06

Plot 7-235. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 191 of 227

MIMO Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5825MHz

Channel: 165



Date: 6.FEB.2017 18:44:37

Plot 7-236. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 192 of 227

MIMO WCP Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64




Date: 17.JAN.2017 13:13:13

Plot 7-237. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 193 of 227

7.7.11 MIMO Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 4.JAN.2017 21:37:38

Plot 7-238. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 194 of 227	

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209




Date: 4.JAN.2017 21:38:27

Plot 7-239. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 195 of 227

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Date: 5.JAN.2017 15:36:22

Plot 7-240. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 196 of 227

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209




Date: 4.JAN.2017 21:50:08

Plot 7-241. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 197 of 227	

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Date: 4.JAN.2017 21:58:43

Plot 7-242. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 198 of 227

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209




Date: 4.JAN.2017 22:58:14

Plot 7-243. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 199 of 227

MIMO Radiated Band Edge Measurements (40MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159





Date: 6.FEB.2017 18:46:10

Plot 7-244. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 200 of 227

7.7.12 MIMO Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42





Date: 4.JAN.2017 21:41:07

Plot 7-246. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 202 of 227

MIMO Radiated Band Edge Measurements (80MHz BW)
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58



Date: 4.JAN.2017 21:52:06

Plot 7-247. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 203 of 227

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106



Date: 4.JAN.2017 22:02:59

Plot 7-248. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 204 of 227

MIMO Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5775MHz

Channel: 155



Date: 6.FEB.2017 18:47:41

Plot 7-249. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 205 of 227

MIMO WCP Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58



Date: 17.JAN.2017 13:16:33

Plot 7-250. Radiated Restricted Band Edge Plot with WCP

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 206 of 227

7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-66 per Section 15.209.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-66. Radiated Limits



Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 207 of 227	

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz






Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 208 of 227	


Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-66.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 209 of 227	

Antenna-1 Radiated Spurious Emissions Measurements (Below 1GHz)



§15.209



Plot 7-251. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 7-252. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 210 of 227	


Antenna-2 Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209



Preview Result 1-PK+ FCC Part 15 Class B QP Limit Final_Result PK+

Plot 7-253. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Preview Result 1-PK+ FCC Part 15 Class B QP Limit Final_Result PK+

Plot 7-254. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 211 of 227	

Simultaneous Tx Radiated Spurious Emissions Measurements (Below 1GHz)



§15.209




Plot 7-255. Radiated Spurious Plot below 1GHz (2.4GHz – 5GHz, Ant. Pol. H)




Plot 7-256. Radiated Spurious Plot below 1GHz (2.4GHz – 5GHz, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 212 of 227	



Plot 7-257. Radiated Spurious Plot below 1GHz (5GHz – 2.4 GHz, Ant. Pol. H)



Plot 7-258. Radiated Spurious Plot below 1GHz (5GHz – 2.4 GHz, Ant. Pol. V)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 213 of 227	

7.9 Line-Conducted Test Data

§15.407

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-67. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2



Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 214 of 227	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-8. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 215 of 227

Line-Conducted Test Data

\$15.407



Plot 7-259. Line Conducted Plot with 802.11a UNII Band 1 (L1)




Plot 7-260. Line Conducted Plot with 802.11a UNII Band 1 (N)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 216 of 227

Line-Conducted Test Data

\$15.407



Plot 7-261. Line Conducted Plot with 802.11a UNII Band 2A (L1)




Plot 7-262. Line Conducted Plot with 802.11a UNII Band 2A (N)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 217 of 227

Line-Conducted Test Data

\$15.407



Plot 7-263. Line Conducted Plot with 802.11a UNII Band 2C (L1)




Plot 7-264. Line Conducted Plot with 802.11a UNII Band 2C (N)


FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 218 of 227

Line-Conducted Test Data

\$15.407



Plot 7-265. Line Conducted Plot with 802.11a UNII Band 3 (L1)





Plot 7-266. Line Conducted Plot with 802.11a UNII Band 3 (N)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 219 of 227

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG950N** is in compliance with Part 15E of the FCC Rules.

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 220 of 227	

APPENDIX A. 802.11A DUAL TX

A.1 Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
15.407 (a.1.iv), (a.2), (a.3)	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a)	CONDUCTED	PASS	Section A.2
15.407 (a.1.iv), (a.2), (a.3)	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a)		PASS	Section A.3
15.205, 15.407(b.1),(5),(6)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		PASS	Section A.4

Table A.1-1. Summary of Test Results

Notes:

- 1) This device employs dual transmission in 802.11a and 802.11g modes using Cyclic Delay Diversity. For all test cases, the device was set to transmit from both antennas simultaneously. The data in this section demonstrates compliance to the dual-transmission requirements specified in KDB 662911 v02r01.
- 2) All data found in this section is compiled from plots found in the main body of this test report.
- 3) Since this device is able to transmit the same data through both of its antennas in a given symbol period, then, by the definition specified in KDB 662911 v02r01 Section F)1), the transmission symbols are correlated.
- 4) Since two antennas are supported in this device and a minimum of $N_{ss} = 1$ antenna can operate at any given time, the maximum array gain for two correlated signals is $10\log_{10}(N_{ant}/N_{ss}) = 3\text{dB}$, where N_{ss} is the number of spatial streams and N_{ant} is the total number of antennas.
- 5) For conducted spurious emissions, per KDB 662911 v02r01 Section E)3)b), the emissions on each individual output complied with its corresponding relative limit for that output, so additional testing was not required for dual transmission operation.

A.2 Output Power Measurement

§15.247(b.3)

Test Overview

Using the “Measure and Sum” technique, the measured conducted power values were summed in linear power units then converted back to dBm.

Freq [MHz]	Channel	Detector	5GHz (20MHz) Conducted Power [dBm]		
			IEEE Transmission Mode		
			ANT1	ANT2	CDD
5180	36	AVG	16.13	15.51	18.84
5200	40	AVG	16.22	15.68	18.97
5220	44	AVG	16.28	15.82	19.07
5240	48	AVG	16.30	15.97	19.15
5260	52	AVG	16.05	15.88	18.98
5280	56	AVG	16.04	15.95	19.01
5300	60	AVG	16.10	15.88	19.00
5320	64	AVG	16.00	16.09	19.06
5500	100	AVG	16.10	15.96	19.04
5580	116	AVG	16.22	16.20	19.22
5600	120	AVG	16.20	15.81	19.02
5620	124	AVG	16.08	15.71	18.91
5640	128	AVG	16.31	16.31	19.32
5660	132	AVG	16.14	16.42	19.29
5720	144	AVG	16.13	15.44	18.81
5745	149	AVG	16.00	15.82	18.92
5785	157	AVG	15.96	15.88	18.93
5825	165	AVG	16.05	15.63	18.86

Table A2-1. Dual Tx 802.11a-mode Conducted Output Power Measurements

A.3 Power Spectral Density



§15.247(e)

Test Overview

Using the “Measure and Sum” technique, the measured conducted power density values were summed in linear power units then converted back to dBm. Original measured values are found in Section 7.5 of this report.

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed CDD Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	a	6.5/7.2 (MCS0)	5.30	4.38	7.87	11.0	-3.13	Pass
	5200	40	a	6.5/7.2 (MCS0)	5.89	4.60	8.30	11.0	-2.70	Pass
	5240	48	a	6.5/7.2 (MCS0)	6.05	4.67	8.43	11.0	-2.57	Pass
Band 2A	5260	52	a	6.5/7.2 (MCS0)	5.82	4.84	8.37	11.0	-2.63	Pass
	5280	56	a	6.5/7.2 (MCS0)	5.49	4.90	8.22	11.0	-2.78	Pass
	5320	64	a	6.5/7.2 (MCS0)	5.07	4.79	7.94	11.0	-3.06	Pass
Band 2C	5500	100	a	6.5/7.2 (MCS0)	5.54	5.27	8.42	11.0	-2.58	Pass
	5600	120	a	6.5/7.2 (MCS0)	5.02	5.01	8.02	11.0	-2.98	Pass
	5720	144	a	6.5/7.2 (MCS0)	5.42	5.20	8.32	11.0	-2.68	Pass
Band 3	5745	149	a	6.5/7.2 (MCS0)	2.67	2.48	5.58	30.0	-24.42	Pass
	5785	157	a	6.5/7.2 (MCS0)	2.24	2.84	5.56	30.0	-24.44	Pass
	5825	165	a	6.5/7.2 (MCS0)	1.86	2.65	5.28	30.0	-24.72	Pass

Table A3-1.802.11a Dual Tx Conducted Power Density Measurements

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 223 of 227	

A.4 Dual Tx Radiated Restricted Band Edge Measurements

§15.205 §15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting on both outputs in 802.11a mode.


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36



Date: 23.FEB.2017 17:22:05

Plot A.4-3. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 1)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 224 of 227

Dual Tx Radiated Band Edge Measurements

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 17.JAN.2017 13:03:20

Plot A.4-3. Radiated Restricted Upper Band Edge Plot (Average & Peak – UNII Band 2A)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 225 of 227

Dual Tx Radiated Band Edge Measurements

§15.407(b.1)(b.2) §15.205 §15.209



Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100




Date: 23.FEB.2017 17:28:27

Plot A.4-3. Radiated Restricted Lower Band Edge Plot (Average & Peak – UNII Band 2C)

FCC ID: A3LSMG950N		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset		Page 226 of 227

Dual Tx Radiated Band Edge Measurements
§15.407(b.1)(b.2) §15.205 §15.209

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165



Date: 23.FEB.2017 17:33:30

Plot A.4-3. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: A3LSMG950N	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1701030008-05.A3L	Test Dates: 1/2 - 2/24/2017	EUT Type: Portable Handset	Page 227 of 227	