

## HEARING AID COMPATIBILITY

**Applicant Name:**  
Samsung Electronics Co., Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do 16677, Korea

**Date of Testing:**  
12/31/2016 - 01/14/2017  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
1M1701030004-13.A3L

**FCC ID:** **A3LSMG950U**

**APPLICANT:** **SAMSUNG ELECTRONICS CO., LTD.**

**Scope of Test:** Audio Band Magnetic Testing (T-Coil)  
**Application Type:** Certification  
**FCC Rule Part(s):** CFR §20.19(b)  
**HAC Standard:** ANSI C63.19-2011  
CTIA Test Plan for Hearing Aid Compatibility Rev 3.0, November 2013  
285076 D01 HAC Guidance v04  
285076 D02 T-Coil testing for CMRS IP v02  
**DUT Type:** Portable Handset  
**Model:** SM-G950U  
**Additional Model(s):** SM-G950U1, SM-G950W  
**Test Device Serial No.:** Pre-Production Sample [S/N: 82773]

**C63.19-2011 HAC Category:** **T3 (SIGNAL TO NOISE CATEGORY)**

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez  
President

**ctia** Authorized<sup>TM</sup>  
Test Lab  
Lab Code: 20020221-00



<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 1 of 72	

# TABLE OF CONTENTS

---

1.	INTRODUCTION .....	3
2.	DUT DESCRIPTION.....	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES .....	7
4.	METHOD OF MEASUREMENT .....	9
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION .....	19
6.	FCC 3G MEASUREMENTS .....	22
7.	TEST SUMMARY .....	24
8.	MEASUREMENT UNCERTAINTY .....	33
9.	EQUIPMENT LIST.....	34
10.	TEST DATA.....	35
11.	CALIBRATION CERTIFICATES.....	60
12.	CONCLUSION.....	67
13.	REFERENCES .....	68
14.	TEST SETUP PHOTOGRAPHS .....	70

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset		Page 2 of 72

# 1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658<sup>1</sup> to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

## Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.




Figure 1-1 Hearing Aid *in-vitu*

<sup>1</sup> FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 3 of 72	

## 2. DUT DESCRIPTION



FCC ID: A3LSMG950U  
 Applicant: Samsung Electronics Co., Ltd.  
 129, Samsung-ro, Maetan dong,  
 Yeongtong-gu, Suwon-si  
 Gyeonggi-do 16677, Korea

Model(s): SM-G950U  
 Additional Model(s): SM-G950U1, SM-G950W

Serial Number: 82773  
 HW Version: Rev.1.0  
 SW Version: G950U.001  
 Antenna: Internal Antenna

HAC Test Configurations: Secondary Cellular CDMA, 476, 564, 684, BT Off, WLAN Off, LTE Off  
 Cellular CDMA, 1013, 384, 777, BT Off, WLAN Off, LTE Off  
 PCS CDMA, 25, 600, 1175, BT Off, WLAN Off, LTE Off  
 GSM 850, 128, 190, 251, BT Off, WLAN Off, LTE Off  
 GSM 1900, 512, 661, 810, BT Off, WLAN Off, LTE Off  
 UMTS V, 4132, 4183, 4233, BT Off, WLAN Off, LTE Off  
 UMTS IV, 1312, 1412, 1513, BT Off, WLAN Off, LTE Off  
 UMTS II, 9262, 9400, 9538, BT Off, WLAN Off, LTE Off  
 LTE FDD B5; BW's: 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off  
 LTE FDD B12; BW's: 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off  
 LTE FDD B13; BW's: 10MHz, 5MHz; BT Off, WLAN Off  
 LTE FDD B25; BW's: 20MHz, 15MHz, 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off  
 LTE FDD B26; BW's: 15MHz, 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off  
 LTE FDD B30; BW's: 10MHz, 5MHz; BT Off, WLAN Off  
 LTE FDD B66; BW's: 20MHz, 15MHz, 10MHz, 5MHz, 3MHz, 1.4MHz; BT Off, WLAN Off  
 LTE TDD B41; BW's: 20MHz, 15MHz, 10MHz, 5MHz; BT Off, WLAN Off

\* Note: LTE test channels for different bands and bandwidths can be found in Sect. 7.II

DUT Type: Portable Handset

### I. LTE Band Selection

This device supports the following pairs of LTE bands with similar frequencies: LTE B2 & B25, LTE B12 & B17 and LTE B4 & B66. Each pair of LTE bands have the same target power and share the same transmission. Since the supported frequency spans for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B25, LTE B12 and LTE B66) were evaluated for hearing-aid compliance.

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 4 of 72	

**Table 2-1: SM-G950U & SM-G950U1 HAC Air Interfaces**

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Voice over Digital Transport OTT Capability	Additional GSM Power Reduction
CDMA	835	VO	Yes	Yes: WIFI or BT	N/A	N/A
	1900					
	EVDO	DT	No	Yes: WIFI or BT	Yes	N/A
GSM	850	VO	Yes	Yes: WIFI or BT	N/A	No
	1900					
	GPRS/EDGE	DT	No	Yes: WIFI or BT	Yes	No
UMTS	850	VD	Yes	Yes: WIFI or BT	N/A	N/A
	1700					
	1900					
	HSPA	DT	No	Yes: WIFI or BT	Yes	N/A
LTE (FDD)	700 (B12)	VD <sup>1</sup>	Yes	Yes: WIFI or BT	Yes	N/A
	700 (B17)					
	780 (B13)					
	850 (B5)					
	850 (B26)					
	1700 (B4)					
	1700 (B66)					
	1900 (B2)					
	1900 (B25)					
2300 (B30)						
LTE (TDD)	2600 (B41)	DT	No	Yes: WIFI or BT	Yes	N/A
WIFI	2450	VD	No <sup>2</sup>	Yes: CDMA, GSM, UMTS, or LTE	Yes	N/A
	5200					
	5300					
	5500					
	5800					
BT	2450	DT	No	Yes: CDMA, GSM, UMTS, or LTE	N/A	N/A
Type Transport VO = Voice Only DT = Digital Data - Not intended for CMRS Service VD = CMRS and Data Transport			Notes: 1. The 3GPP VoLTE CMRS service is defined by GSMA in PRD IR.92 for IP Voice Service and Digital Transport. 2. Not tested in accordance with the guidance issued by OET in KDB publication 285076 D02 T-Coil testing for CMRS IP.			

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 5 of 72	

**Table 2-2: SM-G950W HAC Air Interfaces**

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Voice over Digital Transport OTT Capability	Additional GSM Power Reduction
GSM	850	VO	Yes	Yes: WIFI or BT	N/A	No
	1900					
	GPRS/EDGE	DT	No	Yes: WIFI or BT	Yes	No
UMTS	850	VD	Yes	Yes: WIFI or BT	N/A	N/A
	1700					
	1900					
	HSPA	DT	No	Yes: WIFI or BT	Yes	N/A
LTE (FDD)	700 (B12)	VD <sup>1</sup>	Yes	Yes: WIFI or BT	Yes	N/A
	700 (B17)					
	780 (B13)					
	850 (B5)					
	1700 (B4)					
	1700 (B66)					
	1900 (B2)					
	1900 (B25)					
2300 (B30)						
LTE (TDD)	2600 (B41)	VD <sup>1</sup>	Yes	Yes: WIFI or BT	Yes	N/A
WIFI	2450	VD	No <sup>2</sup>	Yes: GSM, UMTS, or LTE	Yes	N/A
	5200					
	5300					
	5500					
	5800					
BT	2450	DT	No	Yes: GSM, UMTS, or LTE	N/A	N/A
Type Transport VO = Voice Only DT = Digital Data - Not intended for CMRS Service VD = CMRS and Data Transport			Notes: 1. The 3GPP VoLTE CMRS service is defined by GSMA in PRD IR.92 for IP Voice Service and Digital Transport. 2. Not tested in accordance with the guidance issued by OET in KDB publication 285076 D02 T-Coil testing for CMRS IP.			

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 6 of 72	

### 3. ANSI C63.19-2011 PERFORMANCE CATEGORIES


#### I. MAGNETIC COUPLING

##### Axial and Radial Field Intensity


All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be  $\geq -18$  dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

##### Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.



**Figure 3-1**  
Magnetic field frequency response for Wireless Devices with an axial field  $\leq -15$  dB(A/m) at 1 kHz



**Figure 3-2**  
Magnetic Field frequency response for wireless devices with an axial field that exceeds  $-15$  dB(A/m) at 1 kHz

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 7 of 72

## Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Category	Telephone RF Parameters
	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]
T1	0 to 10 dB
T2	10 to 20 dB
T3	20 to 30 dB
T4	> 30 dB


Table 3-1  
**Magnetic Coupling Parameters**

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 8 of 72	


## 4. METHOD OF MEASUREMENT

### I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:



**Figure 4-1**  
Validation Setup with Helmholtz Coil



**Figure 4-2**  
T-Coil Test Setup

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 9 of 72


© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## II. Scanning Mechanism


Manufacturer: TEM  
 Accuracy:  $\pm 0.83$  cm/meter  
 Minimum Step Size: 0.1 mm  
 Maximum speed: 6.1 cm/sec  
 Line Voltage: 115 VAC  
 Line Frequency: 60 Hz  
 Material Composite: Delrin (Acetal)  
 Data Control: Parallel Port  
 Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm  
 Dimensions: 36" x 25" x 38"  
 Operating Area: 36" x 49" x 55"  
 Reflections: < -20 dB (in anechoic chamber)



**Figure 4-3**  
RF Near-Field Scanner

## III. 3GPP2 Normal Test Signal (Speech)

Manufacturer: 3GPP2 (TIA 1042 §3.3.1)  
 Modified-IRS weighted, multi-talker speech signal, 4 Male and 4  
 Stimulus Type: Female speakers (alternating)  
 Single Sample Duration: 51.62 seconds  
 Activity Level: 77.4%



**Figure 4-4**  
Temporal Characteristic of Normal Test Signal


FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 10 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

ABM1 Measurement Block Diagram:



ABM2 Measurement Block Diagram:




Figure 4-5 Magnetic Measurement Processing Steps

#### IV. Test Procedure

1. Ambient Noise Check per C63.19 §7.3.1
  - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
  - b. “A-weighting” and Half-Band Integration was applied to the measurements.
  - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:  

$$-18 - 30 - 10 = -58 \text{ dBA/m}$$
2. Measurement System Validation(See Figure 4-1)
  - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
  - b. ABM1 Validation  
 The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N\left(\frac{V}{R}\right)}{r\sqrt{1.25^3}}$$

Where  $H_c$  = magnetic field strength in amperes per meter  
 $N$  = number of turns per coil

For the Helmholtz Coil,  $N=20$ ;  $r=0.08\text{m}$ ;  $R=10.2\Omega$  and using  $V=18\text{mV}$ :

$$H_c = \frac{20 \cdot \left(\frac{0.018}{10.2}\right)}{0.08 \cdot \sqrt{1.25^3}} = 0.316 \text{ A/m} \approx -10 \text{ dB(A/m)}$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within  $\pm 0.5$  dB of the -10dB(A/m) value (see Page 31).

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 11 of 72

c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the Normal signal as shown below:




Figure 4-6 Frequency Response Validation


d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1  
ABM2 Frequency Response Validation


f (Hz)	HBI, A - Measured (dB re 1kHz)	HBI, A - Theoretical (dB re 1kHz)	dB Var.
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 12 of 72



**Figure 4-7**  
**ABM2 Frequency Response Validation**

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-8). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:




**Figure 4-8**  
**ABM2 Validation Block Diagram**

The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

**Table 4-2**  
**ABM2 Power Sum Validation**

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 13 of 72




**Figure 4-9**  
**ABM2 Power Sum Validation**


3. Measurement Test Setup

a. Fine scan above the WD (TEM)

- i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-11, the grid is not to scale but merely a graphical representation of the coordinate system in use):



**Figure 4-10**  
**Measurement Distance**



**Figure 4-11**  
**Measurement Grid**

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
  - iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
- i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN™	TDMA (22 and 11 Hz)	-18


FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 14 of 72

The CMU200 audio levels were determined using base station simulator manufacturer calibration procedures resulting in the below corresponding voltages relative to handset test point level (in dBm0):

**Table 4-3  
CMU200 Voltage Input Levels for Audio**

dBm0 Ref.	Input Voltage		Notes
3.14 dBm0	1052.0 mV	0.4 dBV	From CDMA2K "DECODER CAL". (What is needed through Encoder for FS)
-18 dBm0	92.260 mV	-20.7 dBV	For 8k Enhanced (Low)
dBm0 Ref.	Voltage		Notes
3.14 dBm0	990.5 mV	-0.08 dBV	From GSM "DECODER CAL". (What is needed through Encoder for FS)
-16 dBm0	109.4 mV	-19.2 dBV	For Speechcod/Handset Low
dBm0 Ref.	Voltage		Notes
3.14 dBm0	1068.5 mV	0.58 dBV	From UMTS "DECODER CAL". (What is needed through Encoder for FS)
-16 dBm0	118.0 mV	-18.6 dBV	For Handset Low

- ii. See Section 5 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE) testing.
- c. Real-Time Analyzer (RTA)
  - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
  - i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 6 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5):



**Figure 4-12  
Vocoder Analysis for ABM Noise for GSM**

- 4. Signal Quality Data Analysis
  - a. Narrow-band Magnetic Intensity
    - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
  - b. Frequency Response
    - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 – 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 15 of 72

- delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-6. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
  - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.
- c. Signal Quality Index
- i. Ensuring the WD was at maximum RF power, maximum volume, backlight on, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz – 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
  - ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
  - iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

## V. Test Setup




Figure 4-13  
Audio Magnetic Field Test Setup

## VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to shielding effects of battery cover.

## VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

According to the April 2013 TCB workshop slides, OTT data services are outside the current definition of a managed CMRS service and are currently not required to be evaluated.

VoIP over WIFI CMRS air interfaces were not tested in accordance with the guidance issued by OET in KDB publication 285076 D02 T-Coil testing for CMRS IP.

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 16 of 72

## VIII. Wireless Device Channels and Frequencies

### 1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band.


**Table 4-4  
Center Channels and Frequencies**

Test frequencies & associated channels	
Channel	Frequency (MHz)
<b>Secondary Cellular 820</b>	
564 (CDMA)	820.10
<b>Cellular 850</b>	
384 (CDMA)	836.52
190 (GSM)	836.60
4183 (UMTS)	836.60
<b>AWS 1750</b>	
1412 (UMTS)	1730.40
<b>PCS 1900</b>	
600 (CDMA)	1880
661 (GSM)	1880
9400 (UMTS)	1880

### 2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. See Table 7-10 through Table 7-17 for LTE bandwidths and channels.

## IX. RF Emission Effect on T-coil Measurements




**Figure 4-14**

**High power RF Emissions Effect with HAC Dipole on the T-coil Probe System 10mm between dipole maximum and magnetic probe**

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 17 of 72

## X. Test Flow

The flow diagram below was followed (From C63.19):



**Figure 4-15**  
**C63.19 T-Coil Signal Test Process**

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 18 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M

11/29/2016


© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

### I. Test System Setup for VoLTE T-coil Testing

#### 1. Equipment Setup

The general test setup used for VoLTE is shown below (adopted from FCC KDB 285076 D02). The callbox used when performing VoLTE T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.



**Figure 5-1**  
**Test Setup for VoLTE T-Coil Measurements**

#### 2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for LTE T-coil testing, -16dBm0 shall be used for the normal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE connection.

\* [http://c63.org/documents/misc/posting/new\\_interpretations.htm](http://c63.org/documents/misc/posting/new_interpretations.htm)

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>	
<b>Approved by:</b> Quality Manager			
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 19 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M

11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## II. DUT Configuration for VoLTE T-coil Testing

### 1. Radio Configuration

An investigation was performed on the worst-case LTE Band and bandwidth combination to determine the modulation and RB configuration to be used for testing. While this device supports 64QAM, this modulation was not evaluated to due to test equipment limitations. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

**Table 5-1**  
**LTE SNNR by Radio Configuration**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	15	QPSK	1	0	-1.65	-38.17	36.52
2593.0	40620	15	QPSK	1	36	-1.87	-38.36	36.49
2593.0	40620	15	QPSK	1	74	-2.06	-39.40	37.34
2593.0	40620	15	QPSK	36	0	-2.10	-38.62	36.52
2593.0	40620	15	QPSK	36	18	-1.64	-38.87	37.23
2593.0	40620	15	QPSK	36	37	-2.02	-38.50	36.48
2593.0	40620	15	QPSK	75	0	-1.64	-38.32	36.68
2593.0	40620	15	16QAM	1	0	-1.94	-38.40	36.46
2593.0	40620	15	16QAM	1	36	-1.51	-38.89	37.38
2593.0	40620	15	16QAM	1	74	-1.90	-38.82	36.92
2593.0	40620	15	16QAM	36	0	-2.23	-39.21	36.98
2593.0	40620	15	16QAM	36	18	-2.12	-39.43	37.31
2593.0	40620	15	16QAM	36	37	-1.53	-39.28	37.75
2593.0	40620	15	16QAM	75	0	-1.98	-39.03	37.05


### 2. Codec Configuration

An investigation was performed on the worst-case LTE Band and bandwidth combination to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE T-coil testing. See below table for ABM1 and ABM2 comparisons between different codecs and codec data rates:

**Table 5-2**  
**FCC 4G ABM Measurements for A3LSMG950U**

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 Pre-test (dBA/m)	-1.05	-1.77	-0.08	-0.07	Axial	LTE TDD Band 41 / 15MHz	40620
ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.)	-37.65	-37.67	-37.59	-37.74			
S+N/N (dB)	36.60	35.90	37.51	37.67			

- Mute on; Backlight on; Max Volume; Max Contrast
- TPC = "Max Power"



**Figure 5-2**  
**Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 20 of 72

### 3. LTE TDD Uplink-Downlink Configuration Investigation

An investigation was performed to determine the worst-case Uplink-Downlink configuration for LTE TDD T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length  $T_f = 307200 \cdot T_s = 10$  ms, where  $T_s$  is a number of time units equal to  $1/(15000 \times 2048)$  seconds. Additionally, each radio frame consists of 10 subframes, each of length  $30720 \cdot T_s = 1$  ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is  $2192 \cdot T_s$  which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

**Table 5-3**  
**Uplink-Downlink Configurations for Type 2 Frame Structures**

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number										Calculated Transmission Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

The following configuration was evaluated: channel 40620, 20MHz BW, 16QAM, 1RB, 0RB Offset. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 2 was used as the worst-case configuration for LTE TDD T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

**Table 5-4**  
**LTE SNNR by UL-DL Configuration**

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	0	0	-1.91	-38.16	36.25
2593.0	40620	20	QPSK	1	0	1	-1.67	-37.86	36.19
2593.0	40620	20	QPSK	1	0	2	-2.02	-38.15	<b>36.13</b>
2593.0	40620	20	QPSK	1	0	3	-1.95	-40.78	38.83
2593.0	40620	20	QPSK	1	0	4	-2.15	-40.51	38.36
2593.0	40620	20	QPSK	1	0	5	-2.31	-41.01	38.70
2593.0	40620	20	QPSK	1	0	6	-2.10	-38.26	36.16

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 21 of 72	

## 6. FCC 3G MEASUREMENTS

### I. CDMA Test Configurations

Radio Configuration 1, Service Option 68 was used for the testing according to the CTIA Test Plan and also as one of the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for an example of ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:




Figure 6-1  
CDMA Audio Band Magnetic Noise

Table 6-1  
FCC 3G ABM Measurements for A3LSMG950U (CDMA)

Codec Setting:	RC1/SO68	RC3/SO68	RC4/SO68	Orientation	Channel
ABM1 Pre-test (dBA/m)	-1.29	-1.13	-1.39	Radial	25
ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.)	-45.62	-52.71	-52.32		
S+N/N (dB)	44.33	51.58	50.93		

- Mute on; Backlight on; Max Volume; Max Contrast
- Power Control Bits = "All Up"





Figure 6-2  
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 22 of 72

## II. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:




**Figure 6-3**  
**UMTS Audio Band Magnetic Noise**

**Table 6-2**  
**FCC 3G ABM Measurements for A3LSMG950U (UMTS)**

Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel
ABM1 Pre-test (dBA/m)	-0.11	-0.16	-0.37	Radial	9400
ABM2 Pre-test (dBA/m) (A-weight, Half-Band Int.)	-52.52	-52.68	-53.12		
S+N/N (dB)	52.41	52.52	52.75		

- Mute on; Backlight on; Max Volume; Max Contrast
- TPC="All 1s"



**Figure 6-4**  
**Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 23 of 72

## 7. TEST SUMMARY

### I. T-Coil Test Summary

**Table 7-1**  
**Table of Results for CDMA**

C63.19 Sec.	Mode	Band	Test Description	Minimum Limit*	Measured	Verdict
				<i>dBa/m</i>	<i>dBa/m</i>	<i>PASS/FAIL</i>
8.3.1	CDMA	Secondary Cellular	Intensity, Axial	-18	6.2	PASS
8.3.1			Intensity, Radial	-18	-1.6	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	51.0	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	45.3	PASS
8.3.2			Frequency Response, Axial	0	1.9	PASS
8.3.1	CDMA	Cellular	Intensity, Axial	-18	6.0	PASS
8.3.1			Intensity, Radial	-18	-1.7	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	50.6	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	45.1	PASS
8.3.2			Frequency Response, Axial	0	1.9	PASS
8.3.1	CDMA	PCS	Intensity, Axial	-18	5.8	PASS
8.3.1			Intensity, Radial	-18	-1.5	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	52.2	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	44.3	PASS
8.3.2			Frequency Response, Axial	0	1.9	PASS

Note: The above summary table represents the worst-case numerical values according to configurations in Table 7-7.

**Table 7-2**  
**Table of Results for GSM**

C63.19 Sec.	Mode	Band	Test Description	Minimum Limit*	Measured	Verdict
				<i>dBa/m</i>	<i>dBa/m</i>	<i>PASS/FAIL</i>
8.3.1	GSM	Cellular	Intensity, Axial	-18	7.9	PASS
8.3.1			Intensity, Radial	-18	-0.3	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	35.5	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	28.1	PASS
8.3.2			Frequency Response, Axial	0	1.5	PASS
8.3.1	GSM	PCS	Intensity, Axial	-18	7.8	PASS
8.3.1			Intensity, Radial	-18	-0.3	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	42.0	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	32.3	PASS
8.3.2			Frequency Response, Axial	0	1.5	PASS

Note: The above summary table represents the worst-case numerical values according to configurations in Table 7-8.

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 24 of 72

**Table 7-3  
Table of Results for UMTS**

C63.19 Sec.	Mode	Band	Test Description	Minimum Limit*	Measured	Verdict
				<i>dBa/m</i>	<i>dBa/m</i>	<i>PASS/FAIL</i>
8.3.1	UMTS	Band 5	Intensity, Axial	-18	7.5	PASS
8.3.1			Intensity, Radial	-18	-0.1	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	62.2	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	52.6	PASS
8.3.2			Frequency Response, Axial	0	1.8	PASS
8.3.1	UMTS	Band 4	Intensity, Axial	-18	7.4	PASS
8.3.1			Intensity, Radial	-18	-0.2	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	62.6	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	52.5	PASS
8.3.2			Frequency Response, Axial	0	1.8	PASS
8.3.1	UMTS	Band 2	Intensity, Axial	-18	7.6	PASS
8.3.1			Intensity, Radial	-18	-0.1	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	62.3	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	52.2	PASS
8.3.2			Frequency Response, Axial	0	1.9	PASS

Note: The above summary table represents the worst-case numerical values according to configurations in Table 7-9.

**Table 7-4  
Table of Results for LTE FDD**

C63.19 Sec.	Mode	Band	Test Description	Minimum Limit*	Measured	Verdict
				<i>dBa/m</i>	<i>dBa/m</i>	<i>PASS/FAIL</i>
8.3.1	LTE FDD	Band 12	Intensity, Axial	-18	5.0	PASS
8.3.1			Intensity, Radial	-18	-2.0	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	52.4	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	46.6	PASS
8.3.2			Frequency Response, Axial	0	1.7	PASS
8.3.1	LTE FDD	Band 13	Intensity, Axial	-18	5.1	PASS
8.3.1			Intensity, Radial	-18	-2.1	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	50.3	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	44.7	PASS
8.3.2			Frequency Response, Axial	0	1.7	PASS
8.3.1	LTE FDD	Band 26	Intensity, Axial	-18	4.7	PASS
8.3.1			Intensity, Radial	-18	-2.2	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	51.2	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	45.7	PASS
8.3.2			Frequency Response, Axial	0	1.6	PASS
8.3.1	LTE FDD	Band 5	Intensity, Axial	-18	5.1	PASS
8.3.1			Intensity, Radial	-18	-2.1	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	51.9	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	46.8	PASS
8.3.2			Frequency Response, Axial	0	1.6	PASS
8.3.1	LTE FDD	Band 66	Intensity, Axial	-18	5.1	PASS
8.3.1			Intensity, Radial	-18	-2.0	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	50.4	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	45.4	PASS
8.3.2			Frequency Response, Axial	0	1.5	PASS
8.3.1	LTE FDD	Band 25	Intensity, Axial	-18	5.1	PASS
8.3.1			Intensity, Radial	-18	-2.0	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	50.7	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	45.1	PASS
8.3.2			Frequency Response, Axial	0	1.5	PASS
8.3.1	LTE FDD	Band 30	Intensity, Axial	-18	5.0	PASS
8.3.1			Intensity, Radial	-18	-1.8	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	49.9	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	44.7	PASS
8.3.2			Frequency Response, Axial	0	1.7	PASS

Note: The above summary table represents the worst-case numerical values according to configurations in Table 7-10 through Table 7-16.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 25 of 72	

**Table 7-5**  
**Table of Results for LTE TDD**

C63.19 Sec.	Mode	Band	Test Description	Minimum Limit*	Measured	Verdict
				<i>dBA/m</i>	<i>dBA/m</i>	<i>PASS/FAIL</i>
8.3.1	LTE TDD	Band 41	Intensity, Axial	-18	4.9	PASS
8.3.1			Intensity, Radial	-18	-2.2	PASS
8.3.4			Signal-to-Noise/Noise, Axial	20	41.2	PASS
8.3.4			Signal-to-Noise/Noise, Radial	20	36.2	PASS
8.3.2			Frequency Response, Axial	0	1.6	PASS

Note: The above summary table represents the worst-case numerical values according to configurations in Table 7-17.

**Table 7-6**  
**Consolidated Tabled Results**

		Freq. Response Margin		Magnetic Intensity Verdict		FCC SNRR Verdict		FCC Margin (dB)	C63.19-2011 Rating
		Axial	Radial	Axial	Radial	Axial	Radial		
CDMA	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS	-24.26	T4
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-8.08	T3
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
UMTS	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-32.18	T4
	AWS	PASS	NA	PASS	PASS	PASS	PASS		
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B12	PASS	NA	PASS	PASS	PASS	PASS	-24.09	T4
	B13	PASS	NA	PASS	PASS	PASS	PASS		
	B26	PASS	NA	PASS	PASS	PASS	PASS		
	B5	PASS	NA	PASS	PASS	PASS	PASS		
	B66	PASS	NA	PASS	PASS	PASS	PASS		
	B25	PASS	NA	PASS	PASS	PASS	PASS		
B30	PASS	NA	PASS	PASS	PASS	PASS			
LTE TDD	B41	PASS	NA	PASS	PASS	PASS	PASS	-16.21	T4

Note: Result shown is for T-coil category only.

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 26 of 72

## II. Raw Handset Data

**Table 7-7**  
**Raw Data Results for CDMA**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
Secondary Cellular	Axial	476	6.19	-46.74	-64.13	1.93	52.93	20.00	-32.93	T4	2.2, 2.6
		564	6.22	-44.76		2.00	50.98	20.00	-30.98	T4	
		684	6.18	-44.95		1.94	51.13	20.00	-31.13	T4	
	Radial	476	-1.46	-48.07	-64.79	N/A	46.61	20.00	-26.61	T4	2.2, 1.8
		564	-1.36	-47.39		46.03	20.00	-26.03	T4		
		684	-1.57	-46.85		45.28	20.00	-25.28	T4		
Cellular	Axial	1013	6.02	-44.61	-64.13	1.97	50.63	20.00	-30.63	T4	2.2, 2.6
		384	6.14	-45.84		1.93	51.98	20.00	-31.98	T4	
		777	6.04	-45.76		2.00	51.80	20.00	-31.80	T4	
	Radial	1013	-1.55	-47.21	-64.79	N/A	45.66	20.00	-25.66	T4	2.2, 1.8
		384	-1.67	-47.17		45.50	20.00	-25.50	T4		
		777	-1.43	-46.50		45.07	20.00	-25.07	T4		
PCS	Axial	25	5.75	-46.60	-64.13	2.00	52.35	20.00	-32.35	T4	2.2, 2.6
		600	6.16	-46.03		1.99	52.19	20.00	-32.19	T4	
		1175	5.97	-46.56		1.92	52.53	20.00	-32.53	T4	
	Radial	25	-1.48	-45.74	-64.79	N/A	44.26	20.00	-24.26	T4	2.2, 1.8
		600	-1.38	-46.16		44.78	20.00	-24.78	T4		
		1175	-1.40	-45.99		44.59	20.00	-24.59	T4		

**Table 7-8**  
**Raw Data Results for GSM**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
GSM850	Axial	128	8.02	-28.10	-64.13	1.49	36.12	20.00	-16.12	T4	2.2, 2.6
		190	8.13	-28.16		1.47	36.29	20.00	-16.29	T4	
		251	7.93	-27.57		1.47	35.50	20.00	-15.50	T4	
	Radial	128	-0.25	-28.33	-64.79	N/A	28.08	20.00	-8.08	T3	2.2, 1.8
		190	-0.27	-29.83		29.56	20.00	-9.56	T3		
		251	-0.29	-30.25		29.96	20.00	-9.96	T3		
GSM1900	Axial	512	8.02	-34.58	-64.13	1.45	42.60	20.00	-22.60	T4	2.2, 2.6
		661	7.80	-34.39		1.47	42.19	20.00	-22.19	T4	
		810	7.78	-34.18		1.51	41.96	20.00	-21.96	T4	
	Radial	512	-0.23	-33.78	-64.79	N/A	33.55	20.00	-13.55	T4	2.2, 1.8
		661	-0.23	-32.52		32.29	20.00	-12.29	T4		
		810	-0.28	-32.73		32.45	20.00	-12.45	T4		

**Table 7-9**  
**Raw Data Results for UMTS**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
UMTS Band 5	Axial	4132	7.45	-54.71	-64.13	1.81	62.16	20.00	-42.16	T4	2.2, 2.6
		4183	7.51	-55.48		1.95	62.99	20.00	-42.99	T4	
		4233	7.53	-55.87		1.77	63.40	20.00	-43.40	T4	
	Radial	4132	-0.10	-53.05	-64.79	N/A	52.95	20.00	-32.95	T4	2.2, 1.8
		4183	-0.10	-52.95		52.85	20.00	-32.85	T4		
		4233	-0.11	-52.71		52.60	20.00	-32.60	T4		
UMTS Band 4	Axial	1312	7.46	-55.30	-64.13	2.00	62.76	20.00	-42.76	T4	2.2, 2.6
		1412	7.43	-55.15		1.77	62.58	20.00	-42.58	T4	
		1513	7.40	-55.22		1.92	62.62	20.00	-42.62	T4	
	Radial	1312	-0.13	-52.65	-64.79	N/A	52.52	20.00	-32.52	T4	2.2, 1.8
		1412	-0.19	-53.07		52.88	20.00	-32.88	T4		
		1513	-0.16	-52.83		52.67	20.00	-32.67	T4		
UMTS Band 2	Axial	9262	7.62	-55.26	-64.13	1.91	62.88	20.00	-42.88	T4	2.2, 2.6
		9400	7.65	-55.17		1.93	62.82	20.00	-42.82	T4	
		9538	7.60	-54.65		1.88	62.25	20.00	-42.25	T4	
	Radial	9262	-0.11	-52.92	-64.79	N/A	52.81	20.00	-32.81	T4	2.2, 1.8
		9400	-0.11	-52.29		52.18	20.00	-32.18	T4		
		9538	-0.11	-53.13		53.02	20.00	-33.02	T4		

FCC ID: A3L3SMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 27 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

**Table 7-10**  
**Raw Data Results for LTE FDD B12**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 12	Axial	10MHz	23095	5.11	-48.04	-61.77	1.66	53.15	20.00	-33.15	T4	2.2, 2.6
		5MHz	23095	5.04	-48.63		1.67	53.67	20.00	-33.67	T4	
		3MHz	23095	5.55	-47.23		1.72	52.78	20.00	-32.78	T4	
		1.4MHz	23095	5.03	-47.34		1.68	52.37	20.00	-32.37	T4	
	Radial	10MHz	23095	-1.98	-49.12	-60.67	N/A	47.14	20.00	-27.14	T4	2.2, 1.8
		5MHz	23095	-1.60	-48.66			47.06	20.00	-27.06	T4	
		3MHz	23095	-2.04	-48.82			46.78	20.00	-26.78	T4	
		1.4MHz	23095	-1.57	-48.15			46.58	20.00	-26.58	T4	

**Table 7-11**  
**Raw Data Results for LTE FDD B13**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 13	Axial	10MHz	23230	5.26	-45.04	-61.77	1.68	50.30	20.00	-30.30	T4	2.2, 2.6
		5MHz	23230	5.10	-46.09		1.69	51.19	20.00	-31.19	T4	
	Radial	10MHz	23230	-1.99	-46.69	-60.67	N/A	44.70	20.00	-24.70	T4	2.2, 1.8
		5MHz	23230	-2.06	-48.38			46.32	20.00	-26.32	T4	

**Table 7-12**  
**Raw Data Results for LTE FDD B26**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 26	Axial	15MHz	26865	4.70	-46.51	-61.77	1.61	51.21	20.00	-31.21	T4	2.2, 2.6
		10MHz	26865	5.29	-46.60		1.77	51.89	20.00	-31.89	T4	
		5MHz	26865	4.90	-47.26		1.70	52.16	20.00	-32.16	T4	
		3MHz	26865	4.97	-47.02		1.70	51.99	20.00	-31.99	T4	
		1.4MHz	26865	5.37	-46.51		1.98	51.88	20.00	-31.88	T4	
	Radial	15MHz	26865	-1.65	-47.60	-60.67	N/A	45.95	20.00	-25.95	T4	2.2, 1.8
		10MHz	26865	-2.08	-47.84			45.76	20.00	-25.76	T4	
		5MHz	26865	-2.15	-48.30			46.15	20.00	-26.15	T4	
		3MHz	26865	-2.16	-47.94			45.78	20.00	-25.78	T4	
		1.4MHz	26865	-2.04	-47.75			45.71	20.00	-25.71	T4	

**Table 7-13**  
**Raw Data Results for LTE FDD B5**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 5	Axial	10MHz	20525	5.06	-46.84	-61.77	1.73	51.90	20.00	-31.90	T4	2.2, 2.6
		5MHz	20525	5.37	-46.60		1.59	51.97	20.00	-31.97	T4	
		3MHz	20525	5.17	-47.37		1.59	52.54	20.00	-32.54	T4	
		1.4MHz	20525	5.34	-46.61		1.69	51.95	20.00	-31.95	T4	
	Radial	10MHz	20525	-1.58	-48.73	-60.67	N/A	47.15	20.00	-27.15	T4	2.2, 1.8
		5MHz	20525	-2.05	-49.22			47.17	20.00	-27.17	T4	
		3MHz	20525	-1.95	-48.72			46.77	20.00	-26.77	T4	
		1.4MHz	20525	-1.64	-48.42			46.78	20.00	-26.78	T4	

FCC ID: A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 28 of 72

**Table 7-14**  
**Raw Data Results for LTE FDD B66**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 66	Axial	20MHz	132322	5.09	-45.65	-61.77	1.72	50.74	20.00	-30.74	T4	2.2, 2.6
		15MHz	132322	5.25	-45.90		1.76	51.15	20.00	-31.15	T4	
		10MHz	132322	5.29	-45.13		1.70	50.42	20.00	-30.42	T4	
		5MHz	132322	5.37	-45.83		1.52	51.20	20.00	-31.20	T4	
		3MHz	132322	5.26	-45.99		1.68	51.25	20.00	-31.25	T4	
		1.4MHz	132208	5.34	-46.04		1.74	51.38	20.00	-31.38	T4	
	Radial	20MHz	132322	-1.56	-48.29	-60.67	N/A	46.73	20.00	-26.73	T4	2.2, 1.8
		15MHz	132322	-1.86	-48.08			46.22	20.00	-26.22	T4	
		10MHz	132322	-1.90	-47.99			46.09	20.00	-26.09	T4	
		5MHz	132322	-1.67	-48.48			46.81	20.00	-26.81	T4	
		3MHz	132322	-2.02	-48.13			46.11	20.00	-26.11	T4	
		1.4MHz	132208	-1.96	-47.39			45.43	20.00	-25.43	T4	

**Table 7-15**  
**Raw Data Results for LTE FDD B25**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 25	Axial	20MHz	26365	5.23	-46.12	-61.77	1.66	51.35	20.00	-31.35	T4	2.2, 2.6
		15MHz	26365	5.25	-45.44		1.63	50.69	20.00	-30.69	T4	
		10MHz	26365	5.07	-46.16		1.83	51.23	20.00	-31.23	T4	
		5MHz	26365	5.18	-46.38		1.68	51.56	20.00	-31.56	T4	
		3MHz	26365	5.40	-46.53		1.52	51.93	20.00	-31.93	T4	
		1.4MHz	26365	5.23	-45.58		1.57	50.81	20.00	-30.81	T4	
	Radial	20MHz	26365	-1.96	-47.74	-60.67	N/A	45.78	20.00	-25.78	T4	2.2, 1.8
		15MHz	26365	-1.97	-47.34			45.37	20.00	-25.37	T4	
		10MHz	26365	-1.83	-46.98			45.15	20.00	-25.15	T4	
		5MHz	26365	-2.00	-48.07			46.07	20.00	-26.07	T4	
		3MHz	26365	-2.02	-47.37			45.35	20.00	-25.35	T4	
		1.4MHz	26365	-1.94	-47.05			45.11	20.00	-25.11	T4	

**Table 7-16**  
**Raw Data Results for LTE FDD B30**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 30	Axial	10MHz	27710	5.11	-44.79	-61.77	1.71	49.90	20.00	-29.90	T4	2.2, 2.6
		5MHz	27710	5.03	-45.26		1.73	50.29	20.00	-30.29	T4	
	Radial	10MHz	27710	-1.83	-46.52	-60.67	N/A	44.69	20.00	-24.69	T4	2.2, 1.8
		5MHz	27710	-1.76	-46.70			44.94	20.00	-24.94	T4	

**Table 7-17**  
**Raw Data Results for LTE TDD B41**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	FCC Margin (dB)	C63.19-2011 Rating	Test Coordinates
LTE Band 41	Axial	20MHz	40620	5.12	-37.84	-61.77	1.65	42.96	20.00	-22.96	T4	2.2, 2.6
		15MHz	41490	5.39	-38.13		1.66	43.52	20.00	-23.52	T4	
		15MHz	41055	5.36	-37.99		1.69	43.35	20.00	-23.35	T4	
		15MHz	40620	4.86	-38.01		1.78	42.87	20.00	-22.87	T4	
		15MHz	40185	5.25	-39.11		1.75	44.36	20.00	-24.36	T4	
		15MHz	39750	4.87	-36.33		1.65	41.20	20.00	-21.20	T4	
		10MHz	40620	5.17	-37.82		1.56	42.99	20.00	-22.99	T4	
		5MHz	40620	5.33	-37.66		1.73	42.99	20.00	-22.99	T4	
		Radial	20MHz	40620	-2.17		-38.48	-60.67	N/A	36.31	20.00	
	15MHz		41490	-2.11	-38.61	36.50	20.00			-16.50	T4	
	15MHz		41055	-1.91	-38.73	36.82	20.00			-16.82	T4	
	15MHz		40620	-1.86	-38.07	36.21	20.00			-16.21	T4	
	15MHz		40185	-1.67	-39.58	37.91	20.00			-17.91	T4	
	15MHz		39750	-1.84	-38.07	36.23	20.00			-16.23	T4	
	10MHz		40620	-1.82	-38.11	36.29	20.00			-16.29	T4	
	5MHz		40620	-1.87	-38.37	36.50	20.00			-16.50	T4	

FCC ID: A3LSMG950U	 PCTEST ENGINEERING LABORATORY, INC.	<b>HAC (T-COIL) TEST REPORT</b>		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 29 of 72	

### III. Test Notes

#### A. General

1. Phone Condition: Mute on; Backlight on; Max Volume; Max Contrast
2. 'Radial' orientation refers to radial transverse.
3. Hearing Aid Mode (**Phone→Call Settings→More Settings→Hearing aids**) was set to ON for Frequency Response compliance

#### B. CDMA

1. Power Configuration: Power Control Bits = "All Up"
2. Vocoder Configuration: RC1/SO68 (CDMA – EVRC-B)
3. Speech Signal: 3GPP2 Normal Test Signal

#### C. GSM

1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
2. Vocoder Configuration: EFR (GSM);
3. Speech Signal: 3GPP2 Normal Test Signal

#### D. UMTS

1. Power Configuration: TPC="All 1s";
2. Vocoder Configuration: AMR 12.2 kbps (UMTS);
3. Speech Signal: 3GPP2 Normal Test Signal

#### E. LTE FDD


1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Vocoder Configuration: WB AMR 6.60kbps
4. Speech Signal: 3GPP2 Normal Test Signal
5. The worst case LTE FDD band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 30 at 10MHz is the worst case for both Axial and Radial probe orientations however there are no low or high channels due to bandwidth size.

#### F. LTE TDD


1. Power Configuration: TPC = "Max Power"
2. Radio Configuration: 16QAM, 1RB, 0RB offset
3. Uplink-Downlink configuration: 2
4. Vocoder Configuration: WB AMR 6.60kbps
5. Speech Signal: 3GPP2 Normal Test Signal
6. The worst case LTE TDD band and bandwidth combination for each probe orientation is additionally tested on the low, low mid, mid high and high channels for those combinations. LTE Band 41 at 15MHz is the worst case for both Axial and Radial probe orientations.

<b>FCC ID:</b> A3L5MG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 30 of 72	

## IV. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE. This measurement was taken in the axial configuration above the maximum location.

## V. T-Coil Validation Test Results

**Table 7-18**  
**Helmholtz Coil Validation Table of Results – 12/31/2016**

Item	Target	Result	Verdict
<b>Axial</b>			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.127	PASS
Environmental Noise	< -58 dBA/m	-64.13	PASS
Frequency Response, from limits	> 0 dB	0.60	PASS
<b>Radial</b>			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.243	PASS
Environmental Noise	< -58 dBA/m	-64.79	PASS
Frequency Response, from limits	> 0 dB	0.60	PASS

**Table 7-19**  
**Helmholtz Coil Validation Table of Results – 01/09/2017**

Item	Target	Result	Verdict
<b>Axial</b>			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.093	PASS
Environmental Noise	< -58 dBA/m	-61.77	PASS
Frequency Response, from limits	> 0 dB	0.60	PASS
<b>Radial</b>			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.234	PASS
Environmental Noise	< -58 dBA/m	-60.67	PASS
Frequency Response, from limits	> 0 dB	0.60	PASS


FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 31 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## VI. ABM1 Magnetic Field Distribution Scan Overlays



**Figure 7-1**  
**T-Coil Scan Overlay Magnetic Field Distributions**

**Notes:**

1. Final measurement locations are indicated by a cursor on the contour plots.
2. See Test Setup Photographs for actual WD overlay.

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 32 of 72	

## 8. MEASUREMENT UNCERTAINTY

**Table 8-1  
Uncertainty Estimation Table**

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

**Notes:**

1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
2. All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 33 of 72	

## 9. EQUIPMENT LIST

**Table 9-1  
Equipment List**

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Listen	SoundCheck	Acoustic Analyzer System	6/13/2016	Annual	6/13/2017	04-06-5876
Listen	SoundConnect	Microphone Power Supply	6/9/2016	Annual	6/9/2017	0899-PS150
Rohde & Schwarz	CMW500	Radio Communication Tester	5/27/2016	Annual	5/27/2017	140144
Rohde & Schwarz	CMU200	Radio Communication Tester	N/A	N/A	N/A	107826
Rohde & Schwarz	CMU200	Radio Communication Tester	3/29/2016	Annual	3/29/2017	836371/0079
TEM	Radial T-Coil Probe	Radial T-Coil Probe	6/8/2016	Annual	6/8/2017	TEM-1129
TEM	Axial T-Coil Probe	Axial T-Coil Probe	6/8/2016	Annual	6/8/2017	TEM-1123
TEM	Helmholtz Coil	Helmholtz Coil	12/7/2016	Annual	12/7/2017	925
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM		HAC Positioner	N/A		N/A	N/A

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 34 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 10. TEST DATA

See following attached pages for Test Data.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 35 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: HH Coil – SN: 925**


Type: HH Coil  
Serial: 925

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016
- Helmholtz Coil – SN: 925; Calibrated: 12/08/2016

**Noise Spectrum**



**Frequency Response**



**Results**

Verification 1kHz Intensity	-10.127 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-64.13 dB	✓	Maximum	-58.0
Frequency Response Margin	600m dB	✓	Tolerance curves	Aligned Data

PCTEST 2016

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 36 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: HH Coil – SN: 925**


Type: HH Coil  
Serial: 925

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016
- Helmholtz Coil – SN: 925; Calibrated: 12/08/2016

**Noise Spectrum**



**Frequency Response**



**Results**

Verification 1kHz Intensity	-10.093 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-61.77 dB	✓	Maximum	-58.0
Frequency Response Margin	600m dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 37 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: HH Coil – SN: 925**


Type: HH Coil  
Serial: 925

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016
- Helmholtz Coil – SN: 925; Calibrated: 12/08/2016

**Noise Spectrum**



**Frequency Response**



**Results**

Verification 1kHz Intensity	-10.243 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-64.79 dB	✓	Maximum	-58.0
Frequency Response Margin	600m dB	✓	Tolerance curves	Aligned Data

PCTEST 2016

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 38 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: HH Coil – SN: 925**


Type: HH Coil  
Serial: 925

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016
- Helmholtz Coil – SN: 925; Calibrated: 12/08/2016

**Noise Spectrum**



**Frequency Response**



**Results**

Verification 1kHz Intensity	-10.234 dB	✓	Max/Min	-9.5/-10.5
Verification ABM2	-60.67 dB	✓	Maximum	-58.0
Frequency Response Margin	600m dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 39 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: CDMA Secondary Cellular
- Channel: 564
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	6.22 dB	✓	Minimum	-18.0
ABM2	-44.76 dB	✓	Maximum	0.0
SNNR	50.98 dB	✓	Minimum	20.0
Aligned Response - Normal	2 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 40 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: CDMA Cellular
- Channel: 1013
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	6.02 dB	✓	Minimum	-18.0
ABM2	-44.62 dB	✓	Maximum	0.0
SNNR	50.63 dB	✓	Minimum	20.0
Aligned Response - Normal	1.97 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 41 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: CDMA PCS
- Channel: 600
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	6.16 dB	✓	Minimum	-18.0
ABM2	-46.04 dB	✓	Maximum	0.0
SNNR	52.19 dB	✓	Minimum	20.0
Aligned Response - Normal	1.99 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 42 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: GSM850
- Channel: 251
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	7.93 dB	✓	Minimum	-18.0
ABM2	-27.57 dB	✓	Maximum	0.0
SNNR	35.5 dB	✓	Minimum	20.0
Aligned Response - Normal	1.47 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 43 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: GSM1900
- Channel: 810
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	7.78 dB	✓	Minimum	-18.0
ABM2	-34.19 dB	✓	Maximum	0.0
SNNR	41.96 dB	✓	Minimum	20.0
Aligned Response - Normal	1.51 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 44 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: UMTS Band V
- Channel: 4132
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	7.45 dB	✓	Minimum	-18.0
ABM2	-54.71 dB	✓	Maximum	0.0
SNNR	62.16 dB	✓	Minimum	20.0
Aligned Response - Normal	1.81 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 45 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: UMTS Band IV
- Channel: 1412
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	7.43 dB	✓	Minimum	-18.0
ABM2	-55.15 dB	✓	Maximum	0.0
SNNR	62.58 dB	✓	Minimum	20.0
Aligned Response - Normal	1.77 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 46 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: UMTS Band II
- Channel: 9538
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	7.6 dB	✓	Minimum	-18.0
ABM2	-54.65 dB	✓	Maximum	0.0
SNNR	62.25 dB	✓	Minimum	20.0
Aligned Response - Normal	1.88 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 47 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



## PCTEST Hearing-Aid Compatibility Facility

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: LTE FDD Band 30
- Bandwidth: 10MHz
- Channel: 27710
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	5.11 dB	✓	Minimum	-18.0
ABM2	-44.79 dB	✓	Maximum	0.0
SNNR	49.9 dB	✓	Minimum	20.0
Aligned Response - Normal	1.71 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 48 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 06/08/2016


**Test Configuration:**

- Mode: LTE TDD Band 41
- Bandwidth: 15MHz
- Channel: 39750
- Speech Signal: 3GPP2 Normal Test Signal

**Noise Spectrum**



**Frequency Response**



**Results**

ABM1	4.87 dB	✓	Minimum	-18.0
ABM2	-36.33 dB	✓	Maximum	0.0
SNNR	41.2 dB	✓	Minimum	20.0
Aligned Response - Normal	1.65 dB	✓	Tolerance curves	Aligned Data

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 49 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: CDMA Secondary Cellular
- Channel: 684

**Noise Spectrum**



**Results**

ABM1	-1.57 dB	✓	Minimum	-18.0
ABM2	-46.84 dB	✓	Maximum	0.0
SNNR	45.28 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 50 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: CDMA Cellular
- Channel: 777

**Noise Spectrum**



**Results**

ABM1	-1.43 dB	✓	Minimum	-18.0
ABM2	-46.51 dB	✓	Maximum	0.0
SNNR	45.07 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 51 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011 / CTIA HAC Test Plan v3.0


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: CDMA PCS
- Channel: 25

**Noise Spectrum**



**Results**

ABM1	-1.48 dB	✓	Minimum	-18.0
ABM2	-45.74 dB	✓	Maximum	0.0
SNNR	44.26 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 52 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: GSM850
- Channel: 128

**Noise Spectrum**



**Results**

ABM1	-250m dB	✓	Minimum	-18.0
ABM2	-28.34 dB	✓	Maximum	0.0
SNNR	28.08 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 53 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: GSM1900
- Channel: 661

**Noise Spectrum**



**Results**

ABM1	-230m dB	✓	Minimum	-18.0
ABM2	-32.52 dB	✓	Maximum	0.0
SNNR	32.29 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 54 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: UMTS Band V
- Channel: 4233

**Noise Spectrum**



**Results**

ABM1	-110m dB	✓	Minimum	-18.0
ABM2	-52.72 dB	✓	Maximum	0.0
SNNR	52.6 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 55 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: UMTS Band IV
- Channel: 1312

**Noise Spectrum**



**Results**

ABM1	-130m dB	✓	Minimum	-18.0
ABM2	-52.64 dB	✓	Maximum	0.0
SNNR	52.52 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 56 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: UMTS Band II
- Channel: 9400

**Noise Spectrum**



**Results**

ABM1	-110m dB	✓	Minimum	-18.0
ABM2	-52.29 dB	✓	Maximum	0.0
SNNR	52.18 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 57 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



**PCTEST Hearing-Aid Compatibility Facility**

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: LTE FDD Band 30
- Bandwidth: 10MHz
- Channel: 27710

**Noise Spectrum**



**Results**

ABM1	-1.83 dB	✓	Minimum	-18.0
ABM2	-46.53 dB	✓	Maximum	0.0
SNNR	44.69 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 58 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



## PCTEST Hearing-Aid Compatibility Facility

**DUT: A3LSMG950U**

Type: Portable Handset  
Serial: 82773

**Measurement Standard:** ANSI C63.19-2011


**Equipment:**

- Probe: Radial T-Coil Probe – SN: TEM-1129; Calibrated: 06/08/2016

**Test Configuration:**

- Mode: LTE TDD Band 41
- Bandwidth: 15MHz
- Channel: 40620

**Noise Spectrum**



**Results**

ABM1	-1.86 dB	✓	Minimum	-18.0
ABM2	-38.06 dB	✓	Maximum	0.0
SNNR	36.21 dB	✓	Minimum	20.0

PCTEST 2017

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 59 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

# 11. CALIBRATION CERTIFICATES

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 60 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

West Caldwell Calibration Laboratories Inc.

# Certificate of Calibration

for

**AXIAL T COIL PROBE**

Manufactured by: TEM CONSULTING  
 Model No: AXIAL T COIL PROBE (ID#80582)  
 Serial No: TEM-1123  
 Calibration Recall No: 26516

Submitted By:

Customer: ANDREW HARWELL  
 Company: PCTEST ENGINEERING LAB  
 Address: 6660-B DOBBIN ROAD  
 COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. AXIAL T C TEM C

Upon receipt for Calibration, the instrument was found to be:

Within ( X )

*JAH*  
06/24/2016

tolerance of the indicated specification. See attached Report of Calibration.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NC SL Z540-1, IEC Guide 25, ISO 9001:2008 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date: 08-Jun-16

*FC*

Certificate No: 26516 - 3

Felix Christopher (QA Mgr.)

QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1


ISO/IEC 17025:2005

**West Caldwell Calibration Laboratories, Inc.**  
 uncompromised calibration  
 1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 61 of 72




## REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe      for      Model No.: Axial T Coil Probe      Serial No.: TEM-1123  
 Company : PCTEST Engineering Lab.      I. D. No: 80582

Calibration results:				
<b>Probe Sensitivity measured with Helmholtz Coil</b>				
<i>Helmholtz Coil;</i>				
the number of turns on each coil;	10	No.	Before & after data same: ...X.....	
the radius of each coil, in meters;	0.204	m		
the current in the coils, in amperes.;	0.09	A		
<i>Helmholtz Coil Constant;</i>	7.08	A/m/V		
<i>Helmholtz Coil magnetic field;</i>	6.20	A/m		
Laboratory Environment:				
Probe Sensitivity at		1000	Hz.	Ambient Temperature: 20.3 °C
was		-60.12	dBV/A/m	Ambient Humidity: 43.4 % RH
		0.987	mV/A/m	Ambient Pressure: 98.3 kPa
Probe resistance		895	Ohms	Calibration Date: 8-Jun-16
				Re-calibration Due: 8-Jun-17
				Report Number: 26516 -3
				Control Number: 26516

The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers: 683/284413-14  
 The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.  
 Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : **Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC**  
 Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSS Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 8-Jun-2016      Measurements performed by: *Felix Christopher*  
 Calibrated on WCCL system type 9700      **Felix Christopher**  
 This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.      Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

FCC ID: A3L5MG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 62 of 72

HCATEMC\_TEM-1123\_Jun-08-2016

**West Caldwell Calibration Laboratories Inc.**

1575 State Route 96, Victor NY 14564  
Tel. (585) 586-3900 FAX (585) 586-4327

**Calibration Data Record**

TEM Consulting LP Axial T Coil Probe      Model No.: Axial T Coil Probe      Serial No.: TEM-1123  
Company : PCTEST Engineering Lab.

Test	Function	Tolerance	Measured values			
			Before	Out	Remarks	
1.0	Probe Sensitivity at	1000 Hz.      dBV/A/m	-60.12			
2.0	Probe Level Linearity	dB				
		6	6.00			
		Ref. (0 dB)	0	0.00		
		-6	-6.03			
		-12	-12.04			
3.0	Probe Frequency Response	Hz				
		100	-19.9			
		126	-17.9			
		158	-15.9			
		200	-14.0			
		251	-12.0			
		316	-10.0			
		398	-8.0			
		501	-6.0			
		631	-4.0			
		794	-2.0			
		Ref. (0 dB)	1000	0.0		
		1259	2.0			
		1585	4.0			
		1995	6.0			
		2512	7.9			
		3162	9.9			
3981	11.9					
5012	13.9					
6310	15.9					
7943	18.0					
10000	20.2					

Instruments used for calibration:		Date of Cal.	Traceability No.	Due Date	
HP	34401A	S/N 36064102	1-Oct-2015	,287708	1-Oct-2016
HP	34401A	S/N 36102471	1-Oct-2015	,287708	1-Oct-2016
HP	33120A	S/N 36043716	1-Oct-2015	,287708	1-Oct-2016
B&K	2133	S/N 1583254	1-Oct-2015	683/284413-14	1-Oct-2016

Cal. Date: 8-Jun-2016      Tested by: Felix Christopher  
Calibrated on WCCL system type 9700  
This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.      Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 63 of 72	

West Caldwell Calibration Laboratories Inc.

# Certificate of Calibration

for

**RADIAL T COIL PROBE**

Manufactured by: TEM CONSULTING  
 Model No: RADIAL T COIL PROBE (ID#80583)  
 Serial No: TEM-1129  
 Calibration Recall No: 26516

Submitted By:

Customer: ANDREW HARWELL  
 Company: PCTEST ENGINEERING LAB  
 Address: 6660-B DOBBIN ROAD  
 COLUMBIA MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No. RADIAL T TEM C

Upon receipt for Calibration, the instrument was found to be:

Within ( X )

*FC*  
06/24/2016

tolerance of the indicated specification. See attached Report of Calibration.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2008 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date: 08-Jun-16

FC

Certificate No: 26516 - 2

Felix Christopher (QA Mgr.)

QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

ISO/IEC 17025:2005

**West Caldwell Calibration Laboratories, Inc.**  
 uncompromised calibration  
 1575 State Route 96, Victor, NY 14564, U.S.A.



Calibration Lab. Cert. # 1533.01

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 64 of 72

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).



ISO/IEC 17025: 2005



Calibration Lab. Cert. # 1533.01

# REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe

for  
Model No.: Radial T Coil Probe

Serial No.: TEM-1129


Company : PCTEST Engineering Lab.

I. D. No: 80583

Probe Sensitivity measured with Helmholtz Coil			Before & after data same: ...X.....	
<i>Helmholtz Coil;</i>				
the number of turns on each coil;	10	No.		
the radius of each coil, in meters;	0.204	m	Laboratory Environment:	
the current in the coils, in amperes.;	0.09	A	Ambient Temperature:	20.3 °C
<i>Helmholtz Coil Constant;</i>	7.08	A/m/V	Ambient Humidity:	43.4 % RH
<i>Helmholtz Coil magnetic field;</i>	6.22	A/m	Ambient Pressure:	98.3 kPa
			Calibration Date:	8-Jun-16
Probe Sensitivity at	1000	Hz.	Re-calibration Due:	8-Jun-17
was	-60.57	dBV/A/m	Report Number:	26516 -2
	0.937	mV/A/m	Control Number:	26516
Probe resistance	899	Ohms		

The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers: 683/284413-14  
 The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.  
 Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : **Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC**  
 Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 8-Jun-2016  
 Measurements performed by: *[Signature]*  
**Felix Christopher**  
 Calibrated on WCCL system type 9700  
 This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc. Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

FCC ID: A3LSMG950U	PCTEST ENGINEERING LABORATORY, INC.	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset	Page 65 of 72	

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564  
Tel. (585) 586-3900 FAX (585) 586-4327

**Calibration Data Record**

TEM Consulting LP Radial T Coil Probe      for      Model No.: Radial T Coil Probe      Serial No.: TEM-1129  
Company : PCTEST Engineering Lab.

Test	Function	Tolerance	Measured values		
			Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.      dBV/A/m	-60.57		
2.0	Probe Level Linearity	dB			
		6	5.95		
		Ref. (0 dB)      0	0.00		
		-6	-6.00		
		-12	-12.02		
3.0	Probe Frequency Response	Hz			
		100	-19.8		
		126	-18.0		
		158	-16.0		
		200	-14.0		
		251	-12.0		
		316	-10.0		
		398	-8.0		
		501	-6.0		
		631	-4.0		
		794	-2.0		
		Ref. (0 dB)      1000	0.0		
		1259	2.0		
		1585	4.0		
		1995	6.0		
		2512	7.9		
		3162	9.9		
		3981	11.9		
		5012	13.9		
6310	15.9				
7943	18.0				
10000	20.2				

Instruments used for calibration:			Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N 36064102	1-Oct-2015	,287708	1-Oct-2016
HP	34401A	S/N 36102471	1-Oct-2015	,287708	1-Oct-2016
HP	33120A	S/N 36043716	1-Oct-2015	,287708	1-Oct-2016
B&K	2133	S/N 1583254	1-Oct-2015	683/284413-14	1-Oct-2016

Cal. Date: 8-Jun-2016      Tested by: Felix Christopher  
Calibrated on WCCL system type 9700  
This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs, Inc.      Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

FCC ID: A3LSMG950U		HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename: 1M1701030004-13.A3L	Test Dates: 12/31/2016 - 01/14/2017	DUT Type: Portable Handset		Page 66 of 72

## 12. CONCLUSION

The measurements taken in accordance with the procedures provided in the CTIA Test Plan for Hearing Aid Compatibility Rev 3.0, November 2013, indicate that the wireless communications device complies with the HAC limits specified in the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 67 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

## 13. REFERENCES

1. ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids., New York, NY, IEEE, May 2011
2. CTIA Certification Program, "Test Plan for Hearing Aid Compatibility", Washington, DC, CTIA, November 2013
3. FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v04," April 26, 2016
4. FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v02," April 26, 2016
5. FCC Public Notice DA 06-1215, *Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard*, June 6, 2006
6. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
7. Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
8. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
9. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices," IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
10. Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
11. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
12. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells," U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
13. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
14. EHIMA GSM Project, Development phase, Project Report (1<sup>st</sup> part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
15. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
16. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
17. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
18. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
19. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
20. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
21. Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
22. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Construction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 68 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).

23. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7<sup>th</sup> International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
24. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
25. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
26. Ma, M. A., Sreenivashiah, I. , and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
27. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
28. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
29. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
30. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
31. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

<b>FCC ID:</b> A3LSMG950U		<b>HAC (T-COIL) TEST REPORT</b>		<b>Approved by:</b> Quality Manager
<b>Filename:</b> 1M1701030004-13.A3L	<b>Test Dates:</b> 12/31/2016 - 01/14/2017	<b>DUT Type:</b> Portable Handset	Page 69 of 72	

© 2017 PCTEST Engineering Laboratory, Inc.

REV 2.1.M  
11/29/2016

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [INFO@PCTESTLAB.COM](mailto:INFO@PCTESTLAB.COM).