




Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102




Plot 7-353. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)





Plot 7-355. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)




Plot 7-354. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)


FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 220 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 229 of 249
© 2019 PCTEST Engineering La	boratory, Inc.		V 8.8 11/19/2018



Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38



Plot 7-356. Radiated Band Edge Plot ANT (Average – WCP)



FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 220 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 230 of 249
© 2019 PCTEST Engineering La	aboratory, Inc.		V 8.8 11/19/2018




7.6.13 MIMO Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




Plot 7-358. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)






Plot 7-360. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-359. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)




Plot 7-361. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 221 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 231 of 249
© 2019 PCTEST Engineering La	boratory, Inc.		V 8.8 11/19/2018




Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106




Plot 7-362. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-364. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)




Plot 7-363. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)


FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 222 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 232 of 249
© 2019 PCTEST Engineering La	boratory, Inc.		V 8.8 11/19/2018




Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-365. Radiated Band Edge Plot ANT (Average – WCP)





FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 222 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 233 of 249
© 2019 PCTEST Engineering La	boratory, Inc.		V 8.8 11/19/2018



7.7 Radiated Spurious Emissions Measurements – Below 1GHz §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-65 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-82. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 120kHz (for emissions from 30MHz 1GHz)
- 3. Detector = quasi-peak
- 4. Sweep time = auto couple
- 5. Trace mode = max hold
- 6. Trace was allowed to stabilize

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Baga 224 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 234 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018



Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.






Figure 7-6. Radiated Test Setup < 30MHz





FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 225 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 235 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018





- 1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-65.
- 2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
- 3. This unit was tested with its standard battery.
- 4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
- 5. Emissions were measured at a 3 meter test distance.
- 6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
- 7. No spurious emissions were detected within 20dB of the limit below 30MHz.
- 8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
- The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: A3LSMG9730	PCTEST HEWELANY LABORATION	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dama 020 of 040
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 236 of 249
© 2019 PCTEST Engineering Laboratory. Inc.			V 8.8 11/19/2018



SISO Antenna Radiated Spurious Emissions Measurements (Below 1GHz) §15.209; RSS-Gen [8.9]








Plot 7-368. Radiated Spurious Plot below 1GHz SISO ANT2 (802.11a - U3 Ch. 157)


FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 227 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 237 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018




Simultaneous Tx Radiated Spurious Emissions Measurements (Below 1GHz) §15.209; RSS-Gen [8.9]














FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 228 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 238 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018



Line-Conducted Test Data

§15.407; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission	Conducted	Limit (dBµV)
(MHz)	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-83. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the spurious emission of interest
- 2. RBW = 9kHz (for emissions from 150kHz 30MHz)
- 3. Detector = quasi-peak
- 4. Sweep time = auto couple
- 5. Trace mode = max hold
- 6. Trace was allowed to stabilize

Average Field Strength Measurements


- 1. Analyzer center frequency was set to the frequency of the spurious emission of interest
- 2. RBW = 9kHz (for emissions from 150kHz 30MHz)
- 3. Detector = RMS
- 4. Sweep time = auto couple
- 5. Trace mode = max hold
- 6. Trace was allowed to stabilize

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 220 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 239 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018



Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Test Notes


- All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
- 2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
- 3. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- 4. QP/AV Level (dB μ V) = QP/AV Analyzer/Receiver Level (dB μ V) + Corr. (dB)
- 5. Margin (dB) = QP/AV Limit (dB μ V) QP/AV Level (dB μ V)
- 6. Traces shown in plot are made using a peak detector.
- 7. Deviations to the Specifications: None.

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 240 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 240 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-372. Line Conducted Plot with 802.11a UNII Band 1 (L1)




Plot 7-373. Line Conducted Plot with 802.11a UNII Band 1 (N)

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 241 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 241 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-374. Line Conducted Plot with 802.11a UNII Band 2A (L1)




Plot 7-375. Line Conducted Plot with 802.11a UNII Band 2A (N)

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 242 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 242 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-376. Line Conducted Plot with 802.11a UNII Band 2C (L1)




Plot 7-377. Line Conducted Plot with 802.11a UNII Band 2C (N)

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 242 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 243 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-378. Line Conducted Plot with 802.11a UNII Band 3 (L1)




Plot 7-379. Line Conducted Plot with 802.11a UNII Band 3 (N)

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 244 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 244 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-380. Line Conducted Plot with 802.11a UNII Band 1 (L1) with Wireless Charging Pad




Plot 7-381. Line Conducted Plot with 802.11a UNII Band 1 (N) with Wireless Charging Pad

FCC ID: A3LSMG9730	THE UP I AND A A DAY AND	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 245 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 245 of 249
© 2019 PCTEST Engineering Laboratory, Inc. V 8.8 11/19/201			






Plot 7-382. Line Conducted Plot with 802.11a UNII Band 2A (L1) with Wireless Charging Pad




Plot 7-383. Line Conducted Plot with 802.11a UNII Band 2A (N) with Wireless Charging Pad

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 246 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 246 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018






Plot 7-384. Line Conducted Plot with 802.11a UNII Band 2C (L1) with Wireless Charging Pad




Plot 7-385. Line Conducted Plot with 802.11a UNII Band 2C (N) with Wireless Charging Pad

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dage 247 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 247 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018





Plot 7-386. Line Conducted Plot with 802.11a UNII Band 3 (L1) with Wireless Charging Pad



Plot 7-387. Line Conducted Plot with 802.11a UNII Band 3 (N) with Wireless Charging Pad

FCC ID: A3LSMG9730		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Dega 249 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 248 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018



8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMG9730** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: A3LSMG9730	HEIMELAINE LALENA THAY . ML	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:	Daga 240 of 240
1M1811230206-06.A3L	12/14/2018 - 1/14/2019	Portable Handset	Page 249 of 249
© 2019 PCTEST Engineering Laboratory, Inc.			V 8.8 11/19/2018