| EMC TEST REPORT | | | | |
|--|----------------------------|---|--|--|
| Project No. | LBE20182053 | Issue No. 0 | | |
| | Name of organization | Samsung Electronics Co., Ltd. | | |
| Applicant | Address | (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea | | |
| | Date of application | November 20, 2018 | | |
| · | Type of device | All other Receivers subject to part15 Class B Personal Computers and peripherals Other Class B digital devices and peripherals FM Broadcast Receiver | | |
| | Equipment authorization | Certification D Supplier's Declaration of Conformity | | |
| | FCC ID | A3LSMG9730 | | |
| | Kind of product | Mobile Phone | | |
| EUI | Model No. | SM-G9730 | | |
| | Variant Model No. | Refer to clause 4.6 | | |
| | Manufacturer | SAMSUNG ELECTRONICS CO., LTD 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea | | |
| | | SAMSUNG ELECTRONICS HUIZHOU CO.,LTD. 516229, Chenjiang Town, HuiZhou City, Guangdong Province, China | | |
| Applied Standards | | 47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014 | | |
| Test Period | | December 17, 2018 ~ December 19, 2018 | | |
| Issue date | | December 19, 2018 | | |
| Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.) | | | | |
| Tested by : Eun-Kyung Oh Reviewed by : Young-Hun Kim Jana San San San San San San San San San | | | | |

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center.

Global CS Center of Samsung Electronics Co., Ltd. (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

Table of contents

| 1. | Report Information | |
|----|--------------------------------------|----|
| | 1.1 Revision history | 3 |
| 2 | Summary of test results | |
| ۷. | | - |
| | 2.1 Emission | 3 |
| 3. | General Information | |
| | 3.1 Test facility | 3 |
| 4. | Test Configuration | |
| | 4.1 Test Peripherals | 4 |
| | 4.2 EUT operating mode | 5 |
| | 4.3 Details of Sampling | 5 |
| | 4.4 Used cable description | 6 |
| | 4.5 Test arrangement | 7 |
| | 4.6 EUT Description | 10 |
| | 4.7 EUT Frequencies | 10 |
| | 4.8 Test configuration and condition | 11 |
| | 4.9 Measurement uncertainty | 11 |
| 5. | Result of individual tests | |
| | 5.1 Conducted disturbance | 12 |
| | 5.2 Radiated disturbance | 18 |

1. Report Information

1.1 Revision history

| No. | Revised detailed information |
|---------|---|
| Issue 0 | There are no revisions and this version is basic test report. |

1.2 RSE test report no.

| No. | Remark |
|-----------------|---|
| 1M1811230206-13 | The cellular receiver mode refers to the radiated spurious emissions test report. |

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

| Applied | Test type | Applied standard | Result |
|---------|---------------------------------------|--|----------|
| | Conducted Disturbance (Mains port) | 47 CFR Part 15 Subpart B / ANSI C63.4-2014 | Complied |
| | Radiated Disturbance | (Class B) | Complied |

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea. All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms. And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

| Mark | Description | Model No. | Serial No. | Manufacture r / Trademark | FCC ID | |
|----------|------------------|---------------|-------------------|---------------------------------|------------|---|
| Α | Mobile Phone | SM-G9730 | - | SAMSUNG | A3LSMG9730 | |
| В | Battery | EB-BG973ABU | - | SAMSUNG | - | |
| С | Headset | EO-IG955 | - | SAMSUNG | - | |
| | Data Cabla | EP-DG970BBE | - | SAMSUNG | - | |
| | Data Cable | JCA141 | BW2K1709000770 | J5CREATE | | |
| E | Micro SD Card | 64GB | - | SAMSUNG | - | |
| F | Travel Adapter | EP-TA200 | R37KAXA02D1DK3 | SAMSUNG | - | |
| <u> </u> | Desk-Top | DM-C410 | HFGD97AB700278X | SAMSUNG | - | |
| G | Computer | DM300S | A20100622 | SAMSUNG | - | |
| | LCD TV Monitor | S22E200N | 0AZSHLLG900906T | SAMSUNG | - | |
| | | EM23TS | NC26H1KSB01550B | SAMSUNG | - | |
| I | DP Monitor | 27DU88 | 711NTQD8H004 | LG | | |
| J | Power Supply | LCAP31 | EH8NN629490055062 | LG | | |
| | Mouse | SMI 210DB | TAKD125024 V | SAMSUNG | - | |
| к | | SIVIE-2 TOP B | TAKD124911 M | SAMSUNG | - | |
| | | B138 | Z5F8353 | SAMSUNG | - | |
| 1 | Keyboard | | 8M001183 | SAMSUNG | - | |
| | | SDM0300F | 8M001033 | SAMSUNG | - | |
| NA | Cigobit Switch 9 | 107044 | CN33FQ703Q | HP | - | |
| IVI | Gigabit Switch 8 | | J9794A | CN33FQ71XK | HP | - |
| N | Power Supply | | DIKD1245096741 | Delta | - | |
| | | | DIKD1245096576 | Delta | - | |
| 0 | OTG Gender | EE-UG970 | - | SAMSUNG | - | |

4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

| No. | Operating mode |
|-----|---|
| 1 | Camera (rear) + Charging (w/ TA) + Cellular receiver (GSM850 Center Frequency) + FM (Low Ch.) |
| 2 | Camera (front) + Charging (w/ TA) + FM (Mid Ch.) |
| 3 | Charging (w/ TA) + FM (High Ch.) |
| 4 | Video + Audio playback from internal memory data + Charging (w/ TA) |
| 5 | USB Data Communication with PC (from external memory data) |

4.2.2 Radiated Emission

| No. | Operating mode |
|-----|---|
| 1 | Camera (rear) + Charging (w/ TA) + FM (Low Ch.) |
| 2 | Camera (front) +USB OTG (w/USB gender: mouse) + FM (Mid Ch.) |
| 3 | FM (High Ch.) |
| 4 | Video + Audio playback from internal memory data + Display out(Direct DP Cable) |
| 5 | USB Data Communication with PC (from external memory data) |

4.3 Details of Sampling

Customer selected, single unit.

4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

| No. | Connected cable | Length [m] | Shielded [Y/N] | Note |
|-----|-----------------|---------------|-------------------|---|
| 1 | Data Cable | 1.0 | Yes | From EUT to Desk-Top Computer |
| 2 | DP Cable | 1.1 | Yes | From EUT to DP Monitor |
| 3 | Headset | 1.2 | No | For EUT |
| 4 | Power | 1.8 | No | For Desk-Top Computer |
| 5 | Power | 1.2 | No | From DP Monitor to Power Supply |
| 6 | Power | 1.6 | No | For Power Supply |
| 7 | Power | 1.8 | No | For LCD TV Monitor |
| 8 | Power | 1.8 | No | From Gigabit Switch 8 to Power Supply |
| 9 | Power | 1.8 | No | For Power Supply |
| 10 | LAN | 1.5 | No | From Desk-Top Computer to Gigabit Switch 8 |
| 11 | LAN | 1.5 | No | From Gigabit Switch 8 to Local Area Network |
| 12 | RGB | 1.8 | Yes | From Desk-Top Computer to LCD TV Monitor |
| 13 | PS/2 | 1.5 | Yes | From Desk-Top Computer to Mouse |
| 14 | PS/2 | 1.5 | Yes | From Desk-Top Computer to Keyboard |
| 15 | USB | 1.5 | Yes | For USB OTG Gender |

4.5 Test arrangement

4.5.1 Conducted Emission



[Mode 1 - 4]



4.5.2 Radiated Emission



[Mode 1]







-8/29-

Project No. : LBE20182053

Mobile Phone : SM-G9730



[Mode 4]



4.6 EUT Description

The EUT is a bar type Mobile Phone which can operate on GSM850/900/1800/1900, WCDMA FDD1/2/5/8, LTE FDD1/2/3/4/5/7/8/12/13/18/19/20/25/26/28, LTE TDD34/38/39/40/41, CDMA BC0, TD-SCDMA B34/39 and Incorporates a camera, Bluetooth, ANT+, Wi-Fi, FM Radio, GNSS, NFC, Wireless Charging, MST, OTG, DP and MP3/MP4 player.

4.6.1 The variant models - SM-G9738

4.7 EUT Frequencies

| The highest frequencies (Generated and used) | Frequency [MHz] | |
|---|-------------------|--|
| Wi-Fi | 5 825 | |

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports are exercised, as well as internal and the external SD card, by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) radiated testing was performed with the GSM850 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The FM radio mode radiated testing was performed with the Low/Mid/High channel.

The video and music were repetitively played connected to the earphone.

The video and music were played on monitor through Display Out function using direct DP Cable or DP converter.

The EUT was connected to USB mouse using USB OTG gender

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

| 4.9.1 Emissi | ion |
|--------------|-----|
|--------------|-----|

| Test type | Measurement uncertainty (C.L. 95 %, k = 2) | |
|-----------------------|---|---------|
| Conducted disturbance | AC Mains | 3.52 dB |
| Radiated Disturbance | Horizontal | 4.99 dB |
| (Below 1 GHz) | Vertical | 4.90 dB |
| Radiated Disturbance | Horizontal | 5.33 dB |
| (Above 1 GHz) | Vertical | 5.32 dB |

5. Results of individual test

5.1 Conducted disturbance

The EUT was connected to the Desk-Top Computer which was powered from one LISN for the measurements. The support equipment power cables were connected to a second LISN. Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

| Frequency range Limits | | esolution Bandwidth | Limits [dB(µV)] | | | |
|------------------------|---|---------------------|-------------------|----------|--|--|
| [MHz |] | [kHz] | Quasi-peak | Average | | |
| 0,15 to 0,50 | | 9 | 66 to 56 | 56 to 46 | | |
| 0,50 to 5 | | 9 | 56 | 46 | | |
| 5 to 30 | | 9 | 60 | 50 | | |
| NOTE 1 The low | TE 1 The lower limit shall apply at the transition frequency. | | | | | |
| NOTE 2 The limit | E 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. | | | | | |

Limits for conducted disturbance at the mains ports of Class B ITE

5.1.1 Test instrumentation

| | | | | | Calibration | |
|---------|---------------------------------|------------|--------------|-------------|-------------|---------------------|
| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Date | Interval (Month) |
| E5I-002 | Universal Radio Communicator | CMU200 | R&S | 100612 | 2018-08-31 | 12 |
| E5I-043 | LISN | ENV216 | R&S | 101630 | 2018-08-17 | 12 |
| E5I-017 | EMI Test Receiver | ESU8 | R&S | 100483 | 2018-01-12 | 12 |
| E5I-127 | LISN | ENV216 | R&S | 102061 | 2018-07-23 | 12 |
| - | Test software | EMC32 | R&S | Ver 9.26.01 | - | - |

5.1.2 Temperature and humidity condition

| Test date | 2018-12-19 Test engine | | Eun-Kyung Oh | | |
|-------------------|------------------------|----------------------|-----------------------------|--|--|
| | Ambient temperature | (23.8 ~ 24.0) °C | Limit (15.0 to 35.0) °C | | |
| Climate condition | Relative humidity | (43.1 ~ 43.3) % R.H. | Limit (25.0 to 75.0) % R.H. | | |
| | Atmospheric pressure | (101.4 ~ 101.6) kPa | Limit (86.0 to 106.0) kPa | | |
| Test place | Shield Room (SR8) | | | | |

5.1.3 Test results



□ Operating Mode 1: AC Mains



| Frequency (MHz) | QP (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|--------------------|--------------|---------------|-----------------|----------------|------|---------------|
| 0.182 | 41.5 | | 64.4 | 22.9 | Ν | 10.0 |
| 0.182 | | 27.5 | 54.4 | 26.9 | Ν | 10.0 |
| 0.547 | 41.2 | | 56.0 | 14.8 | L1 | 10.2 |
| 0.550 | | 36.1 | 46.0 | 9.9 | Ν | 10.2 |
| 0.673 | | 39.1 | 46.0 | 6.9 | Ν | 10.1 |
| 0.676 | 44.9 | | 56.0 | 11.1 | L1 | 10.2 |
| 1.285 | 40.5 | | 56.0 | 15.5 | L1 | 10.0 |
| 1.287 | | 33.8 | 46.0 | 12.2 | Ν | 9.9 |
| 3.583 | | 32.5 | 46.0 | 13.5 | Ν | 9.9 |
| 3.704 | 39.6 | | 56.0 | 16.4 | L1 | 10.0 |
| 14.020 | 47.9 | | 60.0 | 12.1 | L1 | 10.3 |
| 15.244 | | 41.3 | 50.0 | 8.7 | L1 | 10.4 |

| QP / CAV | final mea | surement | results | table: |
|----------|-----------|----------|---------|--------|

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

-13/29-



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

| Frequency (MHz) | QP (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|--------------------|--------------|---------------|-----------------|----------------|------|---------------|
| 0.182 | 40.8 | | 64.4 | 23.6 | N | 10.0 |
| 0.182 | | 27.5 | 54.4 | 26.9 | L1 | 10.0 |
| 0.550 | | 36.0 | 46.0 | 10.0 | N | 10.2 |
| 0.551 | 42.1 | | 56.0 | 13.9 | L1 | 10.2 |
| 0.673 | | 39.0 | 46.0 | 7.0 | N | 10.1 |
| 0.676 | 44.7 | | 56.0 | 11.3 | L1 | 10.2 |
| 0.727 | 41.9 | | 56.0 | 14.1 | L1 | 10.1 |
| 0.734 | | 34.8 | 46.0 | 11.2 | N | 10.0 |
| 1.285 | 40.1 | | 56.0 | 15.9 | L1 | 10.0 |
| 1.287 | | 33.3 | 46.0 | 12.7 | N | 9.9 |
| 15.239 | | 41.9 | 50.0 | 8.1 | L1 | 10.4 |
| 15.304 | 49.4 | | 60.0 | 10.6 | L1 | 10.4 |

| QP/0 | CAV f | inal meas | urement | results | table: |
|------|-------|-----------|---------|---------|--------|
|------|-------|-----------|---------|---------|--------|

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit - Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center. Form No.: SRA-TRF-46/7

-14/29-



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

| Frequency (MHz) | QP (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|--------------------|--------------|---------------|-----------------|----------------|------|---------------|
| 0.154 | 52.8 | | 65.8 | 13.0 | N | 9.9 |
| 0.154 | | 36.4 | 55.8 | 19.4 | N | 9.9 |
| 0.232 | | 35.8 | 52.4 | 16.6 | N | 9.8 |
| 0.232 | 48.9 | | 62.4 | 13.5 | N | 9.8 |
| 0.388 | | 34.7 | 48.1 | 13.4 | L1 | 10.2 |
| 0.388 | 43.5 | | 58.1 | 14.6 | N | 10.1 |
| 0.700 | | 39.1 | 46.0 | 6.9 | N | 10.0 |
| 0.704 | 45.1 | | 56.0 | 10.9 | L1 | 10.1 |
| 1.473 | | 29.9 | 46.0 | 16.1 | N | 9.9 |
| 1.484 | 37.3 | | 56.0 | 18.7 | L1 | 10.0 |
| 15.250 | 44.5 | | 60.0 | 15.5 | L1 | 10.4 |
| 15.779 | | 36.0 | 50.0 | 14.0 | L1 | 10.4 |

| OP / CAV final measurement results | s table: |
|------------------------------------|----------|
|------------------------------------|----------|

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

| Frequency (MHz) | QP (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|--------------------|--------------|---------------|-----------------|----------------|------|---------------|
| 0.182 | 48.6 | | 64.4 | 15.8 | N | 10.0 |
| 0.182 | | 31.9 | 54.4 | 22.5 | Ν | 10.0 |
| 0.308 | 42.9 | | 60.0 | 17.1 | N | 10.0 |
| 0.370 | | 31.1 | 48.5 | 17.4 | N | 10.1 |
| 0.673 | | 38.4 | 46.0 | 7.6 | N | 10.1 |
| 0.678 | 43.6 | | 56.0 | 12.4 | L1 | 10.2 |
| 1.286 | 39.9 | | 56.0 | 16.1 | L1 | 10.0 |
| 1.288 | | 32.8 | 46.0 | 13.2 | Ν | 9.9 |
| 3.639 | 39.7 | | 56.0 | 16.3 | L1 | 10.0 |
| 3.644 | | 32.8 | 46.0 | 13.2 | Ν | 9.9 |
| 14.038 | | 37.1 | 50.0 | 12.9 | L1 | 10.3 |
| 14.720 | 45.3 | | 60.0 | 14.7 | L1 | 10.3 |

| ΩP | / CAV final | measurement | results table. |
|-----|-------------|-------------|----------------|
| U I | | measurement | |

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor



□ Operating Mode 5: AC Mains

Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

| Frequency (MHz) | QP (dBµV) | CAV (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|--------------------|--------------|---------------|-----------------|----------------|------|---------------|
| 0.150 | 49.1 | | 66.0 | 16.9 | N | 9.9 |
| 0.164 | 47.1 | | 65.3 | 18.2 | L1 | 9.9 |
| 0.190 | | 30.4 | 54.0 | 23.6 | L1 | 10.0 |
| 0.208 | | 36.9 | 53.3 | 16.4 | L1 | 10.0 |
| 0.483 | 31.9 | | 56.3 | 24.4 | N | 10.2 |
| 0.487 | | 23.3 | 46.2 | 22.9 | N | 10.2 |
| 0.690 | 28.6 | | 56.0 | 27.4 | N | 10.0 |
| 0.692 | | 24.3 | 46.0 | 21.7 | N | 10.0 |
| 13.879 | | 30.1 | 50.0 | 19.9 | N | 10.4 |
| 13.887 | 34.7 | | 60.0 | 25.3 | L1 | 10.3 |
| 18.540 | 35.1 | | 60.0 | 24.9 | N | 10.6 |
| 18.547 | | 32.4 | 50.0 | 17.6 | N | 10.6 |
| 23.173 | 35.4 | | 60.0 | 24.6 | N | 10.7 |
| 23.186 | | 31.9 | 50.0 | 18.1 | N | 10.7 |

| QP / | CAV | final | measurement | results table. |
|-------|-----|-------|-------------|----------------|
| Q I / | | mai | measurement | |

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

-17/29-

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [kHz] | Video Bandwidth [kHz] | Turntable position [degrees] |
|--------------------------|----------------------|------------------------------------|-------------------------------|-----------------------------------|
| 100 ~ 400 | Horizontal, Vertical | 120 | 300 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operate or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [MHz] | Video Bandwidth [MHz] | Turntable position |
|--------------------------|----------------------|------------------------------------|-------------------------------|--------------------|
| 100 ~ 400 | Horizontal, Vertical | 1 | 3 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

| Frequency range Limits | Field Strength | | | | | |
|------------------------|----------------|------------------|-------------------|--|--|--|
| [MHz] | 3 m [µV/m] | 3 m [dB(µV/m)] | 10 m [dB(µV/m)] | | | |
| 30 to 88 | 100 | 40.0 | 29.5 | | | |
| 88 to 216 | 150 | 43.5 | 33.0 | | | |
| 216 to 960 | 200 | 46.0 | 35.5 | | | |
| Above 960 | 500 | 54.0 | 43.5 | | | |

Results checked manually; and points close to the limit line were re-measured.

-18/29-

5.2.1 Test instrumentation

| | | | | | Calibration | | |
|---------|---------------------------------|------------|--------------|-------------|-------------|---------------------|--|
| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Date | Interval (Month) | |
| E5I-002 | Universal Radio Communicator | CMU200 | R&S | 100612 | 2018-08-31 | 12 | |
| E5I-016 | EMI Test Receiver | ESU8 | R&S | 100482 | 2018-06-08 | 12 | |
| E5I-021 | EMI Test Receiver | ESU40 | R&S | 100376 | 2018-01-31 | 12 | |
| E5I-149 | Horn Antenna | HF907 | R&S | 102525 | 2018-06-15 | 24 | |
| E5I-039 | Signal Conditioning Unit | SCU-18 | R&S | 10211 | 2018-01-22 | 12 | |
| E5I-037 | Wide Band Horn Antenna | WBH 18-40K | R&S | 11201 | 2017-10-13 | 24 | |
| E5I-042 | Signal Conditioning Unit | SCU-40A | R&S | 10004 | 2018-09-05 | 12 | |
| E5I-120 | BiLog Antenna | CBL6112D | TESEQ | 36997 | 2018-04-23 | 24 | |
| E5I-072 | BiLog Antenna | CBL6112D | TESEQ | 36009 | 2018-04-23 | 24 | |
| E5I-073 | Preamplifier | 310N | SONOMA | 332016 | 2018-05-09 | 12 | |
| E5I-074 | Preamplifier | 310N | SONOMA | 332017 | 2018-05-09 | 12 | |
| - | Test software | EP7RE | ΤΟΥΟ | Ver 5.8.2 | - | - | |
| - | Test software | EMC32 | R&S | Ver 9.25.00 | - | - | |

5.2.2 Temperature and humidity condition

| Test date | 2018-12-17, 2018-12-18 | Test engineer | Eun-Kyung Oh | | |
|-------------------|------------------------|------------------------|---|--|--|
| Climate condition | Ambient temperature | (23.4 ~ 23.7) °C | Limit (15.0 to 35.0) $^{\circ}\!$ | | |
| | Relative humidity | (45.3 ~ 45.6) % R.H. | Limit (25.0 to 75.0) % R.H. | | |
| | Atmospheric pressure | (101.7 ~ 102.0) kPa | Limit (86.0 to 106.0) kPa | | |
| Test place | Ser | mi-Anechoic Chamber (S | SAC4) | | |

5.2.3 Test results

□ Operating Mode 1

- Frequencies below 1 GHz



* Radiated emissions (Rx frequency 87.958 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center. Form No.: SRA-TRF-46/7

-20/29-

Project No. : LBE20182053

Mobile Phone : SM-G9730



- Frequencies above 1 GHz

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical Test Distance : 3 m, Antenna Height : 1 to 4 meters Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 2

- Frequencies below 1 GHz



* Radiated emissions (Rx frequency 97.900 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP)

QP = Quasi-Peak, c.f = Correction Factor



- Frequencies above 1 GHz

| Frequency (MHz) | PK (dBμV/m) | CAV (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|--------------------|----------------|-----------------|-------------------|----------------|----------------|-----|------------------|---------------|
| 1 033.500 | 38.4 | | 74.0 | 35.6 | 100.0 | Н | 338.0 | 6.3 |
| 1 033.500 | | 25.6 | 54.0 | 28.4 | 100.0 | Н | 338.0 | 6.3 |
| 1 722.500 | | 27.1 | 54.0 | 26.9 | 100.0 | Н | 356.0 | 10.2 |
| 1 723.500 | 40.8 | | 74.0 | 33.2 | 100.0 | Н | 316.0 | 10.2 |
| 3 131.000 | 41.3 | | 74.0 | 32.7 | 100.0 | Н | 48.0 | 1.2 |
| 3 131.000 | | 30.9 | 54.0 | 23.1 | 100.0 | Н | 48.0 | 1.2 |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3

- Frequencies below 1 GHz



* Radiated emissions (Rx frequency 107.964 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP)

QP = Quasi-Peak, c.f = Correction Factor



- Frequencies above 1 GHz

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical Test Distance : 3 m, Antenna Height : 1 to 4 meters Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4

- Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor



- Frequencies above 1 GHz

| Frequency (MHz) | PK (dBµV/m) | CAV (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|--------------------|----------------|-----------------|-------------------|----------------|----------------|-----|------------------|---------------|
| 1 018.000 | 45.2 | | 74.0 | 28.8 | 100.0 | Н | 186.0 | 6.5 |
| 1 023.500 | | 31.2 | 54.0 | 22.8 | 100.0 | Н | 186.0 | 6.4 |
| 1 181.500 | 46.1 | | 74.0 | 27.9 | 100.0 | V | 309.0 | 6.2 |
| 1 185.000 | | 34.5 | 54.0 | 19.5 | 100.0 | V | 298.0 | 6.2 |
| 1 549.000 | 41.9 | | 74.0 | 32.1 | 100.0 | Н | 126.0 | 9.1 |
| 1 553.000 | | 30.0 | 54.0 | 24.0 | 100.0 | Н | 135.0 | 9.1 |
| 5 399.000 | 46.0 | | 74.0 | 28.0 | 100.0 | Н | 98.0 | 6.7 |
| 5 399.500 | | 41.7 | 54.0 | 12.3 | 100.0 | Н | 125.0 | 6.7 |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 5

- Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor

Project No. : LBE20182053

Mobile Phone : SM-G9730



- Frequencies above 1 GHz

| Frequency (MHz) | PK (dBµV/m) | CAV (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|--------------------|----------------|-----------------|-------------------|----------------|----------------|-----|------------------|---------------|
| 1 000.000 | | 27.8 | 54.0 | 26.2 | 100.0 | Н | 55.0 | 7.0 |
| 1 000.000 | 44.8 | | 74.0 | 29.2 | 100.0 | Н | 55.0 | 7.0 |
| 1 057.000 | | 25.8 | 54.0 | 28.2 | 100.0 | Н | 121.0 | 6.1 |
| 1 057.500 | 47.8 | | 74.0 | 26.2 | 100.0 | Н | 121.0 | 6.1 |
| 1 913.500 | | 46.6 | 54.0 | 7.4 | 100.0 | V | 356.0 | 11.6 |
| 1 913.500 | 51.3 | | 74.0 | 22.7 | 100.0 | V | 356.0 | 11.6 |
| 1 992.000 | | 31.8 | 54.0 | 22.2 | 100.0 | Н | 271.0 | 12.3 |
| 1 996.000 | 54.1 | | 74.0 | 19.9 | 100.0 | Н | 340.0 | 12.3 |
| 2 496.500 | 49.2 | | 74.0 | 24.8 | 100.0 | Н | 244.0 | 13.7 |
| 2 500.000 | | 36.7 | 54.0 | 17.3 | 100.0 | Н | 318.0 | 13.7 |
| 3 186.500 | | 26.1 | 54.0 | 27.9 | 100.0 | Н | 223.0 | 1.1 |
| 3 195.500 | 48.5 | | 74.0 | 25.5 | 100.0 | Н | 334.0 | 1.1 |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor