

FCC ID:	A3LSMG977KOR
Date:	3/7/2019
Test Procedure:	KDB 680106 D01 v03

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.341	n/a	0.335	n/a	0.339	n/a	614.00
B (Right)	0.438	n/a	0.452	n/a	0.437	n/a	614.00
C (Top)	0.339	n/a	0.350	n/a	0.345	n/a	614.00
D (Left)	0.456	n/a	0.455	n/a	0.459	n/a	614.00
E (Front)	1.305	1.255	1.312	0.597	1.242	0.589	614.00
F (Back)	1.531	1.253	1.547	0.629	1.243	0.659	614.00

**Table 1. E-field Measurement by distance/battery level**

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.022	n/a	0.021	n/a	0.022	n/a	1.63
B (Right)	0.024	n/a	0.022	n/a	0.024	n/a	1.63
C (Top)	0.022	n/a	0.023	n/a	0.023	n/a	1.63
D (Left)	0.021	n/a	0.021	n/a	0.025	n/a	1.63
E (Front)	0.023	0.025	0.024	0.023	0.026	0.026	1.63
F (Back)	0.024	0.023	0.025	0.021	0.028	0.025	1.63

**Table 2. H-field Measurement by distance/battery level**

A	B	C	D	E	F
BOTTOM EDGE	RIGHT EDGE	TOP EDGE	LEFT EDGE	FRONT (SCREEN)	Back

**Table 3. EUT Position Description**

**Note:**

The right and left edge are determined with the EUT screen facing the user.

**Description of Test Setup**

- Testing was performed with a calibrated field probe.
- Measurement was performed on each side of the EUT as described per Table 3.
- Testing was performed at the distances and different battery level as indicated on Table 1 and Table 2.
- Measurement procedure was performed per FCC Guidance.

**Test Equipment**

<b><u>Manufacturer</u></b>	<b><u>Model</u></b>	<b><u>Description</u></b>	<b><u>Cal. Date</u></b>	<b><u>Cal Due</u></b>	<b><u>Serial No.</u></b>
Narda	EHP-200A	EM Field Probe	3/7/2018	3/7/2019	170WX50922