

FCC ID:	A3LSMG986W
Date:	12/17/2019
Test Procedure:	KDB 680106 D01 v03

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.231	0.137	0.218	0.238	0.173	0.126	614.00
B (Right)	0.225	0.142	0.235	0.218	0.226	0.118	614.00
C (Top)	0.166	0.141	0.218	0.209	0.163	0.111	614.00
D (Left)	0.173	0.142	0.248	0.227	0.215	0.122	614.00
E (Front)	0.137	0.128	0.268	0.218	1.022	0.188	614.00
F (Back)	0.142	0.160	0.259	0.262	0.543	0.233	614.00

Table 1. E-field Measurement by distance/battery level (D2D)

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)		
	15	20	15	20	15	20	
A (Bottom)	0.084	0.085	0.085	0.085	0.088	0.088	1.63
B (Right)	0.085	0.082	0.084	0.082	0.081	0.085	1.63
C (Top)	0.081	0.078	0.078	0.073	0.088	0.078	1.63
D (Left)	0.082	0.088	0.085	0.085	0.085	0.081	1.63
E (Front)	0.081	0.081	0.073	0.076	0.078	0.085	1.63
F (Back)	0.081	0.078	0.078	0.730	0.077	0.084	1.63

Table 2. H-field Measurement by distance/battery level (D2D)

Note:

The right and left edge are determined with the EUT screen facing the user.

Description of Test Setup

- Testing was performed with a calibrated field probe.
- Measurement was performed on each side of the EUT as described per Table 4.
- Testing was performed at the distances and different battery level as indicated on Table 1 and Table 2.
- Measurement procedure was performed per FCC Guidance.

Test Equipment

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electric & Magnetic Field Probe	6/27/2019	Annual	6/27/2020	170WX60209