

FCC BT LE REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:
September 17, 2021

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-2109-FC019

FCC ID: A3LSMG990E

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model: SM-G990E/DS
Additional Model: SM-G990E
EUT Type: Mobile Phone
Average Output Power: 8.24 dBm (6.66 mW)
Frequency Range: 2 402 MHz ~ 2 480 MHz
Modulation type GFSK
FCC Classification: Digital Transmission System(DTS)
FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Report No.: HCT-RF-2109-FC019

REVIEWED BY



Report prepared by : Jin Gwan Lee
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2109-FC019	September 17, 2021	- First Approval Report

Table of Contents

REVIEWED BY	2
1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	7
3. INSTRUMENT CALIBRATION.....	7
4. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	7
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	8
7. DESCRIPTION OF TESTS.....	9
8. SUMMARY TEST OF RESULTS	24
9. TEST RESULT	25
9.1 DUTY CYCLE.....	25
9.2 6 dB BANDWIDTH	30
9.3 OUTPUT POWER	39
9.4 POWER SPECTRAL DENSITY	41
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	44
9.6 RADIATED SPURIOUS EMISSIONS	61
9.7 RADIATED RESTRICTED BAND EDGES	68
9.8 POWERLINE CONDUCTED EMISSIONS	70
10. LIST OF TEST EQUIPMENT	74
11. ANNEX A_ TEST SETUP PHOTO	76

1. EUT DESCRIPTION

Model	SM-G990E/DS	
Additional Model	SM-G990E	
EUT Type	Mobile Phone	
Power Supply	DC 4.20 V	
Frequency Range	2 402 MHz ~ 2 480 MHz	
Max. RF Output Power	Peak (For information only)	125 kBit/s : 8.399 dBm (6.92 mW) 500 kBit/s : 8.391 dBm (6.90 mW) 1 MBit/s : 8.439 dBm (6.98 mW) 2 MBit/s : 8.779 dBm (7.55 mW)
	Average	125 kBit/s : 7.80 dBm (6.03 mW) 500 kBit/s : 7.81 dBm (6.04 mW) 1 MBit/s : 7.87 dBm (6.12 mW) 2 MBit/s : 8.24 dBm (6.66 mW)
Modulation Type	GFSK	
Bluetooth Version	5.0	
Number of Channels	40 Channels	
Date(s) of Tests	August 18, 2021 ~ September 10, 2021	
Serial number	Radiated: R3CR803NW1R Conducted: R3CR803N9YT	

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5 m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil,

Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05 (Confidence level about 95 %, $k=2$)

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10\log(1/Duty\ Cycle)$

7.2. 6 dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to

(Procedure 8.2 in KDB 558074 v05r02, Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.

- Average Power (Procedure 8.3.2.3 in KDB 558074 v05r02, Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Measured Level+ ATT loss + Cable loss
- Conducted Output Power(Average) = Measured Level+ ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3 kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / RBW]$.
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11) if then duty factor shall be added to adjust the result if the duty cycle is less than 98 %

Sample Calculation

- Power Spectral Density = Measured Level+ ATT loss + Cable loss


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 8.5 in KDB 558074 v05r02, Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points $\geq 2 \times$ Span/VBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	10.40
100	10.45
200	10.49
300	10.54
400	10.60
500	10.60
600	10.61
700	10.62
800	10.63
900	10.65
1000	10.70
2000	10.85
2400	10.88
2412	10.90
2437	10.90
2462	10.90
2500	10.89
3000	10.99
4000	11.07
5000	11.14
5700	11.69
5800	11.69
6000	11.77
7000	11.90
8000	11.90
9000	11.98
10 000	12.08
11 000	12.17
12 000	12.26
13 000	12.27
14 000	12.30
15 000	12.40
16 000	12.48
17 000	12.69
18 000	12.82
19 000	12.74
20 000	12.41
21 000	12.54

Note : 1. 2 400 ~ 2 500 MHz is fundamental frequency range.

2. Factor = Attenuator loss(10 dB) + Cable loss(1ea)


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3 m from the EUT
3. The EUT is placed on a turntable, which is 0.8 m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3\text{ m}/300\text{ m}) = - 80\text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3\text{ m}/30\text{ m}) = - 40\text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW $\geq 3 \times$ RBW
9. Total = Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
 2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
 3. The Hybrid antenna was placed at a location 3 m from the EUT, which is varied from 1m to 4 m to find out the highest emissions.
 4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
 6. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 100 kHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Quasi-peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Quasi-Peak
 - RBW = 120 kHz
- In general, (1) is used mainly
7. Total = Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L)
 8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Average):
 - Duty cycle < 98 %, duty cycle variations are less than ± 2 %
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1
9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
10. Distance extrapolation factor = $20\log$ (test distance / specific distance) (dB)
11. Total (Measurement Type : Peak)
 - = Peak Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G)
 - + Distance Factor(D.F)

Total (Measurement Type : Average)

= Average Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G)
+ Distance Factor(D.F) + Duty Cycle Factor

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Average):
 - Duty cycle < 98 %, duty cycle variations are less than ± 2 %
 - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
 - Detector = RMS
 - Averaging type = power (i.e., RMS)
 - RBW = 1 MHz
 - VBW \geq 3 x RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
 - Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.
9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

11. Total(Measurement Type : Peak)

= Peak Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average)

= Average Measured Level+ Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

+ Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Measured Level+ Correction Factor

7.8. Worst case configuration and mode

Radiated Test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis:
 - Radiated Spurious Emissions : Z
 - Radiated Restricted Band Edge : X, Z
3. All packet length of operation were investigated and the test results are worst case in lowest packet length.
 - Worst case : 1 M(37 Byte), 2 M(255 Byte),
4. All datarate of operation were investigated and the worst case configuration results are reported.
 - Worst case : 1 M, 2 M
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane
6. SM-G990E/DS, SM-G990E were tested and the worst case results are reported.
(Worst case : SM-G990E/DS)

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc)+Travel Adapter, Stand alone + Travel Adapter
 - Worstcase : Stand alone + Travel Adapter
2. SM-G990E/DS, SM-G990E were tested and the worst case results are reported.
(Worst case : SM-G990E/DS)

Conducted test

1. The EUT was configured with packet length of highest power.
 - Worst case : 37 Byte
2. SM-G990E/DS, SM-G990E were tested and the worst case results are reported.
(Worst case : SM-G990E/DS)

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6		PASS


9. TEST RESULT

9.1 DUTY CYCLE

Data rate (Bit/s)	Packet length (Byte)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
125k	37	3.100	3.750	0.8267	0.83
	255	17.067	17.500	0.9752	0.11
500k	37	1.056	1.874	0.5636	2.49
	255	4.540	5.000	0.9080	0.42
1M	37	0.377	0.624	0.6045	2.19
	255	2.120	2.500	0.8480	0.72
2M	37	0.194	0.624	0.3103	5.08
	255	1.068	1.876	0.5693	2.45


125 kBit/s(37 Byte) Test Plots

Duty Cycle (Low-CH 0)




125 kBit/s(255 Byte) Test Plots

Duty Cycle (Low-CH 0)




500 kBit/s(37 Byte) Test Plots

Duty Cycle (Low-CH 0)




500 kBit/s(255 Byte) Test Plots

Duty Cycle (Low-CH 0)




1 MBit/s (37 Byte) Test Plots

Duty Cycle (Low-CH 0)




1 MBit/s (255 Byte) Test Plots

Duty Cycle (Low-CH 0)




2 MBit/s (37 Byte) Test Plots

Duty Cycle (Low-CH 0)



2 MBit/s (255 Byte) Test Plots

Duty Cycle (Low-CH 0)



9.2 6 dB BANDWIDTH


Mode (Bit/s)	Channel	6 dB Bandwidth (kHz)	Limit (kHz)
125k(37)	0	697.9	> 500
	19	699.6	
	39	698.7	
125k(255)	0	702.9	> 500
	19	699.3	
	39	693.9	
500k(37)	0	670.5	> 500
	19	668.9	
	39	667.0	
500k(255)	0	667.8	> 500
	19	668.7	
	39	664.8	
1M(37)	0	702.7	> 500
	19	714.9	
	39	719.8	
1M(255)	0	668.3	> 500
	19	669.1	
	39	667.1	
2M(37)	0	1256	> 500
	19	1262	
	39	1263	
2M(255)	0	1237	> 500
	19	1246	
	39	1251	

Note:


Worst case test Plot Only 255 Byte

125 kBit/s(255 Byte) Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)




6 dB Bandwidth plot (High-CH 39)




▣ 500 kBit/s(255 Byte) Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)




6 dB Bandwidth plot (High-CH 39)




1 MBit/s (255 Byte) Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)




6 dB Bandwidth plot (High-CH 39)




▣ 2 MBit/s (255 Byte) Test Plots


6 dB Bandwidth plot (Low-CH 0)



6 dB Bandwidth plot (Mid-CH 19)



6 dB Bandwidth plot (High-CH 39)



9.3 OUTPUT POWER

Peak Power

Data rate (Bit/s)	Packet length (Byte)	LE Mode		Measured Power(dBm)	Limit (dBm)
		Frequency [MHz]	Channel		
125k	37	2402	0	6.675	30
		2440	19	7.889	
		2480	39	8.399	
	255	2402	0	6.603	
		2440	19	7.783	
		2480	39	8.298	
500k	37	2402	0	6.667	
		2440	19	7.915	
		2480	39	8.391	
	255	2402	0	6.746	
		2440	19	7.918	
		2480	39	8.327	
1M	37	2402	0	6.542	
		2440	19	8.052	
		2480	39	8.439	
	255	2402	0	6.451	
		2440	19	8.013	
		2480	39	8.404	
2M	37	2402	0	6.915	
		2440	19	8.401	
		2480	39	8.702	
	255	2402	0	6.942	
		2440	19	8.424	
		2480	39	8.779	

Note :

1. Power meter offset = Attenuator loss + Cable loss + EUT Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 10.9 dB is offset for 2.4 GHz Band.

Average Power

Data rate (Bit/s)	Packet length (Byte)	LE Mode		Measured Power (dBm)	Duty Cycle Factor (dB)	Result (dBm)	Limit (dBm)
		Frequency [MHz]	Channel				
125k	37	2402	0	5.32	0.83	6.15	30
		2440	19	6.66	0.83	7.49	
		2480	39	6.97	0.83	7.80	
	255	2402	0	5.99	0.11	6.10	
		2440	19	7.30	0.11	7.41	
		2480	39	7.65	0.11	7.76	
500k	37	2402	0	3.72	2.49	6.21	
		2440	19	4.87	2.49	7.36	
		2480	39	5.22	2.49	7.71	
	255	2402	0	5.74	0.42	6.16	
		2440	19	7.06	0.42	7.48	
		2480	39	7.39	0.42	7.81	
1M	37	2402	0	3.84	2.19	6.03	
		2440	19	5.53	2.19	7.72	
		2480	39	5.68	2.19	7.87	
	255	2402	0	5.34	0.72	6.06	
		2440	19	6.90	0.72	7.62	
		2480	39	7.13	0.72	7.85	
2M	37	2402	0	1.31	5.08	6.39	
		2440	19	2.78	5.08	7.86	
		2480	39	3.15	5.08	8.23	
	255	2402	0	3.91	2.45	6.36	
		2440	19	5.40	2.45	7.85	
		2480	39	5.79	2.45	8.24	

Note :

1. Power meter offset = Attenuator loss + Cable loss + EUT cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 10.9 dB is offset for 2.4 GHz Band.

9.4 POWER SPECTRAL DENSITY

Frequency (MHz)	Channel No.	Mode	Test Result			Limit (dBm)
			Measured Power(dBm)	Duty Cycle Factor(dB)	Measured Power(dBm) + Duty Cycle Factor(dB)	
2402	0	125 kBit/s 37 Byte	-0.516	0.83	0.311	8 dBm / 3 kHz
2440	19		0.968	0.83	1.795	
2480	39		1.414	0.83	2.241	
2402	0	125 kBit/s 255 Byte	0.155	0.11	0.264	
2440	19		1.316	0.11	1.425	
2480	39		2.028	0.11	2.137	
2402	0	500 kBit/s 37 Byte	-3.519	2.49	-1.029	
2440	19		-1.661	2.49	0.829	
2480	39		-1.134	0.42	-0.715	
2402	0	500 kBit/s 255 Byte	-1.153	0.42	-0.734	
2440	19		0.396	0.42	0.815	
2480	39		0.392	0.42	0.811	
2402	0	1 MBit/s 37 Byte	-2.849	2.19	-0.663	
2440	19		-1.033	2.19	1.153	
2480	39		-0.236	2.19	1.950	
2402	0	1 MBit/s 255 Byte	-1.832	0.72	-1.116	
2440	19		0.122	0.72	0.838	
2480	39		0.476	0.72	1.192	
2402	0	2 MBit/s 37 Byte	-6.956	5.08	-1.874	
2440	19		-5.563	5.08	-0.481	
2480	39		-3.328	5.08	1.754	
2402	0	2 MBit/s 255 Byte	-5.581	2.45	-3.134	
2440	19		-3.682	2.45	-1.235	
2480	39		-3.724	2.45	-1.277	

Note :

1. Spectrum measured level are not plot data.

The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss + EUT cable loss

3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

So, 10.9 dB is offset for 2.4 GHz Band.


4. Worst case test Plot Only : 125 kBit/s (37 Byte)

125 kBit/s (37 Byte) Test Plots


Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)



Power Spectral Density (High-CH 39)




9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

1 MBit/s (37 Byte) Test Plots –Band Edge

Low-CH 0




High-CH 39



1 MBit/s (37 Byte) Test Plots -Conducted Spurious Emission


30 MHz ~ 1 GHz

Conducted Spurious Emission (High-CH 39)




1 GHz ~ 3 GHz

Conducted Spurious Emission (High-CH 39)




7 GHz ~ 9 GHz

Conducted Spurious Emission (High-CH 39)




9 GHz ~ 11 GHz

Conducted Spurious Emission (High-CH 39)




11 GHz ~ 13 GHz

Conducted Spurious Emission (High-CH 39)




13 GHz ~ 15 GHz

Conducted Spurious Emission (High-CH 39)




15 GHz ~ 17 GHz

Conducted Spurious Emission (High-CH 39)




17 GHz ~ 19 GHz

Conducted Spurious Emission (High-CH 39)




19 GHz ~ 21 GHz

Conducted Spurious Emission (High-CH 39)




21 GHz ~ 23 GHz

Conducted Spurious Emission (High-CH 39)



23 GHz ~ 25 GHz

Conducted Spurious Emission (High-CH 39)




2 MBit/s (37 Byte) Test Plots -BandEdge

Low-CH 0




High-CH 39



2 MBit/s (255 Byte) Test Plots -Conducted Spurious Emission


30 MHz ~ 1 GHz

Conducted Spurious Emission (High-CH 39)




1 GHz ~ 3 GHz

Conducted Spurious Emission (High-CH 39)




3 GHz ~ 5 GHz

Conducted Spurious Emission (High-CH 39)




5 GHz ~ 7 GHz

Conducted Spurious Emission (High-CH 39)




7 GHz ~ 9 GHz

Conducted Spurious Emission (High-CH 39)




9 GHz ~ 11 GHz

Conducted Spurious Emission (High-CH 39)




11 GHz ~ 13 GHz

Conducted Spurious Emission (High-CH 39)




13 GHz ~ 15 GHz

Conducted Spurious Emission (High-CH 39)




15 GHz ~ 17 GHz

Conducted Spurious Emission (High-CH 39)




17 GHz ~ 19 GHz

Conducted Spurious Emission (High-CH 39)




19 GHz ~ 21 GHz

Conducted Spurious Emission (High-CH 39)




21 GHz ~ 23 GHz

Conducted Spurious Emission (High-CH 39)



23 GHz ~ 25 GHz

Conducted Spurious Emission (High-CH 39)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30 MHz

Frequency	Measured Value	A.F+C.L+D.F	POL	Total	Limit	Margin
[MHz]	[dBµV/m]	[dB/m]	[H/V]	[dBµV/m]	[dBµV/m]	[dB]
No Critical peaks found						

Note:

1. The Measured of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBµV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.

Frequency Range : Below 1 GHz

Frequency	Measured Value	A.F+C.L	POL	Total	Limit	Margin
[MHz]	[dBµV/m]	[dB/m]	[H/V]	[dBµV/m]	[dBµV/m]	[dB]
No Critical peaks found						

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
2. Radiated test is performed with hopping off.

Frequency Range : Above 1 GHz
Mode : 1 MBit/s (37 Byte)

Operation Mode: CH Low

Frequency [MHz]	Measured Level [dB μ V]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4804	45.63	0.00	2.76	V	48.39	73.98	25.59	PK
4804	34.00	2.19	2.76	V	38.94	53.98	15.04	AV
7206	40.89	0.00	8.96	V	49.85	73.98	24.13	PK
7206	28.80	2.19	8.96	V	39.94	53.98	14.04	AV
4804	45.61	0.00	2.76	H	48.37	73.98	25.61	PK
4804	34.10	2.19	2.76	H	39.04	53.98	14.94	AV
7206	39.55	0.00	8.96	H	48.51	73.98	25.47	PK
7206	28.49	2.19	8.96	H	39.63	53.98	14.35	AV

Operation Mode: CH Mid

Frequency [MHz]	Measured Level [dB μ V]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4880	44.74	0.00	3.15	V	47.89	73.98	26.09	PK
4880	33.53	2.19	3.15	V	38.86	53.98	15.12	AV
7320	40.98	0.00	9.45	V	50.43	73.98	23.55	PK
7320	29.16	2.19	9.45	V	40.80	53.98	13.18	AV
4880	45.23	0.00	3.15	H	48.38	73.98	25.60	PK
4880	33.94	2.19	3.15	H	39.27	53.98	14.71	AV
7320	41.35	0.00	9.45	H	50.80	73.98	23.18	PK
7320	29.31	2.19	9.45	H	40.95	53.98	13.03	AV

Operation Mode: CH High

Frequency [MHz]	Measured Level [dBμV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
4960	43.64	0.00	2.23	V	45.87	73.98	28.11	PK
4960	33.38	2.19	2.23	V	37.79	53.98	16.19	AV
7440	40.80	0.00	10.35	V	51.15	73.98	22.83	PK
7440	28.34	2.19	10.35	V	40.88	53.98	13.10	AV
4960	44.59	0.00	2.23	H	46.82	73.98	27.16	PK
4960	33.69	2.19	2.23	H	38.10	53.98	15.88	AV
7440	41.02	0.00	10.35	H	51.37	73.98	22.61	PK
7440	28.68	2.19	10.35	H	41.22	53.98	12.76	AV

Mode : 2 MBit/s (255 Byte)

Operation Mode: CH Low

Frequency [MHz]	Measured Level [dB μ V]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4804	44.95	0.00	2.76	V	47.71	73.98	26.27	PK
4804	33.18	2.45	2.76	V	38.38	53.98	15.60	AV
7206	40.62	0.00	8.96	V	49.58	73.98	24.40	PK
7206	28.86	2.45	8.96	V	40.26	53.98	13.72	AV
4804	45.86	0.00	2.76	H	48.62	73.98	25.36	PK
4804	33.39	2.45	2.76	H	38.59	53.98	15.39	AV
7206	40.46	0.00	8.96	H	49.42	73.98	24.56	PK
7206	28.44	2.45	8.96	H	39.84	53.98	14.14	AV

Operation Mode: CH Mid


Frequency [MHz]	Measured Level [dB μ V]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4880	45.15	0.00	3.15	V	48.30	73.98	25.68	PK
4880	32.64	2.45	3.15	V	38.23	53.98	15.75	AV
7320	40.93	0.00	9.45	V	50.38	73.98	23.60	PK
7320	29.15	2.45	9.45	V	41.05	53.98	12.93	AV
4880	44.53	0.00	3.15	H	47.68	73.98	26.30	PK
4880	32.78	2.45	3.15	H	38.37	53.98	15.61	AV
7320	41.27	0.00	9.45	H	50.72	73.98	23.26	PK
7320	29.34	2.45	9.45	H	41.24	53.98	12.74	AV

Operation Mode: CH High

Frequency [MHz]	Measured Level [dBμV]	Duty Cycle Factor [dB]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
4960	43.88	0.00	2.23	V	46.11	73.98	27.87	PK
4960	32.27	2.45	2.23	V	36.94	53.98	17.04	AV
7440	40.09	0.00	10.35	V	50.44	73.98	23.54	PK
7440	28.47	2.45	10.35	V	41.27	53.98	12.71	AV
4960	44.79	0.00	2.23	H	47.02	73.98	26.96	PK
4960	32.52	2.45	2.23	H	37.19	53.98	16.79	AV
7440	40.82	0.00	10.35	H	51.17	73.98	22.81	PK
7440	28.56	2.45	10.35	H	41.36	53.98	12.62	AV


☐ 1 MBit/s 37 Byte Test Plots (Worst case : Z-H)

Radiated Spurious Emissions plot – Average Result (Ch.39 3rd Harmonic)



Date: 20.AUG.2021 10:07:31


Radiated Spurious Emissions plot – Peak Result (Ch.39 3rd Harmonic)



Date: 20.AUG.2021 10:07:55


☑ 2 MBit/s 255 Byte Test Plots (Worst case : Z-H)

Radiated Spurious Emissions plot – Average Result (Ch.39 3rd Harmonic)



Date: 20.AUG.2021 10:09:22

Radiated Spurious Emissions plot – Peak Result (Ch.39 3rd Harmonic)



Date: 20.AUG.2021 10:09:37

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Mode : 1 MBit/s (37 Byte)

Operating Frequency 2402 MHz, 2480 MHz

Channel No. 0 CH, 39 CH

Frequency [MHz]	Measured Level [dBμV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F [dB]	Ant. Pol. [H/V]	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
2390.0	20.10	0.00	33.78	H	53.88	73.98	20.10	PK
2390.0	8.43	2.19	33.78	H	44.39	53.98	9.59	AV
2390.0	20.16	0.00	33.78	V	53.93	73.98	20.05	PK
2390.0	8.46	2.19	33.78	V	44.43	53.98	9.55	AV
2483.5	20.09	0.00	34.10	H	54.19	73.98	19.79	PK
2483.5	8.34	2.19	34.10	H	44.63	53.98	9.35	AV
2483.5	20.22	0.00	34.10	V	54.31	73.98	19.67	PK
2483.5	8.34	2.19	34.10	V	44.63	53.98	9.35	AV

Mode : 2 MBit/s (255 Byte)


Operating Frequency 2402 MHz, 2480 MHz

Channel No. 0 CH, 39 CH


Frequency [MHz]	Measured Level [dBμV/m]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F [dB]	Ant. Pol. [H/V]	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
2390.0	20.20	0.00	33.78	H	53.97	73.98	20.01	PK
2390.0	8.49	2.45	33.78	H	44.71	53.98	9.27	AV
2390.0	20.31	0.00	33.78	V	54.09	73.98	19.89	PK
2390.0	8.58	2.45	33.78	V	44.81	53.98	9.17	AV
2483.5	20.12	0.00	34.10	H	54.21	73.98	19.77	PK
2483.5	8.59	2.45	34.10	H	45.14	53.98	8.84	AV
2483.5	20.36	0.00	34.10	V	54.46	73.98	19.52	PK
2483.5	8.69	2.45	34.10	V	45.23	53.98	8.75	AV

Mode : 2 MBit/s (255 Byte) Test Plots

Radiated Restricted Band Edges plot – Average Result (Ch.39, Z-H)



Radiated Restricted Band Edges plot – Peak Result (Ch.39, Z-H)



Note:

Plot of worst case are only reported.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

Test


1 / 2

Test Report

Common Information

EUT : SM-G990E/DS
 Manufacturer : SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions : BTLE L1
 Operator Name:
 Comment:

Full Spectrum



Final Result QPK

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1500	44.59	66.00	21.41	9.000	L1	OFF	9.6
0.1680	41.14	65.06	23.91	9.000	L1	OFF	9.6
0.1928	41.69	63.92	22.23	9.000	L1	OFF	9.6
0.1995	42.57	63.63	21.06	9.000	L1	OFF	9.6
0.2040	42.37	63.45	21.08	9.000	L1	OFF	9.6
0.2243	40.41	62.66	22.25	9.000	L1	OFF	9.6
4.9505	34.10	56.00	21.90	9.000	L1	OFF	9.9
5.0540	34.41	60.00	25.59	9.000	L1	OFF	9.9
5.0698	34.70	60.00	25.30	9.000	L1	OFF	9.9
5.0968	34.93	60.00	25.07	9.000	L1	OFF	9.9
5.1170	35.21	60.00	24.79	9.000	L1	OFF	9.9
5.1283	35.35	60.00	24.65	9.000	L1	OFF	9.9
12.4633	37.20	60.00	22.80	9.000	L1	OFF	10.1
19.8635	36.51	60.00	23.49	9.000	L1	OFF	10.4
19.9355	36.91	60.00	23.09	9.000	L1	OFF	10.4
20.2303	37.15	60.00	22.85	9.000	L1	OFF	10.4
20.3473	37.29	60.00	22.71	9.000	L1	OFF	10.4
20.5250	36.99	60.00	23.01	9.000	L1	OFF	10.4

Final_Result_CAV

2021-09-01

오후 7:42:02

Test

2 / 2

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1545	26.70	55.75	29.05	9.000	L1	OFF	9.6
0.2018	26.90	53.54	26.64	9.000	L1	OFF	9.6
0.2333	25.63	52.33	26.70	9.000	L1	OFF	9.6
0.2625	19.40	51.35	31.96	9.000	L1	OFF	9.6
0.3008	21.51	50.22	28.71	9.000	L1	OFF	9.6
0.4380	28.52	47.10	18.58	9.000	L1	OFF	9.6
5.0495	26.61	50.00	23.39	9.000	L1	OFF	9.9
5.0810	26.62	50.00	23.38	9.000	L1	OFF	9.9
5.1170	27.09	50.00	22.91	9.000	L1	OFF	9.9
5.1463	27.23	50.00	22.77	9.000	L1	OFF	9.9
5.1620	27.17	50.00	22.83	9.000	L1	OFF	9.9
5.1688	27.26	50.00	22.74	9.000	L1	OFF	9.9
12.2788	28.78	50.00	21.22	9.000	L1	OFF	10.1
12.4633	29.07	50.00	20.93	9.000	L1	OFF	10.1
20.0435	28.99	50.00	21.01	9.000	L1	OFF	10.4
20.0818	28.84	50.00	21.16	9.000	L1	OFF	10.4
20.3045	29.01	50.00	20.99	9.000	L1	OFF	10.4
20.4148	29.07	50.00	20.93	9.000	L1	OFF	10.4

2021-09-01

오후 7:42:02

Conducted Emissions (Line 2)

Test


1 / 2

Test Report

Common Information

EUT : SM-G990E/DS
 Manufacturer : SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions : BTLE N
 Operator Name:
 Comment:

Full Spectrum



Final Result QPK

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1523	42.74	65.88	23.14	9.000	N	OFF	9.6
0.1680	39.31	65.06	25.75	9.000	N	OFF	9.6
0.1793	38.37	64.52	26.15	9.000	N	OFF	9.6
0.1950	40.80	63.82	23.02	9.000	N	OFF	9.6
0.2063	40.79	63.36	22.56	9.000	N	OFF	9.6
0.2288	40.18	62.50	22.32	9.000	N	OFF	9.6
0.4965	33.65	56.06	22.41	9.000	N	OFF	9.6
5.0608	30.63	60.00	29.37	9.000	N	OFF	9.9
5.0765	30.43	60.00	29.57	9.000	N	OFF	9.9
5.1350	30.76	60.00	29.24	9.000	N	OFF	9.9
5.1395	30.78	60.00	29.22	9.000	N	OFF	9.9
5.1485	30.66	60.00	29.34	9.000	N	OFF	9.9
13.1878	32.25	60.00	27.75	9.000	N	OFF	10.2
13.2395	32.22	60.00	27.78	9.000	N	OFF	10.2
13.4330	32.04	60.00	27.96	9.000	N	OFF	10.2
19.3730	30.84	60.00	29.16	9.000	N	OFF	10.4
19.8118	31.19	60.00	28.81	9.000	N	OFF	10.5
20.1875	31.89	60.00	28.11	9.000	N	OFF	10.5

Final_Result_CAV

2021-09-01

오후 7:35:56

Test

2 / 2

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1545	24.72	55.75	31.04	9.000	N	OFF	9.6
0.2018	24.52	53.54	29.02	9.000	N	OFF	9.6
0.2333	23.48	52.33	28.85	9.000	N	OFF	9.6
0.3030	19.27	50.16	30.89	9.000	N	OFF	9.6
0.4403	26.81	47.06	20.24	9.000	N	OFF	9.6
0.5000	24.20	46.00	21.80	9.000	N	OFF	9.6
5.0450	24.18	50.00	25.82	9.000	N	OFF	9.9
5.0540	24.17	50.00	25.83	9.000	N	OFF	9.9
5.0698	24.22	50.00	25.78	9.000	N	OFF	9.9
5.1238	24.55	50.00	25.45	9.000	N	OFF	9.9
5.1395	24.54	50.00	25.46	9.000	N	OFF	9.9
5.1508	24.54	50.00	25.46	9.000	N	OFF	9.9
12.6770	26.67	50.00	23.33	9.000	N	OFF	10.2
12.9808	26.69	50.00	23.31	9.000	N	OFF	10.2
19.3708	24.32	50.00	25.68	9.000	N	OFF	10.4
19.8703	25.30	50.00	24.70	9.000	N	OFF	10.5
20.1133	25.81	50.00	24.19	9.000	N	OFF	10.5
20.2100	25.86	50.00	24.14	9.000	N	OFF	10.5

2021-09-01

오후 7:35:56

10. LIST OF TEST EQUIPMENT

Conducted Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
LISN	ENV216	Rohde & Schwarz	102245	08/23/2022	Annual
Test Receiver	ESCI	Rohde & Schwarz	100033	06/15/2022	Annual
Temperature Chamber	SU-642	ESPAC	0093008124	03/15/2022	Annual
Signal Analyzer	N9020A	Agilent	MY47380318	01/28/2022	Annual
Signal Analyzer	N9030A	Agilent	MY49431210	01/11/2022	Annual
Signal Analyzer	N9030A	KEYSIGHT	MY55410508	09/07/2022	Annual
Power Meter	N1911A	Agilent	MY45100523	04/08/2022	Annual
Power Sensor	N1921A	Agilent	MY57820067	04/08/2022	Annual
Directional Coupler	87300B	Agilent	3116A03621	11/10/2021	Annual
Power Splitter	11667B	Hewlett Packard	05001	05/20/2022	Annual
DC Power Supply	E3632A	Hewlett Packard	KR75303960	06/10/2022	Annual
Attenuator (10 dB)	5910-N-50-010	H+S	00801	10/28/2021	Annual
Software	EMC32	Rohde & Schwarz	N/A	N/A	N/A
FCC WLAN&BT&BLE Conducted Test Software v3.0	FCC WLAN&BT&BLE Conducted Test Software v3.0	HCT CO., LTD.	N/A	N/A	N/A

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Controller (Antenna mast)	CO3000	Innco system	CO3000-4p	N/A	N/A
Antenna Position Tower	MA4640/800-XP-EP	Innco system	N/A	N/A	N/A
Controller	2090	Emco	060520	N/A	N/A
Turn Table	Turn Table	Ets	N/A	N/A	N/A
Loop Antenna	Loop Antenna	Rohde & Schwarz	1513-333	03/19/2022	Biennial
Hybrid Antenna	VULB 9168	Schwarzbeck	9168-0895	09/04/2022	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1191	11/18/2021	Biennial
Horn Antenna (15 GHz ~ 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170541	11/29/2021	Biennial
Spectrum Analyzer	FSP (9 kHz ~ 30 GHz)	Rohde & Schwarz	836650/016	09/14/2021	Annual
Spectrum Analyzer	FSV40-N	Rohde & Schwarz	101068-SZ	09/22/2021	Annual
Band Reject Filter	WRCJV2400/2483.5-2370/2520-60/12SS	Wainwright Instruments	2	01/06/2022	Annual
Band Reject Filter	WRCJV5100/5850-40/50-8EEK	Wainwright Instruments	1	02/08/2022	Annual
Attenuator (10 dB)	CBLU1183540B-01	CERNEX	N/A	12/23/2021	Annual
56-10	56-10	WEINSCHEL			
Broadband Low Noise Amplifier	CBL06185030	CERNEX	N/A	12/23/2021	Annual
Attenuator (3 dB)	18B-03	Api tech.			
High Pass Filter	WHKX10-2700-3000-18000-40SS	Wainwright Instruments	N/A	12/23/2021	Annual
High Pass Filter	WHKX8-6090-7000-18000-40SS	Wainwright Instruments	N/A	12/23/2021	Annual
Thru	COAXIAL ATTENUATOR	T&M SYSTEM	N/A	12/23/2021	Annual
Power Amplifier	CBL18265035	CERNEX	22966	12/04/2021	Annual
Power Amplifier	CBL26405040	CERNEX	25956	03/23/2022	Annual

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2109-FC019-P