

# FCC LTE REPORT

## Certification

<b>Applicant Name:</b> SAMSUNG Electronics Co., Ltd.	<b>Date of Issue:</b> June 15, 2021
<b>Address:</b> 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea	<b>Location:</b> HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
	<b>Report No.:</b> HCT-RF-2105-FC022-R1

**FCC ID:** A3LSMG990U

**APPLICANT:** SAMSUNG Electronics Co., Ltd.

Model(s): SM-G990U  
 Additional Model(s): SM-G990U1/DS, SM-G990U1  
 EUT Type: Mobile Phone  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 FCC Rule Part(s): §90, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band14 (5)	790.5 –795.5	4M51G7D	QPSK	0.113	20.52
		4M51W7D	16QAM	0.099	19.98
		4M50W7D	64QAM	0.079	18.96
		4M49W7D	256QAM	0.038	15.83
LTE – Band14 (10)	793.0	8M94G7D	QPSK	0.118	20.73
		8M98W7D	16QAM	0.109	20.39
		8M96W7D	64QAM	0.081	19.10
		8M96W7D	256QAM	0.037	15.69

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.  
 HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report No.: HCT-RF-2105-FC022-R1

---

REVIEWED BY



---

Report prepared by : Jae Mun Do  
Engineer of Telecommunication Testing Center

---

Report approved by : Jong Seok Lee  
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked \*.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

\* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2105-FC022	May 26, 2021	- First Approval Report
HCT-RF-2105-FC022-R1	June 15, 2021	- Revised the Additional model(s). (SM-G990U1 added)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

**Table of Contents**

**REVIEWED BY ..... 2**

**1. GENERAL INFORMATION ..... 5**

**2. INTRODUCTION ..... 6**

**2.1. DESCRIPTION OF EUT ..... 6**

**2.2. MEASURING INSTRUMENT CALIBRATION ..... 6**

**2.3. TEST FACILITY ..... 6**

**3. DESCRIPTION OF TESTS..... 7**

**3.1 TEST PROCEDURE ..... 7**

**3.2 RADIATED POWER..... 8**

**3.3 RADIATED SPURIOUS EMISSIONS ..... 9**

**3.4 OCCUPIED BANDWIDTH. .... 10**

**3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL .....11**

**3.6 BAND EDGE ..... 12**

**3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE ..... 14**

**3.8 WORST CASE(RADIATED TEST) ..... 15**

**3.9 WORST CASE(CONDUCTED TEST) ..... 16**

**4. LIST OF TEST EQUIPMENT ..... 17**

**5. MEASUREMENT UNCERTAINTY ..... 18**

**6. SUMMARY OF TEST RESULTS ..... 19**

**7. SAMPLE CALCULATION ..... 20**

**8. TEST DATA ..... 22**

**8.1 EFFECTIVE RADIATED POWER..... 22**

**8.2 RADIATED SPURIOUS EMISSIONS ..... 23**

**8.3 OCCUPIED BANDWIDTH ..... 26**

**8.4 CONDUCTED SPURIOUS EMISSIONS ..... 27**

**8.5 BAND EDGE ..... 27**

**8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE ..... 28**

**9. TEST PLOTS..... 32**

**10. APPENDIX A\_ TEST SETUP PHOTO ..... 61**

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMG990U
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	§90, §2
<b>EUT Type:</b>	Mobile Phone
<b>Model(s):</b>	SM-G990U
<b>Additional Model(s):</b>	SM-G990U1/DS, SM-G990U1
<b>Tx Frequency:</b>	790.5 MHz – 795.5 MHz (LTE – BAND 14 (5MHz)) 793.0 MHz (LTE – BAND 14 (10 MHz))
<b>Date(s) of Tests:</b>	April 19, 2021 ~ May 18, 2021
<b>Serial number:</b>	Radiated: R3CR315S6MD Conducted: R3CR3117FBH

## **2. INTRODUCTION**

### **2.1. DESCRIPTION OF EUT**

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS, CDMA(BC0, 1, 10) and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac/ax (HT20/40/80), Bluetooth, BT LE, NFC, WPT, mmWave(n260/261).

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq 3 \times$  RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $> 2 \times$  span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser  
if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit)  
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.  
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where:  $P_g$  is the generator output power into the substitution antenna.

If the fundamental frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

### 3.4 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



**Test setup**

#### **Test Overview**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### **Test Settings**

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 x Span / RBW

### 3.6 BAND EDGE



**Test setup**

#### **Test Overview**

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### **Test Settings**

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

**Test Notes**

§90.543(e)

1. On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations.
2. On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.
3. On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.
4. Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.
5. Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.  
However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.


**Test Notes**

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

### 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



#### Test setup

#### Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

.- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

.- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature

(20°C to provide a reference).

2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter.

Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at

least one half-hour is provided to allow stabilization of the equipment at each temperature level.

**3.8 WORST CASE(RADIATED TEST)**

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- SM-G990U & additional models were tested and the worst case results are reported.  
(Worst case : SM-G990U)

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	1	0	Y
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Y

**3.9 WORST CASE(CONDUCTED TEST)**

- All modes of operation were investigated and the worst case configuration results are reported.
- SM-G990U & additional models were tested and the worst case results are reported.

(Worst case : SM-G990U)

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
<b>Occupied Bandwidth</b>	QPSK, 16QAM, 64QAM, 256QAM	5, 10	Mid	Full RB	0
<b>Band Edge</b>	QPSK	5	Low	1	0
			High	1	24
		10	Mid	1	0
				1	49
		5	Low, High	Full RB	0
		10	Mid	Full RB	0
<b>Spurious and Harmonic Emissions at Antenna Terminal</b>	QPSK	5	Low, Mid, High	1	0
		10	Mid	1	0



#### 4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	03/02/2021	Annual	03/02/2022
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	03/02/2021	Annual	03/02/2022
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	04/07/2021	Annual	04/07/2022
Hewlett Packard	E3632A/DC Power Supply	MY40004427	09/16/2020	Annual	09/16/2021
Schwarzbeck	UHAP/ Dipole Antenna	557	04/05/2021	Biennial	04/05/2023
Schwarzbeck	UHAP/ Dipole Antenna	558	04/05/2021	Biennial	04/05/2023
ESPEC	SU-642 / Chamber	93008124	03/15/2021	Annual	03/15/2022
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	10/13/2020	Biennial	10/13/2022
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	02/11/2020	Biennial	02/11/2022
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY50200093	11/17/2020	Annual	11/17/2021
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2020	Annual	06/04/2021
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2020	Annual	10/14/2021
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/26/2020	Annual	08/26/2021
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-333	03/19/2020	Biennial	03/19/2022
Schwarzbeck	VULB9160/ Bilog Antenna	3150	03/03/2021	Biennial	03/03/2023
Schwarzbeck	VULB9168/ Hybrid Antenna	760	02/22/2021	Biennial	02/22/2023
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6262116770	07/22/2020	Annual	07/22/2021
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/07/2021	Annual	01/07/2022
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/13/2020	Annual	07/13/2021
KEYSIGHT	N9030B / Signal Analyzer(5Hz~40.0GHz)	MY55480167	06/04/2020	Annual	06/04/2021
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §90.543(e)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
On all frequencies between 769-775 MHz and 799-805 MHz.	§90.543(e)	< 65 + 10log10 (P[Watts])	PASS <b>(See Note2)</b>
Conducted Output Power	§2.1046	N/A	<b>See Note1</b>
Frequency stability / variation of ambient temperature	§2.1055, §90.539(e)	< 2.5 ppm	PASS

**Note:**

1. See SAR Report
2. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance.

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§90.542(a)(7)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §90.543(e)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS
Undesirable Emissions in the 1559 – 1610 MHz band	§2.1053, §90.543(f)	< -70dBW/MHz EIRP (wideband) < -80dBW EIRP (narrowband)	PASS

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

**ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

**EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

### 7.3. Emission Designator

#### GSM Emission Designator

**Emission Designator = 249KGXW**

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

#### EDGE Emission Designator

**Emission Designator = 249KG7W**

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

#### WCDMA Emission Designator

**Emission Designator = 4M17F9W**

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

#### QPSK Modulation

**Emission Designator = 4M48G7D**

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

#### QAM Modulation

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 8. TEST DATA

### 8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W
790.5	LTE B14 (5 MHz)	QPSK	-30.62	32.29	-10.41	1.36	V	< 3.00	0.113	20.52
		16-QAM	-31.16	31.75	-10.41	1.36	V		0.099	19.98
		64-QAM	-32.18	30.73	-10.41	1.36	V		0.079	18.96
		256-QAM	-35.31	27.60	-10.41	1.36	V		0.038	15.83
793.0		QPSK	-30.73	32.29	-10.42	1.36	V		0.112	20.51
		16-QAM	-31.40	31.62	-10.42	1.36	V		0.096	19.84
		64-QAM	-32.42	30.60	-10.42	1.36	V		0.076	18.82
		256-QAM	-35.46	27.56	-10.42	1.36	V		0.038	15.78
795.5		QPSK	-30.91	32.09	-10.44	1.37	V		0.107	20.28
		16-QAM	-31.53	31.47	-10.44	1.37	V		0.092	19.66
		64-QAM	-32.65	30.35	-10.44	1.37	V		0.071	18.54
		256-QAM	-35.66	27.34	-10.44	1.37	V		0.036	15.53

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
									W	W
793.0	LTE B14 (10 MHz)	QPSK	-30.51	32.51	-10.42	1.36	V	< 3.00	0.118	20.73
		16-QAM	-30.85	32.17	-10.42	1.36	V		0.109	20.39
		64-QAM	-32.14	30.88	-10.42	1.36	V		0.081	19.10
		256-QAM	-35.55	27.47	-10.42	1.36	V		0.037	15.69

**8.2 RADIATED SPURIOUS EMISSIONS**

- ▣ MODE: LTE B14
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
23305 (790.5)	1 581.0	-54.53	9.05	-62.51	1.95	V	-55.41	-13.00
	2 371.5	-55.43	10.05	-57.93	2.42	V	-50.30	-13.00
	3 162.0	-57.13	11.28	-57.12	2.83	V	-48.67	-13.00
23330 (793.0)	1 586.0	-53.54	9.12	-61.59	1.96	H	-54.43	-13.00
	2 379.0	-54.66	10.05	-57.24	2.44	H	-49.63	-13.00
	3 172.0	-57.66	11.35	-57.88	2.83	H	-49.36	-13.00
23355 (795.5)	1 591.0	-53.46	9.18	-61.57	1.96	H	-54.35	-13.00
	2 386.5	-54.12	10.09	-56.71	2.45	H	-49.07	-13.00
	3 182.0	-57.08	11.35	-57.35	2.83	V	-48.83	-13.00

▣ MODE: LTE B14  
▣ MODULATION SIGNAL: 10 MHz QPSK  
▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
23330 (793.0)	1 586.0	-54.21	9.12	-62.26	1.96	V	-55.10	-13.00
	2 379.0	-56.18	10.05	-58.76	2.44	V	-51.15	-13.00
	3 172.0	-57.51	11.35	-57.73	2.83	V	-49.21	-13.00



**1559 MHz ~ 1610 MHz BAND**

- ▣ OPERATING FREQUENCY: 790.5 MHz, 793.0 MHz, 795.5 MHz
- ▣ MEASURED OUTPUT POWER: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ WIDEBAND EMISSION LIMIT: -80 dBW/ MHz (= -50 dBm/ MHz)

Operating Frequency (MHz)	Measured Frequency (MHz)	EMISSION TYPE	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Margin (dB)
790.5	1606.63	Narrow Band	-63.46	9.34	-72.29	1.99	V	-64.94	14.94
793.0	1608.36		-63.48	9.35	-72.42	1.99	V	-65.06	15.06
795.5	1607.01		-63.51	9.35	-72.45	1.99	V	-65.09	15.09

Note:

The lower narrowband limit was applied because the spurious emission was not found.

- ▣ OPERATING FREQUENCY: 793.0 MHz
- ▣ MEASURED OUTPUT POWER: 10 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ WIDEBAND EMISSION LIMIT: -80 dBW/ MHz (= -50 dBm/ MHz)

Operating Frequency (MHz)	Measured Frequency (MHz)	EMISSION TYPE	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Margin (dB)
793.0	1607.84	Narrow Band	-63.55	9.35	-72.49	1.99	V	-65.13	15.13

Note:

The lower narrowband limit was applied because the spurious emission was not found.

**8.3 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )
14	5 MHz	793.0	QPSK	25	0	4.5059
			16-QAM	25	0	4.5092
			64-QAM	25	0	4.4960
			256-QAM	25	0	4.4889
	10 MHz		QPSK	50	0	8.9354
			16-QAM	50	0	8.9746
			64-QAM	50	0	8.9546
			256-QAM	50	0	8.9627

**Note:**

1. Plots of the EUT's Occupied Bandwidth are shown Page 49 ~ 56.

**8.4 CONDUCTED SPURIOUS EMISSIONS**

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
14	5	790.5	3.7010	27.976	-67.342	-39.366	-13.00
		793.0	3.6915	27.976	-67.234	-39.258	
		795.5	3.6765	27.976	-67.240	-39.264	
	10	793.0	3.6765	27.976	-67.274	-39.298	

**Note:**

1. Plots of the EUT’s Conducted Spurious Emissions are shown Page 57 ~ 60.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


**8.5 BAND EDGE**

- Plots of the EUT’s Band Edge are shown Page 33 ~ 48.

**8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**


- ▣ MODE: LTE 14
- ▣ OPERATING FREQUENCY: 790,500,000 Hz
- ▣ CHANNEL: 23305 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	790 500 016	0.00	0.000 000	0.0000
100%		-30	790 500 031	15.50	0.000 002	0.0196
100%		-20	790 500 012	-3.60	0.000 000	-0.0046
100%		-10	790 500 002	-14.40	-0.000 002	-0.0182
100%		0	790 500 019	3.00	0.000 000	0.0038
100%		+10	790 500 012	-3.60	0.000 000	-0.0046
100%		+30	790 500 032	16.30	0.000 002	0.0206
100%		+40	790 500 012	-3.70	0.000 000	-0.0047
100%		+50	790 500 032	15.80	0.000 002	0.0200
Batt. Endpoint		3.650	+20	790 500 033	17.20	0.000 002




- ▣ MODE: LTE 14
- ▣ OPERATING FREQUENCY: 793,000,000 Hz
- ▣ CHANNEL: 23330 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	792 999 997	0.00	0.000 000	0.0000
100%		-30	793 000 001	4.30	0.000 001	0.0054
100%		-20	793 000 000	2.90	0.000 000	0.0037
100%		-10	793 000 013	15.60	0.000 002	0.0197
100%		0	792 999 995	-1.90	0.000 000	-0.0024
100%		+10	792 999 995	-2.00	0.000 000	-0.0025
100%		+30	792 999 994	-3.40	0.000 000	-0.0043
100%		+40	793 000 009	12.10	0.000 002	0.0153
100%		+50	792 999 994	-3.60	0.000 000	-0.0045
Batt. Endpoint	3.650	+20	793 000 012	15.10	0.000 002	0.0190




- ▣ MODE: LTE 14
- ▣ OPERATING FREQUENCY: 795,500,000 Hz
- ▣ CHANNEL: 23355 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	795 500 012	0.00	0.000 000	0.0000
100%		-30	795 500 007	-5.30	-0.000 001	-0.0067
100%		-20	795 500 026	14.20	0.000 002	0.0179
100%		-10	795 500 008	-3.90	0.000 000	-0.0049
100%		0	795 500 026	14.40	0.000 002	0.0181
100%		+10	795 500 030	17.50	0.000 002	0.0220
100%		+30	795 500 008	-4.40	-0.000 001	-0.0055
100%		+40	795 500 016	3.90	0.000 000	0.0049
100%		+50	795 500 007	-5.20	-0.000 001	-0.0065
Batt. Endpoint		3.650	+20	795 500 006	-5.70	-0.000 001



- ▣ MODE: LTE 14
- ▣ OPERATING FREQUENCY: 793,000,000 Hz
- ▣ CHANNEL: 23330 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	792 999 985	0.00	0.000 000	0.0000
100%		-30	792 999 973	-11.80	-0.000 001	-0.0149
100%		-20	792 999 973	-12.00	-0.000 002	-0.0151
100%		-10	792 999 974	-11.70	-0.000 001	-0.0148
100%		0	792 999 977	-7.90	-0.000 001	-0.0100
100%		+10	792 999 976	-9.20	-0.000 001	-0.0116
100%		+30	792 999 972	-13.10	-0.000 002	-0.0165
100%		+40	792 999 977	-8.60	-0.000 001	-0.0108
100%		+50	792 999 973	-12.40	-0.000 002	-0.0156
Batt. Endpoint		3.650	+20	792 999 974	-11.40	-0.000 001




## 9. TEST PLOTS



5M\_BandEdge\_Lowest Channel\_QPSK\_FullRB(1)



5M\_BandEdge\_Lowest Channel\_QPSK\_FullRB(2)




5M\_BandEdge\_Highest Channel\_QPSK\_FullIRB(1)




5M\_BandEdge\_Highest Channel\_QPSK\_FullIRB(2)




5M\_BandEdge\_Lowest Channel\_QPSK\_1RB(1)



5M\_BandEdge\_Lowest Channel\_QPSK\_1RB(2)



5M\_BandEdge\_Highest Channel\_QPSK\_1RB(1)



5M\_BandEdge\_Highest Channel\_QPSK\_1RB(2)






10M\_BandEdge\_Mid Channel(Lower)\_QPSK\_FullRB(1)



10M\_BandEdge\_Mid Channel(Lower)\_QPSK\_FullRB(2)




10M\_BandEdge\_Mid Channel(Higher)\_QPSK\_FullRB(1)




10M\_BandEdge\_Mid Channel(Higher)\_QPSK\_FullRB(2)



10M\_BandEdge\_Mid Channel(Lower)\_QPSK\_1RB(1)



10M\_BandEdge\_Mid Channel(Lower)\_QPSK\_1RB(2)



10M\_BandEdge\_Mid Channel(Higher)\_QPSK\_1RB(1)




10M\_BandEdge\_Mid Channel(Higher)\_QPSK\_1RB(2)







5M\_OBW\_Mid Channel\_QPSK\_FullRB




5M\_OBW\_Mid Channel\_16QAM\_FullRB




5M\_OBW\_Mid Channel\_64QAM\_FullRB




5M\_OBW\_Mid Channel\_256QAM\_FullIRB




10M\_OBW\_Mid Channel\_QPSK\_FullIRB




10M\_OBW\_Mid Channel\_16QAM\_FullIRB



10M\_OBW\_Mid Channel\_64QAM\_FullRB




10M\_OBW\_Mid Channel\_256QAM\_FullIRB







5M\_CSE(30M-10G)\_Lowest Channel\_QPSK\_1RB




5M\_CSE(30M-10G)\_Mid Channel\_QPSK\_1RB



5M\_CSE(30M-10G)\_Highest Channel\_QPSK\_1RB



10M\_CSE(30M-10G)\_Mid Channel\_QPSK\_1RB



## 10. APPENDIX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2105-FC022-P