



**PCTEST**  
7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. +1.410.290.6652 / Fax +1.410.290.6654  
<http://www.pctest.com>



## PART 0 SAR CHAR REPORT

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro, Maetan dong,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**

09/16/20 – 12/01/20

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Document Serial No.:**

1M2009140143-27-R2.A3L

**FCC ID:****A3LSMG996U****APPLICANT:****SAMSUNG ELECTRONICS CO., LTD****Report Type:**

Part 0 SAR Characterization

**DUT Type:**

Portable Handset

**Model(s):**

SM-G996U

**Additional Model(s):**

SM-G996U1

Note: This revised Test Report (S/N: 1M2009140143-27-R2.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Test results reported herein relate only to the item(s) tested.


Randy Ortanez  
President



FCC ID: A3LSMG996U	 <b>PCTEST</b> Proud to be part of	PART 0 SAR CHAR REPORT			Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset			Page 1 of 11

## TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
1.1	Device Overview	3
1.2	Time-Averaging for SAR and Power Density	3
1.3	Nomenclature for Part 0 Report	4
1.4	Bibliography	4
2	SAR AND POWER DENSITY MEASUREMENTS	5
2.1	SAR Definition	5
2.2	SAR Measurement Procedure	5
3	SAR CHARACTERIZATION	7
3.1	DSI and SAR Determination	7
3.2	SAR Design Target	7
3.3	SAR Char	8
4	EQUIPMENT LIST	10
5	MEASUREMENT UNCERTAINTIES	11
	APPENDIX A: SAR TEST RESULTS FOR $P_{Limit}$ CALCULATIONS	1

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of 		PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset	Page 2 of 11		

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
CDMA/EVDO BC10 (\$90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (\$22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 14	Voice/Data	790.5 - 795.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
LTE Band 48	Voice/Data	3552.5 - 3697.5 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
LTE Band 38	Voice/Data	2572.5 - 2617.5 MHz
NR Band n71	Data	665.5 - 695.5 MHz
NR Band n12	Data	701.5 - 713.5 MHz
NR Band n5 (Cell)	Data	826.5 - 846.5 MHz
NR Band n66 (AWS)	Data	1712.5 - 1777.5 MHz
NR Band n25 (PCS)	Data	1852.5 - 1912.5 MHz
NR Band n2 (PCS)	Data	1852.5 - 1907.5 MHz
NR Band n30	Data	2307.5 - 2312.5 MHz
NR Band n41	Data	2506.02 - 2679.99 MHz
NR Band n77	Data	3700 - 3980 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
2.4 GHz Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
NR Band n260	Data	37000 - 40000 MHz
NR Band n261	Data	27500 - 28350 MHz

This device uses the Qualcomm® Smart Transmit feature to control and manage transmitting power in real time and to ensure the time-averaged RF exposure is in compliance with the FCC requirement at all times for 2G/3G/4G/5G WWAN operations. Additionally, this device supports WLAN/BT/NFC technologies, but the output power of these modems is not controlled by the Smart Transmit algorithm.

## 1.2 Time-Averaging for SAR and Power Density

This device is enabled with Qualcomm® Smart Transmit algorithm to control and manage transmitting power in real time and to ensure that the time-averaged RF exposure from 2G/3G/4G/5G Sub-6 NR WWAN is in compliance with FCC requirements. This Part 0 report shows SAR characterization of WWAN radios for 2G/3G/4G/5G Sub-6 NR. Characterization is achieved by determining  $P_{\text{Limit}}$  for 2G/3G/4G/5G Sub-6 NR that corresponds to the exposure design targets after accounting for all device design related uncertainties, i.e., SAR\_design\_target (< FCC SAR limit) for sub-6 radio. The SAR characterization is denoted as SAR Char in this report. Section 1.3 includes a nomenclature of the specific terms used in this report.

The compliance test under the static transmission scenario and simultaneous transmission analysis are reported in Part 1 report. The validation of the time-averaging algorithm and compliance under the dynamic (time- varying) transmission scenario for WWAN technologies are reported in Part 2 report (report SN could be found in Section 1.4 – Bibliography).

FCC ID: A3LSMG996U	 <b>PCTEST</b> Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset		Page 3 of 11

## 1.3 Nomenclature for Part 0 Report

Technology	Term	Description
2G/3G/4G/5G Sub-6 NR	$P_{limit}$	Power level that corresponds to the exposure design target ( $SAR\_design\_target$ ) after accounting for all device design related uncertainties
	$P_{max}$	Maximum tune up output power
	$SAR\_design\_target$	Target SAR level < FCC SAR limit after accounting for all device design related uncertainties
	SAR Char	Table containing $P_{limit}$ for all technologies and bands

## 1.4 Bibliography

Report Type	Report Serial Number
FCC Part 0 PD Characterization Report	Revision A
FCC SAR Evaluation Report (Part 1)	1M2009140143-01-R2.A3L
FCC PD Evaluation Report (Part 1)	1M2009140143-22-R2.A3L
RF Exposure Part 2 Test Report	1M2009140143-23-R1.A3L
RF Exposure Compliance Summary	1M2009140143-24-R1.A3L

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of 		PART 0 SAR CHAR REPORT	 Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset	Page 4 of 11	

## 2 SAR AND POWER DENSITY MEASUREMENTS

### 2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy ( $dU$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dV$ ) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

**Equation 2-1  
SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dV} \right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:


$\sigma$  = conductivity of the tissue-simulating material (S/m)  
 $\rho$  = mass density of the tissue-simulating material (kg/m<sup>3</sup>)  
 $E$  = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

### 2.2 SAR Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 2-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.



**Figure 2-1  
Sample SAR Area Scan**

FCC ID: A3LSMG996U	 <b>PCTEST</b> Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset		Page 5 of 11

4. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See
5. Table 2-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in
  - b. Table 2-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - c. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - d. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
6. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

**Table 2-1**  
**Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\***

Frequency	Maximum Area Scan Resolution (mm) ( $\Delta x_{area}, \Delta y_{area}$ )	Maximum Zoom Scan Resolution (mm) ( $\Delta x_{zoom}, \Delta y_{zoom}$ )	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid		Graded Grid	
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{zoom}(n-1)$	≥ 22

\*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of 			PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset			Page 6 of 11	

## 3 SAR CHARACTERIZATION

### 3.1 DSI and SAR Determination

This device uses different Device State Index (DSI) to configure different time averaged power levels based on certain exposure scenarios. Depending on the detection scheme implemented in the smartphone, the worst-case SAR was determined by measurements for the relevant exposure conditions for that DSI. Detailed descriptions of the detection mechanisms are included in the operational description.

When 1g SAR and 10g SAR exposure comparison is needed, the worst-case was determined from SAR normalized to 1g or 10g SAR limit.

The device state index (DSI) conditions used in Table 3-1 represent different exposure scenarios.

**Table 3-1**  
**DSI and Corresponding Exposure Scenarios**

Scenario	Description	SAR Test Cases
Head (DSI = 2)	<ul style="list-style-type: none"><li>Device positioned next to head</li><li>Receiver Active</li></ul>	<i>Head SAR per KDB Publication 648474 D04</i>
Hotspot mode (DSI = 3)	<ul style="list-style-type: none"><li>Device transmits in hotspot mode near body</li><li>Hotspot Mode Active</li></ul>	<i>Hotspot SAR per KDB Publication 941225 D06</i>
Phablet Grip (DSI=1 or 4)	<ul style="list-style-type: none"><li>Device is held with hand and grip sensor is triggered</li><li>Grip sensor triggered or earjack is active</li></ul>	<i>Phablet SAR per KDB Publication 648474 D04 &amp; KDB Publication 616217 D04</i>
Phablet (DSI = 0)	<ul style="list-style-type: none"><li>Device is held with hand and grip sensor is not triggered</li><li>Distance grip sensor not triggered</li></ul>	<i>Phablet SAR per KDB Publication 648474 D04 &amp; KDB Publication 616217 D04</i>
Body-worn (DSI = 0)	<ul style="list-style-type: none"><li>Device being used with a body-worn accessory</li></ul>	<i>Body-worn SAR per KDB Publication 648474 D04</i>

### 3.2 SAR Design Target

*SAR\_design\_target* is determined by ensuring that it is less than FCC SAR limit after accounting for total device designed related uncertainties specified by the manufacturer (see Table 3-2).

**Table 3-2**  
***SAR\_design\_target* Calculations**

<b><i>SAR_design_target</i></b>			
$SAR_{design\_target} < SAR_{regulatory\_limit} \times 10^{-Total\ Uncertainty}$			
<b>1g SAR (W/kg)</b>		<b>10g SAR (W/kg)</b>	
<i>Total Uncertainty</i>	1.0 dB	<i>Total Uncertainty</i>	1.0 dB
<i>SAR<sub>regulatory_limit</sub></i>	1.6 W/kg	<i>SAR<sub>regulatory_limit</sub></i>	4.0 W/kg
<i>SAR<sub>design_target</sub></i>	1.0 W/kg	<i>SAR<sub>design_target</sub></i>	2.5 W/kg

FCC ID: A3LSMG996U	 <b>PCTEST</b> Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset		Page 7 of 11

### 3.3 SAR Char

SAR test results corresponding to  $P_{max}$  for each antenna/technology/band/DSI can be found in Appendix A.

$P_{limit}$  is calculated by linearly scaling with the measured SAR at the  $P_{part0}$  to correspond to the  $SAR\_design\_target$ . When  $P_{limit} < P_{max}$ ,  $P_{part0}$  was used as  $P_{limit}$  in the Smart Transmit EFS. When  $P_{limit} > P_{max}$  and  $P_{part0}=P_{max}$ , calculated  $P_{limit}$  was used in the Smart Transmit EFS. All reported SAR obtained from the  $P_{part0}$  SAR tests was less than  $SAR\_Design\_target + 1$  dB Uncertainty. The final  $P_{limit}$  determination for each exposure scenario corresponding to  $SAR\_design\_target$  are shown in Table 3-3.

**Table 3-3**  
 **$P_{limit}$  Determination**

Device State Index (DSI)	$P_{limit}$ Determination Scenarios
0	The worst-case SAR exposure is determined as maximum SAR normalized to the limit among: 1. Body Worn SAR 2. Extremity SAR measured at 5, 4 and 10 mm spacing for back, front, bottom respectively 3. Extremity SAR measured at 0 mm for left and right surfaces
1 or 4	$P_{limit}$ is calculated based on 10g Extremity SAR at 0 mm for back, front, and bottom surfaces
2	$P_{limit}$ is calculated based on 1g Head SAR
3	$P_{limit}$ is calculated based on 1g Hotspot SAR at 10 mm


**Note:**

For DSI = 0,  $P_{limit}$  is calculated by:

$$P_{limit} = \min \{ P_{limit} \text{ corresponding to 1g Body Worn SAR evaluation at 15 mm spacing,}$$

$$P_{limit} \text{ corresponding to 10g Extremity SAR evaluation at 4~10 mm spacing,}$$

$$P_{limit} \text{ corresponding to 10g Extremity SAR evaluation at 0 mm for left and right surfaces}\}$$

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of 		PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset			Page 8 of 11

**Table 3-4**  
**SAR Characterizations**

Exposure Scenario:	Body-Worn	Phablet	Phablet	Head	Hotspot	Earjack	Maximum Tune-up Output Power*
Averaging Volume:	1g	10g	10g	1g	1g	10g	
Spacing:	15 mm	5, 4, 10	0 mm	0 mm	10 mm	0 mm	
DSI:	0	0	1	2	3	4	
Technology/Band	<b>P<sub>limit</sub> corresponding to 1mW/g (SAR_design_target)</b>						P <sub>max</sub>
CDMA/EVDO BC10	30.1	26.6	30.9	26.6	26.6	26.6	24.8
CDMA/EVDO BC0	29.7	26.5	31.7	26.4	26.5	26.5	24.5
CDMA/EVDO BC1	25.6	20.0	31.8	18.0	20.0	20.0	23.5
GSM/GPRS/EDGE 850 MHz	28.8	29.1	32.2	26.8	29.1	29.1	25.3
GSM/GPRS/EDGE 1900 MHz	25.6	20.1	31.9	18.1	20.1	20.1	22.3
UMTS B5	29.5	26.5	32.2	26.5	26.5	26.5	24.8
UMTS B4	24.8	20.5	31.6	18.0	20.5	20.5	23.5
UMTS B2	25.6	20.5	31.9	18.0	20.5	20.5	23.5
LTE FDD B71	32.1	26.9	35.5	26.9	26.9	26.9	24.8
LTE FDD B12	31.2	26.9	33.8	26.9	26.9	26.9	24.8
LTE FDD B13	30.9	27.5	33.6	27.5	27.5	27.5	24.8
LTE FDD B14	30.7	27.3	32.8	27.3	27.3	27.3	24.8
LTE FDD B26	29.8	26.9	32.2	26.6	26.9	26.9	24.8
LTE FDD B5	29.8	26.9	32.6	26.9	26.9	26.9	24.8
LTE FDD B66/4	24.9	19.5	30.6	19.0	19.5	19.5	23.5
LTE FDD B25/2	26.2	19.5	32.4	17.5	19.5	19.5	23.5
LTE FDD B30	26.8	19.0	37.0	19.0	19.0	19.0	23.0
LTE FDD B7	27.3	19.0	36.2	19.0	19.0	19.0	23.5
LTE TDD B48	20.0	20.0	15.0	20.0	20.0	20.0	21.5
LTE TDD B41/38	27.6	20.0	34.7	19.0	20.0	20.0	22.0
LTE TDD B41 (PC2)	27.6	20.0	34.7	19.0	20.0	20.0	23.4
NR FDD n71	32.1	27.9	36.1	27.9	27.9	27.9	24.8
NR FDD n12	30.6	28.6	34.5	28.6	28.6	28.6	24.8
NR FDD n5	30.6	27.3	33.4	26.3	27.3	27.3	24.8
NR FDD n66 Ant A	25.1	19.5	31.0	19.0	19.5	19.5	24.0
NR FDD n25/2 Ant A	26.7	19.5	33.2	17.5	19.5	19.5	24.3
NR FDD n30	26.2	19.0	38.1	19.0	19.0	19.0	23.0
NR TDD n41 Ant B	18.0	14.0	18.0	13.0	14.0	14.0	24.0
NR TDD n77 (PC3)	19.0	19.0	14.0	17.5	19.0	19.0	23.5
NR TDD n77 (PC2)	19.0	19.0	14.0	17.5	19.0	19.0	25.5
NR FDD n66 Ant I	23.6	23.5	17.0	19.0	23.5	23.5	23.5
NR FDD n25/2 Ant I	24.3	23.5	17.0	19.0	23.5	23.5	23.5
NR TDD n41 Ant I	20.0	20.0	16.0	18.0	20.0	20.0	24.3
NR TDD n41 Ant I (PC2)	20.0	20.0	16.0	18.0	20.0	20.0	26.3

**Notes:**

1. For all modes/bands, when Hotspot Mode (DSI=3) and Extremity sensor (DSI=1) are triggered at the same time, DSI=3 takes priority, thus the  $P_{limit}$  for DSI=3 is set to be less or equal to  $P_{limit}$  for DSI=1.
2. When  $P_{max} < P_{limit}$ , the DUT will operate at a power level up to  $P_{max}$ .
3.  $P_{limit}$  for DSI=1 and DSI =4 are the same.
4. For LTE Band 48, NR Band n77, and NR Band n66, n25, n2, and n41 Ant I, , when RCV is active, DSI=2 takes priority over all levels.

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset		Page 9 of 11

## 4 EQUIPMENT LIST

### For SAR measurements

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8503E	3.5mm Standard Calibration Kit	6/6/2020	Annual	6/6/2021	MY53402352
Agilent	8594A	[9kHz-2.9GHz] Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753ES	Network Analyzer	3/5/2020	Annual	3/5/2021	MY40001472
Agilent	8753ES	S-Parameter Network Analyzer	12/31/2019	Annual	12/31/2020	US39370122
Agilent	E4438C	ESG Vector Signal Generator	12/13/2019	Annual	12/13/2020	MY4282659
Agilent	E4438C	ESG Vector Signal Generator	3/6/2019	Biennial	3/8/2021	MY4282385
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	2/10/2020	Annual	2/10/2021	G482730325
Agilent	E5515C	Wireless Communications Test Set	2/26/2020	Annual	2/26/2021	G48400860
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	G48510464
Agilent	N5182A	MXG Vector Signal Generator	2/19/2020	Annual	2/19/2021	MY4282651
Agilent	N5182A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY5250166
Amplifier Research	155106	Amplifier	N/A	N/A	N/A	155106
Amplifier Research	155106	Amplifier	CBT	N/A	CBT	433974
Anritsu	MA24108A	USB Power Sensor	9/15/2020	Annual	9/15/2021	1244515
Anritsu	MA24108A	USB Power Sensor	2/27/2020	Annual	2/27/2021	1244524
Anritsu	MA2411B	Pulse Power Sensor	12/4/2019	Annual	12/4/2020	1126566
Anritsu	MA2411B	Pulse Power Sensor	1/21/2020	Annual	1/21/2021	1207470
Anritsu	ML2495A	Power Meter	11/15/2019	Annual	11/15/2020	1089098
Anritsu	ML2495A	Power Meter	12/17/2019	Annual	12/17/2020	941001
Anritsu	MT8821C	Radio Communication Analyzer	3/10/2020	Annual	3/10/2021	6200901190
Anritsu	MT8821C	Radio Communication Analyzer	6/15/2020	Annual	6/15/2021	6201381794
Anritsu	MT8821C	Radio Communication Analyzer	2/22/2020	Annual	2/22/2021	6261895213
Anritsu	MT8821C	Radio Communication Analyzer	11/22/2020	Annual	11/22/2021	6262044715
Control Company	4040	Therm / Clock / Humidity Monitor	2/17/2020	Biennial	2/17/2022	200113269
Control Company	4040	Therm / Clock / Humidity Monitor	2/17/2020	Biennial	2/17/2022	200113274
Control Company	4040	Therm / Clock / Humidity Monitor	3/6/2020	Biennial	3/6/2022	200170313
Control Company	4352	Long Stem Thermometer	6/26/2019	Biennial	6/26/2021	192287744
Control Company	4352	Long Stem Thermometer	6/26/2019	Biennial	6/26/2021	192287739
Keysight	7720	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
KEYSIGHT	E4438C	VECTOR SIGNAL GENERATOR	6/22/2020	Annual	6/22/2021	MY42902078
Keysight Technologies	A1/N6705B	DC Power Supply	N/A	N/A	N/A	MY3301315
Keysight Technologies	N6705B	DC Power Analyzer	4/27/2019	Biennial	4/27/2021	MY33004059
Keysight Technologies	U3401A	Digital Multimeter	5/14/2020	Biennial	5/14/2022	MY52014070
Insize	1108-350	Digital Caliper	1/17/2020	Biennial	1/17/2022	A09193536
MLC	BW-N6W3+	6dB Attenuator	CBT	N/A	CBT	1139
Mini-Circuits	SUP-2400	Low Pass Filter	CBT	N/A	CBT	RH0500903
Mini-Circuits	UL-2400	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	UL-2500	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-2500	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	N2B-1300	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	N2B-2500	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (1dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (1dB)	CBT	N/A	CBT	120
Paternack	NC-100	Torque Wrench	8/4/2020	Biennial	8/4/2022	N/A
Paternack	NC-100	Torque Wrench	8/4/2020	Biennial	8/4/2022	1445
Paternack	PE220B-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Paternack	PE220B-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	11/4/2020	Annual	11/4/2021	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	11/5/2020	Annual	11/5/2021	112347
Rohde & Schwarz	CMW500	Radio Communication Tester	3/27/2020	Annual	3/27/2021	128633
Rohde & Schwarz	CMW500	Radio Communication Tester	5/21/2020	Annual	5/21/2021	128635
Rohde & Schwarz	ZNL6	Vector Network Analyzer	9/29/2020	Annual	9/29/2021	101307
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2020	Annual	5/12/2021	1070
SPEAG	D1750V2	1750 MHz SAR Dipole	10/22/2018	Triennial	10/22/2021	1150
SPEAG	D1765V2	1765 MHz SAR Dipole	5/23/2018	Triennial	5/23/2021	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Triennial	10/23/2021	5d080
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Triennial	10/23/2021	5d149
SPEAG	D1900V2	1900 MHz SAR Dipole	2/21/2019	Biennial	2/21/2021	5d148
SPEAG	D2300V2	2300 MHz SAR Dipole	8/13/2018	Triennial	8/13/2021	1073
SPEAG	D2450V2	2450 MHz SAR Dipole	8/16/2018	Triennial	8/16/2021	981
SPEAG	D2600V2	2600 MHz SAR Dipole	4/11/2018	Triennial	4/11/2021	1004
SPEAG	D2600V2	2600 MHz SAR Dipole	1/14/2019	Annual	1/14/2020	1071
SPEAG	D2600V2	2600 MHz SAR Dipole	1/14/2019	Biennial	1/14/2021	1054
SPEAG	D3500V2	3500 MHz SAR Dipole	1/21/2020	Annual	1/21/2021	1057
SPEAG	D3700V2	3700 MHz SAR Dipole	1/21/2020	Annual	1/21/2021	1067
SPEAG	D3900V2	3900 MHz SAR Dipole	10/09/2019	Annual	10/09/2021	1056
SPEAG	D5GHV12	5 GHz SAR Dipole	1/16/2018	Triennial	1/16/2021	1057
SPEAG	D5GHV12	5 GHz SAR Dipole	8/10/2018	Biennial	8/10/2021	1237
SPEAG	D750V3	750 MHz SAR Dipole	10/19/2018	Triennial	10/19/2021	1161
SPEAG	D750V3	750 MHz Dipole	3/11/2020	Annual	3/11/2021	1054
SPEAG	D835V2	835 MHz SAR Dipole	1/13/2020	Annual	1/13/2021	4d132
SPEAG	D835V2	835 MHz SAR Dipole	10/19/2018	Triennial	10/19/2021	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/12/2020	Annual	8/12/2021	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2020	Annual	1/13/2021	1530
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2020	Annual	1/13/2021	1558
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/12/2020	Annual	3/12/2021	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/15/2020	Annual	4/15/2021	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/20/2020	Annual	5/20/2021	728
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/18/2020	Annual	6/18/2021	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/11/2020	Annual	8/11/2021	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/14/2020	Annual	5/14/2021	1583
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/5/2019	Annual	12/5/2020	1533
SPEAG	EX3D4V	SAR Probe	1/21/2020	Annual	1/21/2021	3589
SPEAG	EX3D4V	SAR Probe	1/21/2020	Annual	1/21/2021	7488
SPEAG	EX3D4V	SAR Probe	4/21/2020	Annual	4/21/2021	7357
SPEAG	EX3D4V	SAR Probe	6/23/2020	Annual	6/23/2021	7406
SPEAG	EX3D4V	SAR Probe	5/18/2020	Annual	5/18/2021	7538
SPEAG	EX3D4V	SAR Probe	1/21/2019	Annual	1/21/2020	7570
SPEAG	EX3D4V	SAR Probe	12/11/2019	Annual	12/11/2020	7571
SPEAG	EX3D4V	SAR Probe	7/21/2019	Annual	7/21/2020	7572
SPEAG	EX3D4V	SAR Probe	10/20/2020	Annual	10/20/2021	7539
SPEAG	EX3D4V	SAR Probe	8/19/2020	Annual	8/19/2021	7547

38

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

FCC ID: A3LSMG996U	 <b>PCTEST®</b> Proud to be part of  <b>PART 0 SAR CHAR REPORT</b>			Approved by: Quality Manager
Document S/N:	Test Dates:	DUT Type:	Page 10 of 11	
1M2009140143-27-R2.A3L	09/16/20 – 12/01/20	Portable Handset		

## 5 MEASUREMENT UNCERTAINTIES

### For SAR Measurements

a	c	d	e = f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Dlv.	c <sub>l</sub> 1gm	c <sub>l</sub> 10 gms	1gm	10gms	v <sub>l</sub>
<b>Measurement System</b>								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemispherical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
<b>Test Sample Related</b>								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
<b>Phantom &amp; Tissue Parameters</b>								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMG996U	 <b>PCTEST</b> Proud to be part of 	PART 0 SAR CHAR REPORT				Approved by: Quality Manager
Document S/N: 1M2009140143-27-R2.A3L	Test Dates: 09/16/20 – 12/01/20	DUT Type: Portable Handset				Page 11 of 11