



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
<http://www.pctest.com>



## MEASUREMENT REPORT GSM / GPRS / EDGE / WCDMA

**Applicant Name:**  
Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**  
9/24 - 10/22/2018  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M1809210180-02-R1.A3L


<b>FCC ID:</b>	<b>A3LSMJ260AZ</b>
<b>APPLICANT:</b>	<b>Samsung Electronics Co., Ltd.</b>

<b>Application Type:</b>	Certification
<b>Model:</b>	SM-J260AZ
<b>EUT Type:</b>	Portable Handset
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	22, 24, & 27
<b>Test Procedure(s):</b>	ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This revised Test Report (S/N: 1M1809210180-02-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M1809210180-02.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

  
Randy Ortanez  
President




<b>FCC ID:</b> A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 1 of 86	

# T A B L E O F C O N T E N T S

1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location .....	4
1.3	Test Facility / Accreditations .....	4
2.0	PRODUCT INFORMATION .....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities .....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Cellular - Base Frequency Blocks .....	6
3.3	Cellular - Mobile Frequency Blocks .....	6
3.4	PCS - Base Frequency Blocks .....	6
3.5	PCS - Mobile Frequency Blocks .....	7
3.6	AWS - Base Frequency Blocks .....	7
3.7	AWS - Mobile Frequency Blocks .....	7
3.8	Radiated Measurements .....	8
4.0	MEASUREMENT UNCERTAINTY .....	9
5.0	TEST EQUIPMENT CALIBRATION DATA .....	10
6.0	SAMPLE CALCULATIONS .....	11
7.0	TEST RESULTS .....	12
7.1	Summary .....	12
7.2	Occupied Bandwidth .....	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	18
7.4	Band Edge Emissions at Antenna Terminal .....	44
7.5	Peak-Average Ratio .....	53
7.6	Radiated Power (ERP/EIRP) .....	58
7.7	Radiated Spurious Emissions Measurements .....	63
7.8	Frequency Stability / Temperature Variation .....	75
8.0	CONCLUSION .....	86

<b>FCC ID:</b> A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 2 of 86	



## MEASUREMENT REPORT

### GSM / GPRS / EDGE / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	1.318	31.20	2.163	33.35	242KGXW
EDGE850	22H	824.2 - 848.8	0.547	27.38	0.898	29.53	245KG7W
WCDMA850	22H	826.4 - 846.6	0.084	19.23	0.137	21.38	4M16F9W
WCDMA1700	27	1712.4 - 1752.6			0.186	22.69	4M16F9W
GPRS1900	24E	1850.2 - 1909.8			0.915	29.61	244KGXW
EDGE1900	24E	1850.2 - 1909.8			0.307	24.86	245KG7W
WCDMA1900	24E	1852.4 - 1907.6			0.191	22.80	4M16F9W

#### EUT Overview

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 3 of 86	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST is an ISO 17025-2005 accredited test facility under the National Voluntary Laboratory Accreditation Program (NVLAP) with lab code 100431-0 for Specific Absorption (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

<b>FCC ID:</b> A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 4 of 86	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ260AZ**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

**Test Device Serial No.:** 24616, 24723, 24626, 32163, 32163

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE)

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

<b>FCC ID:</b> A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 5 of 86	


## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.


Deviation from Measurement Procedure.....None

### 3.2 Cellular - Base Frequency Blocks




- BLOCK 1: 869 – 880 MHz (A\* Low + A)
- BLOCK 2: 880 – 890 MHz (B)
- BLOCK 3: 890 – 891.5 MHz (A\* High)
- BLOCK 4: 891.5 – 894 MHz (B\*)

### 3.3 Cellular - Mobile Frequency Blocks



- BLOCK 1: 824 – 835 MHz (A\* Low + A)
- BLOCK 2: 835 – 845 MHz (B)
- BLOCK 3: 845 – 846.5 MHz (A\* High)
- BLOCK 4: 846.5 – 849 MHz (B\*)


### 3.4 PCS - Base Frequency Blocks



- BLOCK 1: 1930 – 1945 MHz (A)
- BLOCK 2: 1945 – 1950 MHz (D)
- BLOCK 3: 1950 – 1965 MHz (B)
- BLOCK 4: 1965 – 1970 MHz (E)
- BLOCK 5: 1970 – 1975 MHz (F)
- BLOCK 6: 1975 – 1990 MHz (C)


FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 6 of 86	

### 3.5 PCS - Mobile Frequency Blocks




- BLOCK 1: 1850 – 1865 MHz (A)
- BLOCK 2: 1865 – 1870 MHz (D)
- BLOCK 3: 1870 – 1885 MHz (B)
- BLOCK 4: 1885 – 1890 MHz (E)
- BLOCK 5: 1890 – 1895 MHz (F)
- BLOCK 6: 1895 – 1910 MHz (C)

### 3.6 AWS - Base Frequency Blocks



- BLOCK 1: 2110 – 2120 MHz (A)
- BLOCK 2: 2120 – 2130 MHz (B)
- BLOCK 3: 2130 – 2135 MHz (C)
- BLOCK 4: 2135 – 2140 MHz (D)
- BLOCK 5: 2140 – 2145 MHz (E)
- BLOCK 6: 2145 – 2155 MHz (F)

### 3.7 AWS - Mobile Frequency Blocks



- BLOCK 1: 1710 – 1720 MHz (A)
- BLOCK 2: 1720 – 1730 MHz (B)
- BLOCK 3: 1730 – 1735 MHz (C)
- BLOCK 4: 1735 – 1740 MHz (D)
- BLOCK 5: 1740 – 1745 MHz (E)
- BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 7 of 86

### 3.8 Radiated Measurements

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi]$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g [dBm] - \text{cable loss} [dB]$ .

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 8 of 86	



## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 9 of 86	

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	8/23/2018	Annual	8/23/2019	LTx1
-	LTx3	Licensed Transmitter Cable Set	8/23/2018	Annual	8/23/2019	LTx3
Agilent	N9030A	PXA Signal Analyzer (44GHz)	5/25/2018	Annual	5/25/2019	MY52350166
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2017	Biennial	10/10/2019	121034
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
Emco	3116	Horn Antenna (18 - 40GHz)	6/7/2018	Triennial	6/7/2021	9203-2178
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
Keysight Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/20/2018	Annual	3/20/2019	MY49430494
Keysight Technologies	N9030A	PXA Signal Analyzer	8/6/2018	Annual	8/6/2019	MY54490576
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			107826
Rohde & Schwarz	CMU200	Base Station Simulator	5/18/2018	Annual	5/18/2019	109892
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			836536/0005
Rohde & Schwarz	CMW500	Radio Communication Tester	11/3/2017	Annual	11/3/2018	100976
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	5/21/2018	Annual	5/21/2019	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	8/9/2018	Annual	8/9/2019	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/18/2018	Annual	6/18/2019	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/25/2018	Annual	6/25/2019	102133
Rohde & Schwarz	SMB100A03	SMB100A Signal Generator	5/30/2018	Annual	5/30/2019	180862
Rohde & Schwarz	TC-TA18	Cross-Pol Antenna 400MHz-18GHz	10/30/2017	Annual	10/30/2018	101058
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna	7/16/2018	Biennial	7/16/2020	101073
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	8/17/2018	Biennial	8/17/2020	101072
Rohde & Schwarz	TS-PR18	Shielded Filter Unit	7/2/2018	Annual	7/2/2019	102131
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	1/24/2018	Annual	1/24/2019	100040
Rohde & Schwarz	TS-PR8	Preamplifier-Antenna SYS; 30MHz-8GHz	10/19/2017	Annual	10/19/2018	102324
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

**Table 5-1. Test Equipment**

**Notes:**

- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 10 of 86	

## 6.0 SAMPLE CALCULATIONS

### GPRS Emission Designator

**Emission Designator = 250KGXW**

GPRS BW = 250 kHz  
 G = Phase Modulation  
 X = Cases not otherwise covered  
 W = Combination (Audio/Data)

### EDGE Emission Designator

**Emission Designator = 250KG7W**

EDGE BW = 250 kHz  
 G = Phase Modulation  
 7 = Quantized/Digital Info  
 W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 11 of 86	

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMJ260AZ  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM / GPRS / EDGE / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Conducted Band Edge / Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d) 27.50(b)	RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1) RSS-139(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a)(5)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d)(4)	RSS-139(6.5)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Radiated Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 12 of 86	

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup


### Test Notes

None.

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 13 of 86




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 14 of 86




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 15 of 86




Plot 7-5. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-6. Occupied Bandwidth Plot (AWS WCDMA Mode)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 16 of 86





Plot 7-7. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 17 of 86

## 7.3 Spurious and Harmonic Emissions at Antenna Terminal

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**

### Test Notes


Per 24.238(b), 27.53(h)(3), and RSS-133(6.5), RSS-139(6.5), compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 18 of 86

## Cellular GPRS Mode




Plot 7-8. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)




Plot 7-9. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 19 of 86




**Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode - Low Channel)**




**Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 20 of 86




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 21 of 86




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)



Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)


FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 22 of 86




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode - High Channel)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 23 of 86

**PCS GPRS Mode**




**Plot 7-17. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)**




**Plot 7-18. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 24 of 86






Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 25 of 86




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 26 of 86




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode - High Channel)



Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode - High Channel)


FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 27 of 86




**Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode - High Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 28 of 86

## Cellular WCDMA Mode




Plot 7-26. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-27. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 29 of 86




Plot 7-28. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-29. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 30 of 86




Plot 7-30. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-31. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 31 of 86






Plot 7-32. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-33. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 32 of 86







Plot 7-34. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 33 of 86

**AWS WCDMA Mode**




**Plot 7-35. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)**




**Plot 7-36. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 34 of 86




Plot 7-37. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)




Plot 7-38. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 35 of 86




Plot 7-39. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)




Plot 7-40. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 36 of 86




**Plot 7-41. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)**



**Plot 7-42. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)**


FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 37 of 86




**Plot 7-43. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset		Page 38 of 86

**PCS WCDMA Mode**




**Plot 7-44. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)**




**Plot 7-45. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 39 of 86




Plot 7-46. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-47. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 40 of 86






Plot 7-48. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-49. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 41 of 86




Plot 7-50. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-51. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 42 of 86



Plot 7-52. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 43 of 86

## 7.4 Band Edge Emissions at Antenna Terminal

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.**

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of the emission bandwidth
4. VBW  $\geq$  3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq$  2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes


Per 22.917(b), 24.238(b), 27.53(h)(3), and RSS-132(5.5), RSS-133(6.5), RSS-139(6.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 44 of 86

## Cellular GSM Mode




Plot 7-53. Band Edge Plot (Cellular GSM Mode - Low Channel)




Plot 7-54. Band Edge Plot (Cellular GSM Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 45 of 86

**PCS GSM Mode**




**Plot 7-55. Band Edge Plot (PCS GSM Mode - Low Channel)**




**Plot 7-56. 4MHz Span Plot (PCS GSM Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 46 of 86



Plot 7-57. Band Edge Plot (PCS GSM Mode - High Channel)



Plot 7-58. 4MHz Span Plot (PCS GSM Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 47 of 86



## Cellular WCDMA Mode



Plot 7-59. Band Edge Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-60. Band Edge Plot (Cellular WCDMA Mode - High Channel)


FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 48 of 86



**AWS WCDMA Mode**



**Plot 7-61. Band Edge Plot (AWS WCDMA Mode - Low Channel)**




**Plot 7-62. 4MHz Span Plot (AWS WCDMA Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 49 of 86




Plot 7-63. Band Edge Plot (AWS WCDMA Mode - High Channel)




Plot 7-64. 4MHz Span Plot (AWS WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 50 of 86

**PCS WCDMA Mode**



**Plot 7-65. Band Edge Plot (PCS WCDMA Mode - Low Channel)**




**Plot 7-66. 4MHz Span Plot (PCS WCDMA Mode - Low Channel)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 51 of 86



Plot 7-67. Band Edge Plot (PCS WCDMA Mode - High Channel)



Plot 7-68. 4MHz Span Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 52 of 86

## 7.5 Peak-Average Ratio

### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 5.7.1

### Test Settings

1. The signal analyzer’s CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


### Test Notes

None

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 53 of 86




Plot 7-69. Peak-Average Ratio Plot (Cellular GPRS Mode)




Plot 7-70. Peak-Average Ratio Plot (Cellular EDGE Mode)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 54 of 86




Plot 7-71. Peak-Average Ratio Plot (Cellular WCDMA Mode)




Plot 7-72. Peak-Average Ratio Plot (AWS WCDMA Mode)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 55 of 86






**Plot 7-73. Peak-Average Ratio Plot (PCS GPRS Mode)**



**Plot 7-74. Peak-Average Ratio Plot (PCS EDGE Mode)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 56 of 86





**Plot 7-75. Peak-Average Ratio Plot (PCS WCDMA Mode)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 57 of 86

## 7.6 Radiated Power (ERP/EIRP)

### Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 58 of 86

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup <1GHz**



**Figure 7-6. Radiated Test Setup >1GHz**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 59 of 86	

**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 60 of 86	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	150	357	30.36	1.50	29.71	0.936	38.45	-8.74	31.86	1.535	40.61	-8.75
836.60	GPRS850	H	150	358	30.82	1.50	30.17	1.039	38.45	-8.28	32.32	1.705	40.61	-8.29
848.80	GPRS850	H	150	351	31.85	1.50	<b>31.20</b>	<b>1.318</b>	38.45	-7.25	<b>33.35</b>	<b>2.163</b>	40.61	-7.26
848.80	GPRS850	V	150	79	30.40	1.50	29.74	0.943	38.45	-8.71	31.89	1.547	40.61	-8.71
848.80	EDGE850	H	150	351	28.04	1.50	<b>27.38</b>	0.547	38.45	-11.07	<b>29.53</b>	<b>0.898</b>	40.61	-11.07

**Table 7-2. ERP/EIRP (Cellular GPRS)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	198	285	14.25	6.76	18.86	0.077	38.45	-19.60	21.01	0.126	40.61	-19.60
836.60	WCDMA850	H	208	264	14.14	6.78	18.77	0.075	38.45	-19.69	20.92	0.123	40.61	-19.69
846.60	WCDMA850	H	210	291	14.58	6.80	<b>19.23</b>	<b>0.084</b>	38.45	-19.22	<b>21.38</b>	<b>0.137</b>	40.61	-19.23
846.60	WCDMA850	V	210	295	14.25	6.80	18.90	0.078	38.45	-19.55	21.05	0.127	40.61	-19.56

**Table 7-3. ERP/EIRP (Cellular WCDMA)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	V	153	337	14.53	8.16	<b>22.69</b>	<b>0.186</b>	30.00	-7.31
1732.60	WCDMA1700	V	127	56	13.01	8.18	21.19	0.132	30.00	-8.81
1752.60	WCDMA1700	V	109	330	12.06	8.20	20.26	0.106	30.00	-9.74
1712.40	WCDMA1700	H	223	254	-33.91	8.16	-25.75	0.000	30.00	-55.75

**Table 7-4. EIRP (AWS WCDMA)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	160	190	20.66	8.37	29.03	0.799	33.01	-3.98
1880.00	GPRS1900	H	115	359	21.20	8.41	<b>29.61</b>	<b>0.915</b>	33.01	-3.40
1909.80	GPRS1900	H	107	192	20.56	8.46	29.02	0.798	33.01	-3.99
1880.00	GPRS1900	V	280	352	20.64	8.41	29.05	0.804	33.01	-3.96
1880.00	EDGE1900	H	115	359	16.45	8.41	<b>24.86</b>	0.307	33.01	-8.15

**Table 7-5. EIRP (PCS GPRS)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 61 of 86	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	163	226	14.13	8.37	22.50	0.178	33.01	-10.51
1880.00	WCDMA1900	H	158	158	13.28	8.41	21.69	0.148	33.01	-11.32
1907.60	WCDMA1900	H	154	227	14.34	8.46	<b>22.80</b>	<b>0.191</b>	33.01	-10.21
1907.60	WCDMA1900	V	281	354	16.49	4.74	21.23	0.133	33.01	-11.78

**Table 7-6. EIRP (PCS WCDMA)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset		Page 62 of 86	

## 7.7 Radiated Spurious Emissions Measurements

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 63 of 86	

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**


**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 64 of 86	



### Cellular GPRS Mode



**Plot 7-76. Radiated Spurious Plot (Cellular GPRS Mode)**

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	162	214	-53.77	3.61	-50.17	-37.2
2472.60	H	146	216	-53.75	4.21	-49.54	-36.5
3296.80	H	364	342	-61.99	5.77	-56.22	-43.2
4121.00	H	295	9	-64.47	7.59	-56.87	-43.9
4945.20	H	288	253	-63.13	8.56	-54.57	-41.6
5769.40	H	369	250	-61.20	8.81	-52.39	-39.4
6593.60	H	-	-	-67.88	8.95	-58.93	-45.9
7417.80	H	-	-	-64.66	8.41	-56.26	-43.3

**Table 7-7. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 65 of 86	

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	170	257	-47.14	3.62	-43.52	-30.5
2509.80	H	314	44	-54.54	4.34	-50.21	-37.2
3346.40	H	-	-	-61.55	5.92	-55.63	-42.6
4183.00	H	354	7	-62.98	7.70	-55.28	-42.3
5019.60	H	297	240	-60.55	8.56	-51.99	-39.0
5856.20	H	353	246	-62.95	8.87	-54.08	-41.1
6692.80	H	343	247	-65.42	8.92	-56.50	-43.5
7529.40	H	-	-	-65.36	8.46	-56.90	-43.9
8366.00	H	-	-	-64.14	8.99	-55.15	-42.2

Table 7-8. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)


OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	211	168	-50.11	3.63	-46.48	-33.5
2546.40	H	210	29	-50.01	4.56	-45.45	-32.5
3395.20	H	398	278	-59.16	6.14	-53.02	-40.0
4244.00	H	358	243	-60.14	7.80	-52.35	-39.3
5092.80	H	305	21	-60.39	8.64	-51.75	-38.8
5941.60	H	348	13	-65.58	8.83	-56.75	-43.7
6790.40	H	294	246	-60.10	8.82	-51.27	-38.3
7639.20	H	-	-	-65.46	8.54	-56.92	-43.9

Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 66 of 86	

### Cellular WCDMA Mode



**Plot 7-77. . Radiated Spurious Plot (Cellular WCDMA Mode)**

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	108	172	-63.69	3.61	-60.09	-47.1
2479.20	H	-	-	-66.91	4.23	-62.68	-49.7
3305.60	H	-	-	-67.39	5.80	-61.60	-48.6

**Table 7-10. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 67 of 86	

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	111	164	-67.58	3.62	-63.96	-51.0
2509.80	H	-	-	-67.06	4.34	-62.72	-49.7
3346.40	H	-	-	-67.18	5.92	-61.26	-48.3

**Table 7-11. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)**


OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	147	223	-64.36	3.63	-60.74	-47.7
2539.80	H	-	-	-67.35	4.52	-62.84	-49.8
3386.40	H	-	-	-67.68	6.10	-61.58	-48.6

**Table 7-12. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 68 of 86	

### AWS WCDMA Mode



**Plot 7-78. Radiated Spurious Plot (AWS WCDMA Mode)**

OPERATING FREQUENCY: 1712.40 MHz  
 CHANNEL: 1312  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3424.80	V	179	340	-58.27	9.83	-48.44	-35.4
5137.20	V	184	15	-60.46	10.69	-49.77	-36.8
6849.60	V	209	8	-61.57	11.64	-49.93	-36.9
8562.00	V	-	-	-68.70	11.14	-57.55	-44.6
10274.40	V	-	-	-68.15	12.21	-55.94	-42.9

**Table 7-13. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 69 of 86	

OPERATING FREQUENCY: 1732.60 MHz  
 CHANNEL: 1413  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	V	312	340	-57.80	9.88	-47.92	-34.9
5197.80	V	162	13	-59.34	10.76	-48.58	-35.6
6930.40	V	361	9	-62.37	11.74	-50.62	-37.6
8663.00	V	-	-	-68.24	11.02	-57.22	-44.2
10395.60	V	-	-	-69.17	12.44	-56.73	-43.7

**Table 7-14. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)**


OPERATING FREQUENCY: 1752.60 MHz  
 CHANNEL: 1513  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3505.20	V	300	331	-60.67	9.92	-50.75	-37.7
5257.80	V	142	12	-62.39	10.72	-51.67	-38.7
7010.40	V	349	28	-65.76	11.86	-53.90	-40.9
8763.00	V	-	-	-68.62	10.98	-57.64	-44.6
10515.60	V	-	-	-68.38	12.60	-55.78	-42.8

**Table 7-15. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 70 of 86

### PCS GPRS Mode



**Plot 7-79. Radiated Spurious Plot (PCS GPRS Mode)**

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	V	111	184	-62.45	6.56	-55.89	-42.9
5550.60	V	304	357	-62.28	8.72	-53.56	-40.6
7400.80	V	-	-	-62.80	8.41	-54.39	-41.4

**Table 7-16. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 71 of 86	

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	V	125	177	-61.57	6.67	-54.90	-41.9
5640.00	V	103	211	-59.41	8.81	-50.60	-37.6
7520.00	V	-	-	-63.60	8.48	-55.11	-42.1

**Table 7-17. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)**

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	V	376	181	-62.86	7.00	-55.86	-42.9
5729.40	V	113	209	-61.68	8.77	-52.91	-39.9
7639.20	V	-	-	-63.28	8.54	-54.74	-41.7

**Table 7-18. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 72 of 86	



### PCS WCDMA Mode



**Plot 7-80. Radiated Spurious Plot (PCS WCDMA Mode)**

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	V	160	345	-66.46	6.57	-59.89	-46.9
5557.20	V	116	81	-63.42	8.72	-54.70	-41.7
7409.60	V	-	-	-64.75	8.41	-56.34	-43.3

**Table 7-19. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 73 of 86	

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	V	368	19	-66.76	6.67	-60.09	-47.1
5640.00	V	106	87	-65.67	8.81	-56.86	-43.9
7520.00	V	-	-	-65.50	8.48	-57.01	-44.0

Table 7-20. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	V	308	13	-65.95	6.97	-58.98	-46.0
5722.80	V	106	85	-63.15	8.77	-54.38	-41.4
7630.40	V	-	-	-65.53	8.52	-57.01	-44.0

Table 7-21. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 74 of 86	

## 7.8 Frequency Stability / Temperature Variation

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, RSS-132, and RSS-133, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency. For Part 24, Part 27, and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-E-2016

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset	Page 75 of 86	

## Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	836,600,000	Hz
CHANNEL:	190	
REFERENCE VOLTAGE:	4.21	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.21	+ 20 (Ref)	836,599,981	-19	-0.0000023
100 %		- 30	836,600,119	119	0.0000142
100 %		- 20	836,600,045	45	0.0000054
100 %		- 10	836,599,722	-278	-0.0000332
100 %		0	836,600,263	263	0.0000314
100 %		+ 10	836,600,249	249	0.0000298
100 %		+ 20	836,599,750	-250	-0.0000299
100 %		+ 30	836,599,815	-185	-0.0000221
100 %		+ 40	836,600,170	170	0.0000203
100 %		+ 50	836,600,103	103	0.0000123
BATT. ENDPOINT	3.62	+ 20	836,599,603	-397	-0.0000475

**Table 7-22. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 76 of 86	

## Frequency Stability / Temperature Variation




Figure 7-8. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 77 of 86

## Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	836,600,000	Hz
CHANNEL:	4183	
REFERENCE VOLTAGE:	4.21	VDC
DEVIATION LIMIT:	± 0.00025 % or 2.5 ppm	

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.21	+ 20 (Ref)	836,600,160	160	0.0000191
100 %		- 30	836,599,944	-56	-0.0000067
100 %		- 20	836,600,008	8	0.0000010
100 %		- 10	836,599,692	-308	-0.0000368
100 %		0	836,599,668	-332	-0.0000397
100 %		+ 10	836,599,917	-83	-0.0000099
100 %		+ 20	836,600,289	289	0.0000345
100 %		+ 30	836,599,964	-36	-0.0000043
100 %		+ 40	836,600,186	186	0.0000222
100 %		+ 50	836,599,924	-76	-0.0000091
BATT. ENDPOINT	3.62	+ 20	836,599,956	-44	-0.0000053

**Table 7-23. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)**

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 78 of 86	

## Frequency Stability / Temperature Variation




Figure 7-9. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 79 of 86	

## Frequency Stability / Temperature Variation

OPERATING FREQUENCY:	1,732,600,000	Hz
CHANNEL:	1413	
REFERENCE VOLTAGE:	4.21	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.21	+ 20 (Ref)	1,732,599,636	-364	-0.0000210
100 %		- 30	1,732,600,080	80	0.0000046
100 %		- 20	1,732,600,211	211	0.0000122
100 %		- 10	1,732,599,970	-30	-0.0000017
100 %		0	1,732,599,923	-77	-0.0000044
100 %		+ 10	1,732,599,911	-89	-0.0000051
100 %		+ 20	1,732,599,892	-108	-0.0000062
100 %		+ 30	1,732,599,632	-368	-0.0000212
100 %		+ 40	1,732,600,021	21	0.0000012
100 %		+ 50	1,732,599,819	-181	-0.0000104
BATT. ENDPOINT	3.62	+ 20	1,732,599,951	-49	-0.0000028

**Table 7-24. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)**

**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 80 of 86	



## Frequency Stability / Temperature Variation




Figure 7-10. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 81 of 86

## Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 661  
 REFERENCE VOLTAGE: 4.21 VDC  
 DEVIATION LIMIT:  $\pm 0.00025$  % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.21	+ 20 (Ref)	1,880,000,102	102	0.0000054
100 %		- 30	1,879,999,859	-141	-0.0000075
100 %		- 20	1,879,999,829	-171	-0.0000091
100 %		- 10	1,880,000,155	155	0.0000082
100 %		0	1,880,000,373	373	0.0000198
100 %		+ 10	1,880,000,069	69	0.0000037
100 %		+ 20	1,879,999,981	-19	-0.0000010
100 %		+ 30	1,880,000,469	469	0.0000249
100 %		+ 40	1,880,000,103	103	0.0000055
100 %		+ 50	1,880,000,254	254	0.0000135
BATT. ENDPOINT	3.62	+ 20	1,880,000,357	357	0.0000190

**Table 7-25. Frequency Stability Data (PCS GPRS Mode – Ch. 661)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 82 of 86	

## Frequency Stability / Temperature Variation




Figure 7-11. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 83 of 86	

## Frequency Stability / Temperature Variation

OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 9400  
 REFERENCE VOLTAGE: 4.21 VDC  
 DEVIATION LIMIT:  $\pm 0.00025$  % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.21	+ 20 (Ref)	1,880,000,179	179	0.0000095
100 %		- 30	1,879,999,935	-65	-0.0000035
100 %		- 20	1,880,000,022	22	0.0000012
100 %		- 10	1,879,999,946	-54	-0.0000029
100 %		0	1,879,999,981	-19	-0.0000010
100 %		+ 10	1,880,000,103	103	0.0000055
100 %		+ 20	1,880,000,057	57	0.0000030
100 %		+ 30	1,880,000,235	235	0.0000125
100 %		+ 40	1,879,999,873	-127	-0.0000068
100 %		+ 50	1,879,999,816	-184	-0.0000098
BATT. ENDPOINT	3.62	+ 20	1,880,000,126	126	0.0000067

**Table 7-26. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)**

FCC ID: A3LSMJ260AZ		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 84 of 86	

## Frequency Stability / Temperature Variation




Figure 7-12. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Quality Manager
Test Report S/N: 1M1809210180-02-R1.A3L	Test Dates: 9/21 - 10/25/2018	EUT Type: Portable Handset		Page 85 of 86

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMJ260AZ** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules.

<b>FCC ID:</b> A3LSMJ260AZ		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1809210180-02-R1.A3L	<b>Test Dates:</b> 9/21 - 10/25/2018	<b>EUT Type:</b> Portable Handset	Page 86 of 86	