



**FCC CFR47 PART 22 SUBPART H
FCC CFR47 PART 24 SUBPART E**

WWAN

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA Phone + BT/BLE, DTS b/g/n and NFC

MODEL NUMBER : SM-J320YZ

FCC ID: A3LSMJ320YZ

REPORT NUMBER: 15K22477-E5

ISSUE DATE: DEC 23, 2015

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA**

Prepared by
**UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	12/23/15	Initial issue	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	6
4.2. <i>SAMPLE CALCULATION</i>	6
4.3. <i>MEASUREMENT UNCERTAINTY</i>	6
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT</i>	7
5.2. <i>MAXIMUM OUTPUT POWER (GSM)</i>	7
5.3. <i>MAXIMUM OUTPUT POWER (WCDMA)</i>	7
5.4. <i>DESCRIPTION OF TEST SETUP</i>	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. Summary Table	12
8. RF POWER OUTPUT VERIFICATION	13
8.1. <i>GSM/GPRS/EDGE</i>	13
8.1.1. <i>GSM OUTPUT POWER RESULT</i>	14
8.2. <i>UMTS REL 99</i>	15
8.2.1. <i>WCDMA OUTPUT POWER RESULT</i>	19
9. PEAK TO AVERAGE RATIO	21
9.1. <i>CONDUCTED PEAK TO AVERAGE RESULT</i>	21
9.2. <i>CONDUCTED PEAK TO AVERAGE PLOTS</i>	22
10. LIMITS AND CONDUCTED RESULTS	24
10.1. <i>OCCUPIED BANDWIDTH</i>	24
10.1.1. <i>OCCUPIED BANDWIDTH RESULTS</i>	24
10.1.2. <i>OCCUPIED BANDWIDTH PLOTS</i>	26
10.2. <i>BAND EDGE EMISSIONS</i>	29
10.2.1. <i>BAND EDGE PLOTS</i>	30
10.3. <i>OUT OF BAND EMISSIONS</i>	32
10.3.1. <i>OUT OF BAND EMISSIONS RESULT</i>	33
10.3.2. <i>OUT OF BAND EMISSIONS PLOTS</i>	34
10.4. <i>FREQUENCY STABILITY</i>	37
10.4.1. <i>FREQUENCY STABILITY RESULTS</i>	38

11. RADIATED TEST RESULTS	40
11.1. RADIATED POWER (ERP & EIRP).....	40
11.1.1. ERP/EIRP Results	41
11.1.2. ERP/EIRP DATA.....	42
11.2. FIELD STRENGTH OF SPURIOUS RADIATION	45
11.2.1. SPURIOUS RADIATION PLOTS.....	46
12. SETUP PHOTOS.....	49

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA Phone + BT/BLE, DTS b/g/n and NFC
MODEL NUMBER: SM-J320YZ
SERIAL NUMBER: d6d2d642 (RADIATED); d6cdd626 (CONDUCTED)
DATE TESTED: DEC 14, 2015 - DEC 21, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 22H, 24E	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-D, FCC CFR 47 Part 22 and FCC CFR Part 24.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

EIRP = PSA reading with EUT worst orientation (dBm) + Path loss (dB) – cable loss(between the SG and substitution antenna) + Substitution Antenna Factor (dBi)

ERP = PSA reading with EUT worst orientation (dBm) + Path loss (dB) – cable loss(between the SG and substitution antenna)
 (Path loss = Signal generator output – PSA reading with substitution antenna)

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is GSM/WCDMA Phone + BT/BLE, DTS b/g/n and NFC.

5.2. MAXIMUM OUTPUT POWER (GSM)

The transmitter has a maximum peak conducted and radiated ERP / EIRP output powers as follows:

FCC Part 22/24						
Band	Frequency Range	Modulation	Conducted		Radiated	
	[MHz]		Peak	Avg [dBm]	Avg [mW]	Avg [dBm]
GSM1900	1850~1910	GMSK	29.67	926.83		
		GPRS	29.67	926.83	29.42	874.98
		EGPRS	24.73	297.17	26.07	404.58

5.3. MAXIMUM OUTPUT POWER (WCDMA)

The transmitter has a maximum peak conducted and radiated ERP / EIRP output powers as follows:

FCC Part 22/24						
Band	Frequency Range	Modulation	Conducted		Radiated	
	[MHz]		Peak	Avg [dBm]	Avg [mW]	Avg [dBm]
Band 5	824~849	REL99	22.87	193.64	19.01	79.62
		HSDPA	21.94	156.31	18.25	66.83
		HSUPA	21.83	152.41		
Band 2	1850~1910	REL99	22.18	165.20	23.11	204.64
		HSDPA	21.54	142.56	22.83	191.87
		HSUPA	21.52	141.91		

DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a FPCB antenna for the [List the bands supported] with a maximum peak gain as follow:

Frequency (MHz)	Peak Gain (dBi)
WCDMA Band 5 824 ~ 849 MHz	-4.17
GSM 1900 / WCDMA Band 2 1850 ~ 1910 MHz	-3.59

5.4. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	ETA0U61JWE	DK1GA12HS/A-E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
1	Audio	1	Mini-Jack	Unshielded	1.0m	N/A


TEST SETUP

The EUT is continuously communicated to the call box during the tests.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Tuned Dipole 400~1000 MHz	ETS	3121D DB4	00164753	07-28-16
Antenna, Horn, 40 GHz	ETS	3116C	00166155	09-23-16
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	08-24-17
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	11-17-16
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-26-16
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Combiner	WEINSCHTEL	1575	2151	08-20-16
Communications Test Set	R&S	CMW500	150312	08-18-16
Communications Test Set	R&S	CMW500	115331	08-18-16
Communications Test Set	R&S	CMW500	102271	08-18-16
DC Power Supply	Agilent / HP	E3640A	MY54226395	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-18-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-19-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-19-16
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-16
Average Power Sensor	R&S	NRZ-Z91	102681	08-18-16
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-18-16
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-19-16
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-19-16
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-19-16
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	08-18-16
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	015	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	016	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	015	08-18-16
LISN	R&S	ENV-216	101836	08-19-16
LISN	R&S	ENV-216	101837	08-19-16

7. Summary Table

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Note
2.1049	Occupied Band width (99%)	N/A	Conducted	Pass	4.1778MHz
22.917(a) 24.238(a)	Band Edge / Conducted Spurious Emission	-13dBm		Pass	-18.457dBm
2.1046	Conducted output power	N/A		Pass	29.67dBm
22.355 24.235	Frequency Stability	2.5PPM		Pass	-0.017PPM
22.913(a)(2)	Effective Radiated Power	38 dBm	Radiated	Pass	19.01dBm
24.232(c)	Equivalent Isotropic Radiated Power	33dBm		Pass	29.42dBm
22.917(a) 24.238(a)	Radiated Spurious Emission	-13dBm		Pass	-28.7dBm

FCC Rule Part	Frequency Range [MHz]	Output Power [W]	Frequency Tolerance	Emission Designator	Emission Bandwidth	Communication Type
GSM						
24E	1850.2 - 1909.8	0.875	2.5 ppm	247KGXW		GSM1900
	1850.2 - 1909.8	0.405	2.5 ppm	243KG7W		EGSM1900
WCDMA						
22H	826.4 - 846.6	0.080	2.5 ppm	4M16F9W		WCDMA BAND5
24E	1852.4 - 1907.6	0.205	2.5 ppm	4M18F9W		WCDMA BAND2

8. RF POWER OUTPUT VERIFICATION

8.1. GSM/GPRS/EDGE

Function: Menu select > GSM Mobile Station > GSM 850/900/1800/1900
Press Connection control to choose the different menus
Press RESET > choose all to reset all settings
Connection Press Signal Off to turn off the signal and change settings
Network Support > GSM+GPRS or GSM+EGPRS
Main Service > Packet Data
Service selection > Test Mode A – Auto Slot Config. off
MS Signal Press Slot Config bottom on the right twice to select and change the number of time slots and power setting
 > Slot configuration > Uplink/Gamma
 > 33 dBm for GPRS 850/900
 > 30 dBm for GPRS1800/1900
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset > + 0 Hz
Mode > BCCH and TCH
BCCH Level > -85 dBm (May need to adjust if link is not stable)
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]
Channel Type > Off
P0> 4 dB
Slot Config > Unchanged (if already set under MS Signal)
TCH > choose desired test channel
Hopping > Off
Main Timeslot > 3 (Default)
Network Coding Scheme > CS4 (GPRS) and MCS5 ~ MCS9 (EGPRS)
Bit Stream > 2E9-1PSR Bit Pattern
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection Press Signal On to turn on the signal and change settings

8.1.1. GSM OUTPUT POWER RESULT

GSM1900 Measured Results

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. [MHz]	Max. Power				
						Burst Pwr [dBm]	Frame Pwr [dBm]			
1900	GSM (Voice)	CS1	1	512	1850.2	29.67	20.64			
				661	1880.0	29.65	20.62			
				810	1909.8	29.29	20.26			
	GPRS (GMSK)	CS1	1	1	512	1850.2	29.67	20.64		
					661	1880.0	29.66	20.62		
					810	1909.8	29.31	20.28		
			2	1	512	1850.2	25.79	19.77		
					661	1880.0	25.91	19.89		
					810	1909.8	25.73	19.71		
			EGPRS (8PSK)	MCS5	1	1	512	1850.2	24.69	15.66
							661	1880.0	24.73	15.70
							810	1909.8	24.63	15.60
	2	1			512	1850.2	24.56	18.54		
					661	1880.0	24.57	18.55		
					810	1909.8	24.48	18.46		

8.2. UMTS REL 99

Release 99 Setup Procedures used to establish the test signals

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA Setup Procedures used to establish the test signals

The following 4 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
MPR (dB)	0	0	0.5	0.5	
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSPA (HSDPA & HSUPA) Setup Procedures used to establish the test signals

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	15/1
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15	56/75	47/15
	CM (dB)	1	3	2	3	1
MPR (dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	Ahs = β_{hs}/β_c	30/15				
HSUPA Specific Settings	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
Reference E-TFCI PO	27	27	27	27	27	
Maximum Channelisation Codes	2xSF2				SF4	

DC-HSDPA Setup Procedures used to establish the test signals

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter	Unit	Value
During Connection setup		
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121. A summary of subtest settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c/β_d	2/15	11/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
MPR (dB)	0	0	0.5	0.5	
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack Repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	A _{hs} = β_{hs}/β_c	30/15			

HSPA+

Since 16QAM is not used for uplink, the uplink Category and release is same as HSUPA, i.e., CAT 6 Rel 6. Therefore, the RF conducted power is not measured.

8.2.1. WCDMA OUTPUT POWER RESULT

WCDMA Band 5 Measured Results

Band	Mode		UL Ch No.	Freq. [MHz]	MPR [dB]	Avg Pwr [dBm]	
W-CDMA Band V	Rel 99	RMC, 12.2 kbps	4132	826.4	0	22.84	
			4183	836.6	0	22.87	
			4233	846.6	0	22.73	
	HSDPA	Subtest 1	4132	826.4	0	21.94	
			4183	836.6	0	21.79	
			4233	846.6	0	21.75	
		Subtest 2	4132	826.4	0	21.29	
			4183	836.6	0	21.41	
			4233	846.6	0	21.13	
		Subtest 3	4132	826.4	0.5	21.32	
			4183	836.6	0.5	21.32	
			4233	846.6	0.5	21.16	
		Subtest 4	4132	826.4	0.5	21.33	
			4183	836.6	0.5	21.22	
			4233	846.6	0.5	21.04	
		HSUPA	Subtest 1	4132	826.4	0	21.17
				4183	836.6	0	21.77
				4233	846.6	0	21.58
	Subtest 2		4132	826.4	2	20.29	
			4183	836.6	2	20.29	
			4233	846.6	2	20.54	
	Subtest 3		4132	826.4	1	20.39	
			4183	836.6	1	20.41	
			4233	846.6	1	20.51	
	Subtest 4		4132	826.4	2	20.95	
			4183	836.6	2	20.75	
			4233	846.6	2	20.76	
	Subtest 5		4132	826.4	0	21.85	
			4183	836.6	0	21.83	
			4233	846.6	0	21.67	

WCDMA Band 2 Measured Results

Band	Mode		UL Ch No.	Freq. [MHz]	MPR [dB]	Avg Pwr [dBm]	
W-CDMA Band II	Rel 99	RMC, 12.2 kbps	9262	1852.4	0	22.18	
			9400	1880.0	0	21.90	
			9538	1907.6	0	22.03	
	HSDPA	Subtest 1	9262	1852.4	0	21.54	
			9400	1880.0	0	21.28	
			9538	1907.6	0	21.22	
		Subtest 2	9262	1852.4	0	21.22	
			9400	1880.0	0	20.65	
			9538	1907.6	0	20.82	
		Subtest 3	9262	1852.4	0.5	20.75	
			9400	1880.0	0.5	20.63	
			9538	1907.6	0.5	20.67	
		Subtest 4	9262	1852.4	0.5	20.98	
			9400	1880.0	0.5	20.72	
			9538	1907.6	0.5	20.87	
		HSUPA	Subtest 1	9262	1852.4	0	21.35
				9400	1880.0	0	21.09
				9538	1907.6	0	21.16
	Subtest 2		9262	1852.4	2	19.72	
			9400	1880.0	2	19.93	
			9538	1907.6	2	19.88	
	Subtest 3		9262	1852.4	1	20.48	
			9400	1880.0	1	20.20	
			9538	1907.6	1	20.28	
	Subtest 4		9262	1852.4	2	20.27	
			9400	1880.0	2	20.22	
			9538	1907.6	2	20.38	
	Subtest 5	9262	1852.4	0	21.52		
		9400	1880.0	0	21.00		
		9538	1907.6	0	21.02		

9. PEAK TO AVERAGE RATIO

Test Procedure

Per KDB 971168 D01 Power Meas License Digital Systems v02r02;

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The PAR were measured on the Spectrum Analyzer.

Test Spec

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

9.1. CONDUCTED PEAK TO AVERAGE RESULT

GSM


Band	Channel	f [MHz]	Mode	Ratio [dB]	Limit [dB]
GSM1900	661	1880.0	GPRS	2.68	13.00
			EGPRS	5.75	

WCDMA


Band	Channel	f [MHz]	Mode	Ratio [dB]	Limit [dB]
Band 5	4183	836.6	REL99	2.98	13.00
			HSDPA	3.19	
Band 2	9400	1880.0	REL99	3.09	
			HSDPA	3.19	

9.2. CONDUCTED PEAK TO AVERAGE PLOTS

GSM



WCDMA



10. LIMITS AND CONDUCTED RESULTS

10.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

(KDB 971168 D01 Power Meas License Digital Systems v02r02)

10.1.1. OCCUPIED BANDWIDTH RESULTS

GSM


Band	Mode	Channel	f [MHz]	99% BW [KHz]	26dB BW [KHz]
GSM1900	GPRS	512	1850.2	242.89	314.4
		661	1880.0	242.69	311.7
		810	1909.8	247.31	312.0
	EGPRS	512	1850.2	243.06	304.7
		661	1880.0	242.21	305.3
		810	1909.8	241.25	301.7

WCDMA


Band	Mode	Channel	f [MHz]	99% BW [MHz]	26dB BW [MHz]
Band 5	REL99	4132	826.4	4.1619	4.606
		4183	836.6	4.1451	4.615
		4233	846.6	4.1559	4.617
	HSDPA	4132	826.4	4.1588	4.597
		4183	836.6	4.1412	4.617
		4233	846.6	4.1410	4.606
Band 2	REL99	9262	1852.4	4.1724	4.620
		9400	1880.0	4.1586	4.616
		9538	1907.6	4.1736	4.616
	HSDPA	9262	1852.4	4.1664	4.601
		9400	1880.0	4.1778	4.611
		9538	1907.6	4.1624	4.629

10.1.2. OCCUPIED BANDWIDTH PLOTS


GSM 1900



WCDMA Band 5



WCDMA Band 2



10.2. BAND EDGE EMISSIONS

RULE PART(S)

FCC: §22.359, §24.238

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

RESULTS

GSM


Band	Mode	Side	f [MHz]	Level [dBm]	Limit [dBm]
GSM1900	GPRS	Lower	1849.977	-18.457	-13.00
		Upper	1910.023	-18.628	
	EGPRS	Lower	1849.967	-25.859	
		Upper	1910.008	-25.096	

WCDMA


Band	Mode	Side	f [MHz]	Level [dBm]	Limit [dBm]
Band 5	REL99	Lower	824	-29.676	-13.00
		Upper	849	-34.579	
	HSDPA	Lower	824	-30.782	
		Upper	849	-34.576	
Band 2	REL99	Lower	1850	-33.317	-13.00
		Upper	1910	-38.010	
	HSDPA	Lower	1850	-34.629	
		Upper	1910	-37.910	

10.2.1. BAND EDGE PLOTS

GSM



WCDMA



10.3. OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

RESULTS

10.3.1. OUT OF BAND EMISSIONS RESULT


GSM

Band	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
GSM1900	GPRS	1850.2	-21.92	-13.00	8.92
		1880.0	-22.91		9.91
		1909.8	-22.82		9.82
	EGPRS	1850.2	-23.04		10.04
		1880.0	-22.12		9.12
		1909.8	-22.52		9.52


WCDMA

Band	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
Band 5	REL99	826.4	-32.93	-13.00	19.93
		836.6	-33.24		20.24
		846.6	-32.21		19.21
	HSDPA	826.4	-33.27		20.27
		836.6	-32.93		19.93
		846.6	-33.14		20.14
Band 2	REL99	1852.4	-33.07	-13.00	20.07
		1880.0	-32.35		19.35
		1907.6	-32.82		19.82
	HSDPA	1852.4	-32.68		19.68
		1880.0	-32.60		19.6
		1907.6	-32.90		19.9


10.3.2. OUT OF BAND EMISSIONS PLOTS
GSM 1900



WCDMA Band 5



WCDMA Band 2



10.4. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

RESULTS

See the following pages.

10.4.1. FREQUENCY STABILITY RESULTS

WCDMA Band 5, Channel 4183, Frequency 836.6 MHz

Reference Frequency: GSM850 Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2091.500 Hz				
Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.80	50	836.60000506	-0.010	2.5
3.80	40	836.60000447	-0.010	2.5
3.80	30	836.59999357	0.003	2.5
3.80	20	836.59999639	0	2.5
3.80	10	836.59999179	0.005	2.5
3.80	0	836.59999353	0.003	2.5
3.80	-10	836.60000594	-0.011	2.5
3.80	-20	836.60000466	-0.010	2.5
3.80	-30	836.60000690	-0.013	2.5

Reference Frequency: GSM850 Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2091.500 Hz				
Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.80	20	836.59999639	0	2.5
4.20	20	836.59999639	0.000	2.5
3.40	20	836.59999059	0.007	2.5

WCDMA Band 2, Channel 9400, Frequency 1880.0 MHz

GSM 1900, Channel 661, Frequency 1880.0 MHz

Reference Frequency: GSM1900 Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.80	50	1879.99998710	0.000	2.5
3.80	40	1879.99999238	-0.003	2.5
3.80	30	1879.99998596	0.000	2.5
3.80	20	1879.99998673	0	2.5
3.80	10	1879.99998286	0.002	2.5
3.80	0	1880.00000824	-0.011	2.5
3.80	-10	1879.99999142	-0.002	2.5
3.80	-20	1879.99998883	-0.001	2.5
3.80	-30	1880.00001868	-0.017	2.5

Reference Frequency: GSM1900 Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (*C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.80	20	1879.99998414	0	2.5
4.20	20	1879.99998673	-0.001	2.5
3.40	20	1879.99998394	0.000	2.5

11. RADIATED TEST RESULTS

11.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13dB.

TEST PROCEDURE

ANSI / TIA / EIA 603D Clause 2.2.17; MXA setting reference to 971168 D01 v02r02

For peak power measurement with a MXA:

a) Set the RBW \geq OBW; b) Set VBW $\geq 3 \times$ RBW; c) Set span $\geq 2 \times$ RBW; d) Sweep time = auto couple; e) Detector = peak; f) Ensure that the number of measurement points \geq span/RBW; g) Trace mode = max hold;

For average power measurement with a MXA:

a) Set span to at least 1.5 times the OBW; b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz; c) Set VBW $\geq 3 \times$ RBW; d) Set number of points in sweep $\geq 2 \times$ span / RBW; e) Sweep time = auto-couple; f) Detector = RMS (power averaging); g) Use free run trigger If burst duty cycle ≥ 98 ; h) Use trigger to capture bursts If burst duty cycle < 98 ; i) Trace average at least 100 traces in power averaging (*i.e.*, RMS) mode. j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function.

TEST RESULTS

11.1.1. ERP/EIRP Results

GSM

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
GSM1900	GPRS	512	1850.2	28.32	679.20
		661	1880.0	28.76	751.62
		810	1909.8	29.42	874.98
	EGPRS	512	1850.2	25.66	368.13
		661	1880.0	26.07	404.58
		810	1909.8	25.57	360.58

WCDMA

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
Band 5	REL99	4132	826.4	19.01	79.62
		4183	836.6	18.16	65.46
		4233	846.6	16.73	47.10
	HSDPA	4132	826.4	18.25	66.83
		4183	836.6	17.21	52.60
		4233	846.6	15.88	38.73
Band 2	REL99	9262	1852.4	23.00	199.53
		9400	1880.0	22.84	192.31
		9538	1907.6	23.11	204.64
	HSDPA	9262	1852.4	22.83	191.87
		9400	1880.0	21.94	156.31
		9538	1907.6	22.41	174.18

11.1.2. ERP/EIRP DATA

GSM 1900

GSM GSM1900 GPRS	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2																																																																																																	
	Company: Samsung Project #: 15K22477 Date: 12-21-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: GPRS 1900MHz <u>Test Equipment:</u> Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse																																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">f GHz</th> <th style="text-align: center;">SG reading (dBm)</th> <th style="text-align: center;">Ant. Pol. (H/V)</th> <th style="text-align: center;">Cable Loss (dB)</th> <th style="text-align: center;">Antenna Gain (dBi)</th> <th style="text-align: center;">EIRP (dBm)</th> <th style="text-align: center;">Limit (dBm)</th> <th style="text-align: center;">Delta (dB)</th> <th style="text-align: center;">Notes</th> </tr> </thead> <tbody> <tr> <td colspan="9">Low Ch</td> </tr> <tr> <td style="text-align: center;">1850.20</td> <td style="text-align: center;">16.8</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.60</td> <td style="text-align: center;">8.80</td> <td style="text-align: center;">23.97</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-9.0</td> <td></td> </tr> <tr> <td style="text-align: center;">1850.20</td> <td style="text-align: center;">21.1</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.60</td> <td style="text-align: center;">8.80</td> <td style="text-align: center;">28.32</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-4.7</td> <td></td> </tr> <tr> <td colspan="9">Mid Ch</td> </tr> <tr> <td style="text-align: center;">1880.00</td> <td style="text-align: center;">11.2</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.62</td> <td style="text-align: center;">8.62</td> <td style="text-align: center;">18.24</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-14.8</td> <td></td> </tr> <tr> <td style="text-align: center;">1880.00</td> <td style="text-align: center;">21.8</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.62</td> <td style="text-align: center;">8.62</td> <td style="text-align: center;">28.76</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-4.2</td> <td></td> </tr> <tr> <td colspan="9">High Ch</td> </tr> <tr> <td style="text-align: center;">1909.80</td> <td style="text-align: center;">17.4</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.63</td> <td style="text-align: center;">8.44</td> <td style="text-align: center;">24.16</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-8.8</td> <td></td> </tr> <tr> <td style="text-align: center;">1909.80</td> <td style="text-align: center;">22.6</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.63</td> <td style="text-align: center;">8.44</td> <td style="text-align: center;">29.42</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-3.6</td> <td></td> </tr> </tbody> </table>									f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	16.8	V	1.60	8.80	23.97	33.0	-9.0		1850.20	21.1	H	1.60	8.80	28.32	33.0	-4.7		Mid Ch									1880.00	11.2	V	1.62	8.62	18.24	33.0	-14.8		1880.00	21.8	H	1.62	8.62	28.76	33.0	-4.2		High Ch									1909.80	17.4	V	1.63	8.44	24.16	33.0	-8.8		1909.80	22.6	H	1.63	8.44	29.42	33.0	-3.6	
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
1850.20	16.8	V	1.60	8.80	23.97	33.0	-9.0																																																																																											
1850.20	21.1	H	1.60	8.80	28.32	33.0	-4.7																																																																																											
Mid Ch																																																																																																		
1880.00	11.2	V	1.62	8.62	18.24	33.0	-14.8																																																																																											
1880.00	21.8	H	1.62	8.62	28.76	33.0	-4.2																																																																																											
High Ch																																																																																																		
1909.80	17.4	V	1.63	8.44	24.16	33.0	-8.8																																																																																											
1909.80	22.6	H	1.63	8.44	29.42	33.0	-3.6																																																																																											
Rev. 3.17.11																																																																																																		
GSM GSM1900 EGPRS	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2																																																																																																	
	Company: Samsung Project #: 15K22477 Date: 12-21-15 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: EGPRS 1900MHz <u>Test Equipment:</u> Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse																																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">f GHz</th> <th style="text-align: center;">SG reading (dBm)</th> <th style="text-align: center;">Ant. Pol. (H/V)</th> <th style="text-align: center;">Cable Loss (dB)</th> <th style="text-align: center;">Antenna Gain (dBi)</th> <th style="text-align: center;">EIRP (dBm)</th> <th style="text-align: center;">Limit (dBm)</th> <th style="text-align: center;">Delta (dB)</th> <th style="text-align: center;">Notes</th> </tr> </thead> <tbody> <tr> <td colspan="9">Low Ch</td> </tr> <tr> <td style="text-align: center;">1850.20</td> <td style="text-align: center;">8.0</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.60</td> <td style="text-align: center;">8.80</td> <td style="text-align: center;">15.16</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-17.8</td> <td></td> </tr> <tr> <td style="text-align: center;">1850.20</td> <td style="text-align: center;">18.5</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.60</td> <td style="text-align: center;">8.80</td> <td style="text-align: center;">25.66</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-7.3</td> <td></td> </tr> <tr> <td colspan="9">Mid Ch</td> </tr> <tr> <td style="text-align: center;">1880.00</td> <td style="text-align: center;">15.9</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.62</td> <td style="text-align: center;">8.62</td> <td style="text-align: center;">22.86</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-10.1</td> <td></td> </tr> <tr> <td style="text-align: center;">1880.00</td> <td style="text-align: center;">19.1</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.62</td> <td style="text-align: center;">8.62</td> <td style="text-align: center;">26.07</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-6.9</td> <td></td> </tr> <tr> <td colspan="9">High Ch</td> </tr> <tr> <td style="text-align: center;">1909.80</td> <td style="text-align: center;">11.9</td> <td style="text-align: center;">V</td> <td style="text-align: center;">1.63</td> <td style="text-align: center;">8.44</td> <td style="text-align: center;">18.75</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-14.2</td> <td></td> </tr> <tr> <td style="text-align: center;">1909.80</td> <td style="text-align: center;">18.8</td> <td style="text-align: center;">H</td> <td style="text-align: center;">1.63</td> <td style="text-align: center;">8.44</td> <td style="text-align: center;">25.57</td> <td style="text-align: center;">33.0</td> <td style="text-align: center;">-7.4</td> <td></td> </tr> </tbody> </table>									f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	8.0	V	1.60	8.80	15.16	33.0	-17.8		1850.20	18.5	H	1.60	8.80	25.66	33.0	-7.3		Mid Ch									1880.00	15.9	V	1.62	8.62	22.86	33.0	-10.1		1880.00	19.1	H	1.62	8.62	26.07	33.0	-6.9		High Ch									1909.80	11.9	V	1.63	8.44	18.75	33.0	-14.2		1909.80	18.8	H	1.63	8.44	25.57	33.0	-7.4	
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
1850.20	8.0	V	1.60	8.80	15.16	33.0	-17.8																																																																																											
1850.20	18.5	H	1.60	8.80	25.66	33.0	-7.3																																																																																											
Mid Ch																																																																																																		
1880.00	15.9	V	1.62	8.62	22.86	33.0	-10.1																																																																																											
1880.00	19.1	H	1.62	8.62	26.07	33.0	-6.9																																																																																											
High Ch																																																																																																		
1909.80	11.9	V	1.63	8.44	18.75	33.0	-14.2																																																																																											
1909.80	18.8	H	1.63	8.44	25.57	33.0	-7.4																																																																																											
Rev. 3.17.11																																																																																																		