



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 22, 24, & 27

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:
9/22 - 10/10/2016
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0Y1609221586.A3L

FCC ID:

A3LSMJ327P

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

Application Type: Certification
Model(s): SM-J327P
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2 §22(H) §24(E) §27(L)
Test Procedure(s): ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02
Test Device Serial No.: *identical prototype* [S/N: 01043, 00411, 00166]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 1 of 102

T A B L E O F C O N T E N T S


FCC PART 22, 24, & 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	5
1.1 Scope.....	5
1.2 Testing Facility.....	5
2.0 PRODUCT INFORMATION.....	6
2.1 Equipment Description.....	6
2.2 Device Capabilities	6
2.3 Test Configuration.....	6
2.4 EMI Suppression Device(s)/Modifications.....	6
3.0 DESCRIPTION OF TESTS	7
3.1 Evaluation Procedure.....	7
3.2 Cellular - Base Frequency Blocks	7
3.3 Cellular - Mobile Frequency Blocks.....	7
3.4 PCS - Base Frequency Blocks.....	7
3.5 PCS - Mobile Frequency Blocks	8
3.6 AWS - Base Frequency Blocks	8
3.7 AWS - Mobile Frequency Blocks.....	8
3.8 Radiated Measurements.....	9
4.0 MEASUREMENT UNCERTAINTY.....	10
5.0 TEST EQUIPMENT CALIBRATION DATA	11
6.0 SAMPLE CALCULATIONS	12
7.0 TEST RESULTS.....	13
7.1 Summary.....	13
7.2 Occupied Bandwidth	14
7.3 Spurious and Harmonic Emissions at Antenna Terminal	20
7.4 Band Edge Emissions at Antenna Terminal.....	53
7.5 Peak-Average Ratio	66
7.6 Radiated Power (ERP/EIRP)	69
7.7 Radiated Spurious Emissions Measurements.....	74
7.8 Frequency Stability / Temperature Variation	87
8.0 CONCLUSION.....	102

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



MEASUREMENT REPORT

FCC Part 22, 24, & 27




§2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 129, Samsung-ro,
 Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): §2 §22(H) §24(E) §27(L)
BASE MODEL: SM-J327P
FCC ID: A3LSMJ327P
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
MODE: GSM / GPRS / EDGE / CDMA / WCDMA
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: 01043, 00411, 00166 Production Pre-Production Engineering
DATE(S) OF TEST: 9/22 - 10/10/2016
TEST REPORT S/N: 0Y1609221586.A3L



Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EVDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GPRS, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSMJ327P	PCTEST [®] Engineering Laboratory, Inc.		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		



MEASUREMENT REPORT

FCC Part 22, 24, & 27

Mode	FCC Rule Part	Tx Frequency (MHz)	ERP/EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	
GRPS850	22H	824.2 - 848.8	0.679	28.32	240KGXW
EDGE850	22H	824.2 - 848.8	0.149	21.74	244KG7W
GRPS1900	24E	1850.2 - 1909.8	0.902	29.55	243KGXW
EDGE1900	24E	1850.2 - 1909.8	0.394	25.95	243KG7W
CDMA850	22H	824.70 - 848.31	0.124	20.92	1M27F9W
CDMA1900	24E	1851.25 - 1908.75	0.338	25.29	1M27F9W
WCDMA850	22H	826.4 - 846.6	0.084	19.23	4M14F9W
WCDMA1700	27	1712.4 - 1752.6	0.208	23.18	4M12F9W
WCDMA1900	24E	1852.4 - 1907.6	0.238	23.77	4M12F9W

EUT Overview

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See *Figure 1-1*).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ327P**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 6 of 102

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-D-2010) and "Measurement Guidance for Certification of Licensed Digital Transmitters" (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....**None**

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 7 of 102 08/24/2016


3.5 PCS - Mobile Frequency Blocks

§24.229




3.6 AWS - Base Frequency Blocks

§27.5(h)



3.7 AWS - Mobile Frequency Blocks

§27.5(h)



FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 8 of 102 V 4.2 08/24/2016

3.8 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/ITA-603-D-2010.

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 9 of 102

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX3	Licensed Transmitter Cable Set	7/12/2016	Annual	7/12/2017	N/A
-	RE3	Radiated Emissions Cable Set	11/18/2015	Annual	11/18/2016	N/A
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Biennial	2/26/2018	441128
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/28/2016	Biennial	8/28/2018	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	10/22/2014	Biennial	10/22/2016	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/11/2016	Annual	7/11/2017	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/6/2016	Annual	7/6/2017	13SH10-1000/U1000-1
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	3/4/2016	Annual	3/7/2017	11210140001
Mini-Circuits	SSG-4000HP	USB Synthesized Signal Generator		N/A		11208010032
Mini-Circuits	TVA-11-422	RF Power Amp		N/A		QA1303002
Rohde & Schwarz	CMU200	Base Station Simulator	6/2/2016	Annual	6/2/2017	109892
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	VULB-9161SE	Trilog Super Broadband Test Antenna	11/13/2015	Biennial	11/13/2017	9161-4075
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

1. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

6.0 SAMPLE CALCULATIONS

GPRS Emission Designator

Emission Designator = 250KGXW

GPRS BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz
 G = Phase Modulation
 7 = Quantized/Digital Info
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 12 of 102

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMJ327P
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / EDGE / CDMA / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.4.

FCC ID: A3LSMJ327P	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 13 of 102

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 15 of 102




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode – Ch. 661)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 16 of 102




Plot 7-5. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 17 of 102




Plot 7-7. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 7-8. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Plot 7-9. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 19 of 102

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24, Part 27. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 20 of 102 08/24/2016




Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 23 of 102




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)




Plot 7-17. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 24 of 102




Plot 7-18. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)




Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 25 of 102




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 26 of 102




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 27 of 102




Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-26. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)




Plot 7-27. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)

FCC ID: A3LSMJ327P	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 29 of 102




Plot 7-28. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-29. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 30 of 102




Plot 7-30. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-31. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 31 of 102




Plot 7-32. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-33. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 32 of 102




Plot 7-34. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-35. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 33 of 102




Plot 7-36. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-37. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 34 of 102




Plot 7-38. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-39. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-40. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)



Plot 7-41. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-42. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-43. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-44. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-45. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-46. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-47. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 39 of 102




Plot 7-48. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-49. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 40 of 102




Plot 7-50. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-51. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 41 of 102




Plot 7-52. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-53. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 42 of 102




Plot 7-54. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-55. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-56. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-57. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-58. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-59. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-60. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-61. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-62. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)




Plot 7-63. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 47 of 102




Plot 7-64. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-65. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-66. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-67. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 49 of 102




Plot 7-68. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-69. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 50 of 102




Plot 7-70. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-71. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 51 of 102



Plot 7-72. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup


Test Notes

Per 22.917(b), 24.238(b), 27.53(h)(3), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-73. Band Edge Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-74. Band Edge Plot (Cellular GPRS Mode – Ch. 251)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 54 of 102




Plot 7-75. Band Edge Plot (PCS GPRS Mode – Ch. 512)




Plot 7-76. 4MHz Span Plot (PCS GPRS Mode – Ch. 512)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-77. Band Edge Plot (PCS GPRS Mode – Ch. 810)




Plot 7-78. 4MHz Span Plot (PCS GPRS Mode – Ch. 810)

FCC ID: A3LSMJ327P	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 56 of 102




Plot 7-79. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)



Plot 7-80. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 57 of 102




Plot 7-81. Band Edge Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-82. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 58 of 102



Plot 7-83. Band Edge Plot (PCS CDMA Mode – Ch. 25)




Plot 7-84. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 59 of 102




Plot 7-85. Band Edge Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-86. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 60 of 102




Plot 7-87. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-88. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMJ327P	PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 61 of 102



Plot 7-89. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-90. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset




Plot 7-91. Band Edge Plot (AWS WCDMA Mode – Ch. 1513)




Plot 7-92. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMJ327P	 PCTEST Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 63 of 102



Plot 7-93. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-94. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Plot 7-95. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-96. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 65 of 102

7.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 66 of 102 08/24/2016




Plot 7-97. Peak-Average Ratio Plot (PCS GPRS Mode – Ch. 661)




Plot 7-98. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 67 of 102



Plot 7-99. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-100. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 68 of 102



7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) 27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 69 of 102

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	225	25	22.72	5.00	27.72	0.592	38.45	-10.73
836.60	GPRS850	H	183	25	21.99	5.16	27.15	0.519	38.45	-11.30
848.80	GPRS850	H	210	8	23.01	5.31	28.32	0.679	38.45	-10.13
848.80	GPRS850	V	124	209	21.54	5.05	26.59	0.456	38.45	-11.86
848.80	EDGE850	H	210	8	16.43	5.31	21.74	0.149	38.45	-16.71

Table 7-2. ERP (Cellular GPRS)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 71 of 102

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.70	CDMA850	H	204	160	15.91	5.01	20.92	0.124	38.45	-17.53
836.52	CDMA850	H	357	157	14.36	5.16	19.52	0.089	38.45	-18.93
848.31	CDMA850	H	340	151	13.94	5.30	19.24	0.084	38.45	-19.21
824.70	CDMA850	V	154	221	13.68	4.95	18.63	0.073	38.45	-19.82

Table 7-3. ERP (Cellular CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	225	17	14.20	5.03	19.23	0.084	38.45	-19.22
836.60	WCDMA850	H	206	169	13.98	5.16	19.14	0.082	38.45	-19.31
846.60	WCDMA850	H	206	19	13.82	5.28	19.10	0.081	38.45	-19.35
826.40	WCDMA850	V	134	29	13.03	5.04	18.07	0.064	38.45	-20.38

Table 7-4. ERP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	H	318	292	13.50	9.65	23.15	0.207	30.00	-6.85
1732.60	WCDMA1700	H	114	283	13.57	9.61	23.18	0.208	30.00	-6.82
1752.60	WCDMA1700	H	301	291	13.42	9.57	22.99	0.199	30.00	-7.01
1732.60	WCDMA1700	V	125	154	13.09	9.53	22.62	0.183	30.00	-7.38

Table 7-5. EIRP (AWS WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	267	306	20.20	9.35	29.55	0.902	33.01	-3.46
1880.00	GPRS1900	H	198	324	19.24	9.27	28.51	0.710	33.01	-4.50
1909.80	GPRS1900	H	317	311	20.19	9.25	29.44	0.879	33.01	-3.57
1850.20	GPRS1900	V	117	276	17.03	9.35	26.38	0.435	33.01	-6.63
1850.20	EDGE1900	H	267	306	16.74	9.21	25.95	0.394	33.01	-7.06

Table 7-6. EIRP (PCS GPRS)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	H	257	297	15.94	9.35	25.29	0.338	33.01	-7.72
1880.00	CDMA1900	H	259	312	14.79	9.27	24.06	0.255	33.01	-8.95
1908.75	CDMA1900	H	245	302	15.15	9.25	24.40	0.275	33.01	-8.61
1851.25	CDMA1900	V	135	278	14.08	9.21	23.29	0.213	33.01	-9.72

Table 7-7. EIRP (PCS CDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	265	308	14.34	9.34	23.68	0.234	33.01	-9.33
1880.00	WCDMA1900	H	249	309	14.50	9.27	23.77	0.238	33.01	-9.24
1907.60	WCDMA1900	H	247	304	13.18	9.24	22.42	0.175	33.01	-10.59
1880.00	WCDMA1900	V	100	336	11.41	9.27	20.68	0.117	33.01	-12.33

Table 7-8. EIRP (PCS WCDMA)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a) 27.53(h)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This device was tested under all RC and SO combinations and the worst case is reported with RC3/SO55 with "All Up" power control bits.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 6) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 7) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 8) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MEASURED OUTPUT POWER: 27.72 dBm = 0.592 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 40.72$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1648.40	H	329	19	-47.28	3.65	-43.63	71.4
2472.60	H	274	88	-39.62	3.57	-36.06	63.8
3296.80	H	-	-	-54.53	5.79	-48.75	76.5
4121.00	H	-	-	-55.50	6.96	-48.54	76.3

Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MEASURED OUTPUT POWER: 27.15 dBm = 0.519 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 40.15$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	132	38	-43.85	3.52	-40.33	67.5
2509.80	H	248	51	-39.59	3.59	-36.00	63.1
3346.40	H	-	-	-55.04	5.87	-49.17	76.3
4183.00	H	-	-	-54.77	7.16	-47.60	74.8

Table 7-10. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ327P	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MEASURED OUTPUT POWER: 28.32 dBm = 0.679 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 41.32$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1697.60	H	176	45	-42.38	3.39	-38.99	67.3
2546.40	H	200	193	-40.13	3.75	-36.38	64.7
3395.20	H	-	-	-54.58	5.92	-48.65	77.0
4244.00	H	-	-	-55.49	7.30	-48.19	76.5

Table 7-11. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 20.92 dBm = 0.124 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 33.92$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1649.40	H	125	58	-62.65	3.64	-59.01	79.9
2474.10	H	133	67	-66.95	3.57	-63.39	84.3
3298.80	H	-	-	-68.47	5.81	-62.66	83.6

Table 7-12. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 77 of 102



OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MEASURED OUTPUT POWER: 19.52 dBm = 0.089 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 32.52$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.04	H	237	43	-63.79	3.52	-60.27	79.8
2509.56	H	202	47	-67.91	3.59	-64.32	83.8
3346.08	H	-	-	-68.16	5.87	-62.29	81.8

Table 7-13. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 19.24 dBm = 0.084 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 32.24$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1696.62	H	121	27	-61.82	3.40	-58.42	77.7
2544.93	H	213	60	-65.41	3.74	-61.67	80.9
3393.24	H	-	-	-68.33	5.92	-62.41	81.7

Table 7-14. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 78 of 102



OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MEASURED OUTPUT POWER: 19.23 dBm = 0.084 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 32.23$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1652.80	H	121	51	-64.59	3.62	-60.96	80.2
2479.20	H	-	-	-65.86	3.56	-62.29	81.5
3305.60	H	-	-	-66.19	5.83	-60.36	79.6

Table 7-15. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MEASURED OUTPUT POWER: 19.14 dBm = 0.082 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 32.14$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	126	66	-63.65	3.52	-60.13	79.3
2509.80	H	-	-	-64.83	3.59	-61.24	80.4
3346.40	H	-	-	-66.18	5.87	-60.31	79.4

Table 7-16. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ327P	PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 79 of 102



OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MEASURED OUTPUT POWER: 19.10 dBm = 0.081 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 32.10$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.20	H	132	54	-64.52	3.42	-61.11	80.2
2539.80	H	-	-	-65.74	3.72	-62.02	81.1
3386.40	H	-	-	-66.63	5.91	-60.71	79.8

Table 7-17. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MEASURED OUTPUT POWER: 23.15 dBm = 0.207 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 36.15$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3424.80	H	-	-	-66.14	8.15	-57.99	81.1
5137.20	H	-	-	-64.64	10.37	-54.27	77.4
6849.60	H	-	-	-63.71	11.48	-52.23	75.4

Table 7-18. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 80 of 102



OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MEASURED OUTPUT POWER: 23.18 dBm = 0.208 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 36.18$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.20	H	-	-	-65.47	8.26	-57.21	80.4
5197.80	H	-	-	-65.58	10.41	-55.17	78.4
6930.40	H	-	-	-63.76	11.53	-52.23	75.4

Table 7-19. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1412)

OPERATING FREQUENCY: 1752.60 MHz
 CHANNEL: 1513
 MEASURED OUTPUT POWER: 22.99 dBm = 0.199 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 35.99$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.20	H	183	21	-58.70	8.36	-50.34	73.3
5257.80	H	125	306	-61.61	10.35	-51.25	74.2
7010.40	H	-	-	-63.68	11.59	-52.09	75.1
8763.00	H	-	-	-62.77	13.08	-49.68	72.7
10515.60	H	-	-	-60.26	12.95	-47.30	70.3

Table 7-20. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 81 of 102



OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 29.55 dBm = 0.902 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 42.55$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	V	188	246	-57.26	8.79	-48.47	78.0
5550.60	V	110	202	-49.69	10.44	-39.25	68.8
7400.80	V	-	-	-61.43	11.96	-49.48	79.0

Table 7-21. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 28.51 dBm = 0.710 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 41.51$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	V	186	87	-61.75	8.72	-53.03	81.5
5640.00	V	69	207	-50.26	10.61	-39.65	68.2
7520.00	V	-	-	-61.68	12.03	-49.65	78.2

Table 7-22. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMJ327P	PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 82 of 102



OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 29.44 dBm = 0.879 W
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 42.44$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3819.60	V	132	118	-62.47	8.64	-53.83	83.3
5729.40	V	142	156	-54.47	10.66	-43.81	73.3
7639.20	V	-	-	-62.42	12.15	-50.26	79.7

Table 7-23. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 25.29 dBm = 0.338 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 38.29$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3702.50	H	134	233	-53.40	8.41	-44.99	70.3
5553.75	H	121	210	-59.58	10.52	-49.07	74.4
7405.00	H	168	159	-64.41	12.01	-52.40	77.7
9256.25	H	-	-	-63.78	13.27	-50.51	75.8

Table 7-24. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSMJ327P	PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 83 of 102



OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MEASURED OUTPUT POWER: 24.06 dBm = 0.255 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 37.06$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	108	157	-54.79	8.64	-46.15	70.2
5640.00	H	103	162	-58.94	10.62	-48.33	72.4
7520.00	H	103	159	-64.66	12.04	-52.62	76.7
9400.00	H	-	-	-63.21	13.23	-49.98	74.0

Table 7-25. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MEASURED OUTPUT POWER: 24.40 dBm = 0.275 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 37.40$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3817.50	H	245	296	-55.81	8.77	-47.04	71.4
5726.25	H	255	167	-58.74	10.71	-48.03	72.4
7635.00	H	135	178	-64.64	12.17	-52.47	76.9
9543.75	H	-	-	-62.70	13.29	-49.41	73.8

Table 7-26. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSMJ327P	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MEASURED OUTPUT POWER: 23.68 dBm = 0.234 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 36.68$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3704.80	V	174	20	-59.17	8.79	-50.38	74.1
5557.20	V	129	73	-62.15	10.47	-51.68	75.4
7409.60	V	-	-	-63.62	11.96	-51.66	75.3

Table 7-27. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MEASURED OUTPUT POWER: 23.77 dBm = 0.238 W
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 36.77$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	V	124	358	-64.65	8.72	-55.93	79.7
5640.00	V	105	325	-60.43	10.61	-49.82	73.6
7520.00	V	-	-	-63.50	12.03	-51.47	75.2

Table 7-28. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 85 of 102



OPERATING FREQUENCY: 1907.60 MHz
CHANNEL: 9538
MEASURED OUTPUT POWER: 22.42 dBm = 0.175 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) = 35.42$ dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.20	V	144	13	-59.96	8.64	-51.32	73.7
5722.80	V	127	327	-60.31	10.65	-49.66	72.1
7630.40	V	-	-	-63.74	12.16	-51.58	74.0

Table 7-29. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 86 of 102

7.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 §27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 87 of 102



Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 3.80 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,600,223	223	0.0000267
100 %		- 30	836,600,036	36	0.0000043
100 %		- 20	836,600,342	342	0.0000409
100 %		- 10	836,600,000	0	0.0000000
100 %		0	836,600,050	50	0.0000060
100 %		+ 10	836,600,063	63	0.0000075
100 %		+ 20	836,599,921	-79	-0.0000094
100 %		+ 30	836,600,134	134	0.0000160
100 %		+ 40	836,599,951	-49	-0.0000059
100 %		+ 50	836,599,816	-184	-0.0000220
BATT. ENDPOINT	3.40	+ 20	836,600,203	203	0.0000243

Table 7-30. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 88 of 102

Frequency Stability / Temperature Variation

§2.1055 \$22.355




Figure 7-8. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.80 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,519,980	-20	-0.0000024
100 %		- 30	836,519,543	-457	-0.0000546
100 %		- 20	836,520,247	247	0.0000295
100 %		- 10	836,520,062	62	0.0000074
100 %		0	836,520,360	360	0.0000430
100 %		+ 10	836,519,768	-232	-0.0000277
100 %		+ 20	836,519,985	-15	-0.0000018
100 %		+ 30	836,519,858	-142	-0.0000170
100 %		+ 40	836,519,713	-287	-0.0000343
100 %		+ 50	836,519,679	-321	-0.0000384
BATT. ENDPOINT	3.40	+ 20	836,519,667	-333	-0.0000398

Table 7-31. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 90 of 102

Frequency Stability / Temperature Variation

§2.1055 \$22.355




Figure 7-9. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Frequency Stability / Temperature Variation

§2.1055 \$22.355

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 4183

REFERENCE VOLTAGE: 3.80 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,842	-158	-0.0000189
100 %		- 30	836,599,881	-119	-0.0000142
100 %		- 20	836,599,988	-12	-0.0000014
100 %		- 10	836,600,065	65	0.0000078
100 %		0	836,599,848	-152	-0.0000182
100 %		+ 10	836,600,282	282	0.0000337
100 %		+ 20	836,600,003	3	0.0000004
100 %		+ 30	836,600,000	0	0.0000000
100 %		+ 40	836,599,631	-369	-0.0000441
100 %		+ 50	836,599,677	-323	-0.0000386
BATT. ENDPOINT	3.40	+ 20	836,600,141	141	0.0000169

Table 7-32. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 92 of 102

Frequency Stability / Temperature Variation

§2.1055 \$22.355




Figure 7-10. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Frequency Stability / Temperature Variation

§2.1055 \$27.54

OPERATING FREQUENCY: 1,732,600,000 Hz

CHANNEL: 1413

REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,599,919	-81	-0.0000047
100 %		- 30	1,732,599,738	-262	-0.0000151
100 %		- 20	1,732,599,833	-167	-0.0000096
100 %		- 10	1,732,599,886	-114	-0.0000066
100 %		0	1,732,599,960	-40	-0.0000023
100 %		+ 10	1,732,599,705	-295	-0.0000170
100 %		+ 20	1,732,599,976	-24	-0.0000014
100 %		+ 30	1,732,599,753	-247	-0.0000143
100 %		+ 40	1,732,599,942	-58	-0.0000033
100 %		+ 50	1,732,600,403	403	0.0000233
BATT. ENDPOINT	3.40	+ 20	1,732,600,208	208	0.0000120

Table 7-33. Frequency Stability Data (AWS WCDMA Mode – Ch. 1412)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 94 of 102

Frequency Stability / Temperature Variation

§2.1055 \$27.54




Figure 7-11. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,880,000,142	142	0.0000076
100 %		- 30	1,879,999,900	-100	-0.0000053
100 %		- 20	1,879,999,950	-50	-0.0000027
100 %		- 10	1,880,000,122	122	0.0000065
100 %		0	1,880,000,080	80	0.0000043
100 %		+ 10	1,879,999,815	-185	-0.0000098
100 %		+ 20	1,880,000,144	144	0.0000077
100 %		+ 30	1,879,999,966	-34	-0.0000018
100 %		+ 40	1,880,000,055	55	0.0000029
100 %		+ 50	1,879,999,795	-205	-0.0000109
BATT. ENDPOINT	3.40	+ 20	1,879,999,927	-73	-0.0000039

Table 7-34. Frequency Stability Data (PCS GPRS Mode – Ch. 661)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 96 of 102

Frequency Stability / Temperature Variation

§2.1055 §24.235




Figure 7-12. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset



Frequency Stability / Temperature Variation

§2.1055 §24.235

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,913	-87	-0.0000046
100 %		- 30	1,879,999,927	-73	-0.0000039
100 %		- 20	1,879,999,988	-12	-0.0000006
100 %		- 10	1,880,000,388	388	0.0000206
100 %		0	1,879,999,993	-7	-0.0000004
100 %		+ 10	1,879,999,945	-55	-0.0000029
100 %		+ 20	1,879,999,849	-151	-0.0000080
100 %		+ 30	1,879,999,964	-36	-0.0000019
100 %		+ 40	1,879,999,997	-3	-0.0000002
100 %		+ 50	1,879,999,887	-113	-0.0000060
BATT. ENDPOINT	3.40	+ 20	1,879,999,841	-159	-0.0000085

Table 7-35. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ327P		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 98 of 102

Frequency Stability / Temperature Variation

§2.1055 §24.235




Figure 7-13. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

Frequency Stability / Temperature Variation

§2.1055 \$24.235

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,880,000,034	34	0.0000018
100 %		- 30	1,880,000,003	3	0.0000002
100 %		- 20	1,880,000,002	2	0.0000001
100 %		- 10	1,879,999,992	-8	-0.0000004
100 %		0	1,879,999,837	-163	-0.0000087
100 %		+ 10	1,879,999,853	-147	-0.0000078
100 %		+ 20	1,879,999,957	-43	-0.0000023
100 %		+ 30	1,880,000,268	268	0.0000143
100 %		+ 40	1,879,999,670	-330	-0.0000176
100 %		+ 50	1,879,999,598	-402	-0.0000214
BATT. ENDPOINT	3.40	+ 20	1,880,000,347	347	0.0000185

Table 7-36. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMJ327P	 PCTEST	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset		Page 100 of 102

Frequency Stability / Temperature Variation

§2.1055 §24.235




Figure 7-14. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMJ327P	 FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset** **FCC ID: A3LSMJ327P** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules.

FCC ID: A3LSMJ327P	 PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / CDMA / WCDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1609221586.A3L	Test Dates: 9/22 - 10/10/2016	EUT Type: Portable Handset	Page 102 of 102