




# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 15.225 NFC

**Applicant Name:**  
Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**  
3/21/2017-4/25/2017  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
1M1704110140-10.A3L


<b>FCC ID:</b>	<b>A3LSMJ530G</b>
<b>APPLICANT:</b>	<b>Samsung Electronics Co., Ltd.</b>

**Application Type:** Certification  
**Model:** SM-J530G/DS  
**Additional Model(s):** SM-J530Y/DS, SM-J530Y, SM-J530G  
**EUT Type:** Portable Handset  
**Frequency:** 13.56MHz  
**FCC Classification:** Low Power Communications Device Transmitter (DXX)  
**FCC Rule Part(s):** FCC Part 15 Subpart C (15.225)  
**Test Procedure(s):** ANSI C63.10-2013



The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.10-2013 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*NVLAP accreditation does not constitute any product endorsement by NVLAP or any agency of the United States Government. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.*



  
 Randy Ortanez  
 President




<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 1 of 30	

# TABLE OF CONTENTS


FCC Part 15.225 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION .....		4
1.1 Scope .....		4
1.2 PCTEST Test Location .....		4
2.0 PRODUCT INFORMATION.....		5
2.1 Equipment Description.....		5
2.2 Device Capabilities .....		5
2.3 Test Configuration .....		5
2.4 EMI Suppression Device(s)/Modifications .....		5
3.0 DESCRIPTION OF TEST .....		6
3.1 Evaluation Procedure .....		6
3.2 AC Line Conducted Emissions .....		6
3.3 Radiated Emissions.....		7
3.4 Environmental Conditions.....		7
4.0 ANTENNA REQUIREMENTS .....		8
5.0 MEASUREMENT UNCERTAINTY .....		9
6.0 TEST EQUIPMENT CALIBRATION DATA .....		10
7.0 TEST DATA.....		11
7.1 Summary .....		11
7.2 20dB Bandwidth Measurement.....		12
7.3 Frequency Stability Test Data.....		14
7.4 In-Band Radiated Spurious Emission Measurements.....		17
7.5 Radiated Spurious Emission Measurements, Out-of-Band.....		20
7.6 Line Conducted Measurement Data .....		24
8.0 CONCLUSION.....		30

<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 2 of 30	



# MEASUREMENT REPORT

## FCC Part 15.225





### § 2.1033 General Information



**APPLICANT:** Samsung Electronics Co., Ltd.  
**APPLICANT ADDRESS:** 129, Samsung-ro,  
 Yeongtong-gu, Suwon-si  
 Gyeonggi-do, 16677, Korea  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** Part 15 Subpart C (15.225)  
**BASE MODEL:** SM-J530G/DS  
**FCC ID:** A3LSMJ530G  
**FCC CLASSIFICATION:** Low Power Communications Device Transmitter (DXX)  
**Test Device Serial No.:** 00277       Production     Pre-Production     Engineering  
**DATE(S) OF TEST:** 3/21/2017-4/25/2017  
**TEST REPORT S/N:** 1M1704110140-10.A3L

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

<b>FCC ID:</b> A3LSMJ530G	 ENGINEERING LABORATORY, INC.	<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 3 of 30	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 4 of 30

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ530G**. The test data contained in this report pertains only to the emissions due to the NFC transmitter of the EUT.

### 2.2 Device Capabilities

This device contains the following capabilities:



850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

### 2.3 Test Configuration

The EUT was set to continuously transmit at 13.56MHz. This was performed using manufacturer software loaded on the phone and a passive RFID tag to allow for continuous transmission. This device was tested in accordance with the guidance of ANSI C63.10-2013. See Sections 3.2 and 3.3 of this test report for a description of the AC line conducted emissions and radiated emissions test setups, respectively.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 5 of 30

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

**Deviation from measurement procedure.....None**



### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.6. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 6 of 30

### 3.3 Radiated Emissions



The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 in Clause 5 of ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, a high density expanded polystyrene block is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 7 of 30

## 4.0 ANTENNA REQUIREMENTS



**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the EUT are **permanently attached**.
- This unit was tested with its standard battery.

**Conclusion:**



The EUT complies with the requirement of §15.203.

<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 8 of 30	

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 9 of 30	

## 6.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/11/2016	Annual	7/11/2017	RE1
-	WL25-1	Conducted Cable Set (25GHz)	10/30/2016	Annual	10/30/2017	WL25-1
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/27/2017	Annual	3/27/2018	MY52350166
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Biennial	2/26/2018	441128
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/23/2016	Biennial	8/23/2018	135427
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	7/11/2016	Annual	7/11/2017	100071
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	7/30/2015	Biennial	7/30/2017	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
Agilent	9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 10 of 30	

## 7.0 TEST DATA

### 7.1 Summary



Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMJ530G  
 FCC Classification: Low Power Communications Device Transmitter (DXX)  
 Frequencies Examined: 13.56MHz

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	20 dB Bandwidth	N/A	RADIATED	PASS	Section 7.2
15.225 (a)(b)(c)	In-Band Emissions	15,848µV/m @ 30m 13.553 – 13.567 MHz  334µV/m @ 30m 13.410 – 13.553 MHz 13.567 – 13.710 MHz		PASS	Section 7.4
15.225 (d) 15.209	Out-of-Band Emissions	Emissions outside of the specified band (13.110 – 14.010 MHz) must meet the radiated limits detailed in 15.209		PASS	Section 7.5
15.225 (e)	Frequency Stability Tolerance	± 0.01% of Operating Frequency	Temperature Chamber	PASS	Section 7.3
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 7.6

**Table 7-1. Summary of Test Results**

**Note:**

This unit was tested with its standard battery.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 11 of 30	

## 7.2 20dB Bandwidth Measurement

### §2.1049

#### Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequency.

#### Test Procedure Used



ANSI C63.10-2013 – Section 6.9.2

#### Test Settings

1. Spectrum analyzer frequency is set to the nominal EUT channel center frequency.
2. RBW = 1 – 5% OBW
3. VBW  $\geq$  3 x RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. Using the marker-delta function, determine the “-20dB down amplitude” using [(highest in band spectral density) – 20dB].
10. Set a marker at the lowest frequency of the envelope of the spectral density, such that the marker is at or slightly below the “-20dB down amplitude” determined in Step 9.
11. Reset marker-delta function and move the marker to other side of the emission until the delta marker amplitude is the same level as reference level amplitude. The marker delta frequency reading at this point is the specified emission bandwidth.

#### Test Notes

None.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 12 of 30




Figure 7-1. Test Instrument & Measurement Setup

Frequency	20dB Bandwidth
13.56MHz	436kHz

Table 7-2. 20dB Bandwidth Measurement



Figure 7-2. 20dB Bandwidth Plot

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 13 of 30

## 7.3 Frequency Stability Test Data

### §15.225

#### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.10-2013. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -20°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 15.225, the frequency stability of the transmitter shall be maintained within ±0.01% of the center frequency.***

#### Test Procedure Used

ANSI C63.10-2013 – Section 6.8

#### Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -20°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

#### Test Notes

None.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 14 of 30



## Frequency Stability Test Data

§15.225


OPERATING FREQUENCY: 13,560,000 Hz  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: ± 0.01 % = 1356Hz

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	13,560,107	107	0.0007891
100 %		- 30	13,560,063	63	0.0004646
100 %		- 20	13,560,067	67	0.0004941
100 %		- 10	13,560,206	206	0.0015192
100 %		0	13,559,833	-167	-0.0012316
100 %		+ 10	13,559,902	-98	-0.0007227
100 %		+ 20	13,559,753	-247	-0.0018215
100 %		+ 30	13,559,891	-109	-0.0008038
100 %		+ 40	13,560,375	375	0.0027655
100 %		+ 50	13,560,122	122	0.0008997
BATT. ENDPOINT	3.45	+ 20	13,559,680	-320	-0.0023599



**Table 7-3. Frequency Stability Test Data**

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 15 of 30	

**Frequency Stability Test Data**  
§15.225



**Figure 7-3. Frequency Stability Plot**

<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 16 of 30	

## 7.4 In-Band Radiated Spurious Emission Measurements §15.225(a)(b)(c)

### Test Overview and Limit

The EUT was tested from 13.110 – 14.010 MHz. All in-band radiated spurious emissions are measured with a spectrum analyzer connected to a loop antenna while the EUT is operating at appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All in-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 8-4.***

Frequency [MHz]	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
13.553-13.567 MHz	15,848	30
13.410-13.553 MHz and 13.567-13.710 MHz	334	30
13.110-13.410 MHz	106	30



**Table 7-4. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Section 6.4.7


### Test Settings

1. RBW = 9kHz
2. VBW  $\geq$  3 x RBW
3. Detector = peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 17 of 30	

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.





**Figure 7-4. Radiated Test Setup**

**Test Notes:**

1. All emissions lying in restricted bands specified in §15.225 are below the limit shown in Table 8-4.
2. All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2). Extrapolation Factor =  $20 \log_{10}(30/3)^2 = 40\text{dB}$ .
5. The spectrum was investigated from 9kHz up to 30MHz using the loop antenna. Only the emissions shown in the table below were found to be significant.
6. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

**Sample Calculation**

- Field Strength Level  $[\text{dB}\mu\text{V}/\text{m}] = \text{Analyzer Level} [\text{dBm}] + 107 + \text{AFCL} [\text{dB}/\text{m}]$
- $\text{AFCL} [\text{dB}/\text{m}] = \text{Antenna Factor} [\text{dB}/\text{m}] + \text{Cable Loss} [\text{dB}]$
- $\text{Margin} [\text{dB}] = \text{Field Strength Level} [\text{dB}\mu\text{V}/\text{m}] - \text{Limit} [\text{dB}\mu\text{V}/\text{m}]$

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 18 of 30	



## In-Band Radiated Spurious Emission Measurements §15.225(a)(b)(c)

Frequency: 13.56MHz

Measurement Distance: 3 Meters

Frequency [MHz]	Antenna Position	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	3m Field Strength [dBμV/m]	30m Field Strength [dBμV/m]	Limit [μV/m]	Limit [dBμV/m]	Margin [dB]
13.347	X	110	156	-89.79	14.90	32.11	-7.89	106.00	40.51	-48.40
13.454	X	110	156	-83.88	14.89	38.01	-1.99	334.00	50.47	-52.46
13.478	X	110	156	-84.08	14.89	37.81	-2.19	334.00	50.47	-52.66
13.560	X	110	156	-66.49	14.89	55.40	15.40	15848.00	84.00	-68.60
13.642	X	110	156	-83.01	14.89	38.88	-1.12	334.00	50.47	-51.60
13.663	X	110	156	-85.38	14.88	36.50	-3.50	334.00	50.47	-53.97
13.772	X	110	156	-84.74	14.88	37.14	-2.86	106.00	40.51	-43.37

**Table 7-5. In-Band Radiated Measurements**

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 19 of 30	

## 7.5 Radiated Spurious Emission Measurements, Out-of-Band §15.209 §15.225(d)

### Test Overview and Limit

The EUT was tested from 9kHz up to the 1GHz excluding the band 13.110 – 14.010 MHz. All measurements up to 960MHz were recorded with a spectrum analyzer employing a quasi-peak detector.

*All out-of-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 7-6 per Section 15.209.*

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3



**Table 7-6. Radiated Limits – Out of band**

### Test Procedures Used

ANSI C63.10-2013 – Section 6.5.4


### Test Settings

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 9kHz for emissions below 30MHz and 100kHz for emissions between 30MHz and 1GHz
3. VBW  $\geq$  3 x RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 20 of 30	

**Test Setup**



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup < 30MHz**



**Figure 7-6. Radiated Test Setup > 30MHz**



<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>	 <b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 21 of 30

**Test Notes:**

1. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector for emissions below 960MHz.
2. A loop antenna was used to investigate emissions below 30MHz.
3. Both Vertical and Horizontal polarities of the receive antenna were evaluated with the worst case emissions being reported. Below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
4. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
6. No spurious emissions levels were found to be greater than the level of the fundamental.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

**Sample Calculation**

- Field Strength Level [dB $\mu$ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB $\mu$ V/m] – Limit [dB $\mu$ V/m]

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 22 of 30



## Radiated Spurious Emission Measurements, Out-of-Band §15.209 §15.225(d)

Tx Frequency 13.56MHz

Measurement Distance: 3 Meters

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	3m Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
27.12	X	-	-	-90.65	13.27	29.62	69.54	-39.93
40.68	H	110	93	-76.14	-15.77	15.09	40.00	-24.91
54.24	H	-	-	-74.02	-21.58	11.40	40.00	-28.60
67.80	H	-	-	-74.06	-21.21	11.73	40.00	-28.27
81.36	H	-	-	-72.99	-21.58	12.43	40.00	-27.57
94.92	H	-	-	-72.38	-20.32	14.30	43.52	-29.22
108.48	H	-	-	-72.89	-16.90	17.21	43.52	-26.31

Table 7-7. Radiated Measurements

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 23 of 30	

## 7.6 Line Conducted Measurement Data

### §15.207

#### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below, per 15.207.**

Frequency of emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Table 7-8. Conducted Limits**

\*Decreases with the logarithm of the frequency.

#### Test Procedures Used

ANSI C63.10-2013, Section 6.2



#### Test Settings

##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


##### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset	Page 24 of 30	

## Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**


## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207.
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 25 of 30

## Line-Conducted Test Data (With Antenna Connected)

### §15.207



**Plot 7-1. Line-Conducted Test Plot with Antenna Connected (L1)**


Frequency	Process State	QuasiPeak	Average	Limit	Margin	Meas. Time	Bandwidth	Corr.
MHz		dBµV	dBµV	dBµV	dB	ms	kHz	dB
0.620250	FINAL	---	23.85	46.00	22.15	5000.0	9.000	0.1
0.620250	FINAL	33.71	---	56.00	22.29	5000.0	9.000	0.1
1.968000	FINAL	---	22.99	46.00	23.01	5000.0	9.000	0.2
1.968000	FINAL	33.68	---	56.00	22.32	5000.0	9.000	0.2
2.694750	FINAL	---	22.23	46.00	23.77	5000.0	9.000	0.2
2.694750	FINAL	31.74	---	56.00	24.26	5000.0	9.000	0.2
2.746500	FINAL	---	22.23	46.00	23.77	5000.0	9.000	0.2
2.746500	FINAL	31.70	---	56.00	24.30	5000.0	9.000	0.2
3.774750	FINAL	---	23.11	46.00	22.89	5000.0	9.000	0.2
3.774750	FINAL	33.09	---	56.00	22.91	5000.0	9.000	0.2
13.560000	FINAL	---	56.36	50.00	-6.36	5000.0	9.000	0.4
13.560000	FINAL	60.27	---	60.00	-0.27	5000.0	9.000	0.4

**Table 7-9 Line-Conducted Test Measurements with Antenna Connected (L1)**

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 26 of 30	

# Line Conducted Measurement Data (with Antenna Connected)

**\$15.207**



**Plot 7-2. Line-Conducted Test Plot with Antenna Connected (N)**


Frequency	Process State	QuasiPeak	Average	Limit	Margin	Meas. Time	Bandwidth	Corr.
MHz		dBµV	dBµV	dBµV	dB	ms	kHz	dB
0.188250	FINAL	---	35.28	54.11	18.83	5000.0	9.000	0.3
0.188250	FINAL	49.45	---	64.11	14.66	5000.0	9.000	0.3
0.271500	FINAL	---	27.89	51.07	23.18	5000.0	9.000	0.2
0.271500	FINAL	41.50	---	61.07	19.57	5000.0	9.000	0.2
3.826500	FINAL	---	24.92	46.00	21.08	5000.0	9.000	0.2
3.826500	FINAL	33.93	---	56.00	22.07	5000.0	9.000	0.2
13.560000	FINAL	---	58.97	50.00	-8.97	5000.0	9.000	0.4
13.560000	FINAL	62.61	---	60.00	-2.61	5000.0	9.000	0.4
18.030750	FINAL	---	25.15	50.00	24.85	5000.0	9.000	0.6
18.030750	FINAL	37.13	---	60.00	22.87	5000.0	9.000	0.6
18.341250	FINAL	---	25.65	50.00	24.35	5000.0	9.000	0.6
18.341250	FINAL	38.14	---	60.00	21.86	5000.0	9.000	0.6

**Table 7-10 Line-Conducted Test Measurements with Antenna Connected (N)**

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 27 of 30	

# Line Conducted Measurement Data (with Antenna Terminated in 50Ω)

## §15.207



**Plot 7-3. Line-Conducted Test Plot with Antenna Terminated in 50Ω (L1)**


Frequency MHz	Process State	QuasiPeak dBµV	Average dBµV	Limit dBµV	Margin dB	Meas. Time ms	Bandwidth kHz	Corr. dB
0.183750	FINAL	---	23.06	54.31	31.25	5000.0	9.000	0.3
0.183750	FINAL	37.66	---	64.31	26.65	5000.0	9.000	0.3
13.744500	FINAL	---	22.49	50.00	27.51	5000.0	9.000	0.4
13.744500	FINAL	31.63	---	60.00	28.37	5000.0	9.000	0.4
16.635750	FINAL	---	17.55	50.00	32.45	5000.0	9.000	0.5
16.635750	FINAL	28.45	---	60.00	31.55	5000.0	9.000	0.5
17.148750	FINAL	---	18.75	50.00	31.25	5000.0	9.000	0.5
17.148750	FINAL	32.11	---	60.00	27.89	5000.0	9.000	0.5
20.031000	FINAL	---	23.55	50.00	26.45	5000.0	9.000	0.6
20.031000	FINAL	33.12	---	60.00	26.88	5000.0	9.000	0.6
20.496750	FINAL	---	19.30	50.00	30.70	5000.0	9.000	0.6
20.496750	FINAL	29.99	---	60.00	30.01	5000.0	9.000	0.6

**Table 7-11 Line-Conducted Test Measurements with Antenna Terminated in 50Ω (L1)**

<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset		Page 28 of 30	

# Line Conducted Measurement Data (with Antenna Terminated in 50Ω)

## §15.207



**Plot 7-4. Line-Conducted Test Plot with Antenna Terminated in 50Ω (N)**



Frequency	Process State	QuasiPeak	Average	Limit	Margin	Meas. Time	Bandwidth	Corr.
MHz		dBµV	dBµV	dBµV	dB	ms	kHz	dB
14.388000	FINAL	---	24.56	50.00	25.44	5000.0	9.000	0.5
14.388000	FINAL	35.54	---	60.00	24.46	5000.0	9.000	0.5
14.437500	FINAL	---	23.13	50.00	26.87	5000.0	9.000	0.5
14.437500	FINAL	35.21	---	60.00	24.79	5000.0	9.000	0.5
14.748000	FINAL	---	24.19	50.00	25.81	5000.0	9.000	0.5
14.748000	FINAL	34.95	---	60.00	25.05	5000.0	9.000	0.5
14.799750	FINAL	---	21.58	50.00	28.42	5000.0	9.000	0.5
14.799750	FINAL	31.87	---	60.00	28.13	5000.0	9.000	0.5
14.844750	FINAL	---	22.46	50.00	27.54	5000.0	9.000	0.5
14.844750	FINAL	33.32	---	60.00	26.68	5000.0	9.000	0.5
15.450000	FINAL	---	19.81	50.00	30.19	5000.0	9.000	0.5
15.450000	FINAL	28.24	---	60.00	31.76	5000.0	9.000	0.5

**Table 7-12 Line-Conducted Test Measurements with Antenna Terminated in 50Ω (N)**

FCC ID: A3LSMJ530G		FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1704110140-10.A3L	Test Date(s): 3/21/2017-4/25/2017	EUT Type: Portable Handset		Page 29 of 30

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMJ530G** has been tested to show compliance with the requirements specified in §15.225 of the FCC Rules.

<b>FCC ID:</b> A3LSMJ530G		<b>FCC Pt. 15.225 MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1704110140-10.A3L	<b>Test Date(s):</b> 3/21/2017-4/25/2017	<b>EUT Type:</b> Portable Handset	Page 30 of 30	