

## FCC CFR47 PART 15 SUBPART C

## NFC

## **CERTIFICATION TEST REPORT**

## FOR

## GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and NFC

MODEL NUMBER : SM-J600L, SM-J600N

FCC ID: A3LSMJ600KOR

**REPORT NUMBER: 4788452485-E4V2** 

**ISSUE DATE: MAY 14, 2018** 

Prepared for SAMSUNG ELECTRONICS CO., LTD. 129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI, GYEONGGI-DO, 16677, KOREA

Prepared by UL Korea, Ltd. 26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433



TL-637

## **Revision History**

Rev.	Issue Date	Revisions	Revised By
V1	05/11/18	Initial issue	Junwhan Lee
V2	05/14/18	Updated to address TCB's question	Junwhan Lee

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 2 of 30

# TABLE OF CONTENTS

1.	ATT	TESTATION OF TEST RESULTS 4
2.	TES	ST METHODOLOGY
3.	FAC	CILITIES AND ACCREDITATION
4.	CAI	LIBRATION AND UNCERTAINTY
4	l.1.	MEASURING INSTRUMENT CALIBRATION
4	<sup>1</sup> .2.	SAMPLE CALCULATION
4	<sup>1</sup> .3.	MEASUREMENT UNCERTAINTY
5.	EQI	UIPMENT UNDER TEST
5	5.1.	DESCRIPTION OF EUT
5	5.2.	MAXIMUM E-FIELD STRENGTH
5	5.3.	WORST-CASE CONFIGURATION AND MODE 6
5	5.4.	DESCRIPTION OF TEST SETUP
6.	TES	ST AND MEASUREMENT EQUIPMENT10
7.	20d	IB BANDWIDTH11
8.	RAI	DIATED EMISSION TEST RESULTS12
8	8. <i>1.</i> 8.1. 8.1. 8.1.	LIMITS AND PROCEDURE 12   1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz) 14   2. SPURIOUS EMISSION 0.09 TO 30 MHz 16   3. TX SPURIOUS EMISSION 30 TO 1000 MHz 18
9.	AC	MAINS LINE CONDUCTED EMISSIONS20
10.	F	REQUENCY STABILITY25
11.	S	ETUP PHOTOS

# **1. ATTESTATION OF TEST RESULTS**

COMPANY NAME:	SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION:	GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and NFC
MODEL NUMBER:	SM-J600L, SM-J600N
SERIAL NUMBER:	R39K30VMZRR (RADIATED, CONDUCTED);
DATE TESTED:	MAY 03, 2018 - MAY 09, 2018

APPLICABLE STANDARDS						
STANDARD	TEST RESULTS					
CFR 47 Part 15 Subpart C	Pass					

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL Korea, Ltd. By:

pask

Tested By:

Junwhan Lee Suwon Lab Engineer UL Korea, Ltd.

Page 4 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential

This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

SungGil Park Suwon Lab Engineer UL Korea, Ltd.

# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

- 1. FCC CFR 47 Part 2.
- 2. FCC CFR 47 Part 15.
- 3. ANSI C63.10-2013.

# 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
🛛 Chamber 1
Chamber 2
Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at http://www.iasonline.org/PDF/TL/TL-637.pdf.

# 4. CALIBRATION AND UNCERTAINTY

## 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

## **4.2. SAMPLE CALCULATION**

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

# 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB

Uncertainty figures are valid to a confidence level of 95%.

```
Page 5 of 30
```

This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

# 5. EQUIPMENT UNDER TEST

## 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n and NFC. This test report addresses the DXX (NFC) operational mode.

## 5.2. MAXIMUM E-FIELD STRENGTH

The testing was performed at 3 meter. The transmitter maximum E-field at 30m distance is 15.96 dBuV/m which convert from 3 meter data.

# 5.3. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that the Z orientation was the worst-case orientation; therefore all final radiated testing was performed with the EUT in the Z orientation while generating continuous emissions.

The fundamental level of the EUT was investigated each type and bitrate. All test was performed worst case condition(type A and bit rate 106 kbps).

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 6 of 30

## 5.4. DESCRIPTION OF TEST SETUP

#### SUPPORT EQUIPMENT

Support Equipment List								
Description Manufacturer Model Serial Number FCC ID								
Charger	SAMSUNG	EP-TA50KWK	DW2JC11LS/A- E	N/A				
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A				
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A				

#### I/O CABLES

I/O Cable List								
Cable	Port	# of identical	Remarks					
No		ports	Туре		Length (m)			
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A		
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A		

#### TEST SETUP

For fundamental level below 30MHz, the EUT standalone condition is worst-case configuration. For above 30MHz to 1GHz and AC power line conducted test, the EUT with earphone and chager condition is worst-case configuration.

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 7 of 30

#### SETUP DIAGRAM FOR TESTS

#### **Radiated Emissions Below 30 MHz:**



UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 8 of 30

### Radiated Emissions Above 30 MHz, AC Line Conducted Emissions:



Page 9 of 30

# 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List									
Description	Manufacturer	Model	S/N	Cal Due					
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19					
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	WARZBECK VULB9163		08-31-19					
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK VULB9163		749	09-14-19					
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-26-19					
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18					
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18					
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18					
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18					
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18					
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	08-07-18					
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18					
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18					
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18					
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18					
DC Power Supply	Agilent / HP	E3640A	MY54226395	08-07-18					
Temperature Chamber	ESPEC	SH-642	93001109	08-08-18					
LISN	R&S	ENV216	101837	08-09-18					
UL Software									
Description	Manufacturer	Model	V	ersion					
Radiated software	UL	UL EMC	V	'er 9.5					
AC Line Conducted software	UL	UL EMC	Ver 9.5						

Page 10 of 30

# 7. 20dB BANDWIDTH

### LIMITS

### §15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

### §15.225

Operation within the band 13.110 – 14.010MHz

#### TEST PROCEDURE

The spectrum analyzer connected receive antenna and the EUT placed on near the receive antenna. The RBW is set to 10KHz. The VBW is set to 3 times the RBW. The sweep time is coupled.

#### **RESULTS**

Frequency	20dB Bandwidth		
[MHz]	[KHz]		
13.56	435.15		

#### 20dB Bandwidth Plot



Page 11 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential

This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

# 8. RADIATED EMISSION TEST RESULTS

# 8.1. LIMITS AND PROCEDURE

### <u>LIMIT</u>

### §15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator							
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)					
0.009 - 0.490	2400 / F (kHz)	300					
0.490 – 1.705	24000 / F (kHz)	30					
1.705 – 30.0	30	30					
30 - 88	100**	3					
88 - 216	150**	3					
216 – 960	200**	3					
Above 960	500	3					

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241. §15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is: Limit (dBuV/m) = 20 log limit (uV/m)

Page 12 of 30

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

### TEST PROCEDURE

ANSI C63.10-2013

The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 13.56 MHz. The frequency range was investigated from 0.15 MHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)

### **RESULTS**

No non-compliance noted:

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 13 of 30





Page 14 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential *This report shall not be reproduced except in full, without the written approval of* UL Korea, Ltd.

#### **Trace Markers**

[Face On]

Marker	Frequency	Meter	Det	Loop Antenna	Dist Corr 30m	Cable Loss	Corrected	FCC 15.225	Margin	Azimuth
	(MHz)	Reading					Reading	Limit	(dB)	(Degs)
		(dBuV)					dB(uVolts/met			
							er)			
1	12.93425	23.84	PK	19.9	-40	.5	4.24	29.54	-25.3	0-360
2	13.263	25.01	PK	19.9	-40	.5	5.41	40.51	-35.1	0-360
3	13.47575	22.59	PK	19.9	-40	.5	2.99	50.5	-47.51	0-360
4	13.564	35.56	PK	19.9	-40	.5	15.96	84	-68.04	0-360
5	13.61188	26.11	PK	19.9	-40	.6	6.61	50.5	-43.89	0-360
6	13.88713	22.78	PK	19.8	-40	.6	3.18	40.51	-37.33	0-360
7	14.2045	22.02	PK	19.8	-40	.6	2.42	29.54	-27.12	0-360

## [Face Off]

Marker	Frequency	Meter	Det	Loop Antenna	Dist Corr 30m	Cable Loss	Corrected	FCC 15.225	Margin	Azimuth
	(MHz)	Reading					Reading	Limit	(dB)	(Degs)
		(dBuV)					dB(uVolts/met			
							er)			
8	12.85213	25.12	PK	19.9	-40	.5	5.52	29.54	-24.02	0-360
9	13.17863	24.17	PK	19.9	-40	.5	4.57	40.51	-35.94	0-360
10	13.497	23.21	PK	19.9	-40	.5	3.61	50.5	-46.89	0-360
11	13.55925	33.21	PK	19.9	-40	.5	13.61	84	-70.39	0-360
12	13.65088	23.92	PK	19.9	-40	.6	4.42	50.5	-46.08	0-360
13	13.899	24.73	PK	19.8	-40	.6	5.13	40.51	-35.38	0-360
14	14.197	23.38	PK	19.8	-40	.6	3.78	29.54	-25.76	0-360

PK - Peak Detector

Note : Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 15 of 30



## 8.1.2. SPURIOUS EMISSION 0.09 TO 30 MHz

Page 16 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential *This report shall not be reproduced except in full, without the written approval of* UL Korea, Ltd.

#### **Trace Markers**

[Face On]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna	Cable Loss	Dist Corr 300m	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	QP Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.01048	52.51	Pk	20.2	.1	-80	-7.19	67.18	-74.37	47.18	-54.37	-	-	-	-	-	-	0-360
2	.0182	48.85	Pk	20	.1	-80	-11.05	62.38	-73.43	42.38	-53.43	-	-	-	-	-	-	0-360
3	.22238	33.59	Pk	19.6	.1	-80	-26.71	-	-	-	-	-	-	40.67	-67.38	20.67	-47.38	0-360
4	.85944	19.62	Pk	19.7	.2	-40	48	-	-	-	•	28.93	-29.41	-	-	-	-	0-360
5	7.90665	31.83	Pk	19.9	.4	-40	12.13	-	-	-	-	29.5	-17.37	-	-	-	-	0-360

## [Face Off]

Marker	Frequency	Meter	Det	Loop	Cable	Dist Corr	Corrected	Peak Limit	Margin	Avg Limit	Margin	QP Limit	Margin	Peak Limit	Margin	Avg Limit	Margin	Azimuth
	(MHz)	Reading		Antenna	Loss	30m	Reading	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(Degs)
		(dBuV)					(dBuVolts)											
7	.01129	52.82	Pk	20.2	.1	-80	-6.88	66.53	-73.41	46.53	-53.41	-	-	-	-	-	-	0-360
8	.01852	52.16	Pk	20	.1	-80	-7.74	62.23	-69.97	42.23	-49.97	-	-	-	-	-	-	0-360
9	.25854	33.79	Pk	19.5	.1	-80	-26.61	-	-	-	-	-	-	39.36	-65.97	19.36	-45.97	0-360
10	.99209	19.65	Pk	19.7	.2	-40	45	-	-	-	-	27.69	-28.14	-	-	-	-	0-360
11	7.63333	30.7	Pk	19.9	.4	-40	11	-	-	-	-	29.5	-18.5	-	-	-	-	0-360

Pk - Peak detector

Page 17 of 30



### 8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz

Page 18 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential *This report shall not be reproduced except in full, without the written approval of* UL Korea, Ltd.

### Trace Markers

Marker	Frequency	Meter	Det	750_20170831	30-1000MHz[dB]	Corrected	QPk Limit (dBuV/m)	Margin	Azimuth	Height	Polarity
	(MHz)	Reading				Reading		(dB)	(Degs)	(cm)	
		(dBuV)				(dBuV/m)					
1	45.035	36.27	Pk	19.7	-29.3	26.67	40	-13.33	0-360	100	Н
2	107.309	39.03	Pk	17.4	-28.4	28.03	43.52	-15.49	0-360	300	н
3	303.734	34.35	Pk	19.3	-26.9	26.75	46.02	-19.27	0-360	300	Н
4	44.6955	47.87	Pk	19.6	-29.4	38.07	40	-1.93	0-360	100	V
5	* 115.36	35.97	Pk	16.6	-28.2	24.37	43.52	-19.15	0-360	100	V
6	201.981	36.76	Pk	16.8	-27.5	26.06	43.52	-17.46	0-360	200	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

#### **Radiated Emissions**

Frequency	Meter	Det	750_20170831	30-1000MHz[dB]	Corrected	QPk Limit	Margin	Azimuth	Height	Polarity
(MHz)	Reading				Reading	(dBuV/m)	(dB)	(Degs)	(cm)	
	(dBuV)				(dBuV/m)					
44.332	45.86	Qp	19.5	-29.5	35.86	40	-4.14	100	103	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Qp - Quasi-Peak detector

Page 19 of 30

# 9. AC MAINS LINE CONDUCTED EMISSIONS

### <u>LIMITS</u>

### §15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a  $50\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range	Limit	s (dBµV)							
(MHz)	Quasi-peak	Average							
0.15 to 0.50	66 to 56	56 to 46							
0.50 to 5	56	46							
5 to 30	60	50							
Notes: 1. The lower limit shall apply at the transition frequencies									

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

#### **RESULTS**

No non-compliance noted:

Page 20 of 30

#### WORST EMISSIONS



LINE 1 PLOT

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 21 of 30

## LINE 1 RESULTS

### **Trace Markers**

#### **Trace Markers**

#### Range 1: Phase L1 .15 - 30MHz

Marker	Frequency	Meter	Det	101837_L1_wit	CABLELOSS(dB)	Corrected	CFR 47 FCC	Margin	CFR 47 FCC	Margin
	(MHz)	Reading		h extension		Reading	PART 15 Class B	(dB)	PART 15 Class B	(dB)
		(dBuV)				(dB(uVolts))	QP		AV	
1	.165	36.78	Pk	10	.1	46.88	65.21	-18.33	-	-
2	.168	20.36	Av	10	.1	30.46	-	-	55.06	-24.6
3	.198	36.56	Pk	9.8	.2	46.56	63.69	-17.13	-	-
4	.207	20.87	Av	9.7	.2	30.77	-	-	53.32	-22.55
5	.648	31.18	Pk	9.8	.2	41.18	56	-14.82	-	-
6	.657	20.19	Av	9.8	.2	30.19	-	-	46	-15.81
7	9.546	39.96	Pk	9.8	.4	50.16	60	-9.84	-	-
8	9.552	23.07	Av	9.8	.4	33.27	-	-	50	-16.73
9	10.899	41.18	Pk	9.8	.3	51.28	60	-8.72	-	-
10	10.869	22.63	Av	9.8	.3	32.73	-	-	50	-17.27
11	13.56	36.18	Pk	9.8	.4	46.38	60	-13.62	-	-
12	13.56	25.8	Av	9.8	.4	36	-	-	50	-14

Pk - Peak detector

Av - Average detection

#### **Quasi-Peak Emissions**

Range 1: Phase L1 .15 - 30MHz

Frequency	Meter	Det	101837_L1_with	CABLELOSS(dB)	Corrected	CFR 47 FCC PART	Margin	CFR 47 FCC PART	Margin	
(MHz)	Reading		extension		Reading	15 Class B QP	(dB)	15 Class B AV	(dB)	
	(dBuV)				(dB(uVolts))					
13.5602	32.35	Qp	9.8	.4	42.55	60	-17.45	-	-	

Qp - Quasi-Peak detector

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 22 of 30





UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 23 of 30

## **LINE 2 RESULTS**

### **Trace Markers**

#### **Trace Markers**

#### Range 2: Phase N .15 - 30MHz

Marker	Frequency	Meter	Det	101837_N_with	CABLELOSS(dB)	Corrected	CFR 47 FCC	Margin	CFR 47 FCC	Margin
	(MHz)	Reading		extension		Reading	PART 15 Class B	(dB)	PART 15 Class B	(dB)
		(dBuV)				(dB(uVolts))	QP		AV	
13	.171	36.22	Pk	10	.2	46.42	64.91	-18.49	-	-
14	.171	19.77	Av	10	.2	29.97	-	-	54.91	-24.94
15	.198	35.72	Pk	9.9	.2	45.82	63.69	-17.87	-	-
16	.198	17.71	Av	9.9	.2	27.81	-	-	53.69	-25.88
17	.654	30.33	Pk	9.8	.2	40.33	56	-15.67	-	-
18	.654	15.05	Av	9.8	.2	25.05	-	-	46	-20.95
19	9.555	35.77	Pk	9.8	.4	45.97	60	-14.03	-	-
20	9.552	20.99	Av	9.8	.4	31.19	-	-	50	-18.81
21	10.908	36.82	Pk	9.8	.3	46.92	60	-13.08	-	-
22	10.908	21.36	Av	9.8	.3	31.46	-	-	50	-18.54
23	13.56	33.49	Pk	9.8	.4	43.69	60	-16.31	-	-
24	13.56	24.22	Av	9.8	.4	34.42	-	-	50	-15.58

Pk - Peak detector

Av - Average detection

#### **Quasi-Peak Emissions**

Range 2: Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
	(dBuV)				(dB(uVolts))				
13.5602	28.73	Qp	9.8	.4	38.93	60	-21.07	-	-

**Qp** - Quasi-Peak detector

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Page 24 of 30

# 10. FREQUENCY STABILITY

### <u>LIMIT</u>

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### TEST PROCEDURE

#### ANSI C63.10 §6.8

#### **RESULTS**

	Reference Frequency: EUT Channel 13.56 MHz @ 20ºC Limit: ± 100 ppm  = 1.356 kHz										
Power Supply	Envir.			Freq	uency Dev	iation Measureed	with Time	Elapse			
()(do)	Tomp (°C)	Start up	Delta (ppm)	@ 2mins	Delta (ppm)	@ 5mins	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)	
(vac)	Temp (C)	(11112)	(ppin)	(11112)	(ppin)	(11112)	(ppin)	(11112)	(ppiii)	(ppiii)	
3.85	50	13.559821269	0.343	13.559820906	0.369	13.559820821	0.376	13.559820151	0.425	100	
3.85	40	13.559823334	0.190	13.559823198	0.200	13.559823011	0.214	13.559822664	0.240	100	
3.85	30	13.559824811	0.081	13.559824729	0.087	13.559824546	0.101	13.559824115	0.133	100	
3.85	20	13.559825915	0	13.559826108	-0.014	13.559826426	-0.038	13.559826889	-0.072	100	
3.85	10	13.559829879	-0.292	13.559830226	-0.318	13.559830472	-0.336	13.559830569	-0.343	100	
3.85	0	13.559832862	-0.512	13.559832911	-0.516	13.559833589	-0.566	13.559833997	-0.596	100	
3.85	-10	13.559834215	-0.612	13.559834648	-0.644	13.559834897	-0.662	13.559835426	-0.701	100	
3.85	-20	13.559836122	-0.753	13.559836346	-0.769	13.559836897	-0.810	13.559837022	-0.819	100	
3.85	-30	13.559837425	-0.849	13.559837835	-0.879	13.559838125	-0.900	13.559838429	-0.923	100	

			Re	eference Freque Limi	ency: EUT t: ± 100 pp	Channel 13.56 MHz m  = 1.356 kHz	z @ 20ºC							
Power Supply	Power Frequency Deviation Measureed with Time Elapse													
ouppiy	<b>L</b>	Start up	Delta @ 2mins Delta @ 5mins Delta @ 10 mins Delta Limit											
(Vdc)	Temp (°C)	(MHz)	) (ppm) (MHz) (ppm) (MHz) (ppm) (MHz) (ppm) (ppm)											
3.85	20	13.559825915	825915   0   13.559826108   -0.014   13.559826426   -0.038   13.559826889   -0.072   100											
4.40	20	13.559826016	26016 -0.007 <b>13.559826168</b> -0.019 <b>13.559826511</b> -0.006 <b>13.559826972</b> -0.078 100											
3.60	20	13.559826105	.559826016   -0.007   13.559826018   -0.019   13.559826577   -0.008   13.559826972   -0.078   100     .559826105   -0.014   13.559826282   -0.027   13.559826529   -0.008   13.559826992   -0.080   100											

No non-compliance noted.

Page 25 of 30

UL Korea, Ltd. Suwon Laboratory 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 UL Korea, Ltd. Confidential *This report shall not be reproduced except in full, without the written approval of* UL Korea, Ltd.