

# FCC BT REPORT

## Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Address:**  
129, Samsung-ro, Yeongtong-gu, Suwon-si,  
Gyeonggi-do, 16677, Rep. of Korea

**Date of Issue:**  
September 06, 2018

**Test Site/Location:**  
HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-  
myeo, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-RF-1809-FC022

**FCC ID:** A3LSMJ610G


**APPLICANT:** SAMSUNG Electronics Co., Ltd.

According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID :  
A3LSMJ610F report.


**Model:** SM-J610G/DS  
**Additional Model:** SM-J610G, SM-J415G/DS, SM-J415G  
**EUT Type:** Mobile Phone  
**Max. RF Output Power:** 11.772 dBm (15.038 mW)  
**Frequency Range:** 2402 MHz - 2480 MHz (Bluetooth)  
**Modulation type** GFSK(Normal),  $\pi/4$ DQPSK and 8DPSK(EDR)  
**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter  
**FCC Rule Part(s):** Part 15 subpart C 15.247

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



**Report prepared by : Kwon Jeong**  
**Engineer of Telecommunication testing center**



**Approved by : Jong Seok Lee**  
**Manager of Telecommunication testing center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1809-FC022	September 06, 2018	- First Approval Report

# Table of Contents

1.	EUT DESCRIPTION.....	4
2.	REQUIREMENTS FOR BLUETOOTH TRANSMITTER(15.247).....	5
3.	TEST METHODOLOGY.....	6
	EUT CONFIGURATION.....	6
	EUT EXERCISE .....	6
	GENERAL TEST PROCEDURES .....	6
	DESCRIPTION OF TEST MODES .....	6
4.	INSTRUMENT CALIBRATION .....	7
5.	FACILITIES AND ACCREDITATIONS.....	7
	FACILITIES .....	7
	EQUIPMENT .....	7
6.	ANTENNA REQUIREMENTS .....	7
7.	MEASUREMENT UNCERTAINTY.....	8
8.	DESCRIPTION OF TESTS .....	9
9.	SUMMARY OF TEST RESULTS .....	24
10.	TEST RESULT .....	25
	10.1 PEAK POWER .....	25
	10.2 BAND EDGES.....	31
	10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW) .....	38
	10.4 NUMBER OF HOPPING FREQUENCY .....	46
	10.5 TIME OF OCCUPANCY (DWELL TIME).....	50
	10.6 SPURIOUS EMISSIONS.....	56
	10.6.1 CONDUCTED SPURIOUS EMISSIONS .....	56
	10.6.2 RADIATED SPURIOUS EMISSIONS .....	64
	10.6.3 RADIATED RESTRICTED BAND EDGES .....	70
	10.7 POWERLINE CONDUCTED EMISSIONS.....	73
11	LIST OF TEST EQUIPMENT .....	77
12	ANNEX A_ TEST SETUP PHOTO.....	79

## 1. EUT DESCRIPTION

Model	SM-J610G/DS
Additional Model	SM-J610G, SM-J415G/DS, SM-J415G
EUT Type	Mobile Phone
Power Supply	DC 3.80 V
Battery Information	Model: EB-BG610ABE Type: Li-ion Battery
Travel Adapter Information	Model : ETA0U84IWE Manufacture: SAMSUNG
Frequency Range	2402 MHz - 2480 MHz
Max. RF Output Power	11.772 dBm (15.038 mW)
BT Operating Mode	Normal, EDR, AFH
Modulation Type	GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)
Modulation Technique	FHSS
Number of Channels	79Channels, Minimum 20 Channels(AFH)
Antenna Specification	Antenna type: LDS / PIFA (Planar Inverted F Antenna) Peak Gain : -0.51 dBi
Date(s) of Tests	August 10, 2018~ September 04, 2018

## **2. REQUIREMENTS FOR BLUETOOTH TRANSMITTER(15.247)**

This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:

- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.
  - 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
  - 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### **3. TEST METHODOLOGY**

FCC KDB 558074 D01 15.247 Meas Guidance v05 dated August 24, 2018 entitled "guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices'.

#### **EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **EUT EXERCISE**

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### **GENERAL TEST PROCEDURES**

#### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the analyzer was set to peak detector with a reduced VBW setting(RBW = 1 MHz, VBW = 1/T Hz, where T = Pulse width).

#### **Conducted Antenna Terminal**

See Section from 7.8.2 to 7.8.8.(ANSI 63.10-2013)

### **DESCRIPTION OF TEST MODES**

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

## 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. FACILITIES AND ACCREDITATIONS

### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

\* The antennas of this E.U.T are permanently attached.

\* The E.U.T Complies with the requirement of §15.203

## 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71



## 8. DESCRIPTION OF TESTS


### 8.1. Conducted Maximum Peak Output Power

#### Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 W. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 W.
2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.5 in ANSI 63.10-2013)

- 1) Span: approximately 5 times the 20 dB bandwidth, centered on a hopping channel
- 2) RBW > the 20 dB bandwidth of the emission being measured
- 3) VBW ≥ RBW
- 4) Sweep = Auto
- 5) Detector = Peak
- 6) Trace = Max hold

#### Sample Calculation


$$\begin{aligned}\text{Output Power} &= \text{Spectrum Reading Power} + \text{Power Splitter loss} + \text{Cable loss}(2 \text{ ea}) \\ &= 10 \text{ dBm} + 6 \text{ dB} + 1.5 \text{ dB} = 17.5 \text{ dBm}\end{aligned}$$

## 8.2. Conducted Band Edge(Out of Band Emissions)

### Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### Test Procedure

This test is performed with hopping off and hopping on.

The Spectrum Analyzer is set to (6.10.4 in ANSI 63.10-2013)


- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: Coupled.
- 5) RBW: 100 kHz
- 6) VBW: 300 kHz
- 7) Detector: Peak
- 8) Trace: Max hold

### 8.3. Frequency Separation & 20 dB Bandwidth

#### Limit

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Configuration



#### Test Procedure

The Channel Separation test is performed with hopping on.  
And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.2 in ANSI 63.10-2013)


- 1) Span: Wide enough to capture the peaks of two adjacent channels
- 2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3) VBW  $\geq$  RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.
- 8) Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

## 8.4. Number of Hopping Frequencies

### Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

### Test Configuration



### Test Procedure

The Bluetooth frequency hopping function of the EUT was enabled.

The Spectrum Analyzer is set to (7.8.3 in ANSI 63.10-2013)


- 1) Span: the frequency band of operation
- 2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3) VBW  $\geq$  RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) Allow the trace to stabilize.

## 8.5. Time of Occupancy

### Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### Test Procedure

This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.4 in ANSI 63.10-2013)

- 1) Span: Zero span, centered on a hopping channel
- 2) RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
- 3) Sweep = as necessary to capture the entire dwell time per hopping channel
- 4) Detector: Peak
- 5) Trace: Max hold

The marker-delta function was used to determine the dwell time.

### Sample Calculation

The following calculation process is not relevant to our measurement results. It is just an example.

#### \* Mon-AFH Mode

- DH 5 (GFSK) :  $2.890 * (1600/6)/79 * 31.6 = 308.27$  (ms)
- 2-DH 5 ( $\pi/4$ DQPSK) :  $2.890 * (1600/6)/79 * 31.6 = 308.27$  (ms)
- 3-DH 5 (8DPSK) :  $2.890 * (1600/6)/79 * 31.6 = 308.27$  (ms)

#### \* AFH Mode

- DH 5 (GFSK) :  $2.890 * (800/6)/20 * 8.0 = 154.13$  (ms)
- 2-DH 5 ( $\pi/4$ DQPSK) :  $2.890 * (800/6)/20 * 8.0 = 154.13$  (ms)
- 3-DH 5 (8DPSK) :  $2.890 * (800/6)/20 * 8.0 = 154.13$  (ms)

#### Note :

DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving.

Then the system makes worst case 1600/6 hops per second with 79 channels. So the system have each channel 3.3755 times per second and so for 31.6 seconds the system have 106.667 times of appearance.

Each tx-time per appearance of DH5 is 2.890 ms.


Dwell time = Tx-time \* 106.667 = 308.27 (ms)

## 8.6. Conducted Spurious Emissions

### Limit

Conducted > 20 dBc

### Test Configuration



### Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer.

The Spectrum Analyzer is set to (7.8.8 in ANSI 63.10-2013)

- 1) Span: 30 MHz to 10 times the operating frequency in GHz.
- 2) RBW: 100 kHz
- 3) VBW: 300 kHz
- 4) Sweep: Coupled
- 5) Detector: Peak

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

This test is performed with hopping off.

**Factors for frequency**

Freq(MHz)	Factor(dB)
30	7.18
100	6.35
200	7.04
300	6.58
400	6.26
500	5.95
600	6.17
700	6.34
800	6.72
900	7.08
1000	7.38
2000	7.21
2400*	7.40
2500*	7.44
3000	7.88
4000	8.95
5000	9.57
6000	6.68
7000	9.99
8000	8.34
9000	9.61
10000	10.47
11000	8.96
12000	9.73
13000	8.84
14000	9.50
15000	11.54
16000	8.14
17000	11.73
18000	9.71
19000	10.40
20000	11.69
21000	10.72
22000	12.31
23000	9.85
24000	12.52
25000	11.07
26000	10.50

Note : 1. '\*' is fundamental frequency range.

2. Factor = Cable loss + Splitter loss




**8.7. Radiated Test**

**Limit**


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**Test Configuration**


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



### **Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log(\text{test distance} / \text{specific distance})$  (dB)
7. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
8. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
9. The unit was tested with its standard battery.
10. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot \text{RBW}$
  - (2) Measurement Type(Average):
    - We performed using a reduced video BW method was done with the analyzer in linear mode
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in secondsThe actual setting value of VBW = 1 kHz
11. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

### **Test Procedure of Radiated Restricted Band Edge**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log(\text{test distance} / \text{specific distance})$  (dB)
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting

(1) Measurement Type(Peak):

- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \cdot \text{RBW}$

(2) Measurement Type(Average):

- We performed using a reduced video BW method was done with the analyzer in linear mode
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds

The actual setting value of VBW = 1 kHz

10. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)  
+ Duty Cycle Correction Factor

11. Duty Cycle Correction Factor (79 channel hopping)

- a. Time to cycle through all channels=  $\Delta t = \tau$  [ms] x 79 channels = 229.100 ms, where  $\tau$  = pulse width
- b.  $100 \text{ ms} / \Delta t$  [ms] =  $H \rightarrow$  Round up to next highest integer,  $H' = 1$
- c. Worst Case Dwell Time =  $\tau$  [ms] x  $H' = 2.90$  ms
- d. Duty Cycle Correction =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -30.752 dB

12. Duty Cycle Correction Factor(AFH mode – minimum channel number case - 20 channels)

- a. Time to cycle through all channels=  $\Delta t = \tau$  [ms] x 20 channels = 58.00 ms, where  $\tau$  = pulse width
- b.  $100 \text{ ms} / \Delta t$  [ms] =  $H \rightarrow$  Round up to next highest integer,  $H' = 2$
- c. Worst Case Dwell Time =  $\tau$  [ms] x  $H' = 5.800$  ms
- d. Duty Cycle Correction(AFH) =  $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$  dB = -24.7314 dB

### 8.8. AC Power line Conducted Emissions

#### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

\*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

#### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

#### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.
5. The EUT is the device operating below 30 MHz.
  - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
  - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

#### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

## **8.9. Worst case configuration and mode**

### **Radiated test**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone, Stand alone + external accessories(earphone, etc)
  - Worstcase : Stand alone
2. EUT Axis
  - Radiated Spurious Emissions : Z
  - Radiated Restricted Band Edge : X
3. We applied DCCF in the test result which hopping channel number is 20.
4. All data rate of operation were investigated and the test results are worst case in highest datarate of each mode.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
5. SM-J610G/DS & Additional Models were tested and the worst case results are reported.  
(Worst case : SM-J610G/DS)

### **AC Power line Conducted Emissions**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone+Earphone+Travel Adapter, Stand alone+Travel Adapter
  - Worstcase : Stand alone+Travel Adapter
2. SM-J610G/DS & Additional Models were tested and the worst case results are reported.  
(Worst case : SM-J610G/DS)

### **Conducted test**

1. The EUT was configured with data rate of highest power.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
2. SM-J610G/DS & Additional Models were tested and the worst case results are reported.  
(Worst case : SM-J610G/DS)

## 9. SUMMARY OF TEST RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§15.247(a)(1)	N/A	Conducted	PASS
Occupied Bandwidth	N/A	N/A		N/A
Conducted Maximum Peak Output Power	§15.247(b)(1)	< 0.125 W		PASS
Carrier Frequency Separation	§15.247(a)(1)	> 25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	§15.247(a)(1)(iii)	≥ 15		PASS
Time of Occupancy	§15.247(a)(1)(iii)	< 400 ms		PASS
Conducted Spurious Emissions	§15.247(d)	> 20 dB for all out-of band emissions		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	> 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	§15.207(a)	cf. Section 8.8		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 8.7		Radiated
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.7	PASS	



## 10. TEST RESULT

### 10.1 PEAK POWER

Channel	Frequency (MHz)	Output Power (GFSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	10.226	10.53	125
Mid	2441	10.397	10.96	
High	2480	9.083	8.10	

Channel	Frequency (MHz)	Output Power (8DPSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	11.610	14.49	125
Mid	2441	11.772	15.04	
High	2480	10.496	11.21	

Channel	Frequency (MHz)	Output Power ( $\pi/4$ DQPSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	11.232	13.28	125
Mid	2441	11.383	13.75	
High	2480	10.083	10.19	

**Note:**

1. Spectrum reading values are not plot data.


The power results in plot is already including the actual values of loss for the splitter and cable combination.

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.


Actual value of loss for the splitter and cable combination is 7.36 dB at 2402 MHz and is 7.44 dB at 2480 MHz.

So, 7.4 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result.


Test Plots (GFSK)  
Peak Power (CH.0)




Test Plots (GFSK)  
Peak Power (CH.39)



Test Plots (GFSK)  
Peak Power (CH.78)




Test Plots (8DPSK)  
Peak Power (CH.0)




Test Plots (8DPSK)

Peak Power (CH.39)




Test Plots (8DPSK)

Peak Power (CH.78)




Test Plots ( $\pi/4$ DQPSK)

Peak Power (CH.0)




Test Plots ( $\pi/4$ DQPSK)

Peak Power (CH.39)



Test Plots ( $\pi/4$ DQPSK)

Peak Power (CH.78)



## 10.2 BAND EDGES

### Without hopping

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	57.085	43.730	43.575	20
Upper	61.687	55.349	56.033	

### With hopping

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	56.139	46.149	44.988	20
Upper	66.397	55.959	55.792	

### Note :

1. Spectrum reading values are not plot data.


The power results in plot is already including the actual values of loss for the splitter and cable combination.

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.


Actual value of loss for the splitter and cable combination is 7.36 dB at 2402 MHz and is 7.44 dB at 2480 MHz.

So, 7.4 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result.

Test Plots without hopping (GFSK)  
Band Edges (CH.0)



Test Plots without hopping (GFSK)  
Band Edges (CH.78)






Test Plots without hopping (8DPSK)  
Band Edges (CH.0)



Test Plots without hopping (8DPSK)  
Band Edges (CH.78)




Test Plots without hopping ( $\pi/4$ DQPSK)  
Band Edges (CH.0)




Test Plots without hopping ( $\pi/4$ DQPSK)  
Band Edges (CH.78)




Test Plots with hopping (GFSK)  
Band Edges (CH.0)




Test Plots with hopping (GFSK)  
Band Edges (CH.78)



Test Plots with hopping (8DPSK)  
Band Edges (CH.0)




Test Plots with hopping (8DPSK)  
Band Edges (CH.78)



Test Plots with hopping ( $\pi/4$ DQPSK)  
Band Edges (CH.0)



Test Plots with hopping ( $\pi/4$ DQPSK)  
Band Edges (CH.78)



### 10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

99% BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
CH.0	901.85	1174.5	1174.2
CH.39	905.92	1171.5	1171.3
CH.78	901.59	1174.9	1173.6


20dB BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
CH.0	971.8	1303	1313
CH.39	1030	1296	1321
CH.78	1026	1306	1288

Channel Separation(kHz)			Limit (kHz)
GFSK	8DPSK	$\pi/4$ DQPSK	
1001	998	991	>25 kHz or >2/3 of the 20dB BW

Test Plots (GFSK)  
Channel Separation



Test Plots (8DPSK)  
Channel Separation




Test Plots ( $\pi/4$ DQPSK)  
Channel Separation






Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.0)




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.39)




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.78)




Test Plots (8DPSK)


20 dB Bandwidth & Occupied Bandwidth (CH.0)



Test Plots (8DPSK)  
20 dB Bandwidth & Occupied Bandwidth (CH.39)




Test Plots (8DPSK)  
20 dB Bandwidth & Occupied Bandwidth (CH.78)




Test Plots ( $\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.0)




Test Plots ( $\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.39)



Test Plots ( $\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.78)



## 10.4 NUMBER OF HOPPING FREQUENCY


Result (No. of CH)			Limit
GFSK	8DPSK	$\pi/4$ DQPSK	
79	79	79	>15

**Note :**

In case of AFH mode, minimum number of hopping channels is 20.

Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)




Test Plots (GFSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots (8DPSK)


Number of Channels (2.441 GHz - 2.4835 GHz)






Test Plots ( $\pi/4$ DQPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots ( $\pi/4$ DQPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




### 10.5 TIME OF OCCUPANCY (DWELL TIME)


	Channel	GFSK	8DPSK	$\pi/4$ DQPSK
Pulse Time (ms)	Low	2.890	2.890	2.885
	Mid	2.885	2.890	2.885
	High	2.885	2.890	2.885

	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)
Total of Dwell (ms)	Low	308.27	308.27	307.73	31.6	400
	Mid	307.73	308.27	307.73	31.6	
	High	307.73	308.27	307.73	31.6	


Test Plots (GFSK)  
Dwell Time (CH.0)




Test Plots (GFSK)  
Dwell Time (CH.39)



Test Plots (GFSK)  
Dwell Time (CH.78)




Test Plots (8DPSK)  
Dwell Time (CH.0)




Test Plots (8DPSK)

Dwell Time (CH.39)




Test Plots (8DPSK)

Dwell Time (CH.78)




Test Plots ( $\pi/4$ DQPSK)

Dwell Time (CH.0)




Test Plots ( $\pi/4$ DQPSK)

Dwell Time (CH.39)



Test Plots ( $\pi/4$ DQPSK)

Dwell Time (CH.78)



## **10.6 SPURIOUS EMISSIONS**


### **10.6.1 CONDUCTED SPURIOUS EMISSIONS**

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.




Test Plots (8DPSK)- 30 MHz - 1 GHz  
Spurious Emission (CH.39)




Test Plots (8DPSK)- 1 GHz – 3 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK)- 3 GHz - 5 GHz  
Spurious Emission (CH.39)




Test Plots (8DPSK)- 5 GHz - 7 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK)- 7 GHz - 9 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK)- 9 GHz - 11 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK) 11 GHz - 13 GHz  
Spurious Emission (CH.39)




Test Plots (8DPSK)- 13 GHz – 15 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK)- 15 GHz - 17 GHz  
Spurious Emission (CH.39)




Test Plots(8DPSK)- 17 GHz - 19 GHz  
Spurious Emission (CH.39)




Test Plots (8DPSK)- 19 GHz - 21 GHz  
Spurious Emission (CH.39)



Test Plots (8DPSK)- 21 GHz - 23 GHz  
Spurious Emission (CH.39)



Test Plots (8DPSK)- 23 GHz - 25 GHz  
Spurious Emission (CH.39)



### 10.6.2 RADIATED SPURIOUS EMISSIONS

#### Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

**Note:**

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor =  $40 \cdot \log(\text{specific distance} / \text{test distance})$  (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.
5. The test results for below 30 MHz is correlated to an open site.  
The result on OATS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

#### Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

**Note:**

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
2. Radiated test is performed with hopping off.



**Frequency Range : Above 1 GHz**

Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	51.85	2.07	V	53.92	73.98	20.06	PK
4804	40.07	2.07	V	42.14	53.98	11.84	AV
7206	50.20	9.57	V	59.77	73.98	14.21	PK
7206	36.49	9.57	V	46.06	53.98	7.92	AV
4804	52.17	2.07	H	54.24	73.98	19.74	PK
4804	39.28	2.07	H	41.35	53.98	12.63	AV
7206	50.24	9.57	H	59.81	73.98	14.17	PK
7206	36.60	9.57	H	46.17	53.98	7.81	AV

Operation Mode: CH Low(8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	51.40	2.07	V	53.47	73.98	20.51	PK
4804	38.64	2.07	V	40.71	53.98	13.27	AV
7206	49.58	9.57	V	59.15	73.98	14.83	PK
7206	36.31	9.57	V	45.88	53.98	8.10	AV
4804	50.46	2.07	H	52.53	73.98	21.45	PK
4804	38.51	2.07	H	40.58	53.98	13.40	AV
7206	50.21	9.57	H	59.78	73.98	14.20	PK
7206	36.40	9.57	H	45.97	53.98	8.01	AV

Operation Mode: CH Low( $\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	51.38	2.07	V	53.45	73.98	20.53	PK
4804	38.45	2.07	V	40.52	53.98	13.46	AV
7206	49.89	9.57	V	59.46	73.98	14.52	PK
7206	36.58	9.57	V	46.15	53.98	7.83	AV
4804	51.14	2.07	H	53.21	73.98	20.77	PK
4804	38.37	2.07	H	40.44	53.98	13.54	AV
7206	50.42	9.57	H	59.99	73.98	13.99	PK
7206	36.55	9.57	H	46.12	53.98	7.86	AV

Operation Mode: CH Mid(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	52.27	2.56	V	54.83	73.98	19.15	PK
4882	41.71	2.56	V	44.27	53.98	9.71	AV
7323	50.56	9.72	V	60.28	73.98	13.70	PK
7323	36.47	9.72	V	46.19	53.98	7.79	AV
4882	52.03	2.56	H	54.59	73.98	19.39	PK
4882	41.56	2.56	H	44.12	53.98	9.86	AV
7323	50.13	9.72	H	59.85	73.98	14.13	PK
7323	36.27	9.72	H	45.99	53.98	7.99	AV

Operation Mode: CH Mid(8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	51.69	2.56	V	54.25	73.98	19.73	PK
4882	39.44	2.56	V	42	53.98	11.98	AV
7323	50.46	9.72	V	60.18	73.98	13.80	PK
7323	36.37	9.72	V	46.09	53.98	7.89	AV
4882	51.32	2.56	H	53.88	73.98	20.10	PK
4882	39.26	2.56	H	41.82	53.98	12.16	AV
7323	50.25	9.72	H	59.97	73.98	14.01	PK
7323	36.25	9.72	H	45.97	53.98	8.01	AV

Operation Mode: CH Mid( $\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	52.12	2.56	V	54.68	73.98	19.30	PK
4882	39.38	2.56	V	41.94	53.98	12.04	AV
7323	50.24	9.72	V	59.96	73.98	14.02	PK
7323	36.33	9.72	V	46.05	53.98	7.93	AV
4882	51.58	2.56	H	54.14	73.98	19.84	PK
4882	39.80	2.56	H	42.36	53.98	11.62	AV
7323	49.97	9.72	H	59.69	73.98	14.29	PK
7323	36.21	9.72	H	45.93	53.98	8.05	AV

Operation Mode: CH High(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	52.41	2.66	V	55.07	73.98	18.91	PK
4960	41.69	2.66	V	44.35	53.98	9.63	AV
7440	50.89	10.20	V	61.09	73.98	12.89	PK
7440	36.78	10.20	V	46.98	53.98	7.00	AV
4960	52.12	2.66	H	54.78	73.98	19.20	PK
4960	41.53	2.66	H	44.19	53.98	9.79	AV
7440	50.37	10.20	H	60.57	73.98	13.41	PK
7440	35.86	10.20	H	46.06	53.98	7.92	AV

Operation Mode: CH High(8DPSK)


Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	52.08	2.66	V	54.74	73.98	19.24	PK
4960	39.49	2.66	V	42.15	53.98	11.83	AV
7440	50.13	10.20	V	60.33	73.98	13.65	PK
7440	35.82	10.20	V	46.02	53.98	7.96	AV
4960	51.58	2.66	H	54.24	73.98	19.74	PK
4960	39.40	2.66	H	42.06	53.98	11.92	AV
7440	49.48	10.20	H	59.68	73.98	14.30	PK
7440	35.76	10.20	H	45.96	53.98	8.02	AV

Operation Mode: CH High( $\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	51.78	2.66	V	54.44	73.98	19.54	PK
4960	39.57	2.66	V	42.23	53.98	11.75	AV
7440	50.25	10.20	V	60.45	73.98	13.53	PK
7440	35.85	10.20	V	46.05	53.98	7.93	AV
4960	51.70	2.66	H	54.36	73.98	19.62	PK
4960	39.43	2.66	H	42.09	53.98	11.89	AV
7440	49.96	10.20	H	60.16	73.98	13.82	PK
7440	35.81	10.20	H	46.01	53.98	7.97	AV


**RESULT PLOTS (Worst case : Z)**

Radiated Spurious Emissions plot – Average Reading (GFSK, Ch.0 3rd Harmonic, Z-H)




Date: 28.JUN.2003 10:26:09

Radiated Spurious Emissions plot – Peak Reading (GFSK, Ch.0 3rd Harmonic, Z-H)




Date: 28.JUN.2003 10:26:36

Radiated Spurious Emissions plot – Average Reading (GFSK, Ch.78 2nd Harmonic, Z-V)



Date: 28.JUN.2003 10:19:48

Radiated Spurious Emissions plot – Peak Reading (GFSK, Ch.78 2nd Harmonic, Z-V)



Date: 28.JUN.2003 10:20:18

**Note:**

Plot of worst case are only reported.

### 10.6.3 RADIATED RESTRICTED BAND EDGES

Operation Mode Normal(GFSK)  
 Operating Frequency 2402 MHz, 2480 MHz  
 Channel No CH 0, CH 78

Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	24.58	35.36	H	0	59.94	73.98	14.04	PK
2390.0	11.40	35.36	H	-24.73	22.03	53.98	31.95	AV
2390.0	24.43	35.36	V	0	59.79	73.98	14.19	PK
2390.0	11.41	35.36	V	-24.73	22.04	53.98	31.94	AV
2483.5	29.27	35.73	H	0	65.00	73.98	8.98	PK
2483.5	25.19	35.73	H	-24.73	36.19	53.98	17.79	AV
2483.5	28.39	35.73	V	0	64.12	73.98	9.86	PK
2483.5	24.51	35.73	V	-24.73	35.51	53.98	18.47	AV

Operation Mode EDR(8DPSK)  
 Operating Frequency 2402 MHz, 2480 MHz  
 Channel No CH 0, CH 78


Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	24.31	35.36	H	0	59.67	73.98	14.31	PK
2390.0	11.42	35.36	H	-24.73	22.05	53.98	31.93	AV
2390.0	24.28	35.36	V	0	59.64	73.98	14.34	PK
2390.0	11.39	35.36	V	-24.73	22.02	53.98	31.96	AV
2483.5	29.72	35.73	H	0	65.45	73.98	8.53	PK
2483.5	24.14	35.73	H	-24.73	35.14	53.98	18.84	AV
2483.5	28.94	35.73	V	0	64.67	73.98	9.31	PK
2483.5	23.55	35.73	V	-24.73	34.55	53.98	19.43	AV

Operation Mode	EDR( $\pi/4$ DQPSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	24.38	35.36	H	0	59.74	73.98	14.24	PK
2390.0	11.39	35.36	H	-24.73	22.02	53.98	31.96	AV
2390.0	24.32	35.36	V	0	59.68	73.98	14.30	PK
2390.0	11.32	35.36	V	-24.73	21.95	53.98	32.03	AV
2483.5	29.52	35.73	H	0	65.25	73.98	8.73	PK
2483.5	24.10	35.73	H	-24.73	35.10	53.98	18.88	AV
2483.5	29.05	35.73	V	0	64.78	73.98	9.20	PK
2483.5	23.49	35.73	V	-24.73	34.49	53.98	19.49	AV


**RESULT PLOTS (Worst case : X-H)**

Radiated Restricted Band Edges plot – Average Reading (GFSK, Ch.78)



Date: 28.JUN.2003 08:02:29

Radiated Restricted Band Edges plot – Peak Reading (GFSK, Ch.78)



Date: 28.JUN.2003 08:03:15

**Note:**

Plot of worst case are only reported.



## 10.7 POWERLINE CONDUCTED EMISSIONS

### Conducted Emissions (Line 1)

BT\_N


1 / 2

# HCT TEST Report

### Common Information

EUT: SM-J610F/DS  
 Manufacturer: SAMSUNG  
 Test Site: SHIELD ROOM  
 Operating Conditions: BT\_N

FCC CLASS B\_Exten Cable



— FCC CLASS B\_OP      — FCC CLASS B\_AV      — Preview Result 1-PK+  
— Preview Result 2-AVG      X Final Result 1-QPK      X Final Result 2-CAV

### Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.180000	31.9	9.000	Off	N	9.7	32.6	64.5
0.862000	34.6	9.000	Off	N	9.8	21.4	56.0
0.868000	34.0	9.000	Off	N	9.8	22.0	56.0
0.876000	32.4	9.000	Off	N	9.8	23.6	56.0
0.880000	32.6	9.000	Off	N	9.8	23.4	56.0
0.888000	34.0	9.000	Off	N	9.8	22.0	56.0
1.016000	34.3	9.000	Off	N	9.8	21.7	56.0
1.122000	35.4	9.000	Off	N	9.8	20.6	56.0
1.158000	35.4	9.000	Off	N	9.8	20.6	56.0
1.242000	35.0	9.000	Off	N	9.8	21.0	56.0
1.484000	35.3	9.000	Off	N	9.9	20.7	56.0
2.468000	32.2	9.000	Off	N	9.9	23.8	56.0
17.506000	27.5	9.000	Off	N	10.6	32.5	60.0
17.512000	25.9	9.000	Off	N	10.6	34.1	60.0
18.432000	26.9	9.000	Off	N	10.6	33.1	60.0
18.436000	27.5	9.000	Off	N	10.6	32.5	60.0
18.932000	25.4	9.000	Off	N	10.6	34.6	60.0
18.984000	22.3	9.000	Off	N	10.6	37.7	60.0

2018-08-16

오전 9:43:18

BT\_N

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.176000	18.4	9.000	Off	N	9.7	36.3	54.7
0.180000	18.9	9.000	Off	N	9.7	35.6	54.5
0.858000	24.9	9.000	Off	N	9.8	21.1	46.0
0.862000	25.0	9.000	Off	N	9.8	21.0	46.0
0.866000	24.5	9.000	Off	N	9.8	21.5	46.0
0.870000	23.5	9.000	Off	N	9.8	22.5	46.0
1.122000	29.3	9.000	Off	N	9.8	16.7	46.0
1.158000	29.2	9.000	Off	N	9.8	16.8	46.0
1.242000	28.7	9.000	Off	N	9.8	17.3	46.0
1.296000	29.1	9.000	Off	N	9.8	16.9	46.0
1.300000	29.0	9.000	Off	N	9.8	17.0	46.0
1.484000	28.3	9.000	Off	N	9.9	17.7	46.0
17.214000	14.4	9.000	Off	N	10.6	35.6	50.0
17.510000	17.2	9.000	Off	N	10.6	32.8	50.0
17.872000	19.0	9.000	Off	N	10.6	31.0	50.0
18.068000	17.4	9.000	Off	N	10.6	32.6	50.0
18.432000	15.7	9.000	Off	N	10.6	34.3	50.0
18.984000	13.1	9.000	Off	N	10.6	36.9	50.0

2018-08-16

오전 9:43:18

**Conducted Emissions (Line 2)**

BT\_L1


1 / 2

**HCT TEST Report**

**Common Information**

EUT: SM-J610F/DS  
 Manufacturer: SAMSUNG  
 Test Site: SHIELD ROOM  
 Operating Conditions: BT\_L1

FCC CLASS B\_Exten Cable



— FCC CLASS B\_OP      — FCC CLASS B\_AV      — Preview Result 1-PK+  
— Preview Result 2-AVG      X Final Result 1-QPK      X Final Result 2-CAV

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.532000	37.8	9.000	Off	L1	9.8	18.2	56.0
0.812000	34.9	9.000	Off	L1	9.7	21.1	56.0
0.826000	36.1	9.000	Off	L1	9.7	19.9	56.0
0.848000	33.9	9.000	Off	L1	9.8	22.1	56.0
0.852000	34.2	9.000	Off	L1	9.8	21.8	56.0
0.872000	37.3	9.000	Off	L1	9.8	18.7	56.0
1.070000	39.6	9.000	Off	L1	9.8	16.4	56.0
1.076000	38.8	9.000	Off	L1	9.8	17.2	56.0
1.140000	37.7	9.000	Off	L1	9.8	18.3	56.0
1.348000	38.0	9.000	Off	L1	9.8	18.0	56.0
1.422000	37.5	9.000	Off	L1	9.9	18.5	56.0
1.482000	38.0	9.000	Off	L1	9.9	18.0	56.0
5.140000	26.7	9.000	Off	L1	10.0	33.3	60.0
6.486000	26.9	9.000	Off	L1	10.1	33.1	60.0
16.944000	29.9	9.000	Off	L1	10.3	30.1	60.0
18.364000	32.6	9.000	Off	L1	10.4	27.4	60.0
18.434000	32.7	9.000	Off	L1	10.4	27.3	60.0
18.736000	29.9	9.000	Off	L1	10.4	30.1	60.0

2018-08-16

오전 9:53:23

BT\_L1

2 / 2

**Final Result 2**

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.532000	25.4	9.000	Off	L1	9.8	20.6	46.0
0.768000	26.3	9.000	Off	L1	9.7	19.7	46.0
0.826000	26.4	9.000	Off	L1	9.7	19.6	46.0
0.868000	25.8	9.000	Off	L1	9.8	20.2	46.0
0.872000	25.7	9.000	Off	L1	9.8	20.3	46.0
0.876000	25.8	9.000	Off	L1	9.8	20.2	46.0
1.006000	29.0	9.000	Off	L1	9.8	17.0	46.0
1.070000	30.5	9.000	Off	L1	9.8	15.5	46.0
1.140000	30.4	9.000	Off	L1	9.8	15.6	46.0
1.348000	29.5	9.000	Off	L1	9.8	16.5	46.0
1.422000	29.4	9.000	Off	L1	9.9	16.6	46.0
1.482000	29.6	9.000	Off	L1	9.9	16.4	46.0
8.592000	18.1	9.000	Off	L1	10.1	31.9	50.0
16.944000	17.6	9.000	Off	L1	10.3	32.4	50.0
18.434000	18.2	9.000	Off	L1	10.4	31.8	50.0
18.440000	17.2	9.000	Off	L1	10.4	32.8	50.0
18.736000	16.6	9.000	Off	L1	10.4	33.4	50.0
19.002000	17.0	9.000	Off	L1	10.4	33.0	50.0

2018-08-16

오전 9:53:23

## 11 LIST OF TEST EQUIPMENT

### Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/20/2017	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/27/2018	Annual	100033
ESPACE	SU-642 / Temperature Chamber	03/30/2018	Annual	0093008124
Agilent	N9020A / Signal Analyzer	06/08/2018	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	11/22/2017	Annual	MY49431210
Agilent	N1911A / Power Meter	04/16/2018	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/16/2018	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/20/2017	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/07/2018	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/26/2018	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/10/2018	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/17/2018	Annual	100422

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

**Radiated Test**

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	04/19/2017	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	04/06/2017	Biennial	760
Schwarzbeck	BBHA 9120D / Horn Antenna	05/02/2017	Biennial	9120D-937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	12/04/2017	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/06/2017	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/27/2017	Annual	101068-SZ
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/07/2018	Annual	8
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/09/2018	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/29/2018	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2018	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/07/2018	Annual	1
Agilent	8493C-10 / Attenuator(10 dB)	07/17/2018	Annual	08285
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/10/2018	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/29/2018	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/27/2018	Annual	3000C000276

**Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

## 12 ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1809-FC020-P
2	HCT-RF-1809-FC021-P
3	HCT-RF-1809-FC022-P
4	HCT-RF-1809-FC023-P