

FCC LTE REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:

June 29, 2017

Location:

HCT CO., LTD.,

74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-R-1706-F091

HCT FRN: 0005866421

FCC ID: A3LSMJ701M

APPLICANT: SAMSUNG Electronics Co., Ltd.

According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID: A3LSMJ701F report.

FCC Model(s): SM-J701M/DS
Additional FCC Model(s): SM-J701M
EUT Type: Mobile Phone
FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band7 (5)	2502.5 – 2567.5	4M53G7D	QPSK	0.226	23.54
		4M53W7D	16QAM	0.147	21.66
LTE – Band7 (10)	2505.0 – 2565.0	9M00G7D	QPSK	0.225	23.52
		9M01W7D	16QAM	0.146	21.63
LTE – Band7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.224	23.51
		13M5W7D	16QAM	0.145	21.61
LTE – Band7 (20)	2510.0 – 2560.0	17M9G7D	QPSK	0.222	23.47
		17M9W7D	16QAM	0.144	21.58

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



Report prepared by : Jeong Ho Kim
Engineer of Telecommunication Testing Center



Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1706-F091	June 29, 2017	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	6
3.2 OCCUPIED BANDWIDTH.	7
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	8
3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	9
4. LIST OF TEST EQUIPMENT	10
5. MEASUREMENT UNCERTAINTY	11
6. SUMMARY OF TEST RESULTS	12
7. SAMPLE CALCULATION	13
8. TEST DATA	14
8.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 7)	14
8.2 RADIATED SPURIOUS EMISSIONS	16
8.2.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)	16
8.2.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)	17
8.2.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)	18
8.2.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)	19
8.3 OCCUPIED BANDWIDTH	20
8.4 CONDUCTED SPURIOUS EMISSIONS	21
8.4.1 CHANNEL EDGE	22
8.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	23
8.5.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)	23
8.5.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)	24
8.5.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)	25
8.5.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)	26
9. TEST PLOTS.....	27

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: SAMSUNG Electronics Co., Ltd.

Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

FCC ID: A3LSMJ701M

Application Type: Certification

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §2 , §27

EUT Type: Mobile Phone

FCC Model(s): SM-J701M/DS

Additional FCC Model(s): SM-J701M

Tx Frequency: 2502.5 MHz – 2567.5 MHz (LTE – Band 7): 5 MHz
2505.0 MHz – 2565.0 MHz (LTE – Band 7): 10 MHz
2507.5 MHz – 2562.5 MHz (LTE – Band 7): 15 MHz
2510.0 MHz – 2560.0 MHz (LTE – Band 7): 20 MHz

Max. RF Output Power:

Band 7 (5 MHz) :	0.226 W (QPSK) (23.54 dBm) 0.147 W (16-QAM) (21.66 dBm)
Band 7 (10 MHz) :	0.225 W (QPSK) (23.52 dBm) 0.146 W (16-QAM) (21.63 dBm)
Band 7 (15 MHz) :	0.224 W (QPSK) (23.51 dBm) 0.145 W (16-QAM) (21.61 dBm)
Band 7 (20 MHz) :	0.222 W (QPSK) (23.47 dBm) 0.144 W (16-QAM) (21.58 dBm)

Emission Designator(s):

Band 7 (5 MHz) :	4M53G7D (QPSK) / 4M53W7D (16-QAM)
Band 7 (10 MHz) :	9M00G7D (QPSK) / 9M01W7D (16-QAM)
Band 7 (15 MHz) :	13M5G7D (QPSK) / 13M5W7D (16-QAM)
Band 7 (20 MHz) :	17M9G7D (QPSK) / 17M9W7D (16-QAM)

Date(s) of Tests: June 11, 2017 ~ June 16, 2017

2. INTRODUCTION

2.1. EUT DESCRIPTION

The SAMSUNG Electronics Co., Ltd. SM-J701M/DS Mobile Phone consists of LTE 7.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: EIRP(Equivalent Isotropic Radiated Power)

Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

1. Frequency Range : 9 kHz ~ 10th Harmonics of highest channel fundamental frequency.
2. Measured distance : 30 MHz ~ 11 GHz at 3 m
11 GHz ~ 26 GHz at 1m
3. The EUT was setup to maximum output power. The 100 kHz RBW was used to scan from 30 MHz to 1 GHz. Also, the 1 MHz RBW was used to scan from 1 GHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

3.2 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2.

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.


The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

- Channel Edge Requirement : In the 1 MHz bands immediately outside and adjacent to the channel, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block .

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/24/2017	Annual	04/24/2018
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/10/2017	Annual	04/10/2018
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/10/2017	Annual	04/10/2018
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/04/2017	Annual	05/04/2018
Agilent	E3632A/DC Power Supply	KR75303243	07/12/2016	Annual	07/12/2017
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	0093008124	03/31/2017	Annual	03/31/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/09/2016	Biennial	09/09/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	1298	10/14/2016	Biennial	10/14/2018
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/01/2017	Annual	06/01/2018
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/22/2017	Annual	06/22/2018
REOHDE & SCHWARZ	FSV40-N/Spectrum Analyzer	101068-SZ	09/23/2016	Annual	09/23/2017
Agilent	8960 (E5515C)/ Base Station	MY48360800	10/19/2016	Annual	10/19/2017
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/06/2017	Biennial	04/06/2019
Schwarzbeck	VULB9160/ Bilog Antenna	3150	09/30/2016	Biennial	09/30/2018
Schwarzbeck	VULB9160/ Bilog Antenna	3368	10/14/2016	Biennial	10/14/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	02/15/2017	Annual	02/15/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	02/13/2017	Annual	02/13/2018
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/18/2016	Annual	07/18/2017

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

6. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(m)(4)	Band Edge / Conducted Spurious Emissions.	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS
2.1046	* Conducted Output Power	N/A		PASS
2.1055, 27.54	Frequency stability	Emission must remain in band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(m)(4)	Undesirable Emissions	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS

*: See SAR Report

7. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured	Substitute	Ant. Gain	C.L	Pol.	Limit	EIRP	
	channel	Freq.(MHz)	Level(dBm)	LEVEL(dBm)	(dBi)			W	W	dBm
LTE Band7	21100	2,535.00	-22.63	13.30	10.98	2.38	V	< 2.00	0.155	21.90

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = main carrier modulated in a combination of two

or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 7)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2502.5	5 MHz	QPSK	-20.74	14.94	10.95	2.35	V	< 2.00	0.226	23.54
		16-QAM	-22.62	13.06	10.95	2.35	V		0.147	21.66
2535.0		QPSK	-21.23	14.70	10.98	2.38	V		0.214	23.30
		16-QAM	-23.03	12.90	10.98	2.38	V		0.141	21.50
2567.5		QPSK	-21.76	14.14	11.01	2.39	V		0.189	22.76
		16-QAM	-23.65	12.25	11.01	2.39	V		0.122	20.87

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2505.0	10 MHz	QPSK	-20.77	14.92	10.95	2.35	V	< 2.00	0.225	23.52
		16-QAM	-22.66	13.03	10.95	2.35	V		0.146	21.63
2535.0		QPSK	-21.23	14.70	10.98	2.38	V		0.214	23.30
		16-QAM	-23.06	12.87	10.98	2.38	V		0.140	21.47
2565.0		QPSK	-21.65	14.31	11.00	2.39	V		0.196	22.92
		16-QAM	-23.58	12.38	11.00	2.39	V		0.126	20.99

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2507.5	15 MHz	QPSK	-20.78	14.91	10.96	2.36	V	< 2.00	0.224	23.51
		16-QAM	-22.68	13.01	10.96	2.36	V		0.145	21.61
2535.0		QPSK	-21.29	14.64	10.98	2.38	V		0.211	23.24
		16-QAM	-23.19	12.74	10.98	2.38	V		0.136	21.34
2562.5		QPSK	-21.36	14.66	11.00	2.39	V		0.212	23.27
		16-QAM	-23.34	12.68	11.00	2.39	V		0.135	21.29

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2510.0	20 MHz	QPSK	-20.82	14.87	10.96	2.36	V	< 2.00	0.222	23.47
		16-QAM	-22.71	12.98	10.96	2.36	V		0.144	21.58
2535.0		QPSK	-21.28	14.65	10.98	2.38	V		0.211	23.25
		16-QAM	-23.29	12.64	10.98	2.38	V		0.133	21.24
2560.0		QPSK	-21.63	14.45	11.00	2.39	V		0.202	23.06
		16-QAM	-23.57	12.51	11.00	2.39	V		0.129	21.12

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For 5 MHz, 10MHz BW signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A Horn antenna was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is z plane in LTE mode. Also worst case of detecting Antenna is vertical polarization in LTE mode.

8.2 RADIATED SPURIOUS EMISSIONS

8.2.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2502.50 MHz
- MEASURED OUTPUT POWER: 23.54 dBm = 0.226 W
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 48.54 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20775 (2502.5)	5,005.00	-61.65	12.57	-75.69	3.40	V	-66.52	90.06
	7,507.50	-47.37	11.71	-55.75	4.18	V	-48.22	71.76
	10,010.00	-50.34	11.01	-54.18	5.02	V	-48.19	71.73
	12,512.50	-52.41	14.04	-57.98	5.71	V	-49.65	73.19
	15,015.00	-53.11	13.36	-55.31	6.29	V	-48.24	71.78
21100 (2535.0)	5,070.00	-59.84	12.67	-73.38	3.43	V	-64.14	87.68
	7,605.00	-49.19	11.64	-58.14	4.29	V	-50.79	74.33
	10,140.00	-52.34	10.94	-56.53	4.99	V	-50.58	74.12
	12,675.00	-54.02	13.85	-58.85	5.73	H	-50.73	74.27
	15,210.00	-56.90	14.41	-61.40	6.26	V	-53.25	76.79
21425 (2567.5)	5,135.00	-60.32	12.75	-71.85	3.44	H	-62.54	86.08
	7,702.50	-48.26	11.56	-57.04	4.27	V	-49.75	73.29
	10,270.00	-50.94	10.87	-56.24	4.98	V	-50.35	73.89
	12,837.50	-53.71	13.66	-58.71	5.75	V	-50.80	74.34
	15,405.00	-57.87	15.46	-62.08	6.39	V	-53.01	76.55

- NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2505.00 MHz
- MEASURED OUTPUT POWER: 23.52 dBm = 0.225 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 48.52 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20800 (2505.0)	5,010.00	-63.55	12.58	-77.22	3.40	V	-68.04	91.56
	7,515.00	-47.76	11.70	-56.14	4.12	V	-48.56	72.08
	10,020.00	-50.47	11.01	-54.14	5.04	V	-48.17	71.69
	12,525.00	-50.39	14.02	-56.11	5.72	V	-47.81	71.33
	15,030.00	-53.33	13.44	-55.58	6.26	V	-48.40	71.92
21100 (2535.0)	5,070.00	-63.59	12.67	-77.13	3.43	V	-67.89	91.41
	7,605.00	-47.09	11.64	-56.04	4.29	V	-48.69	72.21
	10,140.00	-52.04	10.94	-56.23	4.99	V	-50.28	73.80
	12,675.00	-51.16	13.85	-55.99	5.73	V	-47.87	71.39
	15,210.00	-56.74	14.41	-61.24	6.26	V	-53.09	76.61
21400 (2565.0)	5,130.00	-58.86	12.76	-70.31	3.44	V	-60.99	84.51
	7,695.00	-47.95	11.57	-56.59	4.26	V	-49.28	72.80
	10,260.00	-48.11	10.87	-53.23	5.00	V	-47.36	70.88
	12,825.00	-52.97	13.67	-58.17	5.74	V	-50.24	73.76
	15,390.00	-56.75	15.38	-60.83	6.36	V	-51.81	75.33

- NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2507.50 MHz
- MEASURED OUTPUT POWER: 23.51 dBm = 0.224 W
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 48.51 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20825 (2507.5)	5,015.00	-65.92	12.59	-78.55	3.40	V	-69.36	92.87
	7,522.50	-47.31	11.70	-55.53	4.09	V	-47.92	71.43
	10,030.00	-50.58	11.00	-54.33	5.16	V	-48.49	72.00
	12,537.50	-50.40	14.01	-56.29	5.69	V	-47.97	71.48
	15,045.00	-53.82	13.52	-56.28	6.21	V	-48.97	72.48
21100 (2535.0)	5,070.00	-62.65	12.67	-76.19	3.43	V	-66.95	90.46
	7,605.00	-47.11	11.64	-56.06	4.29	V	-48.71	72.22
	10,140.00	-52.57	10.94	-56.76	4.99	V	-50.81	74.32
	12,675.00	-50.31	13.85	-55.14	5.73	V	-47.02	70.53
	15,210.00	-58.06	14.41	-62.56	6.26	V	-54.41	77.92
21375 (2562.5)	5,125.00	-57.64	12.75	-69.34	3.44	V	-60.03	83.54
	7,687.50	-48.89	11.57	-57.36	4.26	V	-50.05	73.56
	10,250.00	-50.47	10.88	-55.02	5.04	V	-49.18	72.69
	12,812.50	-54.68	13.68	-59.73	5.71	V	-51.76	75.27
	15,375.00	-58.68	15.28	-62.97	6.32	V	-54.01	77.52

- NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2510.00 MHz
- MEASURED OUTPUT POWER: 23.47 dBm = 0.222 W
- MODULATION SIGNAL: 20 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 48.47 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20850 (2510.0)	5,020.00	-63.67	12.60	-76.28	3.40	V	-67.08	90.55
	7,530.00	-47.65	11.69	-55.65	4.08	V	-48.04	71.51
	10,040.00	-50.54	11.00	-55.39	5.20	V	-49.59	73.06
	12,550.00	-50.66	13.99	-56.17	5.65	V	-47.83	71.30
	15,060.00	-54.57	13.60	-57.20	6.21	V	-49.81	73.28
21100 (2535.0)	5,070.00	-62.24	12.67	-75.78	3.43	V	-66.54	90.01
	7,605.00	-51.21	11.64	-60.16	4.29	V	-52.81	76.28
	10,140.00	-54.54	10.94	-58.73	4.99	V	-52.78	76.25
	12,675.00	-50.63	13.85	-55.46	5.73	V	-47.34	70.81
	15,210.00	-58.74	14.41	-63.24	6.26	V	-55.09	78.56
21350 (2560.0)	5,120.00	-57.39	12.75	-69.37	3.44	V	-60.06	83.53
	7,680.00	-51.34	11.58	-59.66	4.26	V	-52.34	75.81
	10,240.00	-52.83	10.88	-57.15	5.06	V	-51.33	74.80
	12,800.00	-56.82	13.70	-61.67	5.68	V	-53.65	77.12
	15,360.00	-60.73	15.22	-64.76	6.29	V	-55.83	79.30

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.3 OCCUPIED BANDWIDTH

c	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
7	5 MHz	2535.0	QPSK	25	0	4.5280
			16-QAM	25	0	4.5341
	10 MHz		QPSK	50	0	8.9990
			16-QAM	50	0	9.0064
	15 MHz		QPSK	75	0	13.536
			16-QAM	75	0	13.489
	20 MHz		QPSK	100	0	17.927
			16-QAM	100	0	17.947

- Plots of the EUT's Occupied Bandwidth are shown Page 28 ~ 31.

8.4 CONDUCTED SPURIOUS EMISSIONS

■ FACTORS FOR FREQUENCY

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

NOTES:

Factor(dB) = Cable Loss + Attenuator + Power Splitter

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
7	5	2,502.5	26.4402	30.131	-76.219	-46.088	-25.00
		2,535.0	26.1448	30.131	-76.288	-46.157	
		2,567.5	26.0821	30.131	-76.378	-46.247	
	10	2,505.0	26.1341	30.131	-76.284	-46.153	
		2,535.0	26.1749	30.131	-76.310	-46.179	
		2,565.0	26.1155	30.131	-76.481	-46.350	
	15	2,507.5	25.8528	30.131	-76.118	-45.987	
		2,535.0	26.1419	30.131	-76.089	-45.958	
		2,562.5	26.1700	30.131	-76.475	-46.344	
	20	2,510.0	26.1683	30.131	-76.245	-46.114	
		2,535.0	26.1448	30.131	-76.427	-46.296	
		2,560.0	25.8573	30.131	-76.282	-46.151	

NOTES:

1. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)

- Plots of the EUT's Conducted Spurious Emissions are shown Page 40 ~ 51.

8.4.1 CHANNEL EDGE

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1MHz)		2 496 MHz ~ 2 499 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	2 490.5 MHz ~ 2 496 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Below 2 490.5 MHz	Above (C.E + X MHz)
			Lower	Upper	Lower	Upper	Lower	Upper	Lower	Upper
5MHz (QPSK)	2502.5	25 / 0	-18.03	-18.33	-13.65	-13.65	-23.05	-27.86	-42.44	-31.13
10MHz (QPSK)	2505.0	50 / 0	-23.24	-22.97	-20.78	-20.39	-24.91	-24.63	-35.08	-33.98
15MHz (QPSK)	2507.5	75 / 0	-21.37	-20.78	-18.43	-17.44	-21.59	-20.04	-27.67	-32.97
20MHz (QPSK)	2510.0	100 / 0	-22.60	-21.39	-19.94	-18.49	-22.18	-20.14	-27.57	-34.48
Limit			-10.0		-10.0		-13.0		-25.0	

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-18.34	-18.71	-13.77	-14.34
	2567.5	25 / 0	-16.75	-17.52	-12.09	-12.93
10MHz (QPSK)	2535.0	50 / 0	-23.45	-23.56	-20.78	-21.88
	2565.0	50 / 0	-22.09	-22.95	-18.86	-20.43
15MHz (QPSK)	2535.0	75 / 0	-20.77	-21.54	-17.77	-18.67
	2562.5	75 / 0	-19.60	-20.79	-16.23	-17.57
20MHz (QPSK)	2535.0	100 / 0	-21.81	-22.52	-18.92	-19.76
	2560.0	100 / 0	-20.87	-21.73	-17.92	-18.92
Limit			-10.0		-10.0	

Band Width (Modulation)	Frequency (MHz)	Resource Block Size	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-28.43	-29.08	-32.08	-32.70
	2567.5	25 / 0	-27.83	-29.05	-31.72	-32.84
10MHz (QPSK)	2535.0	50 / 0	-26.11	-26.47	-35.22	-35.65
	2565.0	50 / 0	-24.28	-25.79	-34.37	-36.21
15MHz (QPSK)	2535.0	75 / 0	-21.04	-21.48	-33.34	-33.92
	2562.5	75 / 0	-19.49	-21.13	-32.40	-36.37
20MHz (QPSK)	2535.0	100 / 0	-21.86	-22.18	-34.82	-35.65
	2560.0	100 / 0	-20.26	-21.63	-34.03	-43.18
Limit			-13.0		-25.0	

Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)

NOTES: Channel Edge was Tested QPSK Modulation and Full RB (Resource Block) Size


- Plots of the EUT's Band Edge are shown Page 32 ~ 39.

8.5 REQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

8.5.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 006	0.0	0.000 000	0.000
100%		-30	2535 000 000	-5.7	0.000 000	-0.002
100%		-20	2535 000 016	10.0	0.000 000	0.004
100%		-10	2535 000 000	-5.2	0.000 000	-0.002
100%		0	2534 999 998	-7.3	0.000 000	-0.003
100%		+10	2535 000 000	-5.8	0.000 000	-0.002
100%		+30	2534 999 998	-7.6	0.000 000	-0.003
100%		+40	2534 999 996	-9.1	0.000 000	-0.004
100%		+50	2535 000 001	-4.7	0.000 000	-0.002
Batt. Endpoint	3.60	+20	2535 000 011	5.8	0.000 000	0.002



8.5.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100%		-30	2535 000 000	-4.8	0.000 000	-0.002
100%		-20	2535 000 012	6.9	0.000 000	0.003
100%		-10	2535 000 002	-3.4	0.000 000	-0.001
100%		0	2535 000 011	6.2	0.000 000	0.002
100%		+10	2535 000 001	-4.4	0.000 000	-0.002
100%		+30	2535 000 011	5.8	0.000 000	0.002
100%		+40	2535 000 009	3.9	0.000 000	0.002
100%		+50	2535 000 010	4.4	0.000 000	0.002
Batt. Endpoint	3.60	+20	2535 000 015	9.4	0.000 000	0.004



8.5.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2534 999 991	0.0	0.000 000	0.000
100%		-30	2534 999 996	4.6	0.000 000	0.002
100%		-20	2534 999 995	3.6	0.000 000	0.001
100%		-10	2534 999 987	-3.9	0.000 000	-0.002
100%		0	2534 999 986	-5.5	0.000 000	-0.002
100%		+10	2534 999 986	-5.0	0.000 000	-0.002
100%		+30	2534 999 984	-7.1	0.000 000	-0.003
100%		+40	2534 999 984	-7.6	0.000 000	-0.003
100%		+50	2534 999 998	7.1	0.000 000	0.003
Batt. Endpoint	3.60	+20	2534 999 984	-7.5	0.000 000	-0.003



8.5.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)


- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2534 999 993	0.0	0.000 000	0.000
100%		-30	2534 999 997	3.8	0.000 000	0.001
100%		-20	2534 999 988	-5.2	0.000 000	-0.002
100%		-10	2535 000 000	6.3	0.000 000	0.002
100%		0	2534 999 984	-9.2	0.000 000	-0.004
100%		+10	2535 000 002	8.2	0.000 000	0.003
100%		+30	2534 999 997	3.4	0.000 000	0.001
100%		+40	2534 999 985	-8.0	0.000 000	-0.003
100%		+50	2535 000 001	7.3	0.000 000	0.003
Batt. Endpoint	3.60	+20	2535 000 000	6.1	0.000 000	0.002




9. TEST PLOTS


BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 16-QAM RB 25)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 16-QAM RB 50)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 16-QAM RB 75)



BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 QPSK RB 100)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 16-QAM RB 100)




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK RB25)-1




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK RB25)-2




BAND7. Mid Channel Edge Plot (5MHz Ch.21100 QPSK RB 25)



BAND7. High Channel Edge Plot (5MHz Ch.21425 QPSK RB 25)




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK RB50)-1




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK RB50)-2



BAND7. Mid Channel Edge Plot (10MHz Ch.21100 QPSK RB 50)



BAND7. High Channel Edge Plot (10MHz Ch.21400 QPSK RB 50)




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK RB75)-1




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK RB75)-2



BAND7. Mid Channel Edge Plot (15MHz Ch.21100 QPSK RB 75)



BAND7. High Channel Edge Plot (15MHz Ch.21375 QPSK RB 75)




BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK RB100)-1




BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK RB100)-2




BAND7. Mid Channel Edge Plot (20MHz Ch.21100 QPSK RB 100)




BAND7. High Channel Edge Plot (20MHz Ch.21350 QPSK RB 100)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21425 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.21425 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21400 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.20825 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.20850 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (20MHz Ch.20850 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 1 (20MHz Ch.21350 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21350 QPSK RB 1, Offset 0)

