



MEASUREMENT REPORT

LTE

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

2/16 - 4/6/2018

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1802160028-03.A3L

FCC ID:

A3LSMJ737P

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-J737P

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):


22, 24, & 27

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 1 of 158

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	5
1.1	Scope	5
1.2	PCTEST Test Location	5
1.3	Test Facility / Accreditations	5
2.0	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities	6
2.3	Test Configuration	6
2.4	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Measurement Procedure	7
3.2	Block A Frequency Range	7
3.3	Cellular - Base Frequency Blocks	7
3.4	Cellular - Mobile Frequency Blocks	7
3.5	PCS - Base Frequency Blocks	8
3.6	PCS - Mobile Frequency Blocks	8
3.7	AWS - Base Frequency Blocks	8
3.8	AWS - Mobile Frequency Blocks	8
3.9	BRS/EBS Frequency Block	9
3.10	Radiated Power and Radiated Spurious Emissions	10
4.0	MEASUREMENT UNCERTAINTY	11
5.0	TEST EQUIPMENT CALIBRATION DATA	12
6.0	SAMPLE CALCULATIONS	13
7.0	TEST RESULTS	14
7.1	Summary	14
7.2	Occupied Bandwidth	16
7.3	Spurious and Harmonic Emissions at Antenna Terminal	42
7.4	Band Edge Emissions at Antenna Terminal	68
7.5	Peak-Average Ratio	117
7.6	Additional Maximum Power Reduction (A-MPR)	124
7.7	Radiated Power (ERP/EIRP)	126
7.8	Radiated Spurious Emissions Measurements	134
7.9	Frequency Stability / Temperature Variation	147
8.0	CONCLUSION	158

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 2 of 158	



MEASUREMENT REPORT

FCC Part 22, 24, & 27



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)		
LTE Band 12	27	699.7 - 715.3	0.095	19.79	0.156	21.94	1M11G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.071	18.53	0.117	20.68	1M11W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.102	20.07	0.167	22.22	2M74G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.078	18.93	0.128	21.08	2M74W7D	16QAM
LTE Band 12	27	701.5 - 713.5	0.098	19.92	0.161	22.07	4M57G7D	QPSK
LTE Band 12	27	701.5 - 713.5	0.074	18.71	0.122	20.86	4M56W7D	16QAM
LTE Band 12	27	704 - 711	0.105	20.20	0.172	22.35	9M06G7D	QPSK
LTE Band 12	27	704 - 711	0.084	19.26	0.138	21.41	9M04W7D	16QAM
LTE Band 5/26	22H	824.7 - 848.3	0.115	20.62	0.189	22.77	1M10G7D	QPSK
LTE Band 5/26	22H	824.7 - 848.3	0.087	19.39	0.143	21.54	1M11W7D	16QAM
LTE Band 5/26	22H	825.5 - 847.5	0.111	20.46	0.182	22.61	2M74G7D	QPSK
LTE Band 5/26	22H	825.5 - 847.5	0.085	19.31	0.140	21.46	2M72W7D	16QAM
LTE Band 5/26	22H	826.5 - 846.5	0.112	20.51	0.185	22.66	4M57G7D	QPSK
LTE Band 5/26	22H	826.5 - 846.5	0.096	19.81	0.157	21.96	4M55W7D	16QAM
LTE Band 5/26	22H	829 - 844	0.122	20.85	0.200	23.00	9M06G7D	QPSK
LTE Band 5/26	22H	829 - 844	0.096	19.83	0.158	21.98	9M08W7D	16QAM
LTE Band 26	22H	831.5 - 841.5	0.105	20.21	0.172	22.36	13M5G7D	QPSK
LTE Band 26	22H	831.5 - 841.5	0.082	19.15	0.135	21.30	13M5W7D	16QAM

EUT Overview (<1GHz)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 3 of 158

Mode	FCC Rule Part	Tx Frequency (MHz)	EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)		
LTE Band 4	27	1710.7 - 1754.3	0.256	24.09	1M10G7D	QPSK
LTE Band 4	27	1710.7 - 1754.3	0.226	23.55	1M11W7D	16QAM
LTE Band 4	27	1711.5 - 1753.5	0.256	24.08	2M73G7D	QPSK
LTE Band 4	27	1711.5 - 1753.5	0.198	22.97	2M73W7D	16QAM
LTE Band 4	27	1712.5 - 1752.5	0.255	24.07	4M59G7D	QPSK
LTE Band 4	27	1712.5 - 1752.5	0.196	22.92	4M55W7D	16QAM
LTE Band 4	27	1715 - 1750	0.251	24.00	9M04G7D	QPSK
LTE Band 4	27	1715 - 1750	0.204	23.10	9M10W7D	16QAM
LTE Band 4	27	1717.5 - 1747.5	0.246	23.91	13M6G7D	QPSK
LTE Band 4	27	1717.5 - 1747.5	0.201	23.04	13M6W7D	16QAM
LTE Band 4	27	1720 - 1745	0.254	24.05	18M1G7D	QPSK
LTE Band 4	27	1720 - 1745	0.203	23.07	18M0W7D	16QAM
LTE Band 2/25	24E	1850.7 - 1914.3	0.281	24.48	1M10G7D	QPSK
LTE Band 2/25	24E	1850.7 - 1914.3	0.219	23.41	1M11W7D	16QAM
LTE Band 2/25	24E	1851.5 - 1913.5	0.279	24.45	2M73G7D	QPSK
LTE Band 2/25	24E	1851.5 - 1913.5	0.225	23.51	2M73W7D	16QAM
LTE Band 2/25	24E	1852.5 - 1912.5	0.267	24.27	4M56G7D	QPSK
LTE Band 2/25	24E	1852.5 - 1912.5	0.218	23.39	4M57W7D	16QAM
LTE Band 2/25	24E	1855 - 1910	0.288	24.60	9M06G7D	QPSK
LTE Band 2/25	24E	1855 - 1910	0.235	23.72	9M05W7D	16QAM
LTE Band 2/25	24E	1857.5 - 1907.5	0.275	24.39	13M6G7D	QPSK
LTE Band 2/25	24E	1857.5 - 1907.5	0.227	23.55	13M6W7D	16QAM
LTE Band 2/25	24E	1860 - 1905	0.254	24.05	18M0G7D	QPSK
LTE Band 2/25	24E	1860 - 1905	0.211	23.25	18M1W7D	16QAM
LTE Band 41(PC2)	27	2498.5 - 2687.5	0.683	28.34	4M59G7D	QPSK
LTE Band 41(PC2)	27	2498.5 - 2687.5	0.470	26.72	4M56W7D	16QAM
LTE Band 41(PC2)	27	2501 - 2685	0.683	28.34	9M02G7D	QPSK
LTE Band 41(PC2)	27	2501 - 2685	0.444	26.47	9M01W7D	16QAM
LTE Band 41(PC2)	27	2503.5 - 2682.5	0.723	28.59	13M6G7D	QPSK
LTE Band 41(PC2)	27	2503.5 - 2682.5	0.485	26.85	13M5W7D	16QAM
LTE Band 41(PC2)	27	2506 - 2680	0.700	28.45	18M1G7D	QPSK
LTE Band 41(PC2)	27	2506 - 2680	0.448	26.51	18M0W7D	16QAM
LTE Band 41(PC3)	27	2496 - 2687.5	0.378	25.77	4M55G7D	QPSK
LTE Band 41(PC3)	27	2496 - 2687.5	0.301	24.78	4M54W7D	16QAM
LTE Band 41(PC3)	27	2496 - 2685	0.343	25.35	9M06G7D	QPSK
LTE Band 41(PC3)	27	2496 - 2685	0.257	24.10	9M04W7D	16QAM
LTE Band 41(PC3)	27	2496 - 2682.5	0.356	25.52	13M6G7D	QPSK
LTE Band 41(PC3)	27	2496 - 2682.5	0.321	25.06	13M5W7D	16QAM
LTE Band 41(PC3)	27	2496 - 2680	0.362	25.59	18M1G7D	QPSK
LTE Band 41(PC3)	27	2496 - 2680	0.283	24.52	18M0W7D	16QAM

EUT Overview (>1GHz)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 4 of 158

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 5 of 158	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMJ737P**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

Test Device Serial No.: 34945, 34978, 35017, 34944, 34952

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), ANT+

LTE Band 26 (814.7 – 849 MHz) overlaps the entire frequency range of LTE Band 5 (824 – 849 MHz). Therefore, test data provided in this report covers Band 5 and the portion of Band 26 subject to Part 22.

LTE Band 25 (1850 - 1915 MHz) overlaps the entire frequency range of LTE Band 2 (1850 - 1910 MHz). Therefore, test data provided in this report covers Band 2 as well as Band 25.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 6 of 158	

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure


The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03) were used in the measurement of the EUT.

3.2 Block A Frequency Range

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz;
Block B: 704-710 MHz and 734-740 MHz; and
Block C: 710-716 MHz and 740-746 MHz.


3.3 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)
BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)
BLOCK 4: 891.5 – 894 MHz (B*)

3.4 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)
BLOCK 2: 835 – 845 MHz (B)


BLOCK 3: 845 – 846.5 MHz (A* High)
BLOCK 4: 846.5 – 849 MHz (B*)

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 7 of 158


3.5 PCS - Base Frequency Blocks




3.6 PCS - Mobile Frequency Blocks




3.7 AWS - Base Frequency Blocks



3.8 AWS - Mobile Frequency Blocks



FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 8 of 158



FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 9 of 158

3.10 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$. For Band 41, the calculated P_d levels are compared to the absolute spurious emission limit of -25dBm which is equivalent to the required minimum attenuation of $55 + 10\log_{10}(\text{Power [Watts]})$.

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 10 of 158

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 11 of 158

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx2	Licensed Transmitter Cable Set	8/10/2017	Annual	8/10/2018	LTx2
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	8/28/2017	Annual	8/28/2018	MY49432391
COM-Power	AL-130R	Active Loop Antenna	6/5/2017	Annual	6/5/2018	121085
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	5/19/2017	Annual	5/19/2018	251425001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A		N/A	QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A		N/A	11208010032
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2017	Annual	10/13/2018	102060
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102133
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102135
Anritsu	MT8820C	Radio Communication Analyzer	10/25/2017	Annual	10/25/2018	6201144419
Rohde & Schwarz	TC-TA18	Cross-Pol Antenna 400MHz-18GHz	10/30/2017	Annual	10/30/2018	101058
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Rohde & Schwarz	TS-PR8	Preamplifier-Antenna SYS; 30MHz-8GHz	10/19/2017	Annual	10/19/2018	102324
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100040
Seekonk	NC-100	Torque Wrench	12/28/2017	Annual	12/28/2018	N/A
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 12 of 158

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 13 of 158

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMJ737P
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 2.917(a) 24.238(a) 27.53(g) 27.53(h)	Out of Band Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Section 7.3, 7.4
27.53(m)	Out of Band Emissions	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.3, 7.4
24.232(d)	Peak-Average Ratio	$< 13 \text{ dB}$		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	See RF Exposure Report
2.1046	Additional Maximum Power Reduction (A-MPR)	N/A		PASS	Section 7.6
2.1055 22.355 24.235 27.54	Frequency Stability	$< 2.5 \text{ ppm}$ (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section 7.9

Table 7-1. Summary of Conducted Test Results

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 14 of 158

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
22.913(a)(5)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 26/5)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
27.50(c)(10)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 12)	< 3 Watts max. ERP		PASS	Section 7.6
24.232(c) 27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 25/2, 41)	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(g) 27.53(h)	Undesirable Emissions (Band 25/2, 26/5, 12, 4)	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.8
27.53(m)	Undesirable Emissions (Band 41)	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.8

Table 7-2. Summary of Radiated Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.8.
- 5) For operation <1GHz, the EIRP limits in the table above are referenced to the specifications written in the relevant Radio Standards Specifications for Innovation, Science, and Economic Development Canada.

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 15 of 158	

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 16 of 158

Band 12




Plot 7-1. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-2. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 17 of 158




Plot 7-3. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 18 of 158	




Plot 7-5. Occupied Bandwidth Plot (Band 12 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (Band 12 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 19 of 158




Plot 7-7. Occupied Bandwidth Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (Band 12 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 20 of 158




Plot 7-9. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (Band 26/5 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 21 of 158	




Plot 7-11. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz QPSK - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (Band 26/5 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 22 of 158	




Plot 7-13. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (Band 26/5 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 23 of 158




Plot 7-15. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (Band 26/5 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 24 of 158




Plot 7-17. Occupied Bandwidth Plot (Band 26 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-18. Occupied Bandwidth Plot (Band 26 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 25 of 158

Band 4




Plot 7-19. Occupied Bandwidth Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-20. Occupied Bandwidth Plot (Band 4 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 26 of 158




Plot 7-21. Occupied Bandwidth Plot (Band 4 - 3.0MHz QPSK - Full RB Configuration)




Plot 7-22. Occupied Bandwidth Plot (Band 4 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 27 of 158	




Plot 7-23. Occupied Bandwidth Plot (Band 4 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-24. Occupied Bandwidth Plot (Band 4 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 28 of 158




Plot 7-25. Occupied Bandwidth Plot (Band 4 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-26. Occupied Bandwidth Plot (Band 4 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 29 of 158




Plot 7-27. Occupied Bandwidth Plot (Band 4 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-28. Occupied Bandwidth Plot (Band 4 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 30 of 158




Plot 7-29. Occupied Bandwidth Plot (Band 4 - 20.0MHz QPSK - Full RB Configuration)




Plot 7-30. Occupied Bandwidth Plot (Band 4 - 20.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 31 of 158	




Plot 7-31. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-32. Occupied Bandwidth Plot (Band 25/2 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 32 of 158



Plot 7-33. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz QPSK - Full RB Configuration)




Plot 7-34. Occupied Bandwidth Plot (Band 25/2 - 3.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 33 of 158




Plot 7-35. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-36. Occupied Bandwidth Plot (Band 25/2 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 34 of 158




Plot 7-37. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-38. Occupied Bandwidth Plot (Band 25/2 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 35 of 158




Plot 7-39. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-40. Occupied Bandwidth Plot (Band 25/2 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 36 of 158




Plot 7-41. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz QPSK - Full RB Configuration)




Plot 7-42. Occupied Bandwidth Plot (Band 25/2 - 20.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 37 of 158




Plot 7-43. Occupied Bandwidth Plot (Band 41 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-44. Occupied Bandwidth Plot (Band 41 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 38 of 158	




Plot 7-45. Occupied Bandwidth Plot (Band 41 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-46. Occupied Bandwidth Plot (Band 41 - 10.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 39 of 158	




Plot 7-47. Occupied Bandwidth Plot (Band 41 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-48. Occupied Bandwidth Plot (Band 41 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 40 of 158



Plot 7-49. Occupied Bandwidth Plot (Band 41 - 20.0MHz QPSK - Full RB Configuration)



Plot 7-50. Occupied Bandwidth Plot (Band 41 - 20.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 41 of 158

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

For Band 41, the minimum permissible attenuation level of any spurious emission is $55 + \log_{10}(P_{\text{Watts}})$.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1 GHz and 1 MHz or greater for frequencies greater than 1 GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 42 of 158

Band 12




Plot 7-51. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-52. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 43 of 158	




Plot 7-53. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-54. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 44 of 158




Plot 7-55. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-56. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 45 of 158




Plot 7-57. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-58. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 46 of 158




Plot 7-59. Conducted Spurious Plot (Band 12 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 47 of 158




Plot 7-60. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-61. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 48 of 158




Plot 7-62. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-63. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 49 of 158




Plot 7-64. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-65. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 50 of 158




Plot 7-66. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-67. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 51 of 158




Plot 7-68. Conducted Spurious Plot (Band 26/5 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 52 of 158

Band 4




Plot 7-69. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-70. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 53 of 158




Plot 7-71. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-72. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 54 of 158




Plot 7-73. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-74. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 55 of 158




Plot 7-75. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)




Plot 7-76. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 56 of 158




Plot 7-77. Conducted Spurious Plot (Band 4 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 57 of 158




Plot 7-78. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-79. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 58 of 158




Plot 7-80. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-81. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 59 of 158




Plot 7-82. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-83. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 60 of 158




Plot 7-84. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-85. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 61 of 158	




Plot 7-86. Conducted Spurious Plot (Band 25/2 - 1.4MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 62 of 158

Band 41(PC2)




Plot 7-87. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-88. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 63 of 158




Plot 7-89. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-90. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	<div>MEASUREMENT REPORT (CERTIFICATION)</div> <div></div>		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 64 of 158




Plot 7-91. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-92. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 65 of 158	




Plot 7-93. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-94. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 66 of 158



Plot 7-95. Conducted Spurious Plot (Band 41 - 10.0MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 67 of 158

7.4 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

The minimum permissible attenuation level for Band 41 is as noted in the Test Notes on the following page.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

FCC ID: A3LSMJ737P		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 68 of 158

Test Notes


Per 22.917(b) 24.238(a) 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.


Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz.

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 69 of 158

Band 12




Plot 7-96. Lower Band Edge Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-97. Upper Band Edge Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 70 of 158	




Plot 7-98. Lower Band Edge Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-99. Upper Band Edge Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 71 of 158	



Plot 7-100. Lower Band Edge Plot (Band 12 - 5.0MHz QPSK - Full RB Configuration)



Plot 7-101. Upper Band Edge Plot (Band 12 - 5.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 72 of 158	




Plot 7-102. Lower Band Edge Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)



Plot 7-103. Upper Band Edge Plot (Band 12 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 73 of 158




Plot 7-104. Lower Band Edge Plot (Band 26/5 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-105. Upper Band Edge Plot (Band 26/5 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 74 of 158	




Plot 7-106. Lower Band Edge Plot (Band 26/5 - 3.0MHz QPSK - Full RB Configuration)




Plot 7-107. Upper Band Edge Plot (Band 26/5 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 75 of 158




Plot 7-108. Lower Band Edge Plot (Band 26/5 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-109. Upper Band Edge Plot (Band 26/5 - 5.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 76 of 158	




Plot 7-110. Lower Band Edge Plot (Band 26/5 - 10.0MHz QPSK - Full RB Configuration)




Plot 7-111. Upper Band Edge Plot (Band 26/5 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 77 of 158




Plot 7-112. Lower Band Edge Plot (Band 26 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-113. Upper Band Edge Plot (Band 26 - 15.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 78 of 158

Band 4



Plot 7-114. Lower Band Edge Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-115. Lower Extended Band Edge Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 79 of 158	




Plot 7-116. Upper Band Edge Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-117. Upper Extended Band Edge Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset		Page 80 of 158



Plot 7-118. Lower Band Edge Plot (Band 4 - 3.0MHz QPSK - Full RB Configuration)



Plot 7-119. Lower Extended Band Edge Plot (Band 4 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMJ737P	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1802160028-03.A3L	Test Dates: 2/16 - 4/6/2018	EUT Type: Portable Handset	Page 81 of 158