



SAR EVALUATION REPORT

Applicant Name:
 Samsung Electronics Co., Ltd.
 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si
 Gyeonggi-do, 16677, Korea

Date of Testing:
 03/18/18 - 04/10/18
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 1M1803150042-01-R2.A3L

FCC ID: A3LSMJ737T

APPLICANT: SAMSUNG ELECTRONICS CO., LTD.

DUT Type: Portable Handset
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: SM-J737T

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)	10g Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.39	0.40	0.74	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.56	0.26	0.88	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.40	0.43	0.52	N/A
PCE	UMTS 1750	1712.4 - 1752.6 MHz	1.03	0.80	1.03	3.29
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.84	0.46	0.88	3.19
PCE	LTE Band 71	665.5 - 695.5 MHz	0.23	0.37	0.44	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.38	0.54	0.56	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.39	0.43	0.50	N/A
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	1.36	1.01	1.11	3.30
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	1.03	0.54	0.88	3.29
PCE	LTE Band 7	2502.5 - 2567.5 MHz	0.64	0.43	1.04	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.51	0.21	0.40	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	N/A	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.69	0.20	N/A	1.03
NII	U-NII-2C	5500 - 5720 MHz	0.93	0.31	N/A	1.87
NII	U-NII-3	5745 - 5825 MHz	0.69	0.38	1.07	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.29	N/A	N/A	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.57	1.39	1.58	3.60

Note: This revised Test Report (S/N: 1M1803150042-01-R2.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
 President





The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 1 of 97	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	10
3	INTRODUCTION	11
4	DOSIMETRIC ASSESSMENT	12
5	DEFINITION OF REFERENCE POINTS.....	13
6	TEST CONFIGURATION POSITIONS.....	14
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS	24
10	SYSTEM VERIFICATION.....	52
11	SAR DATA SUMMARY	56
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	76
13	SAR MEASUREMENT VARIABILITY	91
14	EQUIPMENT LIST.....	93
15	MEASUREMENT UNCERTAINTIES.....	94
16	CONCLUSION.....	95
17	REFERENCES	96
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: POWER REDUCTION VERIFICATION		
APPENDIX H: LTE CARRIER AGGREGATION CONDUCTED POWERS		

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 2 of 97	

1 DEVICE UNDER TEST



1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device utilizes a power reduction mechanism for some wireless modes and bands for SAR compliance under portable hotspot conditions and under some conditions when the device is being used in close proximity to the user's hand. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device when being used in phablet use conditions. Detailed descriptions of the power reduction mechanism are included in the operational description.

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 3 of 97	

1.3 Nominal and Maximum Output Power Specifications



This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.5	33.5	31.5	30.5	30.0	28.5	26.0	25.5	24.0
	Nominal	32.5	32.5	30.5	29.5	29.0	27.5	25.0	24.5	23.0
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	28.5	27.5	26.5	27.5	25.5	24.5	23.0
	Nominal	29.5	29.5	27.5	26.5	25.5	26.5	24.5	23.5	22.0

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	25.0	23.5	22.5	23.5
	Nominal	24.0	22.5	21.5	22.5
UMTS Band 4 (1750 MHz)	Maximum	24.0	23.0	22.5	23.0
	Nominal	23.0	22.0	21.5	22.0
UMTS Band 2 (1900 MHz)	Maximum	23.0	23.0	22.5	23.0
	Nominal	22.0	22.0	21.5	22.0

Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	25.0
	Nominal	24.0
LTE Band 12	Maximum	25.0
	Nominal	24.0
LTE Band 5 (Cell)	Maximum	25.0
	Nominal	24.0
LTE Band 66 (AWS)	Maximum	24.5
	Nominal	23.5
LTE Band 4 (AWS)	Maximum	24.5
	Nominal	23.5
LTE Band 2 (PCS)	Maximum	23.5
	Nominal	22.5
LTE Band 7	Maximum	23.0
	Nominal	22.0

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 4 of 97	

Mode / Band		Modulated Average (dBm)	
		Ch. 1-10	Ch. 11
IEEE 802.11b (2.4 GHz)	Maximum	19.0	19.0
	Nominal	18.0	18.0
IEEE 802.11g (2.4 GHz)	Maximum	17.0	16.0
	Nominal	16.0	15.0
IEEE 802.11n (2.4 GHz)	Maximum	18.0	16.0
	Nominal	17.0	15.0



Mode / Band		Modulated Average (dBm)
Bluetooth	Maximum	12.5
	Nominal	11.5
Bluetooth LE	Maximum	6.0
	Nominal	5.0

Mode / Band		Modulated Average (dBm)							
		20 MHz Bandwidth	40 MHz Bandwidth			80 MHz Bandwidth			
			Ch. 46,54,110-159	Ch. 38	Ch. 62	Ch. 102	Ch. 122-155	Ch. 42,58	Ch. 106
IEEE 802.11a (5 GHz)	Maximum	17.0							
	Nominal	16.0							
IEEE 802.11n (5 GHz)	Maximum	17.0	15.0	12.0	10.0	11.0			
	Nominal	16.0	14.0	11.0	9.0	10.0			
IEEE 802.11ac (5 GHz)	Maximum	17.0	15.0	12.0	10.0	11.0	15.0	10.0	9.5
	Nominal	16.0	14.0	11.0	9.0	10.0	14.0	9.0	8.5

1.3.2 Reduced Output Power

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 4 (1750 MHz)	Maximum	22.6	22.5	22.0	22.5
	Nominal	21.6	21.5	21.0	21.5
UMTS Band 2 (1900 MHz)	Maximum	22.0	22.0	22.0	22.0
	Nominal	21.0	21.0	21.0	21.0

Mode / Band		Modulated Average (dBm)
LTE Band 66 (AWS)	Maximum	23.0
	Nominal	22.0
LTE Band 4 (AWS)	Maximum	23.0
	Nominal	22.0
LTE Band 2 (PCS)	Maximum	21.8
	Nominal	20.8

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 5 of 97

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	15.0
	Nominal	14.0
IEEE 802.11g (2.4 GHz)	Maximum	15.0
	Nominal	14.0
IEEE 802.11n (2.4 GHz)	Maximum	15.0
	Nominal	14.0

Mode / Band		Modulated Average (dBm)					
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth		
			Ch. 38-54, 102-159	Ch. 62	Ch. 42,58	Ch.106	Ch.122-155
IEEE 802.11a (5 GHz)	Maximum	11.0					
	Nominal	10.0					
IEEE 802.11n (5 GHz)	Maximum	11.0	11.0	10.0			
	Nominal	10.0	10.0	9.0			
IEEE 802.11ac (5 GHz)	Maximum	11.0	11.0	10.0	10.0	9.5	11.0
	Nominal	10.0	10.0	9.0	9.0	8.5	10.0



1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

**Table 1-1
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes	Yes
LTE Band 71	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 7	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN	Yes	Yes	Yes	No	Yes	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 6 of 97	

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities



According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

**Table 1-2
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	Yes	
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A	Yes	
3	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
4	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	Yes	
5	UMTS + 5 GHz WI-FI	Yes	Yes	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
7	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	Yes	
8	LTE + 5 GHz WI-FI	Yes	Yes	Yes	Yes	
9	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
10	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes	Yes	
11	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	Yes	Yes	
12	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	Yes^	Yes	^ Bluetooth Tethering is considered

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
- This device supports VOLTE.
- This device supports VoWIFI.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 7 of 97

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(18/15) * \sqrt{2.480}] = 1.9 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, hotspot Bluetooth SAR was not required; $[(18/5) * \sqrt{2.480}] = 2.8 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:



$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet Bluetooth SAR was not required; $[(18/5) * \sqrt{2.480}] = 5.7 < 7.5$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 1 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-1, U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

FCC ID: A3LSMJ737T	 PCTEST PROFESSIONAL LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 8 of 97	

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. Downlink LTE CA conducted powers are included in Appendix H.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.



This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- FCC KDB Publication 616217 D04v01r02 (Proximity Sensor)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- Fall 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.9 Device Serial Numbers



Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 9 of 97

2

LTE INFORMATION

LTE Information					
FCC ID	A3LSMJ737T				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 71 (665.5 - 695.5 MHz)				
	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
Channel Bandwidths	LTE Band 71: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	Low	Low-Mid	Mid	Mid-High	High
LTE Band 71: 5 MHz	665.5 (133147)		680.5 (133297)		695.5 (133447)
LTE Band 71: 10 MHz	668 (133172)		680.5 (133297)		693 (133422)
LTE Band 71: 15 MHz	670.5 (133197)		680.5 (133297)		690.5 (133397)
LTE Band 71: 20 MHz	673 (133222)		680.5 (133297)		688 (133372)
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)		1779.3 (132665)
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)		1778.5 (132657)
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)		1777.5 (132647)
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)		1775 (132622)
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)		1772.5 (132597)
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)		1770 (132572)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 7: 5 MHz	2502.5 (20775)		2535 (21100)		2567.5 (21425)
LTE Band 7: 10 MHz	2505 (20800)		2535 (21100)		2565 (21400)
LTE Band 7: 15 MHz	2507.5 (20825)		2535 (21100)		2562.5 (21375)
LTE Band 7: 20 MHz	2510 (20850)		2535 (21100)		2560 (21350)
UE Category	6				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eCIC, WIFI Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 10 of 97	

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 11 of 97

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.






Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 12 of 97

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom






Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 SAMSUNG	Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 13 of 97

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 SAMSUNG	Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 14 of 97




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.






Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 15 of 97

dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person’s face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations



Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user’s body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 16 of 97	

6.8 Phablet Configurations



For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna <=25 mm from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR > 1.2 W/kg.

6.9 Proximity Sensor Considerations

This device uses a power reduction mechanism to reduce output powers in certain use conditions when the device is used close the user's body.

When the device's antenna is within a certain distance of the user, the sensor activates and reduces the maximum allowed output power. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, additional evaluation is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a nonreduced output power level. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antennas.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 17 of 97	

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 18 of 97	

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR



The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 19 of 97

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.4.6 SAR Measurement Conditions for DC-HSDPA



SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 20 of 97

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.



8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 21 of 97	

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.3 U-NII-2C and U-NII-3



The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

FCC ID: A3LSMJ737T	 PCTEST PROFESSIONAL LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 22 of 97

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.



8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 23 of 97	

9 RF CONDUCTED POWERS



9.1 GSM Conducted Powers

**Table 9-1
Maximum Conducted Power**

Maximum Burst-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.11	32.22	30.52	29.52	29.03	27.10	25.10	23.75	22.61
	190	32.53	32.54	30.81	29.97	29.20	27.53	25.55	24.31	23.25
	251	32.54	32.43	30.78	29.89	29.39	27.54	25.24	24.24	23.22
GSM 1900	512	29.31	29.35	27.50	26.31	25.49	26.65	24.53	23.64	21.95
	661	29.47	29.53	27.52	26.37	25.49	26.50	24.52	23.75	22.00
	810	29.50	29.53	27.42	26.47	25.50	26.55	24.50	23.69	22.20

Calculated Maximum Frame-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.08	23.19	24.50	25.26	26.02	18.07	19.08	19.49	19.60
	190	23.50	23.51	24.79	25.71	26.19	18.50	19.53	20.05	20.24
	251	23.51	23.40	24.76	25.63	26.38	18.51	19.22	19.98	20.21
GSM 1900	512	20.28	20.32	21.48	22.05	22.48	17.62	18.51	19.38	18.94
	661	20.44	20.50	21.50	22.11	22.48	17.47	18.50	19.49	18.99
	810	20.47	20.50	21.40	22.21	22.49	17.52	18.48	19.43	19.19

GSM 850	Frame	23.47	23.47	24.48	25.24	25.99	18.47	18.98	20.24	19.99
GSM 1900	Avg.Targets:	20.47	20.47	21.48	22.24	22.49	17.47	18.48	19.24	18.99

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 24 of 97	

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.






Figure 9-1
Power Measurement Setup

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 25 of 97	



9.2 UMTS Conducted Powers

Table 9-2
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.00	23.99	24.03	23.10	23.15	23.32	22.32	22.48	22.61	-
99		12.2 kbps AMR	24.02	23.94	23.97	23.11	23.16	23.30	22.33	22.49	22.62	-
6	HSDPA	Subtest 1	22.21	22.20	22.17	22.23	22.39	22.35	21.67	21.53	21.64	0
6		Subtest 2	21.81	21.81	21.78	21.76	21.93	21.95	21.56	21.57	21.70	0
6		Subtest 3	22.27	22.29	22.19	22.27	22.36	22.41	22.21	22.39	22.45	0.5
6		Subtest 4	21.80	21.73	21.88	21.77	21.90	21.96	21.28	21.36	21.41	0.5
6	HSUPA	Subtest 1	21.81	21.83	21.75	21.77	21.85	21.96	21.20	21.32	21.40	0
6		Subtest 2	18.75	18.74	18.71	19.28	19.42	19.47	19.20	19.38	19.44	2
6		Subtest 3	20.22	20.21	20.14	20.44	20.48	20.53	20.28	20.42	20.53	1
6		Subtest 4	18.81	18.86	18.83	19.30	19.41	19.49	19.23	19.42	19.40	2
6		Subtest 5	22.24	22.25	22.23	22.23	22.37	22.43	22.20	22.33	22.35	0
8	DC-HSDPA	Subtest 1	22.23	22.31	22.25	22.16	22.34	22.25	22.21	22.24	22.43	0
8		Subtest 2	22.59	22.45	22.37	21.60	21.87	21.77	21.69	21.89	22.05	0
8		Subtest 3	21.68	21.81	21.53	21.56	21.55	21.71	20.70	20.79	20.82	0.5
8		Subtest 4	22.00	21.88	21.87	21.70	21.81	21.74	21.19	21.26	21.46	0.5

Table 9-3
Reduced Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.28	22.17	22.40	21.10	21.32	21.54	-
99		12.2 kbps AMR	22.27	22.17	22.20	21.11	21.33	21.52	-
6	HSDPA	Subtest 1	22.46	22.30	22.46	21.16	21.24	21.47	0
6		Subtest 2	22.01	21.84	21.98	21.19	21.31	21.53	0
6		Subtest 3	22.49	22.38	22.48	21.23	21.33	21.50	0.5
6		Subtest 4	21.99	21.84	22.12	21.18	21.37	21.48	0.5
6	HSUPA	Subtest 1	21.40	21.31	21.39	20.30	20.46	20.62	0
6		Subtest 2	19.60	19.42	19.59	19.24	19.49	19.56	2
6		Subtest 3	20.57	20.43	20.56	20.38	20.50	20.65	1
6		Subtest 4	19.58	19.47	19.59	19.23	19.48	19.55	2
6		Subtest 5	21.91	21.83	21.94	21.12	21.31	21.45	0
8	DC-HSDPA	Subtest 1	22.34	22.42	22.32	21.23	21.31	21.45	0
8		Subtest 2	22.09	21.95	22.04	21.31	21.32	21.38	0
8		Subtest 3	21.00	20.98	20.90	20.48	20.52	20.62	0.5
8		Subtest 4	21.91	21.88	21.85	21.24	21.30	21.49	0.5

FCC ID: A3LSMJ73TT	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 26 of 97

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 1 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.






Figure 9-2
Power Measurement Setup

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 SAMSUNG	Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 27 of 97	

9.3 LTE Conducted Powers

9.3.1 LTE Band 71

Table 9-4
LTE Band 71 Conducted Powers - 20 MHz Bandwidth

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.93	0	0
	1	50	23.84		0
	1	99	23.79		0
	50	0	22.95	0-1	1
	50	25	22.88		1
	50	50	22.85		1
	100	0	22.90		1
16QAM	1	0	22.91	0-1	1
	1	50	22.75		1
	1	99	22.70		1
	50	0	21.82	0-2	2
	50	25	21.78		2
	50	50	21.72		2
	100	0	21.84		2

Note: LTE Band 71 at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-5
LTE Band 71 Conducted Powers - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.85	0	0
	1	36	23.73		0
	1	74	23.63		0
	36	0	22.90	0-1	1
	36	18	22.85		1
	36	37	22.83		1
	75	0	22.87		1
16QAM	1	0	22.68	0-1	1
	1	36	22.55		1
	1	74	22.48		1
	36	0	21.87	0-2	2
	36	18	21.86		2
	36	37	21.80		2
	75	0	21.83		2

Note: LTE Band 71 at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.





FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 28 of 97

Table 9-6
LTE Band 71 Conducted Powers - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.88	23.86	23.86	0	0
	1	25	23.85	23.76	23.80		0
	1	49	23.84	23.72	23.79		0
	25	0	22.83	22.85	22.86	0-1	1
	25	12	22.81	22.82	22.83		1
	25	25	22.80	22.82	22.84		1
16QAM	50	0	22.80	22.84	22.83	0-1	1
	1	0	22.73	22.68	22.55		1
	1	25	22.70	22.52	22.45		1
	1	49	22.64	22.67	22.36	0-2	1
	25	0	21.80	21.91	21.90		2
	25	12	21.70	21.82	21.85		2
	25	25	21.73	21.83	21.86	2	
	50	0	21.81	21.86	21.85	2	

Table 9-7
LTE Band 71 Conducted Powers - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.87	23.74	24.01	0	0
	1	12	23.83	23.69	23.94		0
	1	24	23.85	23.70	23.94		0
	12	0	22.80	22.88	22.89	0-1	1
	12	6	22.81	22.84	22.87		1
	12	13	22.83	22.83	22.86		1
16QAM	25	0	22.81	22.84	22.91	0-1	1
	1	0	22.76	22.85	22.69		1
	1	12	22.72	22.82	22.67		1
	1	24	22.70	22.82	22.64	0-2	1
	12	0	21.68	21.81	21.83		2
	12	6	21.60	21.85	21.80		2
	12	13	21.73	21.84	21.85	2	
	25	0	21.79	21.83	21.80	2	

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 29 of 97

9.3.2

LTE Band 12

Table 9-8
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.53	0	0
	1	25	23.55		0
	1	49	23.60		0
	25	0	22.64	0-1	1
	25	12	22.64		1
	25	25	22.66		1
16QAM	50	0	22.65	0-1	1
	1	0	22.37		1
	1	25	22.39		1
	1	49	22.43	0-2	1
	25	0	21.60		2
	25	12	21.60		2
	25	25	21.60	2	
	50	0	21.61	2	

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-9
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.81	23.85	23.80	0	0
	1	12	23.82	23.85	23.81		0
	1	24	23.81	23.86	23.79		0
	12	0	22.70	22.70	22.73	0-1	1
	12	6	22.67	22.70	22.75		1
	12	13	22.67	22.71	22.73		1
16QAM	25	0	22.65	22.68	22.70	0-1	1
	1	0	22.48	22.54	22.57		1
	1	12	22.52	22.56	22.61		1
	1	24	22.55	22.53	22.63	0-2	1
	12	0	21.61	21.66	21.64		2
	12	6	21.61	21.62	21.65		2
	12	13	21.62	21.62	21.63	2	
	25	0	21.61	21.60	21.64	2	





FCC ID: A3LSMJ73TT		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 30 of 97

Table 9-10
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.55	23.48	23.57	0	0
	1	7	23.56	23.50	23.57		0
	1	14	23.55	23.46	23.54		0
	8	0	22.55	22.53	22.57	0-1	1
	8	4	22.56	22.53	22.59		1
	8	7	22.53	22.53	22.60		1
16QAM	15	0	22.54	22.54	22.59	0-1	1
	1	0	22.47	22.43	22.48		1
	1	7	22.44	22.48	22.55		1
	1	14	22.49	22.43	22.53	0-2	1
	8	0	21.56	21.55	21.61		2
	8	4	21.56	21.59	21.58		2
	8	7	21.57	21.55	21.57	2	
	15	0	21.52	21.54	21.57	2	

Table 9-11
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.66	23.60	23.64	0	0
	1	2	23.65	23.59	23.65		0
	1	5	23.63	23.56	23.61		0
	3	0	23.73	23.65	23.73		0
	3	2	23.70	23.63	23.70		0
	3	3	23.69	23.61	23.69		0
16QAM	6	0	22.65	22.54	22.62	0-1	1
	1	0	22.40	22.34	22.46	0-1	1
	1	2	22.41	22.37	22.45		1
	1	5	22.41	22.42	22.51		1
	3	0	22.45	22.46	22.52		1
	3	2	22.47	22.43	22.51		1
3	3	22.52	22.47	22.54	1		
	6	0	21.60	21.51	21.55	0-2	2

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 31 of 97

9.3.3

LTE Band 5 (Cell)

Table 9-12
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.89	0	0
	1	25	23.90		0
	1	49	23.84		0
	25	0	22.66	0-1	1
	25	12	22.68		1
	25	25	22.67		1
16QAM	50	0	22.64	0-1	1
	1	0	22.45		1
	1	25	22.45		1
	1	49	22.41	0-2	1
	25	0	21.73		2
	25	12	21.71		2
	25	25	21.71		2
50	0	21.75	2		

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-13
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.91	23.84	23.88	0	0
	1	12	23.91	23.84	23.86		0
	1	24	23.88	23.79	23.81		0
	12	0	22.82	22.73	22.77	0-1	1
	12	6	22.80	22.70	22.77		1
	12	13	22.80	22.71	22.75		1
16QAM	25	0	22.82	22.73	22.78	0-1	1
	1	0	22.75	22.73	22.64		1
	1	12	22.79	22.67	22.58		1
	1	24	22.72	22.65	22.52	0-2	1
	12	0	21.88	21.77	21.84		2
	12	6	21.89	21.75	21.84		2
	12	13	21.85	21.74	21.81		2
25	0	21.87	21.78	21.83	2		





FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 32 of 97

Table 9-14
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.83	23.77	23.80	0	0
	1	7	23.85	23.78	23.79		0
	1	14	23.82	23.73	23.74		0
	8	0	22.79	22.69	22.74	0-1	1
	8	4	22.79	22.69	22.74		1
	8	7	22.79	22.70	22.72		1
16QAM	15	0	22.78	22.70	22.78	0-1	1
	1	0	22.77	22.63	22.71		1
	1	7	22.72	22.71	22.74		1
	1	14	22.67	22.70	22.68	0-2	1
	8	0	21.81	21.73	21.77		2
	8	4	21.78	21.74	21.77		2
	8	7	21.78	21.72	21.77	2	
	15	0	21.80	21.74	21.78	2	

Table 9-15
LTE Band 5 (Cell) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.62	23.59	23.62	0	0	
	1	2	23.63	23.59	23.65		0	
	1	5	23.59	23.58	23.62		0	
	3	0	23.72	23.67	23.72	0-1	0	
	3	2	23.75	23.70	23.74		0	
	3	3	23.72	23.66	23.72		0	
16QAM	6	0	22.69	22.67	22.69	0-1	1	
	1	0	22.63	22.58	22.55		0-1	1
	1	2	22.59	22.58	22.56			1
	1	5	22.56	22.50	22.47	1		
	3	0	22.72	22.63	22.65	1		
	3	2	22.71	22.66	22.67	1		
3	3	22.69	22.65	22.65	1			
	6	0	21.76	21.75	21.75	0-2	2	

FCC ID: A3LSMJ737T	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 33 of 97

9.3.4

LTE Band 66 (AWS)

Table 9-16
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.46	23.65	23.55	0	0
	1	50	23.50	23.58	23.51		0
	1	99	23.40	23.49	23.48		0
	50	0	22.45	22.60	22.48	0-1	1
	50	25	22.46	22.55	22.47		1
	50	50	22.42	22.53	22.47		1
16QAM	100	0	22.42	22.55	22.47	0-1	1
	1	0	22.41	22.48	22.40		1
	1	50	22.38	22.43	22.42		1
	1	99	22.38	22.36	22.39	0-2	1
	50	0	21.47	21.55	21.44		2
	50	25	21.43	21.53	21.43		2
	50	50	21.38	21.48	21.42	2	
	100	0	21.41	21.52	21.45	2	

Table 9-17
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.55	23.71	23.63	0	0
	1	36	23.53	23.65	23.62		0
	1	74	23.51	23.61	23.63		0
	36	0	22.37	22.57	22.51	0-1	1
	36	18	22.39	22.54	22.51		1
	36	37	22.39	22.53	22.51		1
16QAM	75	0	22.40	22.56	22.52	0-1	1
	1	0	22.35	22.47	22.37		1
	1	36	22.30	22.43	22.47		1
	1	74	22.30	22.37	22.48	0-2	1
	36	0	21.38	21.54	21.46		2
	36	18	21.37	21.52	21.47		2
	36	37	21.35	21.49	21.48	2	
	75	0	21.39	21.53	21.49	2	



FCC ID: A3LSMJ73TT		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 34 of 97

Table 9-18
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.47	23.63	23.52	0	0	
	1	25	23.50	23.60	23.53		0	
	1	49	23.44	23.54	23.50		0	
	QPSK	25	0	22.40	22.57	22.46	0-1	1
		25	12	22.40	22.54	22.46		1
		25	25	22.40	22.54	22.48		1
		50	0	22.43	22.56	22.47		1
16QAM	1	0	22.31	22.54	22.45	0-1	1	
	1	25	22.35	22.57	22.44		1	
	1	49	22.33	22.56	22.46		1	
	16QAM	25	0	21.41	21.57	21.44	0-2	2
		25	12	21.40	21.54	21.44		2
		25	25	21.40	21.50	21.46		2
		50	0	21.42	21.56	21.49		2

Table 9-19
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]		
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)				
			Conducted Power [dBm]						
QPSK	1	0	23.47	23.62	23.53	0	0		
	1	12	23.47	23.60	23.55		0		
	1	24	23.44	23.57	23.53		0		
	QPSK	12	0	22.42	22.57	22.45	0-1	1	
		12	6	22.43	22.56	22.46		1	
		12	13	22.43	22.55	22.46		1	
16QAM	25	0	22.44	22.57	22.47	0-2	1		
	1	0	22.34	22.59	22.39		0-1	1	
	1	12	22.35	22.56	22.40			1	
	1	24	22.39	22.51	22.40			1	
	16QAM	12	0	21.44	21.58		21.45	0-2	2
		12	6	21.43	21.55		21.46		2
		12	13	21.42	21.58		21.46		2
25	0	21.38	21.55	21.42	2				



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 35 of 97

Table 9-20
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.42	23.56	23.49	0	0
	1	7	23.44	23.58	23.47		0
	1	14	23.40	23.56	23.46		0
	8	0	22.36	22.52	22.39	0-1	1
	8	4	22.35	22.51	22.40		1
	8	7	22.36	22.49	22.38		1
	15	0	22.39	22.53	22.43		1
16QAM	1	0	22.30	22.47	22.32	0-1	1
	1	7	22.34	22.45	22.35		1
	1	14	22.34	22.42	22.33		1
	8	0	21.38	21.50	21.38	0-2	2
	8	4	21.37	21.50	21.41		2
	8	7	21.36	21.49	21.40		2
	15	0	21.36	21.50	21.40		2

Table 9-21
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.23	23.41	23.29	0	0
	1	2	23.24	23.42	23.31		0
	1	5	23.22	23.40	23.32		0
	3	0	23.32	23.51	23.39		0
	3	2	23.33	23.53	23.42		0
	3	3	23.33	23.50	23.40		0
	6	0	22.34	22.53	22.41	0-1	1
16QAM	1	0	22.15	22.35	22.20	0-1	1
	1	2	22.12	22.36	22.22		1
	1	5	22.15	22.33	22.20		1
	3	0	22.24	22.47	22.32		1
	3	2	22.29	22.50	22.37		1
	3	3	22.28	22.47	22.36		1
	6	0	21.34	21.52	21.42	0-2	2



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 36 of 97	

Table 9-22
LTE Band 66 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.48	22.91	22.28	0	0
	1	50	22.43	22.85	22.29		0
	1	99	22.44	22.83	22.30		0
	50	0	22.50	22.91	22.30	0-1	0
	50	25	22.48	22.84	22.28		0
	50	50	22.46	22.83	22.42		0
	100	0	22.47	22.82	22.34		0
16QAM	1	0	22.45	22.78	22.41	0-1	0
	1	50	22.36	22.72	22.42		0
	1	99	22.38	22.75	22.46		0
	50	0	21.55	21.92	21.30	0-2	1
	50	25	21.51	21.89	21.32		1
	50	50	21.50	21.89	21.37		1
	100	0	21.53	21.88	21.40		1

Table 9-23
LTE Band 66 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.54	22.74	22.30	0	0
	1	36	22.49	22.69	22.32		0
	1	74	22.50	22.72	22.38		0
	36	0	22.45	22.78	22.26	0-1	0
	36	18	22.45	22.77	22.26		0
	36	37	22.42	22.78	22.29		0
	75	0	22.43	22.79	22.30		0
16QAM	1	0	22.30	22.82	22.39	0-1	0
	1	36	22.35	22.79	22.40		0
	1	74	22.32	22.81	22.48		0
	36	0	21.54	21.79	21.21	0-2	1
	36	18	21.51	21.80	21.22		1
	36	37	21.49	21.78	21.27		1
	75	0	21.49	21.84	21.29		1



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 37 of 97	

Table 9-24
LTE Band 66 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.46	22.73	22.12	0	0
	1	25	22.43	22.71	22.11		0
	1	49	22.44	22.73	22.22		0
	25	0	22.47	22.78	22.21	0-1	0
	25	12	22.46	22.77	22.24		0
	25	25	22.45	22.76	22.26		0
	50	0	22.44	22.77	22.25		0
16QAM	1	0	22.14	22.70	22.34	0-1	0
	1	25	22.12	22.67	22.35		0
	1	49	22.08	22.69	22.41		0
	25	0	21.53	21.78	21.28	0-2	1
	25	12	21.49	21.75	21.30		1
	25	25	21.52	21.77	21.36		1
	50	0	21.43	21.79	21.30		1

Table 9-25
LTE Band 66 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.33	22.72	22.22	0	0
	1	12	22.32	22.70	22.23		0
	1	24	22.35	22.74	22.26		0
	12	0	22.41	22.75	22.28	0-1	0
	12	6	22.42	22.74	22.27		0
	12	13	22.43	22.73	22.30		0
	25	0	22.40	22.76	22.25		0
16QAM	1	0	22.24	22.45	22.02	0-1	0
	1	12	22.19	22.67	22.09		0
	1	24	22.22	22.64	22.12		0
	12	0	21.48	21.75	21.21	0-2	1
	12	6	21.45	21.76	21.24		1
	12	13	21.47	21.76	21.26		1
	25	0	21.43	21.79	21.32		1





FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 38 of 97

Table 9-26
LTE Band 66 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.38	22.63	22.21	0	0
	1	7	22.36	22.60	22.22		0
	1	14	22.37	22.64	22.25		0
	8	0	22.42	22.74	22.25	0-1	0
	8	4	22.41	22.72	22.26		0
	8	7	22.40	22.76	22.27		0
	15	0	22.44	22.77	22.26		0
16QAM	1	0	22.39	22.68	22.32	0-1	0
	1	7	22.33	22.71	22.33		0
	1	14	22.30	22.82	22.35		0
	8	0	21.53	21.83	21.28	0-2	1
	8	4	21.49	21.86	21.31		1
	8	7	21.50	21.80	21.26		1
	15	0	21.48	21.75	21.30		1

Table 9-27
LTE Band 66 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.36	22.76	22.22	0	0
	1	2	22.31	22.69	22.21		0
	1	5	22.36	22.75	22.24		0
	3	0	22.38	22.80	22.24		0
	3	2	22.37	22.77	22.24		0
	3	3	22.39	22.79	22.25		0
	6	0	22.44	22.80	22.23	0-1	0
16QAM	1	0	22.52	22.74	22.42	0-1	0
	1	2	22.48	22.57	22.36		0
	1	5	22.55	22.49	22.41		0
	3	0	22.24	22.61	22.12		0
	3	2	22.23	22.58	22.07		0
	3	3	22.24	22.65	22.10		0
	6	0	21.46	21.78	21.19	0-2	1

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 39 of 97	

9.3.5

LTE Band 2 (PCS)

Table 9-28
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.33	22.49	22.39	0	0
	1	50	22.19	22.52	22.50		0
	1	99	22.10	22.62	22.35		0
	50	0	21.30	21.44	21.44	0-1	1
	50	25	21.22	21.45	21.50		1
	50	50	21.18	21.50	21.51		1
16QAM	100	0	21.20	21.46	21.46	0-1	1
	1	0	21.20	21.39	21.33		1
	1	50	21.12	21.39	21.45		1
	1	99	21.01	21.57	21.31	0-2	1
	50	0	20.29	20.43	20.49		2
	50	25	20.25	20.46	20.53		2
16QAM	50	50	20.17	20.53	20.53	0-2	2
	100	0	20.26	20.50	20.53		2

Table 9-29
LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.41	22.63	22.61	0	0
	1	36	22.32	22.62	22.64		0
	1	74	22.21	22.67	22.46		0
	36	0	21.29	21.44	21.52	0-1	1
	36	18	21.24	21.47	21.51		1
	36	37	21.19	21.48	21.49		1
16QAM	75	0	21.24	21.44	21.49	0-1	1
	1	0	21.30	21.32	21.29		1
	1	36	21.13	21.33	21.38		1
	1	74	21.00	21.33	21.24	0-2	1
	36	0	20.27	20.43	20.50		2
	36	18	20.25	20.46	20.51		2
16QAM	36	37	20.21	20.49	20.42	0-2	2
	75	0	20.24	20.47	20.51		2



FCC ID: A3LSMJ73TT	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 40 of 97	

Table 9-30
LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.34	22.55	22.66	0	0
	1	25	22.29	22.57	22.60		0
	1	49	22.20	22.58	22.42		0
	25	0	21.25	21.44	21.55	0-1	1
	25	12	21.21	21.46	21.52		1
	25	25	21.18	21.48	21.47		1
	50	0	21.22	21.47	21.53		1
16QAM	1	0	21.15	21.32	21.50	0-1	1
	1	25	21.12	21.38	21.50		1
	1	49	20.98	21.47	21.38		1
	25	0	20.29	20.47	20.59	0-2	2
	25	12	20.25	20.50	20.55		2
	25	25	20.23	20.50	20.50		2
	50	0	20.25	20.50	20.57		2

Table 9-31
LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.23	22.47	22.59	0	0
	1	12	22.20	22.52	22.52		0
	1	24	22.15	22.49	22.40		0
	12	0	21.24	21.44	21.56	0-1	1
	12	6	21.23	21.45	21.51		1
	12	13	21.18	21.47	21.48		1
	25	0	21.20	21.44	21.50		1
16QAM	1	0	21.13	21.33	21.51	0-1	1
	1	12	21.12	21.31	21.38		1
	1	24	21.04	21.35	21.38		1
	12	0	20.26	20.51	20.63	0-2	2
	12	6	20.25	20.50	20.61		2
	12	13	20.25	20.49	20.55		2
	25	0	20.27	20.47	20.57		2



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 41 of 97

Table 9-32
LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.14	22.43	22.52	0	0
	1	7	22.12	22.48	22.48		0
	1	14	22.09	22.45	22.40		0
	8	0	21.21	21.45	21.51	0-1	1
	8	4	21.21	21.45	21.48		1
	8	7	21.19	21.45	21.47		1
16QAM	15	0	21.22	21.46	21.51	0-1	1
	1	0	21.11	21.41	21.43		1
	1	7	21.15	21.41	21.40		1
	1	14	21.12	21.40	21.41	0-2	1
	8	0	20.25	20.45	20.54		2
	8	4	20.22	20.48	20.52		2
	8	7	20.23	20.47	20.50	2	
	15	0	20.21	20.49	20.53	2	

Table 9-33
LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.10	22.46	22.45	0	0
	1	2	22.12	22.45	22.45		0
	1	5	22.10	22.44	22.41		0
	3	0	22.19	22.52	22.52		0
	3	2	22.18	22.50	22.48		0
	3	3	22.16	22.49	22.46		0
16QAM	6	0	21.19	21.46	21.46	0-1	1
	1	0	21.01	21.29	21.31	0-1	1
	1	2	21.02	21.28	21.32		1
	1	5	21.04	21.29	21.37		1
	3	0	21.10	21.34	21.43		1
	3	2	21.07	21.35	21.41		1
3	3	21.11	21.36	21.39	1		
	6	0	20.21	20.42	20.49	0-2	2



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 42 of 97	

Table 9-34
LTE Band 2 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 2 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18700 (1860.0 MHz)	18900 (1880.0 MHz)	19100 (1900.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.53	21.61	21.63	0	0
	1	50	21.42	21.60	21.76		0
	1	99	21.29	21.66	21.67		0
	50	0	21.49	21.61	21.67	0-1	0
	50	25	21.43	21.61	21.73		0
	50	50	21.36	21.63	21.72		0
16QAM	100	0	21.42	21.67	21.63	0-1	0
	1	0	21.33	21.52	21.50		0
	1	50	21.25	21.54	21.60		0
	1	99	21.21	21.62	21.53	0-2	0
	50	0	20.46	20.59	20.64		1
	50	25	20.39	20.62	20.70		1
	50	50	20.34	20.64	20.70	1	
	100	0	20.39	20.63	20.68	1	

Table 9-35
LTE Band 2 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 2 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18675 (1857.5 MHz)	18900 (1880.0 MHz)	19125 (1902.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.41	21.51	21.54	0	0
	1	36	21.33	21.51	21.62		0
	1	74	21.21	21.55	21.50		0
	36	0	21.39	21.47	21.56	0-1	0
	36	18	21.34	21.47	21.58		0
	36	37	21.28	21.51	21.56		0
16QAM	75	0	21.31	21.50	21.58	0-1	0
	1	0	21.26	21.39	21.40		0
	1	36	21.21	21.33	21.47		0
	1	74	21.14	21.40	21.40	0-2	0
	36	0	20.36	20.51	20.55		1
	36	18	20.31	20.50	20.57		1
	36	37	20.29	20.52	20.50	1	
	75	0	20.30	20.52	20.59	1	



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 43 of 97

Table 9-36
LTE Band 2 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 2 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18650 (1855.0 MHz)	18900 (1880.0 MHz)	19150 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.36	21.53	21.58	0	0
	1	25	21.34	21.53	21.56		0
	1	49	21.22	21.54	21.45		0
	25	0	21.37	21.49	21.59	0-1	0
	25	12	21.34	21.50	21.56		0
	25	25	21.31	21.51	21.52		0
16QAM	50	0	21.33	21.51	21.58	0-1	0
	1	0	21.43	21.57	21.64		0
	1	25	21.34	21.49	21.57		0
	1	49	21.31	21.50	21.54	0-2	0
	25	0	20.36	20.49	20.54		1
	25	12	20.34	20.46	20.50		1
	25	25	20.29	20.50	20.48	1	
	50	0	20.32	20.53	20.54	1	

Table 9-37
LTE Band 2 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 2 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18625 (1852.5 MHz)	18900 (1880.0 MHz)	19175 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.37	21.49	21.60	0	0
	1	12	21.35	21.47	21.56		0
	1	24	21.29	21.47	21.46		0
	12	0	21.35	21.49	21.57	0-1	0
	12	6	21.34	21.49	21.56		0
	12	13	21.33	21.49	21.52		0
16QAM	25	0	21.35	21.51	21.58	0-1	0
	1	0	21.25	21.42	21.55		0
	1	12	21.20	21.47	21.47		0
	1	24	21.11	21.49	21.47	0-2	0
	12	0	20.35	20.46	20.58		1
	12	6	20.34	20.48	20.56		1
	12	13	20.32	20.48	20.54	1	
	25	0	20.31	20.50	20.58	1	





FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 44 of 97

Table 9-38
LTE Band 2 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 2 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			18615 (1851.5 MHz)	18900 (1880.0 MHz)	19185 (1908.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.27	21.44	21.54	0	0
	1	7	21.26	21.44	21.48		0
	1	14	21.22	21.42	21.42		0
	8	0	21.31	21.47	21.52	0-1	0
	8	4	21.29	21.49	21.52		0
	8	7	21.28	21.46	21.51		0
16QAM	15	0	21.30	21.48	21.55	0-1	0
	1	0	21.25	21.45	21.46		0
	1	7	21.29	21.42	21.42		0
	1	14	21.25	21.42	21.36	0-2	0
	8	0	20.26	20.45	20.55		1
	8	4	20.27	20.42	20.54		1
	8	7	20.27	20.46	20.54	1	
	15	0	20.26	20.49	20.55	1	

Table 9-39
LTE Band 2 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 2 (PCS) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			18607 (1850.7 MHz)	18900 (1880.0 MHz)	19193 (1909.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	21.25	21.41	21.48	0	0	
	1	2	21.23	21.42	21.45		0	
	1	5	21.20	21.43	21.40		0	
	3	0	21.32	21.54	21.52	0-1	0	
	3	2	21.31	21.51	21.51		0	
	3	3	21.27	21.51	21.49		0	
16QAM	6	0	21.30	21.52	21.53	0-1	0	
	1	0	21.06	21.24	21.38		0-1	0
	1	2	21.02	21.25	21.37			0
	1	5	20.98	21.28	21.30	0		
	3	0	21.18	21.36	21.41	0		
	3	2	21.15	21.35	21.37	0		
3	3	21.16	21.37	21.38	0			
	6	0	20.19	20.45	20.47	0-2	1	

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 45 of 97	

9.3.6

LTE Band 7

Table 9-40
LTE Band 7 Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
Conducted Power [dBm]							
QPSK	1	0	22.17	22.05	22.07	0	0
	1	50	22.14	22.11	22.06		0
	1	99	22.15	22.18	22.03		0
	50	0	20.93	20.99	20.75	0-1	1
	50	25	20.93	21.01	20.74		1
	50	50	20.92	21.04	20.76		1
	100	0	20.92	21.03	20.75		1
16QAM	1	0	20.82	20.88	20.63	0-1	1
	1	50	20.94	20.97	20.65		1
	1	99	20.90	21.03	20.61		1
	50	0	19.91	19.97	19.76	0-2	2
	50	25	19.93	20.02	19.76		2
	50	50	19.91	20.06	19.75		2
	100	0	19.90	20.02	19.74		2

Table 9-41
LTE Band 7 Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
Conducted Power [dBm]							
QPSK	1	0	21.92	22.07	21.86	0	0
	1	36	21.91	22.11	21.82		0
	1	74	21.92	22.13	21.79		0
	36	0	20.85	21.00	20.77	0-1	1
	36	18	20.84	21.00	20.77		1
	36	37	20.86	21.03	20.76		1
	75	0	20.84	21.04	20.78		1
16QAM	1	0	20.75	20.78	20.59	0-1	1
	1	36	20.67	20.80	20.59		1
	1	74	20.60	20.84	20.56		1
	36	0	19.83	19.99	19.81	0-2	2
	36	18	19.82	20.02	19.79		2
	36	37	19.84	20.06	19.77		2
	75	0	19.87	20.03	19.80		2





FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 46 of 97

Table 9-42
LTE Band 7 Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.88	22.06	21.85	0	0
	1	25	21.87	22.08	21.84		0
	1	49	21.86	22.11	21.79		0
	25	0	20.83	21.01	20.77	0-1	1
	25	12	20.82	21.02	20.78		1
	25	25	20.80	21.03	20.76		1
16QAM	50	0	20.82	21.02	20.76	0-1	1
	1	0	20.78	20.93	20.74		1
	1	25	20.77	20.91	20.77		1
	1	49	20.77	21.02	20.69	0-2	1
	25	0	19.80	19.97	19.74		2
	25	12	19.79	19.97	19.74		2
25	25	19.78	20.00	19.73	2		
50	0	19.90	20.08	19.84	2		

Table 9-43
LTE Band 7 Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.86	22.05	21.77	0	0
	1	12	21.86	22.06	21.76		0
	1	24	21.82	22.05	21.73		0
	12	0	20.84	20.98	20.72	0-1	1
	12	6	20.83	21.01	20.74		1
	12	13	20.83	20.99	20.72		1
16QAM	25	0	20.83	21.01	20.73	0-1	1
	1	0	20.79	20.87	20.67		1
	1	12	20.80	20.92	20.64		1
	1	24	20.72	20.96	20.67	0-2	1
	12	0	19.79	19.97	19.75		2
	12	6	19.80	19.96	19.72		2
12	13	19.78	19.97	19.71	2		
25	0	19.83	19.98	19.72	2		

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 47 of 97

9.4 WLAN Conducted Powers

Table 9-44
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	18.42	16.94	17.78
2437	6	18.65	16.14	17.71
2457	10	N/A	16.02	17.75
2462	11	18.13	15.85	15.56

Table 9-45
5 GHz WLAN Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	16.35	16.18	16.08
5200	40	16.33	16.05	15.90
5220	44	16.17	15.90	15.84
5240	48	16.10	15.89	15.71
5260	52	16.15	15.62	15.64
5280	56	16.01	15.63	15.57
5300	60	15.99	15.63	15.53
5320	64	15.98	15.49	15.43
5500	100	15.86	15.60	15.56
5600	120	15.68	15.46	15.47
5620	124	15.73	15.51	15.35
5720	144	15.61	15.49	15.47
5745	149	15.81	15.77	15.70
5785	157	15.78	15.90	15.85
5825	165	15.84	15.89	15.96



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 48 of 97



Table 9-46
2.4 GHz WLAN Reduced Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	13.92	14.15	14.84
2437	6	14.11	14.31	14.83
2462	11	13.99	14.33	14.77

Table 9-47
5 GHz WLAN Reduced Average RF Power

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11n	802.11ac
		Average	Average
5190	38	10.22	10.99
5230	46	10.95	10.80
5270	54	10.25	10.26
5310	62	8.83	8.89
5510	102	10.99	10.81
5590	118	10.52	10.71
5630	126	10.74	10.72
5710	142	10.65	10.60
5755	151	10.99	10.99
5795	159	10.98	10.96

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5210	42	8.65
5290	58	8.65
5530	106	8.05
5610	122	10.35
5690	138	10.51
5775	155	10.99

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 49 of 97

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.






Figure 9-3
Power Measurement Setup

9.5 Bluetooth Conducted Powers

Table 9-48
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power
			[dBm]
2402	1.0	0	10.83
2441	1.0	39	11.63
2480	1.0	78	11.08
2402	2.0	0	4.44
2441	2.0	39	5.25
2480	2.0	78	4.61
2402	3.0	0	4.53
2441	3.0	39	5.32
2480	3.0	78	4.68

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 50 of 97	




Figure 9-4
Bluetooth Transmission Plot

Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.90\ ms}{3.75\ ms} * 100\% = 77.3\%$$




Figure 9-5
Power Measurement Setup



FCC ID: A3LSMJ737T	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	SAMSUNG	Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 51 of 97

10 SYSTEM VERIFICATION

10.1 Tissue Verification

**Table 10-1
Measured Head Tissue Properties**



Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
3/30/2018	750H	21.0	700	0.863	43.215	0.889	42.201	-2.92%	2.40%
			710	0.873	43.085	0.890	42.149	-1.91%	2.22%
			720	0.882	42.960	0.891	42.097	-1.01%	2.05%
			725	0.886	42.894	0.891	42.071	-0.56%	1.96%
			740	0.900	42.685	0.893	41.994	0.78%	1.65%
			755	0.913	42.469	0.894	41.916	2.13%	1.32%
4/6/2018	750H	22.0	680	0.883	41.566	0.888	42.305	-0.56%	-1.75%
			695	0.887	41.524	0.889	42.227	-0.22%	-1.66%
			700	0.889	41.513	0.889	42.201	0.00%	-1.63%
			710	0.892	41.490	0.890	42.149	0.22%	-1.56%
			720	0.896	41.465	0.891	42.097	0.56%	-1.50%
			725	0.897	41.452	0.891	42.071	0.67%	-1.47%
			740	0.902	41.409	0.893	41.994	1.01%	-1.39%
4/2/2018	835H	19.7	820	0.905	42.630	0.899	41.578	0.67%	2.53%
			835	0.920	42.445	0.900	41.500	2.22%	2.28%
			850	0.935	42.263	0.916	41.500	2.07%	1.84%
3/20/2018	1750H	21.3	1710	1.353	39.663	1.348	40.142	0.37%	-1.19%
			1750	1.396	39.468	1.371	40.079	1.82%	-1.52%
			1790	1.436	39.285	1.394	40.016	3.01%	-1.83%
3/21/2018	1900H	23.0	1850	1.397	38.849	1.400	40.000	-0.21%	-2.88%
			1880	1.428	38.738	1.400	40.000	2.00%	-3.16%
			1910	1.462	38.630	1.400	40.000	4.43%	-3.42%
4/5/2018	1900H	22.3	1850	1.376	40.133	1.400	40.000	-1.71%	0.33%
			1880	1.407	40.025	1.400	40.000	0.50%	0.06%
			1910	1.440	39.896	1.400	40.000	2.86%	-0.26%
3/25/2018	2450H - 2600H	23.5	2450	1.764	40.568	1.800	39.200	-2.00%	3.49%
			2500	1.818	40.397	1.855	39.136	-1.99%	3.22%
			2550	1.876	40.237	1.909	39.073	-1.73%	2.98%
			2600	1.933	40.057	1.964	39.009	-1.58%	2.69%
3/28/2018	2450H	23.2	2400	1.753	40.274	1.756	39.289	-0.17%	2.51%
			2450	1.808	40.109	1.800	39.200	0.44%	2.32%
			2500	1.866	39.918	1.855	39.136	0.59%	2.00%
4/6/2018	2450H	23.5	2400	1.781	39.270	1.756	39.289	1.42%	-0.05%
			2450	1.834	39.087	1.800	39.200	1.89%	-0.29%
			2500	1.893	38.883	1.855	39.136	2.05%	-0.65%
03/26/2018	5200H-5800H	22.3	5240	4.659	37.531	4.696	35.940	-0.79%	4.43%
			5260	4.680	37.538	4.717	35.917	-0.78%	4.51%
			5280	4.677	37.436	4.737	35.894	-1.27%	4.30%
			5600	5.020	36.954	5.065	35.529	-0.89%	4.01%
			5620	5.047	36.994	5.086	35.506	-0.77%	4.19%
			5680	5.116	36.894	5.147	35.437	-0.60%	4.11%
			5700	5.127	36.883	5.168	35.414	-0.79%	4.15%
			5745	5.192	36.779	5.214	35.363	-0.42%	4.00%
			5765	5.201	36.758	5.234	35.340	-0.63%	4.01%
			5785	5.217	36.796	5.255	35.317	-0.72%	4.19%

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 52 of 97

**Table 10-2
Measured Body Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
4/3/2018	750B	21.7	680	0.963	53.194	0.958	55.804	0.52%	-4.68%
			695	0.968	53.162	0.959	55.745	0.94%	-4.63%
			700	0.970	53.149	0.959	55.726	1.15%	-4.62%
			710	0.974	53.123	0.960	55.687	1.46%	-4.60%
			740	0.984	53.066	0.963	55.570	2.18%	-4.51%
3/28/2018	835B	21.2	755	0.990	53.033	0.964	55.512	2.70%	-4.47%
			820	0.946	54.045	0.969	55.258	-2.37%	-2.20%
			835	0.964	53.907	0.970	55.200	-0.62%	-2.34%
4/3/2018	835B	21.3	850	0.976	53.775	0.988	55.154	-1.21%	-2.50%
			820	0.960	53.680	0.969	55.258	-0.93%	-2.86%
			835	0.974	53.530	0.970	55.200	0.41%	-3.03%
4/3/2018	1750B	22.1	850	0.989	53.387	0.988	55.154	0.10%	-3.20%
			1710	1.437	51.957	1.463	53.537	-1.78%	-2.95%
			1750	1.480	51.845	1.488	53.432	-0.54%	-2.97%
4/10/2018	1750B	21.9	1790	1.525	51.702	1.514	53.326	0.73%	-3.05%
			1710	1.448	52.780	1.463	53.537	-1.03%	-1.41%
			1750	1.495	52.635	1.488	53.432	0.47%	-1.49%
3/28/2018	1900B	22.1	1790	1.540	52.490	1.514	53.326	1.72%	-1.57%
			1850	1.525	53.549	1.520	53.300	0.33%	0.47%
			1880	1.560	53.441	1.520	53.300	2.63%	0.26%
4/5/2018	1900B	21.7	1910	1.595	53.334	1.520	53.300	4.93%	0.06%
			1850	1.520	53.877	1.520	53.300	0.00%	1.08%
			1880	1.553	53.793	1.520	53.300	2.17%	0.92%
3/28/2018	2450B - 2600B	22.2	1910	1.587	53.695	1.520	53.300	4.41%	0.74%
			2400	1.954	50.629	1.902	52.767	2.73%	-4.05%
			2450	2.011	50.491	1.950	52.700	3.13%	-4.19%
			2500	2.070	50.356	2.021	52.636	2.42%	-4.33%
			2550	2.126	50.238	2.092	52.573	1.63%	-4.44%
4/3/2018	2450B - 2600B	21.6	2600	2.185	50.074	2.163	52.509	1.02%	-4.64%
			2450	2.043	51.130	1.950	52.700	4.77%	-2.98%
			2500	2.106	50.978	2.021	52.636	4.21%	-3.15%
			2550	2.165	50.835	2.092	52.573	3.49%	-3.31%
03/18/2018	5200B-5800B	20.6	2600	2.225	50.665	2.163	52.509	2.87%	-3.51%
			5240	5.500	47.462	5.346	48.960	2.88%	-3.06%
			5260	5.516	47.381	5.369	48.933	2.74%	-3.17%
			5500	5.865	46.935	5.650	48.607	3.81%	-3.44%
			5520	5.837	46.912	5.673	48.580	2.89%	-3.43%
			5540	5.920	46.831	5.696	48.553	3.93%	-3.55%
			5560	5.932	46.814	5.720	48.526	3.71%	-3.53%
			5580	5.950	46.804	5.743	48.499	3.60%	-3.49%
			5600	5.970	46.771	5.766	48.471	3.54%	-3.51%
			5620	6.014	46.733	5.790	48.444	3.87%	-3.53%
			5700	6.131	46.609	5.883	48.336	4.22%	-3.57%
			5745	6.167	46.545	5.936	48.275	3.89%	-3.58%
			5765	6.217	46.475	5.959	48.248	4.33%	-3.67%
			5785	6.251	46.461	5.982	48.220	4.50%	-3.65%
03/26/2018	5750B	21.6	5825	6.287	46.432	6.029	48.166	4.28%	-3.60%
			5745	6.151	46.296	5.936	48.275	3.62%	-4.10%
			5765	6.184	46.257	5.959	48.248	3.78%	-4.13%
			5825	6.265	46.182	6.029	48.166	3.91%	-4.12%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 53 of 97

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.


**Table 10-3
System Verification Results – 1g**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
H	750	HEAD	03/30/2018	23.8	21.2	0.200	1161	7410	1.620	8.170	8.100	-0.86%
H	750	HEAD	04/06/2018	22.5	22.0	0.200	1046	7410	1.550	8.260	7.750	-6.17%
E	835	HEAD	04/02/2018	19.8	19.7	0.200	4d132	3213	1.900	9.360	9.500	1.50%
H	1750	HEAD	03/20/2018	22.8	21.8	0.100	1148	7410	3.540	36.400	35.400	-2.75%
G	1900	HEAD	03/21/2018	21.3	21.1	0.100	5d148	3332	3.930	40.100	39.300	-2.00%
G	1900	HEAD	04/05/2018	22.2	21.2	0.100	5d080	3332	3.860	39.300	38.600	-1.78%
G	2450	HEAD	03/25/2018	23.2	23.1	0.100	797	3332	4.920	52.700	49.200	-6.64%
G	2450	HEAD	03/28/2018	22.3	21.5	0.100	797	3332	4.920	52.700	49.200	-6.64%
G	2450	HEAD	04/06/2018	22.0	21.7	0.100	797	3332	5.450	52.700	54.500	3.42%
G	2600	HEAD	03/25/2018	23.2	23.1	0.100	1126	3332	5.210	56.400	52.100	-7.62%
H	5250	HEAD	03/26/2018	21.5	20.4	0.050	1120	3589	3.900	81.300	78.000	-4.06%
H	5600	HEAD	03/26/2018	21.5	20.4	0.050	1120	3589	4.270	84.700	85.400	0.83%
H	5750	HEAD	03/26/2018	21.5	20.4	0.050	1120	3589	3.900	81.000	78.000	-3.70%
I	750	BODY	04/03/2018	22.0	20.9	0.200	1054	3287	1.750	8.610	8.750	1.63%
E	835	BODY	03/28/2018	20.8	21.2	0.200	4d132	3213	2.060	9.710	10.300	6.08%
E	835	BODY	04/03/2018	22.0	21.3	0.200	4d132	3213	2.070	9.710	10.350	6.59%
H	1750	BODY	04/03/2018	22.5	22.1	0.100	1148	7410	3.490	37.000	34.900	-5.68%
I	1750	BODY	04/10/2018	22.8	21.4	0.100	1148	3287	3.820	37.000	38.200	3.24%
J	1900	BODY	03/28/2018	21.1	21.8	0.100	5d148	3914	4.180	39.600	41.800	5.56%
J	1900	BODY	04/05/2018	21.9	21.9	0.100	5d148	3914	4.110	39.600	41.100	3.79%
K	2450	BODY	03/28/2018	22.5	22.2	0.100	797	7406	5.060	51.100	50.600	-0.98%
K	2450	BODY	04/03/2018	22.4	21.6	0.100	797	3319	5.050	51.100	50.500	-1.17%
K	2600	BODY	03/28/2018	22.5	22.2	0.100	1126	7406	5.570	54.300	55.700	2.58%
K	2600	BODY	04/03/2018	22.4	21.6	0.100	1126	3319	5.330	54.300	53.300	-1.84%
D	5250	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	3.610	76.900	72.200	-6.11%
D	5600	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	3.840	78.500	76.800	-2.17%
D	5750	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	3.610	77.100	72.200	-6.36%
D	5750	BODY	03/26/2018	21.6	20.7	0.050	1237	7308	3.600	77.100	72.000	-6.61%

FCC ID: A3LSMJ73TT	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 54 of 97	

**Table 10-4
System Verification Results – 10g**



System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
H	1750	BODY	04/03/2018	22.5	22.1	0.100	1148	7410	1.860	19.800	18.600	-6.06%
I	1750	BODY	04/10/2018	22.8	21.4	0.100	1148	3287	2.030	19.800	20.300	2.53%
J	1900	BODY	03/28/2018	21.1	21.8	0.100	5d148	3914	2.140	20.900	21.400	2.39%
D	5250	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	1.010	21.500	20.200	-6.05%
D	5600	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	1.060	22.100	21.200	-4.07%
D	5750	BODY	03/18/2018	21.7	20.7	0.050	1237	7308	1.010	21.400	20.200	-5.61%



**Figure 10-1
System Verification Setup Diagram**



**Figure 10-2
System Verification Setup Photo**

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 55 of 97

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**



MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.53	0.01	Right	Cheek	21930	1:8.3	0.269	1.250	0.336	
836.60	190	GSM 850	GSM	33.5	32.53	0.04	Right	Tilt	21930	1:8.3	0.167	1.250	0.209	
836.60	190	GSM 850	GSM	33.5	32.53	0.02	Left	Cheek	21930	1:8.3	0.312	1.250	0.390	A1
836.60	190	GSM 850	GSM	33.5	32.53	0.07	Left	Tilt	21930	1:8.3	0.163	1.250	0.204	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.5	29.47	0.04	Right	Cheek	21930	1:8.3	0.256	1.268	0.325	
1880.00	661	GSM 1900	GSM	30.5	29.47	0.02	Right	Tilt	21930	1:8.3	0.152	1.268	0.193	
1880.00	661	GSM 1900	GSM	30.5	29.47	0.03	Left	Cheek	21930	1:8.3	0.444	1.268	0.563	A2
1880.00	661	GSM 1900	GSM	30.5	29.47	0.03	Left	Tilt	21930	1:8.3	0.158	1.268	0.200	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-3
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.07	Right	Cheek	21922	1:1	0.304	1.262	0.384	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.14	Right	Tilt	21922	1:1	0.174	1.262	0.220	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.07	Left	Cheek	21922	1:1	0.313	1.262	0.395	A3
836.60	4183	UMTS 850	RMC	25.0	23.99	0.04	Left	Tilt	21922	1:1	0.153	1.262	0.193	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 56 of 97

**Table 11-4
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.03	Right	Cheek	21930	1:1	0.444	1.216	0.540	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	-0.01	Right	Tilt	21930	1:1	0.421	1.216	0.512	
1712.40	1312	UMTS 1750	RMC	24.0	23.10	0.01	Left	Cheek	21930	1:1	0.681	1.230	0.838	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.01	Left	Cheek	21930	1:1	0.791	1.216	0.962	
1752.60	1513	UMTS 1750	RMC	24.0	23.32	0.02	Left	Cheek	21930	1:1	0.884	1.169	1.033	A4
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.02	Left	Tilt	21930	1:1	0.402	1.216	0.489	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-5
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	0.01	Right	Cheek	21930	1:1	0.421	1.127	0.474	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	-0.02	Right	Tilt	21930	1:1	0.255	1.127	0.287	
1852.40	9262	UMTS 1900	RMC	23.0	22.32	0.02	Left	Cheek	21930	1:1	0.706	1.169	0.825	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	0.09	Left	Cheek	21930	1:1	0.738	1.127	0.832	
1907.60	9538	UMTS 1900	RMC	23.0	22.61	0.00	Left	Cheek	21930	1:1	0.767	1.094	0.839	A5
1880.00	9400	UMTS 1900	RMC	23.0	22.48	-0.01	Left	Tilt	21930	1:1	0.267	1.127	0.301	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 57 of 97	

**Table 11-6
LTE Band 71 Head SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.03	0	Right	Cheek	QPSK	1	0	21930	1:1	0.182	1.279	0.233	A6
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.07	1	Right	Cheek	QPSK	50	0	21930	1:1	0.155	1.274	0.197	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.05	0	Right	Tilt	QPSK	1	0	21930	1:1	0.093	1.279	0.119	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.11	1	Right	Tilt	QPSK	50	0	21930	1:1	0.075	1.274	0.096	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.11	0	Left	Cheek	QPSK	1	0	21930	1:1	0.180	1.279	0.230	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.02	1	Left	Cheek	QPSK	50	0	21930	1:1	0.139	1.274	0.177	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.12	0	Left	Tilt	QPSK	1	0	21930	1:1	0.094	1.279	0.120	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.10	1	Left	Tilt	QPSK	50	0	21930	1:1	0.064	1.274	0.082	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-7
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.04	0	Right	Cheek	QPSK	1	49	21922	1:1	0.275	1.380	0.380	A7
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.07	1	Right	Cheek	QPSK	25	25	21922	1:1	0.208	1.361	0.283	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.02	0	Right	Tilt	QPSK	1	49	21922	1:1	0.160	1.380	0.221	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.04	1	Right	Tilt	QPSK	25	25	21922	1:1	0.128	1.361	0.174	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.02	0	Left	Cheek	QPSK	1	49	21922	1:1	0.246	1.380	0.339	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.00	1	Left	Cheek	QPSK	25	25	21922	1:1	0.177	1.361	0.241	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.08	0	Left	Tilt	QPSK	1	49	21922	1:1	0.150	1.380	0.207	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.02	1	Left	Tilt	QPSK	25	25	21922	1:1	0.115	1.361	0.157	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-8
LTE Band 5 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	0.02	0	Right	Cheek	QPSK	1	25	21930	1:1	0.257	1.288	0.331	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.00	1	Right	Cheek	QPSK	25	12	21930	1:1	0.207	1.355	0.280	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	-0.04	0	Right	Tilt	QPSK	1	25	21930	1:1	0.147	1.288	0.189	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.05	1	Right	Tilt	QPSK	25	12	21930	1:1	0.117	1.355	0.159	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	-0.05	0	Left	Cheek	QPSK	1	25	21930	1:1	0.302	1.288	0.389	A8
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.06	1	Left	Cheek	QPSK	25	12	21930	1:1	0.230	1.355	0.312	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	0.00	0	Left	Tilt	QPSK	1	25	21930	1:1	0.142	1.288	0.183	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.04	1	Left	Tilt	QPSK	25	12	21930	1:1	0.115	1.355	0.156	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 58 of 97

**Table 11-9
LTE Band 66 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	-0.01	0	Right	Cheek	QPSK	1	0	21930	1:1	0.487	1.216	0.592	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.00	1	Right	Cheek	QPSK	50	0	21930	1:1	0.402	1.230	0.494	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	-0.01	0	Right	Tilt	QPSK	1	0	21930	1:1	0.474	1.216	0.576	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.01	1	Right	Tilt	QPSK	50	0	21930	1:1	0.377	1.230	0.464	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.5	23.50	0.02	0	Left	Cheek	QPSK	1	50	21930	1:1	0.843	1.259	1.061	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	0.02	0	Left	Cheek	QPSK	1	0	21930	1:1	0.968	1.216	1.177	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.5	23.55	-0.01	0	Left	Cheek	QPSK	1	0	21930	1:1	1.090	1.245	1.357	A9
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.5	22.46	-0.01	1	Left	Cheek	QPSK	50	25	21930	1:1	0.660	1.271	0.839	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	-0.04	1	Left	Cheek	QPSK	50	0	21930	1:1	0.783	1.230	0.963	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.5	22.48	0.01	1	Left	Cheek	QPSK	50	0	21930	1:1	0.835	1.265	1.056	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.55	-0.03	1	Left	Cheek	QPSK	100	0	21930	1:1	0.805	1.245	1.002	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	-0.02	0	Left	Tilt	QPSK	1	0	21930	1:1	0.516	1.216	0.627	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	-0.11	1	Left	Tilt	QPSK	50	0	21930	1:1	0.425	1.230	0.523	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-10
LTE Band 2 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	-0.04	0	Right	Cheek	QPSK	1	99	22078	1:1	0.411	1.225	0.503	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.03	1	Right	Cheek	QPSK	50	50	22078	1:1	0.373	1.256	0.468	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	-0.05	0	Right	Tilt	QPSK	1	99	22078	1:1	0.237	1.225	0.290	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.01	1	Right	Tilt	QPSK	50	50	22078	1:1	0.205	1.256	0.257	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.33	0.10	0	Left	Cheek	QPSK	1	0	22078	1:1	0.788	1.309	1.031	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.08	0	Left	Cheek	QPSK	1	99	22078	1:1	0.833	1.225	1.020	A10
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.50	0.11	0	Left	Cheek	QPSK	1	50	22078	1:1	0.794	1.259	1.000	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.30	-0.04	1	Left	Cheek	QPSK	50	0	22078	1:1	0.603	1.318	0.795	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.50	0.02	1	Left	Cheek	QPSK	50	50	22078	1:1	0.646	1.259	0.813	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.07	1	Left	Cheek	QPSK	50	50	22078	1:1	0.644	1.256	0.809	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.46	-0.02	1	Left	Cheek	QPSK	100	0	22078	1:1	0.625	1.271	0.794	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.01	0	Left	Tilt	QPSK	1	99	22078	1:1	0.291	1.225	0.356	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	0.04	1	Left	Tilt	QPSK	50	50	22078	1:1	0.244	1.256	0.306	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 59 of 97	

**Table 11-11
LTE Band 7 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.15	0	Right	Cheek	QPSK	1	99	21930	1:1	0.231	1.208	0.279	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.12	1	Right	Cheek	QPSK	50	50	21930	1:1	0.172	1.247	0.214	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.01	0	Right	Tilt	QPSK	1	99	21930	1:1	0.247	1.208	0.298	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.10	1	Right	Tilt	QPSK	50	50	21930	1:1	0.182	1.247	0.227	
2510.00	20850	Low	LTE Band 7	20	23.0	22.17	-0.14	0	Left	Cheek	QPSK	1	0	21930	1:1	0.361	1.211	0.437	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	0.15	0	Left	Cheek	QPSK	1	99	21930	1:1	0.533	1.208	0.644	A11
2560.00	21350	High	LTE Band 7	20	23.0	22.07	0.07	0	Left	Cheek	QPSK	1	0	21930	1:1	0.497	1.239	0.616	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.07	1	Left	Cheek	QPSK	50	50	21930	1:1	0.385	1.247	0.480	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.07	0	Left	Tilt	QPSK	1	99	21930	1:1	0.174	1.208	0.210	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.05	1	Left	Tilt	QPSK	50	50	21930	1:1	0.127	1.247	0.158	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Head									
Spatial Peak										1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 1 gram									

**Table 11-12
DTS Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	15.0	14.11	0.16	Right	Cheek	22193	1	98.9	0.482	0.413	1.227	1.011	0.512	A12
2437	6	802.11b	DSSS	22	15.0	14.11	-0.06	Right	Tilt	22193	1	98.9	0.317	0.261	1.227	1.011	0.324	
2437	6	802.11b	DSSS	22	15.0	14.11	-0.15	Left	Cheek	22193	1	98.9	0.218	0.149	1.227	1.011	0.185	
2437	6	802.11b	DSSS	22	15.0	14.11	0.16	Left	Tilt	22193	1	98.9	0.200	-	1.227	1.011	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Head								
Spatial Peak										1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population										averaged over 1 gram								



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 60 of 97

**Table 11-13
NII Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5270	54	802.11n	OFDM	40	11.0	10.25	-0.12	Right	Cheek	22334	13.5	96.9	1.128	0.563	1.189	1.032	0.691	
5270	54	802.11n	OFDM	40	11.0	10.25	0.03	Right	Tilt	22334	13.5	96.9	1.140	0.552	1.189	1.032	0.677	
5270	54	802.11n	OFDM	40	11.0	10.25	-0.15	Left	Cheek	22334	13.5	96.9	1.057	0.551	1.189	1.032	0.676	
5270	54	802.11n	OFDM	40	11.0	10.25	0.12	Left	Tilt	22334	13.5	96.9	1.071	-	1.189	1.032	-	
5690	138	802.11ac	OFDM	80	11.0	10.51	0.21	Right	Cheek	22334	29.3	94.1	1.201	0.550	1.119	1.063	0.654	
5530	106	802.11ac	OFDM	80	9.5	8.05	0.14	Right	Tilt	22334	29.3	94.1	0.839	0.378	1.396	1.063	0.561	
5610	122	802.11ac	OFDM	80	11.0	10.35	0.13	Right	Tilt	22334	29.3	94.1	1.598	0.752	1.161	1.063	0.928	A13
5690	138	802.11ac	OFDM	80	11.0	10.51	0.01	Right	Tilt	22334	29.3	94.1	1.544	0.663	1.119	1.063	0.789	
5690	138	802.11ac	OFDM	80	11.0	10.51	0.02	Left	Cheek	22334	29.3	94.1	0.968	0.593	1.119	1.063	0.705	
5690	138	802.11ac	OFDM	80	11.0	10.51	0.01	Left	Tilt	22334	29.3	94.1	1.103	-	1.119	1.063	-	
5775	155	802.11ac	OFDM	80	11.0	10.99	0.16	Right	Cheek	22334	29.3	94.1	1.248	0.575	1.002	1.063	0.612	
5775	155	802.11ac	OFDM	80	11.0	10.99	-0.12	Right	Tilt	22334	29.3	94.1	1.472	0.643	1.002	1.063	0.685	
5775	155	802.11ac	OFDM	80	11.0	10.99	0.12	Left	Cheek	22334	29.3	94.1	0.976	0.566	1.002	1.063	0.603	
5775	155	802.11ac	OFDM	80	11.0	10.99	0.12	Left	Tilt	22334	29.3	94.1	1.126	-	1.002	1.063	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-14
DSS Head SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle %	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #	
MHz	Ch.											(W/kg)			(W/kg)		
2441.00	39	Bluetooth	FHSS	12.5	11.63	0.00	Right	Cheek	22334	1	77.3	0.185	1.222	1.294	0.293	A14	
2441.00	39	Bluetooth	FHSS	12.5	11.63	-0.03	Right	Tilt	22334	1	77.3	0.119	1.222	1.294	0.188		
2441.00	39	Bluetooth	FHSS	12.5	11.63	0.07	Left	Cheek	22334	1	77.3	0.068	1.222	1.294	0.108		
2441.00	39	Bluetooth	FHSS	12.5	11.63	0.04	Left	Tilt	22334	1	77.3	0.078	1.222	1.294	0.123		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 61 of 97	



11.2 Standalone Body-Worn SAR Data

**Table 11-15
GSM/UMTS Body-Worn SAR Data**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.53	-0.02	15 mm	21922	1:8.3	back	0.319	1.250	0.399	A15
1880.00	661	GSM 1900	GSM	30.5	29.47	-0.02	15 mm	22078	1:8.3	back	0.206	1.268	0.261	A17
836.60	4183	UMTS 850	RMC	25.0	23.99	0.02	15 mm	22078	1:1	back	0.339	1.262	0.428	A19
1712.40	1312	UMTS 1750	RMC	24.0	23.10	0.01	15 mm	21922	1:1	back	0.559	1.230	0.688	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	-0.01	15 mm	21922	1:1	back	0.630	1.216	0.766	
1752.60	1513	UMTS 1750	RMC	24.0	23.32	0.02	15 mm	21922	1:1	back	0.682	1.169	0.797	A21
1880.00	9400	UMTS 1900	RMC	23.0	22.48	-0.01	15 mm	22078	1:1	back	0.409	1.127	0.461	A23
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-16
LTE Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.02	0	21922	QPSK	1	0	15 mm	back	1:1	0.289	1.279	0.370	A25
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	-0.01	1	21922	QPSK	50	0	15 mm	back	1:1	0.261	1.274	0.333	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.00	0	21922	QPSK	1	49	15 mm	back	1:1	0.388	1.380	0.535	A27
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	-0.02	1	21922	QPSK	25	25	15 mm	back	1:1	0.315	1.361	0.429	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	-0.02	0	21930	QPSK	1	25	15 mm	back	1:1	0.334	1.288	0.430	A29
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.02	1	21930	QPSK	25	12	15 mm	back	1:1	0.257	1.355	0.348	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.5	23.50	-0.04	0	21922	QPSK	1	50	15 mm	back	1:1	0.609	1.259	0.767	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	0.02	0	21922	QPSK	1	0	15 mm	back	1:1	0.832	1.216	1.012	A31
1770.00	132572	High	LTE Band 66 (AWS)	20	24.5	23.55	0.02	0	21922	QPSK	1	0	15 mm	back	1:1	0.802	1.245	0.998	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.02	1	21922	QPSK	50	0	15 mm	back	1:1	0.644	1.230	0.792	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.55	-0.02	1	21922	QPSK	100	0	15 mm	back	1:1	0.645	1.245	0.803	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.00	0	22078	QPSK	1	99	15 mm	back	1:1	0.440	1.225	0.539	A33
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	0.04	1	22078	QPSK	50	50	15 mm	back	1:1	0.348	1.256	0.437	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.04	0	21930	QPSK	1	99	15 mm	back	1:1	0.353	1.208	0.426	A35
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.04	1	21930	QPSK	50	50	15 mm	back	1:1	0.280	1.247	0.349	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram												



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 62 of 97	

**Table 11-17
DTS Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	19.0	18.65	-0.02	15 mm	22193	1	back	98.9	0.277	0.189	1.084	1.011	0.207	A37
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-18
NII Body-Worn SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	17.0	16.15	-0.05	15 mm	22334	6	back	98.6	0.361	0.160	1.216	1.014	0.197	
5500	100	802.11a	OFDM	20	17.0	15.86	0.14	15 mm	22334	6	back	98.6	0.506	0.232	1.300	1.014	0.306	
5825	165	802.11a	OFDM	20	17.0	15.84	0.05	15 mm	22334	6	back	98.6	0.696	0.288	1.306	1.014	0.381	A39
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMJ73TT		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 63 of 97	

11.3 Standalone Hotspot SAR Data

**Table 11-19
GPRS/UMTS Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
824.20	128	GSM 850	GPRS	30.0	29.03	0.13	10 mm	21922	4	1:2.076	back	0.469	1.250	0.586	
836.60	190	GSM 850	GPRS	30.0	29.20	-0.07	10 mm	21922	4	1:2.076	back	0.590	1.202	0.709	
848.80	251	GSM 850	GPRS	30.0	29.39	-0.02	10 mm	21922	4	1:2.076	back	0.644	1.151	0.741	A16
836.60	190	GSM 850	GPRS	30.0	29.20	-0.05	10 mm	21922	4	1:2.076	front	0.518	1.202	0.623	
836.60	190	GSM 850	GPRS	30.0	29.20	-0.07	10 mm	21922	4	1:2.076	bottom	0.094	1.202	0.113	
836.60	190	GSM 850	GPRS	30.0	29.20	0.05	10 mm	21922	4	1:2.076	right	0.333	1.202	0.400	
836.60	190	GSM 850	GPRS	30.0	29.20	0.04	10 mm	21922	4	1:2.076	left	0.449	1.202	0.540	
1850.20	512	GSM 1900	GPRS	26.5	25.49	-0.03	10 mm	22078	4	1:2.076	back	0.627	1.262	0.791	
1880.00	661	GSM 1900	GPRS	26.5	25.49	-0.02	10 mm	22078	4	1:2.076	back	0.615	1.262	0.776	
1909.80	810	GSM 1900	GPRS	26.5	25.50	0.01	10 mm	22078	4	1:2.076	back	0.701	1.259	0.883	A18
1880.00	661	GSM 1900	GPRS	26.5	25.49	0.04	10 mm	22078	4	1:2.076	front	0.534	1.262	0.674	
1880.00	661	GSM 1900	GPRS	26.5	25.49	0.00	10 mm	22078	4	1:2.076	bottom	0.186	1.262	0.235	
1880.00	661	GSM 1900	GPRS	26.5	25.49	-0.12	10 mm	22078	4	1:2.076	right	0.106	1.262	0.134	
1880.00	661	GSM 1900	GPRS	26.5	25.49	-0.03	10 mm	22078	4	1:2.076	left	0.492	1.262	0.621	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.01	10 mm	22078	N/A	1:1	back	0.409	1.262	0.516	A20
836.60	4183	UMTS 850	RMC	25.0	23.99	0.00	10 mm	22078	N/A	1:1	front	0.339	1.262	0.428	
836.60	4183	UMTS 850	RMC	25.0	23.99	-0.06	10 mm	22078	N/A	1:1	bottom	0.053	1.262	0.067	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.00	10 mm	22078	N/A	1:1	right	0.193	1.262	0.244	
836.60	4183	UMTS 850	RMC	25.0	23.99	0.01	10 mm	22078	N/A	1:1	left	0.277	1.262	0.350	
1712.40	1312	UMTS 1750	RMC	22.6	22.28	0.01	10 mm	21989	N/A	1:1	back	0.767	1.076	0.825	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	0.06	10 mm	21989	N/A	1:1	back	0.886	1.104	0.978	
1752.60	1513	UMTS 1750	RMC	22.6	22.40	-0.02	10 mm	21989	N/A	1:1	back	0.984	1.047	1.030	A22
1732.40	1412	UMTS 1750	RMC	22.6	22.17	0.01	10 mm	21989	N/A	1:1	front	0.723	1.104	0.798	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	0.00	10 mm	21989	N/A	1:1	bottom	0.221	1.104	0.244	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	0.01	10 mm	21989	N/A	1:1	right	0.092	1.104	0.102	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	-0.01	10 mm	21989	N/A	1:1	left	0.530	1.104	0.585	
1852.40	9262	UMTS 1900	RMC	22.0	21.10	0.02	10 mm	22490	N/A	1:1	back	0.680	1.230	0.836	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	0.02	10 mm	22490	N/A	1:1	back	0.699	1.169	0.817	
1907.60	9538	UMTS 1900	RMC	22.0	21.54	0.05	10 mm	22490	N/A	1:1	back	0.794	1.112	0.883	A24
1880.00	9400	UMTS 1900	RMC	22.0	21.32	0.05	10 mm	22490	N/A	1:1	front	0.657	1.169	0.768	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	0.04	10 mm	22490	N/A	1:1	bottom	0.214	1.169	0.250	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	-0.01	10 mm	22490	N/A	1:1	right	0.124	1.169	0.145	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	-0.02	10 mm	22490	N/A	1:1	left	0.521	1.169	0.609	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak							Body 1.6 W/kg (mW/g) averaged over 1 gram								
Uncontrolled Exposure/General Population															



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 64 of 97	

**Table 11-20
LTE Band 71 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.01	0	21922	QPSK	1	0	10 mm	back	1:1	0.346	1.279	0.443	A26
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.03	1	21922	QPSK	50	0	10 mm	back	1:1	0.316	1.274	0.403	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.01	0	21922	QPSK	1	0	10 mm	front	1:1	0.238	1.279	0.304	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.01	1	21922	QPSK	50	0	10 mm	front	1:1	0.233	1.274	0.297	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.02	0	21922	QPSK	1	0	10 mm	bottom	1:1	0.032	1.279	0.041	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	-0.01	1	21922	QPSK	50	0	10 mm	bottom	1:1	0.030	1.274	0.038	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	0.05	0	21922	QPSK	1	0	10 mm	right	1:1	0.269	1.279	0.344	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	-0.01	1	21922	QPSK	50	0	10 mm	right	1:1	0.236	1.274	0.301	
680.50	133297	Mid	LTE Band 71	20	25.0	23.93	-0.03	0	21922	QPSK	1	0	10 mm	left	1:1	0.294	1.279	0.376	
680.50	133297	Mid	LTE Band 71	20	24.0	22.95	0.00	1	21922	QPSK	50	0	10 mm	left	1:1	0.259	1.274	0.330	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



**Table 11-21
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.02	0	21922	QPSK	1	49	10 mm	back	1:1	0.408	1.380	0.563	A28
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.00	1	21922	QPSK	25	25	10 mm	back	1:1	0.341	1.361	0.464	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.01	0	21922	QPSK	1	49	10 mm	front	1:1	0.335	1.380	0.462	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	-0.05	1	21922	QPSK	25	25	10 mm	front	1:1	0.266	1.361	0.362	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	-0.12	0	21922	QPSK	1	49	10 mm	bottom	1:1	0.035	1.380	0.048	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	-0.01	1	21922	QPSK	25	25	10 mm	bottom	1:1	0.027	1.361	0.037	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	-0.03	0	21922	QPSK	1	49	10 mm	right	1:1	0.291	1.380	0.402	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.01	1	21922	QPSK	25	25	10 mm	right	1:1	0.244	1.361	0.332	
707.50	23095	Mid	LTE Band 12	10	25.0	23.60	0.13	0	21922	QPSK	1	49	10 mm	left	1:1	0.316	1.380	0.436	
707.50	23095	Mid	LTE Band 12	10	24.0	22.66	0.01	1	21922	QPSK	25	25	10 mm	left	1:1	0.266	1.361	0.362	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 65 of 97	

**Table 11-22
LTE Band 5 (Cell) Hotspot SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	0.01	0	21930	QPSK	1	25	10 mm	back	1:1	0.388	1.288	0.500	A30
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.05	1	21930	QPSK	25	12	10 mm	back	1:1	0.304	1.355	0.412	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	0.07	0	21930	QPSK	1	25	10 mm	front	1:1	0.310	1.288	0.399	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.01	1	21930	QPSK	25	12	10 mm	front	1:1	0.245	1.355	0.332	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	-0.04	0	21930	QPSK	1	25	10 mm	bottom	1:1	0.046	1.288	0.059	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	-0.01	1	21930	QPSK	25	12	10 mm	bottom	1:1	0.038	1.355	0.051	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	-0.06	0	21930	QPSK	1	25	10 mm	right	1:1	0.194	1.288	0.250	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.05	1	21930	QPSK	25	12	10 mm	right	1:1	0.153	1.355	0.207	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	23.90	0.00	0	21930	QPSK	1	25	10 mm	left	1:1	0.260	1.288	0.335	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	22.68	0.02	1	21930	QPSK	25	12	10 mm	left	1:1	0.206	1.355	0.279	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 66 of 97	

**Table 11-23
LTE Band 66 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.48	-0.02	0	21989	QPSK	1	0	10 mm	back	1:1	0.785	1.127	0.885	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.03	0	21989	QPSK	1	0	10 mm	back	1:1	0.987	1.021	1.008	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.30	0.01	0	21989	QPSK	1	99	10 mm	back	1:1	0.917	1.175	1.077	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.50	0.02	0	21989	QPSK	50	0	10 mm	back	1:1	0.799	1.122	0.896	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.01	0	21989	QPSK	50	0	10 mm	back	1:1	0.970	1.021	0.990	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.42	0.00	0	21989	QPSK	50	50	10 mm	back	1:1	0.884	1.143	1.010	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.82	0.04	0	21989	QPSK	100	0	10 mm	back	1:1	0.975	1.042	1.016	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.48	-0.01	0	21989	QPSK	1	0	10 mm	front	1:1	0.820	1.127	0.924	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.01	0	21989	QPSK	1	0	10 mm	front	1:1	1.010	1.021	1.031	A32
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.30	0.00	0	21989	QPSK	1	99	10 mm	front	1:1	0.945	1.175	1.110	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.50	0.01	0	21989	QPSK	50	0	10 mm	front	1:1	0.832	1.122	0.934	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.02	0	21989	QPSK	50	0	10 mm	front	1:1	0.996	1.021	1.017	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.42	-0.04	0	21989	QPSK	50	50	10 mm	front	1:1	0.924	1.143	1.056	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.82	0.00	0	21989	QPSK	100	0	10 mm	front	1:1	0.999	1.042	1.041	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.01	0	21989	QPSK	1	0	10 mm	bottom	1:1	0.300	1.021	0.306	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.02	0	21989	QPSK	50	0	10 mm	bottom	1:1	0.250	1.021	0.255	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.01	0	21989	QPSK	1	0	10 mm	right	1:1	0.146	1.021	0.149	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.02	0	21989	QPSK	50	0	10 mm	right	1:1	0.119	1.021	0.121	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.01	0	21989	QPSK	1	0	10 mm	left	1:1	0.777	1.021	0.793	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.01	0	21989	QPSK	50	0	10 mm	left	1:1	0.624	1.021	0.637	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.02	0	21989	QPSK	1	0	10 mm	front	1:1	1.010	1.021	1.031	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



Note: Blue entry represents variability measurement

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 67 of 97	

**Table 11-24
LTE Band 2 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.53	0.05	0	22490	QPSK	1	0	10 mm	back	1:1	0.805	1.064	0.857	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.66	-0.04	0	22490	QPSK	1	99	10 mm	back	1:1	0.844	1.033	0.872	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	0.03	0	22490	QPSK	1	50	10 mm	back	1:1	0.865	1.009	0.873	A34
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.49	0.03	0	22490	QPSK	50	0	10 mm	back	1:1	0.792	1.074	0.851	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.63	-0.04	0	22490	QPSK	50	50	10 mm	back	1:1	0.822	1.040	0.855	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	0.00	0	22490	QPSK	50	25	10 mm	back	1:1	0.863	1.016	0.877	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.67	-0.09	0	22490	QPSK	100	0	10 mm	back	1:1	0.834	1.030	0.859	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	0.06	0	22490	QPSK	1	50	10 mm	front	1:1	0.668	1.009	0.674	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.01	0	22490	QPSK	50	25	10 mm	front	1:1	0.669	1.016	0.680	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	-0.01	0	22490	QPSK	1	50	10 mm	bottom	1:1	0.240	1.009	0.242	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.02	0	22490	QPSK	50	25	10 mm	bottom	1:1	0.239	1.016	0.243	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	0.01	0	22490	QPSK	1	50	10 mm	right	1:1	0.139	1.009	0.140	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.04	0	22490	QPSK	50	25	10 mm	right	1:1	0.139	1.016	0.141	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	-0.03	0	22490	QPSK	1	50	10 mm	left	1:1	0.552	1.009	0.557	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	0.03	0	22490	QPSK	50	25	10 mm	left	1:1	0.563	1.016	0.572	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	-0.05	0	22490	QPSK	1	50	10 mm	back	1:1	0.849	1.009	0.857	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement

FCC ID: A3LSMJ73TT		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 68 of 97	

**Table 11-25
LTE Band 7 Hotspot SAR**



MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2510.00	20850	Low	LTE Band 7	20	23.0	22.17	-0.04	0	21930	QPSK	1	0	10 mm	back	1:1	0.653	1.211	0.791	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	0.08	0	21930	QPSK	1	99	10 mm	back	1:1	0.745	1.208	0.900	
2560.00	21350	High	LTE Band 7	20	23.0	22.07	0.05	0	21930	QPSK	1	0	10 mm	back	1:1	0.837	1.239	1.037	A36
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	0.08	1	21930	QPSK	50	50	10 mm	back	1:1	0.584	1.247	0.728	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.03	-0.02	1	21930	QPSK	100	0	10 mm	back	1:1	0.492	1.250	0.615	
2510.00	20850	Low	LTE Band 7	20	23.0	22.17	0.12	0	21930	QPSK	1	0	10 mm	front	1:1	0.583	1.211	0.706	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.01	0	21930	QPSK	1	99	10 mm	front	1:1	0.667	1.208	0.806	
2560.00	21350	High	LTE Band 7	20	23.0	22.07	-0.01	0	21930	QPSK	1	0	10 mm	front	1:1	0.712	1.239	0.882	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	-0.02	1	21930	QPSK	50	50	10 mm	front	1:1	0.513	1.247	0.640	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.03	-0.19	1	21930	QPSK	100	0	10 mm	front	1:1	0.542	1.250	0.678	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	0.00	0	21930	QPSK	1	99	10 mm	bottom	1:1	0.446	1.208	0.539	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	-0.04	1	21930	QPSK	50	50	10 mm	bottom	1:1	0.352	1.247	0.439	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	0.17	0	21930	QPSK	1	99	10 mm	right	1:1	0.061	1.208	0.074	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	-0.17	1	21930	QPSK	50	50	10 mm	right	1:1	0.047	1.247	0.059	
2535.00	21100	Mid	LTE Band 7	20	23.0	22.18	-0.03	0	21930	QPSK	1	99	10 mm	left	1:1	0.426	1.208	0.515	
2535.00	21100	Mid	LTE Band 7	20	22.0	21.04	-0.07	1	21930	QPSK	50	50	10 mm	left	1:1	0.334	1.247	0.416	
2560.00	21350	High	LTE Band 7	20	23.0	22.07	-0.01	0	21930	QPSK	1	0	10 mm	back	1:1	0.745	1.239	0.923	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement

**Table 11-26
WLAN Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	19.0	18.65	0.03	10 mm	22193	1	back	98.9	0.578	0.367	1.084	1.011	0.402	A38
2437	6	802.11b	DSSS	22	19.0	18.65	0.03	10 mm	22193	1	front	98.9	0.514	0.318	1.084	1.011	0.349	
2437	6	802.11b	DSSS	22	19.0	18.65	0.02	10 mm	22193	1	top	98.9	0.474	-	1.084	1.011	-	
2437	6	802.11b	DSSS	22	19.0	18.65	0.08	10 mm	22193	1	left	98.9	0.364	-	1.084	1.011	-	
5825	165	802.11a	OFDM	20	17.0	15.84	0.22	10 mm	22334	6	back	98.6	0.803	0.406	1.306	1.014	0.538	
5825	165	802.11a	OFDM	20	17.0	15.84	-0.14	10 mm	22334	6	front	98.6	0.763	0.379	1.306	1.014	0.502	
5745	149	802.11a	OFDM	20	17.0	15.81	0.04	10 mm	22334	6	top	98.6	1.688	0.799	1.315	1.014	1.065	
5785	157	802.11a	OFDM	20	17.0	15.78	-0.02	10 mm	22334	6	top	98.6	1.693	0.792	1.324	1.014	1.063	
5825	165	802.11a	OFDM	20	17.0	15.84	0.01	10 mm	22334	6	top	98.6	1.743	0.806	1.306	1.014	1.067	A40
5825	165	802.11a	OFDM	20	17.0	15.84	-0.17	10 mm	22334	6	right	98.6	0.489	-	1.306	1.014	-	
5825	165	802.11a	OFDM	20	17.0	15.84	-0.13	10 mm	22334	6	left	98.6	0.059	0.015	1.306	1.014	0.020	
5825	165	802.11a	OFDM	20	17.0	15.84	-0.02	10 mm	22334	6	top	98.6	1.710	0.796	1.306	1.014	1.054	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										



Note: Blue entry represents variability measurement

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 69 of 97	

11.4 Standalone Phablet SAR Data

**Table 11-27
UMTS Phablet SAR Data**



MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.03	4 mm	22078	1:1	back	1.360	1.216	1.654	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.08	2 mm	22078	1:1	front	1.550	1.216	1.885	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	-0.03	2 mm	22078	1:1	bottom	0.322	1.216	0.392	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	0.05	0 mm	22078	1:1	right	0.126	1.216	0.153	
1732.40	1412	UMTS 1750	RMC	24.0	23.15	-0.02	0 mm	22078	1:1	left	1.390	1.216	1.690	
1712.40	1312	UMTS 1750	RMC	22.6	22.28	0.05	0 mm	21989	1:1	back	2.800	1.076	3.013	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	-0.04	0 mm	21989	1:1	back	2.950	1.104	3.257	
1752.60	1513	UMTS 1750	RMC	22.6	22.40	-0.05	0 mm	21989	1:1	back	3.140	1.047	3.288	A41
1712.40	1312	UMTS 1750	RMC	22.6	22.28	0.05	0 mm	21989	1:1	front	2.490	1.076	2.679	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	0.02	0 mm	21989	1:1	front	2.610	1.104	2.881	
1752.60	1513	UMTS 1750	RMC	22.6	22.40	-0.03	0 mm	21989	1:1	front	2.810	1.047	2.942	
1732.40	1412	UMTS 1750	RMC	22.6	22.17	-0.05	0 mm	21989	1:1	bottom	0.444	1.104	0.490	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	-0.02	4 mm	22078	1:1	back	1.360	1.127	1.533	
1852.40	9262	UMTS 1900	RMC	23.0	22.32	0.06	2 mm	22078	1:1	front	1.720	1.169	2.011	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	0.10	2 mm	22078	1:1	front	1.860	1.127	2.096	
1907.60	9538	UMTS 1900	RMC	23.0	22.61	0.01	2 mm	22078	1:1	front	1.870	1.094	2.046	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	0.07	2 mm	22078	1:1	bottom	0.414	1.127	0.467	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	0.03	0 mm	22078	1:1	right	0.132	1.127	0.149	
1880.00	9400	UMTS 1900	RMC	23.0	22.48	-0.01	0 mm	22078	1:1	left	1.360	1.127	1.533	
1852.40	9262	UMTS 1900	RMC	22.0	21.10	0.00	0 mm	22490	1:1	back	2.590	1.230	3.186	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	-0.03	0 mm	22490	1:1	back	2.670	1.169	3.121	
1907.60	9538	UMTS 1900	RMC	22.0	21.54	0.02	0 mm	22490	1:1	back	2.830	1.112	3.147	A42
1852.40	9262	UMTS 1900	RMC	22.0	21.10	0.04	0 mm	22490	1:1	front	2.120	1.230	2.608	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	0.04	0 mm	22490	1:1	front	2.180	1.169	2.548	
1907.60	9538	UMTS 1900	RMC	22.0	21.54	0.11	0 mm	22490	1:1	front	2.300	1.112	2.558	
1880.00	9400	UMTS 1900	RMC	22.0	21.32	-0.02	0 mm	22490	1:1	bottom	0.431	1.169	0.504	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams							

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 70 of 97	

**Table 11-28
LTE Band 66 (AWS) Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.5	23.50	0.00	0	21922	QPSK	1	50	4 mm	back	1:1	1.750	1.259	2.203	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	-0.01	0	21922	QPSK	1	0	4 mm	back	1:1	2.110	1.216	2.566	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.5	23.55	-0.05	0	21922	QPSK	1	0	4 mm	back	1:1	2.100	1.245	2.615	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.5	22.46	-0.02	1	21922	QPSK	50	25	4 mm	back	1:1	1.460	1.271	1.856	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	-0.02	1	21922	QPSK	50	0	4 mm	back	1:1	1.670	1.230	2.054	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.5	22.48	0.03	1	21922	QPSK	50	0	4 mm	back	1:1	1.680	1.265	2.125	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.55	-0.01	1	21922	QPSK	100	0	4 mm	back	1:1	1.670	1.245	2.079	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.5	23.50	-0.01	0	21922	QPSK	1	50	2 mm	front	1:1	2.200	1.259	2.770	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	0.06	0	21922	QPSK	1	0	2 mm	front	1:1	2.510	1.216	3.052	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.5	23.55	-0.02	0	21922	QPSK	1	0	2 mm	front	1:1	2.470	1.245	3.075	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.5	22.46	0.01	1	21922	QPSK	50	25	2 mm	front	1:1	1.800	1.271	2.288	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.03	1	21922	QPSK	50	0	2 mm	front	1:1	2.010	1.230	2.472	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.5	22.48	-0.01	1	21922	QPSK	50	0	2 mm	front	1:1	1.980	1.265	2.505	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.55	0.00	1	21922	QPSK	100	0	2 mm	front	1:1	1.990	1.245	2.478	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	0.02	0	21922	QPSK	1	0	2 mm	bottom	1:1	0.483	1.216	0.587	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.01	1	21922	QPSK	50	0	2 mm	bottom	1:1	0.384	1.230	0.472	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	0.00	0	21922	QPSK	1	0	0 mm	right	1:1	0.164	1.216	0.199	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.10	1	21922	QPSK	50	0	0 mm	right	1:1	0.131	1.230	0.161	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.5	23.50	-0.01	0	21922	QPSK	1	50	0 mm	left	1:1	2.000	1.259	2.518	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.5	23.65	-0.15	0	21922	QPSK	1	0	0 mm	left	1:1	2.230	1.216	2.712	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.5	23.55	0.03	0	21922	QPSK	1	0	0 mm	left	1:1	2.310	1.245	2.876	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.5	22.46	0.06	1	21922	QPSK	50	25	0 mm	left	1:1	1.640	1.271	2.084	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.60	0.02	1	21922	QPSK	50	0	0 mm	left	1:1	1.850	1.230	2.276	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.5	22.48	0.03	1	21922	QPSK	50	0	0 mm	left	1:1	1.840	1.265	2.328	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.5	22.55	0.05	1	21922	QPSK	100	0	0 mm	left	1:1	1.850	1.245	2.303	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.48	-0.03	0	21989	QPSK	1	0	0 mm	back	1:1	2.750	1.127	3.099	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.02	0	21989	QPSK	1	0	0 mm	back	1:1	3.220	1.021	3.288	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.30	0.05	0	21989	QPSK	1	99	0 mm	back	1:1	2.750	1.175	3.231	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.50	-0.03	0	21989	QPSK	50	0	0 mm	back	1:1	2.830	1.122	3.175	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.01	0	21989	QPSK	50	0	0 mm	back	1:1	3.230	1.021	3.298	A43
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.42	0.00	0	21989	QPSK	50	50	0 mm	back	1:1	2.840	1.143	3.246	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.82	0.00	0	21989	QPSK	100	0	0 mm	back	1:1	3.110	1.042	3.241	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.48	0.01	0	21989	QPSK	1	0	0 mm	front	1:1	2.720	1.127	3.065	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.02	0	21989	QPSK	1	0	0 mm	front	1:1	3.070	1.021	3.134	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.30	-0.01	0	21989	QPSK	1	99	0 mm	front	1:1	2.740	1.175	3.220	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.0	22.50	-0.01	0	21989	QPSK	50	0	0 mm	front	1:1	2.870	1.122	3.220	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	0.07	0	21989	QPSK	50	0	0 mm	front	1:1	3.160	1.021	3.226	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.42	0.03	0	21989	QPSK	50	50	0 mm	front	1:1	2.880	1.143	3.292	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.82	0.07	0	21989	QPSK	100	0	0 mm	front	1:1	3.160	1.042	3.293	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.09	0	21989	QPSK	1	0	0 mm	bottom	1:1	0.469	1.021	0.479	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.02	0	21989	QPSK	50	0	0 mm	bottom	1:1	0.494	1.021	0.504	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.0	22.91	-0.01	0	21989	QPSK	50	0	0 mm	back	1:1	3.190	1.021	3.257	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Phablet									
Spatial Peak										4.0 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 10 grams									



Note: Blue entry represents variability measurement

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 71 of 97

**Table 11-29
LTE Band 2 (PCS) Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.33	0.01	0	22078	QPSK	1	0	4 mm	back	1:1	1.620	1.309	2.121	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	-0.05	0	22078	QPSK	1	99	4 mm	back	1:1	1.720	1.225	2.107	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.50	-0.03	0	22078	QPSK	1	50	4 mm	back	1:1	1.670	1.259	2.103	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.02	1	22078	QPSK	50	50	4 mm	back	1:1	1.370	1.256	1.721	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.46	0.06	1	22078	QPSK	100	0	4 mm	back	1:1	1.350	1.271	1.716	
1860.00	18700	Low	LTE Band 2 (PCS)	20	23.5	22.33	0.02	0	22078	QPSK	1	0	2 mm	front	1:1	1.840	1.309	2.409	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.04	0	22078	QPSK	1	99	2 mm	front	1:1	1.940	1.225	2.377	
1900.00	19100	High	LTE Band 2 (PCS)	20	23.5	22.50	-0.03	0	22078	QPSK	1	50	2 mm	front	1:1	1.840	1.259	2.317	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	0.05	1	22078	QPSK	50	50	2 mm	front	1:1	1.550	1.256	1.947	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.46	0.00	1	22078	QPSK	100	0	2 mm	front	1:1	1.470	1.271	1.868	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.01	0	22078	QPSK	1	99	2 mm	bottom	1:1	0.492	1.225	0.603	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.05	1	22078	QPSK	50	50	2 mm	bottom	1:1	0.387	1.256	0.486	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	0.08	0	22078	QPSK	1	99	0 mm	right	1:1	0.149	1.225	0.183	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.04	1	22078	QPSK	50	50	0 mm	right	1:1	0.110	1.256	0.138	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	23.5	22.62	-0.05	0	22078	QPSK	1	99	0 mm	left	1:1	1.530	1.225	1.874	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.51	-0.02	1	22078	QPSK	50	50	0 mm	left	1:1	1.190	1.256	1.495	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.53	-0.03	0	22490	QPSK	1	0	0 mm	back	1:1	3.000	1.064	3.192	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.66	0.03	0	22490	QPSK	1	99	0 mm	back	1:1	2.980	1.033	3.078	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	-0.04	0	22490	QPSK	1	50	0 mm	back	1:1	3.040	1.009	3.067	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.49	0.04	0	22490	QPSK	50	0	0 mm	back	1:1	3.060	1.074	3.286	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.63	0.08	0	22490	QPSK	50	50	0 mm	back	1:1	3.090	1.040	3.214	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.02	0	22490	QPSK	50	25	0 mm	back	1:1	3.150	1.016	3.200	A44
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.67	-0.02	0	22490	QPSK	100	0	0 mm	back	1:1	3.090	1.030	3.183	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.53	0.12	0	22490	QPSK	1	0	0 mm	front	1:1	2.560	1.064	2.724	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.66	0.12	0	22490	QPSK	1	99	0 mm	front	1:1	2.570	1.033	2.655	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	0.05	0	22490	QPSK	1	50	0 mm	front	1:1	2.580	1.009	2.603	
1860.00	18700	Low	LTE Band 2 (PCS)	20	21.8	21.49	0.12	0	22490	QPSK	50	0	0 mm	front	1:1	2.620	1.074	2.814	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.63	0.12	0	22490	QPSK	50	50	0 mm	front	1:1	2.610	1.040	2.714	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	0.03	0	22490	QPSK	50	25	0 mm	front	1:1	2.640	1.016	2.682	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	21.8	21.67	0.12	0	22490	QPSK	100	0	0 mm	front	1:1	2.550	1.030	2.627	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.76	-0.06	0	22490	QPSK	1	50	0 mm	bottom	1:1	0.483	1.009	0.487	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.08	0	22490	QPSK	50	25	0 mm	bottom	1:1	0.486	1.016	0.494	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.8	21.73	-0.05	0	22490	QPSK	50	25	0 mm	back	1:1	2.990	1.016	3.038	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Phablet 4.0 W/kg (mW/g) averaged over 10 grams										

Note: Blue entry represents variability measurement

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 72 of 97	



**Table 11-30
WLAN Phablet SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	17.0	16.15	0.15	0 mm	22334	6	back	98.6	4.005	0.738	1.216	1.014	0.910	
5260	52	802.11a	OFDM	20	17.0	16.15	-0.18	0 mm	22334	6	front	98.6	6.533	0.832	1.216	1.014	1.026	
5260	52	802.11a	OFDM	20	17.0	16.15	-0.20	0 mm	22334	6	top	98.6	7.272	0.694	1.216	1.014	0.856	
5260	52	802.11a	OFDM	20	17.0	16.15	0.16	0 mm	22334	6	right	98.6	0.964	-	1.216	1.014	-	
5260	52	802.11a	OFDM	20	17.0	16.15	0.12	0 mm	22334	6	left	98.6	0.867	0.111	1.216	1.014	0.137	
5500	100	802.11a	OFDM	20	17.0	15.86	0.03	0 mm	22334	6	back	98.6	8.315	1.220	1.300	1.014	1.608	
5500	100	802.11a	OFDM	20	17.0	15.86	-0.14	0 mm	22334	6	front	98.6	11.396	1.420	1.300	1.014	1.872	A45
5620	124	802.11a	OFDM	20	17.0	15.73	-0.12	0 mm	22334	6	front	98.6	7.530	1.250	1.340	1.014	1.698	
5720	144	802.11a	OFDM	20	17.0	15.61	-0.02	0 mm	22334	6	front	98.6	7.248	0.968	1.377	1.014	1.352	
5500	100	802.11a	OFDM	20	17.0	15.86	0.12	0 mm	22334	6	top	98.6	11.887	1.220	1.300	1.014	1.608	
5500	100	802.11a	OFDM	20	17.0	15.86	-0.16	0 mm	22334	6	right	98.6	1.215	-	1.300	1.014	-	
5500	100	802.11a	OFDM	20	17.0	15.86	-0.12	0 mm	22334	6	left	98.6	0.602	0.081	1.300	1.014	0.107	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams										

11.5 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
- Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
- This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
- Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 73 of 97	

13. Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (see Section 6.9 for more information).
14. Per KDB Publication 865664 D01v01r04, if the SAR of the highest peak was within 2 dB of the SAR limit, additional zoom scans were performed for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to confirm there was no increase in SAR.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:



1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

WLAN Notes:



1. For held-to-ear, hotspot, and phablet operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 74 of 97	

3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.6.6 for more information.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.5 for the time domain plot and calculation for the duty factor of the device.

FCC ID: A3LSMJ737T	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 75 of 97

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$



When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 10g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1
Estimated SAR**

Mode	Frequency	Maximum Allowed Power	Separation Distance (Hotspot)	Estimated SAR (Hotspot)	Separation Distance (Body-worn)	Estimated SAR (Body-Worn)	Separation Distance (Phablet)	Estimated SAR (Phablet)
	[MHz]	[dBm]	[mm]	[W/kg]	[mm]	[W/kg]	[mm]	[W/kg]
Bluetooth	2480	12.50	10	0.378	15	0.252	5	0.302

Note: Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 76 of 97



12.3 Head SAR Simultaneous Transmission Analysis

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM 850	0.390	0.512	0.902
	GSM 1900	0.563	0.512	1.075
	UMTS 850	0.395	0.512	0.907
	UMTS 1750	1.033	0.512	1.545
	UMTS 1900	0.839	0.512	1.351
	LTE Band 71	0.233	0.512	0.745
	LTE Band 12	0.380	0.512	0.892
	LTE Band 5 (Cell)	0.389	0.512	0.901
	LTE Band 66 (AWS)	1.357	0.512	See Table Below
	LTE Band 2 (PCS)	1.031	0.512	1.543
	LTE Band 7	0.644	0.512	1.156

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	Right Cheek	0.592	0.512	1.104
	Right Tilt	0.576	0.324	0.900
	Left Cheek	1.357	0.185	1.542
	Left Tilt	0.627	0.512*	1.139



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 77 of 97

**Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM 850	0.390	0.928	1.318
	GSM 1900	0.563	0.928	1.491
	UMTS 850	0.395	0.928	1.323
	UMTS 1750	1.033	0.928	See Table Below
	UMTS 1900	0.839	0.928	See Table Below
	LTE Band 71	0.233	0.928	1.161
	LTE Band 12	0.380	0.928	1.308
	LTE Band 5 (Cell)	0.389	0.928	1.317
	LTE Band 66 (AWS)	1.357	0.928	See Table Below
	LTE Band 2 (PCS)	1.031	0.928	See Table Below
	LTE Band 7	0.644	0.928	1.572

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2	1+2			1	2	1+2
Head SAR	Right Cheek	0.540	0.691	1.231	N/A	Head SAR	Right Cheek	0.474	0.691	1.165
	Right Tilt	0.512	0.928	1.440	N/A		Right Tilt	0.287	0.928	1.215
	Left Cheek	1.033	0.705	See Note 1	0.03		Left Cheek	0.839	0.705	1.544
	Left Tilt	0.489	0.928*	1.417	N/A		Left Tilt	0.301	0.928*	1.229

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Head SAR	Right Cheek	0.592	0.691	1.283	N/A	Head SAR	Right Cheek	0.503	0.691	1.194	N/A
	Right Tilt	0.576	0.928	1.504	N/A		Right Tilt	0.290	0.928	1.218	N/A
	Left Cheek	1.357	0.705	See Note 1	0.04		Left Cheek	1.031	0.705	See Note 1	0.03
	Left Tilt	0.627	0.928*	1.555	N/A		Left Tilt	0.356	0.928*	1.284	N/A

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 78 of 97



**Table 12-4
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)**

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM 850	0.390	0.293	0.683
	GSM 1900	0.563	0.293	0.856
	UMTS 850	0.395	0.293	0.688
	UMTS 1750	1.033	0.293	1.326
	UMTS 1900	0.839	0.293	1.132
	LTE Band 71	0.233	0.293	0.526
	LTE Band 12	0.380	0.293	0.673
	LTE Band 5 (Cell)	0.389	0.293	0.682
	LTE Band 66 (AWS)	1.357	0.293	See Table Below
	LTE Band 2 (PCS)	1.031	0.293	1.324
	LTE Band 7	0.644	0.293	0.937

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	Right Cheek	0.592	0.293	0.885
	Right Tilt	0.576	0.188	0.764
	Left Cheek	1.357	0.108	1.465
	Left Tilt	0.627	0.123	0.750

Notes:

- No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 79 of 97	

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.399	0.207	0.606
	GSM 1900	0.261	0.207	0.468
	UMTS 850	0.428	0.207	0.635
	UMTS 1750	0.797	0.207	1.004
	UMTS 1900	0.461	0.207	0.668
	LTE Band 71	0.370	0.207	0.577
	LTE Band 12	0.535	0.207	0.742
	LTE Band 5 (Cell)	0.430	0.207	0.637
	LTE Band 66 (AWS)	1.012	0.207	1.219
	LTE Band 2 (PCS)	0.539	0.207	0.746
LTE Band 7	0.426	0.207	0.633	

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.399	0.381	0.780
	GSM 1900	0.261	0.381	0.642
	UMTS 850	0.428	0.381	0.809
	UMTS 1750	0.797	0.381	1.178
	UMTS 1900	0.461	0.381	0.842
	LTE Band 71	0.370	0.381	0.751
	LTE Band 12	0.535	0.381	0.916
	LTE Band 5 (Cell)	0.430	0.381	0.811
	LTE Band 66 (AWS)	1.012	0.381	1.393
	LTE Band 2 (PCS)	0.539	0.381	0.920
LTE Band 7	0.426	0.381	0.807	





FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 80 of 97

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.399	0.252	0.651
	GSM 1900	0.261	0.252	0.513
	UMTS 850	0.428	0.252	0.680
	UMTS 1750	0.797	0.252	1.049
	UMTS 1900	0.461	0.252	0.713
	LTE Band 71	0.370	0.252	0.622
	LTE Band 12	0.535	0.252	0.787
	LTE Band 5 (Cell)	0.430	0.252	0.682
	LTE Band 66 (AWS)	1.012	0.252	1.264
	LTE Band 2 (PCS)	0.539	0.252	0.791
	LTE Band 7	0.426	0.252	0.678

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 81 of 97	

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-8
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	
Hotspot SAR	GPRS 850	0.741	0.402	1.143
	GPRS 1900	0.883	0.402	1.285
	UMTS 850	0.516	0.402	0.918
	UMTS 1750	1.030	0.402	1.432
	UMTS 1900	0.883	0.402	1.285
	LTE Band 71	0.443	0.402	0.845
	LTE Band 12	0.563	0.402	0.965
	LTE Band 5 (Cell)	0.500	0.402	0.902
	LTE Band 66 (AWS)	1.110	0.402	1.512
	LTE Band 2 (PCS)	0.877	0.402	1.279
	LTE Band 7	1.037	0.402	1.439



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 82 of 97

Table 12-9
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.741	1.067	See Table Below
	GPRS 1900	0.883	1.067	See Table Below
	UMTS 850	0.516	1.067	1.583
	UMTS 1750	1.030	1.067	See Table Below
	UMTS 1900	0.883	1.067	See Table Below
	LTE Band 71	0.443	1.067	1.510
	LTE Band 12	0.563	1.067	See Table Below
	LTE Band 5 (Cell)	0.500	1.067	1.567
	LTE Band 66 (AWS)	1.110	1.067	See Table Below
	LTE Band 2 (PCS)	0.877	1.067	See Table Below
	LTE Band 7	1.037	1.067	See Table Below

Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Hotspot SAR	Back	0.883	0.538	1.421	Hotspot SAR	Back	0.741	0.538	1.279
	Front	0.674	0.502	1.176		Front	0.623	0.502	1.125
	Top	-	1.067	1.067		Top	-	1.067	1.067
	Bottom	0.235	-	0.235		Bottom	0.113	-	0.113
	Right	0.134	1.067*	1.201		Right	0.400	1.067*	1.467
	Left	0.621	0.020	0.641		Left	0.540	0.020	0.560
Hotspot SAR	Back	0.883	0.538	1.421	Hotspot SAR	Back	1.030	0.538	1.568
	Front	0.768	0.502	1.270		Front	0.798	0.502	1.300
	Top	-	1.067	1.067		Top	-	1.067	1.067
	Bottom	0.250	-	0.250		Bottom	0.244	-	0.244
	Right	0.145	1.067*	1.212		Right	0.102	1.067*	1.169
	Left	0.609	0.020	0.629		Left	0.585	0.020	0.605

Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2			1	2	1+2	1+2
Hotspot SAR	Back	0.563	0.538	1.101	Hotspot SAR	Back	1.077	0.538	See Note 1	0.02
	Front	0.462	0.502	0.964		Front	1.110	0.502	See Note 1	0.02
	Top	-	1.067	1.067		Top	-	1.067	1.067	N/A
	Bottom	0.048	-	0.048		Bottom	0.306	-	0.306	N/A
	Right	0.402	1.067*	1.469		Right	0.149	1.067*	1.216	N/A
	Left	0.436	0.020	0.456		Left	0.793	0.020	0.813	N/A

Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 7 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Hotspot SAR	Back	0.877	0.538	1.415	Hotspot SAR	Back	1.037	0.538	1.575
	Front	0.680	0.502	1.182		Front	0.882	0.502	1.384
	Top	-	1.067	1.067		Top	-	1.067	1.067
	Bottom	0.243	-	0.243		Bottom	0.539	-	0.539
	Right	0.141	1.067*	1.208		Right	0.074	1.067*	1.141
	Left	0.572	0.020	0.592		Left	0.515	0.020	0.535



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 83 of 97	

Table 12-10
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.741	0.378	1.119
	GPRS 1900	0.883	0.378	1.261
	UMTS 850	0.516	0.378	0.894
	UMTS 1750	1.030	0.378	1.408
	UMTS 1900	0.883	0.378	1.261
	LTE Band 71	0.443	0.378	0.821
	LTE Band 12	0.563	0.378	0.941
	LTE Band 5 (Cell)	0.500	0.378	0.878
	LTE Band 66 (AWS)	1.110	0.378	1.488
	LTE Band 2 (PCS)	0.877	0.378	1.255
	LTE Band 7	1.037	0.378	1.415

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

12.6 Phablet Simultaneous Transmission Analysis

Since wireless router 1g SAR was not > 1.2 W/kg, Phablet SAR was not required for 2.4 GHz WLAN. Thus, 2.4 GHz WLAN is not considered for Phablet Simultaneous Transmission Analysis.

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for applicable exposure conditions was used for simultaneous transmission analysis.



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 84 of 97	

Table 12-11
Simultaneous Transmission Scenario with 5 GHz WLAN (Phablet)

Exposure Condition	Mode	3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	
		1	2	1+2	1+2
Phablet SAR	UMTS 1750	3.288	1.872	See Table Below	
	UMTS 1900	3.186	1.872	See Table Below	
	LTE Band 66 (AWS)	3.298	1.872	See Table Below	
	LTE Band 2 (PCS)	3.286	1.872	See Table Below	

Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Phablet SAR	Back	3.288	1.608	See Note 1	0.08	Phablet SAR	Back	3.186	1.608	See Note 1	0.08
	Front	2.942	1.872	See Note 1	0.08		Front	2.608	1.872	See Note 1	0.07
	Top	-	1.608	1.608	N/A		Top	-	1.608	1.608	N/A
	Bottom	0.490	-	0.490	N/A		Bottom	0.504	-	0.504	N/A
	Right	0.153	1.872*	2.025	N/A		Right	0.149	1.872*	2.021	N/A
	Left	1.690	0.137	1.827	N/A		Left	1.533	0.137	1.670	N/A

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2			1	2	1+2	1+2
Phablet SAR	Back	3.298	1.608	See Note 1	0.09	Phablet SAR	Back	3.286	1.608	See Note 1	0.09
	Front	3.293	1.872	See Note 1	0.09		Front	2.814	1.872	See Note 1	0.08
	Top	-	1.608	1.608	N/A		Top	-	1.608	1.608	N/A
	Bottom	0.587	-	0.587	N/A		Bottom	0.603	-	0.603	N/A
	Right	0.199	1.872*	2.071	N/A		Right	0.183	1.872*	2.055	N/A
	Left	2.876	0.137	3.013	N/A		Left	1.874	0.137	2.011	N/A



Table 12-12
Simultaneous Transmission Scenario with Bluetooth (Phablet)

Exposure Condition	Mode	3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Phablet SAR	UMTS 1750	3.288	0.302	3.590
	UMTS 1900	3.186	0.302	3.488
	LTE Band 66 (AWS)	3.298	0.302	3.600
	LTE Band 2 (PCS)	3.286	0.302	3.588

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

Notes:

- No evaluation was performed to determine the aggregate 10g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.10 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 85 of 97	

2. For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.

12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g and 4 W/kg for 10g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g and ≤ 0.10 for 10g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2} \text{ (Head)}$$

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2} \text{ (Hotspot and Phablet)}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.7.1 Left Cheek SPLSR Evaluation and Analysis

Table 12-13
Peak SAR Locations for Left Cheek

Mode/Band	x (mm)	y (mm)	z (mm)	Reported SAR (W/kg)
5 GHz WLAN	-7.33	307.40	-171.12	0.705
LTE Band 66 (AWS)	44.92	253.71	-173.55	1.357
UMTS 1750	45.81	253.18	-173.49	1.033
LTE Band 2 (PCS)	42.36	253.44	-172.59	1.031

Table 12-13
Left Cheek SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
UMTS 1750	5 GHz WLAN	1.033	0.705	1.738	75.96	0.03	1
LTE Band 66 (AWS)	5 GHz WLAN	1.357	0.705	2.062	74.96	0.04	2
LTE Band 2 (PCS)	5 GHz WLAN	1.031	0.705	1.736	73.37	0.03	3




FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 86 of 97	

Table 12-14
Left Cheek to Peak Location Separation Ratio Plots



12.7.2 Hotspot SPLSR Evaluation and Analysis

Table 12-15
Peak SAR Locations for Back Side at 1.0 cm

Mode/Band	x (mm)	y (mm)
5 GHz WLAN	-19.00	65.00
LTE Band 66 (AWS)	0.50	-43.50

Table 12-16
Back Side at 1.0 cm SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLSR Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	$(a+b)^{1.5}/D_{a-b}$	
LTE Band 66 (AWS)	5 GHz WLAN	1.077	0.538	1.615	110.24	0.02	1



FCC ID: A3LSMJ737T	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 87 of 97

Table 12-17
Back Side at 1.0 cm SAR to Peak Location Separation Ratio Plots





Table 12-18
Peak SAR Locations for Front Side at 1.0 cm



Mode/Band	x (mm)	y (mm)
5 GHz WLAN	-24.00	75.00
LTE Band 66 (AWS)	-49.00	-54.00

Table 12-19
Front Side at 1.0 cm SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$	
LTE Band 66 (AWS)	5 GHz WLAN	1.11	0.502	1.612	131.40	0.02	1

Table 12-20
Front Side at 1.0 cm SAR to Peak Location Separation Ratio Plots



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 88 of 97

12.7.3

Phablet SPLSR Evaluation and Analysis


Table 12-21
Peak SAR Locations for Phablet Back Side

Mode/Band	x (mm)	y (mm)
5 GHz WLAN	-20.00	62.00
UMTS 1750	5.50	-66.00
UMTS 1900	-1.00	-69.00
LTE Band 66 (AWS)	-1.00	-63.00
LTE Band 2 (PCS)	-1.00	-61.50

Table 12-22
Phablet Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLSR Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$	
UMTS 1750	5 GHz WLAN	3.288	1.608	4.896	130.52	0.08	1
UMTS 1900	5 GHz WLAN	3.186	1.608	4.794	132.37	0.08	2
LTE Band 66 (AWS)	5 GHz WLAN	3.298	1.608	4.906	126.44	0.09	3
LTE Band 2 (PCS)	5 GHz WLAN	3.286	1.608	4.894	124.95	0.09	4

Table 12-23
Phablet Back Side SAR to Peak Location Separation Ratio Plots



FCC ID: A3LSMJ737T	PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 89 of 97


Table 12-24
Peak SAR Locations for Phablet Front Side

Mode/Band	x (mm)	y (mm)
5 GHz WLAN	-18.00	62.00
UMTS 1750	-45.50	-69.00
UMTS 1900	-53.50	-60.00
LTE Band 66 (AWS)	-50.50	-63.00
LTE Band 2 (PCS)	-60.00	-61.00

Table 12-25
Phablet Front Side SAR to Peak Location Separation Ratio Calculations



Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
UMTS 1750	5 GHz WLAN	2.942	1.872	4.814	133.86	0.08	1
UMTS 1900	5 GHz WLAN	2.608	1.872	4.480	127.06	0.07	2
LTE Band 66 (AWS)	5 GHz WLAN	3.293	1.872	5.165	129.16	0.09	3
LTE Band 2 (PCS)	5 GHz WLAN	2.814	1.872	4.686	129.97	0.08	4

Table 12-26
Phablet Front Side SAR to Peak Location Separation Ratio Plots



12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: A3LSMJ737T	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 90 of 97	

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability



Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

**Table 13-1
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1745.00	132322	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	N/A	front	10 mm	1.010	1.010	1.00	N/A	N/A	N/A	N/A
1900	1900.00	19100	LTE Band 2 (PCS), 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	N/A	back	10 mm	0.865	0.849	1.02	N/A	N/A	N/A	N/A
2600	2560.00	21350	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	N/A	back	10 mm	0.837	0.745	1.12	N/A	N/A	N/A	N/A
5750	5825.00	165	802.11a, 20 MHz Bandwidth	OFDM	6	top	10 mm	0.806	0.796	1.01	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 91 of 97	

**Table 13-2
Phablet SAR Measurement Variability Results**

PHABLET VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (10g)	1st Repeated SAR (10g)	Ratio	2nd Repeated SAR (10g)	Ratio	3rd Repeated SAR (10g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1745.00	132322	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 50 RB, 0 RB Offset	back	0 mm	3.230	3.190	1.01	N/A	N/A	N/A	N/A
1900	1900.00	19100	LTE Band 2 (PCS), 20 MHz Bandwidth	QPSK, 50 RB, 25 RB Offset	back	0 mm	3.150	2.990	1.05	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams						

13.2 Measurement Uncertainty



The measured SAR was <1.5 W/kg for 1g and <3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 92 of 97

14 EQUIPMENT LIST



Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	E4438C	ESG Vector Signal Generator	3/21/2017	Biennial	3/21/2019	MY45090700
Agilent	E5515C	Wireless Communications Test Set	5/31/2017	Annual	5/31/2018	GB43304278
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	11/15/2017	Annual	11/15/2018	GB42230325
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	11/1/2017	Annual	11/1/2018	MY47420603
Agilent	N5182A	MXG Vector Signal Generator	1/24/2018	Annual	1/24/2019	MY47420651
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Amplifier Research	150A100C	DC Amplifier	CBT	NA	CBT	348812
Amplifier Research	15S1G6	Amplifier	CBT	NA	CBT	433978
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231538
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231535
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1339018
Anritsu	ML2496A	Power Meter	4/20/2017	Annual	4/20/2018	1306009
Anritsu	MT8821C	Radio Communication Analyzer	11/17/2017	Annual	11/17/2018	6201381794
COMTech	AR85729-5	Solid State Amplifier	CBT	NA	CBT	M155A00-009
Control Company	4040	Therm/ Clock/ Humidity Monitor	1/8/2018	Annual	1/8/2019	160473909
Control Company	4352	Ultra Long Stem Thermometer	1/8/2018	Annual	1/8/2019	160508097
Keysight	772D	Dual Directional Coupler	CBT	NA	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/1/2017	Annual	6/1/2018	MY53401181
MCL	BW-N6W5+	6dB Attenuator	CBT	NA	CBT	1139
Mini Circuits	PWR-4GH5	USB Power Sensor	1/20/2018	Annual	1/20/2019	11710030063
Mini Circuits	PWR-4GH5	USB Power Sensor	1/22/2018	Annual	1/22/2019	11710030062
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	NA	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	NA	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	NA	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	NA	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	NA	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	NA	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	NA	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	NA	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	NA	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	NA	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	NA	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	5/4/2017	Annual	5/4/2018	112347
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/20/2017	Annual	7/20/2018	132885
Seekonk	NC-100	Torque Wrench (8" lb)	8/30/2016	Biennial	8/30/2018	N/A
Seekonk	NC-100	Torque Wrench	12/28/2017	Annual	12/28/2018	N/A
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	1/22/2018	Annual	1/22/2019	N/A
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/12/2017	Annual	9/12/2018	1091
SPEAG	EX3DV4	SAR Probe	7/17/2017	Annual	7/17/2018	7410
SPEAG	ES3DV3	SAR Probe	2/13/2018	Annual	2/13/2019	3213
SPEAG	ES3DV3	SAR Probe	8/14/2017	Annual	8/14/2018	3332
SPEAG	EX3DV4	SAR Probe	1/16/2018	Annual	1/16/2019	3589
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3287
SPEAG	EX3DV4	SAR Probe	2/14/2018	Annual	2/14/2019	3914
SPEAG	EX3DV4	SAR Probe	4/18/2017	Annual	4/18/2018	7406
SPEAG	ES3DV3	SAR Probe	3/13/2018	Annual	3/13/2019	3319
SPEAG	EX3DV4	SAR Probe	8/16/2017	Annual	8/16/2018	7308
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/13/2017	Annual	7/13/2018	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2018	Annual	2/9/2019	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/9/2017	Annual	8/9/2018	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/21/2017	Annual	6/21/2018	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/15/2018	Annual	2/15/2019	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2017	Annual	4/11/2018	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/7/2018	Annual	3/7/2019	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/14/2017	Annual	6/14/2018	1334
SPEAG	D750V3	750 MHz SAR Dipole	7/13/2016	Biennial	7/13/2018	1161
SPEAG	D750V3	750 MHz SAR Dipole	2/7/2018	Annual	2/7/2019	1046
SPEAG	D835V2	835 MHz SAR Dipole	1/15/2018	Annual	1/15/2019	4d132
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1148
SPEAG	D1900V2	1900 MHz SAR Dipole	2/7/2018	Annual	2/7/2019	5d148
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Biennial	7/8/2018	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Annual	9/11/2018	797
SPEAG	D2600V2	2600 MHz SAR Dipole	7/10/2017	Annual	7/10/2018	1126
SPEAG	D5GHZV2	5 GHz SAR Dipole	2/12/2018	Annual	2/12/2019	1120
SPEAG	D750V3	750 MHz Dipole	3/7/2017	Biennial	3/7/2019	1054
SPEAG	D5GHZV2	5 GHz SAR Dipole	8/15/2017	Annual	8/15/2018	1237

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 93 of 97

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c ₁ 1gm	c ₁ 10 gms	1gm u ₁ (± %)	10gms u ₁ (± %)	v ₁
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	



FCC ID: A3LSMJ73TT		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 94 of 97	

16 CONCLUSION

16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset		Page 95 of 97

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

FCC ID: A3LSMJ737T	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 96 of 97	

- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMJ737T		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1803150042-01-R2.A3L	Test Dates: 03/18/18 - 04/10/18	DUT Type: Portable Handset	Page 97 of 97	

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.922 \text{ S/m}$; $\epsilon_r = 42.426$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 04-02-2018; Ambient Temp: 19.8°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.10 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.391 W/kg
SAR(1 g) = 0.312 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium: 1900 Head Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.428 \text{ S/m}$; $\epsilon_r = 38.738$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 03-21-2018; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 8/9/2017
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.30 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.675 W/kg
SAR(1 g) = 0.444 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.6$ MHz; $\sigma = 0.922$ S/m; $\epsilon_r = 42.426$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Test Date: 04-02-2018; Ambient Temp: 19.8°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Left Head, Cheek, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.94 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.392 W/kg
SAR(1 g) = 0.313 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
 $f = 1752.6$ MHz; $\sigma = 1.399$ S/m; $\epsilon_r = 39.456$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Test Date: 03-20-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7410; ConvF(8.66, 8.66, 8.66); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 7/13/2017
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Left Head, Cheek, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.15 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.884 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used (interpolated):
 $f = 1907.6$ MHz; $\sigma = 1.459$ S/m; $\epsilon_r = 38.639$; $\rho = 1000$ kg/m³
Phantom section: Left Section

Test Date: 03-21-2018; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 8/9/2017
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Left Head, Cheek, High.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.19 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.19 W/kg
SAR(1 g) = 0.767 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750MHz Head Medium parameters used (interpolated):

$f = 680.5$ MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.565$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 04-06-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7410; ConvF(10.6, 10.6, 10.6); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 71, Right Head, Cheek, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.06 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.220 W/kg

SAR(1 g) = 0.182 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5$ MHz; $\sigma = 0.871$ S/m; $\epsilon_r = 43.118$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 03-30-2018; Ambient Temp: 23.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7410; ConvF(10.6, 10.6, 10.6); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.51 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.275 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium: 835 Head Medium parameters used (interpolated):
 $f = 836.5 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 42.427$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 04-02-2018; Ambient Temp: 19.8°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Left Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.53 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.374 W/kg
SAR(1 g) = 0.302 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used (interpolated):
 $f = 1770 \text{ MHz}$; $\sigma = 1.416 \text{ S/m}$; $\epsilon_r = 39.377$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 03-20-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7410; ConvF(8.66, 8.66, 8.66); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 7/13/2017
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Left Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.21 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.66 W/kg
SAR(1 g) = 1.09 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.407 \text{ S/m}$; $\epsilon_r = 40.025$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 04-05-2018; Ambient Temp: 22.2°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.03 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.833 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930


Communication System: UID 0, _LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1
Medium: 2450 Head Medium parameters used (interpolated):
 $f = 2535 \text{ MHz}$; $\sigma = 1.859 \text{ S/m}$; $\epsilon_r = 40.285$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

Test Date: 03-25-2018; Ambient Temp: 23.2C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3332; ConvF(4.56, 4.56, 4.56); Calibrated: 8/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 8/9/2017
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Left Head, Cheek, Mid.ch, QPSK,
20 MHz Bandwidth, 1 RB, 99 RB Offset**

Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 18.75 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.971 W/kg
SAR(1 g) = 0.533 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22193

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Head Medium parameters used (interpolated):
 $f = 2437 \text{ MHz}$; $\sigma = 1.794 \text{ S/m}$; $\epsilon_r = 40.152$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section

Test Date: 03-28-2018; Ambient Temp: 22.3°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 8/9/2017
Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Right Head, Cheek, Ch 6, 1 Mbps**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.329 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.898 W/kg

SAR(1 g) = 0.413 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22334

Communication System: UID 0, 802.11ac 5.2-5.8 GHz Band; Frequency: 5610 MHz; Duty Cycle: 1:1
Medium: 5GHz Head Medium parameters used (interpolated):
 $f = 5610 \text{ MHz}$; $\sigma = 5.033 \text{ S/m}$; $\epsilon_r = 36.974$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section


Test Date: 03-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(4.17, 4.17, 4.17); Calibrated: 1/16/2018;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 7/13/2017
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11ac, U-NII-2C, 80 MHz Bandwidth,
Right Head, Tilt, Ch 122, 29.3 Mbps**

Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4
Reference Value = 12.67 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 3.04 W/kg
SAR(1 g) = 0.752 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22334

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.294

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.824 \text{ S/m}$; $\epsilon_r = 39.12$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-06-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Right Head, Cheek, Ch 39, 1 Mbps


Area Scan (11x19x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.69 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.411 W/kg

SAR(1 g) = 0.185 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922


Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.965 \text{ S/m}$; $\epsilon_r = 53.893$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 20.8°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.82 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.405 W/kg
SAR(1 g) = 0.319 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:2.076

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$; $\sigma = 0.975 \text{ S/m}$; $\epsilon_r = 53.786$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 20.8°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Back side, High.ch, 4 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.49 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.807 W/kg

SAR(1 g) = 0.644 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078


Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium: 1900 Body Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.441$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/15/2018
Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: GSM 1900, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (7x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.90 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.346 W/kg
SAR(1 g) = 0.206 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body Medium parameters used:

$f = 1910$ MHz; $\sigma = 1.595$ S/m; $\epsilon_r = 53.334$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Body SAR, Back side, High.ch, 4 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.64 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.701 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.965 \text{ S/m}$; $\epsilon_r = 53.893$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 20.8°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.34 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.428 W/kg
SAR(1 g) = 0.339 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078


Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium: 835 Body Medium parameters used (interpolated):
 $f = 836.6 \text{ MHz}$; $\sigma = 0.965 \text{ S/m}$; $\epsilon_r = 53.893$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 20.8°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 2/9/2018
Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.33 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.515 W/kg
SAR(1 g) = 0.409 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1752.6$ MHz; $\sigma = 1.483$ S/m; $\epsilon_r = 51.836$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7410; ConvF(8.32, 8.32, 8.32); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.00 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.682 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21989

Communication System: UID 0, UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1752.6$ MHz; $\sigma = 1.483$ S/m; $\epsilon_r = 51.836$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7410; ConvF(8.32, 8.32, 8.32); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.96 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.984 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078


Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:
 $f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.441$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/15/2018
Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch

Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Zoom Scan (6x8x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 16.85 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.702 W/kg
SAR(1 g) = 0.409 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22490

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used (interpolated):
 $f = 1907.6$ MHz; $\sigma = 1.592$ S/m; $\epsilon_r = 53.343$; $\rho = 1000$ kg/m³
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.55 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.794 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922


Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1
Medium: 750 Body Medium parameters used (interpolated):
 $f = 680.5 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 53.193$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3287; ConvF(6.71, 6.71, 6.71); Calibrated: 9/18/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 6/21/2017
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 71, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.90 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.363 W/kg
SAR(1 g) = 0.289 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922


Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1
Medium: 750 Body Medium parameters used (interpolated):
 $f = 680.5 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 53.193$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3287; ConvF(6.71, 6.71, 6.71); Calibrated: 9/18/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 6/21/2017
Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 71, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.55 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.432 W/kg
SAR(1 g) = 0.346 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5$ MHz; $\sigma = 0.973$ S/m; $\epsilon_r = 53.129$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3287; ConvF(6.71, 6.71, 6.71); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 6/21/2017

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back side,
Mid.ch, 10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.49 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.488 W/kg

SAR(1 g) = 0.388 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.973 \text{ S/m}$; $\epsilon_r = 53.129$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3287; ConvF(6.71, 6.71, 6.71); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 6/21/2017

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.07 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.509 W/kg

SAR(1 g) = 0.408 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.975$ S/m; $\epsilon_r = 53.516$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.10 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.420 W/kg

SAR(1 g) = 0.334 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.975$ S/m; $\epsilon_r = 53.516$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.59 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.484 W/kg

SAR(1 g) = 0.388 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21922

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1745 \text{ MHz}$; $\sigma = 1.475 \text{ S/m}$; $\epsilon_r = 51.859$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7410; ConvF(8.32, 8.32, 8.32); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.63 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.832 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21989

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1745 \text{ MHz}$; $\sigma = 1.489 \text{ S/m}$; $\epsilon_r = 52.653$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-10-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3287; ConvF(5.19, 5.19, 5.19); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 6/21/2017

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Front side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.59 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 1.01 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22078

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.56 \text{ S/m}$; $\epsilon_r = 53.441$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.53 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.761 W/kg

SAR(1 g) = 0.440 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22490

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 53.37$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.39 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.64 W/kg

SAR(1 g) = 0.865 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 2.109 \text{ S/m}$; $\epsilon_r = 50.273$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.65 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.676 W/kg

SAR(1 g) = 0.353 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21930

Communication System: UID 0, LTE Band 7; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2560$ MHz; $\sigma = 2.177$ S/m; $\epsilon_r = 50.801$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.33, 4.33, 4.33); Calibrated: 3/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/7/2018

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.21 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 0.837 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22193

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.996 \text{ S/m}$; $\epsilon_r = 50.527$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-28-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.14 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.342 W/kg

SAR(1 g) = 0.189 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22193

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437$ MHz; $\sigma = 1.996$ S/m; $\epsilon_r = 50.527$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, Back Side**


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.861 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.783 W/kg

SAR(1 g) = 0.367 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22334

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.287 \text{ S/m}$; $\epsilon_r = 46.432$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth,
Body SAR, Ch 165, 6 Mbps, Back Side**


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 6.660 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.288 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22334

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.287 \text{ S/m}$; $\epsilon_r = 46.432$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth,
Body SAR, Ch 165, 6 Mbps, Top Edge**


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 11.16 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.83 W/kg

SAR(1 g) = 0.806 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21989

Communication System: UID 0, UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1752.6 \text{ MHz}$; $\sigma = 1.483 \text{ S/m}$; $\epsilon_r = 51.836$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7410; ConvF(8.32, 8.32, 8.32); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Phablet SAR, Back side, High.ch


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 68.53 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 16.6 W/kg

SAR(10 g) = 3.14 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22490

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used (interpolated):
 $f = 1907.6 \text{ MHz}$; $\sigma = 1.592 \text{ S/m}$; $\epsilon_r = 53.343$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Phablet SAR, Back side, High.ch


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 68.59 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 18.7 W/kg

SAR(10 g) = 2.83 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 21989


Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1745 MHz; Duty Cycle: 1:1
Medium: 1750 Body Medium parameters used (interpolated):
 $f = 1745 \text{ MHz}$; $\sigma = 1.489 \text{ S/m}$; $\epsilon_r = 52.653$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 0.0 cm

Test Date: 04-10-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3287; ConvF(5.19, 5.19, 5.19); Calibrated: 9/18/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1333; Calibrated: 6/21/2017
Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Phablet SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 50 RB, 0 RB Offset**

Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 70.81 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 16.1 W/kg
SAR(10 g) = 3.23 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22490

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 53.37$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 2 (PCS), Phablet SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 50 RB, 25 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 73.72 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 21.8 W/kg

SAR(10 g) = 3.15 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMJ737T; Type: Portable Handset; Serial: 22334

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5500 \text{ MHz}$; $\sigma = 5.865 \text{ S/m}$; $\epsilon_r = 46.935$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.23, 4.23, 4.23); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, U-NII-2C, 20 MHz Bandwidth,
Phablet SAR, Ch 100, 6 Mbps, Front Side**


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 28.21 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 23.4 W/kg

SAR(10 g) = 1.42 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.909 \text{ S/m}$; $\epsilon_r = 42.541$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 03-30-2018; Ambient Temp: 23.8°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7410; ConvF(10.6, 10.6, 10.6); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.41 W/kg

SAR(1 g) = 1.62 W/kg

Deviation(1 g) = -0.86%



0 dB = 2.15 W/kg = 3.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750MHz Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.906 \text{ S/m}$; $\epsilon_r = 41.379$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-06-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7410; ConvF(10.6, 10.6, 10.6); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.33 W/kg

SAR(1 g) = 1.55 W/kg

Deviation(1 g) = -6.17%



0 dB = 2.08 W/kg = 3.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ S/m}$; $\epsilon_r = 42.445$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-02-2018; Ambient Temp: 19.8°C; Tissue Temp: 19.7°C

Probe: ES3DV3 - SN3213; ConvF(6.42, 6.42, 6.42); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.79 W/kg

SAR(1 g) = 1.9 W/kg

Deviation(1 g) = 1.50%



0 dB = 2.22 W/kg = 3.46 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148


Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1
Medium: 1750 Head Medium parameters used:
 $f = 1750 \text{ MHz}$; $\sigma = 1.396 \text{ S/m}$; $\epsilon_r = 39.468$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-20-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN7410; ConvF(8.66, 8.66, 8.66); Calibrated: 7/17/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 7/13/2017
Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Peak SAR (extrapolated) = 6.57 W/kg
SAR(1 g) = 3.54 W/kg
Deviation(1 g) = -2.75%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.451 \text{ S/m}$; $\epsilon_r = 38.666$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-21-2018; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.10 W/kg

SAR(1 g) = 3.93 W/kg

Deviation(1 g) = -2.00%



0 dB = 4.97 W/kg = 6.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Head Medium parameters used (interpolated):
 $f = 1900 \text{ MHz}$; $\sigma = 1.429 \text{ S/m}$; $\epsilon_r = 39.939$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-05-2018; Ambient Temp: 22.2°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3332; ConvF(5.33, 5.33, 5.33); Calibrated: 8/14/2017;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 8/9/2017
Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)

Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm
\Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Peak SAR (extrapolated) = 7.02 W/kg
SAR(1 g) = 3.86 W/kg
Deviation(1 g) = -1.78%



0 dB = 3.64 W/kg = 5.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450$ MHz; $\sigma = 1.764$ S/m; $\epsilon_r = 40.568$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-25-2018; Ambient Temp: 23.2°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 9.98 W/kg

SAR(1 g) = 4.92 W/kg

Deviation(1 g) = -6.64%



0 dB = 6.43 W/kg = 8.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450$ MHz; $\sigma = 1.808$ S/m; $\epsilon_r = 40.109$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 22.3°C; Tissue Temp: 21.5°C

Probe: ES3DV3 - SN3332; ConvF(4.68, 4.68, 4.68); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.92 W/kg

Deviation(1 g) = -6.64%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 1.933$ S/m; $\epsilon_r = 40.057$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-25-2018; Ambient Temp: 23.2°C; Tissue Temp: 23.1°C

Probe: ES3DV3 - SN3332; ConvF(4.56, 4.56, 4.56); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.21 W/kg

Deviation(1 g) = -7.62%



0 dB = 6.83 W/kg = 8.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.67 \text{ S/m}$; $\epsilon_r = 37.535$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(4.69, 4.69, 4.69); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.2 W/kg

SAR(1 g) = 3.9 W/kg

Deviation(1 g) = -4.06%



0 dB = 9.62 W/kg = 9.83 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.02 \text{ S/m}$; $\epsilon_r = 36.954$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(4.17, 4.17, 4.17); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.3 W/kg

SAR(1 g) = 4.27 W/kg

Deviation(1 g) = 0.83%



0 dB = 10.4 W/kg = 10.17 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used (interpolated):

$f = 5750$ MHz; $\sigma = 5.194$ S/m; $\epsilon_r = 36.774$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.5°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(4.42, 4.42, 4.42); Calibrated: 1/16/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.3 W/kg

SAR(1 g) = 3.9 W/kg

Deviation(1 g) = -3.70%



0 dB = 9.45 W/kg = 9.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.988 \text{ S/m}$; $\epsilon_r = 53.044$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 20.9°C

Probe: ES3DV3 - SN3287; ConvF(6.71, 6.71, 6.71); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 6/21/2017

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1692

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.59 W/kg

SAR(1 g) = 1.75 W/kg

Deviation(1 g) = 1.63%



0 dB = 2.00 W/kg = 3.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.974 \text{ S/m}$; $\epsilon_r = 53.53$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-03-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3213; ConvF(6.2, 6.2, 6.2); Calibrated: 2/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2018

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.04 W/kg

SAR(1 g) = 2.07 W/kg

Deviation(1 g) = 6.59%



0 dB = 2.41 W/kg = 3.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.48 \text{ S/m}$; $\epsilon_r = 51.845$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7410; ConvF(8.32, 8.32, 8.32); Calibrated: 7/17/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/13/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.23 W/kg

SAR(1 g) = 3.49 W/kg; SAR(10 g) = 1.86 W/kg

Deviation(1 g) = -5.68%; Deviation(10 g) = -6.06%



0 dB = 5.32 W/kg = 7.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.495$ S/m; $\epsilon_r = 52.635$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-10-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3287; ConvF(5.19, 5.19, 5.19); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 6/21/2017

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.69 W/kg

SAR(1 g) = 3.82 W/kg; SAR(10 g) = 2.03 W/kg

Deviation(1 g) = 3.24%; Deviation(10 g) = 2.53%



0 dB = 4.72 W/kg = 6.74 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 53.37$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(7.62, 7.62, 7.62); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.73 W/kg

SAR(1 g) = 4.18 W/kg; SAR(10 g) = 2.14 W/kg

Deviation(1 g) = 5.56%; Deviation(10 g) = 2.39%



0 dB = 6.46 W/kg = 8.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.011$ S/m; $\epsilon_r = 50.491$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.06 W/kg

Deviation(1 g) = -0.98%



0 dB = 8.51 W/kg = 9.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used:
 $f = 2450 \text{ MHz}$; $\sigma = 2.043 \text{ S/m}$; $\epsilon_r = 51.13$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.51, 4.51, 4.51); Calibrated: 3/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 3/7/2018

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797
Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.5 W/kg

SAR(1 g) = 5.05 W/kg

Deviation(1 g) = -1.17%



0 dB = 6.67 W/kg = 8.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used:
 $f = 2600 \text{ MHz}$; $\sigma = 2.185 \text{ S/m}$; $\epsilon_r = 50.074$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-28-2018; Ambient Temp: 22.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN7406; ConvF(7.31, 7.31, 7.31); Calibrated: 4/18/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 12.3 W/kg

SAR(1 g) = 5.57 W/kg

Deviation(1 g) = 2.58%



0 dB = 9.60 W/kg = 9.82 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1
Medium: 2450 Body Medium parameters used:
 $f = 2600 \text{ MHz}$; $\sigma = 2.225 \text{ S/m}$; $\epsilon_r = 50.665$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-03-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3319; ConvF(4.33, 4.33, 4.33); Calibrated: 3/13/2018;
Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/7/2018

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 5.33 W/kg

Deviation(1 g) = -1.84%



0 dB = 7.08 W/kg = 8.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used (interpolated):
 $f = 5250 \text{ MHz}$; $\sigma = 5.508 \text{ S/m}$; $\epsilon_r = 47.422$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.84, 4.84, 4.84); Calibrated: 8/16/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 3.61 W/kg; SAR(10 g) = 1.01 W/kg

Deviation(1 g) = -6.11%; Deviation(10 g) = -6.05%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.97 \text{ S/m}$; $\epsilon_r = 46.771$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.23, 4.23, 4.23); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.8 W/kg

SAR(1 g) = 3.84 W/kg; SAR(10 g) = 1.06 W/kg

Deviation(1 g) = -2.17%; Deviation(10 g) = -4.07%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750$ MHz; $\sigma = 6.179$ S/m; $\epsilon_r = 46.528$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-18-2018; Ambient Temp: 21.7°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.3 W/kg

SAR(1 g) = 3.61 W/kg; SAR(10 g) = 1.01 W/kg

Deviation(1 g) = -6.36%; Deviation(10 g) = -5.61%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1
Medium: 5 GHz Body Medium parameters used (interpolated):
 $f = 5750 \text{ MHz}$; $\sigma = 6.159 \text{ S/m}$; $\epsilon_r = 46.286$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 03-26-2018; Ambient Temp: 21.6°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7308; ConvF(4.5, 4.5, 4.5); Calibrated: 8/16/2017;
Sensor-Surface: 1.4mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1334; Calibrated: 6/14/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646
Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 3.6 W/kg

Deviation(1 g) = -6.61%



APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D5GHzV2-1120_Feb18**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1120**

Calibration procedure(s) **QA CAL-22.v2**
Calibration procedure for dipole validation kits between 3-6 GHz

Calibration date: **February 12, 2018**

BW
03-02-2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Michael Weber** Name: **Michael Weber** Function: **Laboratory Technician**

Signature: *M. Weber*

Approved by: **Katja Pokovic** Name: **Katja Pokovic** Function: **Technical Manager**

Signature: *K. Pokovic*

Issued: February 12, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5250 MHz ± 1 MHz 5600 MHz ± 1 MHz 5750 MHz ± 1 MHz	

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.3 ± 6 %	4.59 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.12 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	81.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.33 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.3 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.8 ± 6 %	4.95 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.47 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	84.7 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.42 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.4	5.22 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.6 ± 6 %	5.10 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	81.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.36 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.4 ± 6 %	5.48 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.54 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.10 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.9 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.8 ± 6 %	5.95 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.85 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	78.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.19 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.7 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.3	5.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.5 ± 6 %	6.15 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.51 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	74.6 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.09 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	20.7 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	52.0 Ω - 1.3 j Ω
Return Loss	- 32.5 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	57.9 Ω + 0.2 j Ω
Return Loss	- 22.7 dB

Antenna Parameters with Head TSL at 5750 MHz

Impedance, transformed to feed point	53.3 Ω + 5.5 j Ω
Return Loss	- 24.2 dB

Antenna Parameters with Body TSL at 5250 MHz

Impedance, transformed to feed point	51.4 Ω + 0.3 j Ω
Return Loss	- 36.8 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	59.1 Ω + 1.6 j Ω
Return Loss	- 21.4 dB

Antenna Parameters with Body TSL at 5750 MHz

Impedance, transformed to feed point	54.0 Ω + 5.9 j Ω
Return Loss	- 23.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.206 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 08, 2011

DASY5 Validation Report for Head TSL

Date: 09.02.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1120

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250$ MHz; $\sigma = 4.59$ S/m; $\epsilon_r = 36.3$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5600$ MHz; $\sigma = 4.95$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5750$ MHz; $\sigma = 5.1$ S/m; $\epsilon_r = 35.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.51, 5.51, 5.51); Calibrated: 30.12.2017, ConvF(5.05, 5.05, 5.05); Calibrated: 30.12.2017, ConvF(4.98, 4.98, 4.98); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.09 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 28.2 W/kg

SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.33 W/kg

Maximum value of SAR (measured) = 18.3 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.10 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 32.4 W/kg

SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.42 W/kg

Maximum value of SAR (measured) = 19.7 W/kg



Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.73 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 31.7 W/kg

SAR(1 g) = 8.1 W/kg; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 19.1 W/kg




0 dB = 19.1 W/kg = 12.81 dBW/kg

Impedance Measurement Plot for Head TSL

9 Feb 2018 16:32:46

CH1 S11 1 U FS 1: 52.027 Ω -1.3301 Ω 22.792 pF 5 250.000 000 MHz


*
Del
Cor
Avg
16
H1d



CH1 Markers
2: 57.941 Ω
0.1582 Ω
5.60000 GHz
3: 53.338 Ω
5.4805 Ω
5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -32.474 dB 5 250.000 000 MHz

Cor
Avg
16
H1d



CH2 Markers
2: -22.665 dB
5.60000 GHz
3: -24.150 dB
5.75000 GHz

DASY5 Validation Report for Body TSL

Date: 12.02.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1120

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250$ MHz; $\sigma = 5.48$ S/m; $\epsilon_r = 47.4$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5600$ MHz; $\sigma = 5.95$ S/m; $\epsilon_r = 46.8$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5750$ MHz; $\sigma = 6.15$ S/m; $\epsilon_r = 46.5$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.26, 5.26, 5.26); Calibrated: 30.12.2017, ConvF(4.65, 4.65, 4.65); Calibrated: 30.12.2017, ConvF(4.57, 4.57, 4.57); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.63 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 29.0 W/kg

SAR(1 g) = 7.54 W/kg; SAR(10 g) = 2.1 W/kg

Maximum value of SAR (measured) = 17.1 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.26 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 32.9 W/kg

SAR(1 g) = 7.85 W/kg; SAR(10 g) = 2.19 W/kg

Maximum value of SAR (measured) = 18.5 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:



Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.56 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 32.2 W/kg

SAR(1 g) = 7.51 W/kg; SAR(10 g) = 2.09 W/kg

Maximum value of SAR (measured) = 17.9 W/kg




0 dB = 17.1 W/kg = 12.33 dBW/kg

Impedance Measurement Plot for Body TSL

12 Feb 2018 15:24:41

CH1 S11 1 U FS 1: 51.432 Ω 0.2832 Ω 8.5854 μ H 5 250.000 000 MHz

*
Del
Cor




CH1 Markers
2: 59.125 Ω
1.6230 Ω
5.60000 GHz
3: 54.004 Ω
5.8711 Ω
5.75000 GHz

Avg
16

H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1: -36.820 dB 5 250.000 000 MHz

Cor



CH2 Markers
2: -21.420 dB
5.60000 GHz
3: -23.315 dB
5.75000 GHz

Avg
16

H1d

START 5 000.000 000 MHz

STOP 5 000.000 000 MHz



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D5GHzV2-1237_Aug17**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1237**

Calibration procedure(s) **QA CAL-22.v2
Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **August 15, 2017**

PMV
8/27/17

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 3503	31-Dec-16 (No. EX3-3503_Dec16)	Dec-17
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by:	Name Johannes Kurikka	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature

Issued: August 16, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5250 MHz ± 1 MHz 5600 MHz ± 1 MHz 5750 MHz ± 1 MHz	

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.7 ± 6 %	4.49 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.14 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.7 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.33 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.0 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.2 ± 6 %	4.84 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.33 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	82.5 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.5 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.4	5.22 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.0 ± 6 %	4.99 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.2 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.8 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.36 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.0 ± 6 %	5.46 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.75 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	76.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.17 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.5 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.4 ± 6 %	5.93 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.91 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	78.5 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.23 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.3	5.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.2 ± 6 %	6.13 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.77 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	77.1 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.16 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.4 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	49.9 Ω - 5.3 j Ω
Return Loss	- 25.5 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	51.9 Ω + 2.3 j Ω
Return Loss	- 30.7 dB

Antenna Parameters with Head TSL at 5750 MHz

Impedance, transformed to feed point	55.6 Ω - 0.5 j Ω
Return Loss	- 25.5 dB

Antenna Parameters with Body TSL at 5250 MHz

Impedance, transformed to feed point	46.9 Ω - 4.2 j Ω
Return Loss	- 25.4 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	50.2 Ω + 3.0 j Ω
Return Loss	- 30.4 dB

Antenna Parameters with Body TSL at 5750 MHz

Impedance, transformed to feed point	53.4 Ω + 0.2 j Ω
Return Loss	- 29.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.194 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	May 04, 2015

DASY5 Validation Report for Head TSL

Date: 15.08.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1237

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250$ MHz; $\sigma = 4.49$ S/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5600$ MHz; $\sigma = 4.84$ S/m; $\epsilon_r = 34.2$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5750$ MHz; $\sigma = 4.99$ S/m; $\epsilon_r = 34$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.58, 5.58, 5.58); Calibrated: 31.12.2016, ConvF(5.09, 5.09, 5.09); Calibrated: 31.12.2016, ConvF(5.02, 5.02, 5.02); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.08 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 30.6 W/kg

SAR(1 g) = 8.14 W/kg; SAR(10 g) = 2.33 W/kg

Maximum value of SAR (measured) = 19.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.04 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 32.7 W/kg

SAR(1 g) = 8.33 W/kg; SAR(10 g) = 2.38 W/kg

Maximum value of SAR (measured) = 19.8 W/kg


Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.11 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 32.4 W/kg

SAR(1 g) = 8.1 W/kg; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 19.6 W/kg




0 dB = 19.2 W/kg = 12.83 dBW/kg

Impedance Measurement Plot for Head TSL

9 Aug 2017 12:04:29

CH1 S11 1 U FS 1: 49.920 Ω -5.3223 Ω 5.6959 pF 5 250.000 000 MHz


*
De1
Cor
Avg
16
H1d



CH1 Markers
2: 51.904 Ω
2.3008 Ω
5.60000 GHz
3: 55.609 Ω
-492.19 m Ω
5.75000 GHz

CH2 S11 LOG 5 dB/ REF -20 dB 1: -25.482 dB 5 250.000 000 MHz

Cor
Avg
16
H1d



CH2 Markers
2: -30.654 dB
5.60000 GHz
3: -25.460 dB
5.75000 GHz

START 5 000.000 000 MHz

STOP 6 000.000 000 MHz

DASY5 Validation Report for Body TSL

Date: 08.08.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1237

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250$ MHz; $\sigma = 5.46$ S/m; $\epsilon_r = 47$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5600$ MHz; $\sigma = 5.93$ S/m; $\epsilon_r = 46.4$; $\rho = 1000$ kg/m³,
Medium parameters used: $f = 5750$ MHz; $\sigma = 6.13$ S/m; $\epsilon_r = 46.2$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.14, 5.14, 5.14); Calibrated: 31.12.2016, ConvF(4.57, 4.57, 4.57); Calibrated: 31.12.2016, ConvF(4.51, 4.51, 4.51); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.87 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 29.9 W/kg

SAR(1 g) = 7.75 W/kg; SAR(10 g) = 2.17 W/kg

Maximum value of SAR (measured) = 18.4 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.11 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 33.0 W/kg

SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.23 W/kg

Maximum value of SAR (measured) = 19.3 W/kg



Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.64 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 33.8 W/kg

SAR(1 g) = 7.77 W/kg; SAR(10 g) = 2.16 W/kg

Maximum value of SAR (measured) = 19.1 W/kg




0 dB = 18.4 W/kg = 12.65 dBW/kg

Impedance Measurement Plot for Body TSL

8 Aug 2017 15:23:50

CH1 S11 1 U FS 1: 46.885 Ω -4.1973 Ω 7.2226 pF 5 250.000 000 MHz


*
De1
Cor
Avg
16
H1d



CH1 Markers
2: 50.184 Ω
3: 0.215 Ω
5.60000 GHz
3: 53.363 Ω
0.1719 Ω
5.75000 GHz

CH2 S11 LOG 5 dB/REF -20 dB 1: -25.364 dB 5 250.000 000 MHz

Cor
Avg
16
H1d



CH2 Markers
2: -30.389 dB
5.60000 GHz
3: -29.742 dB
5.75000 GHz



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1046_Feb18**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1046**

Calibration procedure(s) **QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz**

*BNV
03-02-2018*

Calibration date: **February 07, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Claudio Leubler** Name Function
Laboratory Technician

Signature

Approved by: **Katja Pokovic** Technical Manager

Issued: February 7, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	41.4 \pm 6 %	0.89 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.07 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.26 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.35 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.39 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	55.2 \pm 6 %	0.96 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.59 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.43 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.72 W/kg \pm 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	57.0 Ω + 2.2 j Ω
Return Loss	- 23.3 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	52.3 Ω - 2.5 j Ω
Return Loss	- 29.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.040 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 02, 2011

DASY5 Validation Report for Head TSL

Date: 07.02.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1046

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.39 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.11 W/kg

SAR(1 g) = 2.07 W/kg; SAR(10 g) = 1.35 W/kg

Maximum value of SAR (measured) = 2.76 W/kg



0 dB = 2.76 W/kg = 4.41 dBW/kg

Impedance Measurement Plot for Head TSL

7 Feb 2018 11:46:33


CH1 S11 1 U FS 1: 56.977 Ω 2.2461 Ω 476.64 pF 750.000 000 MHz

*
Del

CΔ

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1: -23.287 dB 750.000 000 MHz

CΔ

Avg
16

H1d



DASY5 Validation Report for Body TSL

Date: 07.02.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1046

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.19, 10.19, 10.19); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.54 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.19 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.43 W/kg

Maximum value of SAR (measured) = 2.82 W/kg




0 dB = 2.82 W/kg = 4.50 dBW/kg

Impedance Measurement Plot for Body TSL

7 Feb 2018 11:45:45

CH1 S11 1 U FS 1: 52.295 Ω -2.5059 Ω 84.684 pF 750.000 000 MHz


*
De1
Ca



Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-29.578 dB 750.000 000 MHz

Ca
Avg
16
H1d





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D750V3-1054_Mar17**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1054**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

BNV
03-27-2017
BNV
04-04-2018

Calibration date: **March 07, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 20 dB Attenuator	SN: 5058 (20K)	05-Apr-16 (No. 217-02292)	Apr-17
Type-N mismatch combination	SN: 5047.2 / 06327	05-Apr-16 (No. 217-02295)	Apr-17
Reference Probe EX3DV4	SN: 7349	31-Dec-16 (No. EX3-7349_Dec16)	Dec-17
DAE4	SN: 601	04-Jan-17 (No. DAE4-601_Jan17)	Jan-18

Secondary Standards	ID #	Check Date (In house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (In house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (In house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (In house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (In house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (In house check Oct-18)	In house check: Oct-17

Calibrated by: **Johannes Kurikka** Name: Johannes Kurikka Function: Laboratory Technician

Signature: *Johannes Kurikka*

Approved by: **Katja Pokovic** Name: Katja Pokovic Technical Manager

Signature: *Katja Pokovic*

Issued: March 14, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	40.9 \pm 6 %	0.91 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.14 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.37 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.40 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.60 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	54.6 \pm 6 %	0.99 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.21 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.61 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.45 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.68 W/kg \pm 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.7 Ω - 0.7 j Ω
Return Loss	- 26.8 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.7 Ω - 3.6 j Ω
Return Loss	- 28.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.033 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 08, 2011

DASY5 Validation Report for Head TSL

Date: 07.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1054

Communication System: UID 0 - CW ; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 40.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.17, 10.17, 10.17); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 59.71 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.21 W/kg

SAR(1 g) = 2.14 W/kg; SAR(10 g) = 1.4 W/kg

Maximum value of SAR (measured) = 2.85 W/kg




0 dB = 2.85 W/kg = 4.55 dBW/kg

Impedance Measurement Plot for Head TSL

7 Mar 2017 12:25:14
 CH1 S11 1 U FS 1: 54.732 Ω -732.42 $m\Omega$ 289.73 pF 750.000 000 MHz

*
 Del
 CA



Avg
 16


H1d

CH2 S11 LOG 5 dB/REF -20 dB 1: -26.788 dB 750.000 000 MHz

CA

Avg
 16

H1d



DASY5 Validation Report for Body TSL

Date: 07.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1054

Communication System: UID 0 - CW ; Frequency: 750 MHz

Medium parameters used: $f = 750$ MHz; $\sigma = 0.99$ S/m; $\epsilon_r = 54.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.99, 9.99, 9.99); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.88 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.31 W/kg

SAR(1 g) = 2.21 W/kg; SAR(10 g) = 1.45 W/kg

Maximum value of SAR (measured) = 2.94 W/kg



0 dB = 2.94 W/kg = 4.68 dBW/kg

Impedance Measurement Plot for Body TSL


7 Mar 2017 11:51:37
S11 1 U FS 1150.666 Ω -3.6309 Ω 58.445 pF 750.000 000 MHz

*
De1

Ca

Avg
16

H1d




CH2 S11 LOG 5 dB/REF -20 dB 1:-28.716 dB 750.000 000 MHz

Ca

Avg
16

H1d



Certification of Calibration

Object: D750V3 – SN:1054

Calibration procedure(s): Procedure for Calibration Extension for SAR Dipoles.

Extended Calibration date: March 07, 2018

Description: SAR Validation Dipole at 750 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	8/3/2017	Annual	8/3/2018	MY40000670
Agilent	N5182A	MXG Vector Signal Generator	1/24/2018	Annual	1/24/2019	MY47420651
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	10/16/2017	Annual	10/16/2018	1126066
Anritsu	ML2495A	Power Meter	10/22/2017	Annual	10/22/2018	1328004
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/1/2017	Annual	6/1/2018	MY53401181
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	1/22/2018	Annual	1/22/2019	N/A
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/13/2017	Annual	7/13/2018	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/21/2017	Annual	6/21/2018	1333
SPEAG	EX3DV4	SAR Probe	7/17/2017	Annual	7/17/2018	7410
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3287

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Brodie Halfoster	Test Engineer	<i>BRODIE HALFOSTER</i>
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	<i>KOK</i>

DIPOLE CALIBRATION EXTENSION

Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:



1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.

The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Expiration Date	Certificate Elect Cal Delay (ns)	Certificate SAR Target Head (150 W/m ² @ 210 dBm)	Measured Head SAR (150 W/m ² @ 210 dBm)	Deviation (%)	Certificate SAR Target Body (150 W/m ² @ 210 dBm)	Measured Body SAR (150 W/m ² @ 210 dBm)	Deviation (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
3/7/2017	3/7/2018	1.033	1.67	1.70	1.80%	1.10	1.11	0.01%	54.7	53.4	-1.3	-0.7	-2.0	1.6	-20.6	-20.0	-4.00%	PASS

Calibration Date	Expiration Date	Certificate Elect Cal Delay (ns)	Certificate SAR Target Body (150 W/m ² @ 210 dBm)	Measured Body SAR (150 W/m ² @ 210 dBm)	Deviation (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL			
3/7/2017	3/7/2018	1.033	1.72	1.70	-1.20%	4.14	4.12	-1.41%	50.7	50.4	-0.3	-3.6	-3.0	0.3	-28.7	-28.5	0.69%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL

